

APPENDIX A: SYSTEM CHECKING SCANS

Plot #1

Date/Time: 2014-08-06 08:52:48

Test Laboratory: TCC Microsoft

Type: D750V3; Serial: D750V3 - SN:1075

Communication System: CW750

Frequency: 750 MHz; Duty Cycle: 1:1

Medium: HSL750; Medium Notes: $t = 21\text{ C}$

Medium parameters used: $f = 750\text{ MHz}$; $\sigma = 0.893\text{ S/m}$; $\epsilon_r = 40.565$; $\rho = 1000\text{ kg/m}^3$

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3960
- ConvF(10.78, 10.78, 10.78); Calibrated: 2013-12-10;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1302; Calibrated: 2013-11-08
- Phantom: #1 SAM, SAR4; Type: SAM; Serial: TP-1018
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

Configuration (below 1Ghz)/d=15mm, Pin=250mW/Area Scan (61x81x1): Interpolated grid: $dx=1.500\text{ mm}$, $dy=1.500\text{ mm}$

Reference Value = 49.068 V/m

Fast SAR: SAR(1 g) = 2.03 W/kg

Fast SAR(10 g) = 1.38 W/kg

Maximum value of SAR (interpolated) = 2.32 W/kg

Configuration (below 1Ghz)/d=15mm, Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 49.068 V/m


Peak SAR (extrapolated) = 2.96 W/kg

SAR(1 g) = 1.99 W/kg

SAR(10 g) = 1.31 W/kg

Power Drift = -0.02 dB

Maximum value of SAR (measured) = 2.32 W/kg



Plot #2

Date/Time: 2014-08-06 13:26:39

Test Laboratory: TCC Nokia

Type: D835V2; Serial: D835V2 - SN:462

Communication System: CW835

Frequency: 835 MHz; Duty Cycle: 1:1

Medium: HSL835; Medium Notes: t= 22.5 C

Medium parameters used: f = 835 MHz; σ = 0.908 S/m; ϵ_r = 40.259; ρ = 1000 kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: ES3DV3 - SN3194
- ConvF(6.12, 6.12, 6.12); Calibrated: 2013-11-14;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn538; Calibrated: 2013-11-19
- Phantom: SAM 1; Type: Twin SAM 040 CA; Serial: TP-1596
- Measurement SW: DASY52, Version 52.8 (6); SEMCAD X Version 14.6.9 (7117)

Configuration 835 MHz/d=15mm, Pin=250mW/Area Scan (61x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 52.576 V/m

Fast SAR: SAR(1 g) = 2.36 W/kg

Fast SAR(10 g) = 1.59 W/kg

Maximum value of SAR (interpolated) = 2.70 W/kg

Configuration 835 MHz/d=15mm, Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 52.576 V/m


Peak SAR (extrapolated) = 3.46 W/kg

SAR(1 g) = 2.33 W/kg

SAR(10 g) = 1.52 W/kg

Power Drift = 0.07 dB

Maximum value of SAR (measured) = 2.72 W/kg



Plot #3

Date/Time: 2014-07-31 13:48:51

Test Laboratory: TCC Microsoft
Type: D1750V2; Serial: D1750V2 - SN:1083

Communication System: CW1750

Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: HSL1800; Medium Notes: $t = 20.7$ C

Medium parameters used: $f = 1750$ MHz; $\sigma = 1.329$ S/m; $\epsilon_r = 38.268$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3834
- ConvF(7.62, 7.62, 7.62); Calibrated: 2014-05-08;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1355; Calibrated: 2014-05-13
- Phantom: SAM 4; Type: Twin SAM 040 CA; Serial: TP-1692
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

d=10mm, Pin=250mW/Area Scan (61x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 86.653 V/m

Fast SAR: SAR(1 g) = 9.27 W/kg

Fast SAR(10 g) = 4.96 W/kg

Maximum value of SAR (interpolated) = 11.5 W/kg

d=10mm, Pin=250mW/Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 86.653 V/m


Peak SAR (extrapolated) = 16.5 W/kg

SAR(1 g) = 9.05 W/kg

SAR(10 g) = 4.78 W/kg

Power Drift = 0.10 dB

Maximum value of SAR (measured) = 11.5 W/kg



Plot #4

Date/Time: 2014-07-31 08:37:31

Test Laboratory: TCC Microsoft
Type: D1900V2; Serial: D1900V2 - SN:5d013

Communication System: CW1900

Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: HSL1900; Medium Notes: t= 21.7c

Medium parameters used: f = 1900 MHz; σ = 1.373 S/m; ϵ_r = 39.047; ρ = 1000 kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3834
- ConvF(7.33, 7.33, 7.33); Calibrated: 2014-05-08;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1355; Calibrated: 2014-05-13
- Phantom: SAM 1; Type: Twin SAM 040 CA; Serial: TP-1449
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

d=10mm, Pin=250mW/Area Scan (61x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 88.301 V/m

Fast SAR: SAR(1 g) = 9.92 W/kg

Fast SAR(10 g) = 5.1 W/kg

Maximum value of SAR (interpolated) = 12.7 W/kg

d=10mm, Pin=250mW/Zoom Scan (5x6x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 88.301 V/m


Peak SAR (extrapolated) = 18.0 W/kg

SAR(1 g) = 9.74 W/kg

SAR(10 g) = 5.08 W/kg

Power Drift = 0.03 dB

Maximum value of SAR (measured) = 12.2 W/kg



Plot #5

Date/Time: 2014-07-25 09:51:17

Test Laboratory: TCC Nokia

Type: D2450V2; Serial: D2450V2 - SN:749

Communication System: CW2450

Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: HSL2450; Medium Notes: $t = 21.0$ C

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.75$ S/m; $\epsilon_r = 38.256$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3960
- ConvF(7.39, 7.39, 7.39); Calibrated: 2013-12-10;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1302; Calibrated: 2013-11-08
- Phantom: #4 SAM, SAR4 ; Type: QD000P40CD; Serial: TP-1691
- Measurement SW: DASY52, Version 52.8 (6); SEMCAD X Version 14.6.9 (7117)

Configuration (2450 GHz)/d=10mm, Pin=250mW/Area Scan (81x61x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Reference Value = 92.847 V/m

Fast SAR: SAR(1 g) = 13.2 W/kg

Fast SAR(10 g) = 6.11 W/kg

Maximum value of SAR (interpolated) = 17.3 W/kg

Configuration (2450 GHz)/d=10mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 92.847 V/m


Peak SAR (extrapolated) = 27.2 W/kg

SAR(1 g) = 13 W/kg

SAR(10 g) = 5.99 W/kg

Power Drift = -0.02 dB

Maximum value of SAR (measured) = 17.2 W/kg



Plot #6

Date/Time: 2014-08-05 10:12:42

Test Laboratory: TCC Microsoft
Type: D2600V2; Serial: D2600V2 - SN:1056

Communication System: CW2600

Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: HSL2600; Medium Notes: $t = 21.2$ C

Medium parameters used: $f = 2600$ MHz; $\sigma = 1.959$ S/m; $\epsilon_r = 38.651$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3960
- ConvF(7.33, 7.33, 7.33); Calibrated: 2013-12-10;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1302; Calibrated: 2013-11-08
- Phantom: #4 SAM, SAR4 ; Type: QD000P40CD; Serial: TP-1691
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

Configuration (2600MHz)/d=10mm, Pin=250mW/Area Scan (61x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Reference Value = 89.562 V/m

Fast SAR: SAR(1 g) = 14.7 W/kg

Fast SAR(10 g) = 6.53 W/kg

Maximum value of SAR (interpolated) = 19.9 W/kg

Configuration (2600MHz)/d=10mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 89.562 V/m


Peak SAR (extrapolated) = 31.2 W/kg

SAR(1 g) = 14.3 W/kg

SAR(10 g) = 6.35 W/kg

Power Drift = 0.01 dB

Maximum value of SAR (measured) = 19.3 W/kg



Plot #7

Date/Time: 2014-07-30 08:40:53

Test Laboratory: TCC Microsoft
Type: D5GHzV2; Serial: D5GHzV2 - SN: 1032

Communication System: CW5600

Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: HSL5000; Medium Notes: $t = 22.2$ C

Medium parameters used: $f = 5600$ MHz; $\sigma = 4.951$ S/m; $\epsilon_r = 35.554$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3892
- ConvF(4.66, 4.66, 4.66); Calibrated: 2013-11-15;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2013-11-11
- Phantom: SAM2; Type: SAM; Serial: TP-1570
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

d=10mm, Pin=100mW 5600/Area Scan (61x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Reference Value = 60.841 V/m

Fast SAR: SAR(1 g) = 7.57 W/kg

Fast SAR(10 g) = 2.04 W/kg

Maximum value of SAR (interpolated) = 17.2 W/kg

d=10mm, Pin=100mW 5600/Zoom Scan (8x8x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 60.841 V/m


Peak SAR (extrapolated) = 35.2 W/kg

SAR(1 g) = 7.95 W/kg

SAR(10 g) = 2.2 W/kg

Power Drift = 0.09 dB

Maximum value of SAR (measured) = 15.8 W/kg



Plot #8

Date/Time: 2014-07-31 09:42:45

Test Laboratory: TCC Microsoft
Type: D5GHzV2; Serial: D5GHzV2 - SN: 1032

Communication System: CW5800

Frequency: 5800 MHz; Duty Cycle: 1:1

Medium: HSL5000; Medium Notes: $t = 22.2$ C

Medium parameters used: $f = 5800$ MHz; $\sigma = 5.09$ S/m; $\epsilon_r = 34.791$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3892
- ConvF(4.6, 4.6, 4.6); Calibrated: 2013-11-15;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2013-11-11
- Phantom: SAM2; Type: SAM; Serial: TP-1570
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

d=10mm, Pin=100mW 5800/Area Scan (61x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Reference Value = 59.502 V/m

Fast SAR: SAR(1 g) = 6.93 W/kg

Fast SAR(10 g) = 1.86 W/kg

Maximum value of SAR (interpolated) = 16.0 W/kg

d=10mm, Pin=100mW 5800/Zoom Scan (8x8x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 59.502 V/m


Peak SAR (extrapolated) = 34.2 W/kg

SAR(1 g) = 7.52 W/kg

SAR(10 g) = 2.09 W/kg

Power Drift = 0.09 dB

Maximum value of SAR (measured) = 14.7 W/kg



Plot #9

Date/Time: 2014-08-06 18:04:53

Test Laboratory: TCC Microsoft

Type: D750V3; Serial: D750V3 - SN:1075

Communication System:

Frequency: 750 MHz; Duty Cycle: 1:1

Medium: BSL750; Medium Notes: $t = 20.8\text{ }^{\circ}\text{C}$

Medium parameters used: $f = 750\text{ MHz}$; $\sigma = 0.992\text{ S/m}$; $\epsilon_r = 54.271$; $\rho = 1000\text{ kg/m}^3$

Phantom section: Center Section

DASY Configuration:

- Probe: EX3DV4 - SN3960
- ConvF(10.24, 10.24, 10.24); Calibrated: 2013-12-10;
- Sensor-Surface: 3mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1302; Calibrated: 2013-11-08
- Phantom: #2 Triple, SAR4; Type: QD 000 P51 CA; Serial: TP-1123/1 (750 MHz), TP-1124/1 (2450 MHz)
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

d=15mm, Pin=250mW/Area Scan (81x61x1): Interpolated grid: $dx=1.500\text{ mm}$, $dy=1.500\text{ mm}$

Reference Value = 48.259 V/m

Fast SAR: SAR(1 g) = 2.22 W/kg

Fast SAR(10 g) = 1.51 W/kg

Maximum value of SAR (interpolated) = 2.54 W/kg

d=15mm, Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=7.5\text{ mm}$, $dy=7.5\text{ mm}$, $dz=5\text{ mm}$

Reference Value = 48.259 V/m


Peak SAR (extrapolated) = 3.21 W/kg

SAR(1 g) = 2.18 W/kg

SAR(10 g) = 1.45 W/kg

Power Drift = -0.00 dB

Maximum value of SAR (measured) = 2.54 W/kg



Plot #10

Date/Time: 2014-08-08 17:42:25

Test Laboratory: TCC Microsoft

Type: D835V2; Serial: D835V2 - SN:462

Communication System: CW835

Frequency: 835 MHz; Duty Cycle: 1:1

Medium: BSL835; Medium Notes: $t = 22.4\text{ }^{\circ}\text{C}$

Medium parameters used: $f = 835\text{ MHz}$; $\sigma = 0.985\text{ S/m}$; $\epsilon_r = 53.504$; $\rho = 1000\text{ kg/m}^3$

Phantom section: Center Section

DASY Configuration:

- Probe: ES3DV3 - SN3194
- ConvF(6.05, 6.05, 6.05); Calibrated: 2013-11-14;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn538; Calibrated: 2013-11-19
- Phantom: SAM 3 Triple Phantom 5.1C; Type: QD 000 P51 CA; Serial: TP-1123/3
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

Configuration 835 MHz/d=15mm, Pin=250mW/Area Scan (61x81x1): Interpolated grid: $dx=1.500\text{ mm}$, $dy=1.500\text{ mm}$

Reference Value = 52.308 V/m

Fast SAR: SAR(1 g) = 2.47 W/kg

Fast SAR(10 g) = 1.65 W/kg

Maximum value of SAR (interpolated) = 2.84 W/kg

Configuration 835 MHz/d=15mm, Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=7.5\text{ mm}$, $dy=7.5\text{ mm}$, $dz=5\text{ mm}$

Reference Value = 52.308 V/m


Peak SAR (extrapolated) = 3.53 W/kg

SAR(1 g) = 2.43 W/kg

SAR(10 g) = 1.6 W/kg

Power Drift = -0.01 dB

Maximum value of SAR (measured) = 2.82 W/kg



Plot #11

Date/Time: 2014-08-01 08:18:26

Test Laboratory: TCC Microsoft
Type: D1750V2; Serial: D1750V2 - SN:1083

Communication System: CW1750

Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: BSL1800; Medium Notes: $t = 21.2$ C

Medium parameters used: $f = 1750$ MHz; $\sigma = 1.45$ S/m; $\epsilon_r = 52.075$; $\rho = 1000$ kg/m³

Phantom section: Center Section

DASY Configuration:

- Probe: EX3DV4 - SN3834
- ConvF(7.35, 7.35, 7.35); Calibrated: 2014-05-08;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1355; Calibrated: 2014-05-13
- Phantom: SAM 3 Triple Phantom 5.1C; Type: QD 000 P51 CA; Serial: TP-1124/2 (1800MHz), TP-1123/2 (1900MHz)
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

d=10mm, Pin=250mW/Area Scan (81x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 86.167 V/m

Fast SAR: SAR(1 g) = 9.75 W/kg

Fast SAR(10 g) = 5.07 W/kg

Maximum value of SAR (interpolated) = 12.2 W/kg

d=10mm, Pin=250mW/Zoom Scan (6x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 86.167 V/m


Peak SAR (extrapolated) = 17.2 W/kg

SAR(1 g) = 9.69 W/kg

SAR(10 g) = 5.18 W/kg

Power Drift = 0.09 dB

Maximum value of SAR (measured) = 12.1 W/kg



Plot #12

Date/Time: 2014-07-29 08:17:08

Test Laboratory: TCC Microsoft
Type: D1900V2; Serial: D1900V2 - SN:5d030

Communication System: CW1900

Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: BSL1900; Medium Notes: $t = 21.2$ C

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.526$ S/m; $\epsilon_r = 52.978$; $\rho = 1000$ kg/m³

Phantom section: Center Section

DASY Configuration:

- Probe: EX3DV4 - SN3834
- ConvF(7.15, 7.15, 7.15); Calibrated: 2014-05-08;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1355; Calibrated: 2014-05-13
- Phantom: SAM 3 Triple Phantom 5.1C; Type: QD 000 P51 CA; Serial: TP-1124/2 (1800MHz), TP-1123/2 (1900MHz)
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

d=10mm, Pin=250mW/Area Scan (81x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 87.777 V/m

Fast SAR: SAR(1 g) = 10.5 W/kg

Fast SAR(10 g) = 5.23 W/kg

Maximum value of SAR (interpolated) = 13.3 W/kg

d=10mm, Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 87.777 V/m


Peak SAR (extrapolated) = 18.9 W/kg

SAR(1 g) = 10.5 W/kg

SAR(10 g) = 5.47 W/kg

Power Drift = 0.05 dB

Maximum value of SAR (measured) = 13.3 W/kg



Plot #13

Date/Time: 2014-07-29 09:21:18

Test Laboratory: TCC Microsoft

Type: D2450V2; Serial: D2450V2 - SN:749

Communication System: CW2450

Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: BSL2450; Medium Notes: t= 21.0 C

Medium parameters used: f = 2450 MHz; σ = 1.916 S/m; ϵ_r = 51.009; ρ = 1000 kg/m³

Phantom section: Center Section

DASY Configuration:

- Probe: EX3DV4 - SN3960
- ConvF(7.44, 7.44, 7.44); Calibrated: 2013-12-10;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1302; Calibrated: 2013-11-08
- Phantom: #2 Triple, SAR4; Type: QD 000 P51 CA; Serial: TP-1123/1 (750 MHz), TP-1124/1 (2450 MHz)
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

Configuration (2450 GHz)/d=10mm, Pin=250mW/Area Scan (81x61x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Reference Value = 80.464 V/m

Fast SAR: SAR(1 g) = 12.3 W/kg

Fast SAR(10 g) = 5.63 W/kg

Maximum value of SAR (interpolated) = 16.7 W/kg

Configuration (2450 GHz)/d=10mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 80.464 V/m


Peak SAR (extrapolated) = 24.7 W/kg

SAR(1 g) = 12.2 W/kg

SAR(10 g) = 5.68 W/kg

Power Drift = 0.06 dB

Maximum value of SAR (measured) = 16.0 W/kg



Plot #14

Date/Time: 2014-08-01 08:17:30

Test Laboratory: TCC Microsoft
Type: D2600V2; Serial: D2600V2 - SN:1056

Communication System: CW2600

Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: BSL2600; Medium Notes: t= 21 C

Medium parameters used: f = 2600 MHz; σ = 2.112 S/m; ϵ_r = 50.731; ρ = 1000 kg/m³

Phantom section: Center Section

DASY Configuration:

- Probe: EX3DV4 - SN3960
- ConvF(7.14, 7.14, 7.14); Calibrated: 2013-12-10;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1302; Calibrated: 2013-11-08
- Phantom: #2 Triple, SAR4; Type: QD 000 P51 CA; Serial: TP-1123/1 (750 MHz), TP-1124/1 (2450 MHz)
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

Configuration (2600 GHz)/d=10mm, Pin=250mW/Area Scan (81x61x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Reference Value = 82.363 V/m

Fast SAR: SAR(1 g) = 14.5 W/kg

Fast SAR(10 g) = 6.34 W/kg

Maximum value of SAR (interpolated) = 19.9 W/kg

Configuration (2600 GHz)/d=10mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 82.363 V/m


Peak SAR (extrapolated) = 30.3 W/kg

SAR(1 g) = 14.3 W/kg

SAR(10 g) = 6.41 W/kg

Power Drift = 0.03 dB

Maximum value of SAR (measured) = 19.1 W/kg



Plot #15

Date/Time: 2014-07-31 17:13:37

Test Laboratory: TCC Microsoft
Type: D5GHzV2; Serial: D5GHzV2 - SN: 1032

Communication System: CW5200

Frequency: 5200 MHz; Duty Cycle: 1:1

Medium: BSL 5000; Medium Notes: t= 21.8 C

Medium parameters used: f = 5200 MHz; σ = 5.332 S/m; ϵ_r = 47.695; ρ = 1000 kg/m³

Phantom section: Center Section

DASY Configuration:

- Probe: EX3DV4 - SN3892
- ConvF(4.34, 4.34, 4.34); Calibrated: 2013-11-15;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2013-11-11
- Phantom: 1. Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: TP-1124/3
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

d=10mm, Pin=100mW 5200/Area Scan (81x61x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Reference Value = 57.648 V/m

Fast SAR: SAR(1 g) = 6.91 W/kg

Fast SAR(10 g) = 1.92 W/kg

Maximum value of SAR (interpolated) = 15.3 W/kg

d=10mm, Pin=100mW 5200/Zoom Scan (8x8x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 57.648 V/m


Peak SAR (extrapolated) = 30.9 W/kg

SAR(1 g) = 7.52 W/kg

SAR(10 g) = 2.1 W/kg

Power Drift = -0.03 dB

Maximum value of SAR (measured) = 14.8 W/kg



Plot #16

Date/Time: 2014-08-01 13:48:47

Test Laboratory: TCC Microsoft

Type: D5GHzV2; Serial: D5GHzV2 - SN: 1032

Communication System: CW5600

Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: BSL5000; Medium Notes: $t = 21.8$ C

Medium parameters used: $f = 5600$ MHz; $\sigma = 5.839$ S/m; $\epsilon_r = 46.965$; $\rho = 1000$ kg/m³

Phantom section: Center Section

DASY Configuration:

- Probe: EX3DV4 - SN3892
- ConvF(4, 4, 4); Calibrated: 2013-11-15;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2013-11-11
- Phantom: 1. Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: TP-1124/3
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

d=10mm, Pin=100mW 5600/Area Scan (81x61x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Reference Value = 56.264 V/m

Fast SAR: SAR(1 g) = 7.26 W/kg

Fast SAR(10 g) = 2 W/kg

Maximum value of SAR (interpolated) = 16.5 W/kg

d=10mm, Pin=100mW 5600/Zoom Scan (8x8x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 56.264 V/m


Peak SAR (extrapolated) = 35.7 W/kg

SAR(1 g) = 8.01 W/kg

SAR(10 g) = 2.23 W/kg

Power Drift = -0.03 dB

Maximum value of SAR (measured) = 15.7 W/kg



Plot #17

Date/Time: 2014-07-31 13:52:39

Test Laboratory: TCC Microsoft
Type: D5GHzV2; Serial: D5GHzV2 - SN: 1032

Communication System: CW5800

Frequency: 5800 MHz; Duty Cycle: 1:1

Medium: BSL 5000; Medium Notes: $t = 21.8$ C

Medium parameters used: $f = 5800$ MHz; $\sigma = 6.12$ S/m; $\epsilon_r = 46.728$; $\rho = 1000$ kg/m³

Phantom section: Center Section

DASY Configuration:

- Probe: EX3DV4 - SN3892
- ConvF(4.02, 4.02, 4.02); Calibrated: 2013-11-15;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2013-11-11
- Phantom: 1. Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: TP-1124/3
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

d=10mm, Pin=100mW 5800/Area Scan (81x61x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Reference Value = 53.922 V/m

Fast SAR: SAR(1 g) = 6.57 W/kg

Fast SAR(10 g) = 1.8 W/kg

Maximum value of SAR (interpolated) = 15.1 W/kg

d=10mm, Pin=100mW 5800/Zoom Scan (8x8x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 53.922 V/m


Peak SAR (extrapolated) = 32.1 W/kg

SAR(1 g) = 7.23 W/kg

SAR(10 g) = 1.99 W/kg

Power Drift = 0.15 dB

Maximum value of SAR (measured) = 14.5 W/kg



APPENDIX B: MEASUREMENT SCANS

Plot #1

Date/Time: 2014-08-06 10:39:32

Test Laboratory: TCC Microsoft

Type: RM-985; Serial: 004402/47/815356/6

Communication System: LTE700 (Band 17)

Frequency: 711 MHz; Duty Cycle: 1:1

Medium: HSL750; Medium Notes: t= 21 C

Medium parameters used: f = 711 MHz; $\sigma = 0.867$ S/m; $\epsilon_r = 40.864$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

- Probe: EX3DV4 - SN3960
- ConvF(10.78, 10.78, 10.78); Calibrated: 2013-12-10;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1302; Calibrated: 2013-11-08
- Phantom: #1 SAM, SAR4; Type: SAM; Serial: TP-1018
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

LTE700 (Band 17) - Right/Cheek - High - QPSK - 10 MHz - 1RB - 100% offset/Area Scan (81x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 16.286 V/m

Fast SAR: SAR(1 g) = 0.218 W/kg

Fast SAR(10 g) = 0.154 W/kg

Maximum value of SAR (interpolated) = 0.250 W/kg

LTE700 (Band 17) - Right/Cheek - High - QPSK - 10 MHz - 1RB - 100% offset/Zoom Scan (6x6x7)/Cube 0:

Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 15.963 V/m


Peak SAR (extrapolated) = 0.281 W/kg

SAR(1 g) = 0.219 W/kg

SAR(10 g) = 0.166 W/kg

Power Drift = 0.01 dB

Maximum value of SAR (measured) = 0.241 W/kg



Plot #2

Date/Time: 2014-08-03 09:54:18

Test Laboratory: TCC Microsoft

Type: RM-985; Serial: 004402/47/815344/2

Communication System: 2-slot GPRS850

Frequency: 836.4 MHz; Duty Cycle: 1:4.19952

Medium: HSL835; Medium Notes: t= 22.2 C

Medium parameters used (interpolated): f = 836.4 MHz; $\sigma = 0.904$ S/m; $\epsilon_r = 40.06$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY Configuration:

- Probe: ES3DV3 - SN3194
- ConvF(6.12, 6.12, 6.12); Calibrated: 2013-11-14;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn538; Calibrated: 2013-11-19
- Phantom: SAM 1; Type: Twin SAM 040 CA; Serial: TP-1596
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

2-slot GPRS850 - Left/Cheek - Scenario 2 - Sub 2 - Middle/Area Scan (81x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 21.506 V/m

Fast SAR: SAR(1 g) = 0.377 W/kg

Fast SAR(10 g) = 0.263 W/kg

Maximum value of SAR (interpolated) = 0.430 W/kg

2-slot GPRS850 - Left/Cheek - Scenario 2 - Sub 2 - Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid:

dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 22.366 V/m


Peak SAR (extrapolated) = 0.497 W/kg

SAR(1 g) = 0.407 W/kg

SAR(10 g) = 0.317 W/kg

Power Drift = -0.05 dB

Maximum value of SAR (measured) = 0.443 W/kg



Plot #3

Date/Time: 2014-08-03 12:13:37

Test Laboratory: TCC Microsoft

Type: RM-985; Serial: 004402/47/815344/2

Communication System: WCDMA850 (Band 5)

Frequency: 843.8 MHz; Duty Cycle: 1:1

Medium: HSL835; Medium Notes: t= 22.2 C

Medium parameters used: f = 844 MHz; $\sigma = 0.909$ S/m; $\epsilon_r = 40.016$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY Configuration:

- Probe: ES3DV3 - SN3194
- ConvF(6.12, 6.12, 6.12); Calibrated: 2013-11-14;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn538; Calibrated: 2013-11-19
- Phantom: SAM 1; Type: Twin SAM 040 CA; Serial: TP-1596
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

WCDMA850 (Band 5) - Left/Cheek - Scenario 2 - Sub 3 - High/Area Scan (81x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 19.304 V/m

Fast SAR: SAR(1 g) = 0.294 W/kg

Fast SAR(10 g) = 0.208 W/kg

Maximum value of SAR (interpolated) = 0.332 W/kg

WCDMA850 (Band 5) - Left/Cheek - Scenario 2 - Sub 3 - High/Zoom Scan (5x5x7)/Cube 0: Measurement grid:

dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 19.304 V/m


Peak SAR (extrapolated) = 0.381 W/kg

SAR(1 g) = 0.310 W/kg

SAR(10 g) = 0.240 W/kg

Power Drift = 0.02 dB

Maximum value of SAR (measured) = 0.338 W/kg



Plot #4

Date/Time: 2014-08-04 10:13:42

Test Laboratory: TCC Microsoft

Type: RM-985; Serial: 004402/47/815344/2

Communication System: LTE850 (Band 5)

Frequency: 829 MHz; Duty Cycle: 1:1

Medium: HSL835; Medium Notes: $t = 22.7$ C

Medium parameters used: $f = 829$ MHz; $\sigma = 0.908$ S/m; $\epsilon_r = 40.676$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY Configuration:

- Probe: ES3DV3 - SN3194
- ConvF(6.12, 6.12, 6.12); Calibrated: 2013-11-14;
- Sensor-Surface: 3mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn538; Calibrated: 2013-11-19
- Phantom: SAM 1; Type: Twin SAM 040 CA; Serial: TP-1596
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

LTE850 (Band 5) - Left/Cheek - Low - QPSK - 10MHz - 1%RB - 0% offset/Area Scan (81x121x1): Interpolated
grid: $dx=1.500$ mm, $dy=1.500$ mm

Reference Value = 19.397 V/m

Fast SAR: SAR(1 g) = 0.295 W/kg

Fast SAR(10 g) = 0.207 W/kg

Maximum value of SAR (interpolated) = 0.333 W/kg

LTE850 (Band 5) - Left/Cheek - Low - QPSK - 10MHz - 1%RB - 0% offset/Zoom Scan (6x5x7)/Cube 0:

Measurement grid: $dx=7.5$ mm, $dy=7.5$ mm, $dz=5$ mm

Reference Value = 19.495 V/m


Peak SAR (extrapolated) = 0.370 W/kg

SAR(1 g) = 0.303 W/kg

SAR(10 g) = 0.237 W/kg

Power Drift = 0.03 dB

Maximum value of SAR (measured) = 0.327 W/kg



Plot #5

Date/Time: 2014-07-31 16:01:31

Test Laboratory: TCC Microsoft

Type: RM-985; Serial: 004402/47/815349/1

Communication System: LTE1700/2100 (Band 4)

Frequency: 1720 MHz; Duty Cycle: 1:1

Medium: HSL1800; Medium Notes: $t = 20.7$ C

Medium parameters used: $f = 1720$ MHz; $\sigma = 1.302$ S/m; $\epsilon_r = 38.388$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

- Probe: EX3DV4 - SN3834
- ConvF(7.62, 7.62, 7.62); Calibrated: 2014-05-08;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1355; Calibrated: 2014-05-13
- Phantom: SAM 4; Type: Twin SAM 040 CA; Serial: TP-1692
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

LTE1700_2100 (Band 4) - Right/Cheek - Low - QPSK - 20MHz - 1RB - 0% offset/Area Scan (81x121x1):

Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm

Reference Value = 15.267 V/m

Fast SAR: SAR(1 g) = 0.402 W/kg

Fast SAR(10 g) = 0.233 W/kg

Maximum value of SAR (interpolated) = 0.498 W/kg

LTE1700_2100 (Band 4) - Right/Cheek - Low - QPSK - 20MHz - 1RB - 0% offset/Zoom Scan (5x5x7)/Cube 0:

Measurement grid: $dx=7.5$ mm, $dy=7.5$ mm, $dz=5$ mm

Reference Value = 15.517 V/m


Peak SAR (extrapolated) = 0.626 W/kg

SAR(1 g) = 0.410 W/kg

SAR(10 g) = 0.255 W/kg

Power Drift = 0.06 dB

Maximum value of SAR (measured) = 0.477 W/kg



Plot #6

Date/Time: 2014-07-30 11:45:18

Test Laboratory: TCC Microsoft

Type: RM-985; Serial: 004402/47/815349/1

Communication System: 3-slot GPRS1900

Frequency: 1850.2 MHz; Duty Cycle: 1:2.80027

Medium: HSL1900; Medium Notes: t= 22.1 C

Medium parameters used (interpolated): f = 1850.2 MHz; $\sigma = 1.329$ S/m; $\epsilon_r = 39.346$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

- Probe: EX3DV4 - SN3834
- ConvF(7.33, 7.33, 7.33); Calibrated: 2014-05-08;
- Sensor-Surface: 3mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1355; Calibrated: 2014-05-13
- Phantom: SAM 1; Type: Twin SAM 040 CA; Serial: TP-1449
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

3-slot GPRS1900 - Right/Cheek - Low/Area Scan (81x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 10.722 V/m

Fast SAR: SAR(1 g) = 0.135 W/kg

Fast SAR(10 g) = 0.079 W/kg

Maximum value of SAR (interpolated) = 0.167 W/kg

3-slot GPRS1900 - Right/Cheek - Low/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 10.870 V/m


Peak SAR (extrapolated) = 0.204 W/kg

SAR(1 g) = 0.137 W/kg

SAR(10 g) = 0.089 W/kg

Power Drift = -0.00 dB

Maximum value of SAR (measured) = 0.157 W/kg



Plot #7

Date/Time: 2014-07-30 13:59:49

Test Laboratory: TCC Microsoft

Type: RM-985; Serial: 004402/47/815349/1

Communication System: WCDMA1900 (Band 2)

Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium: HSL1900; Medium Notes: t= 22.1 C

Medium parameters used (interpolated): f = 1852.4 MHz; $\sigma = 1.331$ S/m; $\epsilon_r = 39.339$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

- Probe: EX3DV4 - SN3834
- ConvF(7.33, 7.33, 7.33); Calibrated: 2014-05-08;
- Sensor-Surface: 3mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1355; Calibrated: 2014-05-13
- Phantom: SAM 1; Type: Twin SAM 040 CA; Serial: TP-1449
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

WCDMA1900 (Band 2) - Right/Cheek - Low/Area Scan (81x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 14.104 V/m

Fast SAR: SAR(1 g) = 0.239 W/kg

Fast SAR(10 g) = 0.139 W/kg

Maximum value of SAR (interpolated) = 0.294 W/kg

WCDMA1900 (Band 2) - Right/Cheek - Low/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 14.127 V/m


Peak SAR (extrapolated) = 0.347 W/kg

SAR(1 g) = 0.235 W/kg

SAR(10 g) = 0.152 W/kg

Power Drift = 0.07 dB

Maximum value of SAR (measured) = 0.274 W/kg



Plot #8

Date/Time: 2014-07-29 18:04:39

Test Laboratory: TCC Microsoft

Type: RM-985; Serial: 004402/47/815349/1

Communication System: LTE1900 (Band 2)

Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: HSL1900; Medium Notes: $t = 22.1$ C

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.377$ S/m; $\epsilon_r = 39.193$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

- Probe: EX3DV4 - SN3834
- ConvF(7.33, 7.33, 7.33); Calibrated: 2014-05-08;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1355; Calibrated: 2014-05-13
- Phantom: SAM 1; Type: Twin SAM 040 CA; Serial: TP-1449
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

LTE1900 (Band 2) - Right/Cheek - High - QPSK - 20MHz - 1RB - 100% offset/Area Scan (81x121x1): Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm

Reference Value = 11.588 V/m

Fast SAR: SAR(1 g) = 0.260 W/kg

Fast SAR(10 g) = 0.147 W/kg

Maximum value of SAR (interpolated) = 0.326 W/kg

LTE1900 (Band 2) - Right/Cheek - High - QPSK - 20MHz - 1RB - 100% offset/Zoom Scan (5x5x7)/Cube 0:

Measurement grid: $dx=7.5$ mm, $dy=7.5$ mm, $dz=5$ mm

Reference Value = 10.833 V/m


Peak SAR (extrapolated) = 0.349 W/kg

SAR(1 g) = 0.227 W/kg

SAR(10 g) = 0.141 W/kg

Power Drift = 0.05 dB

Maximum value of SAR (measured) = 0.267 W/kg



Plot #9

Date/Time: 2014-08-04 12:46:32

Test Laboratory: TCC Microsoft

Type: RM-985; Serial: 004402/47/815356/6

Communication System: LTE2500 (Band 7)

Frequency: 2511.7 MHz; Duty Cycle: 1:1

Medium: HSL2600; Medium Notes: $t = 21\text{ C}$

Medium parameters used: $f = 2512\text{ MHz}$; $\sigma = 1.87\text{ S/m}$; $\epsilon_r = 37.998$; $\rho = 1000\text{ kg/m}^3$

Phantom section: Left Section

DASY Configuration:

- Probe: EX3DV4 - SN3960
- ConvF(7.33, 7.33, 7.33); Calibrated: 2013-12-10;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1302; Calibrated: 2013-11-08
- Phantom: #4 SAM, SAR4 ; Type: QD000P40CD; Serial: TP-1691
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

LTE2500 (Band 7) - Left/Cheek - Sub 1- Scenario 1 - QPSK - 20MHz - 1RB - 0% offset/Area Scan (121x181x1):

Interpolated grid: $dx=1.000\text{ mm}$, $dy=1.000\text{ mm}$

Reference Value = 9.884 V/m

Fast SAR: SAR(1 g) = 0.295 W/kg

Fast SAR(10 g) = 0.151 W/kg

Maximum value of SAR (interpolated) = 0.379 W/kg

LTE2500 (Band 7) - Left/Cheek - Sub 1- Scenario 1 - QPSK - 20MHz - 1RB - 0% offset/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 9.982 V/m


Peak SAR (extrapolated) = 0.535 W/kg

SAR(1 g) = 0.294 W/kg

SAR(10 g) = 0.157 W/kg

Power Drift = -0.00 dB

Maximum value of SAR (measured) = 0.362 W/kg



SAR Report

Appendix B for FCC_RM-985_02

Applicant: Microsoft

Type: RM-985

Copyright © 2014 TCC Microsoft

Plot #10

Date/Time: 2014-08-04 13:22:38

Test Laboratory: TCC Microsoft

Type: RM-985; Serial: 004402/47/815356/6

Communication System: LTE2500 (Band 7)

Frequency: 2511.7 MHz; Duty Cycle: 1:1

Medium: HSL2600; Medium Notes: t= 21 C

Medium parameters used: f = 2512 MHz; $\sigma = 1.87$ S/m; $\epsilon_r = 37.998$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY Configuration:

- Probe: EX3DV4 - SN3960
- ConvF(7.33, 7.33, 7.33); Calibrated: 2013-12-10;
- Sensor-Surface: 3mm (Mechanical Surface Detection (Locations From Previous Scan Used))
- Electronics: DAE4 Sn1302; Calibrated: 2013-11-08
- Phantom: #4 SAM, SAR4 ; Type: QD000P40CD; Serial: TP-1691
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

LTE2500 (Band 7) - Left/Tilt - Sub 1- Scenario 2 - QPSK - 20MHz - 1RB - 0% offset/Area Scan (121x181x1):

Interpolated grid: dx=1.000 mm, dy=1.000 mm


Reference Value = 4.648 V/m

Fast SAR: SAR(1 g) = 0.093 W/kg

Fast

AR(10 g) = 0.043 W/kg

Maximum value of SAR (interpolated) = 0.130 W/kg



Plot #11

Date/Time: 2014-08-04 13:48:24

Test Laboratory: TCC Microsoft

Type: RM-985; Serial: 004402/47/815356/6

Communication System: LTE2500 (Band 7)

Frequency: 2511.7 MHz; Duty Cycle: 1:1

Medium: HSL2600; Medium Notes: $t = 21\text{ C}$

Medium parameters used: $f = 2512\text{ MHz}$; $\sigma = 1.87\text{ S/m}$; $\epsilon_r = 37.998$; $\rho = 1000\text{ kg/m}^3$

Phantom section: Right Section

DASY Configuration:

- Probe: EX3DV4 - SN3960
- ConvF(7.33, 7.33, 7.33); Calibrated: 2013-12-10;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1302; Calibrated: 2013-11-08
- Phantom: #4 SAM, SAR4 ; Type: QD000P40CD; Serial: TP-1691
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

LTE2500 (Band 7) - Right/Cheek - Sub 1 - Scenario 2 - QPSK - 20MHz - 1RB - 0% offset/Area Scan (121x181x1):

Interpolated grid: $dx=1.000\text{ mm}$, $dy=1.000\text{ mm}$


Reference Value = 6.811 V/m

Fast SAR: SAR(1 g) = 0.137 W/kg

Fast

AR(10 g) = 0.069 W/kg

Maximum value of SAR (interpolated) = 0.177 W/kg



Plot #12

Date/Time: 2014-08-04 14:42:47

Test Laboratory: TCC Microsoft

Type: RM-985; Serial: 004402/47/815356/6

Communication System: LTE2500 (Band 7)

Frequency: 2511.7 MHz; Duty Cycle: 1:1

Medium: HSL2600; Medium Notes: $t = 21$ C

Medium parameters used: $f = 2512$ MHz; $\sigma = 1.87$ S/m; $\epsilon_r = 37.998$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

- Probe: EX3DV4 - SN3960
- ConvF(7.33, 7.33, 7.33); Calibrated: 2013-12-10;
- Sensor-Surface: 3mm (Mechanical Surface Detection (Locations From Previous Scan Used))
- Electronics: DAE4 Sn1302; Calibrated: 2013-11-08
- Phantom: #4 SAM, SAR4 ; Type: QD000P40CD; Serial: TP-1691
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

LTE2500 (Band 7) - Right/Tilt - Sub 1 - Scenario 1 - QPSK - 20MHz - 1RB - 0% offset/Area Scan (121x181x1):

Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm


Reference Value = 5.117 V/m

Fast SAR: SAR(1 g) = 0.048 W/kg

Fast

AR(10 g) = 0.024 W/kg

Maximum value of SAR (interpolated) = 0.0647 W/kg



Plot #13

Date/Time: 2014-07-28 10:21:54

Test Laboratory: TCC Microsoft

Type: RM-985; Serial: 004402/47/815308/7

Communication System: WLAN2450

Frequency: 2437 MHz; Duty Cycle: 1:1

Medium: HSL2450; Medium Notes: t= 21.1 C

Medium parameters used: f = 2437 MHz; $\sigma = 1.78$ S/m; $\epsilon_r = 38.907$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

- Probe: EX3DV4 - SN3960
- ConvF(7.39, 7.39, 7.39); Calibrated: 2013-12-10;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1302; Calibrated: 2013-11-08
- Phantom: #4 SAM, SAR4 ; Type: QD000P40CD; Serial: TP-1691
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

WLAN2450 b-mode - Right/Tilt - Channel 6 - QPSK 5,5 Mbps/Area Scan (121x181x1): Interpolated grid:

dx=1.000 mm, dy=1.000 mm

Reference Value = 14.565 V/m

Fast SAR: SAR(1 g) = 0.545 W/kg

Fast SAR(10 g) = 0.248 W/kg

Maximum value of SAR (interpolated) = 0.854 W/kg

WLAN2450 b-mode - Right/Tilt - Channel 6 - QPSK 5,5 Mbps/Zoom Scan (8x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm

Reference Value = 19.117 V/m


Peak SAR (extrapolated) = 1.20 W/kg

SAR(1 g) = 0.538 W/kg

SAR(10 g) = 0.235 W/kg

Power Drift = 0.16 dB

Maximum value of SAR (measured) = 0.745 W/kg



Plot #14

Date/Time: 2014-07-30 11:46:36

Test Laboratory: TCC Microsoft

Type: RM-985; Serial: 004402/47/815319/4

Communication System: WLAN5000

Frequency: 5680 MHz; Duty Cycle: 1:1

Medium: HSL5000; Medium Notes: t= 22.2 C

Medium parameters used: f = 5680 MHz; σ = 5.032 S/m; ϵ_r = 35.45; ρ = 1000 kg/m³

Phantom section: Right Section

DASY Configuration:

- Probe: EX3DV4 - SN3892
- ConvF(4.66, 4.66, 4.66); Calibrated: 2013-11-15;
- Sensor-Surface: 2mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2013-11-11
- Phantom: SAM2; Type: SAM; Serial: TP-1570
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

WLAN5000 a-mode - Right/Cheek - Channel 136 - BPSK 6 Mbps/Area Scan (121x181x1): Interpolated grid:

dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.412 W/kg

WLAN5000 a-mode - Right/Cheek - Channel 136 - BPSK 6 Mbps/Zoom Scan (9x8x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 8.881 V/m


Peak SAR (extrapolated) = 0.771 W/kg

SAR(1 g) = 0.174 W/kg

SAR(10 g) = 0.048 W/kg

Power Drift = 0.20 dB

Maximum value of SAR (measured) = 0.414 W/kg



Plot #15

Date/Time: 2014-08-06 20:09:51

Test Laboratory: TCC Microsoft

Type: RM-985; Serial: 004402/47/815356/6

Communication System: LTE700 (Band 17)

Frequency: 711 MHz; Duty Cycle: 1:1

Medium: BSL750; Medium Notes: t= 20.8 C

Medium parameters used: f = 711 MHz; $\sigma = 0.968$ S/m; $\epsilon_r = 54.472$; $\rho = 1000$ kg/m³

Phantom section: Center Section

DASY Configuration:

- Probe: EX3DV4 - SN3960
- ConvF(10.24, 10.24, 10.24); Calibrated: 2013-12-10;
- Sensor-Surface: 3mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1302; Calibrated: 2013-11-08
- Phantom: #2 Triple, SAR4; Type: QD 000 P51 CA; Serial: TP-1123/1 (750 MHz), TP-1124/1 (2450 MHz)
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

LTE 700 (Band 17)/Body - High - QPSK - 10MHz - 1RB - 100% offset - Spacer 15mm - No Headset - Display Facing Phantom/Area Scan (81x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 15.766 V/m

Fast SAR: SAR(1 g) = 0.394 W/kg

Fast SAR(10 g) = 0.280 W/kg

Maximum value of SAR (interpolated) = 0.446 W/kg

LTE 700 (Band 17)/Body - High - QPSK - 10MHz - 1RB - 100% offset - Spacer 15mm - No Headset - Display Facing Phantom/Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 15.784 V/m


Peak SAR (extrapolated) = 0.541 W/kg

SAR(1 g) = 0.402 W/kg

SAR(10 g) = 0.293 W/kg

Power Drift = 0.08 dB

Maximum value of SAR (measured) = 0.451 W/kg



Plot #16

Date/Time: 2014-07-30 11:57:47

Test Laboratory: TCC Microsoft

Type: RM-985; Serial: 004402/47/815344/2

Communication System: 2-slot GPRS850

Frequency: 836.4 MHz; Duty Cycle: 1:4.19952

Medium: BSL835; Medium Notes: t= 21.8 C

Medium parameters used (interpolated): f = 836.4 MHz; $\sigma = 0.977$ S/m; $\epsilon_r = 53.362$; $\rho = 1000$ kg/m³

Phantom section: Center Section

DASY Configuration:

- Probe: ES3DV3 - SN3194
- ConvF(6.05, 6.05, 6.05); Calibrated: 2013-11-14;
- Sensor-Surface: 3mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn538; Calibrated: 2013-11-19
- Phantom: SAM 3 Triple Phantom 5.1C; Type: QD 000 P51 CA; Serial: TP-1123/3
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

2-slot GPRS850/Body - Scenario 0 - Sub2 - Spacer 15mm - No Headset - Display Facing phantom/Area Scan (81x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 22.527 V/m

Fast SAR: SAR(1 g) = 0.420 W/kg

Fast SAR(10 g) = 0.298 W/kg

Maximum value of SAR (interpolated) = 0.486 W/kg

2-slot GPRS850/Body - Scenario 0 - Sub2 - Spacer 15mm - No Headset - Display Facing phantom/Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 23.005 V/m


Peak SAR (extrapolated) = 0.559 W/kg

SAR(1 g) = 0.442 W/kg

SAR(10 g) = 0.336 W/kg

Power Drift = -0.06 dB

Maximum value of SAR (measured) = 0.484 W/kg



Plot #17

Date/Time: 2014-08-03 15:12:32

Test Laboratory: TCC Microsoft

Type: RM-985; Serial: 004402/47/815344/2

Communication System: WCDMA850 (Band 5)

Frequency: 843.8 MHz; Duty Cycle: 1:1

Medium: BSL835; Medium Notes: $t = 22.3$ C

Medium parameters used: $f = 844$ MHz; $\sigma = 0.983$ S/m; $\epsilon_r = 53.123$; $\rho = 1000$ kg/m³

Phantom section: Center Section

DASY Configuration:

- Probe: ES3DV3 - SN3194
- ConvF(6.05, 6.05, 6.05); Calibrated: 2013-11-14;
- Sensor-Surface: 3mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn538; Calibrated: 2013-11-19
- Phantom: SAM 3 Triple Phantom 5.1C; Type: QD 000 P51 CA; Serial: TP-1123/3
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

WCDMA850 (Band 5)/Body - Scenario 0 - Sub 3 - Spacer 15mm - No Headset - Display facing phantom/Area Scan (81x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 20.350 V/m

Fast SAR: SAR(1 g) = 0.327 W/kg

Fast SAR(10 g) = 0.235 W/kg

Maximum value of SAR (interpolated) = 0.374 W/kg

WCDMA850 (Band 5)/Body - Scenario 0 - Sub 3 - Spacer 15mm - No Headset - Display facing phantom/Zoom Scan (5x6x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 19.828 V/m


Peak SAR (extrapolated) = 0.428 W/kg

SAR(1 g) = 0.338 W/kg

SAR(10 g) = 0.254 W/kg

Power Drift = 0.08 dB

Maximum value of SAR (measured) = 0.372 W/kg



Plot #18

Date/Time: 2014-08-04 15:41:09

Test Laboratory: TCC Microsoft

Type: RM-985; Serial: 004402/47/815344/2

Communication System: LTE850 (Band 5)

Frequency: 829 MHz; Duty Cycle: 1:1

Medium: BSL835; Medium Notes: $t = 22.3$ C

Medium parameters used: $f = 829$ MHz; $\sigma = 0.972$ S/m; $\epsilon_r = 53.711$; $\rho = 1000$ kg/m³

Phantom section: Center Section

DASY Configuration:

- Probe: ES3DV3 - SN3194
- ConvF(6.05, 6.05, 6.05); Calibrated: 2013-11-14;
- Sensor-Surface: 3mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn538; Calibrated: 2013-11-19
- Phantom: SAM 3 Triple Phantom 5.1C; Type: QD 000 P51 CA; Serial: TP-1124/2 (1800MHz), TP-1123/2 (1900MHz)
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

LTE850 (Band 5)/Body - Low - QPSK - 10MHz - 1RB - 0% offset - Spacer 15mm - No Headset - Display Facing Phantom/Area Scan (81x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 19.815 V/m

Fast SAR: SAR(1 g) = 0.316 W/kg

Fast SAR(10 g) = 0.227 W/kg

Maximum value of SAR (interpolated) = 0.362 W/kg

LTE850 (Band 5)/Body - Low - QPSK - 10MHz - 1RB - 0% offset - Spacer 15mm - No Headset - Display Facing Phantom/Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 19.809 V/m


Peak SAR (extrapolated) = 0.416 W/kg

SAR(1 g) = 0.325 W/kg

SAR(10 g) = 0.245 W/kg

Power Drift = 0.01 dB

Maximum value of SAR (measured) = 0.356 W/kg



SAR Report

Appendix B for FCC_RM-985_02

Applicant: Microsoft

Type: RM-985

Copyright © 2014 TCC Microsoft

Plot #19

Date/Time: 2014-08-01 10:29:29

Test Laboratory: TCC Microsoft

Type: RM-985; Serial: 004402/47/815349/1

Communication System: LTE1700/2100 (Band 4)

Frequency: 1745 MHz; Duty Cycle: 1:1

Medium: BSL1800; Medium Notes: t= 21.2 C

Medium parameters used: f = 1745 MHz; $\sigma = 1.446$ S/m; $\epsilon_r = 52.088$; $\rho = 1000$ kg/m³

Phantom section: Center Section

DASY Configuration:

- Probe: EX3DV4 - SN3834
- ConvF(7.35, 7.35, 7.35); Calibrated: 2014-05-08;
- Sensor-Surface: 3mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1355; Calibrated: 2014-05-13
- Phantom: SAM 3 Triple Phantom 5.1C; Type: QD 000 P51 CA; Serial: TP-1124/2 (1800MHz), TP-1123/2 (1900MHz)
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

LTE 1700_2100 (Band 4)/Body - High - QPSK - 20MHz - 1RB - 0% offset - Spacer 15mm - WH-208 - Display Facing Phantom/Area Scan (81x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 25.033 V/m

Fast SAR: SAR(1 g) = 0.776 W/kg

Fast SAR(10 g) = 0.439 W/kg

Maximum value of SAR (interpolated) = 0.959 W/kg

LTE 1700_2100 (Band 4)/Body - High - QPSK - 20MHz - 1RB - 0% offset - Spacer 15mm - WH-208 - Display Facing Phantom/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 24.989 V/m


Peak SAR (extrapolated) = 1.26 W/kg

SAR(1 g) = 0.805 W/kg

SAR(10 g) = 0.480 W/kg

Power Drift = 0.02 dB

Maximum value of SAR (measured) = 0.967 W/kg



Plot #20

Date/Time: 2014-07-28 12:43:05

Test Laboratory: TCC Microsoft

Type: RM-985; Serial: 004402/47/815349/1

Communication System: 3-slot GPRS1900

Frequency: 1909.8 MHz; Duty Cycle: 1:2.80027

Medium: BSL1900; Medium Notes: t= 21.3 C

Medium parameters used: f = 1910 MHz; $\sigma = 1.538$ S/m; $\epsilon_r = 53.171$; $\rho = 1000$ kg/m³

Phantom section: Center Section

DASY Configuration:

- Probe: EX3DV4 - SN3834
- ConvF(7.15, 7.15, 7.15); Calibrated: 2014-05-08;
- Sensor-Surface: 3mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1355; Calibrated: 2014-05-13
- Phantom: SAM 3 Triple Phantom 5.1C; Type: QD 000 P51 CA; Serial: TP-1124/2 (1800MHz), TP-1123/2 (1900MHz)
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

3-slot GRPS1900/Body - High - Spacer 15mm - WH-208 - Display Facing Phantom/Area Scan (81x121x1):

Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 19.105 V/m

Fast SAR: SAR(1 g) = 0.473 W/kg

Fast SAR(10 g) = 0.258 W/kg

Maximum value of SAR (interpolated) = 0.592 W/kg

3-slot GRPS1900/Body - High - Spacer 15mm - WH-208 - Display Facing Phantom/Zoom Scan (5x5x7)/Cube 0:

Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 19.194 V/m


Peak SAR (extrapolated) = 0.792 W/kg

SAR(1 g) = 0.488 W/kg

SAR(10 g) = 0.279 W/kg

Power Drift = -0.02 dB

Maximum value of SAR (measured) = 0.541 W/kg



Plot #21

Date/Time: 2014-07-28 16:07:10

Test Laboratory: TCC Microsoft

Type: RM-985; Serial: 004402/47/815349/1

Communication System: WCDMA1900 (Band 2)

Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium: BSL1900; Medium Notes: t= 21.3 C

Medium parameters used (interpolated): f = 1852.4 MHz; $\sigma = 1.484$ S/m; $\epsilon_r = 53.279$; $\rho = 1000$ kg/m³

Phantom section: Center Section

DASY Configuration:

- Probe: EX3DV4 - SN3834
- ConvF(7.15, 7.15, 7.15); Calibrated: 2014-05-08;
- Sensor-Surface: 3mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1355; Calibrated: 2014-05-13
- Phantom: SAM 3 Triple Phantom 5.1C; Type: QD 000 P51 CA; Serial: TP-1124/2 (1800MHz), TP-1123/2 (1900MHz)
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

WCDMA1900 (Band 2)/Body - Low - Spacer 15mm - No Headset - Display Facing Phantom - Repeated/Area Scan (81x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 25.220 V/m

Fast SAR: SAR(1 g) = 0.824 W/kg

Fast SAR(10 g) = 0.458 W/kg

Maximum value of SAR (interpolated) = 1.02 W/kg

WCDMA1900 (Band 2)/Body - Low - Spacer 15mm - No Headset - Display Facing Phantom - Repeated/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 25.220 V/m


Peak SAR (extrapolated) = 1.42 W/kg

SAR(1 g) = 0.883 W/kg

SAR(10 g) = 0.511 W/kg

Power Drift = 0.06 dB

Maximum value of SAR (measured) = 0.979 W/kg



Plot #22

Date/Time: 2014-07-29 16:30:17

Test Laboratory: TCC Microsoft

Type: RM-985; Serial: 004402/47/815349/1

Communication System: LTE1900 (Band 2)

Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: BSL1900; Medium Notes: $t = 21.2$ C

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.526$ S/m; $\epsilon_r = 52.978$; $\rho = 1000$ kg/m³

Phantom section: Center Section

DASY Configuration:

- Probe: EX3DV4 - SN3834
- ConvF(7.15, 7.15, 7.15); Calibrated: 2014-05-08;
- Sensor-Surface: 3mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1355; Calibrated: 2014-05-13
- Phantom: SAM 3 Triple Phantom 5.1C; Type: QD 000 P51 CA; Serial: TP-1124/2 (1800MHz), TP-1123/2 (1900MHz)
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

LTE 1900 (Band 2)/Body - High - QPSK - 20MHz - 1RB - 100% offset - Spacer 15mm - WH-208 - Display Facing Phantom/Area Scan (81x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 23.578 V/m

Fast SAR: SAR(1 g) = 0.730 W/kg

Fast SAR(10 g) = 0.402 W/kg

Maximum value of SAR (interpolated) = 0.906 W/kg

LTE 1900 (Band 2)/Body - High - QPSK - 20MHz - 1RB - 100% offset - Spacer 15mm - WH-208 - Display Facing Phantom/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 23.585 V/m


Peak SAR (extrapolated) = 1.24 W/kg

SAR(1 g) = 0.766 W/kg

SAR(10 g) = 0.441 W/kg

Power Drift = 0.02 dB

Maximum value of SAR (measured) = 0.928 W/kg



Plot #23

Date/Time: 2014-07-31 17:11:46

Test Laboratory: TCC Microsoft

Type: RM-985; Serial: 004402/47/815356/6

Communication System: LTE2500 (Band 7)

Frequency: 2511.7 MHz; Duty Cycle: 1:1

Medium: BSL2600; Medium Notes: t= 21.2 C

Medium parameters used: f = 2512 MHz; σ = 2.013 S/m; ϵ_r = 50.572; ρ = 1000 kg/m³

Phantom section: Center Section

DASY Configuration:

- Probe: EX3DV4 - SN3960
- ConvF(7.14, 7.14, 7.14); Calibrated: 2013-12-10;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1302; Calibrated: 2013-11-08
- Phantom: #2 Triple, SAR4; Type: QD 000 P51 CA; Serial: TP-1123/1 (750 MHz), TP-1124/1 (2450 MHz)
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

LTE2500 (Band 7)/Body - Sub 1 - Scenario 1 - QPSK - 20MHz - 1RB - 0% offset - Spacer 15mm - No Headset - Back Facing Phantom/Area Scan (121x181x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm


Reference Value = 17.061 V/m

Fast SAR: SAR(1 g) = 0.503 W/kg

Fast

AR(10 g) = 0.276 W/kg

Maximum value of SAR (interpolated) = 0.626 W/kg



Plot #24

Date/Time: 2014-07-31 17:47:56

Test Laboratory: TCC Microsoft

Type: RM-985; Serial: 004402/47/815356/6

Communication System: LTE2500 (Band 7)

Frequency: 2511.7 MHz; Duty Cycle: 1:1

Medium: BSL2600; Medium Notes: $t = 21.2$ C

Medium parameters used: $f = 2512$ MHz; $\sigma = 2.013$ S/m; $\epsilon_r = 50.572$; $\rho = 1000$ kg/m³

Phantom section: Center Section

DASY Configuration:

- Probe: EX3DV4 - SN3960
- ConvF(7.14, 7.14, 7.14); Calibrated: 2013-12-10;
- Sensor-Surface: 3mm (Mechanical Surface Detection (Locations From Previous Scan Used))
- Electronics: DAE4 Sn1302; Calibrated: 2013-11-08
- Phantom: #2 Triple, SAR4; Type: QD 000 P51 CA; Serial: TP-1123/1 (750 MHz), TP-1124/1 (2450 MHz)
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

LTE2500 (Band 7)/Body - Sub 1 - Scenario 1 - QPSK - 20MHz - 1RB - 0% offset - Spacer 15mm - WH-208 - Back Facing Phantom/Area Scan (121x181x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm


Reference Value = 17.450 V/m

Fast SAR: SAR(1 g) = 0.501 W/kg

Fast

AR(10 g) = 0.274 W/kg

Maximum value of SAR (interpolated) = 0.623 W/kg



Plot #25

Date/Time: 2014-07-31 18:18:23

Test Laboratory: TCC Microsoft

Type: RM-985; Serial: 004402/47/815356/6

Communication System: LTE2500 (Band 7)

Frequency: 2511.7 MHz; Duty Cycle: 1:1

Medium: BSL2600; Medium Notes: t= 21.2 C

Medium parameters used: f = 2512 MHz; σ = 2.013 S/m; ϵ_r = 50.572; ρ = 1000 kg/m³

Phantom section: Center Section

DASY Configuration:

- Probe: EX3DV4 - SN3960
- ConvF(7.14, 7.14, 7.14); Calibrated: 2013-12-10;
- Sensor-Surface: 3mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1302; Calibrated: 2013-11-08
- Phantom: #2 Triple, SAR4; Type: QD 000 P51 CA; Serial: TP-1123/1 (750 MHz), TP-1124/1 (2450 MHz)
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

LTE2500 (Band 7)/Body - Sub 1 - Scenario 1 - QPSK - 20MHz - 1RB - 0% offset - Spacer 15mm - No Headset - Display Facing Phantom/Area Scan (121x181x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Reference Value = 14.879 V/m

Fast SAR: SAR(1 g) = 0.643 W/kg

Fast SAR(10 g) = 0.341 W/kg

Maximum value of SAR (interpolated) = 0.808 W/kg

LTE2500 (Band 7)/Body - Sub 1 - Scenario 1 - QPSK - 20MHz - 1RB - 0% offset - Spacer 15mm - No Headset - Display Facing Phantom/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 14.970 V/m


Peak SAR (extrapolated) = 1.17 W/kg

SAR(1 g) = 0.642 W/kg

SAR(10 g) = 0.348 W/kg

Power Drift = -0.03 dB

Maximum value of SAR (measured) = 0.799 W/kg



Plot #26

Date/Time: 2014-07-31 19:02:23

Test Laboratory: TCC Microsoft

Type: RM-985; Serial: 004402/47/815356/6

Communication System: LTE2500 (Band 7)

Frequency: 2511.7 MHz; Duty Cycle: 1:1

Medium: BSL2600; Medium Notes: t= 21.2 C

Medium parameters used: f = 2512 MHz; $\sigma = 2.013$ S/m; $\epsilon_r = 50.572$; $\rho = 1000$ kg/m³

Phantom section: Center Section

DASY Configuration:

- Probe: EX3DV4 - SN3960
- ConvF(7.14, 7.14, 7.14); Calibrated: 2013-12-10;
- Sensor-Surface: 3mm (Mechanical Surface Detection (Locations From Previous Scan Used))
- Electronics: DAE4 Sn1302; Calibrated: 2013-11-08
- Phantom: #2 Triple, SAR4; Type: QD 000 P51 CA; Serial: TP-1123/1 (750 MHz), TP-1124/1 (2450 MHz)
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)


LTE2500 (Band 7)/Body - Sub 1 - Scenario 1 - QPSK - 20MHz - 1RB - 0% offset - Spacer 15mm - WH-208 - Display Facing Phantom/Area Scan (121x181x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Reference Value = 15.043 V/m

Fast SAR: SAR(1 g) = 0.636 W/kg

Fast SAR(10 g) = 0.337 W/kg

Maximum value of SAR (interpolated) = 0.800 W/kg



Plot #27

Date/Time: 2014-07-29 10:56:34

Test Laboratory: TCC Microsoft

Type: RM-985; Serial: 004402/47/815308/7

Communication System: WLAN2450

Frequency: 2412 MHz; Duty Cycle: 1:1

Medium: BSL2450; Medium Notes: t= 21.0 C

Medium parameters used: f = 2412 MHz; $\sigma = 1.871$ S/m; $\epsilon_r = 51.094$; $\rho = 1000$ kg/m³

Phantom section: Center Section

DASY Configuration:

- Probe: EX3DV4 - SN3960
- ConvF(7.44, 7.44, 7.44); Calibrated: 2013-12-10;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1302; Calibrated: 2013-11-08
- Phantom: #2 Triple, SAR4; Type: QD 000 P51 CA; Serial: TP-1123/1 (750 MHz), TP-1124/1 (2450 MHz)
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

WLAN2450 b-mode/Body - Channel 1 - BPSK 1 Mbps - Spacer 15mm - No Headset - Back Facing Phantom/Area Scan (121x181x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Reference Value = 9.326 V/m

Fast SAR: SAR(1 g) = 0.139 W/kg

Fast SAR(10 g) = 0.068 W/kg

Maximum value of SAR (interpolated) = 0.186 W/kg

WLAN2450 b-mode/Body - Channel 1 - BPSK 1 Mbps - Spacer 15mm - No Headset - Back Facing Phantom/Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.115 V/m


Peak SAR (extrapolated) = 0.229 W/kg

SAR(1 g) = 0.123 W/kg

SAR(10 g) = 0.069 W/kg

Power Drift = 0.04 dB

Maximum value of SAR (measured) = 0.151 W/kg



Plot #28

Date/Time: 2014-07-31 14:33:58

Test Laboratory: TCC Microsoft

Type: RM-985; Serial: 004402/47/815319/4

Communication System: WLAN5000

Frequency: 5825 MHz; Duty Cycle: 1:1

Medium: BSL 5000; Medium Notes: t= 21.8 C

Medium parameters used: f = 5825 MHz; σ = 6.155 S/m; ϵ_r = 46.675; ρ = 1000 kg/m³

Phantom section: Center Section

DASY Configuration:

- Probe: EX3DV4 - SN3892
- ConvF(4.02, 4.02, 4.02); Calibrated: 2013-11-15;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2013-11-11
- Phantom: 1. Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: TP-1124/3
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

WLAN5000 a-mode/Body - Channel 165 - BPSK 6 Mbps - Spacer 15mm - No Headset - Back Facing

Phantom/Area Scan (121x181x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.299 W/kg

WLAN5000 a-mode/Body - Channel 165 - BPSK 6 Mbps - Spacer 15mm - No Headset - Back Facing

Phantom/Zoom Scan (8x8x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 5.519 V/m


Peak SAR (extrapolated) = 0.605 W/kg

SAR(1 g) = 0.154 W/kg

SAR(10 g) = 0.053 W/kg

Power Drift = -0.05 dB

Maximum value of SAR (measured) = 0.294 W/kg



Plot #29

Date/Time: 2014-08-07 10:01:16

Test Laboratory: TCC Microsoft

Type: RM-985; Serial: 004402/47/815356/6

Communication System: LTE700 (Band 17)

Frequency: 711 MHz; Duty Cycle: 1:1

Medium: BSL750; Medium Notes: $t = 20.8$ C

Medium parameters used: $f = 711$ MHz; $\sigma = 0.968$ S/m; $\epsilon_r = 54.472$; $\rho = 1000$ kg/m³

Phantom section: Center Section

DASY Configuration:

- Probe: EX3DV4 - SN3960
- ConvF(10.24, 10.24, 10.24); Calibrated: 2013-12-10;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1302; Calibrated: 2013-11-08
- Phantom: #2 Triple, SAR4; Type: QD 000 P51 CA; Serial: TP-1123/1 (750 MHz), TP-1124/1 (2450 MHz)
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

LTE700 (Band 17) /Body - High - QPSK - 10MHz - 1RB - 100% offset - Spacer 10mm - No Headset - Display Facing Phantom/Area Scan (81x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 25.334 V/m

Fast SAR: SAR(1 g) = 0.551 W/kg

Fast SAR(10 g) = 0.385 W/kg

Maximum value of SAR (interpolated) = 0.626 W/kg

LTE700 (Band 17) /Body - High - QPSK - 10MHz - 1RB - 100% offset - Spacer 10mm - No Headset - Display Facing Phantom/Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 25.334 V/m


Peak SAR (extrapolated) = 0.804 W/kg

SAR(1 g) = 0.546 W/kg

SAR(10 g) = 0.380 W/kg

Power Drift = -0.02 dB

Maximum value of SAR (measured) = 0.622 W/kg



Plot #30

Date/Time: 2014-08-06 09:51:57

Test Laboratory: TCC Microsoft

Type: RM-985; Serial: 004402/47/815344/2

Communication System: 2-slot GPRS850

Frequency: 836.4 MHz; Duty Cycle: 1:4.19952

Medium: BSL835; Medium Notes: t= 22.3 C

Medium parameters used (interpolated): f = 836.4 MHz; $\sigma = 0.977$ S/m; $\epsilon_r = 53.631$; $\rho = 1000$ kg/m³

Phantom section: Center Section

DASY Configuration:

- Probe: ES3DV3 - SN3194
- ConvF(6.05, 6.05, 6.05); Calibrated: 2013-11-14;
- Sensor-Surface: 3mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn538; Calibrated: 2013-11-19
- Phantom: SAM 3 Triple Phantom 5.1C; Type: QD 000 P51 CA; Serial: TP-1123/3
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

2-slot GPRS850 (Band 5)/Body - Scenario 0 - Sub 2 - Spacer 10mm - No Headset - Display Facing Phantom/Area Scan (81x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 29.090 V/m

Fast SAR: SAR(1 g) = 0.667 W/kg

Fast SAR(10 g) = 0.431 W/kg

Maximum value of SAR (interpolated) = 0.797 W/kg

2-slot GPRS850 (Band 5)/Body - Scenario 0 - Sub 2 - Spacer 10mm - No Headset - Display Facing Phantom/Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 29.090 V/m


Peak SAR (extrapolated) = 1.18 W/kg

SAR(1 g) = 0.669 W/kg

SAR(10 g) = 0.377 W/kg

Power Drift = 0.10 dB

Maximum value of SAR (measured) = 0.720 W/kg



Plot #31

Date/Time: 2014-07-31 15:26:18

Test Laboratory: TCC Microsoft

Type: RM-985; Serial: 004402/47/815344/2

Communication System: WCDMA850 (Band 5)

Frequency: 836 MHz; Duty Cycle: 1:1

Medium: BSL835; Medium Notes: t= 21.8 C

Medium parameters used: f = 836 MHz; σ = 0.98 S/m; ϵ_r = 53.338; ρ = 1000 kg/m³

Phantom section: Center Section

DASY Configuration:

- Probe: ES3DV3 - SN3194
- ConvF(6.05, 6.05, 6.05); Calibrated: 2013-11-14;
- Sensor-Surface: 3mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn538; Calibrated: 2013-11-19
- Phantom: SAM 3 Triple Phantom 5.1C; Type: QD 000 P51 CA; Serial: TP-1123/3
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

WCDMA850 (Band 5)/Body - Scenario 0 - Sub 2 - Spacer 10mm - No Headset - Display Facing Phantom/Area Scan (81x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 24.481 V/m

Fast SAR: SAR(1 g) = 0.530 W/kg

Fast SAR(10 g) = 0.346 W/kg

Maximum value of SAR (interpolated) = 0.631 W/kg

WCDMA850 (Band 5)/Body - Scenario 0 - Sub 2 - Spacer 10mm - No Headset - Display Facing Phantom/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 24.703 V/m


Peak SAR (extrapolated) = 0.931 W/kg

SAR(1 g) = 0.540 W/kg

SAR(10 g) = 0.303 W/kg

Power Drift = 0.00 dB

Maximum value of SAR (measured) = 0.586 W/kg



Plot #32

Date/Time: 2014-08-05 15:20:50

Test Laboratory: TCC Microsoft

Type: RM-985; Serial: 004402/47/815344/2

Communication System: LTE850 (Band 5)

Frequency: 829 MHz; Duty Cycle: 1:1

Medium: BSL835; Medium Notes: t= 22.3 C

Medium parameters used: f = 829 MHz; $\sigma = 0.972$ S/m; $\epsilon_r = 53.659$; $\rho = 1000$ kg/m³

Phantom section: Center Section

DASY Configuration:

- Probe: ES3DV3 - SN3194
- ConvF(6.05, 6.05, 6.05); Calibrated: 2013-11-14;
- Sensor-Surface: 3mm (Mechanical Surface Detection), Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn538; Calibrated: 2013-11-19
- Phantom: SAM 3 Triple Phantom 5.1C; Type: QD 000 P51 CA; Serial: TP-1123/3
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

LTE 850 (Band 5)/Body - Low - QPSK - 10MHz - 1Rb - 0% offset - Spacer 10mm - No Headset - Display Facing Phantom/Area Scan (81x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 23.523 V/m

Fast SAR: SAR(1 g) = 0.452 W/kg

Fast SAR(10 g) = 0.312 W/kg

Maximum value of SAR (interpolated) = 0.528 W/kg

LTE 850 (Band 5)/Body - Low - QPSK - 10MHz - 1Rb - 0% offset - Spacer 10mm - No Headset - Display Facing Phantom/Zoom Scan 2 (6x6x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 23.523 V/m


Peak SAR (extrapolated) = 0.766 W/kg

SAR(1 g) = 0.457 W/kg

SAR(10 g) = 0.264 W/kg

Power Drift = 0.02 dB

Maximum value of SAR (measured) = 0.503 W/kg



Plot #33

Date/Time: 2014-08-01 13:47:41

Test Laboratory: TCC Microsoft

Type: RM-985; Serial: 004402/47/815312/9

Communication System: LTE1700/2100 (Band 4)

Frequency: 1745 MHz; Duty Cycle: 1:1

Medium: BSL1800; Medium Notes: t= 21.2 C

Medium parameters used: f = 1745 MHz; $\sigma = 1.446$ S/m; $\epsilon_r = 52.088$; $\rho = 1000$ kg/m³

Phantom section: Center Section

DASY Configuration:

- Probe: EX3DV4 - SN3834
- ConvF(7.35, 7.35, 7.35); Calibrated: 2014-05-08;
- Sensor-Surface: 3mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1355; Calibrated: 2014-05-13
- Phantom: SAM 3 Triple Phantom 5.1C; Type: QD 000 P51 CA; Serial: TP-1124/2 (1800MHz), TP-1123/2 (1900MHz)
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

LTE 1700_2100 (Band 4)/Body - High - QPSK - 20MHz - 1RB - 0% offset - Spacer 10mm - No Headset - Bottom Edge Facing Phantom/Area Scan (41x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 30.108 V/m

Fast SAR: SAR(1 g) = 1.01 W/kg

Fast SAR(10 g) = 0.515 W/kg

Maximum value of SAR (interpolated) = 1.28 W/kg

LTE 1700_2100 (Band 4)/Body - High - QPSK - 20MHz - 1RB - 0% offset - Spacer 10mm - No Headset - Bottom Edge Facing Phantom/Zoom Scan (5x6x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 30.115 V/m


Peak SAR (extrapolated) = 1.71 W/kg

SAR(1 g) = 1.02 W/kg

SAR(10 g) = 0.558 W/kg

Power Drift = -0.01 dB

Maximum value of SAR (measured) = 1.25 W/kg



Plot #34

Date/Time: 2014-08-02 11:12:59

Test Laboratory: TCC Microsoft

Type: RM-985; Serial: 004402/47/815312/9

Communication System: 1-slot GPRS1900

Frequency: 1909.8 MHz; Duty Cycle: 1:8.30042

Medium: BSL1900; Medium Notes: t= 21.0 C

Medium parameters used: f = 1910 MHz; σ = 1.544 S/m; ϵ_r = 52.759; ρ = 1000 kg/m³

Phantom section: Center Section

DASY Configuration:

- Probe: EX3DV4 - SN3834
- ConvF(7.15, 7.15, 7.15); Calibrated: 2014-05-08;
- Sensor-Surface: 3mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1355; Calibrated: 2014-05-13
- Phantom: SAM 3 Triple Phantom 5.1C; Type: QD 000 P51 CA; Serial: TP-1124/2 (1800MHz), TP-1123/2 (1900MHz)
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

1-slot GPRS1900/Body - High - Spacer 10mm - No Headset - Bottom Edge Facing Phantom - Repeated/Area Scan (41x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 28.668 V/m

Fast SAR: SAR(1 g) = 0.988 W/kg

Fast SAR(10 g) = 0.489 W/kg

Maximum value of SAR (interpolated) = 1.31 W/kg

1-slot GPRS1900/Body - High - Spacer 10mm - No Headset - Bottom Edge Facing Phantom - Repeated/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 28.668 V/m


Peak SAR (extrapolated) = 1.69 W/kg

SAR(1 g) = 0.993 W/kg

SAR(10 g) = 0.533 W/kg

Power Drift = -0.04 dB

Maximum value of SAR (measured) = 1.10 W/kg



Plot #35

Date/Time: 2014-08-02 10:26:14

Test Laboratory: TCC Microsoft

Type: RM-985; Serial: 004402/47/815312/9

Communication System: WCDMA1900 (Band 2)

Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium: BSL1900; Medium Notes: t= 21.0 C

Medium parameters used: f = 1908 MHz; $\sigma = 1.542$ S/m; $\epsilon_r = 52.763$; $\rho = 1000$ kg/m³

Phantom section: Center Section

DASY Configuration:

- Probe: EX3DV4 - SN3834
- ConvF(7.15, 7.15, 7.15); Calibrated: 2014-05-08;
- Sensor-Surface: 3mm (Mechanical Surface Detection), Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1355; Calibrated: 2014-05-13
- Phantom: SAM 3 Triple Phantom 5.1C; Type: QD 000 P51 CA; Serial: TP-1124/2 (1800MHz), TP-1123/2 (1900MHz)
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

WCDMA1900 (Band 2)/Body - High - Spacer 10mm - No Headset - Bottom Edge Facing Phantom/Area Scan (41x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 27.563 V/m

Fast SAR: SAR(1 g) = 0.915 W/kg

Fast SAR(10 g) = 0.454 W/kg

Maximum value of SAR (interpolated) = 1.21 W/kg

WCDMA1900 (Band 2)/Body - High - Spacer 10mm - No Headset - Bottom Edge Facing Phantom/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 27.563 V/m


Peak SAR (extrapolated) = 1.59 W/kg

SAR(1 g) = 0.930 W/kg

SAR(10 g) = 0.496 W/kg

Power Drift = -0.02 dB

Maximum value of SAR (measured) = 1.03 W/kg



SAR Report

Appendix B for FCC_RM-985_02

Applicant: Microsoft

Type: RM-985

Copyright © 2014 TCC Microsoft

Plot #36

Date/Time: 2014-08-02 09:51:01

Test Laboratory: TCC Microsoft

Type: RM-985; Serial: 004402/47/815312/9

Communication System: LTE1900 (Band 2)

Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: BSL1900; Medium Notes: t= 21.0 C

Medium parameters used: f = 1900 MHz; $\sigma = 1.533$ S/m; $\epsilon_r = 52.788$; $\rho = 1000$ kg/m³

Phantom section: Center Section

DASY Configuration:

- Probe: EX3DV4 - SN3834
- ConvF(7.15, 7.15, 7.15); Calibrated: 2014-05-08;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1355; Calibrated: 2014-05-13
- Phantom: SAM 3 Triple Phantom 5.1C; Type: QD 000 P51 CA; Serial: TP-1124/2 (1800MHz), TP-1123/2 (1900MHz)
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

LTE 1900 (Band 2)/Body - High - QPSK - 20MHz - 1RB - 100% offset - Spacer 10mm - No Headset - Bottom Edge Facing Phantom/Area Scan (41x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 27.434 V/m

Fast SAR: SAR(1 g) = 0.897 W/kg

Fast SAR(10 g) = 0.445 W/kg

Maximum value of SAR (interpolated) = 1.19 W/kg

LTE 1900 (Band 2)/Body - High - QPSK - 20MHz - 1RB - 100% offset - Spacer 10mm - No Headset - Bottom Edge Facing Phantom/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 27.434 V/m


Peak SAR (extrapolated) = 1.54 W/kg

SAR(1 g) = 0.910 W/kg

SAR(10 g) = 0.486 W/kg

Power Drift = -0.03 dB

Maximum value of SAR (measured) = 1.12 W/kg



Plot #37

Date/Time: 2014-08-01 09:19:28

Test Laboratory: TCC Microsoft

Type: RM-985; Serial: 004402/47/815312/9

Communication System: LTE2500 (Band 7)

Frequency: 2511.7 MHz; Duty Cycle: 1:1

Medium: BSL2600; Medium Notes: t= 21 C

Medium parameters used: f = 2512 MHz; σ = 2.009 S/m; ϵ_r = 50.991; ρ = 1000 kg/m³

Phantom section: Center Section

DASY Configuration:

- Probe: EX3DV4 - SN3960
- ConvF(7.14, 7.14, 7.14); Calibrated: 2013-12-10;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1302; Calibrated: 2013-11-08
- Phantom: #2 Triple, SAR4; Type: QD 000 P51 CA; Serial: TP-1123/1 (750 MHz), TP-1124/1 (2450 MHz)
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

LTE2500 (Band 7)/Body - Sub 1 - Scenario 1 - QPSK - 20MHz - 1RB - 100% offset - Spacer 10mm - No Headset - Back Facing Phantom/Area Scan (121x181x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm


Reference Value = 11.769 V/m

Fast SAR: SAR(1 g) = 0.251 W/kg

Fast

AR(10 g) = 0.133 W/kg

Maximum value of SAR (interpolated) = 0.317 W/kg



Plot #38

Date/Time: 2014-08-04 09:05:48

Test Laboratory: TCC Microsoft

Type: RM-985; Serial: 004402/47/815312/9

Communication System: LTE2500 (Band 7)

Frequency: 2511.7 MHz; Duty Cycle: 1:1

Medium: BSL2600; Medium Notes: t= 20.9 C

Medium parameters used: f = 2512 MHz; σ = 2.017 S/m; ϵ_r = 50.831; ρ = 1000 kg/m³

Phantom section: Center Section

DASY Configuration:

- Probe: EX3DV4 - SN3960
- ConvF(7.14, 7.14, 7.14); Calibrated: 2013-12-10;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1302; Calibrated: 2013-11-08
- Phantom: #2 Triple, SAR4; Type: QD 000 P51 CA; Serial: TP-1123/1 (750 MHz), TP-1124/1 (2450 MHz)
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

LTE2500 (Band 7)/Body - Sub 1 - Scenario 2 - QPSK - 20MHz - 1RB - 100% offset - Spacer 10mm - No Headset - Display Facing Phantom/Area Scan (121x181x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Reference Value = 13.862 V/m

Fast SAR: SAR(1 g) = 0.324 W/kg

Fast SAR(10 g) = 0.164 W/kg

Maximum value of SAR (interpolated) = 0.416 W/kg

LTE2500 (Band 7)/Body - Sub 1 - Scenario 2 - QPSK - 20MHz - 1RB - 100% offset - Spacer 10mm - No Headset - Display Facing Phantom/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 13.830 V/m


Peak SAR (extrapolated) = 0.613 W/kg

SAR(1 g) = 0.330 W/kg

SAR(10 g) = 0.172 W/kg

Power Drift = 0.04 dB

Maximum value of SAR (measured) = 0.414 W/kg



Plot #39

Date/Time: 2014-08-01 11:59:40

Test Laboratory: TCC Microsoft

Type: RM-985; Serial: 004402/47/815312/9

Communication System: LTE2500 (Band 7)

Frequency: 2511.7 MHz; Duty Cycle: 1:1

Medium: BSL2600; Medium Notes: t= 21 C

Medium parameters used: f = 2512 MHz; σ = 2.009 S/m; ϵ_r = 50.991; ρ = 1000 kg/m³

Phantom section: Center Section

DASY Configuration:

- Probe: EX3DV4 - SN3960
- ConvF(7.14, 7.14, 7.14); Calibrated: 2013-12-10;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1302; Calibrated: 2013-11-08
- Phantom: #2 Triple, SAR4; Type: QD 000 P51 CA; Serial: TP-1123/1 (750 MHz), TP-1124/1 (2450 MHz)
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

LTE2500 (Band 7)/Body - Sub 1 - Scenario 0 - QPSK - 20MHz - 1RB - 100% offset - Spacer 10mm - No Headset - Bottom Edge Facing Phantom/Area Scan (61x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Reference Value = 19.669 V/m

Fast SAR: SAR(1 g) = 0.987 W/kg

Fast SAR(10 g) = 0.471 W/kg

Maximum value of SAR (interpolated) = 1.29 W/kg

LTE2500 (Band 7)/Body - Sub 1 - Scenario 0 - QPSK - 20MHz - 1RB - 100% offset - Spacer 10mm - No Headset - Bottom Edge Facing Phantom/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 19.752 V/m


Peak SAR (extrapolated) = 1.90 W/kg

SAR(1 g) = 0.985 W/kg

SAR(10 g) = 0.481 W/kg

Power Drift = 0.07 dB

Maximum value of SAR (measured) = 1.27 W/kg



Plot #40

Date/Time: 2014-08-01 10:02:24

Test Laboratory: TCC Microsoft

Type: RM-985; Serial: 004402/47/815312/9

Communication System: LTE2500 (Band 7)

Frequency: 2511.7 MHz; Duty Cycle: 1:1

Medium: BSL2600; Medium Notes: t= 21 C

Medium parameters used: f = 2512 MHz; σ = 2.009 S/m; ϵ_r = 50.991; ρ = 1000 kg/m³

Phantom section: Center Section

DASY Configuration:

- Probe: EX3DV4 - SN3960
- ConvF(7.14, 7.14, 7.14); Calibrated: 2013-12-10;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1302; Calibrated: 2013-11-08
- Phantom: #2 Triple, SAR4; Type: QD 000 P51 CA; Serial: TP-1123/1 (750 MHz), TP-1124/1 (2450 MHz)
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

LTE2500 (Band 7)/Body - Sub 1 - Scenario 1 - QPSK - 20MHz - 1RB - 100% offset - Spacer 10mm - No Headset - Left Edge Facing Phantom/Area Scan (61x181x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm


Reference Value = 5.931 V/m

Fast SAR: SAR(1 g) = 0.057 W/kg

Fast

AR(10 g) = 0.030 W/kg

Maximum value of SAR (interpolated) = 0.0739 W/kg



Plot #41

Date/Time: 2014-08-01 10:27:18

Test Laboratory: TCC Microsoft

Type: RM-985; Serial: 004402/47/815312/9

Communication System: LTE2500 (Band 7)

Frequency: 2535 MHz; Duty Cycle: 1:1

Medium: BSL2600; Medium Notes: t= 21 C

Medium parameters used: f = 2535 MHz; $\sigma = 2.036$ S/m; $\epsilon_r = 50.918$; $\rho = 1000$ kg/m³

Phantom section: Center Section

DASY Configuration:

- Probe: EX3DV4 - SN3960
- ConvF(7.14, 7.14, 7.14); Calibrated: 2013-12-10;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1302; Calibrated: 2013-11-08
- Phantom: #2 Triple, SAR4; Type: QD 000 P51 CA; Serial: TP-1123/1 (750 MHz), TP-1124/1 (2450 MHz)
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

LTE2500 (Band 7)/Body - Sub 2 - Scenario 2 - QPSK - 20MHz - 1RB - 100% offset - Spacer 10mm - No Headset - Right Edge Facing Phantom/Area Scan (61x181x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm


Reference Value = 8.277 V/m

Fast SAR: SAR(1 g) = 0.122 W/kg

Fast

AR(10 g) = 0.051 W/kg

Maximum value of SAR (interpolated) = 0.179 W/kg



Plot #42

Date/Time: 2014-08-07 11:31:03

Test Laboratory: TCC Microsoft

Type: RM-985; Serial: 004402/47/815308/7

Communication System: WLAN2450

Frequency: 2417 MHz; Duty Cycle: 1:1

Medium: BSL2450; Medium Notes: t= 21.4 C

Medium parameters used: f = 2417 MHz; σ = 1.901 S/m; ϵ_r = 51.559; ρ = 1000 kg/m³

Phantom section: Center Section

DASY Configuration:

- Probe: EX3DV4 - SN3960
- ConvF(7.44, 7.44, 7.44); Calibrated: 2013-12-10;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1302; Calibrated: 2013-11-08
- Phantom: #2 Triple, SAR4; Type: QD 000 P51 CA; Serial: TP-1123/1 (750 MHz), TP-1124/1 (2450 MHz)
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.9 (7117)

WLAN2450 b-mode/Body - Channel 2 - QPSK 5.5 Mbps - Spacer 10mm - No Headset - Back Facing

Phantom/Area Scan (121x181x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Reference Value = 11.969 V/m

Fast SAR: SAR(1 g) = 0.306 W/kg

Fast SAR(10 g) = 0.139 W/kg

Maximum value of SAR (interpolated) = 0.411 W/kg

WLAN2450 b-mode/Body - Channel 2 - QPSK 5.5 Mbps - Spacer 10mm - No Headset - Back Facing

Phantom/Zoom Scan (7x8x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.969 V/m


Peak SAR (extrapolated) = 0.665 W/kg

SAR(1 g) = 0.317 W/kg

SAR(10 g) = 0.151 W/kg

Power Drift = 0.01 dB

Maximum value of SAR (measured) = 0.419 W/kg



SAR Report

Appendix B for FCC_RM-985_02

Applicant: Microsoft

Type: RM-985

Copyright © 2014 TCC Microsoft

APPENDIX C: DIELECTRIC PARAMETERS OF THE TISSUE SIMULANTS

Head tissue simulant dielectric parameters used in the measurements:

LTE17 f (MHz)	Date	Dielectric Parameters					
		Ch 23780 709.0 MHz		Ch 23790 710.0 MHz		Ch 23800 711.0 MHz	
		ϵ_r	σ [S/m]	ϵ_r	σ [S/m]	ϵ_r	σ [S/m]
710	2014-08-06	40.9	0.86	40.9	0.87	40.9	0.87
WCDMA5 f (MHz)	Date	Dielectric Parameters					
		Ch 4147 829.4 MHz		Ch 4183 836.6 MHz		Ch 4219 843.8 MHz	
		ϵ_r	σ [S/m]	ϵ_r	σ [S/m]	ϵ_r	σ [S/m]
837	2014-08-02	40.1	0.90	40.1	0.90	40.0	0.91
	2014-08-06	40.3	0.90	40.3	0.91	40.2	0.91
GPRS850 f (MHz)	Date	Dielectric Parameters					
		Ch 148 828.2 MHz		Ch 189 836.4 MHz		Ch 231 844.8 MHz	
		ϵ_r	σ [S/m]	ϵ_r	σ [S/m]	ϵ_r	σ [S/m]
836	2014-08-02	40.1	0.90	40.1	0.90	40.0	0.91
	2014-08-06	40.3	0.90	40.2	0.91	40.2	0.92
LTE5 f (MHz)	Date	Dielectric Parameters					
		Ch 20450 829.0 MHz		Ch 20525 836.5 MHz		Ch 20600 844.0 MHz	
		ϵ_r	σ [S/m]	ϵ_r	σ [S/m]	ϵ_r	σ [S/m]
837	2014-08-04	40.7	0.91	40.6	0.91	40.6	0.92
	2014-08-06	40.3	0.90	40.2	0.91	40.2	0.91
LTE4 f (MHz)	Date	Dielectric Parameters					
		Ch 20050 1720.0 MHz		Ch 20175 1732.5 MHz		Ch 20300 1745.0 MHz	
		ϵ_r	σ [S/m]	ϵ_r	σ [S/m]	ϵ_r	σ [S/m]
1732	2014-07-31	38.4	1.30	38.3	1.31	38.3	1.32

(Head tissue simulant table continues)

(Head tissue simulant table continues)

GPRS1900 f (MHz)	Date	Dielectric Parameters					
		Ch 512 1850.2 MHz		Ch 661 1880.0 MHz		Ch 810 1909.8 MHz	
		ϵ_r	σ [S/m]	ϵ_r	σ [S/m]	ϵ_r	σ [S/m]
1900	2014-07-29	39.3	1.33	39.3	1.36	39.2	1.38
WCDMA2 f (MHz)	Date	Dielectric Parameters					
		Ch 9262 1852.4 MHz		Ch 9400 1880.0 MHz		Ch 9538 1907.6 MHz	
		ϵ_r	σ [S/m]	ϵ_r	σ [S/m]	ϵ_r	σ [S/m]
1900	2014-07-29	39.3	1.33	39.3	1.36	39.2	1.38
LTE2 f (MHz)	Date	Dielectric Parameters					
		Ch 18700 1860.0 MHz		Ch 18900 1880.0 MHz		Ch 19100 1900.0 MHz	
		ϵ_r	σ [S/m]	ϵ_r	σ [S/m]	ϵ_r	σ [S/m]
1900	2014-07-29	39.3	1.34	39.3	1.36	39.2	1.38
	2014-07-31	39.2	1.33	39.1	1.35	39.0	1.37
WLAN2450 f (MHz)	Date	Dielectric Parameters					
		Ch 1 2412.0 MHz		Ch 6 2437.0 MHz		Ch 11 2462.0 MHz	
		ϵ_r	σ [S/m]	ϵ_r	σ [S/m]	ϵ_r	σ [S/m]
2437	2014-07-25	38.4	1.71	38.3	1.73	38.2	1.76
	2014-07-28	39.0	1.75	38.9	1.78	38.8	1.80
LTE7 f (MHz)	Date	Dielectric Parameters					
		Ch 20867 2511.7 MHz		Ch 21100 2535.0 MHz		Ch 21333 2558.3 MHz	
		ϵ_r	σ [S/m]	ϵ_r	σ [S/m]	ϵ_r	σ [S/m]
2535	2014-08-04	38.0	1.87	38.0	1.89	37.9	1.92
	2014-08-05	38.9	1.86	38.9	1.89	38.8	1.92

Head tissue simulant dielectric parameters used in the measurements 5200 – 5825 MHz:

f (MHz)	Date	Dielectric Parameters					
		Ch 104 5520.0 MHz		Ch 124 5620.0 MHz		Ch 136 5680.0 MHz	
		ϵ_r	σ [S/m]	ϵ_r	σ [S/m]	ϵ_r	σ [S/m]
5520 5620	2014-07-30	35.7	4.86	35.5	4.96	35.5	5.03
f (MHz)	Date	Dielectric Parameters					
		Ch 151 5760.0 MHz		Ch 153 5765.0 MHz			
		ϵ_r	σ [S/m]	ϵ_r	σ [S/m]		
5760	2014-07-31	34.8	5.05	34.8	5.05		

Body tissue simulant dielectric parameters used in the measurements:

LTE17 f (MHz)	Date	Dielectric Parameters					
		Ch 23780 709.0 MHz		Ch 23790 710.0 MHz		Ch 23800 711.0 MHz	
		ϵ_r	σ [S/m]	ϵ_r	σ [S/m]	ϵ_r	σ [S/m]
710	2014-08-06	53.5	0.97	53.5	0.97	53.5	0.97
WCDMA5 f (MHz)	Date	Dielectric Parameters					
		Ch 4147 829.4 MHz		Ch 4183 836.6 MHz		Ch 4219 843.8 MHz	
		ϵ_r	σ [S/m]	ϵ_r	σ [S/m]	ϵ_r	σ [S/m]
837	2014-07-31	53.4	0.98	53.3	0.98	53.3	0.99
	2014-08-03	53.1	0.97	53.1	0.98	53.1	0.98
	2014-08-05	53.7	0.97	53.6	0.97	53.6	0.98
GPRS850 f (MHz)	Date	Dielectric Parameters					
		Ch 148 828.2 MHz		Ch 189 836.4 MHz		Ch 231 844.8 MHz	
		ϵ_r	σ [S/m]	ϵ_r	σ [S/m]	ϵ_r	σ [S/m]
836	2014-07-30	53.4	0.97	53.4	0.98	53.3	0.98
	2014-07-31	53.4	0.98	53.3	0.98	53.3	0.99
	2014-08-05	53.7	0.97	53.6	0.98	53.6	0.98
	2014-09-17	54.2	0.97	54.2	0.98	54.1	0.98
LTE5 f (MHz)	Date	Dielectric Parameters					
		Ch 20450 829.0 MHz		Ch 20525 836.5 MHz		Ch 20600 844.0 MHz	
		ϵ_r	σ [S/m]	ϵ_r	σ [S/m]	ϵ_r	σ [S/m]
837	2014-08-04	53.7	0.97	53.7	0.98	53.7	0.98
	2014-08-05	53.7	0.97	53.6	0.98	53.6	0.98
	2014-08-08	53.5	0.98	53.5	0.98	53.5	0.99
LTE4 f (MHz)	Date	Dielectric Parameters					
		Ch 20050 1720.0 MHz		Ch 20175 1732.5 MHz		Ch 20300 1745.0 MHz	
		ϵ_r	σ [S/m]	ϵ_r	σ [S/m]	ϵ_r	σ [S/m]
1732	2014-08-01	52.2	1.42	52.1	1.43	52.1	1.44
	2014-08-05	52.3	1.43	52.2	1.44	52.2	1.46

(Body tissue simulant table continues)

(Body tissue simulant table continues)

GPRS1900 f (MHz)	Date	Dielectric Parameters					
		Ch 512 1850.2 MHz		Ch 661 1880.0 MHz		Ch 810 1909.8 MHz	
		ϵ_r	σ [S/m]	ϵ_r	σ [S/m]	ϵ_r	σ [S/m]
1900	2014-07-28	51.6	1.46	51.5	1.49	51.5	1.52
	2014-08-02	52.9	1.49	52.8	1.51	52.8	1.54
WCDMA2 f (MHz)	Date	Dielectric Parameters					
		Ch 9262 1852.4 MHz		Ch 9400 1880.0 MHz		Ch 9538 1907.6 MHz	
		ϵ_r	σ [S/m]	ϵ_r	σ [S/m]	ϵ_r	σ [S/m]
1900	2014-07-28	53.3	1.48	53.2	1.51	53.2	1.53
	2014-08-02	52.9	1.49	52.8	1.51	52.8	1.54
LTE2 f (MHz)	Date	Dielectric Parameters					
		Ch 18700 1860.0 MHz		Ch 18900 1880.0 MHz		Ch 19100 1900.0 MHz	
		ϵ_r	σ [S/m]	ϵ_r	σ [S/m]	ϵ_r	σ [S/m]
1900	2014-07-29	53.1	1.49	53.0	1.50	53.0	1.52
	2014-08-02	52.9	1.49	52.8	1.51	52.8	1.53
WLAN f (MHz)	Date	Dielectric Parameters					
		Ch 1 2412.0 MHz		Ch 6 2437.0 MHz		Ch 11 2462.0 MHz	
		ϵ_r	σ [S/m]	ϵ_r	σ [S/m]	ϵ_r	σ [S/m]
2437	2014-07-29	51.1	1.87	51.0	1.90	51.0	1.93
	2014-08-07	51.6	1.89	51.5	1.92	51.4	1.95
LTE7 f (MHz)	Date	Dielectric Parameters					
		Ch 20867 2511.7 MHz		Ch 21100 2535.0 MHz		Ch 21333 2558.3 MHz	
		ϵ_r	σ [S/m]	ϵ_r	σ [S/m]	ϵ_r	σ [S/m]
2535	2014-07-31	50.6	2.01	50.5	2.04	50.4	2.07
	2014-08-01	51.0	2.01	50.9	2.03	50.8	2.06
	2014-08-04	50.8	2.02	50.8	2.04	50.7	2.07

Body tissue simulant dielectric parameters used in the measurements 5200 – 5825 MHz:

f (MHz)	Date	Dielectric Parameters					
		Ch 40 5200.0 MHz		Ch 44 5210.0 MHz			
		ϵ_r	σ [S/m]	ϵ_r	σ [S/m]		
5210	2014-07-31	47.7	5.32	47.7	5.34		
f (MHz)	Date	Dielectric Parameters					
		Ch 104 5520.0 MHz		Ch 124 5620.0 MHz		Ch 136 5680.0 MHz	
		ϵ_r	σ [S/m]	ϵ_r	σ [S/m]	ϵ_r	σ [S/m]
5520 5620	2014-08-01	47.1	5.73	46.9	5.86	46.9	5.94
f (MHz)	Date	Dielectric Parameters					
		Ch 151 5760.0 MHz		Ch 153 5765.0 MHz			
		ϵ_r	σ [S/m]	ϵ_r	σ [S/m]		
5760	2014-07-31	46.8	6.07	46.8	6.07		

APPENDIX D: CONDUCTED AVERAGE POWER MEASUREMENTS FOR WCDMA AND HSUPA

D.1. WCDMA850 (Band 5) Test results

Type: RM-985; Serial: 004402/47/815344/2, HW: 0200, SW: 02030.00000.14271.24000

Average power

Ch / f(MHz)	P [dBm]
4147	23.1
4183	23.0
4219	23.1

D.2. HSUPA850 (Band 5) Test results

Average power

Ch / f (MHz)	P [dBm]				
	Subtest mode 1	Subtest mode 2	Subtest mode 3	Subtest mode 4	Subtest mode 5
4147	22.1	21.2	20.7	21.7	22.2
4183	21.5	21.1	20.2	21.7	22.0
4219	21.5	21.2	20.6	21.6	22.1

Note: In HSUPA operation, the output power is reduced relative to the tuning target power for WCDMA. This device runs MPR power control routines for HSUPA. As a result, the MPR for each of the Subtest modes is as follows:

Maximum Power Reduction (MPR)				
Subtest mode 1	Subtest mode 2	Subtest mode 3	Subtest mode 4	Subtest mode 5
1.5dB	2.0dB	1.0dB	2.0dB	0.0dB

D.3. WCDMA1900 (Band 2) Test results

Type: RM-985; Serial: 004402/47/815349/1, HW: 0200, SW: 02030.00000.14271.24000

Average power

Ch / f(MHz)	P [dBm]
9262	23.2
9400	23.3
9538	23.4

D.4. HSUPA1900 Test results

Average power

Ch / f (MHz)	P [dBm]				
	Subtest mode 1	Subtest mode 2	Subtest mode 3	Subtest mode 4	Subtest mode 5
9262	21.5	21.2	21.0	21.7	22.2
9400	21.6	21.5	21.0	21.9	22.3
9538	22.3	21.1	21.2	21.8	22.4

Note: In HSUPA operation, the output power is reduced relative to the tuning target power for WCDMA. This device runs MPR power control routines for HSUPA. As a result, the MPR for each of the Subtest modes is as follows:

Maximum Power Reduction (MPR)				
Subtest mode 1	Subtest mode 2	Subtest mode 3	Subtest mode 4	Subtest mode 5
1.5dB	2.0dB	1.0dB	2.0dB	0.0dB

APPENDIX E: RELEVANT PAGES FROM PROBE CALIBRATION REPORTS



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Client **Nokia Salo TCC**

Certificate No: **ES3-3194_Nov13**

CALIBRATION CERTIFICATE

Object **ES3DV3 - SN:3194**

Calibration procedure(s) **QA CAL-01.v9, QA CAL-23.v5, QA CAL-25.v6
Calibration procedure for dosimetric E-field probes**

Calibration date: **November 14, 2013**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	04-Apr-13 (No. 217-01733)	Apr-14
Power sensor E4412A	MY41498087	04-Apr-13 (No. 217-01733)	Apr-14
Reference 3 dB Attenuator	SN: S5054 (3c)	04-Apr-13 (No. 217-01737)	Apr-14
Reference 20 dB Attenuator	SN: S5277 (20x)	04-Apr-13 (No. 217-01735)	Apr-14
Reference 30 dB Attenuator	SN: S5129 (30b)	04-Apr-13 (No. 217-01738)	Apr-14
Reference Probe ES3DV2	SN: 3013	28-Dec-12 (No. ES3-3013_Dec12)	Dec-13
DAE4	SN: 660	4-Sep-13 (No. DAE4-660_Sep13)	Sep-14
Secondary Standards	ID	Check Date (in house)	Scheduled Check
RF generator HP 8648C	US3642U01700	4-Aug-99 (in house check Apr-13)	In house check: Apr-15
Network Analyzer HP 8753E	US37390585	18-Oct-01 (in house check Oct-13)	In house check: Oct-14

	Name	Function	Signature
Calibrated by:	Israe El-Naouq	Laboratory Technician	
Approved by:	Katja Pokovic	Technical Manager	
Issued: November 15, 2013			
This calibration certificate shall not be reproduced except in full without written approval of the laboratory.			

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3194

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unct. (k=2)
835	41.5	0.90	6.12	6.12	6.12	0.28	2.07	± 12.0 %

^C Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2); else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3194

Calibration Parameter Determined in Body Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Uncl. (k=2)
835	55.2	0.97	6.05	6.05	6.05	0.69	1.30	± 12.0 %

^C Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Client **Nokia Salo TCC**

Certificate No: **EX3-3834_May14**

CALIBRATION CERTIFICATE

Object **EX3DV4 - SN:3834**

Calibration procedure(s) **QA CAL-01.v9, QA CAL-23.v5, QA CAL-25.v6
Calibration procedure for dosimetric E-field probes**

Calibration date: **May 8, 2014**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	03-Apr-14 (No. 217-01911)	Jan-15
Power sensor E4412A	MY41498087	03-Apr-14 (No. 217-01911)	Jan-15
Reference 3 dB Attenuator	SN: S5054 (3c)	03-Apr-14 (No. 217-01915)	Jan-15
Reference 20 dB Attenuator	SN: S5277 (20x)	03-Apr-14 (No. 217-01919)	Jan-15
Reference 30 dB Attenuator	SN: S5129 (30b)	03-Apr-14 (No. 217-01920)	Jan-15
Reference Probe ES3DV2	SN: 3013	30-Dec-13 (No. ES3-3013_Dec13)	Dec-14
DAE4	SN: 660	13-Dec-13 (No. DAE4-660_Dec13)	Dec-14
Secondary Standards	ID	Check Date (in house)	Scheduled Check
RF generator HP 8648C	US3642U01700	4-Aug-99 (in house check Apr-13)	In house check: Apr-16
Network Analyzer HP 8753E	US37390585	18-Oct-01 (in house check Oct-13)	In house check: Oct-14

	Name	Function	Signature
Calibrated by:	Israe El-Naouq	Laboratory Technician	
Approved by:	Katja Pokovic	Technical Manager	
Issued: May 12, 2014			
This calibration certificate shall not be reproduced except in full without written approval of the laboratory.			

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3834

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unct. (k=2)
1750	40.1	1.37	7.62	7.62	7.62	0.80	0.59	± 12.0 %
1900	40.0	1.40	7.33	7.33	7.33	0.63	0.66	± 12.0 %

^C Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3834

Calibration Parameter Determined in Body Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unct. (k=2)
1750	53.4	1.49	7.35	7.35	7.35	0.77	0.63	± 12.0 %
1900	53.3	1.52	7.15	7.15	7.15	0.45	0.81	± 12.0 %

^C Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Client **Nokia Salo TCC**

Certificate No: **EX3-3892_Nov13**

CALIBRATION CERTIFICATE

Object **EX3DV4 - SN:3892**

Calibration procedure(s) **QA CAL-01.v9, QA CAL-14.v4, QA CAL-23.v5, QA CAL-25.v6**
Calibration procedure for dosimetric E-field probes

Calibration date: **November 15, 2013**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^{\circ}\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	04-Apr-13 (No. 217-01733)	Apr-14
Power sensor E4412A	MY41498087	04-Apr-13 (No. 217-01733)	Apr-14
Reference 3 dB Attenuator	SN: S5054 (3c)	04-Apr-13 (No. 217-01737)	Apr-14
Reference 20 dB Attenuator	SN: S5277 (20x)	04-Apr-13 (No. 217-01735)	Apr-14
Reference 30 dB Attenuator	SN: S5129 (30b)	04-Apr-13 (No. 217-01738)	Apr-14
Reference Probe ES3DV2	SN: 3013	28-Dec-12 (No. ES3-3013_Dec12)	Dec-13
DAE4	SN: 660	4-Sep-13 (No. DAE4-660_Sep13)	Sep-14
Secondary Standards	ID	Check Date (in house)	Scheduled Check
RF generator HP 8648C	US3642U01700	4-Aug-99 (in house check Apr-13)	In house check: Apr-15
Network Analyzer HP 8753E	US37390585	18-Oct-01 (in house check Oct-13)	In house check: Oct-14

	Name	Function	Signature
Calibrated by:	Claudio Leubler	Laboratory Technician	
Approved by:	Katja Pokovic	Technical Manager	
Issued: November 16, 2013			
This calibration certificate shall not be reproduced except in full without written approval of the laboratory.			

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3892

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unct. (k=2)
750	41.9	0.89	10.15	10.15	10.15	0.80	0.61	± 12.0 %
835	41.5	0.90	9.75	9.75	9.75	0.37	0.88	± 12.0 %
1750	40.1	1.37	8.43	8.43	8.43	0.49	0.82	± 12.0 %
1900	40.0	1.40	8.18	8.18	8.18	0.48	0.84	± 12.0 %
2450	39.2	1.80	7.40	7.40	7.40	0.43	0.87	± 12.0 %
2600	39.0	1.96	7.23	7.23	7.23	0.39	0.95	± 12.0 %
5200	36.0	4.66	5.29	5.29	5.29	0.35	1.80	± 13.1 %
5300	35.9	4.76	4.96	4.96	4.96	0.35	1.80	± 13.1 %
5500	35.6	4.96	4.84	4.84	4.84	0.35	1.80	± 13.1 %
5600	35.5	5.07	4.66	4.66	4.66	0.35	1.80	± 13.1 %
5800	35.3	5.27	4.60	4.60	4.60	0.40	1.80	± 13.1 %

^C Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3892

Calibration Parameter Determined in Body Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unct, (k=2)
750	55.5	0.96	9.74	9.74	9.74	0.32	0.99	± 12.0 %
835	55.2	0.97	9.65	9.65	9.65	0.45	0.87	± 12.0 %
1750	53.4	1.49	7.86	7.86	7.86	0.39	0.87	± 12.0 %
1900	53.3	1.52	7.69	7.69	7.69	0.42	0.84	± 12.0 %
2450	52.7	1.95	7.27	7.27	7.27	0.75	0.56	± 12.0 %
2600	52.5	2.16	7.13	7.13	7.13	0.70	0.50	± 12.0 %
5200	49.0	5.30	4.34	4.34	4.34	0.45	1.90	± 13.1 %
5300	48.9	5.42	4.15	4.15	4.15	0.45	1.90	± 13.1 %
5500	48.6	5.65	4.12	4.12	4.12	0.45	1.90	± 13.1 %
5600	48.5	5.77	4.00	4.00	4.00	0.40	1.90	± 13.1 %
5800	48.2	6.00	4.02	4.02	4.02	0.50	1.90	± 13.1 %

^C Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Client **Nokia Salo TCC**

Certificate No: **EX3-3960_Dec13**

CALIBRATION CERTIFICATE

Object **EX3DV4 - SN:3960**

Calibration procedure(s) **QA CAL-01.v9, QA CAL-14.v4, QA CAL-23.v5, QA CAL-25.v6
Calibration procedure for dosimetric E-field probes**

Calibration date: **December 10, 2013**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^{\circ}\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	04-Apr-13 (No. 217-01733)	Apr-14
Power sensor E4412A	MY41498087	04-Apr-13 (No. 217-01733)	Apr-14
Reference 3 dB Attenuator	SN: S5054 (3c)	04-Apr-13 (No. 217-01737)	Apr-14
Reference 20 dB Attenuator	SN: S5277 (20x)	04-Apr-13 (No. 217-01735)	Apr-14
Reference 30 dB Attenuator	SN: S5129 (30b)	04-Apr-13 (No. 217-01738)	Apr-14
Reference Probe ES3DV2	SN: 3013	28-Dec-12 (No. ES3-3013_Dec12)	Dec-13
DAE4	SN: 660	4-Sep-13 (No. DAE4-660_Sep13)	Sep-14
Secondary Standards	ID	Check Date (in house)	Scheduled Check
RF generator HP 8648C	US3642U01700	4-Aug-99 (in house check Apr-13)	In house check: Apr-15
Network Analyzer HP 8753E	US37390585	18-Oct-01 (in house check Oct-13)	In house check: Oct-14

Calibrated by: **Name** **Function**
Claudio Leubler **Laboratory Technician**

Signature

Approved by: **Katja Pokovic** **Technical Manager**

Issued: December 11, 2013

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3960

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unct. (k=2)
750	41.9	0.89	10.78	10.78	10.78	0.47	0.86	± 12.0 %
835	41.5	0.90	10.45	10.45	10.45	0.41	0.86	± 12.0 %
1750	40.1	1.37	8.49	8.49	8.49	0.57	0.67	± 12.0 %
1900	40.0	1.40	8.23	8.23	8.23	0.62	0.64	± 12.0 %
2450	39.2	1.80	7.39	7.39	7.39	0.38	0.83	± 12.0 %
2600	39.0	1.96	7.33	7.33	7.33	0.39	0.84	± 12.0 %
5200	36.0	4.66	5.27	5.27	5.27	0.35	1.80	± 13.1 %
5300	35.9	4.76	5.07	5.07	5.07	0.35	1.80	± 13.1 %
5500	35.6	4.96	4.99	4.99	4.99	0.35	1.80	± 13.1 %
5600	35.5	5.07	4.80	4.80	4.80	0.35	1.80	± 13.1 %
5800	35.3	5.27	4.80	4.80	4.80	0.40	1.80	± 13.1 %

^C Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3960

Calibration Parameter Determined in Body Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unct. (k=2)
750	55.5	0.96	10.24	10.24	10.24	0.43	0.86	± 12.0 %
835	55.2	0.97	10.08	10.08	10.08	0.34	1.00	± 12.0 %
1750	53.4	1.49	8.33	8.33	8.33	0.52	0.72	± 12.0 %
1900	53.3	1.52	7.88	7.88	7.88	0.62	0.64	± 12.0 %
2450	52.7	1.95	7.44	7.44	7.44	0.62	0.50	± 12.0 %
2600	52.5	2.16	7.14	7.14	7.14	0.59	0.50	± 12.0 %
5200	49.0	5.30	4.60	4.60	4.60	0.45	1.90	± 13.1 %
5300	48.9	5.42	4.33	4.33	4.33	0.50	1.90	± 13.1 %
5500	48.6	5.65	4.12	4.12	4.12	0.50	1.90	± 13.1 %
5600	48.5	5.77	3.97	3.97	3.97	0.50	1.90	± 13.1 %
5800	48.2	6.00	4.14	4.14	4.14	0.55	1.90	± 13.1 %

^C Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.