

ETS Dr.GenZ Taiwan PS Co., LTD

FCC Registration No.: 930600

Industry Canada filed test laboratory Reg. No. IC 5679

Accredited Testing Laboratory



A2LA Cert.No.: 2300.01

PCTRB Accredited Type Certification Test House

FCC

TEST - REPORT

FCC RULES PART 15 / SUBPART C

FCC ID: QQGBU-2084-J

Test report no.: W6M20604-6807-P-15

TABLE OF CONTENTS

1	GENERAL INFORMATION	3
1.1	Notes	3
1.2	Testing laboratory	4
1.2.1	Location	4
1.2.2	Details of accreditation status	4
1.3	Details of approval holder.....	4
1.4	Application details	5
1.5	General information of Test item.....	5
1.6	Test standards.....	6
2	TECHNICAL TEST	7
2.1	Summary of test results.....	7
2.2	Test environment.....	7
2.3	Test Equipment List.....	8
3	TEST RESULTS (ENCLOSURE)	13
3.1	Peak Output Power (transmitter).....	14
3.2	Equivalent isotropic radiated power	16
3.2.1	Transmitter.....	16
3.3	RF Exposure Compliance Requirements	16
3.4	Out of Band Radiated Emissions	16
3.5	Transmitter Radiated Emissions in restricted Bands	17
3.6	Spurious emissions (tx).....	18
3.7	Carrier Frequency Separation	21
3.8	Number of Hopping Frequencies.....	22
3.8.1	Pseudorandom Frequency Hopping Sequence	22
3.8.2	Coordination of hopping sequences to other transmitters.....	22
3.8.3	System Receiver Hopping Capability.....	22
3.9	Time of Occupancy (Dwell Time).....	23
3.10	20dB Bandwidth	24
3.10.1	System Receiver Input Bandwidth.....	25
3.11	Band-edge Compliance of RF Emissions	25
3.12	Radiated Emissions from Receiver Section of Transceiver.....	27
3.13	Power Line Conducted Emission.....	30
	APPENDIX.....	32
	Appendix A	33
	Appendix B	34
	Appendix C	35
	Appendix D	36
	Appendix E	37
	Appendix F.....	38
	Appendix G.....	39
	Appendix H.....	40
	Appendix I.....	41
	Appendix J	42

Registration number: W6M20604-6807-P-15

FCC ID : QQGBU-2084-J

1 General Information**1.1 Notes**

The purpose of conformity testing is to increase the probability of adherence to the essential requirements or conformity specifications, as appropriate.

The complexity of the technical specifications, however, means that full and thorough testing is impractical for both technical and economic reasons.

Furthermore, there is no guarantee that a test sample which has Passed all the relevant tests conforms to a specification.

Neither is there any guarantee that such a test sample will interwork with other genuinely open systems.

The existence of the tests nevertheless provides the confidence that the test sample possesses the qualities as maintained and that its performance generally conforms to representative cases of communications equipment.

The test results of this test report relate exclusively to the item tested as specified in 1.5.

The test report may only be reproduced or published in full.

Reproduction or publication of extracts from the report requires the prior written approval of the ETS DR. GENZ TAIWAN PS CO., LTD.

Tester:

April 18, 2006

Jay Chaing



Date

ETS-Lab.


Name

Signature

Technical responsibility for area of testing:

April 18, 2006

Steven Chuang



Date

ETS

Name

Signature

Registration number: W6M20604-6807-P-15
FCC ID : QQGBU-2084-J

1.2 Testing laboratory

1.2.1 Location

OATS
No.5-1, Shuang Sing Village,
LiShuei Rd., Wanli Township,
Taipei County 207, Taiwan (R.O.C.)

Company
ETS DR. GENZ TAIWAN PS CO., LTD.
6F, NO. 58, LANE 188, RUEY-KUANG RD.
NEIHU, TAIPEI 114, TAIWAN R.O.C.
Tel : 886-2-66068877
Fax : 886-2-66068879

1.2.2 Details of accreditation status

Accredited testing laboratory

A2LA-registration number: 2300.01

FCC filed test laboratory Reg. No. 930600

Industry Canada filed test laboratory Reg. No. IC 5679

PCTRB Accredited Type Certification Test House

1.3 Details of approval holder

Name	: J-Three International Holding Co., Ltd.
Street	: No.23-7, Dungshyh 12 Lirn Dungshyh Lii Pingchien City
Town	: Taoyuan Hsien 324
Country	: Taiwan, R.O.C.
Telephone	: +886-3-4606755
Fax	: +886-3-4606761
Contact	: Mr. David Wu
Telephone	: +886-3-4606755

Registration number: W6M20604-6807-P-15

FCC ID : QQGBU-2084-J

1.4 Application details

Date of receipt of application : April 12, 2006
 Date of receipt of test item : March 13, 2006
 Date of test : from March 14, 2006 to April 14, 2006

1.5 General information of Test item

Type of test item : BLUETOOTH USB ADAPTER(Class II)
 Model Number : BU-2084-J
 Hardware : V1.0
 Software : V1.0
 Serial number : without
 Photos : see Annex

Technical data

Frequency band : 2.4 GHz – 2.4835 GHz
 Frequency (ch A) : 2.402 GHz
 Frequency (ch B) : 2.441 GHz
 Frequency (ch C) : 2.480 GHz

Transmitter

Unom

Normal Mode

Power (ch A or **ch 0**) : **Conducted: -2.45 dBm**
 Power (ch B or **ch 39**) : **Conducted: -1.35 dBm**
 Power (ch C or **ch 78**) : **Conducted: -0.87 dBm**

EDR Mode

Power (ch A or **ch 0**) : **Conducted: -0.53 dBm**
 Power (ch B or **ch 39**) : **Conducted: 0.48 dBm**
 Power (ch C or **ch 78**) : **Conducted: 0.83 dBm**

Power supply : 120 VAC(power on pc)

Operation modes : duplex

Modulation Type : GFSK

Antenna Type : PCB Antenna

Antenna gain : -2.83 dBi

Registration number: W6M20604-6807-P-15

FCC ID : QQGBU-2084-J

Host device : none

Classification :

Fixed Device	☒
Mobile Device (Human Body distance > 20cm)	☐
Portable Device (Human Body distance < 20cm)	☐

Manufacturer:
(if applicable)

Name : ./.
Street : ./.
Town : ./.
Country : ./.

Additional information : The test sample is designed as BU-2084-J device. Its pseudorandom hopping scheme, authentication, receiver parameters, synchronization procedure and other parameters are determined by BU-2084-J Specification.

1.6 Test standards

Technical standard : FCC RULES PART 15 / SUBPART C § 15.247 / Subpart B

Registration number: W6M20604-6807-P-15
FCC ID : QQGBU-2084-J

2 Technical test

2.1 Summary of test results

No deviations from the technical specification(s) were ascertained in the course of the tests performed.



or

The deviations as specified in 2.5 were ascertained in the course of the tests performed.



2.2 Test environment

Temperature	: 23 °C
Relative humidity content	: 20 ... 75 %
Air pressure	: 86 ... 103 kPa
Details of power supply	: 120 VAC(power on pc)
Extreme conditions parameters	: test voltage : -- extreme min :-- V max :-- V

Registration number: W6M20604-6807-P-15

FCC ID : QQGBU-2084-J

2.3 Test Equipment List

No.	Test equipment	Type	Serial No.	Manufacturer	Cal. Date	Next Cal. Date
ETSTW-CE 001	EMI TEST RECEIVER	ESHS10	842121/013	R&S	2005/10/27	2006/10/26
ETSTW-CE 003	AC POWER SOURCE	APS-9102	D161137	GW		
ETSTW-CE 004	ZWEILEITER-V- NETZNACHBILDUNG TWO-LINE V-NETWORK	ESH3-Z5	840731/011	R&S	2005/10/25	2006/10/24
ETSTW-CE 005	Line-Impedance Stabilisation Network	NNBM 8126D	137	Schwarzbeck	2005/10/21	2006/10/20
ETSTW-CE 006	IMPULS-BEGRENZER PULSE LIMITER	ESH3-Z2	100226	R&S	2004/11/11	2006/11/10
ETSTW-CE 008	ABSORBING CLAMP	MDS 21	3469	ABSORPTIONS- MESSWANDLER- ZANGE	2005/10/24	2007/10/23
ETSTW-CE 009	TEMP.&HUMIDITY CHAMBER	GTH-225-40- 1P-U	MAA0305-009	GIANT FORCE	2005/8/18	2006/8/17
ETSTW-CS 001	SIGNAL GENERATOR	SMX	849254/003	R&S	2005/10/14	2006/10/13
ETSTW-CS 002	COUPLING AND DECOUPLING NETWORK	CDN S751	19263	SCHAFFNER	2005/10/14	2006/10/13
ETSTW-CS 003	COUPLING AND DECOUPLING NETWORK	CDN T400	19820	SCHAFFNER	2005/10/14	2006/10/13
ETSTW-CS 004	COUPLING AND DECOUPLING NETWORK	CDN M016	20053	SCHAFFNER	2005/10/27	2006/10/26
ETSTW-CS 005	RF Power Amplifier	100A250A	306547	AR	2005/10/14	2006/10/13
ETSTW-CS 004	6 dB Attenuator	HFP-5100-3/06 N M/F	2010876106			
ETSTW-RE 002	Function Generator	33220A	MY43004982	Agilent	2005/10/14	2007/10/13
ETSTW-RE 003	EMI TEST RECEIVER	ESI 26	831438/001	R&S	2005/10/24	2006/10/23
ETSTW-RE 004	EMI TEST RECEIVER	ESI 40	832427/004	R&S	2005/10/29	2006/10/30
ETSTW-RE 005	EMI TEST RECEIVER	ESVS10	843207/020	R&S	2005/10/16	2006/10/15
ETSTW-RE 015	ANTENNA	HK116	841489/003	R&S	2005/1/14	2007/1/11
ETSTW-RE 016	ANTENNA	HL223	848953/006	R&S	2005/1/14	2007/1/11
ETSTW-RE 017	ANTENNA	HL025	352886/001	R&S	2005/9/6	2007/9/3
ETSTW-RE 018	ANTENNA	AT4560	27212	AR	2004/11/8	2007/11/7
ETSTW-RE 021	SWEEP GENERATOR	SWM05	835130/010	R&S	2005/10/14	2006/10/13
ETSTW-RE 022	AMPLIFIER	8447D	2944A09837	Brüel&Kjær	2005/10/14	2006/10/13
ETSTW-RE 027	Passive Loop Antenna	6512	34563	EMCO	2004/6/30	2007/6/29

Registration number: W6M20604-6807-P-15

FCC ID : QQGBU-2084-J

ETSTW-RE 030	Double-Ridged Waveguide Horn Antenna	3117	35224	EMCO	2004/5/5	2006/5/4
ETSTW-RE 032	Millivoltmeter	URV 55	849086/013	R&S	2005/10/17	2006/10/16
ETSTW-RE 034	Power Sensor	URV5-Z4	839313/006	R&S	2005/10/17	2006/10/16
ETSTW-RE 048	Triple Loop Antenna	HXYZ 9170	HXYZ 9170-134	Schwarzbeck	2005/3/22	2008/3/21
ETSTW-RE 049	TRILOG Super Broadband test Antenna	VULB 9160	9160-3185	Schwarzbeck	2005/5/19	2007/5/18
ETSTW-RE 055	SPECTRUM ANALYZER	FSU-26	200074	R&S	2005/9/6	2006/9/5
ETSTW-EMI 001	HARMONICS 1000	HAR1000-1P	93	EMC-PARTNER	2005/9/11	2006/11/10
ETSTW-EMS 001	Clamp BASELSTRASSE 160 CH-4242 LAUFEN	CN-EFT1000	354	EMC-PARTNER	2004/11/2	2006/11/1
ETSTW-EMS 003	EMC Immunity Test System	TRA2000IN6	579	EMC-PARTNER	2005/10/27	2006/10/26
ETSTW-EMS 004	ESD generator minizap	ESD2000	016	EMC-PARTNER	2005/10/27	2006/10/26
ETSTW-EMS 008	Safety Test Solutions	ELT-400	E-0039	Narda	2005/1/4	2007/1/3
ETSTW-EMS 009	Magnetic Field Antenna	MF1000-1	104	EMC-PARTNER	2004/12/3	2007/12/2
ETSTW-EMS 010	Coupling De-coupling Network	CDN-UTP8	014	EMC-PARTNER	2005/9/1	2008/8/31
ETSTW-EMS 012	EM Injection Clamp	F-2031-23MM	476	FCC	2005/8/11	2007/8/11
ETSTW-RS 003	RF Power Amplifier	30S1G3	306933	AR		
ETSTW-RS 004	RF Power Amplifier	150W1000	307009	AR	2005/10/21	2006/10/20
ETSTW-RS 005	Electric Field Probe Type 8.3	EMR-20	BN 2244/20	Narda	2005/9/7	2006/9/6
ETSTW-RS 006	SIGNAL GENERATOR	SML03	101551	R&S	2005/10/21	2006/10/20
ETSTW-GSM 01	SIM Simulator	IT3	B2004-50106	ORGA	2005/9/15	2006/9/14
ETSTW-GSM 02	Universal Radio Communication Tester	CMU 200	103489	R&S	2005/11/15	2006/11/14
ETSTW-GSM 03	Agilent 8960 Test Set 1	E5515C	GB44052675	Agilent	2004/7/14	2006/7/13
ETSTW-GSM 04	Agilent 8960 Test Set 2	E5515C	GB44052665	Agilent	2004/7/14	2006/7/13
ETSTW-GSM 05	Agilent 8960 Test Set 3	E5515C	GB44052652	Agilent	2004/7/17	2006/7/16
ETSTW-GSM 06	Agilent 8960 Test Set 4	E5515C	GB44052684	Agilent	2004/7/16	2006/7/15
ETSTW-GSM 07	Agilent 8960 Test Set 5	E5515C	GB44052658	Agilent	2004/7/14	2006/7/13
ETSTW-GSM 08	Agilent 8960 Test Set 6	E5515C	GB44052666	Agilent	2004/7/16	2006/7/15
ETSTW-GSM 10	Combiner Wessex / Anite	B4605/100	053	Wessex / Anite	2004/7/14	2006/7/13

Registration number: W6M20604-6807-P-15

FCC ID : QQGBU-2084-J

ETSTW-GSM 11	GSM 850,900,1800,1900 Test system	TS8950G		R&S	2005/11/1	2006/10/31
ETSTW-GSM 12	Acoustical Calibrator	4231	2463874	Brüel&Kjær	2005/10/31	2006/10/30
ETSTW-GSM 13	Conditioning Amplifier	2690--0S2	2437856	Brüel&Kjær		
ETSTW-GSM 14	Telephone Test Head	4602B	2465324	Brüel&Kjær		
ETSTW-GSM 15	Mouth Simulator	4227	2462516	Brüel&Kjær		
ETSTW-GSM 16	TEMP.&HUMIDITY CHAMBER	GTH-120-40-1P-U	MAA0501002	GIANT FORCE	2005/12/29	2006/12/28
ETSTW-GSM 17	ANTENNT COPLER	CMU-Z10	100988	R&S		
ETSTW-GSM 18	AUDIO ANALYZER	UPL16	100173	R&S	2005/10/29	2006/10/28
ETSTW-GSM 23	SPLITTER	4901.19.A	None	SUHNER		
ETSTW-GSM 24	Vibration Testing System	VS-100V	5494	Vibration	2005/12/20	2006/12/19

2.4 General Test Procedure

POWER LINE CONDUCTED INTERFERENCE: The procedure used was ANSI STANDARD C63.4-2003 using a 50 μ H LISN (if necessary). Both lines were observed. The bandwidth of the spectrum analyzer was 10 kHz with an appropriate sweep speed.

RADIATION INTERFERENCE: The test procedure used was according to ANSI STANDARD C63.4-2003 employing a spectrum analyzer. For investigated frequency is equal to or below 1GHz, the RBW and VBW of the spectrum analyzer was 100 kHz and 100kHz respectively with an appropriate sweep speed. For investigated frequency is above 1GHz, both of RBW and VBW of the spectrum analyzer were 1 MHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The ambient. temperature of the UUT was 23°C with a humidity of 40 %.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dB μ V) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB.

Example:

Freq (MHz)	METER READING + ACF + CABLE LOSS (to the receiver) = FS
33	20 dB μ V + 10.36 dB + 6 dB = 36.36 dB μ V/m @3m

The UUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m (non metallic table) and arranged according to ANSI C63.4-2003 Section 13.1.2. The table used for radiated measurements is capable of continuous rotation. The spectrum was scanned from 30 MHz to the frequency specified as follows:

- (1) If the intentional radiator operates below 10 GHz: to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
- (2) If the intentional radiator operates at or above 10 GHz and below 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 100 GHz, whichever is lower.
- (3) If the intentional radiator operates at or above 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 200 GHz, whichever is lower, unless specified otherwise elsewhere in the rules.
- (4) If the intentional radiator contains a digital device, regardless of whether this digital device controls the functions of the intentional radiator or the digital device is used for additional control or function purposes other than to enable the operation of the intentional radiator, the frequency range shall be investigated up to the range specified in paragraphs (a)(1)-(a)(3) of this section or the range applicable to the digital device, as shown in paragraph (b)(1) of this Section, whichever is the higher frequency range of investigation.

For hand-held devices, a exploratory test was performed with three (3) orthogonal planes to determine the highest emissions.

Measurements were made by ETS Dr. Genz Taiwan PS Co., Ltd. at the registered open field test site located No.5-1, Shuang Sing Village, LiShuei Rd., Wanli Township, Taipei County 207, Taiwan (R.O.C.). The Registration Number: 930600.

Registration number: W6M20604-6807-P-15
FCC ID : QQGBU-2084-J

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

When the radiated emission limits are expressed in terms of the average value of the emission, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.

The formula is as follows:

Average = Peak + Duty Factor

Duty Factor = $20 \log (\text{dwell time}/T)$

T = 100ms when the pulse train period is over 100 ms or the period of the pulse train.

Modified Limits for peak according to 15.35 (b) = Max Permitted average Limits + 20dB

ANTENNA & GROUND:

This unit uses PCB Antenna.

Registration number: W6M20604-6807-P-15

FCC ID : QQGBU-2084-J

3 Test results (enclosure)

TEST CASE	Para. Number	Required	Test passed	Test failed
Peak Output Power	15.247(b)	☒	☒	☐
Equivalent radiated Power	15.247(b)	☒	☒	☐
Spurious Emissions radiated – Transmitter operating	15.247(c)	☒	☒	☐
Spurious Emissions conducted – Transmitter operating	15.247	☐	☐	☐
Carrier Frequency Separation	15.247(a) (1)	☒	☒	☐
Number of Hopping Frequencies	15.247(a) (1)(i)	☒	☒	☐
Time of Occupancy (Dwell Time)	15.247(a) (1)(i)	☒	☒	☐
20 dB Bandwidth	15.247(a) (1)(i)	☒	☒	☐
Band-edge Compliance of RF Emission	15.247(c)	☒	☒	☐
Radiated Emission from Digital Part And Receiver L.O.	15.109	☒	☒	☐
Power Line Conducted Emission	15.207(a)	☒	☒	☐

The follows is intended to leave blank.

Registration number: W6M20604-6807-P-15

FCC ID : QQGBU-2084-J

3.1 Peak Output Power (transmitter)

FCC Rule: 15.247

This measurement applies to equipment with an integral antenna and to equipment with an antenna connector and equipped with an antenna as declared by the applicant.

The power was measured with modulation (declared by the applicant).

(Normal Mode)

Test conditions		Conducted Power		
		Channel A [dBm]	Channel B [dBm]	Channel C [dBm]
$T_{nom} = 23^{\circ}\text{C}$	$V_{nom} = 120\text{ V}$	-2.45	-1.35	-0.87
Measurement uncertainty		< 3 dB		

(EDR Mode)

Test conditions		Conducted Power		
		Channel A [dBm]	Channel B [dBm]	Channel C [dBm]
$T_{nom} = 23^{\circ}\text{C}$	$V_{nom} = 120\text{ V}$	-0.53	0.48	0.83
Measurement uncertainty		< 3 dB		

Test conditions		Radiated Power		
		Channel A [dBm]	Channel B [dBm]	Channel C [dBm]
$T_{nom} = 23^{\circ}\text{C}$	$V_{nom} = 120\text{ V}$	--	--	--
Measurement uncertainty		< 3 dB		

Registration number: W6M20604-6807-P-15

FCC ID : QQGBU-2084-J

Test conditions $T_{nom} = 23^{\circ}\text{C}$, $V_{nom} = 120\text{ V}$ Frequency[MHz]	Signal Field strength TX highest power mode dB $\mu\text{V/m}$
2441	87.94
Measurement uncertainty	< 3 dB

The diagrams for the field strength measurements are included in Appendix.

Maximum Peak Output Power

Limits:

Frequency MHz	Number of hopping channels			
	≥ 75	≥ 50	$49 \geq 25$	$74 \geq 15$
902-928		30 dBm	24 dBm	
2400-2483.5 MHz	30 dBm	-		21 dbm
5725-5850 MHz	30 dBm	-		

In case of employing transmitter antennas having antenna gain >dBi and using fixed poin-to point operation consider §15.247 (b)(4).

Test equipment used: ETSTW-RE 003, ETSTW-RE 012, ETSTW-RE 017, ETSTW-RE 024

Registration number: W6M20604-6807-P-15
FCC ID : QQGBU-2084-J

3.2 Equivalent isotropic radiated power

FCC Rule: 15.239(b), 15.35

Because using an internal antenna there are no deviations from the radiated test results according 3.1.

3.2.1 Transmitter

Integral Antenna:

At the transmitter the measurement was transacted with the modulation declared by the manufacturer and the maximum available output power of the EUT.

In this arrangement the EUT fulfils the requirements of the FCC rules § 15.247, subpart C, section b. This unit uses an internal antenna. There is no provision for an external antenna (see photo).

3.3 RF Exposure Compliance Requirements

According to Supplement C, Edition 01-01 to OET Bulletin 65, Edition 97-01 this spread spectrum transmitter is categorically excluded from routine environmental evaluation because of the low power level, where there is a high likelihood of compliance with RF exposure standards.

The antenna used for this Bluetooth transceiver module must not be co-located or operating in conjunction with any other antenna or transmitter.

3.4 Out of Band Radiated Emissions

FCC Rule: 15.247(c) , 15.35

For out of band emissions that are close to or that exceed the 20 dB attenuation requirement described in the specification, radiated measurements were performed at a 3 m separation distance to determine whether these emissions complied with the general radiated emission requirement.

Limits:

For frequencies below 1GHz :

Max. reading – 20 dB

$$87.94\text{dB}\mu\text{V/m} - 20\text{ dB} = 67.94\text{ dB}\mu\text{V/m}$$

Guidance on Measurement of FHSS Systems:

“If the emission is pulsed, modify the unit for continuous operation , use the settings shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation.” Here the correction was added to the limit instead subtracted from the reading.

Duty Cycle correction = $20 \log (\text{dwell time}/100\text{ms})$

For frequencies above 1GHz (Peak measurements).

Limit = max. aver. reading-20dB +20dB(because Peak detector is used)

$$67.94\text{ dB}\mu\text{V/m}$$

For frequencies above 1GHz (Average measurements).

Max. reading – 20 dB - duty cycle correction:

No duty cycle correction was added to the reading

$$87.94\text{dB}\mu\text{V/m} - 20\text{ dB} = 67.94\text{ dB}\mu\text{V/m}$$

Remarks: See attached diagrams.

Test equipment used: ETSTW-CE 003 , ETSTW-RE 003

Registration number: W6M20604-6807-P-15

FCC ID : QQGBU-2084-J

3.5 Transmitter Radiated Emissions in restricted Bands

FCC Rules: 15.247 (c), 15.205, 15.209, 15.35

Radiated emission measurements were performed from 30 MHz to 26000 MHz.

For radiated emission tests, the analyzer setting was as followings:

RES BW VID BW

Frequency <1 GHz 100 kHz 100 kHz (Peak measurements)

Frequency >1 GHz 1 MHz 1 MHz (Peak measurements)

1 MHz 1 MHz (Average measurements)

Limits:

For frequencies below 1GHz :

Frequency of Emission (MHz)	Field strength (microvolts/meter)	Field Strength (dB microvolts/meter)
30 – 88	100	40.0
88 – 216	150	43.5
216 – 960	200	46.0
Above 960	500	54.0

For frequencies above 1GHz (Average measurements).

Guidance on Measurement of FHSS Systems:

“If the emission is pulsed, modify the unit for continues operation , use the settings shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation.” Here the correction was added to the limit instead subtracted from the reading.

Duty cycle correction = $20 \log (\text{dwell time}/100\text{ms})$

For frequencies above 1GHz (Average measurements).

Limit – duty cycle correction

No duty cycle correction was added to the reading.

54.0dB μ V/m

For frequencies above 1GHz (Peak measurements).

Limit + 20dB

54.0dB μ V/m + 20 dB= 74 dB μ V/m

Remarks: See attached diagrams.

Test equipment used: ETSTW-RE 003, ETSTW-RE 012, ETSTW-RE 015, ETSTW-RE 016,
ETSTW-RE 017, ETSTW-RE 024

Registration number: W6M20604-6807-P-15

FCC ID : QQGBU-2084-J

3.6 Spurious emissions (tx)

Spurious emission was measured with modulation (declared by manufacturer).

In any 100 kHz bandwidth outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c))

SAMPLE CALCULATION OF LIMIT. All results will be updated by an automatic measuring system in accordance to point 2.3.

Calculation of test results:

Such factors like antenna correction, cable loss, external attenuation etc. are already included in the provided measurement results. This is done by using validated test software and calibrated test system according the accreditation requirements.

The peak and average spurious emission plots was measured with the average limits.

In the Table being listed the critical peak and average value an exhibit the compliance with the above calculated Limits.

If in the column's correction factor states a value then the max. Field strength in the same row is corrected by a value gained from the "Marker-Delta-Method" or the „Duty-Cycle Correction Factor“.

Summary table with radiated data of the test plots

Low Channel

Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBuV)	Correction Factor (dB)	Detector	Test Result (dBuV/m)	Compliance Limit (dBuV/m)	Margin (dB)	Table Azimuth (degree)
V	67.47495	20.98	13.41	PK	34.39	67.94	33.55	90
	166.613226	22.96	15.23	PK	38.19	54	15.81	205
	196.593186	33.79	12.18	PK	45.97	67.94	21.97	213
	201.603206	30.27	12.14	PK	42.41	67.94	25.53	175
	2370.4609	47.28	2.12	PK	49.4	54	4.6	250
	7206.4128	49.19	7.64	PK	56.83	67.94	11.11	185

Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBuV)	Correction Factor (dB)	Detector	Test Result (dBuV/m)	Compliance Limit (dBuV/m)	Margin (dB)	Table Azimuth (degree)
H	37.49499	15.29	13.37	PK	28.66	54	25.34	68
	201.603206	26.66	12.14	PK	38.8	67.94	29.14	170
	2370.4609	48.81	2.12	PK	50.93	54	3.07	243
	7206.4128	50.79	7.64	PK	58.43	67.94	9.51	184

Registration number: W6M20604-6807-P-15

FCC ID : QQGBU-2084-J

Middle Channel


Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBuV)	Correction Factor (dB)	Detector	Test Result (dBuV/m)	Compliance Limit (dBuV/m)	Margin (dB)	Table Azimuth (degree)
V	130.841683	19.92	14.09	PK	34.01	54	19.99	274
	163.88777	19.03	15.46	PK	34.49	54	19.51	135
	201.603206	29.5	12.14	PK	41.64	67.94	26.3	170
	610.420842	17.1	22.2	PK	39.3	54	14.7	294
	7323.4775	44.87	6.38	AV	51.25	54	2.75	10
	7323.4775	50.1	6.38	PK	56.48	74	17.52	10

Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBuV)	Correction Factor (dB)	Detector	Test Result (dBuV/m)	Compliance Limit (dBuV/m)	Margin (dB)	Table Azimuth (degree)
H	37.49499	16.91	13.37	PK	30.28	54	23.72	65
	149.91984	16.84	15.39	PK	32.23	54	21.77	120
	201.603206	26.04	12.14	PK	38.18	67.94	29.76	175
	7323.05314	43.26	6.38	AV	49.64	54	4.36	200
	7323.05314	51.42	6.38	PK	57.8	74	16.2	200

High Channel

Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBuV)	Correction Factor (dB)	Detector	Test Result (dBuV/m)	Compliance Limit (dBuV/m)	Margin (dB)	Table Azimuth (degree)
V	133.567134	19.53	14.12	PK	33.65	43.5	9.85	283
	149.91984	20.21	15.39	AV	35.6	43.5	7.9	125
	201.603206	30.15	12.14	PK	42.29	67.94	25.65	178
	256.112224	20.28	13.9	PK	34.18	46	11.82	264
	2511.4629	50.13	-1.74	PK	48.39	67.94	19.55	213
	7439.947082	44.26	6.14	AV	50.5	54	3.5	185
	7439.947082	48.3	6.14	PK	54.44	74	19.56	185

Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBuV)	Correction Factor (dB)	Detector	Test Result (dBuV/m)	Compliance Limit (dBuV/m)	Margin (dB)	Table Azimuth (degree)
H	37.49499	16.62	13.37	PK	29.99	54	37.38	300
	149.91984	17.37	15.39	PK	32.76	54	21.24	122
	201.603206	25.91	12.14	PK	38.05	67.94	29.89	173
	2511.462926	55.11	-1.74	PK	53.37	67.94	14.57	212
	2383.9178	48.26	2.12	PK	50.38	54	3.62	69
	7439.58072	45.89	6.14	AV	52.03	54	1.97	189
	7439.58072	49.53	6.14	PK	55.67	74	18.33	189



Registration number: W6M20604-6807-P-15
FCC ID : QQGBU-2084-J

All other not noted test plots do not contain significant test results in relation to the limits.

TEST RESULT (Transmitter): The unit DOES meet the FCC requirements.

Comment: see attached diagrams

Test equipment used: ETSTW-RE 003, ETSTW-RE 012, ETSTW-RE 015, ETSTW-RE 016,
ETSTW-RE 017, ETSTW-RE 024

Registration number: W6M20604-6807-P-15

FCC ID : QQGBU-2084-J

3.7 Carrier Frequency Separation

Carrier Frequency Separation was measured with modulation (declared by manufacturer).

According to FCC rules part 15 subpart C §15.247 frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or 20 dB bandwidth of the hopping channel, whichever is greater.

Test conditions		Channel Separation	
		Channel B	Channel B+1
$T_{nom} = 23^{\circ}\text{C}$	$V_{nom} = 120\text{ V}$	1.000000000 MHz	
Measurement uncertainty		< 10 Hz	

Limits:

Frequency Range MHz	Limits	
	20 dB bandwidth < 25 kHz	20 dB bandwidth > 25 kHz
902-928	25 kHz	20 dB bandwidth
2400-2483.5 5725-5850.0	25 kHz	20 dB bandwidth

Test equipment used: ETSTW-CE 003, ETSTW-RE 003

Comment: see attached diagram

3.8 Number of Hopping Frequencies

According to FCC rules part 15 subpart C §15.247 frequency hopping systems operating in the 2400-2483.5 MHz band shall use at least 15 hopping frequencies. Frequency hopping systems in 5725-5850 MHz bands shall use least 75 hopping frequencies.

For frequency hopping systems operating in the 902-928 MHz band: if the 20dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies; if the 20dB bandwidth of the hopping channel 250 kHz or greater, the system shall use at least 25 hopping frequencies.

Test conditions		Operating Mode	Number of Channels
$T_{nom} = 23^{\circ}\text{C}$	$V_{nom} = 120\text{ V}$	normal transmitting	79
$T_{nom} = 23^{\circ}\text{C}$	$V_{nom} = 120\text{ V}$	Inquiry mode	32

Limits:

Frequency Range MHz	Limit			
	20dB Bandwidth		20dB Bandwidth < 250 kHz	20dB Bandwidth ≥ 250 kHz
	≤ 1MHz			
902-928 MHz			≥ 50	≥ 25
2400-2483.5	≥ 15	≥ 15		
5725-5850.0 MHz	≥ 75			

Test equipment used: ETSTW-CE 003 , ETSTW-RE 003

Comment: see attached diagrams

3.8.1 Pseudorandom Frequency Hopping Sequence

The generation of the hopping sequence is determined by the Bluetooth cord specification and complies with the FCC requirements.

3.8.2 Coordination of hopping sequences to other transmitters

According to the Bluetooth core specification V1.1 such a coordination is not possible. During scatternet function only one of the two hopping sequences will be used at a definite moment.

3.8.3 System Receiver Hopping Capability

According to the Bluetooth core specification. The system receivers shift frequencies in synchronization with the transmitted signals.

Registration number: W6M20604-6807-P-15

FCC ID : QQGBU-2084-J

3.9 Time of Occupancy (Dwell Time)

Frequency hopping systems operating in the 5725-5850 MHz band shall use an average time of occupancy on any frequency not greater than 0.4 seconds within a 30 second period.

In 2400-2483,5 MHz band the average time of occupancy on any channel shall not be greater than 0,4 seconds multiplied by the number of hopping channels employed.

For frequency hopping systems operating in the 902-928 MHz band: if the 20dB bandwidth of the hopping channel is less than 250 kHz, the average time of occupancy on any frequency shall not greater than 0.4 seconds within a 20 second period; if the 20dB bandwidth of the hopping channel is 250 kHz or greater, the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period.

Test conditions	Operating mode	Measurement periode	Time of Occupancy
$T_{nom} = 23^{\circ}\text{C}$ $V_{nom} = 120\text{ V}$ Channel B	normal transmitting		119.583 ms
	inquiry mode		55.678 ms
Measurement uncertainty	< 1 μs		

Limits and measurement periods:

Frequency MHz	Number of channels	Measurement Periode	Limit
902 – 928	≥ 50	20 s	0,4 s
	$49 \geq 25$	10 s	0,4 s
2400 – 2483,5	≥ 15	0,4 s * number of used channels	0,4 s
5725- 5850	≥ 75	30 s	0,4s

Test equipment used: ETSTW-CE 003 , ETSTW-RE 003

Comment: See attached diagram, which show the On-time and the number of counted events during the measurement period

Registration number: W6M20604-6807-P-15

FCC ID : QQGBU-2084-J

3.10 20dB Bandwidth

Frequency hopping systems operating in the 5725-5850 MHz bands shall use a maximum 20dB bandwidth of 1 MHz.

The 20dB bandwidth is measured on the lowest, middle and highest hopping channel.

For frequency hopping systems operating in the 902-928 MHz band the maximum 20dB bandwidth of the hopping channel is 500 kHz.

(Normal Mode)

Test conditions		20 dB Bandwidth		
		Channel A	Channel B	Channel C
$T_{nom} = 23^{\circ}\text{C}$	$V_{nom} = 120\text{ V}$	993.589743590 kHz	993.589743590 kHz	993.589743589 kHz
Measurement uncertainty		< 10 Hz		

(EDR Mode)

Test conditions		20 dB Bandwidth		
		Channel A	Channel B	Channel C
$T_{nom} = 23^{\circ}\text{C}$	$V_{nom} = 120\text{ V}$	1.365384615 MHz	1.365384615 MHz	1.378205128 MHz
Measurement uncertainty		< 10 Hz		

Limits:

Frequency Range / MHz	Number of channels	Limit
902-928	< 50	< 250 kHz
	$49 \geq 25$	500 kHz $\geq$ 250 kHz
2400-2483.5	≥ 15	not determined
5725-5850	75	$\leq 1\text{ MHz}$

Test equipment used: ETSTW-CE 003 , ETSTW-RE 003

Comment: see attached diagram

3.10.1 System Receiver Input Bandwidth

It is determined in the Bluetooth core specification. The value matches to the bandwidth of transmitter signal.

3.11 Band-edge Compliance of RF Emissions

According to FCC rules part 15 subpart C §15.247(c) in any 100 kHz bandwidth outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required.

In addition radiated emission which fall in the restricted bands, as defined in section 15.205(a), must also with the radiated emission limits.

(Normal Mode)

Test conditions		Attenuation at or outside band-edges Single Frequency	
		Lower Band-edge	Upper Band-edge
$T_{nom} = 23^{\circ}\text{C}$	$V_{nom} = 120 \text{ V}$	65.54 dB	68.15 dB
Measurement uncertainty		< 100 Hz	

Test conditions		Attenuation at or outside band-edges Hopping Frequency	
		Lower Band-edge	Upper Band-edge
$T_{nom} = 23^{\circ}\text{C}$	$V_{nom} = 120 \text{ V}$	59.84 dB	60.53 dB
Measurement uncertainty		< 100 Hz	

(EDR Mode)

Test conditions		Attenuation at or outside band-edges Single Frequency	
		Lower Band-edge	Upper Band-edge
$T_{nom} = 23^{\circ}\text{C}$	$V_{nom} = 120 \text{ V}$	65.44 dB	69.53 dB
Measurement uncertainty		< 100 Hz	

Registration number: W6M20604-6807-P-15

FCC ID : QQGBU-2084-J

Test conditions		Attenuation at or outside band-edges Hopping Frequency	
		Lower Band-edge	Upper Band-edge
$T_{nom} = 23^{\circ}\text{C}$	$V_{nom} = 120 \text{ V}$	53.61 dB	59.56 dB
Measurement uncertainty		< 100 Hz	

Limits:

Frequency Range / MHz	Limit
902 – 928	- 20 dB
2400 – 2483.5	
5725 - 5850	

Test equipment used: ETSTW-CE 003 , ETSTW-RE 003

Comment: see attached diagrams

Registration number: W6M20604-6807-P-15

FCC ID : QQGBU-2084-J

3.12 Radiated Emissions from Receiver Section of Transceiver

FCC Rule: 15.109

Summary table with radiated data of the test plots

(RX)

Low Channel

Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBuV)	Correction Factor (dB)	Detector	Test Result (dBuV/m)	Compliance Limit (dBuV/m)	Margin (dB)	Table Azimuth (degree)
V	44.98998	10.42	13.69	PK	24.11	40	15.89	52
	196.593186	26.78	12.18	PK	38.96	43.5	4.54	168
	212.825651	18.22	12.43	PK	30.65	43.5	12.85	234
	1901.803607	37.38	-5.14	PK	32.24	54	21.76	341

Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBuV)	Correction Factor (dB)	Detector	Test Result (dBuV/m)	Compliance Limit (dBuV/m)	Margin (dB)	Table Azimuth (degree)
H	46.012024	11.2	13.6	PK	24.8	40	15.2	43
	196.593186	25.4	12.18	PK	37.58	43.5	5.92	177
	144.468938	12.36	15.1	PK	27.46	43.5	16.04	63
	200	21.4	12.14	PK	33.54	43.5	9.96	280
	499.799599	13.2	19.8	PK	33	46	13	98
	1901.803607	37.58	-5.14	PK	32.44	54	21.56	345

Middle Channel

Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBuV)	Correction Factor (dB)	Detector	Test Result (dBuV/m)	Compliance Limit (dBuV/m)	Margin (dB)	Table Azimuth (degree)
V	44.98998	10.68	13.69	PK	24.37	40	15.63	46
	196.593186	24.82	12.18	PK	37	43.5	6.5	170
	214.428858	18.18	12.3	PK	30.48	43.5	13.02	228
	1895.791583	37.64	-4.4	PK	33.24	54	20.76	306

Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBuV)	Correction Factor (dB)	Detector	Test Result (dBuV/m)	Compliance Limit (dBuV/m)	Margin (dB)	Table Azimuth (degree)
H	200.0	18.06	12.14	PK	30.2	43.5	13.3	288
	212.82565	16.66	12.43	PK	29.09	43.5	14.41	230
	499.799599	13.73	19.8	PK	33.53	46	12.47	95
	198.637275	17.64	12.18	PK	29.82	43.5	13.68	180
	1901.803607	37.48	-5.14	PK	32.34	54	21.66	340

Registration number: W6M20604-6807-P-15

FCC ID : QQGBU-2084-J

High Channel

Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBuV)	Correction Factor (dB)	Detector	Test Result (dBuV/m)	Compliance Limit (dBuV/m)	Margin (dB)	Table Azimuth (degree)
V	44.98998	11.23	13.69	PK	24.92	40	15.08	42
	196.593241	25.4	12.18	PK	37.58	43.5	5.92	173
	212.825651	17.9	12.43	PK	30.33	43.5	13.17	214
	1901.803607	37.32	-5.14	PK	32.18	54	21.82	340

Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBuV)	Correction Factor (dB)	Detector	Test Result (dBuV/m)	Compliance Limit (dBuV/m)	Margin (dB)	Table Azimuth (degree)
H	145.150301	13.04	15	PK	28.04	43.5	15.46	68
	209.619238	16.58	12.23	PK	28.81	46	17.19	105
	499.799599	12.68	19.8	PK	32.48	46	13.52	98
	1901.803607	38.8	-5.14	PK	33.66	54	20.34	344

Registration number: W6M20604-6807-P-15

FCC ID : QQGBU-2084-J

Summary table with radiated data of the test plots
(Digital)

Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBuv)	Correction Factor (dB)	Detector	Test Result (dBuV/m)	Compliance Limit (dBuV/m)	Margin (dB)	Table Azimuth (degree)	Antenna Height (cm)
V	41.242485	11.16	13.58	PK	24.74	40	15.26	40	170
	198.97795	22.6	12.2	PK	34.8	43.5	8.7	180	200
	200.0	24.49	12.14	PK	36.63	43.5	6.87	175	210

Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBuv)	Correction Factor (dB)	Detector	Test Result (dBuV/m)	Compliance Limit (dBuV/m)	Margin (dB)	Table Azimuth (degree)	Antenna Height (cm)
H	41.24248	11.18	13.58	PK	24.76	40	15.24	35	277
	200.0	21.69	12.14	PK	33.83	43.5	9.67	172	213
	878.156313	15.24	25.74	PK	40.98	46	5.02	93	165

Except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency of Emission (MHz)	Field Strength (microvolts/meter)	Field Strength (dBmicrovolts/meter)
30 – 88	100	40.0
88 – 216	150	43.5
216 – 960	200	46.0
Above 960	500	54.0

Test equipment used: ETSTW-RE 015, ETSTW-RE 016, ETSTW-RE 017, ETSTW-CS 001, ETSTW-RE 026, ETSTW-RE 003, ETSTW-RE 025

Comment: see attached diagram

3.13 Power Line Conducted Emission

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the table bellows with this provision shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminals.

This measurement was transact first with instrumentation using an average and peak detector and a 10 kHz bandwidth. If the peak detector achieves a calculated level, the measurement is repeated by an instrumentation using a quasi-peak detector.

Frequency	Level (dB μ V)	
	quasi-peak	average
150 kHz	lower limit line	Lower limit line

LISN type	Frequency Marker	Corrected Reading (dBuV)		Correction Factor	Test Result (dBuV)		Compliance Limit (dBuV)		Margin (dB)	
		QP	AV		QP	AV	QP	AV	QP	AV
N	MHz	QP	AV	dB	QP	AV	QP	AV	QP	AV
	0.1523	46.2	29.1	10.1	56.3	39.2	66	56	9.7	16.8
	0.58	39.57	32.2	10.1	49.67	42.3	56	46	6.33	3.7
	0.65	39.7	31.1	10.1	49.8	41.2	56	46	6.2	4.8
	24.96	42	33.98	10.1	52.1	44.08	60	50	7.9	5.92

LISN type	Frequency Marker	Corrected Reading (dBuV)		Correction Factor	Test Result (dBuV)		Compliance Limit (dBuV)		Margin (dB)	
		QP	AV		QP	AV	QP	AV	QP	AV
L1	MHz	QP	AV	dB	QP	AV	QP	AV	QP	AV
	0.1518	44.72	31.7	10.1	54.82	41.8	66	56	11.18	14.2
	0.51	41.8	30.96	10.1	51.9	41.06	56	46	4.1	4.94
	0.57	38.3	28.1	10.1	48.4	38.2	56	46	7.6	7.8
	0.67	41.2	29.5	10.1	51.3	39.6	56	46	4.7	6.4
	25.34	43.57	34.18	10.1	53.67	44.28	60	50	6.33	5.72

Registration number: W6M20604-6807-P-15
FCC ID : QQGBU-2084-J

Limits:

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi Peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

Test equipment used: ETSTW-CE 004, ETSTW-CE 001, ETSTW-RE 023

Comment: see attached diagram

Registration number: W6M20604-6807-P-15
FCC ID : QQGBU-2084-J

Appendix

- A Peak Output Power
- B Spurious Emissions radiated
- C Carrier Frequency Separation
- D Number of Hopping Frequencies
- E Time of Occupancy (Dwell Time)
- F 20dB Bandwidth
- G Band-edge Compliance of RF Conducted Emissions
- H Radiated Emissions from Receiver Section of Transceiver
- I Power Line Conducted Emission
- J Pictures




Registration number: W6M20604-6807-P-15
FCC ID : QQGBU-2084-J


Appendix A

Peak Output Power


The measurement diagram are wideband pre-scan results; only for reference.



Date: 7.APR.2006 14:09:35




Date: 7.APR.2006 14:09:07



Date: 7.APR.2006 14:08:33




1 PK
MAXH




MAX OUTPUT POWER CH0 (EDR MODE)

Date: 7.APR.2006 15:21:07



Date: 7.APR.2006 15:20:36




Date: 7.APR.2006 15:21:38

Date: 7.APR.2006 15:21:38

Carrier power (Field Strength)

FCC RULES PART 15, SUBPART C


Model: BHOOTH SB ADAPTER (Class II)
MODENO.: BH2084-J Channel
Approval: Three International Hong Co., Ltd.
Test Site / Operator: ES / Catey
Temperature/Vmag: Temp.: 24.9°C / Vm.: 120VAC per a PC)
Test Specification: according to 5.247
Comment 2: Dist.: 3m, Ant.: H025
Freq 2.402GHz, Max 87.58dBμ/m, RBW: 1MHz



Carrier power (Field Strength)

FCC RULES PART 15, SUBPART C


Model: BHOOTH SB ADAPTER (Class II)
MODENO.: BH2084-J Channel
Approval No.: JThree International Hong Co, Ltd.
Test Site / Operator: ES / Catey
Temperature/Voltag: Temp.: 24.9°C/ Hum.: 120VAC per a PC)
Test Specification: according to 5.247
Comment 2: Dist.: 3m, Ant.: H025
Freq 2.402GHz, Max 81.67dBμV/m, RBW: 1MHz



Carrier power (Field Strength)

FCC RULES PART 15, SUBPART C


Model: BHOOTH SB ADAPTER (Class II)
MODENO.: BH2084-J middle channel
Approval Holder: The International Holding Co., Ltd.
Test Site / Operator: ES / Catey
Temperature/Voltage: Temp.: 24.9°C / Hum.: 120VAC per a PC)
Test Specification: according to 5.247
Comment 2: Dist.: 3m, Ant.: H025
Freq 2.441GHz, Max 87.94dBμV/m, RBW: 1MHz



Carrier power (Field Strength)


FCC RULES PART 15, SUBPART C

Model: BHOOTH SB ADAPTER (Class II)
MODENO.: BH2084-J model channel
Approval Holder: The International Hong Co., Ltd.
Test Site / Operator: ES / Catey
Temperature/Voltage: Temp.: 24.9°C / Hum.: 120VAC per a PC)
Test Specification: according to 5.247
Comment 2: Dist.: 3m, Ant.: H025
Freq 2.441GHz, Max 82.03dBμV/m, RBW: 1MHz



FCC RULES PART 15, SUBPART C


Model: BHOOTH SB ADAPTER (Class II)
MODENO.: BH2084-J Channel
Approval Holder: JThree International Hong Co, Ltd.
Test Site / Operator: ES / Catey
Temperature/Voltag: Temp.: 24.9°C/ Hum.: 120VAC per a PC)
Test Specification: according to 5.247
Comment 2: Dist.: 3m, Ant.: H025
Freq 2.480GHz, Max 87.50dBμV/m, RBW: 1MHz



Carrier power (Field Strength)

FCC RULES PART 15, SUBPART C

Model: BHOOTH SB ADAPTER (Class II)
MODENO.: BH2084-J Channel
Approval: The International Hong Co., Ltd.
Test Site / Operator: ES / Catey
Temperature/Vmag: Temp.: 24.9°C / Vm.: 120VAC per a PC)
Test Specification: according to 5.247
Comment 2: Dist.: 3m, Ant.: H025
Freq 2.480GHz, Max 81.38dBV/m, RBW: 1MHz



Registration number: W6M20604-6807-P-15
FCC ID : QQGBU-2084-J

Appendix B


Spurious Emissions radiated

The measurement diagram are wideband pre-scan results; only for reference.

Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Model: BHOOTH SB ADAPTER (Class II)
MODENO.: BH2084-J Channel
Approval Holder: The International Holding Co., Ltd.
Test Site / Operator: ES / Catey
Temperature/Voltag: Temp.: 24.9°C / Hum.: 120VAC per a PC)
Test Specification: according to 15.247
Comment 2: Dist.: 3m, Ant.: HK116
Freq 199.659MHz, Max 38.12dBμV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Model: BHOOTH SB ADAPTEC (Class II)
MODENO.: BH208 4-J Channel
Approval: JThree International Hong Co, Ltd.
Test Site / Operator: ES / Catey
Temperature/Vmag: Temp.: 24.9°C/ Hum.: 120VAC per a PC)
Test Specification: according to 15.247
Comment 2: Dist.: 3m, Ant.: HK116
Freq 196.593MHz, Max 45.97dBμV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


ID: BHOOTH SB ADAPTE (Class II)
 MODENO.: BH2084-J Channel
 Approval Holder: JThree International Hong Co, Ltd.
 Test Site / Operator: ES / Catey
 Temperature/Vmag: Temp.: 24.9°C / Hum.: 120VAC per a PC)
 Test Specification: according to EC15.247
 Comment 2: Dist.: 3m, Ant.: HL223, amp f.
 Freq 988.778MHz, Max 44.00dBμ/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Model: BHOOTH SB ADAPTER (Class II)
MODENO.: BH2084-J Channel
Approval No.: JThree International Hong Co., Ltd.
Test Site / Operator: ES / Catey
Temperature/Voltage: Temp.: 24.9°C / Hum.: 120VAC per a PC)
Test Specification: according to EC15.247
Comment 2: Dist.: 3m, Ant.: HL223, amp f.
Freq 902.204MHz, Max 45.84dBμ/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


E: BHOOTH SB ADAPTE (class II)
 MODENO.: BH208 4-J Channel
 Approval Holder: JThree International Holding Co., Ltd.
 Test Site / Operator: ES / Catey
 Temperature/Vbag: Temp.: 24.9°C/ Hum.: 120VAC per a PC)
 Test Specification: according to 15.247, peak detector
 Comment 2: Dist.: 3m, Ant.: H025, amp f.
 Freq 2.370GHz, Max 50.93dBV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


E: BHOOTH SB ADAPTE (class II)
 MODENO.: BH208 4-J Channel
 Approval Holder: JThree International Holding Co., Ltd.
 Test Site / Operator: ES / Catey
 Temperature/Voltage: Temp.: 24.9°C/ Hum.: 120VAC per a PC)
 Test Specification: according to 15.247, peak detector
 Comment 2: Dist.: 3m, Ant.: H025, amp f.
 Freq 2.370GHz, Max 49.40dBV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


E: BHOOTH SB ADAPTE (class II)
 MODENO.: BH2084-J Channel
 Approval Holder: JThee International Holding Co., Ltd.
 Test Site / Operator: ES / Catey
 Temperature/Vbag: Temp.: 24.9°C / Hum.: 120VAC per a PC)
 Test Specification: according to 15.247, peak detector
 Comment 2: Dist.: 3m, Ant.: H025, ampl#P.
 Freq 7.206GHz, Max 58.43dBV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Model: BHOOTH SB ADAPTER (Class II)
MODENO.: BH2084-J Channel
Approval No.: Three International Holding Co., Ltd.
Test Site / Operator: ES / Catey
Temperature/Voltage: Temp.: 24.9°C / Hum.: 120VAC per a PC)
Test Specification: according to 15.247, peak detection
Comment 2: Dist.: 3m, Ant.: H025, amplifier.
Freq 7.206GHz, Max 56.83dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Model: BHOOTH SB ADAPTER (Class II)
MODENO.: BH208 4-J Channel
ApprvalHder: JThree InternationalHongCo, Ltd.
Test Site / Operator: ES / Catey
Temperature/Vbag: Temp.: 24.9C/ Hum.: 120VAC per a PC)
Test Specification: according to 5.247, peak detector
Comment 2: Dist.: 3m, Ant.: H025, ampl#P.
Freq 11.559GHz, Max 49.36dBu/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


E: BHOOTH SB ADAPTE (class II)
 MODENO.: BH208 4-J Channel
 Approval Holder: JThee International Holding Co., Ltd.
 Test Site / Operator: ES / Catey
 Temperature/Vbag: Temp.: 24.9°C/ Hum.: 120VAC per a PC)
 Test Specification: according to 5.247, peak detector
 Comment 2: Dist.: 3m, Ant.: H025, amplifier.
 Freq 11.992GHz, Max 49.66dBμ/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Model: BHOOTH SB ADAPTE (Class II)
MODENO.: BH208 4-J Channel
ApprvalHder: JThee InternationalHdngCo,Ed.
Test Site / Operator: ES / Catey
Temperature/Vbag: Temp.: 24.9C/ Hum.: 120VAC per a PC)
Test Specification: accordingto\$5.247,peak detecto
Comment 2: Dist.: 3m,Ant.: H025,ampl#P.
Freq 15.559GHz,Max 53.04dBu/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Model: BHOOTH SB ADAPTER (Class II)
MODENO.: BH2084-J Channel
Approval No.: JThree International Hong Co, Ltd.
Test Site / Operator: ES / Catey
Temperature/Vbag: Temp.: 24.9°C / Hum.: 120VAC per a PC)
Test Specification: according to 15.247, peak detector
Comment 2: Dist.: 3m, Ant.: H025, amplifier.
Freq 17.988GHz, Max 52.64dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


E: BHOOTH SB ADAPTE (class II)
 MODENO.: BH2084-J Channel
 Approval Holder: JThee International Holding Co., Ltd.
 Test Site / Operator: ES / Catey
 Temperature/Vbag: Temp.: 24.9°C / Hum.: 120VAC per a PC)
 Test Specification: according to 5.247, peak detection
 Comment 1: Dist.: 3m, Ant.: H025, amp f.
 Freq 26.483GHz, Max 50.69dBμ/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


E: BHOOTH SB ADAPTE (class II)
 MODENO.: BH208 4-J Channel
 Approval Holder: JThee International Holding Co., Ltd.
 Test Site / Operator: ES / Catey
 Temperature/Vbag: Temp.: 24.9°C / Hum.: 120VAC per a PC)
 Test Specification: according to 5.247, peak detector
 Comment 1: Dist.: 3m, Ant.: H025, amp f.
 Freq 22.753GHz, Max 50.71dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Model: BHOOTH SB ADAPTER (Class II)
MODENO.: BH2084-J model channel
Approval No.: JThree International Hong Co, Ltd.
Test Site / Operator: ES / Catey
Temperature/Voltag: Temp.: 24.9°C/ Hum.: 120VAC per a PC)
Test Specification: according to 15.247
Comment 2: Dist.: 3m, Ant.: HK116
Freq 199.319MHz, Max 38.62dBμV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Model: BHOOTH SB ADAPTER (Class II)
MODENO.: BH208 4-J mda channel
ApprvalHder: The International Hong Co, Ltd.
Test Site / Operator: ES / Catey
Temperature/Vbag: Temp.: 24.9C/ Hum.: 120VAC per a PC)
Test Specification: according to 15.247
Comment 2: Dist.: 3m, Ant.: HK116
Freq 196.593MHz, Max 45.53dBu/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Model: BHOOTH SB ADAPTE (Class II)
MODENO.: BH208 4-J mda channel
ApprvalHder: The International Hong Co, Ltd.
Test Site / Operator: ES / Catey
Temperature/Vbag: Temp.: 24.9C/ Hum.: 120VAC per a PC)
Test Specification: according to EC15.247
Comment 2: Dist.: 3m, Ant.: HL223, amp f.
Freq 929.459MHz, Max 44.32dBu/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


E: BHOOTH SB ADAPTE (Class II)
 MODENO.: BH208 4-J mda channel
 Approval Holder: The International Hong Co, Ltd.
 Test Site / Operator: ES / Catey
 Temperature/Vbag: Temp.: 24.9°C/ Hum.: 120VAC per a PC)
 Test Specification: according to EC15.247
 Comment 2: Dist.: 3m, Ant.: HL223, amp f.
 Freq 902.204MHz, Max 47.62dBμ/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


E: BHOOTH SB ADAPTE (Class II)
 MODENO.: BH2084-J mdd@bnnel
 Approval Holder: JThree International Holding Co., Ltd.
 Test Site / Operator: ES / Catey
 Temperature/Vbag: Temp.: 24.9°C/ Hum.: 120VAC per a PC)
 Test Specification: according to 15.247, peak detector
 Comment 2: Dist.: 3m, Ant.: H025, amp f.
 Freq 3.040GHz, Max 48.47dBV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Model: BHOOTH SB ADAPTEC (class II)
MODENO.: BH2084-J model channel
Approval No.: Three International Holding Co., Ltd.
Test Site / Operator: ES / Catey
Temperature/Voltage: Temp.: 24.9°C / Hum.: 120VAC per a PC)
Test Specification: according to 15.247, peak detector
Comment 2: Dist.: 3m, Ant.: H025, amp f.
Freq 3.353GHz, Max 48.77dBV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Model: BHOOTH SB ADAPTER (Class II)
MODENO.: BH2084-J model channel
Approval No.: The International Hong Kong, Ltd.
Test Site / Operator: ES / Catey
Temperature/Voltage: Temp.: 24.9°C / Hum.: 120VAC per a PC)
Test Specification: according to 15.247, peak detector
Comment 2: Dist.: 3m, Ant.: H025, amplifier.
Freq 7.327GHz, Max 57.80dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Model: BHOOTH SB ADAPTER (Class II)
MODENO.: BH2084-J model channel
Approval No.: The International Holding Co., Ltd.
Test Site / Operator: ES / Catey
Temperature/Voltage: Temp.: 24.9°C / Hum.: 120VAC per a PC)
Test Specification: according to 47.247, peak detector
Comment 2: Dist.: 3m, Ant.: H025, amplifier.
Freq 7.327GHz, Max 56.48dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


U: BHOOTH SB ADAPTE (class II)
MODENO.: BH2084-J mdd@bnnel
ApprvalHder: JThee InternatnalHdngCo,Ed.
Test Site / Operator: ES / Catey
Temperature/Vbag: Temp.: 24.9C/ Um.: 120VAC per a PC)
Test Specfctn: accordingto\$5.247,peak detecto
Comment 2: Dst.: 3m,Ant.: H025,ampl#P.
Freq 11.832GHz,Max 49.44dBu/m,RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Model: BHOOTH SB ADAPTER (Class II)
MODENO.: BH2084-J model channel
Approval Holder: The International Holding Co., Ltd.
Test Site / Operator: ES / Catey
Temperature/Voltage: Temp.: 24.9°C / Hum.: 120VAC per a PC)
Test Specification: according to 5.247, peak detector
Comment 2: Dist.: 3m, Ant.: H025, amplifier.
Freq 11.856GHz, Max 49.67dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Model: BHOOTH SB ADAPTEC (Class II)
MODENO.: BH2084-J model number
Approval No.: JThree International Hong Kong, Ltd.
Test Site / Operator: ES / Catey
Temperature/Voltage: Temp.: 24.9°C / Hum.: 120VAC per a PC)
Test Specification: according to 15.247, peak detection
Comment 2: Dist.: 3m, Ant.: H025, amplifier.
Freq 17.339GHz, Max 53.68dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Model: BHOOTH SB ADAPTER (Class II)
MODENO.: BH2084-J model channel
Approval Holder: JThree International Holding Co., Ltd.
Test Site / Operator: ES / Catey
Temperature/Vbag: Temp.: 24.9°C / Hum.: 120VAC per a PC)
Test Specification: according to 15.247, peak detector
Comment 2: Dist.: 3m, Ant.: H025, ampl#P.
Freq 18.000GHz, Max 53.59dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Model: BHOOTH SB ADAPTER (Class II)
MODENO.: BH2084-J model channel
Approval: The International Holding Co., Ltd.
Test Site / Operator: ES / Catey
Temperature/Vmag: Temp.: 24.9°C / Vm.: 120VAC per a PC)
Test Specification: according to 15.247, peak detection
Comment 1: Dist.: 3m, Ant.: H025, ampf.
Freq 25.546GHz, Max 50.85dBu/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


E: BHOOTH SB ADAPTE (class II)
 MODENO.: BH2084-J mdd@bnnel
 Approval Holder: JThee International Holding Co, Ltd.
 Test Site / Operator: ES / Catey
 Temperature/Vmag: Temp.: 24.9°C/ Hum.: 120VAC per a PC)
 Test Specification: according to 15.247, peak detection
 Comment 1: Dist.: 3m, Ant.: H025, amp f.
 Freq 24.354GHz, Max 50.41dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Model: BHOOTH SB ADAPTE (Class II)
MODENO.: BH208 4-J Channel
Approval: The International Hong Co., Ltd.
Test Site / Operator: ES / Catey
Temperature/Vmag: Temp.: 24.9°C / Vm.: 120VAC per a PC)
Test Specification: according to 15.247
Comment 2: Dist.: 3m, Ant.: HK116
Freq 200.000MHz, Max 39.29dBμV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Model: BHOOTH SB ADAPTER (Class II)
MODENO.: BH208 4-J Channel
Approval: The International Hong Co., Ltd.
Test Site / Operator: ES / Catey
Temperature/Vmag: Temp.: 24.9°C / Vm.: 120VAC per a PC)
Test Specification: according to 15.247
Comment 2: Dist.: 3m, Ant.: HK116
Freq 196.593MHz, Max 44.62dBμV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Model: BHOOTH SB ADAPTE (Class II)
 MODENO.: BH2084-J Channel
 Approval: The International Hong Co., Ltd.
 Test Site / Operator: ES / Catey
 Temperature/Voltag: Temp.: 24.9°C / Hum.: 120VAC per a PC)
 Test Specification: according to 15.247
 Comment 2: Dist.: 3m, Ant.: HL223, amp f.
 Freq 963.126MHz, Max 43.78dBμ/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Model: BHOOTH SB ADAPTE (Class II)
MODENO.: BH208 4-J Channel
Approval Holder: JThree International Holding Co., Ltd.
Test Site / Operator: ES / Catey
Temperature/Voltage: Temp.: 24.9°C / Vm.: 120VAC per a PC)
Test Specification: according to 15.247
Comment 2: Dist.: 3m, Ant.: HL223, amp f.
Freq 924.649MHz, Max 44.20dBμ/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: BLUETOOTH USB ADAPTER(Class II)
MODEL NO.: BU-2084-J high channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Catey
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120VAC (power on PC)
Test Specification: according to §15.247, peak detector
Comment 2: Dist.: 3m, Ant.: HL025, amplif.
Freq: 2.511GHz, Emax: 53.37dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


E: BHOOTH SB ADAPTE (class II)
 MODENO.: BH2084-J Channel
 Approval Holder: JThree International Hong Co, Ltd.
 Test Site / Operator: ES / Catey
 Temperature/Vbag: Temp.: 24.9°C/ Hum.: 120VAC per a PC)
 Test Specification: according to 5.247, peak detector
 Comment 2: Dist.: 3m, Ant.: H025, amp f.
 Freq 3.822GHz, Max 48.44dBV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


E: BHOOTH SB ADAPTE (Class II)
 MODENO.: BH208 4-J Channel
 Approval Holder: JThee International Holding Co, Ltd.
 Test Site / Operator: ES / Catey
 Temperature/Vbag: Temp.: 24.9°C / Hum.: 120VAC per a PC)
 Test Specification: according to 15.247, peak detector
 Comment 2: Dist.: 3m, Ant.: H025, ampl#P.
 Freq 7.447GHz, Max 55.67dBV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Model: BHOOTH SB ADAPTEC (Class II)
MODENO.: BH208 4-J Channel
ApprvalHder: JThree InternationalHongCo,Ed.
Test Site / Operator: ES / Catey
Temperature/Vbag: Temp.: 24.9C/ Hum.: 120VAC per a PC)
Test Specification: according to 15.247, peak detector
Comment 2: Dist.: 3m, Ant.: H025, ampl#P.
Freq 7.447GHz, Max 54.44dBV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


E: BHOOTH SB ADAPTE (class II)
 MODENO.: BH2084-J Channel
 Approval Holder: JThee International Hong Co, Ltd.
 Test Site / Operator: ES / Catey
 Temperature/Vbag: Temp.: 24.9°C/ Hum.: 120VAC per a PC)
 Test Specification: according to 5.247, peak detector
 Comment 2: Dist.: 3m, Ant.: H025, ampl#P.
 Freq 11.495GHz, Max 49.28dBμ/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Model: BHOOTH SB ADAPTER (Class II)
 MODENO.: BH2084-J Channel 5
 Approval Holder: JThree International Hong Kong, Ltd.
 Test Site / Operator: ES / Catey
 Temperature/Voltage: Temp.: 24.9°C / Hum.: 120VAC per a PC)
 Test Specification: according to 5.247, peak detector
 Comment 2: Dist.: 3m, Ant.: H025, amplifier.
 Freq 11.904GHz, Max 49.37dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


E: BHOOTH SB ADAPTE (class II)
 MODENO.: BH2084-J Channel
 Approval Holder: JThree International Hong Co, Ltd.
 Test Site / Operator: ES / Catey
 Temperature/Vbag: Temp.: 24.9°C / Hum.: 120VAC per a PC)
 Test Specification: according to 15.247, peak detector
 Comment 2: Dist.: 3m, Ant.: H025, ampl#P.
 Freq 18.000GHz, Max 53.04dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Model: BHOOTH SB ADAPTER (Class II)
MODENO.: BH2084-J Channel
Approval: JThree International Hong Co, Ltd.
Test Site / Operator: ES / Catey
Temperature/Vbag: Temp.: 24.9°C / Hum.: 120VAC per a PC)
Test Specification: according to 15.247, peak detection
Comment 2: Dist.: 3m, Ant.: H025, ampl#P.
Freq 18.000GHz, Max 53.23dBu/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


E: BHOOTH SB ADAPTE (Class II)
 MODENO.: BH2084-J Channel
 Approval: JThee International Hong Co, Ltd.
 Test Site / Operator: ES / Catey
 Temperature/Vbag: Temp.: 24.9°C / Hum.: 120VAC per a PC)
 Test Specification: according to 5.247, peak detector
 Comment 1: Dist.: 3m, Ant.: H025, ampf.
 Freq 26.466GHz, Max 50.83dBμ/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C

Model: BHOOTH SB ADAPTER (Class II)
MODENO.: BH2084-J Channel
Approval: JThree International Hong Co., Ltd.
Test Site / Operator: ES / Catey
Temperature/Vbag: Temp.: 24.9°C Hum.: 120VAC per a PC)
Test Specification: according to 5.247, peak detection
Comment 1: Dist.: 3m, Ant.: H025, amp f.
Freq 24.899GHz, Max 50.96dBu/m, RBW: 1MHz






Registration number: W6M20604-6807-P-15
FCC ID : QQGBU-2084-J


Appendix C

Carrier Frequency Separation



FREQUENCY SEPARATION CH38 & CH39


Date: 7.APR.2006 15:08:32



Registration number: W6M20604-6807-P-15
FCC ID : QQGBU-2084-J


Appendix D

Number of Hopping Frequencies




NUMBER OF HOPPING FREQUENCIES (CH : 0 ~ 13)

Date: 7.APR.2006 14:45:21




NUMBER OF HOPPING FREQUENCIES (CH : 14 ~ 38)

Date: 7.APR.2006 14:48:18




NUMBER OF HOPPING FREQUENCIES (CH : 39 ~ 63)

Date: 7.APR.2006 14:51:10




NUMBER OF HOPPING FREQUENCIES (CH : 64 ~ 78)

Date: 7.APR.2006 14:52:54




NUMBER OF HOPPING FREQUENCIES (MASTER INQUIRY MODE)

Date: 7.APR.2006 14:56:02




NUMBER OF HOPPING FREQUENCIES (MASTER INQUIRY MODE)

Date: 7.APR.2006 14:58:08



NUMBER OF HOPPING FREQUENCIES (MASTER INQUIRY MODE)

Date: 7.APR.2006 15:00:22



NUMBER OF HOPPING FREQUENCIES (MASTER INQUIRY MODE)


Date: 7.APR.2006 15:02:03



Registration number: W6M20604-6807-P-15
FCC ID : QQGBU-2084-J


Appendix E

Time of Occupancy (Dwell Time)



Time of occupancy(Hopping DH1) = 383.28 us * 312 events = 119.583 ms

Date: 12.APR.2006 14:32:41



Time of occupancy (Inquiry Mode) 95.667 μ s * 582 events = 55.678 ms


Date: 12.APR.2006 14:18:54



Registration number: W6M20604-6807-P-15
FCC ID : QQGBU-2084-J

Appendix F

20dB Bandwidth




Date: 7.APR.2006 14:00:44



Ref 10 dBm *Att 0 dB *RBW 50 kHz Marker 1 [T1] -2.81 dBm
*VBW 100 kHz *SWT 200 ms 2.440993590 GHz

1 PK
MAXH





A


LVL

20 dB BANDWIDTH CH 39


Date: 7.APR.2006 13:47:14



Date: 13.APR.2006 13:24:50




Date: 13.APR.2006 13:26:15



Date: 13.APR.2006 13:25:53

Date: 13.APR.2006 13:25:53




Date: 13.APR.2006 13:25:18




Registration number: W6M20604-6807-P-15
FCC ID : QQGBU-2084-J

Appendix G



Band-edge Compliance of RF Conducted Emissions




Date: 7.APR.2006 13:57:48




Date: 12.APR.2006 14:02:12






BANDEDGE COMPLIANCE CH 78 (CONDUCT , SIGNAL MODE)

Date: 12.APR.2006 14:03:09




BANDEDGE COMPLIANCE ch0 (CONDUCTED , HOPPING , EDR MODE)

Date: 7.APR.2006 15:31:55





BANDEDGE COMPLIANCE ch0 (CONDUCTED , SINGLE , EDR MODE)

Date: 7.APR.2006 15:56:20



BANDEDGE COMPLIANCE ch78 (CONDUCTED , HOPPING , EDR MODE)

Date: 7.APR.2006 15:58:07





Registration number: W6M20604-6807-P-15
FCC ID : QQGBU-2084-J

Appendix H


Radiated Emissions from Receiver Section of Transceiver

The measurement diagram are wideband pre-scan results; only for reference.

Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: BLUETOOTH USB ADAPTER(Class II)
MODEL NO.: BU-2084-J low channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Catey
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120VAC (power on PC)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HK 116
Freq:198.637MHz Emax:30.53dBμV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: BLUETOOTH USB ADAPTER(Class II)
MODEL NO.: BU-2084-J low channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Catey
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120VAC (power on PC)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HK 116
Freq:196.593MHz Emax:38.96dBμV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: BLUETOOTH USB ADAPTER(Class II)
MODEL NO.: BU-2084-J low channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Catey
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120VAC (power on PC)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL 223, ampl.
Freq:947.094MHz Emax:36.08dBμV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: BLUETOOTH USB ADAPTER(Class II)
MODEL NO.: BU-2084-J low channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Catey
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120VAC (power on PC)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL 223, ampl.
Freq:948.697MHz Emax:36.39dBμV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: BLUETOOTH USB ADAPTER(Class II)
MODEL NO.: BU-2084-J low channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Catey
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120VAC (power on PC)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:3.766GHz Emax:36.15dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: BLUETOOTH USB ADAPTER(Class II)
MODEL NO.: BU-2084-J low channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Catey
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120VAC (power on PC)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:3.886GHz Emax:36.42dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: BLUETOOTH USB ADAPTER(Class II)
MODEL NO.: BU-2084-J low channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Catey
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120VAC (power on PC)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:7.559GHz Emax:46.32dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: BLUETOOTH USB ADAPTER(Class II)
MODEL NO.: BU-2084-J low channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Catey
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120VAC (power on PC)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:7.142GHz Emax:45.84dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: BLUETOOTH USB ADAPTER(Class II)
MODEL NO.: BU-2084-J low channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Catey
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120VAC (power on PC)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:11.599GHz Emax:51.12dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: BLUETOOTH USB ADAPTER(Class II)
MODEL NO.: BU-2084-J low channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Catey
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120VAC (power on PC)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:11.511GHz Emax:51.18dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: BLUETOOTH USB ADAPTER(Class II)
MODEL NO.: BU-2084-J low channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Catey
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120VAC (power on PC)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:17.808GHz Emax:52.05dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: BLUETOOTH USB ADAPTER(Class II)
MODEL NO.: BU-2084-J low channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Catey
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120VAC (power on PC)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:17.651GHz Emax:52.56dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: BLUETOOTH USB ADAPTER(Class II)
MODEL NO.: BU-2084-J low channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Catey
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120VAC (power on PC)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL025, ampl.
Freq:25.291GHz Emax:51.03dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: BLUETOOTH USB ADAPTER(Class II)
MODEL NO.: BU-2084-J low channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Catey
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120VAC (power on PC)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL025, ampl.
Freq:26.466GHz Emax:51.54dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: BLUETOOTH USB ADAPTER(Class II)
MODEL NO.: BU-2084-J middle channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Catey
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120VAC (power on PC)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HK 116
Freq:200.000MHz Emax:30.20dBμV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: BLUETOOTH USB ADAPTER(Class II)
MODEL NO.: BU-2084-J middle channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Catey
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120VAC (power on PC)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HK 116
Freq:196.593MHz Emax:37.00dBμV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: BLUETOOTH USB ADAPTER(Class II)
MODEL NO.: BU-2084-J middle channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Catey
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120VAC (power on PC)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL 223, ampl.
Freq:918.236MHz Emax:35.37dBμV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: BLUETOOTH USB ADAPTER(Class II)
MODEL NO.: BU-2084-J middle channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Catey
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120VAC (power on PC)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL 223, ampl.
Freq:950.301MHz Emax:35.87dBμV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: BLUETOOTH USB ADAPTER(Class II)
MODEL NO.: BU-2084-J middle channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Catey
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120VAC (power on PC)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:4.000GHz Emax:36.66dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: BLUETOOTH USB ADAPTER(Class II)
MODEL NO.: BU-2084-J middle channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Catey
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120VAC (power on PC)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:3.946GHz Emax:36.18dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: BLUETOOTH USB ADAPTER(Class II)
MODEL NO.: BU-2084-J middle channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Catey
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120VAC (power on PC)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:7.703GHz Emax:45.97dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: BLUETOOTH USB ADAPTER(Class II)
MODEL NO.: BU-2084-J middle channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Catey
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120VAC (power on PC)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:7.776GHz Emax:47.10dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: BLUETOOTH USB ADAPTER(Class II)
MODEL NO.: BU-2084-J middle channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Catey
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120VAC (power on PC)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:11.591GHz Emax:51.32dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: BLUETOOTH USB ADAPTER(Class II)
MODEL NO.: BU-2084-J middle channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Catey
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120VAC (power on PC)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:11.952GHz Emax:51.12dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: BLUETOOTH USB ADAPTER(Class II)
MODEL NO.: BU-2084-J middle channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Catey
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120VAC (power on PC)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:17.784GHz Emax:52.16dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: BLUETOOTH USB ADAPTER(Class II)
MODEL NO.: BU-2084-J middle channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Catey
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120VAC (power on PC)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:17.880GHz Emax:52.24dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: BLUETOOTH USB ADAPTER(Class II)
MODEL NO.: BU-2084-J middle channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Catey
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120VAC (power on PC)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL025, ampl.
Freq:24.354GHz Emax:51.16dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: BLUETOOTH USB ADAPTER(Class II)
MODEL NO.: BU-2084-J middle channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Catey
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120VAC (power on PC)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL025, ampl.
Freq:26.449GHz Emax:51.24dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: BLUETOOTH USB ADAPTER(Class II)
MODEL NO.: BU-2084-J high channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Catey
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120VAC (power on PC)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HK 116
Freq:200.000MHz Emax:30.70dBμV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: BLUETOOTH USB ADAPTER(Class II)
MODEL NO.: BU-2084-J high channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Catey
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120VAC (power on PC)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HK 116
Freq:196.593MHz Emax:37.58dBμV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: BLUETOOTH USB ADAPTER(Class II)
MODEL NO.: BU-2084-J high channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Catey
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120VAC (power on PC)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL 223, ampl.
Freq:948.697MHz Emax:36.61dBμV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: BLUETOOTH USB ADAPTER(Class II)
MODEL NO.: BU-2084-J high channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Catey
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120VAC (power on PC)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL 223, ampl.
Freq:948.697MHz Emax:37.26dBμV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: BLUETOOTH USB ADAPTER(Class II)
MODEL NO.: BU-2084-J high channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Catey
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120VAC (power on PC)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:3.910GHz Emax:36.52dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: BLUETOOTH USB ADAPTER(Class II)
MODEL NO.: BU-2084-J high channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Catey
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120VAC (power on PC)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:3.940GHz Emax:36.18dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: BLUETOOTH USB ADAPTER(Class II)
MODEL NO.: BU-2084-J high channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Catey
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120VAC (power on PC)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:7.703GHz Emax:45.54dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: BLUETOOTH USB ADAPTER(Class II)
MODEL NO.: BU-2084-J high channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Catey
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120VAC (power on PC)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:7.703GHz Emax:46.22dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: BLUETOOTH USB ADAPTER(Class II)
MODEL NO.: BU-2084-J high channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Catey
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120VAC (power on PC)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:11.880GHz Emax:51.19dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: BLUETOOTH USB ADAPTER(Class II)
MODEL NO.: BU-2084-J high channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Catey
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120VAC (power on PC)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:11.848GHz Emax:50.71dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: BLUETOOTH USB ADAPTER(Class II)
MODEL NO.: BU-2084-J high channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Catey
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120VAC (power on PC)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:17.808GHz Emax:52.05dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: BLUETOOTH USB ADAPTER(Class II)
MODEL NO.: BU-2084-J high channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Catey
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120VAC (power on PC)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:17.808GHz Emax:52.30dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: BLUETOOTH USB ADAPTER(Class II)
MODEL NO.: BU-2084-J high channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Catey
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120VAC (power on PC)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL025, ampl.
Freq:26.347GHz Emax:51.15dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: BLUETOOTH USB ADAPTER(Class II)
MODEL NO.: BU-2084-J high channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Catey
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120VAC (power on PC)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL025, ampl.
Freq:26.466GHz Emax:51.76dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: BLUETOOTH USB ADAPTER(Class II)
MODEL NO.: BU-2084-J
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Catey
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120VAC (power on PC)
Test Specification: according to subpart B
Comment 2: Dist.: 3m, Ant.: HK 116
Freq:199.659MHz Emax:34.68dBμV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: BLUETOOTH USB ADAPTER(Class II)
MODEL NO.: BU-2084-J
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Catey
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120VAC (power on PC)
Test Specification: according to subpart B
Comment 2: Dist.: 3m, Ant.: HK 116
Freq:200.000MHz Emax:32.20dBμV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: BLUETOOTH USB ADAPTER(Class II)
MODEL NO.: BU-2084-J
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Catey
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120VAC (power on PC)
Test Specification: according to subpart B
Comment 2: Dist.: 3m, Ant.: HL 223, ampl.
Freq:953.507MHz Emax:39.21dBμV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B

EUT: BLUETOOTH USB ADAPTER(Class II)
MODEL NO.: BU-2084-J
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Catey
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120VAC (power on PC)
Test Specification: according to subpart B
Comment 2: Dist.: 3m, Ant.: HL 223, ampl.
Freq:878.156MHz Emax:40.98dBμV/m RBW: 100 kHz





Registration number: W6M20604-6807-P-15
FCC ID : QQGBU-2084-J

Appendix I


Power Line Conducted Emission

The measurement diagram are wideband pre-scan results; only for reference.

EMI voltage test in the ac-mains according to FCC Part 15

Class B


EUT: BLUETOOTH USB ADAPTER(Class II)
Manufacturer: J-Three International Holding Co.,Ltd.
Operating Condition: Unom : 120 VAC (power on PC) , Tnom : 24.2°C
Test Site: ETS
Operator: Catey
Test Specification: V-network: ESH3-Z5 N
Comment: model: BU-2084-J mode: active




EMI voltage test in the ac-mains according to FCC Part 15

Class B

EUT: BLUETOOTH USB ADAPTER(Class II)
Manufacturer: J-Three International Holding Co.,Ltd.
Operating Condition: Unom : 120 VAC (power on PC) , Tnom : 24.2°C
Test Site: ETS
Operator: Catey
Test Specification: V-network: ESH3-Z5 L1
Comment: model: BU-2084-J mode: active





Registration number: W6M20604-6807-P-15
FCC ID : QQGBU-2084-J

Appendix J

Pictures