

FCC PART 15 SUBPART C TEST REPORT

for

Solo Speed/Cadence Sensor

Model No.: ZA5D

FCC ID: QSWDSCSCS1

of

Applicant: Zentan Technology Co., Ltd.

**Address: NO.92, Hsing-Sheng Road, Chia-Li District, Tainan City,
72254 Taiwan**

Tested and Prepared

by

Worldwide Testing Services (Taiwan) Co., Ltd.

FCC Registration No.: TW1477

Industry Canada filed test laboratory Reg. No. IC 5679A-1, IC 5107A-1

A2LA Accredited No.: 2732.01



Report No.: W6M21707-17191-C-1

6F, NO. 58, LANE 188, RUEY-KUANG RD., NEIHU TAIPEI 114, TAIWAN, R.O.C.
TEL: 886-2-66068877 FAX: 886-2-66068879 E-mail: wts@wts-lab.com



TABLE OF CONTENTS

1	GENERAL INFORMATION.....	2
1.1	NOTES	2
1.2	TESTING LABORATORY	3
1.2.1	Location	3
1.2.2	Details of accreditation status	3
1.3	DETAILS OF APPROVAL HOLDER	3
1.4	APPLICATION DETAILS.....	4
1.5	GENERAL INFORMATION OF TEST ITEM.....	4
1.6	TEST STANDARDS	5
2	TECHNICAL TEST.....	6
2.1	SUMMARY OF TEST RESULTS.....	6
2.2	TEST ENVIRONMENT	6
2.3	TEST EQUIPMENT LIST.....	7
2.4	GENERAL TEST PROCEDURE.....	10
3	TEST RESULTS (ENCLOSURE)	12
3.1	PEAK OUTPUT POWER (TRANSMITTER).....	13
3.2	RF EXPOSURE COMPLIANCE REQUIREMENTS	16
3.3	TRANSMITTER RADIATED EMISSIONS IN RESTRICTED BANDS	17
3.4	SPURIOUS EMISSIONS (TX).....	18
3.5	RADIATED EMISSION ON THE BAND EDGE.....	20
3.6	MINIMUM 6 DB BANDWIDTH	23
3.7	PEAK POWER SPECTRAL DENSITY	26
3.8	RADIATED EMISSION FROM DIGITAL PART	29
3.9	POWER LINE CONDUCTED EMISSION	30
	APPENDIX.....	31



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21707-17191-C-1

FCC ID: QSWDSCSCS1

1 General Information

1.1 Notes

The purpose of conformity testing is to increase the probability of adherence to the essential requirements or conformity specifications, as appropriate.

The complexity of the technical specifications, however, means that full and thorough testing is impractical for both technical and economic reasons.

Furthermore, there is no guarantee that a test sample which has passed all the relevant tests conforms to a specification.

Neither is there any guarantee that such a test sample will interwork with other genuinely open systems.

The existence of the tests nevertheless provides the confidence that the test sample possesses the qualities as maintained and that its performance generally conforms to representative cases of communications equipment.

The test results of this test report relate exclusively to the item tested as specified in 1.5.

The test report may only be reproduced or published in full.

Reproduction or publication of extracts from the report requires the prior written approval of the Worldwide Testing Services(Taiwan) Co., Ltd.

Tester:

August 28, 2017

Kent Lin

Date

WTS-Lab.

Name

Signature

Technical responsibility for area of testing:

August 28, 2017

Kevin Wang

Date

WTS

Name

Signature



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21707-17191-C-1

FCC ID: QSWDSCSCS1

1.2 Testing laboratory

1.2.1 Location

OATS

No.5-1, Lishui, Shuang Sing Village,

Wanli Dist., New Taipei City 207,

Taiwan (R.O.C.)

3 meter semi-anechoic chamber

No.35, Aly. 21, Ln. 228, Ankang Rd., Neihu Dist., Taipei City 114, Taiwan (R.O.C.)

TEL:886-2-6613-0228

FAX:886-2-2791-5046

Company

Worldwide Testing Services(Taiwan) Co., Ltd.

6F, NO. 58, LANE 188, RUEY-KUANG RD.

NEIHU, TAIPEI 114, TAIWAN R.O.C.

Tel : 886-2-66068877

Fax : 886-2-66068879

1.2.2 Details of accreditation status

Accredited testing laboratory

A2LA accredited number: 2732.01

FCC filed test laboratory Reg. No. TW1477

Industry Canada filed test laboratory Reg. No. IC 5679A-1, IC 5107A-1

Test location, where different from Worldwide Testing Services (Taiwan) Co., Ltd. :

Name: ./.

Accredited number: ./.

Street: ./.

Town: ./.

Country: ./.

Telephone: ./.

Fax: ./.

1.3 Details of approval holder

Name: Zentan Technology Co., Ltd.

Street: NO.92, Hsing-Sheng Road, Chia-Li District,

Town: Tainan City, 72254

Country: Taiwan

Telephone: (06)7232226

Fax: (06)7231289



Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1

1.4 Application details

Date of receipt of test item: July 10, 2017
Date of test: from July 11, 2017 to August 25, 2017


1.5 General information of Test item

Type of test item: Solo Speed/Cadence Sensor
Model Number: ZA5D
Brand Name: CARDIOSPORT
Multi-listing model number: ./.
Photos: see Appendix

Technical data

Frequency band: 2402 MHz – 2480 MHz (BLE), 2457 MHz (ANT+)
Frequency (ch 0 or A): 2402 MHz
Frequency (ch 19 or B): 2441 MHz
Frequency (ch 39 or C): 2480 MHz
Number of Channels: 40
Operation modes: Duplex
Modulation Type: GFSK
Fixed point-to-point operation: ☐ Yes / ☒ No
Type of Antenna: Chip Antenna
Antenna gain: 3.09 dBi
Power supply: Battery 3Vdc(CR 2032)
Emission designator: 1M07G1D (BLE), 1M81G1D (ANT+)
Host device: none
Classification :

Fixed Device	☐
Mobile Device (Human Body distance > 20cm)	☐
Portable Device (Human Body distance < 20cm)	☒



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21707-17191-C-1

FCC ID: QSWDSCSCS1

Transmitter

Unom

BLE

Power (ch 0 or A): Conducted: -4.22 dBm

Power (ch 19 or B): Conducted: -4.21 dBm

Power (ch 39 or C): Conducted: -4.55 dBm

ANT+: Conducted: -1.92 dBm

Manufacturer: (if applicable)

Name: ./.

Street: ./.

Town: ./.

Country: ./.

Additional information: ./.

1.6 Test standards

Technical standard : FCC RULES SUBPART C § 15.247 (2016-10)



Registration number: W6M21707-17191-C-1

FCC ID: QSWDSCSCS1

2 Technical test

2.1 Summary of test results

No deviations from the technical specification(s) were ascertained in the course of the tests performed. ☒

or

The deviations as specified in 2.5 were ascertained in the course of the tests performed. ☐

2.2 Test environment

Temperature: 23 °C

Relative humidity content: 20 ... 75 %

Air pressure: 86 ... 103 kPa

Power supply: Battery 3Vdc(CR 2032)

Extreme conditions parameters: ./.

Test item Name	Uncertainty
Estimation Result of Uncertainty of Conducted Emission	Expanded Uncertainty : 0.74 dB
Estimation Result of Uncertainty of Radiated Emission(3M)	Expanded Uncertainty : 0.009-30 MHz : 2.17 dB 30-1000 MHz : 3.30 dB 1-18 GHz : 2.28 dB 18-40 GHz : 2.19 dB
Estimation Result of Uncertainty of Bandwidth Measurement 20 dB Bandwidth, Occupied bandwidth, Channel bandwidth, Necessary Bandwidth	Expanded Uncertainty : 0.45 kHz
Estimation Result of Uncertainty of Conducted Output Power Measurement Output power	Expanded Uncertainty : 1.01 dB
Estimation Result of Uncertainty of Power Density Measurement Power density	Expanded Uncertainty : 1.09 dB
Estimation Result of Uncertainty of Band Edge Measurement	Expanded Uncertainty : 0.98 dBc




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21707-17191-C-1

FCC ID: QSWDSCSCS1

2.3 Test Equipment List

No.	Test equipment	Type	Serial No.	Manufacturer	Cal. Date	Next Cal. Date
ETSTW-CE 001	EMI TEST RECEIVER	ESHS10	842121/013	R&S	2017/5/26	2018/5/25
ETSTW-CE 003	AC POWER SOURCE	APS-9102	D161137	GW	Function Test	
ETSTW-CE 004	ZWEILEITER-V-NETZNACHBILDUNG TWO-LINE V-NETWORK	ESH3-Z5	840731/011	R&S	2016/10/13	2017/10/12
ETSTW-CE 006	IMPULSBEGRENZER PULSE LIMITER	ESH3-Z2	100226	R&S	2017/8/22	2018/8/21
ETSTW-CE 008	HF-EICHLLEITUNG RF STEP ATTENUATOR 139dB DPSP	334.6010.02	844581/024	R&S	Function Test	
ETSTW-CE 009	TEMP.&HUMIDITY CHAMBER	GTH-225-40-1P-U	MAA0305-009	GIANT FORCE	2017/7/14	2018/7/13
ETSTW-CE 016	TWO-LINE V-NETWORK	ENV216	100050	R&S	2016/9/12	2017/9/11
ETSTW-CE 028	MXE EMI Receiver	N9038A	MY53220110	Agilent	2017/7/11	2018/7/10
ETSTW-RE 003	EMI TEST RECEIVER	ESI 26	831438/001	R&S	2017/5/26	2018/5/25
ETSTW-RE 004	EMI TEST RECEIVER	ESI 40	832427/004	R&S	2017/5/17	2018/5/16
ETSTW-RE 005	EMI TEST RECEIVER	ESVS10	843207/020	R&S	2017/7/3	2018/7/2
ETSTW-RE 012	TUNABLE BANDREJECT FILTER	D.C 0309	146	K&L	Function Test	
ETSTW-RE 013	TUNABLE BANDREJECT FILTER	D.C 0336	397	K&L	Function Test	
ETSTW-RE 018	MICROWAVE HORN ANTENNA	AT4560	27212	AR	2017/7/4	2018/7/3
ETSTW-RE 027	Passive Loop Antenna	6512	00034563	ETS-Lindgren	2017/7/3	2018/7/2
ETSTW-RE 030	Double-Ridged Guide Horn Antenna	3117	00035224	ETS-Lindgren	2017/3/22	2018/3/21
ETSTW-RE 042	Biconical Antenna	HK116	100172	R&S	2017/2/7	2018/2/6
ETSTW-RE 043	Log-Periodic Dipole Antenna	HL223	100166	R&S	2017/4/10	2018/4/9
ETSTW-RE 044	Log-Periodic Antenna	HL050	100094	R&S	2017/4/27	2018/4/26
ETSTW-RE 045	ESA-E SERIES SPECTRUM ANALYZER	E4404B	MY45111242	Agilent	Pre-test Use	
ETSTW-RE 050	Attenuator 10dB	50HF-010-1	None	JFW	2017/3/1	2018/2/28
ETSTW-RE 051	Attenuator 6dB	50HF-006-1	None	JFW	2017/3/1	2018/2/28
ETSTW-RE 053	Attenuator 3dB	50HF-003-1	None	JFW	2017/3/1	2018/2/28
ETSTW-RE 055	SPECTRUM ANALYZER	FSU 26	200074	R&S	2017/3/1	2018/2/28
ETSTW-RE 060	Attenuator 30dB	5015-30	F651012z-01	ATM	2017/3/1	2018/2/28
ETSTW-RE 062	Amplifier Module	CHC 2	None	KMIC	2017/4/12	2018/4/11
ETSTW-RE 064	Bluetooth Test Set	MT8852B-042	6K00005709	Anritsu	Function Test	
ETSTW-RE 069	Double-Ridged Guide Horn Antenna	3117	00069377	ETS-Lindgren	Function Test	
ETSTW-RE 072	CELL SITE TEST SET	8921A	3339A00375	HP	2016/9/8	2017/9/7
ETSTW-RE 088	SOLID STATE AMPLIFIER	KMA180265A01	99057	KMIC	2016/9/20	2017/9/19
ETSTW-RE 091	Match Pad	MDCS1500	None	WOKEN	2017/4/6	2018/4/5
ETSTW-RE 099	DC Block	50DB-007-1	None	JFW	2017/3/1	2018/2/28




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21707-17191-C-1

FCC ID: QSWDSCSCS1

ETSTW-RE 112	AC POWER SOURCE	TFC-1005	T-0A023536	T-Power	Function test	
ETSTW-RE 115	2.4GHz Notch Filter	N0124411	473874	MICROWAVE CIRCUITS	2017/1/12	2018/1/11
ETSTW-RE 120	RF Player	MP9200	MP9210-111022	ADIVIC	Function test	
ETSTW-RE 122	SIGNAL GENERATOR	SMF100A	102149	R&S	2017/5/26	2018/5/25
ETSTW-RE 125	5GHz Notch filter	5NSL11-5200/E221.3-O/O	1	K&L Microwave	2017/8/9	2018/8/8
ETSTW-RE 126	5GHz Notch filter	5NSL12-5800/E221.3-O/O	1	K&L Microwave	2017/8/9	2018/8/8
ETSTW-RE 127	RF Switch Box	RFS-01	None	WTS	2017/3/1	2018/2/28
ETSTW-RE 128	5.3GHz Notch filter	N0153001	SN487233	Microwave Circuits	2017/8/9	2018/8/8
ETSTW-RE 129	5.5GHz Notch filter	N0555984	SN487234	Microwave Circuits	2017/8/9	2018/8/8
ETSTW-RE 130	Handheld RF Spectrum Analyzer	N9340A	CN0147000204	Agilent	Pre-test Use	
ETSTW-RE 142	Amplifier	8447D	2805A03378	Agilent	2017/4/12	2018/4/11
ETSTW-RE 143	Humidity Temperature Meter	TES-1260	110104623	TES	2017/8/9	2018/8/8
ETSTW-RE 147	Bi-log Hybrid Antenna	MCTD 2786B	BLB16M04005	ETC	2017/3/22	2018/3/21
ETSTW-EMI 011	USB Compact Modulator	SFC-U	101689	R&S	2017/5/10	2018/5/9
ETSTW-GSM 002	Universal Radio Communication Tester	CMU 200	109439	R&S	2017/2/24	2018/2/23
ETSTW-GSM 003	Radio Communication Analyzer	MT8820C	6201342073	Anritsu	2017/2/10	2018/2/9
ETSTW-GSM 004	Wideband Radio Communication Tester	CMW500	128092	R&S	2016/12/15	2017/12/14
ETSTW-GSM 019	Band Reject Filter	WRCTF824/849-822/851-40/12+9SS	3	WI	2017/1/12	2018/1/11
ETSTW-GSM 020	Band Reject Filter	WRCD1747/1748-1743/1752-32/5SS	1	WI	2017/1/12	2018/1/11
ETSTW-GSM 021	Band Reject Filter	WRCD1879.5/1880.5-1875.5/1884.5-32/5SS	3	WI	2017/1/12	2018/1/11
ETSTW-GSM 022	Band Reject Filter	WRCT901.9/903.1-904.25-50/8SS	1	WI	2017/1/12	2018/1/11
ETSTW-GSM 023	Power Divider	4901.19.A	None	SUHNER	2016/9/14	2017/9/13
ETSTW-Cable 010	BNC Cable	RGS-142	None	THERMAX	2016/9/12	2017/9/11
ETSTW-Cable 011	SMA to N type Cable	RGU-400	None	THERMAX	Pre-test Use NCR	
ETSTW-Cable 012	BNC Cable	RGS-400	None	THERMAX	2016/9/12	2017/9/11
ETSTW-Cable 016	BNC Cable	Switch Box	B Cable 1	Schwarz beck	2017/2/23	2018/2/22
ETSTW-Cable 017	BNC Cable	X Cable	B Cable 2	Schwarz beck	2017/2/23	2018/2/22
ETSTW-Cable 018	BNC Cable	Y Cable	B Cable 3	Schwarz beck	2017/2/23	2018/2/22
ETSTW-Cable 019	BNC Cable	Z Cable	B Cable 4	Schwarz beck	2017/2/23	2018/2/22
ETSTW-Cable 020	N TYPE Cable	OATS Cable 1	N30N30-L335-15M	JYE BAO CO.,LTD.	2017/7/3	2018/7/2
ETSTW-Cable 022	N TYPE Cable	5006	0002	JYE BAO CO.,LTD.	2017/4/6	2018/4/5
ETSTW-Cable 026	Microwave Cable	SUCOFLEX 104	279075	HUBER+SUHNER	2017/3/1	2018/2/28
ETSTW-Cable 027	Microwave Cable	SUCOFLEX 104	279083	HUBER+SUHNER	2017/5/12	2018/5/11
ETSTW-Cable 028	Microwave Cable	FA147A0015M2020	30064-2	UTIFLEX	2016/9/20	2017/9/19
ETSTW-Cable 029	Microwave Cable	FA147A0015M2020	30064-3	UTIFLEX	2016/9/20	2017/9/19
ETSTW-Cable 030	Microwave Cable	SUCOFLEX 104 (S Cable 9)	279067	HUBER+SUHNER	2017/3/1	2018/2/28
ETSTW-Cable 031	Microwave Cable	SUCOFLEX 104 (S Cable 10)	238092	HUBER+SUHNER	2017/4/12	2018/4/11




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21707-17191-C-1

FCC ID: QSWDSCSCS1

ETSTW-Cable 043	Microwave Cable	SUCOFLEX 104	317576	HUBER+SUHNER	2017/4/12	2018/4/11
ETSTW-Cable 048	Microwave Cable	SUCOFLEX 104	325519	HUBER+SUHNER	2017/4/12	2018/4/11
ETSTW-Cable 058	Microwave Cable	SUCOFLEX 104	none	HUBER+SUHNER	2017/2/20	2018/2/19
ETSTW-Cable 064	Microwave Cable	SUCOFLEX 104	MY28891	HUBER+SUHNER	2017/4/12	2018/4/11
ETSTW-Cable 066	SMA type cable	32022	None	ASTROLAB	2016/9/12	2017/9/11
ETSTW-Cable 071	N TYPE CABLE	EMCCFD400-NM- NM-25000	170239	EMCI	2017/2/20	2018/2/19
WTSTW-SW 002	EMI TEST SOFTWARE	EZ EMC	None	Farad	Version ETS-03A1	
WTSTW-SW 006	EMI TEST SOFTWARE	e3	None	AUDIX	Version 9.161014	
WTSTW-SW 008	Signal studio	Agilent	None	AUDIX	Version 2.0.0.1	



2.4 General Test Procedure

POWER LINE CONDUCTED INTERFERENCE: The procedure used was ANSI STANDARD C63.10-2013 5.2 using a 50 μ H LISN (if necessary). Both lines were observed. The bandwidth of the spectrum analyzer was 10 kHz with an appropriate sweep speed.

RADIATION INTERFERENCE: The test procedure used was according to ANSI STANDARD C63.10-2013 6.4 employing a spectrum analyzer. For investigated frequency is equal to or below 1GHz, the RBW and VBW of the spectrum analyzer was 100 kHz and 100kHz respectively with an appropriate sweep speed. For investigated frequency is above 1GHz, both of RBW and VBW of the spectrum analyzer were 1 MHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dB μ V) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB.

Example:

Freq (MHz)	METER READING + ACF + CABLE LOSS (to the receiver) = FS
33	20 dB μ V + 10.36 dB + 6 dB = 36.36 dB μ V/m @3m


The EUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m (non metallic table) and arranged according to ANSI C63.10-2013 6.3.1. The table used for radiated measurements is capable of continuous rotation. The spectrum was scanned from 30 MHz to the frequency specified as follows:

- (1) If the intentional radiator operates below 10 GHz: to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
- (2) If the intentional radiator operates at or above 10 GHz and below 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 100 GHz, whichever is lower.
- (3) If the intentional radiator operates at or above 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 200 GHz, whichever is lower, unless specified otherwise elsewhere in the rules.
- (4) If the intentional radiator contains a digital device, regardless of whether this digital device controls the functions of the intentional radiator or the digital device is used for additional control or function purposes other than to enable the operation of the intentional radiator, the frequency range shall be investigated up to the range specified in paragraphs (a)(1)-(a)(3) of this section or the range applicable to the digital device, as shown in paragraph (b)(1) of this Section, whichever is the higher frequency range of investigation.

For hand-held devices, a exploratory test was performed with three (3) orthogonal planes to determine the highest emissions.

Measurements were made by Worldwide Testing Services(Taiwan) Co., Ltd. at the registered open field test site located at No.5-1, Lishui, Shuang Sing Village, Wanli Dist., New Taipei City 207, Taiwan (R.O.C.). The Registration Number: 930600.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.



Registration number: W6M21707-17191-C-1

FCC ID: QSWDSCSCS1

When the radiated emission limits are expressed in terms of the average value of the emission, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.

The formula is as follows:


Average = Peak + Duty Factor

Duty Factor = $20 \log (\text{dwell time}/T)$

$T = 100\text{ms}$ when the pulse train period is over 100 ms or the period of the pulse train.

Modified Limits for peak according to 15.35 (b) = Max Permitted average Limits + 20dB

ANSI STANDARD C63.10-2013 B.2.7: Any measurements that utilize special test software shall be indicated and referenced in the test report. During testing, test software 'EZ EMC' was used for setting up different operation modes.



Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M21707-17191-C-1

FCC ID: QSWDSCSCS1

3 Test results (enclosure)

TEST CASE	Para. Number	Required	Test passed	Test failed
Peak Output Power	15.247(d)	☒	☒	☐
Equivalent isotropically radiated Power	15.247(b)	☒	☒	☐
Spurious Emissions radiated – Transmitter operating	15.247(d): 15.209	☒	☒	☐
Band Edge Measurement	15.247(d)	☒	☒	☐
Minimum 6 dB Bandwidth	15.247(a)(2)	☒	☒	☐
Peak Power Spectral Density	15.247(e)	☒	☒	☐
Radiated Emission from Receiver part	15.109	☐	☐	☐
Power Line Conducted Emission	15.207	☐	☐	☐

The following is intentionally left blank.



Registration number: W6M21707-17191-C-1


FCC ID: QSWDSCSCS1

3.1 Peak Output Power (transmitter)

FCC Rule: 15.247(d)(3)


This measurement applies to equipment with an integral antenna and to equipment with an antenna connector and equipped with an antenna as declared by the applicant.

BLE




MAX OUTPUT POWER BT4.0 CH00

Date: 7.AUG.2017 16:24:48




Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1



MAX OUTPUT POWER BT4.0 CH19
Date: 7.AUG.2017 16:28:09



MAX OUTPUT POWER BT4.0 CH39
Date: 7.AUG.2017 16:30:33




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21707-17191-C-1

FCC ID: QSWDSCSCS1

ANT+



MAX OUTPUT POWER ANT+ 2457MHZ


Date: 7.AUG.2017 17:28:07

Limits:

Frequency MHz	Power dBm
902 - 928	30
2400 – 2483.5	30
5725 – 5850	30

In case of employing transmitter antennas having antenna gain > 6 dBi and using fixed point-to point operation consider §15.247 (b)(4)

Test equipment used: ETSTW-RE 055, ETSTW-RE 050



Registration number: W6M21707-17191-C-1

FCC ID: QSWDSCSCS1

3.2 RF Exposure Compliance Requirements

FCC Rule: 15.247(b)(3)

Test exclusion = max. conducted output power

Test exclusion = -4.21dBm (BLE)

Test exclusion = -1.92 dBm (ANT+)

RESULT:

Test standard : FCC KDB Publication
447498 D01 General RF Exposure Guidance v06

According to 447498 D01 General RF Exposure Guidance v06:

SAR evaluation, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

The enclosure of the device provides ≥ 0.5 cm separation from the antenna elements to significant metal parts of the enclosure to minimize potential perturbations.

Frequency Band: 2400-2483.5 MHz

Maximum Power fed to Antenna: 0.3793 mW (BLE)

Maximum Power fed to Antenna: 0.6427 mW (ANT+)

Separation distances:


Radiator to user: > 5 mm

Distance prescribed in user manual: > 5 mm

MHz	5	10	15	20	25	mm
2450	10	19	29	38	48	SAR Test Exclusion Threshold (mW)

MHz	30	35	40	45	50	mm
2450	57	67	77	86	96	SAR Test Exclusion Threshold (mW)

MHz	50	60	70	80	90	100	110	120	130	140	150	160	170	180	190	mm
2450	96	196	296	396	496	596	696	796	896	996	1096	1196	1296	1396	1496	mW



Registration number: W6M21707-17191-C-1

FCC ID: QSWDSCSCS1

3.3 Transmitter Radiated Emissions in Restricted Bands

FCC Rules: 15.247 (d), 15.205, 15.209, 15.35

Radiated emission measurements were performed from 30 MHz to 26500 MHz.

For radiated emission tests, the analyzer setting was as followings:

Frequency $\leq$ 1 GHz, RBW:100 kHz, VBW: 100 kHz (Peak measurements)

Frequency $>$ 1 GHz, RBW: 1 MHz, VBW: 1 MHz (Peak measurements)

Frequency $>$ 1 GHz , RBW:1 MHz , VBW: 10 Hz (Average measurements)

Limits.

For frequencies below 1GHz:

Frequency of Emission (MHz)	Field strength (microvolts/meter)	Field Strength (dB microvolts/meter)
30 - 88	100	40.0
88 - 216	150	43.5
216 - 960	200	46.0
Above	500	54.0

For frequencies above 1GHz (Average measurements).

Guidance on Measurement of Digit Transmission Systems:


“If the emission is pulsed, modify the unit for continuous operation, use the setting shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation.”

The correction factor, based on the total channel dwell time in a 100 ms period, may be mathematically applied to a measurement made with an average detector, to further reduce the value.

Duty cycle correction = $20 \log (\text{dwell time} / 100\text{ms})$

Note: No duty cycle correction was added to the reading of this EUT.

Explanation: See attached diagrams in Appendix.



Registration number: W6M21707-17191-C-1

FCC ID: QSWDSCSCS1

3.4 Spurious Emissions (tx)

Spurious emission was measured with modulation (declared by manufacturer).

In any 100 kHz bandwidth outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c))

FCC Rule: 15.247(d), 15.35

For out of band emissions that are close to or that exceed the 20 dB attenuation requirement described in the specification, radiated measurements were performed at a 3 m separation distance to determine whether these emissions complied with the general radiated emission requirement.

Limits:

For frequencies above 1GHz (Peak measurements).

Modified Limit for peak according to 15.35 (b) = Max Permitted average Limits + 20dB

For frequencies above 1GHz (Average measurements).

Max. reading – 20dB

Max. reading – 20 dB


Guidance on Measurement of Digit Transmission Systems:

“If the emission is pulsed, modify the unit for continuous operation, use the settings shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation.”

The correction factor, based on the total channel dwell time in a 100 ms period, may be mathematically applied to a measurement made with an average detector, to further reduce the value.

Duty Cycle correction = $20 \log (\text{dwell time}/100\text{ms})$

Note: No duty cycle correction was added to the reading of EUT.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21707-17191-C-1

FCC ID: QSWDSCSCS1

SAMPLE CALCULATION OF LIMIT. All results will be updated by an automatic measuring system in accordance with point 2.3.

Calculation of test results:

Such factors like antenna correction, cable loss, external attenuation etc. are already included in the provided measurement results. This is done by using validated test software and calibrated test system according the accreditation requirements.

The peak and average spurious emission plots was measured with the average limits.

In the Table being listed the critical peak and average value and exhibit the compliance with the above calculated Limits.

If in the column's correction factor states a value then the max. Field strength in the same row is corrected by a value gained from the "Correction Factor".

Summary table with radiated data of the test plots

Model: ZA5D

Date: --

Mode: --

Temperature: -- °C Engineer: --

Polarization: --

Humidity: -- %

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--

Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result (dBuV/m)		Limit (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (m)
	Peak	Ave.		Peak	Ave.	Peak	Ave.			
--	--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--	--

Note

1. **Correction Factor = Antenna factor + Cable loss - Preamplifier**
2. **The formula of measured value as: Test Result = Reading + Correction Factor**
3. **Detector function in the form : PK = Peak, QP = Quasi Peak, AV = Average**
4. **All not in the table noted test results are more than 20 dB below the relevant limits.**
5. **Measurement uncertainty for 3m measurement: 30-1000 MHz = ± 3.30 dB, 1-18 GHz = ± 2.28 dB, 18-40 GHz = ± 2.19 dB ; Reported uncertainties represent expanded uncertainties expressed at approximately the 95% confidence level using a coverage factor of k = 2.**
6. **Please see attached diagrams in Appendix.**

TEST RESULT (Transmitter): The unit DOES meet the FCC requirements.

Test equipment used: ETSTW-RE 004, ETSTW-RE 030, ETSTW-RE 062, ETSTW-RE 142, ETSTW-RE 147, ETSTW-RE 088, ETSTW-RE 018

Registration number: W6M21707-17191-C-1


FCC ID: QSWDSCSCS1

3.5 Radiated Emission on the band edge


According to FCC rules part 15 subpart C §15.247(d) in any 100 kHz bandwidth outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required.

In addition radiated emission which fall in the restricted bands, as defined in section 15.205(a), must also with the radiated emission limits.


BLE



BANDEDGE BT4.0 CH00
Date: 7.AUG.2017 15:53:23




Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1




BANDEDGE BT4.0 CH39
Date: 7.AUG.2017 15:58:35


ANT+



BANDEDGE ANT+ 2457MHz
Date: 7.AUG.2017 17:24:51



Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1




BANDEDGE ANT+ 2457MHz
Date: 7.AUG.2017 17:25:20

Limit:

Frequency Range / MHz	Limit
902 –928	- 20 dB
2400 – 2483.5	
5725 - 5850	

Test equipment used: ETSTW-RE 055, ETSTW-RE 050




Registration number: W6M21707-17191-C-1

FCC ID: QSWDSCSCS1


3.6 Minimum 6 dB Bandwidth

The analyzer ResBW was set to 100 kHz. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A PEAK reading was taken, two markers were set 6 dB below the maximum level on the right and the left side of the emission. The 6 dB bandwidth is the frequency difference between the two markers.


BLE




6DB BANDWIDTH BT4.0 CH00
Date: 7.AUG.2017 15:19:45



Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1



6DB BANDWIDTH BT4.0 CH19
Date: 7.AUG.2017 15:42:11



6DB BANDWIDTH BT4.0 CH39
Date: 7.AUG.2017 15:44:49




ANT+

Date: 7.AUG.2017 17:21:25

Limits:

Frequency Range MHz	Limits
902-928	min 500 kHz
2400-2483.5	min 500 kHz
5725-5850	min 500 kHz

Test equipment used: ETSTW-RE 055, ETSTW-RE 050



Registration number: W6M21707-17191-C-1


FCC ID: QSWDSCSCS1

3.7 Peak Power Spectral Density


Peak Power Spectral density is a measured at low, middle and high channel.

The peak output power is measured with a measurement bandwidth of 10 MHz and displayed on diagram together with Peak Power Spectral Density result which was measured with a bandwidth of 3 kHz, appreciate frequency span and sweep time.

BLE




POWER DENSITY BT4.0 CH00
Date: 7.AUG.2017 16:34:38




Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1



POWER DENSITY BT4.0 CH19
Date: 7.AUG.2017 16:37:01



POWER DENSITY BT4.0 CH39
Date: 7.AUG.2017 16:38:53




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21707-17191-C-1

FCC ID: QSWDSCSCS1

ANT+




POWER DENSITY ANT+ 2457MHZ

Date: 7.AUG.2017 17:29:11

Limits:

Frequency Range MHz	dBm
902-928	8
2400-2483.5	8
5725-5850	8

Test equipment used: ETSTW-RE 055, ETSTW-RE 050



Registration number: W6M21707-17191-C-1

FCC ID: QSWDSCSCS1

3.8 Radiated Emission from Receiver Part

Model: ZA5D

Date: --

Mode: --

Temperature: -- °C Engineer: --

Polarization: --


Humidity: -- %

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--

Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result (dBuV/m)		Limit (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (m)
	Peak	Ave.		Peak	Ave.	Peak	Ave.			
--	--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--	--

Note

1. **Correction Factor = Antenna factor + Cable loss - Preamplifier**
2. **The formula of measured value as: Test Result = Reading + Correction Factor**
3. **Detector function in the form : PK = Peak, QP = Quasi Peak, AV = Average**
4. **All not in the table noted test results are more than 20 dB below the relevant limits.**
5. **Measurement uncertainty for 3m measurement: 30-1000 MHz = ± 3.30 dB, 1-18 GHz = ± 2.28 dB, 18-40 GHz = ± 2.19 dB ; Reported uncertainties represent expanded uncertainties expressed at approximately the 95% confidence level using a coverage factor of k = 2.**
6. **The test results are listed in the separated test report no.: W6M21707-17191-P-15B.**



Registration number: W6M21707-17191-C-1

FCC ID: QSWDSCSCS1

3.9 Power Line Conducted Emission

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the table bellows with this provision shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminals.

This measurement was transact first with instrumentation using an average and peak detector and a 10 kHz bandwidth. If the peak detector achieves a calculated level, the measurement is repeated by an instrumentation using a quasi-peak detector.

Model:	ZA5D		Date:	--				
Mode:	--		Temperature:	--	°C	Engineer:		--
Polarization:	--		Humidity:	--	%			
Frequency (MHz)	Reading (dBuV) QP Ave.		Factor (dB) Corr.	Result (dBuV) QP Ave.		Limit (dBuV) QP Ave.		Margin (dB)
--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--

Polarization: --


Frequency (MHz)	Reading (dBuV) QP Ave.		Factor (dB) Corr.	Result (dBuV) QP Ave.		Limit (dBuV) QP Ave.		Margin (dB)
--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--

- Note:**
1. The formula of measured value as: **Test Result = Reading + Correction Factor**
 2. The **Correction Factor = Cable Loss + LISN Insertion Loss + Pulse Limit Loss**
 3. Detector function in the form : **PK = Peak, QP = Quasi Peak, AV = Average**
 4. All not in the table noted test results are more than 20 dB below the relevant limits.
 5. Measurement uncertainty = ± 0.74 dB; Reported uncertainties represent expanded uncertainties expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.
 6. This test is not required because the EUT is battery-used.

Limits:

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi Peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

Test equipment used: ETSTW-CE 001, ETSTW-CE 016, ETSTW-CE 028.




Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1

Appendix

Measurement diagrams

Spurious Emissions radiated



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21707-17191-C-1

FCC ID: QSWDSCSCS1


BLE



Address:NO. 35, Aly. 21, Ln 228, Ankang Rd, Neihu, Taipei

Tel:+886-2-6606-8877

Fax:+886-2-6606-8875



Site : 966 chamber

Condition: FCC_part 15B RE-Class C_30-1000MHz (3m) 3m horizontal

EUT: W6M21707-17191


Mode:

Power: 3 Vd.c.

Operator: Leon

Note: BT4.0, TX, 2402

	Freq	Read Level	Remark	Ant Factor	Level	Limit Line	APos	TPos	Over Limit
	MHz	dBuV		dB/m	dBuV/m	dBuV/m	cm	deg	dB
1	263.267	34.30	peak	-7.05	27.25	46.00	100	151	-18.75
2 PP	298.257	43.35	peak	-5.98	37.37	46.00	100	164	-8.63




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1




Address: NO. 35, Aly. 21, Ln 228, Ankang Rd, Neihu, Taipei
Tel: +886-2-6606-8877
Fax: +886-2-6606-8875



Site : 966 chamber
Condition: FCC_part 15B RE-Class C_30-1000MHz (3m) 3m Vertical
EUT: W6M21707-17191
Mode:
Power: 3 Vd.c.
Operator: Leon
Note: BT4.0, TX, 2402

	Freq	Read Level	Remark	Ant Factor	Level	Limit Line	APos	TPos	Over Limit
	MHz	dBuV		dB/m	dBuV/m	dBuV/m	cm	deg	dB
1	35.832	39.13	peak	-8.89	30.24	40.00	100	94	-9.76
2 PP	47.495	43.51	peak	-10.23	33.28	40.00	100	17	-6.72




Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1



Address: NO. 35, Aly. 21, Ln 228, Ankang Rd, Neihu, Taipei
Tel: +886-2-6606-8877
Fax: +886-2-6606-8875



Site : 966 chamber
Condition: FCC_part 15B RE-Class C_Above 1GHz_PK 3m horizontal
EUT: W6M21707-17191
Mode:
Power: 3 Vd.c.
Operator: Leon
Note: BT4.0, TX, 2402




Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1



Address: NO. 35, Aly. 21, Ln 228, Ankang Rd, Neihu, Taipei
Tel: +886-2-6606-8877
Fax: +886-2-6606-8875




Site : 966 chamber
Condition: FCC_part 15B RE-Class C_Above 1GHz_PK 3m Vertical
EUT: W6M21707-17191
Mode:
Power: 3 Vd.c.
Operator: Leon
Note: BT4.0, TX, 2402



Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1




Address: NO. 35, Aly. 21, Ln 228, Ankang Rd, Neihu, Taipei
Tel: +886-2-6606-8877
Fax: +886-2-6606-8875



Site : 966 chamber
Condition: FCC_part 15B RE-Class C_Above 1GHz_PK 3m horizontal
EUT: W6M21707-17191
Mode:
Power: 3 Vd.c.
Operator: Leon
Note: BT4.0, TX, 2402


	Freq	Read Level	Remark	Ant Factor	Level	Limit Line	APos	TPos	Over Limit
	MHz	dBuV		dB/m	dBuV/m	dBuV/m	cm	deg	dB
1	4801.603	53.94	peak	0.08	54.02	74.00	160	56	-19.98
2	4801.603	45.58	average	0.08	45.66	54.00	160	56	-8.34
3 PK	7206.124	57.61	peak	5.06	62.67	74.00	225	188	-11.33
4 PP	7206.124	47.57	average	5.06	52.63	54.00	225	188	-1.37



Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1




Address: NO. 35, Aly. 21, Ln 228, Ankang Rd, Neihu, Taipei
Tel: +886-2-6606-8877
Fax: +886-2-6606-8875



Site : 966 chamber
Condition: FCC_part 15B RE-Class C_Above 1GHz_PK 3m Vertical
EUT: W6M21707-17191
Mode:
Power: 3 Vd.c.
Operator: Leon
Note: BT4.0, TX, 2402

	Freq	Read Level	Remark	Ant Factor	Level	Limit Line	APos	TPos	Over Limit
	MHz	dBuV		dB/m	dBuV/m	dBuV/m	cm	deg	dB
1	4801.603	53.09	peak	0.08	53.17	74.00	150	219	-20.83
2	4801.603	44.67	average	0.08	44.75	54.00	150	219	-9.25
3 PK	7206.413	55.68	peak	5.06	60.74	74.00	150	180	-13.26
4 PP	7206.413	46.17	average	5.06	51.23	54.00	150	180	-2.77




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1




Address: NO. 35, Aly. 21, Ln 228, Ankang Rd, Neihu, Taipei
Tel: +886-2-6606-8877
Fax: +886-2-6606-8875



Site : 966 chamber
Condition: FCC_part 15B RE-Class C_Above 1GHz_PK 3m horizontal
EUT: W6M21707-17191
Mode:
Power: 3 Vd.c.
Operator: Leon
Note: BT4.0, TX, 2402


	Freq	Read Level	Remark	Ant Factor	Level	Limit Line	APos	TPos	Over Limit
	MHz	dBuV		dB/m	dBuV/m	dBuV/m	cm	deg	dB
1	9608.000	36.31	peak	7.96	44.27	74.00	150	118	-29.73
2	PP12010.000	34.70	peak	12.90	47.60	74.00	150	360	-26.40



Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1




Address: NO. 35, Aly. 21, Ln 228, Ankang Rd, Neihu, Taipei
Tel: +886-2-6606-8877
Fax: +886-2-6606-8875



Site : 966 chamber
Condition: FCC_part 15B RE-Class C_Above 1GHz_PK 3m Vertical
EUT: W6M21707-17191
Mode:
Power: 3 Vd.c.
Operator: Leon
Note: BT4.0, TX, 2402

	Freq	Read Level	Remark	Ant Factor	Level	Limit Line	APos	TPos	Over Limit
	MHz	dBuV		dB/m	dBuV/m	dBuV/m	cm	deg	dB
1	9608.000	36.13	peak	7.96	44.09	74.00	150	196	-29.91
2	PP12010.000	35.00	peak	12.90	47.90	74.00	150	360	-26.10




Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1



Address: NO. 35, Aly. 21, Ln 228, Ankang Rd, Neihu, Taipei
Tel: +886-2-6606-8877
Fax: +886-2-6606-8875



Site : 966 chamber
Condition: FCC_part 15B RE-Class C_Above 1GHz_PK 3m horizontal
EUT: W6M21707-17191
Mode:
Power: 3 Vd.c.
Operator: Leon
Note: BT4.0, TX, 2402




Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1



Address: NO. 35, Aly. 21, Ln 228, Ankang Rd, Neihu, Taipei
Tel: +886-2-6606-8877
Fax: +886-2-6606-8875



Site : 966 chamber
Condition: FCC_part 15B RE-Class C_Above 1GHz_PK 3m Vertical
EUT: W6M21707-17191
Mode:
Power: 3 Vd.c.
Operator: Leon
Note: BT4.0, TX, 2402




Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1



Address: NO. 35, Aly. 21, Ln 228, Ankang Rd, Neihu, Taipei
Tel: +886-2-6606-8877
Fax: +886-2-6606-8875



Site : 966 chamber
Condition: FCC_part 15B RE-Class C_Above 1GHz_PK 3m horizontal
EUT: W6M21707-17191
Mode:
Power: 3 Vd.c.
Operator: Leon
Note: BT4.0, TX, 2402




Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1



Address: NO. 35, Aly. 21, Ln 228, Ankang Rd, Neihu, Taipei
Tel: +886-2-6606-8877
Fax: +886-2-6606-8875



Site : 966 chamber
Condition: FCC_part 15B RE-Class C_Above 1GHz_PK 3m Vertical
EUT: W6M21707-17191
Mode:
Power: 3 Vd.c.
Operator: Leon
Note: BT4.0, TX, 2402




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1




Address: NO. 35, Aly. 21, Ln 228, Ankang Rd, Neihu, Taipei
Tel: +886-2-6606-8877
Fax: +886-2-6606-8875



Site : 966 chamber
Condition: FCC_part 15B RE-Class C_30-1000MHz (3m) 3m horizontal
EUT: W6M21707-17191
Mode:
Power: 3 Vd.c.
Operator: Leon
Note: BT4.0, TX, 2440

	Freq	Read Level	Remark	Ant Factor	Level	Limit Line	APos	TPos	Over Limit
	MHz	dBuV		dB/m	dBuV/m	dBuV/m	cm	deg	dB
1	214.669	35.92	peak	-10.33	25.59	43.50	100	28	-17.91
2 PP	300.200	43.09	peak	-5.94	37.15	46.00	100	162	-8.85




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1




Address: NO. 35, Aly. 21, Ln 228, Ankang Rd, Neihu, Taipei
Tel: +886-2-6606-8877
Fax: +886-2-6606-8875



Site : 966 chamber
Condition: FCC_part 15B RE-Class C_30-1000MHz (3m) 3m Vertical
EUT: W6M21707-17191
Mode:
Power: 3 Vd.c.
Operator: Leon
Note: BT4.0, TX, 2440

	Freq	Read Level	Remark	Ant Factor	Level	Limit Line	APos	TPos	Over Limit
	MHz	dBuV		dB/m	dBuV/m	dBuV/m	cm	deg	dB
1	35.832	39.08	peak	-8.89	30.19	40.00	100	190	-9.81
2 PP	47.495	43.18	peak	-10.23	32.95	40.00	100	42	-7.05




Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1



Address: NO. 35, Aly. 21, Ln 228, Ankang Rd, Neihu, Taipei
Tel: +886-2-6606-8877
Fax: +886-2-6606-8875



Site : 966 chamber
Condition: FCC_part 15B RE-Class C_Above 1GHz_PK 3m horizontal
EUT: W6M21707-17191
Mode:
Power: 3 Vd.c.
Operator: Leon
Note: BT4.0, TX, 2440




Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1



Address: NO. 35, Aly. 21, Ln 228, Ankang Rd, Neihu, Taipei
Tel: +886-2-6606-8877
Fax: +886-2-6606-8875



Site : 966 chamber
Condition: FCC_part 15B RE-Class C_Above 1GHz_PK 3m Vertical
EUT: W6M21707-17191
Mode:
Power: 3 Vd.c.
Operator: Leon
Note: BT4.0, TX, 2440




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1




Address: NO. 35, Aly. 21, Ln 228, Ankang Rd, Neihu, Taipei
Tel: +886-2-6606-8877
Fax: +886-2-6606-8875



Site : 966 chamber
Condition: FCC_part 15B RE-Class C_Above 1GHz_PK 3m horizontal
EUT: W6M21707-17191
Mode:
Power: 3 Vd.c.
Operator: Leon
Note: BT4.0, TX, 2440


	Freq	Read Level	Remark	Ant Factor	Level	Limit Line	APos	TPos	Over Limit
	MHz	dBuV			dB/m	dBuV/m	cm	deg	dB
1	4881.764	51.99	peak	0.17	52.16	74.00	100	187	-21.84
2	4881.764	45.08	average	0.17	45.25	54.00	100	187	-8.75
3	PK 7320.087	55.50	peak	5.10	60.60	74.00	205	218	-13.40
4	PP 7320.087	45.39	average	5.10	50.49	54.00	205	218	-3.51



Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1




Address: NO. 35, Aly. 21, Ln 228, Ankang Rd, Neihu, Taipei
Tel: +886-2-6606-8877
Fax: +886-2-6606-8875



Site : 966 chamber
Condition: FCC_part 15B RE-Class C_Above 1GHz_PK 3m Vertical
EUT: W6M21707-17191
Mode:
Power: 3 Vd.c.
Operator: Leon
Note: BT4.0, TX, 2440

		Read		Ant	Limit	APos	TPos	Over
	Freq	Level	Remark	Factor	Level	Line		Limit
	MHz	dBuV		dB/m	dBuV/m	dBuV/m	cm	deg
1	4881.764	52.02	peak	0.17	52.19	74.00	150	213
2	4881.764	43.60	average	0.17	43.77	54.00	150	213
3 PK	7318.637	55.15	peak	5.10	60.25	74.00	150	62
4 PP	7318.637	46.57	average	5.10	51.67	54.00	150	62




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1




Address: NO. 35, Aly. 21, Ln 228, Ankang Rd, Neihu, Taipei
Tel: +886-2-6606-8877
Fax: +886-2-6606-8875



Site : 966 chamber
Condition: FCC_part 15B RE-Class C_Above 1GHz_PK 3m horizontal
EUT: W6M21707-17191
Mode:
Power: 3 Vd.c.
Operator: Leon
Note: BT4.0, TX, 2440

	Freq	Read Level	Remark	Ant Factor	Level	Limit Line	APos	TPos	Over Limit
	MHz	dBuV		dB/m	dBuV/m	dBuV/m	cm	deg	dB
1	9760.000	34.50	peak	8.21	42.71	74.00	150	75	-31.29
2	PP12200.000	34.19	peak	14.09	48.28	74.00	150	90	-25.72




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1




Address: NO. 35, Aly. 21, Ln 228, Ankang Rd, Neihu, Taipei
Tel: +886-2-6606-8877
Fax: +886-2-6606-8875



Site : 966 chamber
Condition: FCC_part 15B RE-Class C_Above 1GHz_PK 3m Vertical
EUT: W6M21707-17191
Mode:
Power: 3 Vd.c.
Operator: Leon
Note: BT4.0, TX, 2440

	Freq	Read Level	Remark	Ant Factor	Level	Limit Line	APos	TPos	Over Limit
	MHz	dBuV		dB/m	dBuV/m	dBuV/m	cm	deg	dB
1	9760.000	35.20	peak	8.21	43.41	74.00	150	158	-30.59
2	PP12200.000	34.08	peak	14.09	48.17	74.00	150	261	-25.83




Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1



Address: NO. 35, Aly. 21, Ln 228, Ankang Rd, Neihu, Taipei
Tel: +886-2-6606-8877
Fax: +886-2-6606-8875



Site : 966 chamber
Condition: FCC_part 15B RE-Class C_Above 1GHz_PK 3m horizontal
EUT: W6M21707-17191
Mode:
Power: 3 Vd.c.
Operator: Leon
Note: BT4.0, TX, 2440




Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1



Address: NO. 35, Aly. 21, Ln 228, Ankang Rd, Neihu, Taipei
Tel: +886-2-6606-8877
Fax: +886-2-6606-8875



Site : 966 chamber
Condition: FCC_part 15B RE-Class C_Above 1GHz_PK 3m Vertical
EUT: W6M21707-17191
Mode:
Power: 3 Vd.c.
Operator: Leon
Note: BT4.0, TX, 2440




Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1



Address: NO. 35, Aly. 21, Ln 228, Ankang Rd, Neihu, Taipei
Tel: +886-2-6606-8877
Fax: +886-2-6606-8875



Site : 966 chamber
Condition: FCC_part 15B RE-Class C_Above 1GHz_PK 3m horizontal
EUT: W6M21707-17191
Mode:
Power: 3 Vd.c.
Operator: Leon
Note: BT4.0, TX, 2440




Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1



Address: NO. 35, Aly. 21, Ln 228, Ankang Rd, Neihu, Taipei
Tel: +886-2-6606-8877
Fax: +886-2-6606-8875



Site : 966 chamber
Condition: FCC_part 15B RE-Class C_Above 1GHz_PK 3m Vertical
EUT: W6M21707-17191
Mode:
Power: 3 Vd.c.
Operator: Leon
Note: BT4.0, TX, 2440




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1




Address: NO. 35, Aly. 21, Ln 228, Ankang Rd, Neihu, Taipei
Tel: +886-2-6606-8877
Fax: +886-2-6606-8875



Site : 966 chamber
Condition: FCC_part 15B RE-Class C_30-1000MHz (3m) 3m horizontal
EUT: W6M21707-17191
Mode:
Power: 3 Vd.c.
Operator: Leon
Note: BT4.0,TX,2480

	Freq	Read Level	Remark	Ant Factor	Level	Limit Line	APos	TPos	Over Limit
	MHz	dBuV		dB/m	dBuV/m	dBuV/m	cm	deg	dB
1	47.495	30.83	peak	-10.23	20.60	40.00	100	305	-19.40
2 PP	300.200	43.17	peak	-5.94	37.23	46.00	100	164	-8.77




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1




Address: NO. 35, Aly. 21, Ln 228, Ankang Rd, Neihu, Taipei
Tel: +886-2-6606-8877
Fax: +886-2-6606-8875



Site : 966 chamber
Condition: FCC_part 15B RE-Class C_30-1000MHz (3m) 3m Vertical
EUT: W6M21707-17191
Mode:
Power: 3 Vd.c.
Operator: Leon
Note: BT4.0, TX, 2480

	Freq	Read Level	Remark	Ant Factor	Level	Limit Line	APos	TPos	Over Limit
	MHz	dBuV		dB/m	dBuV/m	dBuV/m	cm	deg	dB
1	35.832	40.05	peak	-8.89	31.16	40.00	100	242	-8.84
2 PP	47.495	43.16	peak	-10.23	32.93	40.00	100	18	-7.07




Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1



Address: NO. 35, Aly. 21, Ln 228, Ankang Rd, Neihu, Taipei
Tel: +886-2-6606-8877
Fax: +886-2-6606-8875



Site : 966 chamber
Condition: FCC_part 15B RE-Class C_Above 1GHz_PK 3m horizontal
EUT: W6M21707-17191
Mode:
Power: 3 Vd.c.
Operator: Leon
Note: BT4.0, TX, 2480




Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1



Address: NO. 35, Aly. 21, Ln 228, Ankang Rd, Neihu, Taipei
Tel: +886-2-6606-8877
Fax: +886-2-6606-8875



Site : 966 chamber
Condition: FCC_part 15B RE-Class C_Above 1GHz_PK 3m Vertical
EUT: W6M21707-17191
Mode:
Power: 3 Vd.c.
Operator: Leon
Note: BT4.0, TX, 2480




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1




Address: NO. 35, Aly. 21, Ln 228, Ankang Rd, Neihu, Taipei
Tel: +886-2-6606-8877
Fax: +886-2-6606-8875



Site : 966 chamber
Condition: FCC_part 15B RE-Class C_Above 1GHz_PK 3m horizontal
EUT: W6M21707-17191
Mode:
Power: 3 Vd.c.
Operator: Leon
Note: BT4.0, TX, 2480

	Freq	Read Level	Remark	Ant Factor	Level	Limit Line	APos	TPos	Over Limit
	MHz	dBuV		dB/m	dBuV/m	dBuV/m	cm	deg	dB
1	4953.908	53.08	peak	0.21	53.29	74.00	165	240	-20.71
2	4953.908	46.32	average	0.21	46.53	54.00	165	240	-7.47
3 PK	7440.128	54.92	peak	5.18	60.10	74.00	350	184	-13.90
4 PP	7440.128	46.17	average	5.18	51.35	54.00	350	184	-2.65




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1




Address: NO. 35, Aly. 21, Ln 228, Ankang Rd, Neihu, Taipei
Tel: +886-2-6606-8877
Fax: +886-2-6606-8875



Site : 966 chamber
Condition: FCC_part 15B RE-Class C_Above 1GHz_PK 3m Vertical
EUT: W6M21707-17191
Mode:
Power: 3 Vd.c.
Operator: Leon
Note: BT4.0,TX,2480

	Freq	Read Level	Remark	Ant Factor	Level	Limit Line	APos	TPos	Over Limit
	MHz	dBuV		dB/m	dBuV/m	dBuV/m	cm	deg	dB
1	4961.924	53.98	peak	0.21	54.19	74.00	150	271	-19.81
2	4961.924	44.30	average	0.21	44.51	54.00	150	271	-9.49
3 PK	7446.894	55.37	peak	5.18	60.55	74.00	150	219	-13.45
4 PP	7446.894	46.45	average	5.18	51.63	54.00	150	219	-2.37




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1




Address: NO. 35, Aly. 21, Ln 228, Ankang Rd, Neihu, Taipei
Tel: +886-2-6606-8877
Fax: +886-2-6606-8875



Site : 966 chamber
Condition: FCC_part 15B RE-Class C_Above 1GHz_PK 3m horizontal
EUT: W6M21707-17191
Mode:
Power: 3 Vd.c.
Operator: Leon
Note: BT4.0, TX, 2480

	Read	Ant	Limit	APos	TPos	Over
Freq	Level	Factor	Level	Line		Limit
MHz	dBuV		dB/m	dBuV/m	dBuV/m	
1 9920.000	34.47	peak	8.55	43.02	74.00	150 359 -30.98
2 PP12400.000	32.81	peak	14.41	47.22	74.00	150 343 -26.78




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1




Address: NO. 35, Aly. 21, Ln 228, Ankang Rd, Neihu, Taipei
Tel: +886-2-6606-8877
Fax: +886-2-6606-8875



Site : 966 chamber
Condition: FCC_part 15B RE-Class C_Above 1GHz_PK 3m Vertical
EUT: W6M21707-17191
Mode:
Power: 3 Vd.c.
Operator: Leon
Note: BT4.0, TX, 2480

		Read		Ant		Limit	APos	TPos	Over
	Freq	Level	Remark	Factor	Level	Line			Limit
	MHz	dBuV		dB/m	dBuV/m	dBuV/m	cm	deg	dB
1	9920.000	35.11	peak	8.55	43.66	74.00	150	325	-30.34
2	PP12400.000	33.66	peak	14.41	48.07	74.00	150	261	-25.93




Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1



Address: NO. 35, Aly. 21, Ln 228, Ankang Rd, Neihu, Taipei
Tel: +886-2-6606-8877
Fax: +886-2-6606-8875



Site : 966 chamber
Condition: FCC_part 15B RE-Class C_Above 1GHz_PK 3m horizontal
EUT: W6M21707-17191
Mode:
Power: 3 Vd.c.
Operator: Leon
Note: BT4.0, TX, 2480




Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1



Address: NO. 35, Aly. 21, Ln 228, Ankang Rd, Neihu, Taipei
Tel: +886-2-6606-8877
Fax: +886-2-6606-8875



Site : 966 chamber
Condition: FCC_part 15B RE-Class C_Above 1GHz_PK 3m Vertical
EUT: W6M21707-17191
Mode:
Power: 3 Vd.c.
Operator: Leon
Note: BT4.0, TX, 2480




Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1



Address: NO. 35, Aly. 21, Ln 228, Ankang Rd, Neihu, Taipei
Tel: +886-2-6606-8877
Fax: +886-2-6606-8875



Site : 966 chamber
Condition: FCC_part 15B RE-Class C_Above 1GHz_PK 3m horizontal
EUT: W6M21707-17191
Mode:
Power: 3 Vd.c.
Operator: Leon
Note: BT4.0, TX, 2480




Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1



Address: NO. 35, Aly. 21, Ln 228, Ankang Rd, Neihu, Taipei
Tel: +886-2-6606-8877
Fax: +886-2-6606-8875



Site : 966 chamber
Condition: FCC_part 15B RE-Class C_Above 1GHz_PK 3m Vertical
EUT: W6M21707-17191
Mode:
Power: 3 Vd.c.
Operator: Leon
Note: BT4.0, TX, 2480



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21707-17191-C-1

FCC ID: QSWDSCSCS1


ANT+



Address: NO. 35, Aly. 21, Ln 228, Ankang Rd, Neihu, Taipei

Tel: +886-2-6606-8877

Fax: +886-2-6606-8875



Site : 966 chamber

Condition: FCC_part 15B RE-Class C_30-1000MHz (3m) 3m horizontal

EUT: W6M21707-17191


Mode:

Power: 3 Vd.c.

Operator: Leon

Note: ANT+, TX, 2457

	Freq	Read Level	Remark	Ant Factor	Level	Limit Line	APos	TPos	Over Limit
	MHz	dBuV		dB/m	dBuV/m	dBuV/m	cm	deg	dB
1	47.495	30.55	peak	-10.23	20.32	40.00	100	307	-19.68
2	191.343	34.90	peak	-11.12	23.78	43.50	100	196	-19.72
3	214.669	37.85	peak	-10.33	27.52	43.50	100	15	-15.98
4 PP	300.200	41.67	peak	-5.94	35.73	46.00	100	170	-10.27




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1




Address: NO. 35, Aly. 21, Ln 228, Ankang Rd, Neihu, Taipei
Tel: +886-2-6606-8877
Fax: +886-2-6606-8875



Site : 966 chamber
Condition: FCC_part 15B RE-Class C_30-1000MHz (3m) 3m Vertical
EUT: W6M21707-17191
Mode:
Power: 3 Vd.c.
Operator: Leon
Note: ANT+, TX, 2457

	Freq	Read Level	Remark	Ant Factor	Level	Limit Line	APos	TPos	Over Limit
	MHz	dBuV		dB/m	dBuV/m	dBuV/m	cm	deg	dB
1	35.832	39.27	peak	-8.89	30.38	40.00	100	117	-9.62
2 PP	47.495	43.68	peak	-10.23	33.45	40.00	100	91	-6.55
3	70.822	37.90	peak	-13.78	24.12	40.00	100	149	-15.88
4	119.419	29.66	peak	-6.90	22.76	43.50	100	188	-20.74




Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1



Address: NO. 35, Aly. 21, Ln 228, Ankang Rd, Neihu, Taipei
Tel: +886-2-6606-8877
Fax: +886-2-6606-8875



Site : 966 chamber
Condition: FCC_part 15B RE-Class C_Above 1GHz_PK 3m horizontal
EUT: W6M21707-17191
Mode:
Power: 3 Vd.c.
Operator: Leon
Note: ANT+,TX,2457




Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1



Address: NO. 35, Aly. 21, Ln 228, Ankang Rd, Neihu, Taipei
Tel: +886-2-6606-8877
Fax: +886-2-6606-8875



Site : 966 chamber
Condition: FCC_part 15B RE-Class C_Above 1GHz_PK 3m Vertical
EUT: W6M21707-17191
Mode:
Power: 3 Vd.c.
Operator: Leon
Note: ANT+,TX,2457




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1




Address: NO. 35, Aly. 21, Ln 228, Ankang Rd, Neihu, Taipei
Tel: +886-2-6606-8877
Fax: +886-2-6606-8875



Site : 966 chamber
Condition: FCC_part 15B RE-Class C_Above 1GHz_PK 3m horizontal
EUT: W6M21707-17191
Mode:
Power: 3 Vd.c.
Operator: Leon
Note: ANT+, TX, 2457

	Freq	Read Level	Remark	Ant Factor	Level	Limit Line	APos	TPos	Over Limit
	MHz	dBuV		dB/m	dBuV/m	dBuV/m	cm	deg	dB
1 PK	4913.828	50.35	peak	0.19	50.54	74.00	150	120	-23.46
2 PP	4913.828	41.44	average	0.19	41.63	54.00	150	120	-12.37
3	7371.000	41.16	peak	5.16	46.32	74.00	150	159	-27.68




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1




Address: NO. 35, Aly. 21, Ln 228, Ankang Rd, Neihu, Taipei
Tel: +886-2-6606-8877
Fax: +886-2-6606-8875



Site : 966 chamber
Condition: FCC_part 15B RE-Class C_Above 1GHz_PK 3m Vertical
EUT: W6M21707-17191
Mode:
Power: 3 Vd.c.
Operator: Leon
Note: ANT+,TX,2457

	Freq	Read Level	Remark	Ant Factor	Level	Limit Line	APos	TPos	Over Limit
	MHz	dBuV		dB/m	dBuV/m	dBuV/m	cm	deg	dB
1	PK 4913.828	48.90	peak	0.19	49.09	74.00	150	302	-24.91
2	PP 4913.828	40.37	average	0.19	40.56	54.00	150	302	-13.44
3	7371.000	40.70	peak	5.16	45.86	74.00	150	100	-28.14




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1




Address: NO. 35, Aly. 21, Ln 228, Ankang Rd, Neihu, Taipei
Tel: +886-2-6606-8877
Fax: +886-2-6606-8875



Site : 966 chamber
Condition: FCC_part 15B RE-Class C_Above 1GHz_PK 3m horizontal
EUT: W6M21707-17191
Mode:
Power: 3 Vd.c.
Operator: Leon
Note: ANT+, TX, 2457


	Freq	Read Level	Remark	Ant Factor	Level	Limit Line	APos	TPos	Over Limit
	MHz	dBuV		dB/m	dBuV/m	dBuV/m	cm	deg	dB
1	9828.000	34.99	peak	8.39	43.38	74.00	150	158	-30.62
2	PP12285.000	34.40	peak	13.90	48.30	74.00	150	360	-25.70



Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1




Address: NO. 35, Aly. 21, Ln 228, Ankang Rd, Neihu, Taipei
Tel: +886-2-6606-8877
Fax: +886-2-6606-8875



Site : 966 chamber
Condition: FCC_part 15B RE-Class C_Above 1GHz_PK 3m Vertical
EUT: W6M21707-17191
Mode:
Power: 3 Vd.c.
Operator: Leon
Note: ANT+, TX, 2457

	Freq	Read Level	Remark	Ant Factor	Level	Limit Line	APos	TPos	Over Limit
	MHz	dBuV		dB/m	dBuV/m	dBuV/m	cm	deg	dB
1	9828.000	34.84	peak	8.39	43.23	74.00	150	81	-30.77
2	PP12285.000	34.15	peak	13.90	48.05	74.00	150	360	-25.95




Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1



Address: NO. 35, Aly. 21, Ln 228, Ankang Rd, Neihu, Taipei
Tel: +886-2-6606-8877
Fax: +886-2-6606-8875



Site : 966 chamber
Condition: FCC_part 15B RE-Class C_Above 1GHz_PK 3m horizontal
EUT: W6M21707-17191
Mode:
Power: 3 Vd.c.
Operator: Leon
Note: ANT+,TX,2457




Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1



Address: NO. 35, Aly. 21, Ln 228, Ankang Rd, Neihu, Taipei
Tel: +886-2-6606-8877
Fax: +886-2-6606-8875



Site : 966 chamber
Condition: FCC_part 15B RE-Class C_Above 1GHz_PK 3m Vertical
EUT: W6M21707-17191
Mode:
Power: 3 Vd.c.
Operator: Leon
Note: ANT+, TX, 2457




Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1



Address: NO. 35, Aly. 21, Ln 228, Ankang Rd, Neihu, Taipei
Tel: +886-2-6606-8877
Fax: +886-2-6606-8875



Site : 966 chamber
Condition: FCC_part 15B RE-Class C_Above 1GHz_PK 3m horizontal
EUT: W6M21707-17191
Mode:
Power: 3 Vd.c.
Operator: Leon
Note: ANT+, TX, 2457




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21707-17191-C-1
FCC ID: QSWDSCSCS1



Address: NO. 35, Aly. 21, Ln 228, Ankang Rd, Neihu, Taipei
Tel: +886-2-6606-8877
Fax: +886-2-6606-8875



Site : 966 chamber
Condition: FCC_part 15B RE-Class C_Above 1GHz_PK 3m Vertical
EUT: W6M21707-17191
Mode:
Power: 3 Vd.c.
Operator: Leon
Note: ANT+, TX, 2457