

## FCC Part 22/24 Compliance Test Report

|                                                         |                                                                                                                                                                                                                                                                                                                             |                                   |                                                                                                                                                                                    |
|---------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Test Report no.:</b>                                 | FCC22&24_RM-915_10.docx                                                                                                                                                                                                                                                                                                     | <b>Date of Report:</b>            | 06-Feb-2013                                                                                                                                                                        |
| <b>Number of pages:</b>                                 | 16                                                                                                                                                                                                                                                                                                                          | <b>Customer's Contact person:</b> | Hu Dongji (dohu)                                                                                                                                                                   |
| <b>Testing laboratory:</b>                              | TCC Nokia Beijing Laboratory<br>Beijing Economic and Technological Development Area<br>No.5 Donghuan Zhonglu<br>Beijing<br>PRC China 100176<br>Tel. +86 10 8711 8888<br>Fax. +86 10 8711 4550                                                                                                                               | <b>Customer:</b>                  | Nokia Corporation<br>Beijing Economic and Technological Development Area<br>No.5 Donghuan Zhonglu<br>Beijing<br>PRC China 100176<br>Tel. +86 10 8711 8888<br>Fax. +86 10 8711 4550 |
| <b>FCC listing no.:</b>                                 | 975940                                                                                                                                                                                                                                                                                                                      |                                   |                                                                                                                                                                                    |
| <b>IC recognition no.:</b>                              | 661AH-1                                                                                                                                                                                                                                                                                                                     |                                   |                                                                                                                                                                                    |
| <b>Tested devices/ accessories:</b>                     | <b>Phone RM-915 / Battery BL-5J / AC-charger AC-20E / Headset WH-108</b>                                                                                                                                                                                                                                                    |                                   |                                                                                                                                                                                    |
| <b>FCC ID:</b>                                          | QTLRM-915                                                                                                                                                                                                                                                                                                                   | <b>IC:</b>                        | 661AB-RM915                                                                                                                                                                        |
| <b>Supplement reports:</b>                              | -                                                                                                                                                                                                                                                                                                                           |                                   |                                                                                                                                                                                    |
| <b>Testing has been carried out in accordance with:</b> | <b>CFR 47, FCC rules Parts 22/24 , TIA-603-C-2004 and IC standards, RSS-GEN (Issue 3, December 2010), RSS-132 (Issue 2, September 2005), RSS-133 (Issue 5, February 2009). Deviations, modifications or clarifications (if any) to above mentioned documents are written in each section under "Test method and limit".</b> |                                   |                                                                                                                                                                                    |
| <b>Documentation:</b>                                   | The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 15 years at TCC Nokia.                                                                        |                                   |                                                                                                                                                                                    |
| <b>Test Results:</b>                                    | <b>The EUT complies with the requirements in respect of all parameters subject to the test.</b><br>The test results relate only to devices specified in this document                                                                                                                                                       |                                   |                                                                                                                                                                                    |
| <b>Date and signature for the contents:</b>             |                                                                                                                                                                                                                                                                                                                             |                                   |                                                                                                                                                                                    |

Gao Sherina, Engineer, EMC

## 1. Summary for FCC Part 22/24 Compliance Test Report

|                               |                                                             |
|-------------------------------|-------------------------------------------------------------|
| Date of receipt               | 14-Jan-2013                                                 |
| Testing completed             | 25-Jan-2013                                                 |
| The customer's contact person | Hu Dongji (dohu)                                            |
| Test Plan referred to         | T:\Projects\RM-914\TestPlan\RS_testplan_RM-914_EMC_FCC.xlsm |
| Notes                         | -                                                           |
| Document name                 | FCC22&24_RM-915_10.docx                                     |

### 1.1. EUT and Accessory Information

The EUT is a mobile phone with following features:  
GSM/WCDMA/WLAN/Bluetooth  
The EUT is tested with maximum rated TX power.

Devices under tests

| Product       | Type   | SN                          | HW   | MV | SW                   | DUT   |
|---------------|--------|-----------------------------|------|----|----------------------|-------|
| Phone         | RM-914 | 004402472072127             | 0201 | -  | 1030.6300.1302.10055 | 53091 |
| Battery       | BL-5J  | 4955402215032305410;0670574 | -    | -  | -                    | 53103 |
| AC-charger    | AC-20E | 4868672461450500632;0675628 | -    | -  | -                    | 53094 |
| Headset       | WH-108 | 2462171                     | -    | -  | -                    | 53100 |
| Phone         | RM-914 | 004402472071749             | 0201 | -  | 1030.6300.1302.10055 | 53107 |
| Battery       | BL-5J  | 4955402215032305298;0670574 | -    | -  | -                    | 53105 |
| AC-charger    | AC-20E | 4868672461450501522;0675628 | -    | -  | -                    | 53097 |
| Headset       | WH-108 | 2462171                     | -    | -  | -                    | 53101 |
| Dummy battery | SD-50B | 07484K                      | -    | -  | -                    | 53108 |

### 1.2. Summary of Test Results

#### GSM850:

| Section in CFR 47     | Section in RSS-GEN or RSS-132 | Name of the test                           | Result |
|-----------------------|-------------------------------|--------------------------------------------|--------|
| §2.1046(a), 22.913(a) | 4.4                           | Conducted RF output power                  | NP     |
| §22.913(a)            | 4.4                           | Radiated RF output power                   | NP     |
| §2.1049(h)            | 4.6.1                         | 99 % occupied bandwidth                    | PASSED |
| §22.917(a)            | 4.5                           | Band edge compliance                       | NP     |
| §22.917(a), §2.1051   | 4.5                           | Spurious emissions at antenna terminals    | NP     |
| §22.917(a), §2.1053   | 4.5                           | Spurious radiated emissions                | PASSED |
| §2.1055(a)            | 4.3                           | Frequency stability, temperature variation | PASSED |
| §2.1055(d)            | 4.3                           | Frequency stability, voltage variation     | PASSED |

#### GSM1900:

| Section in CFR 47   | Section in RSS-GEN or RSS-133 | Name of the test                           | Result |
|---------------------|-------------------------------|--------------------------------------------|--------|
| §2.1046(a)          | 6.4                           | Conducted RF output power                  | NP     |
| §24.232(b)          | 6.4                           | Radiated RF output power                   | NP     |
| §2.1049(h)          | 4.6.1                         | 99 % occupied bandwidth                    | PASSED |
| §24.238(a)          | 6.5                           | Band edge compliance                       | NP     |
| §24.238(a), §2.1051 | 6.5                           | Spurious emissions at antenna terminals    | NP     |
| §24.238(a), §2.1053 | 6.5                           | Spurious radiated emissions                | PASSED |
| §2.1055(a)          | 6.3                           | Frequency stability, temperature variation | PASSED |
| §2.1055(d)          | 6.3                           | Frequency stability, voltage variation     | PASSED |

---

|        |                                                                          |
|--------|--------------------------------------------------------------------------|
| PASSED | The EUT complies with the essential requirements in the standard.        |
| FAILED | The EUT does not comply with the essential requirements in the standard. |
| NP     | The test was not performed by the TCC Nokia Laboratory.                  |

*The test results of QTLRM-915 are re-used for certification of the QTLRM-914. The table above indicates the results, which will be re-used.*


## CONTENTS

|                                                                                                                         |           |
|-------------------------------------------------------------------------------------------------------------------------|-----------|
| <b>1. Summary for FCC Part 22/24 Compliance Test Report .....</b>                                                       | <b>2</b>  |
| 1.1. EUT and Accessory Information.....                                                                                 | 2         |
| 1.2. Summary of Test Results.....                                                                                       | 2         |
| <b>2. 99% occupied bandwidth<br/>(FCC §2.1049(h), RSS-GEN 4.6.1) .....</b>                                              | <b>5</b>  |
| 2.1. Test Setup.....                                                                                                    | 5         |
| 2.2. Test method and limit.....                                                                                         | 5         |
| 2.3. GSM 850 Test results .....                                                                                         | 6         |
| 2.4. GSM 1900 Test results .....                                                                                        | 7         |
| <b>3. Spurious radiated emissions<br/>(FCC §22.917(a), §2.1053, §24.238(a), §2.1053, RSS-132 4.5, RSS-133 6.5).....</b> | <b>8</b>  |
| 3.1. Test setup .....                                                                                                   | 8         |
| 3.2. Test method and limit.....                                                                                         | 8         |
| 3.3. GSM850 TX test results .....                                                                                       | 10        |
| 3.4. GSM850-E1 TX test results.....                                                                                     | 10        |
| 3.5. GSM1900 TX test results .....                                                                                      | 10        |
| 3.6. GSM1900-E1 TX test results.....                                                                                    | 10        |
| <b>4. Frequency stability, temperature variation<br/>(FCC §2.1055(a), RSS-132 4.3, RSS-133 6.3).....</b>                | <b>11</b> |
| 4.1. Test Setup.....                                                                                                    | 11        |
| 4.2. Test method and limit.....                                                                                         | 11        |
| 4.3. GSM 850 Test results .....                                                                                         | 12        |
| 4.4. GSM 1900 Test results .....                                                                                        | 12        |
| <b>5. Frequency stability, voltage variation<br/>(FCC §2.1055(d), RSS-132 4.3, RSS-133 6.3) .....</b>                   | <b>13</b> |
| 5.1. Test Setup.....                                                                                                    | 13        |
| 5.2. Test method and limit.....                                                                                         | 13        |
| 5.3. GSM 850 Test results .....                                                                                         | 14        |
| 5.4. GSM 1900 Test results .....                                                                                        | 14        |
| <b>6. Test Equipment.....</b>                                                                                           | <b>15</b> |
| 6.1. Conducted measurements .....                                                                                       | 15        |
| 6.2. Radiated measurements .....                                                                                        | 15        |

## 2. 99% occupied bandwidth (FCC §2.1049(h), RSS-GEN 4.6.1)

|                                                 |                                                          |
|-------------------------------------------------|----------------------------------------------------------|
| EUT with DUT number                             | RM-914, DUT 53107                                        |
| Accessories with DUT numbers                    | BL-5J, DUT 53105 ; AC-20E, DUT 53097 ; WH-108, DUT 53101 |
| Operation Voltage [V] / [Hz]                    | Nominal                                                  |
| Results                                         | PASSED                                                   |
| Remarks                                         | -                                                        |
| Temp [°C] / Humidity [%RH] / Air Pressure [kPa] | 20/28/103.1                                              |
| Date of measurements                            | 21-Jan-2013                                              |
| Measured by                                     | Gao Sherina                                              |

### 2.1. Test Setup




### 2.2. Test method and limit

The measurement is made according to FCC rules parts 22, 24 and IC standard RSS-GEN.


## 2.3. GSM 850 Test results

| Operation mode (TX on) | 99% Occupied bandwidth [kHz] |
|------------------------|------------------------------|
| GSM                    | 248                          |
| EGPRS                  | 246                          |

### GSM, Channel 190 / 836.6 MHz




### EGPRS, Channel 190 / 836.6 MHz




## 2.4. GSM 1900 Test results

| Operation mode (TX on) | 99% Occupied bandwidth [kHz] |
|------------------------|------------------------------|
| GSM                    | 244                          |
| EGPRS                  | 246                          |

### GSM, Channel 661 / 1880.0 MHz



### EGPRS, Channel 661 / 1880.0 MHz




### 3. Spurious radiated emissions

(FCC §22.917(a), §2.1053, §24.238(a), §2.1053, RSS-132 4.5, RSS-133 6.5)

|                                                 |                                                        |
|-------------------------------------------------|--------------------------------------------------------|
| EUT with DUT number                             | RM-914, DUT53091                                       |
| Accessories with DUT numbers                    | BL-5J, DUT 53103; AC-20E, DUT 53094; WH-108, DUT 53100 |
| Operation Voltage [V] / [Hz]                    | Nominal                                                |
| Results                                         | PASSED                                                 |
| Remarks                                         | -                                                      |
| Temp [°C] / Humidity [%RH] / Air Pressure [kPa] | 21/25/103.2                                            |
| Date of measurements                            | 18-Jan-2013                                            |
| Measured by                                     | Zou Ming                                               |

#### 3.1. Test setup



#### 3.2. Test method and limit

The measurement is made according to TIA-603-C-2004 as follows:

The measurement is divided into the Preliminary Measurement and the Final Measurement.

The suspected frequencies are searched for in Preliminary Measurement with absorbers on floor and measuring antenna at fixed height using 2-axis EUT position system.

The Final Measurement is performed in the Semi-Anechoic Chamber with conducting metal floor, if the Preliminary Measurement results are closer than 20 dB to the permissible value.

The EUT is placed at nonconductive plate at the turntable center.

For each suspected frequency, the turntable is rotated 360 degrees and antenna is scanned from 1 to 4 m. This is repeated for both horizontal and vertical receive antenna polarizations.

The emissions less than 20 dB below the permissible value are reported.

The substitution method is used. Substitution values at each frequencies are measured beforehand and saved to the test software. The substitution corrections are obtained as described below:

$$ASUBST = PSUBST\ TX - PSUBST\ RX - LSUBST\ CABLES + GSUBST\ TX\ ANT$$

Where ASUBST is the final substitution correction including receive antenna gain. PSUBST TX is signal generator level, PSUBST RX is receiver level, LSUBST CABLES is cable losses including both TX and RX cables and GSUBST TX ANT is substitution antenna gain.

The measurement results are obtained as described below:

$$P[\text{dBm}] = \text{PMEAS} + \text{ATOT}$$

Where PMEAS is receiver reading in dBm and ATOT is total correction factor including cable loss and substitution correction ( $\text{ATOT} = \text{LCABLES} - \text{GPREAMP} + \text{ASUBST}$ ).

Limits for spurious radiated emissions measurements

| Operation band | Frequency range [MHz] | Limit [dBm] |
|----------------|-----------------------|-------------|
| GSM850         | 30 - 8500             | -13         |
| GSM1900        | 30 - 18000            | -13         |

### 3.3. GSM850 TX test results

GSM mode, Channel 190 / 836.6 MHz

| Frequency [MHz] | P [dBm] | P [ $\mu$ W] | P <sub>MEAS</sub> [dBm] | A <sub>TOT</sub> [dB] | Polarization | Results |
|-----------------|---------|--------------|-------------------------|-----------------------|--------------|---------|
| 1673.106        | -46.57  | 0.02201      | -51.28                  | 4.71                  | HORIZONTAL   | PASSED  |
| 1673.106        | -46.71  | 0.02131      | -51.42                  | 4.71                  | HORIZONTAL   | PASSED  |
| 2489.379        | -51.52  | 0.00704      | -63.32                  | 11.8                  | HORIZONTAL   | PASSED  |
| 2509.579        | -48.79  | 0.01323      | -60.79                  | 12                    | HORIZONTAL   | PASSED  |
| 3315.591        | -54.6   | 0.00347      | -63.61                  | 9.01                  | VERTICAL     | PASSED  |

\*Substitution method could not be utilized as no emissions above noise floor were found during measurements.

### 3.4. GSM850-E1 TX test results

EGPRS mode, Channel 190 / 836.6 MHz

| Frequency [MHz] | P [dBm] | P [ $\mu$ W] | P <sub>MEAS</sub> [dBm] | A <sub>TOT</sub> [dB] | Polarization | Results |
|-----------------|---------|--------------|-------------------------|-----------------------|--------------|---------|
| 1673.126        | -57.54  | 0.00176      | -62.25                  | 4.71                  | HORIZONTAL   | PASSED  |
| 1673.206        | -54.48  | 0.00357      | -59.19                  | 4.71                  | HORIZONTAL   | PASSED  |
| 2497.776        | -50.87  | 0.00819      | -63.05                  | 12.18                 | HORIZONTAL   | PASSED  |
| 2508.958        | -51.76  | 0.00666      | -63.75                  | 11.99                 | HORIZONTAL   | PASSED  |
| 3335.17         | -53.41  | 0.00456      | -62                     | 8.59                  | VERTICAL     | PASSED  |

\*Substitution method could not be utilized as no emissions above noise floor were found during measurements.

### 3.5. GSM1900 TX test results

GSM mode, channel 661 / 1880.0 MHz

| Frequency [MHz] | P [dBm] | P [ $\mu$ W] | P <sub>MEAS</sub> [dBm] | A <sub>TOT</sub> [dB] | Polarization | Results |
|-----------------|---------|--------------|-------------------------|-----------------------|--------------|---------|
| 2876.344        | -44.41  | 0.0362       | -63.08                  | 18.67                 | VERTICAL     | PASSED  |
| 2910.861        | -44.54  | 0.03515      | -63.65                  | 19.11                 | HORIZONTAL   | PASSED  |
| 2917.839        | -44.96  | 0.03192      | -63.87                  | 18.91                 | HORIZONTAL   | PASSED  |
| 2919.801        | -43.52  | 0.04449      | -62.17                  | 18.65                 | VERTICAL     | PASSED  |
| 2985.798        | -45.32  | 0.0294       | -64.41                  | 19.09                 | HORIZONTAL   | PASSED  |
| 2994.334        | -45.94  | 0.02547      | -64.87                  | 18.93                 | HORIZONTAL   | PASSED  |

\*Substitution method could not be utilized as no emissions above noise floor were found during measurements.

### 3.6. GSM1900-E1 TX test results

EGPRS mode, Channel 661 / 1880.0 MHz


| Frequency [MHz] | P [dBm] | P [ $\mu$ W] | P <sub>MEAS</sub> [dBm] | A <sub>TOT</sub> [dB] | Polarization | Results |
|-----------------|---------|--------------|-------------------------|-----------------------|--------------|---------|
| 2845.663        | -44.71  | 0.03378      | -63.49                  | 18.78                 | VERTICAL     | PASSED  |
| 2885.991        | -43.9   | 0.0407       | -62.84                  | 18.94                 | HORIZONTAL   | PASSED  |
| 2894.57         | -44.64  | 0.03435      | -63.29                  | 18.65                 | VERTICAL     | PASSED  |
| 2916.376        | -43.85  | 0.04121      | -62.92                  | 19.07                 | HORIZONTAL   | PASSED  |
| 2944.118        | -44.98  | 0.03178      | -63.72                  | 18.74                 | HORIZONTAL   | PASSED  |
| 2983.815        | -43.56  | 0.04406      | -62.6                   | 19.04                 | HORIZONTAL   | PASSED  |

\*Substitution method could not be utilized as no emissions above noise floor were found during measurements.

#### 4. Frequency stability, temperature variation (FCC §2.1055(a), RSS-132 4.3, RSS-133 6.3)

|                                                 |                                                          |
|-------------------------------------------------|----------------------------------------------------------|
| EUT with DUT number                             | RM-914, DUT 53107                                        |
| Accessories with DUT numbers                    | BL-5J, DUT 53105 ; AC-20E, DUT 53097 ; WH-108, DUT 53101 |
| Operation Voltage [V] / [Hz]                    | Nominal                                                  |
| Results                                         | PASSED                                                   |
| Remarks                                         | -                                                        |
| Temp [°C] / Humidity [%RH] / Air Pressure [kPa] | 20/28/103.1                                              |
| Date of measurements                            | 21-Jan-2013                                              |
| Measured by                                     | Gao Sherina                                              |

##### 4.1. Test Setup



##### 4.2. Test method and limit

The measurement is made according to FCC rules parts 22, 24 and IC standard RSS-132, RSS-133 as follows:

The climate chamber temperature is set to the maximum value and the temperature is allowed to stabilize.

The EUT is placed in the chamber.

The EUT is set in idle mode for 15 minutes.

The EUT is set to transmit.

The transmit frequency error was measured immediately.

The steps c - e were repeated for each temperature. Limits for frequency stability, temperature variation measurements

| Frequency deviation [ppm] |
|---------------------------|
| +/- 2.5                   |

### 4.3. GSM 850 Test results

GSM, Channel 190 / 836.6 MHz

| Temperature [°C] | Frequency [MHz] | Deviation [Hz] | Deviation [ppm] | Result |
|------------------|-----------------|----------------|-----------------|--------|
| 50               | 836.60          | -25.63000      | -0.0306         | PASSED |
| 40               | 836.60          | 6.91000        | 0.0083          | PASSED |
| 50               | 836.60          | -20.66000      | -0.0247         | PASSED |
| 40               | 836.60          | -19.76000      | -0.0236         | PASSED |
| 30               | 836.60          | -22.79000      | -0.0272         | PASSED |
| 20               | 836.60          | -24.41000      | -0.0292         | PASSED |
| 10               | 836.60          | -13.43000      | -0.0161         | PASSED |
| 0                | 836.60          | -16.27000      | -0.0194         | PASSED |
| -10              | 836.60          | -10.85000      | -0.013          | PASSED |
| -20              | 836.60          | -3.68000       | -0.0044         | PASSED |
| -26              | 836.60          | -28.35000      | -0.0339         | PASSED |

### 4.4. GSM 1900 Test results


GSM, Channel 661 / 1880.0 MHz

| Temperature [°C] | Frequency [MHz] | Deviation [Hz] | Deviation [ppm] | Result |
|------------------|-----------------|----------------|-----------------|--------|
| 50               | 1880.00         | -31.51000      | -0.0168         | PASSED |
| 40               | 1880.00         | -8.07000       | -0.0043         | PASSED |
| 50               | 1880.00         | -32.54000      | -0.0173         | PASSED |
| 40               | 1880.00         | 14.79000       | 0.0079          | PASSED |
| 30               | 1880.00         | -32.48000      | -0.0173         | PASSED |
| 20               | 1880.00         | 8.52000        | 0.0045          | PASSED |
| 10               | 1880.00         | -33.77000      | -0.018          | PASSED |
| 0                | 1880.00         | -25.18000      | -0.0134         | PASSED |
| -10              | 1880.00         | -7.81000       | -0.0042         | PASSED |
| -20              | 1880.00         | -27.57000      | -0.0147         | PASSED |
| -26              | 1880.00         | -45.72000      | -0.0243         | PASSED |

## 5. Frequency stability, voltage variation (FCC §2.1055(d), RSS-132 4.3, RSS-133 6.3)

|                                                 |                   |
|-------------------------------------------------|-------------------|
| EUT with DUT number                             | RM-914, DUT 53107 |
| Accessories with DUT numbers                    | SD-50B, DUT 53108 |
| Operation Voltage [V] / [Hz]                    | Nominal           |
| Results                                         | PASSED            |
| Remarks                                         | -                 |
| Temp [°C] / Humidity [%RH] / Air Pressure [kPa] | 20/24/102.8       |
| Date of measurements                            | 25-Jan-2013       |
| Measured by                                     | Gao Sherina       |

### 5.1. Test Setup



### 5.2. Test method and limit

The measurement is made according to FCC rules parts 22, 24 and IC standard RSS-132, RSS-133 as follows:

The EUT battery was replaced with an adjustable power supply. The frequency stability was measured at nominal voltage and at the battery cut-off point.

Limits for frequency stability, voltage variation measurements

| Frequency deviation [ppm] |
|---------------------------|
| +/- 2.5                   |

### 5.3. GSM 850 Test results

GSM, Channel 190 / 836.6 MHz

| Voltage level [V]           | Frequency [MHz] | Deviation [Hz] | Deviation [ppm] | Result |
|-----------------------------|-----------------|----------------|-----------------|--------|
| Max / 4.1                   | 836.60          | 2.52000        | 0.003           | PASSED |
| Nominal / 3.7               | 836.60          | -14.08000      | -0.0168         | PASSED |
| Battery cut-off point / 3.3 | 836.60          | -0.71000       | -0.0008         | PASSED |

### 5.4. GSM 1900 Test results

GSM, Channel 661 / 1880.0 MHz

| Voltage level [V]           | Frequency [MHz] | Deviation [Hz] | Deviation [ppm] | Result |
|-----------------------------|-----------------|----------------|-----------------|--------|
| Max / 4.1                   | 1880.00         | -36.35000      | -0.0193         | PASSED |
| Nominal / 3.7               | 1880.00         | -3.10000       | -0.0016         | PASSED |
| Battery cut-off point / 3.3 | 1880.00         | 16.08000       | 0.0086          | PASSED |

## 6. Test Equipment

### 6.1. Conducted measurements

| Eq. No     | Equipment                       | Type                | Manufacturer            | Used in            |
|------------|---------------------------------|---------------------|-------------------------|--------------------|
| -          | RF Emission Software            | EMC32 Test Software | R&S                     | 22/24/27, 15C, 15B |
| BJPCHW0020 | DC Power supply                 | HP6632B             | HP                      | 22/24/27, 15C      |
| BJPCPT0040 | Receiver                        | ESCS30              | R&S                     | 15C, 15B           |
| BJPCPT0069 | LISN 50 $\mu$ H                 | ESH3-Z5             | R&S                     | 15C, 15B           |
| BJPCPT0073 | Signal Generator                | SMR 20              | R&S                     | 22/24/27, 15C, 15B |
| BJPCPT0191 | Pulse Limiter                   | ESH3-Z2             | R&S                     | 15C, 15B           |
| BJPCPT0208 | UPS                             | PULSAR RX10         | Merlin gerin            | 15C, 15B           |
| BJPCTC0001 | DIGITAL CAMERA                  | PC1015              | CANON                   | 15C, 15R           |
| BJPCTC0017 | Communication Tester            | CMU200              | R&S                     | 22/24/27, 15C, 15B |
| BJPCTC0062 | AC Power source                 | 6812B               | Hp                      | 15C, 15B           |
| BJPCTC0067 | Bluetooth Tester                | CBT                 | R&S                     | 22/24/27, 15C      |
| BJPCTC0082 | Humidity and Temperature Sensor | 175-H2              | Testo                   | 15B, 15C           |
| BJPCTC0088 | Absolut pressure meter          | testo 511           | Testo                   | 22/24/27, 15B, 15C |
| BJPCTC0089 | Tempreture Test chamber         | VT4002              | Votsch industrietechnik | 22/24/27, 15C      |
| BJPCTC0090 | FSP spectrum analyzer           | FSP30               | R&S                     | 22/24/27, 15C      |
| BJPCTC0094 | GPIO-RS232 convertor            | GPIO-RS232          | NI                      | 22/24/27, 15C      |
| BJPCTC0112 | Power Splitter                  | 11667B              | Agilent                 | 22/24/27, 15C      |
| BJPCTC0114 | Signal Generator                | E8257C              | Agilent                 | 22/24/27, 15C      |
| BJPCTC0115 | Communication Tester            | CMU200              | R&S                     | 22/24/27, 15B, 15C |
| BJPCTC0127 | AC Power source                 | SOYI-500VA          | SOYI                    | 15B 15C            |
| BJPCTC0128 | Communication antenna           | JXTXLB-10180        | A-INFOMW                | 22/24/27 15B 15C   |
| BJPCTC0129 | Communication antenna           | JXTXLB-10180        | A-INFOMW                | 22/24/27 15B 15C   |
| BJPCTC0131 | Communication tester            | CMW500              | R&S                     | 22/24/27 15B 15C   |
| BJPCTC0136 | Communication antenna           | JXTXLB-880-NF       | A-INFOMW                | 15B 15C            |

### 6.2. Radiated measurements

| Eq. No     | Equipment            | Type                              | Manufacturer | Used in            |
|------------|----------------------|-----------------------------------|--------------|--------------------|
| -          | BT / WLAN Antenna    | SPA 2400/75/9/0/V                 | Huber-Suhner | 15C, 15B           |
| -          | BT / WLAN Antenna    | SPA 2400/75/9/0/V                 | Huber-Suhner | 15C, 15B           |
| -          | RF Emission Software | EMC32 Test Software               | R&S          | 22/24/27, 15C, 15B |
| BJPCPT0072 | Receiver             | ESI B26                           | R&S          | 22/24/27, 15C, 15B |
| BJPCPT0130 | Relay Switch Unit    | TS-RSP                            | R&S          | 22/24/27, 15C, 15B |
| BJPCPT0150 | High Pass Filter     | WHKS1200-10SS                     | Wainwright   | 22/24/27, 15C, 15B |
| BJPCPT0151 | Band Reject Filter   | WRCD1880/2000-0.2/40-5SSK         | Wainwright   | 24, 15B            |
| BJPCPT0154 | Band Reject Filter   | WRCT2402/2480-2400/2483.5-30-20SS | Wainwright   | 15C, 15B           |
| BJPCPT0162 | Antenna              | HF906                             | R&S          | 22/24/27, 15C, 15B |
| BJPCPT0208 | UPS                  | PULSAR RX10                       | Merlin gerin | 15C, 15B           |
| BJPCTC0001 | DIGITAL CAMERA       | PC1015                            | CANON        | 15C, 15R           |
| BJPCTC0007 | Antenna              | HL562                             | R&S          | 22/24/27, 15C, 15B |
| BJPCTC0029 | Antenna              | HF906                             | R&S          | 22/24/27, 15C, 15B |
| BJPCTC0034 | Band Reject Filter   | WRCT 800/880-0.2/40-5SSK          | Wainwright   | 22, 15B            |
| BJPCTC0049 | Preamplifier         | Blma 0118-1A-Bt                   | Bonn         | 22/24/27, 15C, 15B |
| BJPCTC0055 | Communication Tester | CMU200                            | R&S          | 22/24/27, 15C, 15B |
| BJPCTC0058 | Bluetooth Tester     | CBT                               | R&S          | 15C, 15B           |
| BJPCTC0062 | AC Power source      | 6812B                             | Hp           | 15C, 15B           |
| BJPCTC0064 | Band Reject Filter   | WRCG1877/1883-1870/1890-40/6SS    | Wainwright   | 24, 15B            |
| BJPCTC0065 | Band Reject Filter   | WRCG832/838-825/845-40/5SS        | Wainwright   | 27, 15B            |

| Eq. No     | Equipment                       | Type                             | Manufacturer       | Used in            |
|------------|---------------------------------|----------------------------------|--------------------|--------------------|
| BJPCTC0071 | Multi-Device Controller         | 2090                             | EMCO               | 22/24/27, 15C, 15B |
| BJPCTC0072 | Anechoic Chamber                | 3 m Semi / Full Anechoic Chamber | ETS                | 22/24/27, 15C, 15B |
| BJPCTC0073 | MAST                            | Model-TR/POL                     | ETS                | 22/24/27, 15C, 15B |
| BJPCTC0074 | MAST                            | Model 2070-2                     | ETS                | 22/24/27, 15C, 15B |
| BJPCTC0075 | Turntable                       | Model 2188                       | ETS-EMCO           | 22/24/27, 15C, 15B |
| BJPCTC0081 | Humidity and Temperature Sensor | 175-H2                           | Testo              | 15B, 15C           |
| BJPCTC0088 | Absolut pressure meter          | testo 511                        | Testo              | 22/24/27, 15B, 15C |
| BJPCTC0096 | Preamplifier                    | AFS4-00100300-20-23P-6           | Miteq              | 22/24/27, 15C, 15B |
| BJPCTC0113 | Receiver                        | ESI B26                          | R&S                | 22/24/27, 15B, 15C |
| BJPCTC0115 | Communication Tester            | CMU200                           | R&S                | 22/24/27, 15B, 15C |
| BJPCTC0124 | Attenuator                      | SA18N200W-40                     | Fairview Microwave | -                  |
| BJPCTC0125 | Loop Antenna                    | HFH2-Z2                          | R&S                | 15C                |
| BJPCTC0126 | Tripod                          | FHU-Z                            | R&S                | 15C                |
| BJPCTC0128 | Communication antenna           | JXTXLB-10180                     | A-INFOMW           | 22/24/27 15B 15C   |
| BJPCTC0129 | Communication antenna           | JXTXLB-10180                     | A-INFOMW           | 22/24/27 15B 15C   |
| BJPCTC0131 | Communication tester            | CMW500                           | R&S                | 22/24/27 15B 15C   |
| BJPCTC0133 | Open Swith and contril unit     | OSP 150                          | R&S                | 15B, 15C           |
| BJPCTC0134 | Open Swith and contril unit     | OSP 150                          | R&S                | 15B, 15C           |
| BJPCTC0135 | Open Swith and contril unit     | OSP 130                          | R&S                | 15B, 15C           |
| BJPCTC0136 | Communication antenna           | JXTXLB-880-NF                    | A-INFOMW           | 15B 15C            |