



**Load Systems International Inc.**  
2666 boul. du Parc Technologique, Suite 190  
Québec QC, G1P 4S6  
Canada

Quebec, January 19th, 2015

Nemko Canada Inc  
303 River Road  
Ottawa, Ontario, Canada  
K1V 1H2

### Model differences

This letter is a declaration of the differences between model MBR100 and MBR105.

The MBR100 is a battery powered portable model. The MBR105 is designed to be powered by an external DC voltage supply and permanently installed in cranes and other off-road machinery.

The MBR100 PCBA is MB139 and the MBR105 PCBA is MB139-A. Both assemblies are based on the same PCB. Both models share the same RF circuit and are electrically identical. The sole difference between both assemblies is related to the reed switch SW1 open door detection function. In the case of the MBR100, when the door is closed, the internal power supplies are deactivated to increase battery life. In the case of the MBR105, when the door is closed, the buzzer is activated in order to alert the user that the screen is blocked.

The MBR105 has a lockout output which outputs either 0V or the MBR105 supply voltage minus 1.5V. This function is deactivated in the MBR100.

Both units share the same enclosure and are constructed the same way with the exception of the MBR105 having an external connector instead of a battery enclosure.

All other functions are identical.

Signature: \_\_\_\_\_

A handwritten signature in blue ink, appearing to read "E. Beaulieu", written over a horizontal line.

Name: Éric Beaulieu

Date: January 19th, 2015

Title: Research, Prototype and Technology Manager