

849 NW STATE ROAD 45 NEWBERRY, FL 32669 USA

PH: 888.472.2424 OR 352.472.5500

FAX: 352.472.2030

EMAIL: <u>INFO@TIMCOENGR.COM</u> HTTP://WWW.TIMCOENGR.COM

FCC PART 15.227 TEST REPORT LOW POWER UNLICENSED TRANSMITTER

Applicant	HOBBYENGINE MODEL INDUSTRIAL LTD.			
Address	ROOM 619, 6/F., PENINSULA CENTRE, 67 MODY ROAD,			
	TSIMSHATSUI EAST			
	KOWLOON HONG KONG			
FCC ID	QW70205			
Product Description	27 MHZ WIRELESS R/C TOY-TX			
Date Sample Received	1/7/2008			
Date Tested	1/8/2008			
Tested By	NAM NGUYEN			
Approved By	MARIO DE ARANZETA			
Timco Report No.	42UT8TestReport.doc			
Test Results	⊠ Pass ☐ Fail			

THE ATTACHED REPORT SHALL NOT BE REPRODUCED EXCEPT IN FULL WITHOUT THE WRITTEN APPROVAL OF TIMCO ENGINEERING, INC.



TABLE OF CONTENTS

GENERAL REMARKS	3
REPORT SUMMARY	4
TEST ENVIRONMENT	4
TEST SETUP	4
DUT SPECIFICATION	5
TEST EQUIPMENT LIST	6
TEST PROCEDURES	7
RADIATION INTERFERENCE	8
OCCUPIED BANDWIDTH	9
RADIATED EMISSIONS TEST SET UP PHOTO	10

APPLICANT: HOBBYENGINE MODEL INDUSTRIAL LTD.

FCC ID:

QW70205 X:\H\HOBBYENGINE_QW7\42UT8\42UT8TestReport.doc REPORT:

GENERAL REMARKS

The attached report shall not be reproduced except in full without the written permission of Timco Engineering Inc.

The test results only relate to the item tested.

Summary

The device under test does:

fulfill the general approval requirements as identified in this test report not fulfill the general approval requirements as identified in this test report

Attestations

This equipment has been tested in accordance with the standards identified in this test report. To the best of my knowledge and belief, these tests were performed using the measurement procedures described in this report.

All instrumentation and accessories used to test products for compliance to the indicated standards are calibrated regularly in accordance with ISO 17025 requirements.

Testing Certificate # 0955-01

I attest that the necessary measurements were made, under my supervision, at:

Timco Engineering Inc. 849 NW State Road 45 Newberry, Fl 32669



Authorized Signatory Name:

Mario de Aranzeta C.E.T. Compliance Engineer/ Lab. Supervisor

Date: 01/08/2008

APPLICANT: HOBBYENGINE MODEL INDUSTRIAL LTD.

FCC ID: QW70205

REPORT: X:\H\HOBBYENGINE_QW7\42UT8\42UT8TestReport.doc

Page 3 of 10 mdea 09.20.2007

REPORT SUMMARY

Applicable Rule(s	FCC Pt 15.227, ANSI C63.4: 2003
-------------------	---------------------------------

TEST ENVIRONMENT

Test Facility	The test sites are located at 849 NW State Road 45 Newberry, FL 32669 USA.
Test Condition:	Temperature: 26°C
	Relative humidity: 50%

TEST SETUP

Test Exercise (e.g software description, test signal, etc.):	The DUT was placed in continuous transmit mode of operation.
Deviation from the standard(s)	No deviation from the standard(s)
Modification to the DUT:	No modification was made to the DUT.
Supporting Peripheral Equipment	Not applicable. The device is a stand-alone remote control radio.

APPLICANT: HOBBYENGINE MODEL INDUSTRIAL LTD.

FCC ID: QW70205

DUT SPECIFICATION

Applicant	HOBBYENGINE MODEL INDUSTRIAL LTD.					
Description	27 MHZ WIRELE	27 MHZ WIRELESS R/C TOY-TX				
FCC ID	QW70205	QW70205				
Frequency Range	27.145 MHz	27.145 MHz				
DUT Power Source	☐ 110-120Vac/50- 60Hz					
	☐ DC Power					
	☐ Battery Operated Exclusively					
Test Item	☐ Prototype ☐ Pre-Production ☐ Production					
Type of Equipment	Fixed Mobile Mortable					

APPLICANT: HOBBYENGINE MODEL INDUSTRIAL LTD.

FCC ID:

QW70205 X:\H\HOBBYENGINE_QW7\42UT8\42UT8TestReport.doc REPORT:

TEST EQUIPMENT LIST

Device	Manufacturer	Model	Serial Number	Cal/Char Date	Due Date
3/10-Meter OATS	TEI	N/A	N/A	Listed 3/20/07	3/19/10
3-Meter OATS	TEI	N/A	N/A	Listed 1/11/06	1/10/09
3-Meter Semi- Anechoic Chamber	Panashield	N/A	N/A	Listed 5/11/07	5/10/10
Antenna: Biconnical	Eaton	94455-1	1096	CAL 10/11/06	10/11/08
Antenna: Biconnical	Electro- Metrics	BIA-25	1171	CAL 7/18/07	7/18/09
Analyzer Blue Tower Quasi-Peak Adapter	НР	85650A	2811A01279	CAL 5/17/07	5/17/09
Analyzer Blue Tower RF Preselector	HP	85685A	2926A00983	CAL 5/17/07	5/17/09
Analyzer Blue Tower Spectrum Analyzer	НР	8568B	2928A04729 2848A18049	CAL 5/17/07	5/17/09
LISN	Electro- Metrics	ANS-25/2	2604	CAL 10/5/06	10/5/08
LISN	Electro- Metrics	EM-7820	2682	CAL 7/23/07	7/23/09
Antenna: Log- Periodic	Eaton	96005	1243	CAL 12/14/07	12/14/09

APPLICANT: HOBBYENGINE MODEL INDUSTRIAL LTD.

FCC ID: QW70205

TEST PROCEDURES

Radiated Spurious Emissions: The test procedure used was ANSI C63.4-2003 using a spectrum analyzer with a preselector. The bandwidth of the spectrum analyzer was 100 kHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100 kHz and the video bandwidth was always greater than the RBW.

Occupied Bandwidth: A small sample of the transmitter output was fed into the spectrum analyzer and the following plot was generated. The vertical scale is set to 10 dB per division.

Formula Of Conversion Factors: The field strength at 3m was established by adding the meter reading of the spectrum analyzer to the antenna correction factor supplied by the antenna manufacturer plus the coax loss. The antenna correction factors are stated in terms of dB/m. The gain of the preselector was accounted for in the spectrum analyzer reading.

Example:

Freq	Meter Reading	ACF	Cable Loss	Field Strength
MHz	dBuV	dB/m	dB	dBuV/m@3 m
33	20	+10.36	+1.2	= 31.56

ANSI C63.4-2003 Measurement Procedures: The unit under test was placed on a table 80 cm high and with dimensions of 1mby 1.5m. The table used for radiated measurements is capable of continuous rotation. When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and verticals planes.

For measurements below 30 MHz, a loop antenna was used and rotated in horizontal and vertical positions to maximize emissions.

APPLICANT: HOBBYENGINE MODEL INDUSTRIAL LTD.

FCC ID: OW70205

RADIATION INTERFERENCE

Rules Part No.: 15.227

Requirements:

CARRIER FREQUENCY WILL NOT EXCEEDS 80 dBuV/m AT 3M.

Frequency MHz	Limits
30 – 88	40.0 dBμV/m measured @ 3 meters
80 – 216	43.5 dBμV/m measured @ 3 meters
216 – 960	46.0 dBμV/m measured @ 3 meters
Above 960	54.0 dBμV/m measured @ 3 meters

Test Data:

Emission Frequency MHz	Meter Reading dBuV	Ant. Polarity	Coax Loss dB	Correction Factor dB	Field Strength dBuV/m	Margin dB
27.15	18.0	Н	0.80	34.16	52.96	27.04
27.15	28.5	V	0.80	34.16	63.46	16.54
54.29	14.9	Н	1.01	10.04	25.95	14.05
54.29	17.4	V	1.01	9.48	27.89	12.11
81.44	20.3	V	1.24	8.75	30.29	9.71
81.44	22.1	Н	1.24	8.65	31.99	8.01
108.58	12.8	V	1.46	10.81	25.07	18.43
108.58	14.1	Н	1.46	10.29	25.85	17.65
135.73	12.0	Н	1.65	14.35	28.00	15.50
135.73	22.0	V	1.65	14.95	38.60	4.90
162.87	14.4	V	1.84	17.23	33.47	10.03
162.87	14.5	Н	1.84	16.26	32.60	10.90
190.02	10.4	V	2.03	14.51	26.94	16.56
190.02	13.6	Н	2.03	14.11	29.74	13.76
217.16	11.0	Н	2.19	11.64	24.83	21.17
217.16	14.2	V	2.19	11.44	27.83	18.17
244.31	9.2	Н	2.32	12.32	23.84	22.16
244.31	18.5	V	2.32	12.36	33.18	12.82
271.45	13.5	Н	2.46	13.64	29.60	16.40
271.45	14.2	V	2.46	13.53	30.19	15.81

APPLICANT: HOBBYENGINE MODEL INDUSTRIAL LTD.

FCC ID: QW70205

OCCUPIED BANDWIDTH

Rules Part No.: 15.227


Requirements: The field strength of any emissions appearing outside of 26.96 and

27.28MHz shall be attenuated to the general limits of 15.209.

Test Data: Please refer to the following plots.

NOTES:

HOBBYENGINE MODEL INDUSTRIAL LTD.- FCC ID: QW70205 OCCUPIED BANDWIDTH PLOT



APPLICANT: HOBBYENGINE MODEL INDUSTRIAL LTD.

FCC ID: QW70205

RADIATED EMISSIONS TEST SET UP PHOTO



APPLICANT: HOBBYENGINE MODEL INDUSTRIAL LTD.

FCC ID:

REPORT:

Page 10 of 10 mdea 09.20.2007