

Nemko-CCL, Inc.
1940 West Alexander Street
Salt Lake City, UT 84119
801-972-6146

Test Report

Certification

Test Of: C4-EA5

FCC ID: R33C4EA5

Test Specifications:

FCC PART 15, Subpart C

Test Report Serial No: 297668-4.2

Applicant:
Control4
11734 S. Election Road, Suite 200
Draper, UT 84020
U.S.A

Dates of Test: October 20, 21, 26 and November 2 & 3, 2015

Report Issue Date: December 28, 2015

Accredited Testing Laboratory By:



NVLAP Lab Code 100272-0

CERTIFICATION OF ENGINEERING REPORT

This report has been prepared by Nemko-CCL, Inc. to document compliance of the device described below with the requirements of Federal Communications Commission (FCC) Part 15, Subpart C. This report may be reproduced in full, partial reproduction may only be made with the written consent of the laboratory. The results in this report apply only to the sample tested.

- Applicant: Control4
- Manufacturer: Control4
- Brand Name: Control4
- Model Number: C4-EA5
- FCC ID: R33C4EA5

On this 28th day of December 2015, I, individually and for Nemko-CCL, Inc., certify that the statements made in this engineering report are true, complete, and correct to the best of my knowledge, and are made in good faith.

Although NVLAP has recognized that the Nemko-CCL, Inc. EMC testing facilities are in good standing, this report must not be used to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.

Nemko-CCL, Inc.



Tested by: Norman P. Hansen
Test Technician



Reviewed by: Thomas C. Jackson
Certification Manager

Revision History		
Revision	Description	Date
1	Original Report Release	November 28, 2015
2	1. Asus FCC ID corrected pg 7 2. Transmitter setting channels 11-24 changed from -2 to 2	December 28, 2015

TABLE OF CONTENTS

	PAGE
<u>SECTION 1.0 CLIENT INFORMATION</u>	5
<u>SECTION 2.0 EQUIPMENT UNDER TEST (EUT)</u>	6
<u>SECTION 3.0 TEST SPECIFICATION, METHODS & PROCEDURES</u>	9
<u>SECTION 4.0 OPERATION OF EUT DURING TESTING</u>	15
<u>SECTION 5.0 SUMMARY OF TEST RESULTS</u>	16
<u>SECTION.0 MEASUREMENTS AND RESULTS</u>	17
<u>APPENDIX 1 TEST PROCEDURES AND TEST EQUIPMENT</u>	47
<u>APPENDIX 2 PHOTOGRAPHS</u>	52

SECTION 1.0 CLIENT INFORMATION

1.1 Applicant:

Company Name: Control4
11734 S. Election Road, Suite 200
Draper, UT 84020
U.S.A.

Contact Name: Roger Midgley
Title: Sr. Regulatory Compliance Engineer

1.2 Manufacturer:

Company Name: Control4
11734 S. Election Road, Suite 200
Draper, UT 84020
U.S.A.

Contact Name: Roger Midgley
Title: Sr. Regulatory Compliance Engineer

SECTION 2.0 EQUIPMENT UNDER TEST (EUT)**2.1 Identification of EUT:**

Brand Name: Control4
Model Number: C4-EA5
Serial Number: 000FFF19BD3D and 000FFF1984C4
Dimensions: 44 cm x 23 cm x 5 cm

2.2 Description of EUT:

The C4-EA5 is a system controller for Control4 home automation systems. An 802.15.4 transceiver is used to interface other devices in the home automation system. A WiFi module carrying FCC modular approval 2AE3B-AEH-AR9462 is included in the device. An HDMI output, USB port, e-SATA port, 2 serial ports, 2 Analog Audio In ports, 2 Analog Audio Out port, 2 Digital Audio In and 2 Digital Audio Out ports are provided. There are 4 relay out ports and 4 contact ports provided. The C4-EA5 has a 5 port Ethernet switch built in.

The C4-EA5 802.15.4 transceiver use 15 channels in the 2400 to 2483.5 MHz frequency range. The 802.15.4 transceiver uses either an Oxford Tec WAND2DBI-SMA or a Cirocomm Technology 03A15304379240 antenna. See the table of frequencies used and channel assignments below.

Channel	Frequency (MHz)						
11	2405	15	2425	19	2445	23	2465
12	2410	16	2430	20	2450	24	2470
13	2415	17	2435	21	2455	25	2475
14	2420	18	2440	22	2460		

The transmitter power settings that are incorporated in production software and were used in testing are shown below.

Channel	Transmit Power Setting
11 – 24	2
25	-4

This report covers the 802.15.4 transceiver subject to FCC Part 15, Subpart C. The circuitry of the device subject to FCC Subpart B was found to be compliant and is covered in a separate report from Nemko-CCL, Inc. The WiFi transceiver carries its own modular certification.

2.3 EUT and Support Equipment:

The FCC ID numbers for all the EUT and support equipment used during the test are listed below:

Brand Name Model Number Serial Number	FCC ID Number or Compliance	Description	Name of Interface Ports / Interface Cables
BN: Control4 MN: C4-EA5 (Note 1) SN: 000FFF19BD3D & 000FFF1984C4	R33C4EA5 and contains 2AE3B-AEH-AR9462	System Controller	See Section 2.4
BN: Samsung MN: LN19D450G1D SN: Z2ZS3CKB410674V	DoC	Television	HDMI/HDMI cable (Note 2)
BN: GForce Megadisk MN: GF3B1000EU SN: SE5756875	DoC	eSATA drive	eSATA/eSATA cable (Note 2)
BN: Trendnet MN: TE100-S8P SN: 0243C3A16540	DoC	Network Switch	LAN/Cat 5e cables (Note 2)
BN: ASUS MN: WL-520GU SN: A11AAC051369	MSQWL520GU GC	Network Router	Ethernet/Cat 5e cable (Note 2)
BN: Samsung MN: N130 SN: ZLCM93HS900480X	DoC	Netbook Computer	Ethernet/Cat 5e cable (Note 2)
BN: Dell MN: Latitude E5410 SN: HL4PP1	DoC	Computer	Ethernet/Cat 5e cable (Note 2)
BN: Dell MN: Vostro SN: 43YLRP1	DoC	Computer	Ethernet/Cat 5e cable (Note 2)

Note: (1) EUT

(2) Interface port connected to EUT (See Section 2.4)

The support equipment listed above was not modified in order to achieve compliance with this standard.

2.4 Interface Ports on EUT:

Name of Ports	No. of Ports Fitted to EUT	Cable Descriptions/Length
Contact	1	Phoenix Contact connector w/12 unshielded conductors/ 1 meter
Relay	1	Phoenix Contact connector w/12 unshielded conductors/ 1 meter
Ethernet	5	Cat 5e cables/5 to 7 meters
USB	1	USB A to USB B cable/1 meter
eSATA	1	eSATA cable/1 meter
Serial	2	Shielded cable with DB9 connectors/1 meter
HDMI Out	1	HDMI cable/1.5 meters
IR	8	IR transmitters with unshielded cables with mono jacks/3 meters
Digital Audio In	2	Cables with RCA connector/1 meter
Digital Audio Out	2	Cables with RCA connector/1 meter
Analog Audio In (Left and Right)	2	Cables with RCA connectors/1 meter
Analog Audio Out (Left and Right)	2	Cables with RCA connectors/1 meter
WiFi Antenna	2	RP-SMA connectors direct to antennas
802.15.4 Antenna	1	RP-SMA connectors direct to antenna

2.5 Modification Incorporated/Special Accessories on EUT:

There were no modifications or special accessories required to comply with the specification.

SECTION 3.0 TEST SPECIFICATION, METHODS & PROCEDURES**3.1 Test Specification:**

Title: FCC PART 15, Subpart C (47 CFR 15)
15.203, 15.207, and 15.247

Limits and methods of measurement of radio interference characteristics of radio frequency devices.

Purpose of Test: The tests were performed to demonstrate initial compliance.

3.2 Methods & Procedures:**3.2.1 §15.203 Antenna Requirement**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

3.2.2 §15.207 Conducted Limits

(a) Except for Class A digital devices, for equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the band edges.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15 – 0.5*	66 to 56*	56 to 46*
0.5 – 5	56	46
5 - 30	60	50

*Decreases with the logarithm of the frequency.

3.2.3 §15.247 Operation within the bands 902 – 928 MHz, 2400 – 2483.5 MHz, and 5725 – 5850 MHz

(a) Operation under the provisions of this Section is limited to frequency hopping and digitally modulated intentional radiators that comply with the following provisions:

(1) Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400 – 2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudorandomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

(i) For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.

(ii) Frequency hopping systems operating in the 5725-5850 MHz band shall use at least 75 hopping frequencies. The maximum 20 dB bandwidth of the hopping channel is 1 MHz. The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 30 second period.

(iii) Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 non-overlapping channels are used.

(2) Systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

(b) The maximum peak output power of the intentional radiator shall not exceed the following:

(1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

(2) For frequency hopping systems operating in the 902-928 MHz band: 1 watt for systems employing at least 50 hopping channels; and, 0.25 watts for systems employing less than 50 hopping channels, but at least 25 hopping channels, as permitted under paragraph (a)(1)(i) of this section.

(3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725 – 5850 MHz bands: 1 watt. As an alternative to a peak power measurement, compliance with the Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(c) Operation with directional antenna gains greater than 6 dBi.

(1) Fixed point-to-point operation:

(i) Systems operating in the 2400-2483.5 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

(ii) Systems operating in the 5725-5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter peak output power.

(iii) Fixed, point-to-point operation, as used in paragraphs (b)(4)(i) and (b)(4)(ii) of this section, excludes the use of point-to-multipoint systems, omnidirectional applications, and multiple co-located intentional radiators transmitting the same information. The operator of the spread spectrum or digitally modulated intentional radiator or, if the equipment is professionally installed, the installer is responsible for ensuring that the system is used exclusively for fixed, point-to-point operations. The instruction manual furnished with the intentional radiator shall contain language in the installation instructions informing the operator and the installer of this responsibility.

(2) In addition to the provisions in paragraphs (b)(1), (b)(3), (b)(4) and (c)(1)(i) of this section, transmitters operating in the 2400-2483.5 MHz band that emit multiple directional beams, simultaneously or sequentially, for the purpose of directing signals to individual receivers or to groups of receivers provided the emissions comply with the following:

(i) Different information must be transmitted to each receiver.

(ii) If the transmitter employs an antenna system that emits multiple directional beams but does not emit multiple directional beams simultaneously, the total output power conducted to the array or arrays that comprise the device, i.e., the sum of the power supplied to all antennas, antenna elements, staves, etc. and summed across all carriers or frequency channels, shall not exceed the limit specified in paragraph (b)(1) or (b)(3) of this section, as applicable. However, the total conducted output power shall be reduced by 1 dB below the specified limits for each 3 dB that the directional gain of the antenna /antenna array exceeds 6 dBi. The directional antenna gain shall be computed as follows:

(A) The directional gain shall be calculated as the sum of $10 \log$ (number of array elements or staves) plus the directional gain of the element or stave having the highest gain.

(B) A lower value for the directional gain than that calculated in paragraph (c)(2)(ii)(A) of this section will be accepted if sufficient evidence is presented, e.g., due to shading of the array or coherence loss in the beamforming.

(iii) If a transmitter employs an antenna that operates simultaneously on multiple directional beams using the same or different frequency channels, the power supplied to each emission beam is subject to the power limit specified in paragraph (c)(2)(ii) of this section. If transmitted beams overlap, the power shall be reduced to ensure that their aggregate power does not exceed the limit specified in paragraph (c)(2)(ii) of this section. In addition, the aggregate power transmitted simultaneously on all beams shall not exceed the limit specified in paragraph (c)(2)(ii) of this section by more than 8 dB.

(iv) Transmitters that emit a single directional beam shall operate under the provisions of paragraph (c)(1) of this section.

(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

(e) For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

(f) For the purposes of this section, hybrid systems are those that employ a combination of both frequency hopping and digital modulation techniques. The frequency hopping operation of the hybrid system, with the direct sequence or digital modulation operation turned off, shall have an average time of occupancy on any frequency not to exceed 0.4 seconds within a time period in seconds equal to the number of hopping frequencies employed multiplied by 0.4. The digital modulation operation of the hybrid system, with the frequency hopping turned off, shall comply with the power density requirements of paragraph (d) of this section.

(g) Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

(h) The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

(i) Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this Chapter.

Note: Spread spectrum systems are sharing these bands on a noninterference basis with systems supporting critical Government requirements that have been allocated the usage of these bands, secondary only to ISM equipment operated under the provisions of Part 18 of this Chapter. Many of these Government systems are airborne radiolocation systems that emit a high EIRP which

can cause interference to other users. Also, investigations of the effect of spread spectrum interference to U. S. Government operations in the 902-928 MHz band may require a future decrease in the power limits allowed for spread spectrum operation.

3.3 Test Procedure

The testing was performed according to the procedures in ANSI C63.10: 2013. Testing was performed at the Nemko-CCL, Inc. Wanship open area test site #2, located at 29145 Old Lincoln Highway, Wanship, UT. This site has been registered with the FCC, and was renewed January 22, 2015 (90504). This registration is valid for three years.

Nemko-CCL, Inc. is accredited by National Voluntary Laboratory Accreditation Program (NVLAP); NVLAP Lab Code: 100272-0, which is effective until September 30, 2016.

SECTION 4.0 OPERATION OF EUT DURING TESTING

4.1 Operating Environment:

Power Supply: 120 VAC/60 Hz

4.2 Operating Modes:

The 802.15.4 transmitter was tested while in a constant transmit mode at the upper, middle, and lower channels. The voltage to the EUT was varied with no change seen in transmitter characteristics.

4.3 EUT Exercise Software:

Control4 Composer software and firmware version 2.8.1.512959 was used to exercise the transmitter.

SECTION 5.0 SUMMARY OF TEST RESULTS**5.1 FCC Part 15, Subpart C**

The C4-EA5 802.15.4 transceiver was subjected to each of the tests shown in the summary table below.

5.1.1 Summary of Tests:

Section	Environmental Phenomena	Frequency Range (MHz)	Result
15.203	Antenna Requirements	Structural requirement	Complied
15.207	Conducted Disturbance at Mains Ports	0.15 to 30	Complied
15.247(a)	Bandwidth Requirement	2400 – 2483.5	Complied
15.247(b)	Peak Output Power	2400 – 2483.5	Complied
15.247(c)	Antenna Conducted Spurious Emissions	0.009 - 25000	Complied
15.247(c)	Radiated Spurious Emissions	0.009 - 25000	Complied
15.247(d)	Peak Power Spectral Density	2400 – 2483.5	Complied
15.247(e)	Reserved Paragraph	N/A	Not Applicable
15.247(f)	Hybrid System Requirements	2400 – 2483.5	Not Applicable
15.247(g)	Frequency Hopping Channel Usage	2400 – 2438.5	Not Applicable
15.247(h)	Frequency Hopping Intelligence	2400 – 2483.5	Not Applicable

5.2 Result

In the configuration tested, the transceiver complied with the requirements of the specification.

SECTION 6.0 MEASUREMENTS AND RESULTS**6.1 General Comments:**

This section contains the test results only. Details of the test methods used and a list of the test equipment used during the measurements can be found in Appendix 1 of this report.

6.2 Test Results:**6.2.1 §15.203 Antenna Requirements**

The EUT uses either an Oxford Tec WAND2DBI-SMA antenna with a RP-SMA connector and a maximum gain of 2.0 dBi or a Cirocomm Technology 03A15304379240 antenna with a maximum gain of -5.0 dBi.

RESULT

The EUT complied with the specification.

6.2.2 §15.207 Conducted Disturbance at the AC Mains Ports

Frequency (MHz)	AC Mains Lead	Detector	Measured Level (dB μ V)	Limit (dB μ V)	Margin (dB)
4.56	Hot Lead	Peak (Note 1)	31.8	46.0	-14.2
11.83	Hot Lead	Peak (Note 1)	34.7	50.0	-15.3
12.20	Hot Lead	Peak (Note 1)	37.3	50.0	-12.7
12.48	Hot Lead	Peak (Note 1)	34.1	50.0	-15.9
17.80	Hot Lead	Peak (Note 1)	34.7	50.0	-15.3
18.35	Hot Lead	Peak (Note 1)	33.3	50.0	-16.7
0.16	Neutral Lead	Peak (Note 1)	50.7	55.7	-5.0
0.20	Neutral Lead	Peak (Note 1)	46.9	53.6	-6.7
0.24	Neutral Lead	Peak (Note 1)	42.0	52.2	-10.2
0.30	Neutral Lead	Peak (Note 1)	36.3	50.3	-14.0
4.56	Neutral Lead	Peak (Note 1)	32.8	46.0	-13.2
11.90	Neutral Lead	Peak (Note 1)	35.4	50.0	-14.6

Note 1: The reference detector used for the measurements was Quasi-Peak or Peak and the data was compared to the average limit; therefore, the EUT was deemed to meet both the average and quasi-peak limits.

RESULT

In the configuration tested, the EUT complied with the specification by 5.0 dB.


6.2.3 §15.247(a)(2) Emission Bandwidth

Frequency (MHz)	Emission 6 dB bandwidth (kHz)
2405	1615
2440	1570
2470	1570
2475	1565

RESULT


In the configuration tested, the 6 dB bandwidth was greater than 500 kHz; therefore, the EUT complied with the requirements of the specification (see spectrum analyzer plots below).

2405 MHz Emission 6 dB Bandwidth




Mkr	Trace	X-Axis	Value	Notes
1	Trace A	2.4048 GHz	10.90 dBm	
2-1	Trace A	-560.0000 kHz	-6.14 dB	
3-2	Trace A	1.6150 MHz	0.23 dB	

2440 MHz Emission 6 dB Bandwidth



Mkr	Trace	X-Axis	Value	Notes
1 ▽	Trace A	2.4398 GHz	9.74 dBm	
2-1▽	Trace A	-535.0000 kHz	-5.95 dB	
3-2▽	Trace A	1.5700 MHz	-0.54 dB	

2470 MHz Emission 6 dB Bandwidth



Start: 2.4675 GHz

Stop: 2.4725 GHz

Res BW: 100 kHz

Vid BW: 300 kHz

Sweep: 5.00 ms


10/26/2015 2:56:53 PM

Atten: 20 dB

ESU-40

Mkr	Trace	X-Axis	Value	Notes
1 ▽	Trace A	2.4702 GHz	8.84 dBm	
2-1▽	Trace A	-1.0100 MHz	-6.13 dB	
3-2▽	Trace A	1.5700 MHz	0.01 dB	

2475 MHz Emission 6 dB Bandwidth



Start: 2.4725 GHz

Stop: 2.4775 GHz

Res BW: 100 kHz

Vid BW: 300 kHz

Sweep: 5.00 ms

10/26/2015 3:09:35 PM

Atten: 20 dB

ESU-40

Mkr	Trace	X-Axis	Value	Notes
1 ▽	Trace A	2.4748 GHz	6.61 dBm	
2-1 ▽	Trace A	-545.0000 kHz	-6.02 dB	
3-2 ▽	Trace A	1.5650 MHz	-0.37 dB	

6.2.4 §15.247(b)(3) Peak Output Power


The maximum peak RF Conducted output power measured for this device was 13.89 dBm or 24.49 mW. The limit is 30 dBm or 1 Watt when using antennas with 6 dBi or less gain. The antenna has a maximum gain of 2.0 dBi.

Frequency (MHz)	Power Setting	Measured Output Power (dBm)	Measured Output Power (mW)
2405	2	13.89	24.49
2440	2	12.84	19.23
2470	2	12.33	17.10
2475	-4	9.87	9.71

RESULT

In the configuration tested, the RF peak output power was less than 1 Watt; therefore, the EUT complied with the requirements of the specification (see spectrum analyzer plots below).

2405 MHz Output Power Plot



Start: 2.4005 GHz

Stop: 2.4095 GHz

Res BW: 3 MHz

Vid BW: 10 MHz

Sweep: 5.00 ms


10/26/2015 2:36:37 PM

Atten: 20 dB

ESU-40

Mkr	Trace	X-Axis	Value	Notes
1	Trace A	2.4046 GHz	13.89 dBm	

2440 MHz Output Power Plot



Start: 2.4355 GHz

Stop: 2.4445 GHz

Res BW: 3 MHz

Vid BW: 10 MHz

Sweep: 5.00 ms


10/26/2015 2:51:17 PM

Atten: 20 dB

ESU-40


Mkr	Trace	X-Axis	Value	Notes
1	Trace A	2.4394 GHz	12.84 dBm	

2470 MHz Output Power Plot



Mkr	Trace	X-Axis	Value	Notes
1	Trace A	2.4694 GHz	12.33 dBm	

2475 MHz Output Power Plot



Start: 2.4705 GHz

Stop: 2.4795 GHz

Res BW: 3 MHz

Vid BW: 10 MHz

Sweep: 5.00 ms

10/26/2015 3:12:01 PM

Atten: 20 dB

ESU-40

Mkr	Trace	X-Axis	Value	Notes
1	Trace A	2.4744 GHz	9.87 dBm	

6.2.5 §15.247(c) Spurious Emissions**6.2.5.1 Conducted Spurious Emissions**

The frequency range from the lowest frequency generated or used in the device to the tenth harmonic of the highest fundamental frequency was investigated to measure any antenna-conducted emissions. The tables show the measurement data from spurious emissions noted across the frequency range when transmitting at the lowest frequency, middle frequency, and upper frequency. Shown below are plots with the EUT tuned to the upper and lower channels. These demonstrate compliance with the provisions of this section at the band edges.

The emissions must be attenuated 20 dB below the highest power level measured within the authorized band as measured with a 100 kHz RBW. The highest level measured using a 100 kHz RBW was 10.9 dBm; therefore, the criteria is $10.9 - 20 = -9.1$ dBm.

RESULT

Conducted spurious emissions were attenuated 20 dB or more from the fundamental; therefore, the EUT complies with the specification.

Transmitting at 2405 MHz (Power Setting at 2)

Frequency (MHz)	Corrected Level (dBm)	Criteria (dBm)	Margin (dB)
4810	-51.6	-9.1	-42.5
7215	-62.1	-9.1	-53.0
9620	-59.3	-9.1	-50.2
12025	-60.7	-9.1	-51.6
14430	-61.5	-9.1	-52.4
16835	-61.9	-9.1	-52.8
19240	-62.1	-9.1	-53.0
21645	-62.4	-9.1	-53.3
24050	-62.1	-9.1	-53.0

Transmitting at 2440 MHz (Power Setting at 2)

Frequency (MHz)	Corrected Level (dBm)	Criteria (dBm)	Margin (dB)
4880	-50.2	-9.1	-41.1
7320	-62.6	-9.1	-53.5
9760	-57.7	-9.1	-48.6
12200	-61.7	-9.1	-52.6
14640	-61.8	-9.1	-52.7
17080	-62.6	-9.1	-53.5
19520	-61.9	-9.1	-52.8

Frequency (MHz)	Corrected Level (dBm)	Criteria (dBm)	Margin (dB)
21960	-62.3	-9.1	-53.2
24400	-62.2	-9.1	-53.1


Transmitting at 2470 MHz (Power Setting at 2)

Frequency (MHz)	Corrected Level (dBm)	Criteria (dBm)	Margin (dB)
4940	-52.9	-9.1	-43.8
7410	-62.3	-9.1	-53.2
9880	-55.9	-9.1	-46.8
12350	-62.3	-9.1	-53.2
14820	-62.4	-9.1	-53.3
17290	-62.9	-9.1	-53.8
19760	-62.5	-9.1	-53.4
22230	-62.9	-9.1	-53.8
24700	-62.2	-9.1	-53.1


Transmitting at 2475 MHz (Power Setting at -4)

Frequency (MHz)	Corrected Level (dBm)	Criteria (dBm)	Margin (dB)
4950	-57.8	-9.1	-48.7
7425	-62.2	-9.1	-53.1
9900	-59.4	-9.1	-50.3
12375	-62.4	-9.1	-53.3
14850	-60.7	-9.1	-51.6
17325	-61.9	-9.1	-52.8
19800	-61.9	-9.1	-52.8
22275	-62.2	-9.1	-53.1
24750	-62.4	-9.1	-53.3


Lower Band Edge Plot – Transmitting at 2405 MHz Using 2 Power Setting



Upper Band Edge Plot – Transmitting at 2470 MHz Using 2 Power Setting



Upper Band Edge Plot – Transmitting at 2475 MHz Using -4 Power Setting



6.2.5.2 Radiated Emissions in the Restricted Bands of §15.205

The frequency range from the lowest frequency generated or used in the device to the tenth harmonic of the highest fundamental emission was investigated to measure any radiated emissions in the restricted bands. The following tables show measurements of any emission that fell into the restricted bands of §15.205. The tables show the worst-case emission measured from the EUT. For frequencies above 12.5 GHz, a measurement distance of 1 meter was used. The noise floor was a minimum of 6 dB below the limit. The emissions in the restricted bands must meet the limits specified in §15.209. Tabular data for each of the spurious emissions is shown below for each of the units. The spurious emissions tabular data is shown with the transmitter power set to 2 at the 2405 MHz, 2440 MHz, and 2475 MHz. Plots of the band edges are shown using power settings incorporated in production firmware; power setting 2 for 2405 MHz and 2470 MHz and power setting -4 for 2475 MHz. Data for both the Oxford Tec and Cirrocom antenna are shown.

RESULT

All emissions in the restricted bands of §15.205 met the limits specified in §15.209; therefore, the EUT complies with the specification.

6.2.5.2.1 Using Oxford TEC Antenna**Transmitting at 2405 MHz**

Frequency (MHz)	Detection Mode	Antenna Polarity	Receiver Reading (dB μ V)	Correction Factor (dB)	Field Strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
4810.0	Peak	Vertical	17.5	39.0	56.5	74.0	-17.5
4810.0	Average	Vertical	11.0	39.0	50.0	54.0	-4.0
4810.0	Peak	Horizontal	13.0	39.0	52.0	74.0	-22.0
4810.0	Average	Horizontal	4.2	39.0	43.2	54.0	-10.8
7215.0	Peak	Vertical	16.3	43.4	59.7	74.0	-14.3
7215.0	Average	Vertical	9.2	43.4	52.6	54.0	-1.4
7215.0	Peak	Horizontal	14.0	43.4	57.4	74.0	-16.6
7215.0	Average	Horizontal	6.7	43.4	50.1	54.0	-3.9
12025.0	Peak	Vertical	4.4	49.0	53.4	74.0	-20.6
12025.0	Average	Vertical	-5.2	49.0	43.8	54.0	-10.2
12025.0	Peak	Horizontal	3.5	49.0	52.5	74.0	-21.5
12025.0	Average	Horizontal	-5.2	49.0	43.8	54.0	-10.2


Transmitting at 2440 MHz

Frequency (MHz)	Detection Mode	Antenna Polarity	Receiver Reading (dB μ V)	Correction Factor (dB)	Field Strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
4880.0	Peak	Vertical	15.4	39.2	54.6	74.0	-19.4
4880.0	Average	Vertical	8.3	39.2	47.5	54.0	-6.5
4880.0	Peak	Horizontal	12.6	39.2	51.8	74.0	-22.2
4880.0	Average	Horizontal	2.6	39.2	41.8	54.0	-12.2
7320.0	Peak	Vertical	14.0	43.7	57.7	74.0	-16.3
7320.0	Average	Vertical	6.6	43.7	50.3	54.0	-3.7
7320.0	Peak	Horizontal	12.5	43.7	56.2	74.0	-17.8
7320.0	Average	Horizontal	4.8	43.7	48.5	54.0	-5.5
12200.0	Peak	Vertical	3.5	49.1	52.6	74.0	-21.4
12200.0	Average	Vertical	-5.8	49.1	43.3	54.0	-10.7
12200.0	Peak	Horizontal	2.1	49.1	51.2	74.0	-22.8
12200.0	Average	Horizontal	-6.7	49.1	42.4	54.0	-11.6

Transmitting at 2475 MHz


Frequency (MHz)	Detection Mode	Antenna Polarity	Receiver Reading (dB μ V)	Correction Factor (dB)	Field Strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
4950.0	Peak	Vertical	16.7	39.3	56.0	74.0	-18.0
4950.0	Average	Vertical	9.9	39.3	49.2	54.0	-4.8
4950.0	Peak	Horizontal	13.9	39.3	53.2	74.0	-20.8
4950.0	Average	Horizontal	6.6	39.3	45.9	54.0	-8.1
7425.0	Peak	Vertical	10.1	44.0	54.1	74.0	-19.9
7425.0	Average	Vertical	3.5	44.0	47.5	54.0	-6.5
7425.0	Peak	Horizontal	6.2	44.0	50.2	74.0	-23.8
7425.0	Average	Horizontal	-1.9	44.0	42.1	54.0	-11.9
12375.0	Peak	Vertical	4.6	49.1	53.7	74.0	-20.3
12375.0	Average	Vertical	-4.7	49.1	44.4	54.0	-9.6
12375.0	Peak	Horizontal	2.9	49.1	52.0	74.0	-22.0
12375.0	Average	Horizontal	-5.0	49.1	44.1	54.0	-9.9

Radiated Band Edge Plot Transmitting at 2405 MHz




Mkr	Trace	X-Axis	Value	Notes
1 	Peak	2.3899 GHz	62.77 dBuV	
2 	Average	2.3900 GHz	51.76 dBuV	

Radiated Upper Band Edge Plot Transmitting at 2470 MHz



Mkr	Trace	X-Axis	Value	Notes
1	Peak	2.4835 GHz	64.20 dBuV	
2	Average	2.4835 GHz	52.11 dBuV	

Radiated Upper Band Edge Plot Transmitting at 2475 MHz



Mkr	Trace	X-Axis	Value	Notes
1	Peak	2.4835 GHz	62.90 dBuV	
2	Average	2.4835 GHz	53.16 dBuV	

6.2.5.2.2 Using Cirocomm Technology Antenna**Transmitting at 2405 MHz**

Frequency (MHz)	Detection Mode	Antenna Polarity	Receiver Reading (dB μ V)	Correction Factor (dB)	Field Strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
4810.0	Peak	Vertical	19.0	39.0	58.0	74.0	-16.0
4810.0	Average	Vertical	12.4	39.0	51.4	54.0	-2.6
4810.0	Peak	Horizontal	15.3	39.0	54.3	74.0	-19.7
4810.0	Average	Horizontal	5.4	39.0	44.4	54.0	-9.6
7215.0	Peak	Vertical	9.2	43.4	52.6	74.0	-21.4
7215.0	Average	Vertical	0.4	43.4	43.8	54.0	-10.2
7215.0	Peak	Horizontal	9.4	43.4	52.8	74.0	-21.2
7215.0	Average	Horizontal	1.1	43.4	44.5	54.0	-9.5
12025.0	Peak	Vertical	5.0	49.0	54.0	74.0	-20.0
12025.0	Average	Vertical	-3.2	49.0	45.8	54.0	-8.2
12025.0	Peak	Horizontal	3.0	49.0	52.0	74.0	-22.0
12025.0	Average	Horizontal	-5.0	49.0	44.0	54.0	-10.0


Transmitting at 2440 MHz

Frequency (MHz)	Detection Mode	Antenna Polarity	Receiver Reading (dB μ V)	Correction Factor (dB)	Field Strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
4880.0	Peak	Vertical	18.6	39.2	57.8	74.0	-16.2
4880.0	Average	Vertical	12.2	39.2	51.4	54.0	-2.6
4880.0	Peak	Horizontal	15.8	39.2	55.0	74.0	-19.0
4880.0	Average	Horizontal	8.1	39.2	47.3	54.0	-6.7
7320.0	Peak	Vertical	8.4	43.7	52.1	74.0	-21.9
7320.0	Average	Vertical	-0.6	43.7	43.1	54.0	-10.9
7320.0	Peak	Horizontal	6.8	43.7	50.5	74.0	-23.5
7320.0	Average	Horizontal	-0.3	43.7	43.4	54.0	-10.6
12200.0	Peak	Vertical	4.1	49.1	53.2	74.0	-20.8
12200.0	Average	Vertical	-5.0	49.1	44.1	54.0	-9.9
12200.0	Peak	Horizontal	3.3	49.1	52.4	74.0	-21.6
12200.0	Average	Horizontal	-6.2	49.1	42.9	54.0	-11.1

Transmitting at 2475 MHz


Frequency (MHz)	Detection Mode	Antenna Polarity	Receiver Reading (dB μ V)	Correction Factor (dB)	Field Strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
4950.0	Peak	Vertical	16.1	39.3	55.4	74.0	-18.6
4950.0	Average	Vertical	9.2	39.3	48.5	54.0	-5.5
4950.0	Peak	Horizontal	14.4	39.3	53.7	74.0	-20.3
4950.0	Average	Horizontal	7.0	39.3	46.3	54.0	-7.7
7425.0	Peak	Vertical	9.4	44.0	53.4	74.0	-20.6
7425.0	Average	Vertical	2.4	44.0	46.4	54.0	-7.6
7425.0	Peak	Horizontal	6.4	44.0	50.4	74.0	-23.6
7425.0	Average	Horizontal	-1.3	44.0	42.7	54.0	-11.3
12375.0	Peak	Vertical	6.2	49.1	55.3	74.0	-18.7
12375.0	Average	Vertical	-4.2	49.1	44.9	54.0	-9.1
12375.0	Peak	Horizontal	3.8	49.1	52.9	74.0	-21.1
12375.0	Average	Horizontal	-5.0	49.1	44.1	54.0	-9.9

Radiated Band Edge Plot Transmitting at 2405 MHz




Mkr	Trace	X-Axis	Value	Notes
1	Peak	2.3898 GHz	59.79 dBuV	
2	Average	2.3900 GHz	47.96 dBuV	

Radiated Upper Band Edge Plot Transmitting at 2470 MHz



Mkr	Trace	X-Axis	Value	Notes
1	Peak	2.4842 GHz	61.83 dBuV	
2	Average	2.4835 GHz	49.37 dBuV	

Radiated Upper Band Edge Plot Transmitting at 2475 MHz



Mkr	Trace	X-Axis	Value	Notes
1 	Peak	2.4835 GHz	62.84 dBuV	
2 	Average	2.4835 GHz	50.27 dBuV	

6.2.6 §15.247(d) Peak Power Spectral Density


The peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. The result of this testing is summarized in the table below.

Frequency (MHz)	Power Setting	Measurement (dBm)	Criteria (dBm)
2405	2	-0.73	8.0
2440	2	-2.76	8.0
2470	2	-2.35	8.0
2475	-4	-5.43	8.0

RESULT


The maximum peak power spectral density was -0.73 dBm. The EUT complies with the specification by 8.73 dB.

Transmitting at 2405 MHz




Mkr	Trace	X-Axis	Value	Notes
1 ▽	Trace A	2.4046 GHz	-0.73 dBm	

Transmitting at 2440 MHz




Mkr	Trace	X-Axis	Value	Notes
1 ▽	Trace A	2.4404 GHz	-2.76 dBm	

Transmitting at 2470 MHz



Mkr	Trace	X-Axis	Value	Notes
1 ▽	Trace A	2.4694 GHz	-2.35 dBm	

Transmitting at 2475 MHz



Mkr	Trace	X-Axis	Value	Notes
1 ▽	Trace A	2.4754 GHz	-5.43 dBm	

APPENDIX 1 TEST PROCEDURES AND TEST EQUIPMENT**A1.1 §15.207 Conducted Disturbance at the AC Mains**

The conducted disturbance at mains ports from the EUT was measured using a spectrum analyzer with a quasi-peak adapter for peak, quasi-peak and average readings. The quasi-peak adapter uses a bandwidth of 9 kHz, with the spectrum analyzer's resolution bandwidth set at 100 kHz, for readings in the 150 kHz to 30 MHz frequency ranges.

The conducted disturbance at mains ports measurements are performed in a screen room using a (50 Ω/50 µH) Line Impedance Stabilization Network (LISN).

Where mains flexible power cords are longer than 1 m, the excess cable is folded back and forth as far as possible so as to form a bundle not exceeding 0.4 m in length.

Where the EUT is a collection of equipment with each device having its own power cord, the point of connection for the LISN is determined from the following rules:

- (a) Each power cord, which is terminated in a mains supply plug, shall be tested separately.
- (b) Power cords, which are not specified by the manufacturer to be connected via a host unit, shall be tested separately.
- (c) Power cords which are specified by the manufacturer to be connected via a host unit or other power supplying equipment shall be connected to that host unit and the power cords of that host unit connected to the LISN and tested.
- (d) Where a special connection is specified, the necessary hardware to effect the connection is supplied by the manufacturer for the testing purpose.
- (e) When testing equipment with multiple mains cords, those cords not under test are connected to an artificial mains network (AMN) different than the AMN used for the mains cord under test.


For AC mains port testing, desktop EUT are placed on a non-conducting table at least 0.8 meters from the metallic floor and placed 40 cm from the vertical coupling plane (copper plating in the wall behind EUT table). Floor standing equipment is placed directly on the earth grounded floor.

Type of Equipment	Manufacturer	Model Number	Barcode Number	Date of Last Calibration	Due Date of Calibration
Spectrum Analyzer	Hewlett Packard	8566B	644	03/23/2015	03/23/2016
Quasi-Peak Detector	Hewlett Packard	85650A	1130	03/16/2015	03/16/2016
LISN	Nemko	LISN-COMM-50	1424	02/25/2015	02/25/2016
Conductance Cable Wanship Site #2	Nemko	Cable J	840	12/23/2014	12/23/2015
Transient Limiter	Hewlett Packard	11947A	768	12/23/2014	12/23/2015

An independent calibration laboratory or Nemko-CCL, Inc. personnel calibrates all the equipment listed above at intervals defined in ANSI C63.4:2003 Section 4.4 following outlined calibration procedures. All

measurement instrumentation is traceable to the National Institute of Standards and Technology (NIST). Supporting documentation relative to tractability is on file and is available for examination upon request.


Conducted Emissions Test Setup



A1.2 Direct Connection at the Antenna Port Tests

Type of Equipment	Manufacturer	Model Number	Barcode Number	Date of Last Calibration	Due Date of Calibration
Spectrum Analyzer/Receiver	Rohde & Schwarz	ESU40	1229	04/07/2015	04/07/2016
6 dB Attenuator	Hewlett Packard	8491A	1103	12/23/2014	12/23/2015
Low Loss Cable	N/A	N/A	1116	12/23/2014	12/23/2015

An independent calibration laboratory or Nemko-CCL, Inc. personnel calibrates all the equipment listed above at intervals defined in ANSI C63.4:2003 Section 4.4 following outlined calibration procedures. All measurement instrumentation is traceable to the National Institute of Standards and Technology (NIST). Supporting documentation relative to tractability is on file and is available for examination upon request.

Test Configuration Block Diagram

A1.3 §15.247(c) Radiated Spurious Emissions in the Restricted Bands

The radiated emissions from the intentional radiator were measured using a spectrum analyzer with a quasi-peak adapter for peak and quasi-peak readings.

A loop antenna was used to measure emissions below 30 MHz. Emission readings more than 20 dB below the limit at any frequency may not be listed in the reported data. For frequencies between 9 kHz and 30 MHz, or the lowest frequency generated or used in the device greater than 9 kHz, and less than 30 MHz, the spectrum analyzer resolution bandwidth was set to 9 kHz and the video bandwidth was set to 30 kHz. For average measurements, the spectrum analyzer average detector was used.

For frequencies above 30 MHz, an amplifier and preamplifier were used to increase the sensitivity of the measuring instrumentation. The quasi-peak adapter uses a bandwidth of 120 kHz, with the spectrum analyzer's resolution bandwidth set at 1 MHz, for readings in the 30 to 1000 MHz frequency ranges. For peak emissions above 1000 MHz the spectrum analyzer's resolution bandwidth was set to 1 MHz and the video bandwidth was set to 3 MHz. For average measurements above 1000 MHz the spectrum analyzer's resolution bandwidth was set to 1 MHz and the average detector of the analyzer was used.

A biconilog antenna was used to measure the frequency range of 30 to 1000 MHz and a Double Ridge Guide Horn antenna was used to measure the frequency range of 1 GHz to 18 GHz, and a Pyramidal Horn antenna was used to measure the frequency range of 18 GHz to 25 GHz, at a distance of 3 meters and/or 1 meter from the EUT. The readings obtained by the antenna are correlated to the levels obtained with a tuned dipole antenna by adding antenna factors.

The configuration of the EUT was varied to find the maximum radiated emission. The EUT was connected to the peripherals listed in Section 2.3 via the interconnecting cables listed in Section 2.4. A technician manually manipulated these interconnecting cables to obtain worst-case radiated disturbance. The EUT was rotated 360 degrees, and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission. Where there were multiple interface ports all of the same type, cables are either placed on all of the ports or cables added to these ports until the emissions do not increase by more than 2 dB.


Desktop EUT are measured on a non-conducting table 0.8 meters above the ground plane for frequencies below 1000 MHz and at 1.5 meters for frequencies greater than 1000 MHz. The table is placed on a turntable, which is level with the ground plane. For equipment normally placed on floors, the equipment shall be placed directly on the turntable.

For radiated emission testing at 30 MHz or above that is performed at distances closer than the specified distance, an inverse proportionality factor of 20 dB per decade is used to normalize the measured data for determining compliance.

Type of Equipment	Manufacturer	Model Number	Barcode Number	Date of Last Calibration	Due Date of Calibration
Spectrum Analyzer/Receiver	Rohde & Schwarz	ESU40	1229	04/07/2015	04/07/2016
Spectrum Analyzer	Hewlett Packard	8566B	644	03/23/2015	03/23/2016
Quasi-Peak Detector	Hewlett Packard	85650A	1130	03/16/2015	03/16/2016
Loop Antenna	EMCO	6502	176	03/17/2015	03/17/2017
Biconilog Antenna	EMCO	3142	713	10/22/2014	10/22/2016
Double Ridged Guide Antenna	EMCO	3115	735	03/17/2015	03/17/2017
Pyramidal Standard Gain Horn	EMC Test System	3160-09	1052	04/10/2009	ICO
High Frequency Amplifier	Miteq	AFS4-00101800-35-10P-4	1179	06/29/2015	06/29/2016
20' High Frequency Cable	Microcoax	UFB197C-1-3120-000000	1297	12/23/2014	12/23/2015
3 Meter Radiated Emissions Cable Wanship Site #2	Microcoax	UFB205A-0-4700-000000	1295	12/23/2014	12/23/2015
Pre/Power-Amplifier	Hewlett Packard	8447F	762	09/18/2015	09/18/2016
6 dB Attenuator	Hewlett Packard	8491A	1103	12/23/2014	12/23/2015

An independent calibration laboratory or Nemko-CCL, Inc. personnel calibrates all the equipment listed above at intervals defined in ANSI C63.4:2003 Section 4.4 following outlined calibration procedures. All measurement instrumentation is traceable to the National Institute of Standards and Technology (NIST). Supporting documentation relative to tractability is on file and is available for examination upon request.

Radiated Emissions Test Setup




APPENDIX 2 PHOTOGRAPHS

Photograph 1 – Front View of the Radiated Emission Setup




Photograph 2 – Back View of the Radiated Emission Setup



Photograph 3 – Front View of the Conducted Emission Setup



Photograph 4 – Back View of the Conducted Emission Setup




Photograph 5 – Front View of the EUT




Photograph 6 – View of the Back of the EUT (Note that in production, the HDMI In port will be removed and covered)



Photograph 7 - View of the Top Side of the PCB



Photograph 8 – View of the Bottom of the PCB



Photograph 9 – View of the 802.15.4 Transceiver Circuitry with RF Shield



Photograph 10 – View of the Circuitry of the 802.15.4 Transceiver with RF Shield Removed

