


MPE Report

Applicant : Control4
Product Type : 802.11ac 4x4 Wave 2 Access Point
Trade Name : pakedge
Model Number : WA-4200, WA-4200-1, WA-4200-C, WA-4200-C-1
Applicable Standard : ANSI / IEEE Std.C95.1
47 CFR § 2.1091
47 CFR § 1.1310
Received Date : May 30, 2019
Test Period : Nov. 11, 2019
Issued Date : Nov. 21, 2019

Issue by

Approved By : 
(Mark Duan)

Tested By : 
(Kris Pan)

A Test Lab Techno Corp.
No. 140-1, Changan Street, Bade District,
Taoyuan City 33465, Taiwan (R.O.C.)
Tel : +886-3-2710188 / Fax : +886-3-2710190



Taiwan Accreditation Foundation accreditation number: 1330

Note: This report shall not be reproduced except in full, without the written approval of A Test Lab Techno Corp. This document may be altered or revised by A Test Lab Techno Corp. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, or any government agencies. The test results in the report only apply to the tested sample.



Revision History

Rev.	Issued Date	Revisions	Revised By
00	Aug. 21, 2019	Initial Issue	Jennifer Liu
01	Oct. 02, 2019	Page 6 Revised EUT Modify Description.	Jennifer Liu
02	Nov. 21, 2019	Page 6 Removed EUT modify description. Page 8 、 9 Revised RF Output Power. Page 10 Revised Test Results.	Jennifer Liu



Contents

1.	Description of Equipment under Test (EUT).....	5
2.	Human Exposure Assessment.....	7
3.	RF Output Power	8
4.	Test Results	10



1. Reference Testing Standards

Standard	Description	Version
ANSI/IEEE C95.1	American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 300 KHz to 100 GHz, New York.	1992



2. Description of Equipment under Test (EUT)

Applicant	Control4 11734 S. Election Road, Draper, Utah, 84020, United States							
Manufacturer	Control4 11734 S. Election Road, Draper, Utah, 84020, United States							
Product Type	802.11ac 4x4 Wave 2 Access Point							
Trade Name	pakedge							
Model Number	WA-4200, WA-4200-1, WA-4200-C, WA-4200-C-1							
Difference description of model number	Difference is due to selling region.							
FCC ID	R33WA4200							
Frequency Range	Operate Band				Frequency Range (MHz)			
	IEEE 802.11b / 802.11g / 802.11n 2.4 GHz 20 MHz (64QAM/256QAM)				2412 - 2462			
	IEEE 802.11n 2.4 GHz 40 MHz (64QAM/256QAM)				2422 - 2452			
	IEEE 802.11a U-NII Band I				5180 - 5240			
	IEEE 802.11a U-NII Band III				5745 - 5825			
	IEEE 802.11n 5 GHz / 802.11ac 20 MHz U-NII Band I				5180 - 5240			
	IEEE 802.11n 5 GHz / 802.11ac 20 MHz U-NII Band III				5745 - 5825			
	IEEE 802.11n 5 GHz / 802.11ac 40 MHz U-NII Band I				5190 - 5230			
	IEEE 802.11n 5 GHz / 802.11ac 40 MHz U-NII Band III				5755 - 5795			
	IEEE 802.11ac 80 MHz U-NII Band I				5210			
	IEEE 802.11ac 80 MHz U-NII Band III				5775			
Antenna Information	Band	Antenna	Model	Type	Frequency (MHz)	Max. Gain (dBi)		
	2.4 GHz	ANT-0	5718A0346300	Metal PIFA Antenna	2412-2462	2.86		
		ANT-1	5718A0347300	Metal PIFA Antenna	2412-2462	3.12		
		ANT-2	5718A0348300	Metal PIFA Antenna	2412-2462	3.14		
		ANT-3	5718A0349300	Metal PIFA Antenna	2412-2462	3.29		
		G _{ANT}			3.11			
		Directional Gain			9.12			
	5 GHz	ANT-0	5718A0350300	Metal PIFA Antenna	5150-5250	4.87		
					5725-5850	5.07		
		ANT-1	5718A0351300	Metal PIFA Antenna	5150-5250	4.61		
					5725-5850	5.50		
		ANT-2	5718A0352300	Metal PIFA Antenna	5150-5250	4.31		
					5725-5850	5.36		
		ANT-3	5718A0353300	Metal PIFA Antenna	5150-5250	4.15		
					5725-5850	5.84		
		G _{ANT}			5150-5250	4.47		
					5725-5850	5.45		
		Directional Gain			5150-5250	10.49		
					5725-5850	11.47		



Antenna Delivery	IEEE 802.11b / IEEE 802.11g: 4TX (CDD) IEEE 802.11n 2.4GHz 20 MHz / 40 MHz: 4TX (STBC / Beamforming on) IEEE 802.11a: 4TX (CDD) IEEE 802.11ac 20 MHz / 40 MHz / 80 MHz: 4TX (STBC / Beamforming on)
RF Evaluation	0.351 mW/cm ²
Temperature Range	0 ~ +50°C

The above equipment was tested by A Test Lab Techno Corp. For compliance with the requirements set forth in 47 CFR § 2.1091 / 47 CFR § 1.1310. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties



3. Human Exposure Assessment

Due to the design and installation of this product, it is not possible to conduct SAR evaluation. This is because client either manufactures or supplies the antenna(s) that will be used in the installation of this product. Therefore, this product will be evaluated as a mobile device per 47 CFR § 1.1310 titled "Radiofrequency radiation exposure limits", generally referred to as MPE limits.

In 47 CFR § 2.1091, paragraph (b) defines a mobile device as "a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 cm is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons. " This product is intended to be installed into a vehicle such that the unit is physically secured at one location. In the installation guide supplied with the product,

Client has made the following statement: "IMPORTANT: To meet the FCC's RF Exposure Guidelines, the antenna should be installed so there is at least 20 cm of separation between the body of the user and nearby persons and the antenna". Based on the installation of the transceiver and the antenna, the transmitters radiating structure is more than 20 cm from the user. Thus, this product is a "mobile device" as defined in section § 2.1091 paragraph (b).

Exposure evaluation

$$S = \frac{PG}{4\pi R^2}$$

Where

S: power density

P: power input to the antenna

G: power gain of the antenna in the direction of interest relative to an isotropic radiator.

R: distance to the center of radiation of the antenna.

4. RF Output Power

The conducted power turn-up tolerance reference manufacturer specification.

Band	Data Rate (Mbps)	Frequency (MHz)	Average Conducted power (dBm)				
			ANT-0	ANT-1	ANT-2	ANT-3	ANT-0+1+2+3
IEEE 802.11b	1M	2412.0	17.01	17.56	18.06	17.16	23.49
		2437.0	16.95	17.11	17.95	17.18	23.34
		2462.0	17.21	17.76	17.62	17.52	23.55
IEEE 802.11g	6M	2412.0	15.45	15.62	16.47	15.93	21.91
		2437.0	15.37	15.56	16.26	15.85	21.79
		2462.0	15.05	15.46	15.85	15.73	21.55
IEEE 802.11n 2.4 GHz 20 MHz (256QAM)	26M	2412.0	15.11	15.21	16.09	15.51	21.52
		2437.0	15.06	15.18	15.89	15.54	21.45
		2462.0	13.57	14.12	14.35	14.35	20.13
IEEE 802.11n 2.4 GHz 40 MHz (256QAM)	54M	2422.0	13.32	13.58	14.43	13.66	19.79
		2437.0	15.73	15.92	16.94	16.14	22.23
		2452.0	12.98	13.14	13.78	13.43	19.36
IEEE 802.11a	6M	5180.0	17.35	16.94	16.04	15.40	22.52
		5200.0	17.41	17.09	16.06	15.54	22.61
		5220.0	17.43	17.05	16.01	15.62	22.61
		5240.0	17.51	17.03	15.94	15.60	22.61
		5745.0	19.46	19.12	18.56	18.70	25.00
		5765.0	19.28	19.16	18.51	18.53	24.90
		5785.0	19.20	19.21	18.48	18.39	24.86
		5805.0	19.01	19.33	18.53	18.27	24.83
IEEE 802.11ac 20 MHz	26M	5825.0	18.82	19.52	18.60	17.97	24.78
		5180.0	19.02	18.64	17.81	17.16	24.24
		5200.0	19.08	18.65	17.90	17.23	24.29
		5220.0	19.04	18.68	17.94	17.38	24.33
		5240.0	19.03	18.71	17.88	17.31	24.31
		5745.0	18.03	17.85	17.17	17.42	23.65
		5765.0	17.85	17.73	17.17	17.25	23.53
		5785.0	17.78	17.85	17.15	17.12	23.51
IEEE 802.11ac 40 MHz	54M	5805.0	17.66	18.02	17.18	17.01	23.51
		5825.0	17.58	17.95	17.24	16.74	23.42
		5190.0	18.98	18.50	17.63	17.02	24.12
		5230.0	18.92	18.71	17.60	17.16	24.18
IEEE 802.11ac 80 MHz	117.2M	5755.0	17.65	17.51	16.81	17.04	23.29
		5795.0	17.46	17.68	16.85	16.75	23.22
		5210.0	15.29	14.91	13.92	13.44	20.47
		5775.0	17.97	18.02	17.22	17.30	23.66

Note: The relevant measured result has the offset with cable loss already.

Beamforming on

Band	Data Rate (Mbps)	Frequency (MHz)	Average Conducted power (dBm)				
			ANT-0	ANT-1	ANT-2	ANT-3	ANT-0+1+2+3
IEEE 802.11n 2.4 GHz 20 MHz (256QAM)	26M	2412.0	8.34	8.62	9.34	8.78	14.81
		2437.0	8.37	8.67	9.15	8.67	14.74
		2462.0	6.88	7.39	7.87	7.53	13.45
IEEE 802.11n 2.4 GHz 40 MHz (256QAM)	54M	2422.0	6.34	6.85	7.62	6.92	12.98
		2437.0	9.03	9.26	10.13	9.30	15.47
		2452.0	6.13	6.42	7.11	6.61	12.60
IEEE 802.11ac 20 MHz	26M	5180.0	12.41	11.89	11.28	10.77	17.65
		5200.0	12.44	12.06	11.41	10.74	17.73
		5220.0	12.46	12.22	11.42	10.91	17.82
		5240.0	12.34	12.03	11.29	10.83	17.68
		5745.0	11.32	11.02	10.73	10.94	17.03
		5765.0	11.18	10.98	10.74	10.78	16.94
		5785.0	11.01	11.06	10.71	10.71	16.90
		5805.0	10.90	11.17	10.76	10.62	16.89
IEEE 802.11ac 40 MHz	54M	5825.0	10.82	12.55	10.82	10.34	17.24
		5190.0	12.22	11.70	10.91	10.42	17.39
		5230.0	12.19	11.89	10.85	10.68	17.47
		5755.0	11.02	10.80	10.05	10.60	16.65
IEEE 802.11ac 80 MHz	117.2M	5795.0	10.80	10.91	10.05	10.29	16.55
		5210.0	8.65	8.14	7.51	6.87	13.86
		5775.0	11.36	11.27	10.55	10.73	17.01

Note:1. The relevant measured result has the offset with cable loss already.

2. Evaluated high and low data rate, the report record worst case low data rate measurement results.

5. Test Results

Antenna	Band	Frequency (MHz)	Limit (mw)	Distance [R] (cm)	Max tune-up Power (upper limit) [P] (dBm)	ANT Gain (dBi)	Numeric Gain [G]	Duty Cycle	Power with Duty cycle [TP] (mW)	Power Density [S] (mw/cm ²)
Wi-Fi Antenna	2.4 GHz	2412-2462	1	20	24.05	3.11	2.05	1	521.23	0.104
	5 GHz U-NII Band I	5180-5240	1	20	24.83	4.47	2.80	1	851.04	0.169
	5 GHz U-NII Band III	5745-5825	1	20	25.50	5.45	3.51	1	1244.01	0.247
Wi-Fi Antenna (Beamforming on)	2.4 GHz	2412-2462	1	20	15.97	9.12	8.17	1	323.1	0.064
	5 GHz U-NII Band I	5180-5240	1	20	18.32	10.49	11.19	1	759.49	0.151
	5 GHz U-NII Band III	5745-5825	1	20	17.74	11.47	14.03	1	833.68	0.166

Note:

1. Mobile or fixed location transmitters, minimum separation distance is 20 cm, even if calculations indicate MPE distance is less.
2. We used the maximum power to provide MPE results.
3. The Numeric Gain calculated by $10^{(\text{ant. Gain(dBi)} / 10)}$.
4. The MPE results are evaluated by lowest data rate for WLAN.
5. The device operating IEEE 802.11 a/b/g mode is 4TX MIMO / CDD.

The device operating IEEE 802.11 ac/n mode is 4TX MIMO / STBC.

Simultaneous Transmitting :

$$\text{Total MPE} = 2.4\text{GHz MPE} + 5\text{GHz MPE} = 0.104 + 0.247 = 0.351 \text{ (mw)/cm}^2 < 1 \text{ (mw)/cm}^2$$

---END---