

8. RADIO FREQUENCY EXPOSURE

Limit

According to §1.1310 and §2.1091 RF exposure is calculated.

Table: Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Power Density (S) (mW/cm ²)
0.3–1.34	*(100)
1.34–30	*(180/f ²)
30–300	0.2
300–1500	f/1500
1500–100,000	1.0

F = frequency in MHz

* = Plane-wave equivalent power density

Maximum Permissible Exposure

The MPE was calculated at 20cm to show compliance with the power density limit.

$$S = PG/4\pi R^2$$

S = Power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna.

Note:

1. Manufacturer declared that GSM 850 Integral Antenna maximum gain 3.0dBi,
PCS 1900 Integral Antenna maximum gain, 3.0dBi.
2. Manufacturer declared that the nearest distance between human and the EUT is 20cm.
3. Only record worst case data.

GSM 850 Band

Max. Peak output Power in dBm (ERP)	30.61	dBm
Max. Peak output Power in mW (ERP)	1150.80	mW
Prediction distance	20	cm
Prediction frequency	836.6	MHz
Antenna Gain(typical)	3.0	dBi
Antenna Gain(numeric)	2.0	
Power density at prediction frequency(S)	0.4581	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	0.5577	mW/cm ²

PCS 1900 Band

Max. Peak output Power in dBm (EIRP)	26.99	dBm
Max. Peak output Power in mW (EIRP)	490.91	mW
Prediction distance	20	cm
Prediction frequency	1880.0	MHz
Antenna Gain(typical)	3.0	dBi
Antenna Gain(numeric)	2.0	
Power density at prediction frequency(S)	0.1954	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1	mW/cm ²

Test Results

The power density level worst case at 20 cm is below the uncontrolled exposure limit.