



TEST REPORT

No. 2010TAR386

for

TCT Mobile Limited

GSM/GPRS/EDGE dual band mobile phone

Model Name: Jade Lite A

Marketing Name : OT-799A

FCC ID: RAD152

with

Hardware Version: PROTO

Software Version: SW221

Issued Date: Dec 13, 2010

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of TMC Beijing.

Test Laboratory:

DAR accreditation (DIN EN ISO/IEC 17025): No. DGA-PL-114/01-02

FCC 2.948 Listed: No.733176

IC O.A.T.S listed: No.6629A-1

TMC Beijing, Telecommunication Metrology Center of Ministry of Industry and Information Technology

3/F Shou Xiang Technology Building, No.51 Xueyuan Road, Hai Dian District, Beijing, P. R. China,100191.

Tel:+86(0)10-62304633-2604, Fax:+86(0)10-62304793, Email:welcome@emcite.com, web: www.emcite.com

CONTENTS

1. TEST LABORATORY	3
1.1. TESTING LOCATION	3
1.2. TESTING ENVIRONMENT	3
1.3. PROJECT DATA	3
1.4. SIGNATURE	3
2. CLIENT INFORMATION	4
2.1. APPLICANT INFORMATION	4
2.2. MANUFACTURER INFORMATION	4
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	5
3.1. ABOUT EUT	5
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	5
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	5
3.4. GENERAL DESCRIPTION	6
4. REFERENCE DOCUMENTS	6
4.1. REFERENCE DOCUMENTS FOR TESTING	6
5. LABORATORY ENVIRONMENT	7
6. SUMMARY OF TEST RESULTS	8
7. TEST EQUIPMENTS UTILIZED	9
ANNEX A: MEASUREMENT RESULTS.....	10
A.1 OUTPUT POWER (§22.913(A)/§24.232(B)).....	10
A.2 EMISSION LIMIT (§2.1051/§24.238).....	16
A.3 CONDUCTED EMISSION (§15.107§15.207)	21
A.4 FREQUENCY STABILITY (§2.1055/§24.235)	27
A.5 OCCUPIED BANDWIDTH (§2.1049(H)(I))	29
A.6 EMISSION BANDWIDTH (§22.917(B)/§24.238(B))	41
A.7 BAND EDGE COMPLIANCE (§22.917(B)/§24.238(B)).....	53
A.8 CONDUCTED SPURIOUS EMISSION (§2.1057/§22.917/§24.238)	59

1. Test Laboratory

1.1. Testing Location

Company Name: TMC Beijing, Telecommunication Metrology Center of MIIT
Address: 3/F Shou Xiang Technology Building, No.51 Xueyuan Road, Hai
Dian District, Beijing, P. R. China
Postal Code: 100191
Telephone: 00861062304633
Fax: 00861062304793


1.2. Testing Environment

Normal Temperature: 15-35℃
Relative Humidity: 20-75%


1.3. Project data

Testing Start Date: Sep 6, 2010
Testing End Date: Dec 13, 2010

1.4. Signature



Zi Xiaogang
(Prepared this test report)



Sun Xiangqian
(Reviewed this test report)



Lu Bingsong
Deputy Director of the laboratory
(Approved this test report)

2. Client Information

2.1. Applicant Information

Company Name: TCT Mobile Limited
Address /Post: 4F, South Building, No.2966, JinKe Road, Zhangjiang High-Tech Park
City: Shanghai
Postal Code: 201203
Country: P.R.China
Telephone: 0086 2161460890
Fax: 0086 2161460602

2.2. Manufacturer Information

Company Name: TCT Mobile Limited
Address /Post: 4F, South Building, No.2966, JinKe Road, Zhangjiang High-Tech Park
City: Shanghai
Postal Code: 201203
Country: P.R.China
Telephone: 0086 2161460890
Fax: 0086 2161460602

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	GSM/GPRS/EDGE dual band mobile phone
Model Name	Jade Lite A
Marketing Name	OT-799A
FCC ID	RAD152
Frequency	GSM 850MHz; PCS 1900MHz
Antenna	Internal
Power supply	Battery or Charger (AC Adaptor)
Output power	29.05 dBm maximum ERP measured for GSM850
Extreme vol. Limits	3.5VDC to 4.2VDC (nominal: 3.8VDC)

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of Telecommunication Metrology Center of MIIT of People's Republic of China.

3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version
N01	012454000010871	PROTO	SW221
N02	012454000011275	PROTO	SW221

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description	SN
AE1	Battery	/
AE2	Charger	/
AE3	Charger	/

AE1

Model	CAB30P0000C1
Manufacturer	BYD
Capacitance	850mAh
Nominal Voltage	3.7V

AE2

Model	CBA30Y0AG0C1
Manufacturer	BYD
Length of DC line	120cm

AE3

Model	CBA30Y0AG0C2
Manufacturer	Tenpao
Length of DC line	120cm

*AE ID: is used to identify the test sample in the lab internally.

3.4. General Description

The Equipment Under Test (EUT) is a model of GSM/GPRS/EDGE dual band mobile phone with integrated antenna. It consists of normal options: lithium battery, charger Manual and specifications of the EUT were provided to fulfil the test. Samples undergoing test were selected by the Client.

4. Reference Documents

4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 24	PERSONAL COMMUNICATIONS SERVICES	V 10.1.09
FCC Part 22	PUBLIC MOBILE SERVICES	V 10.1.09
ANSI/TIA-603-C	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards	2004
ANSI C63.4	Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2003

5. LABORATORY ENVIRONMENT

Semi-anechoic chamber (23 meters×17meters×10meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω
Normalised site attenuation (NSA)	< ±3.2 dB, 10 m distance, from 30 to 1000 MHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 2000 MHz

Control room did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. =30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω

Conducted chamber did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω

Fully-anechoic chamber (6.8 meters×3.08 meters×3.53 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω
Uniformity of field strength	Between 0 and 6 dB, from 80 to 2000 MHz

6. SUMMARY OF TEST RESULTS

Items	List	Clause in FCC rules	Verdict
1	Output Power	22.913(a)/24.232(b)	P
2	Emission Limit	2.1051/22.917/24.238	P
3	Conducted Emission	15.107/207	P
4	Frequency Stability	2.1055/24.235	P
5	Occupied Bandwidth	2.1049(h)(i)	P
6	Emission Bandwidth	22.917(b)/24.238(b)	P
7	Band Edge Compliance	22.917(b)/24.238(b)	P
8	Conducted Spurious Emission	2.1057/22.917/24.238	P

7. Test Equipments Utilized

NO.	NAME	TYPE	SERIES NUMBER	PRODUCER	CAL DUE DATE
1	Test Receiver	ESS	847151/015	R&S	2010-12-30
2	Test Receiver	ESI40	831564/002	R&S	2011-2-10
3	BiLog Antenna	3142B	9908-1403	EMCO	2011-1-15
4	BiLog Antenna	3142B	9908-1405	EMCO	2010-12-19
5	Signal Generator	SMT06	831285/005	R&S	2010-12-25
6	Signal Generator	SMP04	100070	R&S	2011-4-19
7	LISN	ESH2-Z5	829991/012	R&S	2010-12
8	Spectrum Analyzer	FSU26	200030	R&S	2010-12-18
9	Universal Radio Communication Tester	CMU200	100680	R&S	2010-12-23
10	Dual-Ridge Waveguide Horn Antenna	3115	9906-5827	EMCO	2011-3
11	Dual-Ridge Waveguide Horn Antenna	3115	9906-5831	EMCO	2011-3
12	Dual-Ridge Waveguide Horn Antenna	3116	2663	EMCO	2011-3
13	Dual-Ridge Waveguide Horn Antenna	3116	2661	EMCO	2011-3
14	Climatic chamber	PL-2G	343074	ESPEC	2010-12-15

ANNEX A: MEASUREMENT RESULTS

A.1 OUTPUT POWER (§22.913(a)/§24.232(b))

A.1.1 Summary

During the process of testing, the EUT was controlled via Rhode & Schwarz Digital Radio Communication tester (CMU-200) to ensure max power transmission and proper modulation.

This result contains peak output power and EIRP measurements for the EUT.

In all cases, output power is within the specified limits.

A.1.2 Conducted

A.1.2.1 Method of Measurements

The EUT was set up for the max output power with pseudo random data modulation.

The power was measured with Rhode & Schwarz Spectrum Analyzer FSU (peak)

These measurements were done at 3 frequencies, 1850.2 MHz, 1880.0MHz and 1909.8MHz for PCS1900 band;824.4MHz, 836.6MHz and 848.8MHz for GSM850 band. (bottom, middle and top of operational frequency range).

GSM850

Limit

	Power step	Nominal Peak output power (dBm)	Target (dB)
GSM	5	33dBm(2W)	33±1
GPRS	3	33dBm(2W)	33±1
EGPRS	6	27dBm(0.5W)	27±6

Measurement result

GSM

Frequency(MHz)	Power Step	Peak output power(dBm)
824.2	5	32.93
836.6	5	32.87
848.8	5	32.81

GPRS

Frequency(MHz)	Power Step	Peak output power(dBm)
824.2	3	32.86
836.6	3	32.81
848.8	3	32.80

EGPRS (Modulation type: GMSK)

Frequency(MHz)	Power Step	Peak output power(dBm)
824.2	6	32.28
836.6	6	32.26
848.8	6	32.26

PCS1900

Limit

	Power step	Nominal Peak output power (dBm)	Target (dB)
GSM	0	30dBm(1W)	30±2
GPRS	3	30dBm(1W)	30±2
EGPRS	5	26 dBm(0.4W)	26±4

Measurement result

GSM

Frequency(MHz)	Power Step	Peak output power(dBm)
1850.2	0	28.30
1880.0	0	28.53
1909.8	0	28.57

GPRS

Frequency(MHz)	Power Step	Peak output power(dBm)
1850.2	3	28.60
1880.0	3	28.93
1909.8	3	28.89

EGPRS (Modulation type: GMSK)

Frequency(MHz)	Power Step	Peak output power(dBm)
1850.2	5	28.84
1880.0	5	29.03
1909.8	5	29.11

A.1.3 Radiated

A.1.3.1 Description

This is the test for the maximum radiated power from the EUT.


Rule Part 24.232(b) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power" and 24.232(c) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage."

Rule Part 22.913(a) specifies "Maximum ERP. The effective radiated power (ERP) of base transmitters and cellular repeaters must not exceed 500 Watts. The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts."


A.1.3.2 Method of Measurement

The measurements procedures in TIA-603C-2004 are used.

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is

connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. The cable loss (P_{cl}) between the Signal Source with the Substitution Antenna and the Substitution Antenna Gain (G_a) should be recorded after test.

The measurement results are obtained as described below:

$$\text{Power(EIRP)} = P_{Mea} + P_{cl} + G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15\text{dBi}$.

GSM 850-ERP 22.913(a)
Limits

	Power Step	Burst Peak ERP (dBm)
GSM	5	≤38.45dBm (7W)
GPRS	3	≤38.45dBm (7W)
EGPRS	6	≤38.45dBm (7W)

Measurement result
GSM

Frequency(MHz)	Peak ERP(dBm)	P _{cl} Cable Loss(dB)	G _a Antenna Gain(dB)	Correction (dBm)	P _{Mea} (dBm)	Polarization
824.2	27.87	20.5	5.3	2.15	4.22	Horizontal
836.6	27.45	20.5	5.3	2.15	3.8	Horizontal
848.8	28.39	20.5	5.3	2.15	4.74	Horizontal

GPRS

Frequency(MHz)	Peak ERP(dBm)	P _{cl} Cable Loss(dB)	G _a Antenna Gain(dB)	Correction (dBm)	P _{Mea} (dBm)	Polarization
824.2	28.55	20.5	5.3	2.15	4.9	Horizontal
836.6	28.27	20.5	5.3	2.15	4.62	Horizontal
848.8	29.05	20.5	5.3	2.15	5.4	Horizontal

EGPRS (Modulation type: GMSK)

Frequency(MHz)	Peak ERP(dBm)	P _{cl} Cable Loss(dB)	G _a Antenna Gain(dB)	Correction (dBm)	P _{Mea} (dBm)	Polarization
824.2	22.56	20.5	5.3	2.15	-1.09	Horizontal
836.6	23.09	20.5	5.3	2.15	-0.56	Horizontal
848.8	23.92	20.5	5.3	2.15	0.27	Horizontal

Frequency: 848.8MHz

Peak ERP(dBm)= P_{Mea}(5.4dBm)+ P_{cl}(20.5dB)+G_a (5.3dB)-2.15dBm= 29.05dBm

ANALYZER SETTINGS: RBW = VBW = 3MHz

PCS1900-EIRP 24.232(b)
Limits

	Power Step	Burst Peak EIRP (dBm)
GSM	0	≤33dBm (2W)
GPRS	3	≤33dBm (2W)
EGPRS	5	≤33dBm (2W)

Measurement result
GSM

Frequency(MHz)	Peak EIRP(dBm)	P _{cl} Cable Loss(dB)	G _a Antenna Gain(dB)	P _{Mea} (dBm)	Polarization
1850.2	25.82	-10.9	27.5	9.22	Horizontal
1880	26.52	-10.8	27.5	9.82	Horizontal
1909.8	27.36	-11.3	27.5	11.16	Horizontal

GPRS

Frequency(MHz)	Peak EIRP(dBm)	P _{cl} Cable Loss(dB)	G _a Antenna Gain(dB)	P _{Mea} (dBm)	Polarization
1850.2	25.79	-10.9	27.5	9.19	Horizontal
1880	26.54	-10.8	27.5	9.84	Horizontal
1909.8	27.38	-11.3	27.5	11.18	Horizontal

EGPRS (Modulation type: GMSK)

Frequency(MHz)	Peak EIRP(dBm)	P _{cl} Cable Loss(dB)	G _a Antenna Gain(dB)	P _{Mea} (dBm)	Polarization
1850.2	15.53	-10.9	27.5	-1.07	Horizontal
1880	15.28	-10.8	27.5	-1.42	Horizontal
1909.8	14.89	-11.3	27.5	-1.31	Horizontal

Frequency: 1909.8MHz

Peak EIRP(dBm)= P_{Mea}(11.16dBm)+ P_{cl}(-11.3dB)+G_a (27.5dB) =27.36 dBm

ANALYZER SETTINGS: RBW = VBW = 3MHz

A.2 EMISSION LIMIT (§2.1051/§24.238)


A.2.1 Measurement Method

The measurements procedures in TIA-603C-2004 are used.


The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier that can be as high as 1910 MHz. The resolution bandwidth is set 1MHz as outlined in Part 24.238. The spectrum was scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of the PCS1900 band ,GSM850 band.

The procedure of radiated spurious emissions is as follows:

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (P_r).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the

substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. The cable loss (P_{cl}) between the Signal Source with the Substitution Antenna and the Substitution Antenna Gain (G_a) should be recorded after test.
The measurement results are obtained as described below:
$$\text{Power(EIRP)} = P_{Mea} + P_{cl} + G_a$$
5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15\text{dBi}$.

A.2.2 Measurement Limit

Sec. 24.238 Emission Limits.

(a) On any frequency outside a licensee's frequency block (e.g. A, D, B, etc.) within the USPCS spectrum, the power of any emission shall be attenuated below the transmitter power (P , in Watts) by at least $43 + 10\log(P)$ dB. The specification that emissions shall be attenuated below the transmitter power (P) by at least $43 + 10 \log (P)$ dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

A.2.3 Measurement Results

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of the PCS band (1850.2 MHz, 1880 MHz and 1909.8 MHz) ,GSM850 band (824.2MHz, 836.6MHz, 848.8MHz) . It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the PCS1900 ,GSM850 into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this.

A.2.4 Measurement Results Table

Frequency	Channel	Frequency Range	Result
GSM 850MHz	Low	30MHz-10GHz	Pass
	Middle	30MHz-10GHz	Pass
	High	30MHz-10GHz	Pass
GSM 1900MHz	Low	30MHz-20GHz	Pass
	Middle	30MHz-20GHz	Pass
	High	30MHz-20GHz	Pass

A.2.5 Sweep Table

Working Frequency	Subrange (GHz)	RBW	VBW	Sweep time (s)
850MHz	0.03~1	100KHz	300KHz	10
	1-2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~10	1 MHz	3 MHz	3
1900MHz	0.03~1	100KHz	300KHz	10
	1-2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~11	1 MHz	3 MHz	3
	11~14	1 MHz	3 MHz	3
	14~18	1 MHz	3 MHz	3
	18~20	1 MHz	3 MHz	2

GSM Mode Channel 128/824.2MHz

Frequency(MHz)	Peak ERP(dBm)	Cable Loss	Antenna Gain	Correction (dBm)	P _{Mea} (dBm)	Limit (dBm)	Polarization
1647.75	-46.78	-40.7	25.2	2.15	-36.47	-13	Horizontal
1648.2	-48.24	-40.7	25.2	2.15	-36.33	-13	Horizontal
1648.95	-46.73	-42.6	27.5	2.15	-35.55	-13	Horizontal
1650.45	-50.78	-42.7	29.2	2.15	-38.42	-13	Horizontal
2472.9	-47.41	-42.1	29.2	2.15	-38.54	-13	Horizontal
3296.8	-43.14	-45.4	38.7	2.15	-44.97	-13	Vertical

GSM Mode Channel 190/836.6MHz

Frequency(MHz)	Peak ERP(dBm)	Cable Loss	Antenna Gain	Correction (dBm)	P _{Mea} (dBm)	Limit (dBm)	Polarization
1673.4	-46.00	-40.7	25.2	2.15	-30.25	-13	Horizontal
2509.35	-47.14	-40.7	25.2	2.15	-30.56	-13	Horizontal
2510.7	-47.62	-42.6	27.5	2.15	-31.57	-13	Horizontal
3346.4	-47.11	-42.7	29.2	2.15	-32.33	-13	Vertical
8140.9	-44.07	-42.1	29.2	2.15	-29.46	-13	Horizontal
9779.5	-41.25	-45.4	38.7	2.15	-34.53	-13	Vertical

GSM Mode Channel 251/848.8MHz

Frequency(MHz)	Peak ERP(dBm)	Cable Loss	Antenna Gain	Correction (dBm)	P _{Mea} (dBm)	Limit (dBm)	Polarization
1696.35	-46.47	-40.7	25.2	2.15	-35.03	-13	Horizontal
1697.25	-45.32	-40.7	25.2	2.15	-37.07	-13	Horizontal
2545.35	-47.01	-42.6	27.5	2.15	-36.58	-13	Horizontal
2546.85	-46.87	-42.7	29.2	2.15	-38.61	-13	Horizontal
7995.1	-44.15	-42.1	29.2	2.15	-37.86	-13	Horizontal
9903.7	-41.35	-45.4	38.7	2.15	-43.5	-13	Horizontal

GSM Mode Channel 512/1850.2MHz

Frequency(MHz)	Peak EIRP(dBm)	Cable Loss	Antenna Gain	P _{Mea} (dBm)	Limit (dBm)	Polarization
2000.6	-43.73	-41.7	27.5	-28.52	-13	Vertical
8073.5	-43.27	-42.1	33.4	-38.32	-13	Horizontal
9677	-42.13	-43.7	35.7	-38.81	-13	Vertical
17768.4	-28.73	-44.8	36.3	-35.78	-13	Vertical

GSM Mode Channel 661/1880.0MHz

Frequency(MHz)	Peak EIRP(dBm)	Cable Loss	Antenna Gain	P _{Mea} (dBm)	Limit (dBm)	Polarization
2000.2	-43.81	-41.7	27.5	-30.9	-13	Horizontal
8056.1	-42.90	-42.1	33.4	-36.58	-13	Horizontal
9953.6	-42.37	-43.7	35.7	-35.83	-13	Horizontal
15428.8	-35.52	-44.8	36.3	-35.22	-13	Vertical
17546.4	-28.19	-45.5	38.7	-36.04	-13	Vertical

GSM Mode Channel 810/1909.8MHz

Frequency(MHz)	Peak EIRP(dBm)	Cable Loss	Antenna Gain	P _{Mea} (dBm)	Limit (dBm)	Polarization
2000.2	-19.95	-41.7	27.5	-27.52	-13	Horizontal
2000.5	-22.05	-42.1	33.4	-36.31	-13	Vertical
2001.4	-27.25	-43.7	35.7	-38.93	-13	Horizontal
2002	-31.32	-44.8	36.3	-31.79	-13	Horizontal
2002.6	-34.75	-45.5	38.7	-33.53	-13	Horizontal
2002.9	-38.45	-47	39.5	-34.23	-13	Horizontal

A.3 CONDUCTED EMISSION (§15.107§15.207)

The measurement procedure in ANSI C63.4-1003 is used. Conducted Emission is measured with travel charger.


A.3.1 Limit

Frequency of Emission (MHz)	Conducted Limit (dBμV)	
	Quasi -Peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

* Decreases with logarithm of the frequency

A.3.2 Measurement result

GSM850MHz AE2



MEASUREMENT RESULT: "10TA781_8C_fin QP"

9/6/10 15:57

Frequency	Level	Transd	Limit	Margin	Line	PE
MHz	dBμV		dB	dBμV	dB	
2.040200	48.80	10.1	56	7.2	L1	GND
2.144271	44.70	10.1	56	11.3	L1	FLO


MEASUREMENT RESULT: "10TA781_8C_fin AV"

9/6/10 15:57

Frequency	Level	Transd	Limit	Margin	Line	PE
MHz	dBμV		dB	dBμV	dB	

0.307065	41.00	10.1	50	9.1	N	GND
1.935015	42.80	10.1	46	3.2	L1	FLO
1.993648	35.50	10.1	46	10.5	L1	GND
2.040200	41.50	10.1	46	4.5	L1	GND
2.144271	24.50	10.1	46	21.5	L1	GND
2.345157	38.10	10.1	46	7.9	L1	GND

GSM850MHz AE3



MEASUREMENT RESULT: "10TA781_28C_fin QP"

9/6/10 16:09


Frequency MHz	Level dBμV	Transd	Limit dB	Margin dBμV	Line dB	PE
0.177646	57.00	10.1	65	7.6	L1	FLO
0.393790	45.70	10.1	58	12.3	L1	GND
3.256697	42.50	10.1	56	13.5	L1	FLO

MEASUREMENT RESULT: "10TA781_28C_fin AV"

9/6/10 16:09

Frequency MHz	Level dBμV	Transd	Limit dB	Margin dBμV	Line dB	PE
0.165693	42.70	10.1	55	12.5	N	GND

PCS1900MHz AE2



MEASUREMENT RESULT: "10TA781_PC_fin QP"

9/6/10 15:59


Frequency MHz	Level dBμV	Transd	Limit dB	Margin dBμV	Line dB	PE
2.040200	43.40	10.1	56	12.6	L1	GND
2.187371	44.50	10.1	56	11.5	L1	FLO

MEASUREMENT RESULT: "10TA781_PC_fin AV"

9/6/10 15:59

Frequency MHz	Level dBμV	Transd	Limit dB	Margin dBμV	Line dB	PE
1.878106	40.00	10.1	46	6.0	L1	FLO
1.935015	38.00	10.1	46	8.0	L1	GND
2.040200	34.30	10.1	46	11.7	L1	GND
2.081208	23.40	10.1	46	22.6	L1	GND
2.187371	38.00	10.1	46	8.0	L1	GND
2.392295	34.70	10.1	46	11.3	L1	GND

PCS1900MHz AE3




MEASUREMENT RESULT: "10TA781_2PC_fin QP"

9/6/10 16:11

Frequency MHz	Level dBμV	Transd	Limit dB	Margin dBμV	Line dB	PE
0.175887	54.90	10.1	65	9.8	L1	GND
0.397728	42.90	10.1	58	15.0	L1	FLO
2.861538	39.60	10.1	56	16.4	L1	GND

MP3



MEASUREMENT RESULT: "10TA781_MC_fin QP"

9/6/10 16:01

Frequency	Level	Transd	Limit	Margin	Line	PE
-----------	-------	--------	-------	--------	------	----


MHz	dB μ V	dB	dB μ V	dB		
1.973909	50.30	10.1	56	5.7	L1	GND
2.123040	46.20	10.1	56	9.8	L1	GND

MEASUREMENT RESULT: "10TA781_MC_fin AV"

9/6/10 16:01

Frequency MHz	Level dB μ V	Transd dB	Limit dB	Margin dB μ V	Line dB	PE
0.304025	41.60	10.1	50	8.5	N	GND
0.759408	36.40	10.1	46	9.6	N	FLO
1.878106	37.80	10.1	46	8.2	L1	FLO
1.973909	42.90	10.1	46	3.1	L1	GND
2.081208	39.00	10.1	46	7.0	L1	FLO
2.231337	27.60	10.1	46	18.4	L1	FLO

Camera



MEASUREMENT RESULT: "10TA781_CC_fin QP"

9/6/10 16:04

Frequency MHz	Level dB μ V	Transd dB	Limit dB	Margin dB μ V	Line dB	PE
2.020000	49.90	10.1	56	6.1	L1	FLO
2.123040	46.50	10.1	56	9.5	L1	FLO

MEASUREMENT RESULT: "10TA781_CC_fin AV"

9/6/10 16:04

Frequency MHz	Level dBμV	Transd	Limit dB	Margin dBμV	Line dB	PE
0.304025	41.30	10.1	50	8.8	N	FLO
1.822872	35.70	10.1	46	10.3	L1	GND
1.973909	43.00	10.1	46	3.0	L1	GND
2.020000	42.00	10.1	46	4.0	L1	FLO
2.123040	39.90	10.1	46	6.1	L1	FLO
2.276187	36.00	10.1	46	10.0	L1	GND

A.4 FREQUENCY STABILITY **(§2.1055/§24.235)**

A.4.1 Method of Measurement

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMU200 DIGITAL RADIO COMMUNICATION TESTER.

1. Measure the carrier frequency at room temperature.
2. Subject the EUT to overnight soak at -30°C.
3. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on channel 661 for PCS 1900, channel 190 for GSM850 measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
4. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
5. Remeasure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments remeasuring carrier frequency at each voltage. Pause at nominal voltage for 1 1/2 hours unpowered, to allow any self-heating to stabilize, before continuing.
6. Subject the EUT to overnight soak at +50°C.
7. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
8. Repeat the above measurements at 10 C increments from +50°C to -30°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

A.4.2 Measurement Limit

A.4.2.1 For Hand carried battery powered equipment

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.5VDC and 4.2VDC, with a nominal voltage of 3.7VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress. These voltages represent a tolerance of -10 % and +12.5 %. For the purposes of measuring frequency stability these voltage limits are to be used.

A.4.2.2 For equipment powered by primary supply voltage

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the

fundamental emission stays within the authorized frequency block. For this EUT section 2.1055(d)(1) applies. This requires varying primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

A.4.3 Measurement results

GSM 850

Frequency Error vs Voltage

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.5	25	0.027
3.8	23	0.025
4.2	28	0.031

Frequency Error vs Temperature

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-30	40	0.044
-20	38	0.042
-10	33	0.036
0	26	0.029
10	23	0.025
20	23	0.025
30	23	0.025
40	29	0.032
50	35	0.038

PCS 1900

Frequency Error vs Voltage

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.5	44	0.023
3.8	38	0.018
4.2	43	0.022

Frequency Error vs Temperature

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-30	60	0.031
-20	58	0.029
-10	55	0.028
0	49	0.025
10	43	0.022
20	38	0.018
30	38	0.018
40	38	0.018
50	51	0.026

A.5 OCCUPIED BANDWIDTH (§2.1049(h)(i))

A.5.1 Occupied Bandwidth Results


Similar to conducted emissions; occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of the USPCS frequency band. The table below lists the measured -20dBc BW (99%). Spectrum analyzer plots are included on the following pages.

GSM 850(99%)

Frequency(MHz)	Occupied Bandwidth (99%)(kHz)
824.2	248.397
836.6	250.000
848.8	250.000


GSM 850

Channel 128-Occupied Bandwidth (99%)




Date: 6.SEP.2010 03:29:43

Channel 190-Occupied Bandwidth (99%)



Date: 6.SEP.2010 03:30:10

Channel 251-Occupied Bandwidth (99%)




Date: 6.SEP.2010 03:30:38

GPRS 850(99%)

Frequency(MHz)	Occupied Bandwidth (99%)(kHz)
824.2	243.590
836.6	250.000
848.8	246.795


GPRS 850

Channel 128-Occupied Bandwidth (99%)




Date: 6.SEP.2010 03:48:04

Channel 190-Occupied Bandwidth (99%)



Date: 6.SEP.2010 03:48:31

Channel 251-Occupied Bandwidth (99%)




Date: 6.SEP.2010 03:48:58

EGPRS 850(99%) (Modulation type: GMSK)

Frequency(MHz)	Occupied Bandwidth (99%)(kHz)
824.2	248.397
836.6	246.795
848.8	245.192


EGPRS 850

Channel 128-Occupied Bandwidth (99%)




Date: 6.SEP.2010 04:05:24

Channel 190-Occupied Bandwidth (99%)



Date: 6.SEP.2010 04:05:51

Channel 251-Occupied Bandwidth (99%)




Date: 6.SEP.2010 04:06:18

PCS 1900(99%)

Frequency(MHz)	Occupied Bandwidth (99%)(kHz)
1850.2	248.397
1880.0	245.192
1909.8	245.192


PCS 1900

Channel 512-Occupied Bandwidth (99%)




Date: 6.SEP.2010 03:39:01

Channel 661-Occupied Bandwidth (99%)



Date: 6.SEP.2010 03:39:29

Channel 810-Occupied Bandwidth (99%)




Date: 6.SEP.2010 03:39:56

GPRS 1900(99%)

Frequency(MHz)	Occupied Bandwidth (99%)(kHz)
1850.2	246.795
1880.0	248.397
1909.8	241.987


GPRS 1900

Channel 512-Occupied Bandwidth (99%)




Date: 6.SEP.2010 03:58:29

Channel 661-Occupied Bandwidth (99%)



Date: 6.SEP.2010 03:58:56

Channel 810-Occupied Bandwidth (99%)




Date: 6.SEP.2010 03:59:23

EGPRS 1900(99%) (Modulation type: GMSK)

Frequency(MHz)	Occupied Bandwidth (99%)(kHz)
1850.2	248.397
1880.0	246.795
1909.8	248.397


EGPRS 1900

Channel 512-Occupied Bandwidth (99%)




Date: 6.SEP.2010 04:34:23

Channel 661-Occupied Bandwidth (99%)



Date: 6.SEP.2010 04:34:50

Channel 810-Occupied Bandwidth (99%)



Date: 6.SEP.2010 04:35:17

A.6 EMISSION BANDWIDTH (§22.917(b)/§24.238(b))

A.6.1 Emission Bandwidth Results


Similar to conducted emissions; Emission bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of the PCS1900 band and GSM850 band. Table below lists the measured -26dBc BW. Spectrum analyzer plots are included on the following pages.

GSM 850(-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc BW)(kHz)
824.2	310.897
836.6	309.295
848.8	310.897

GSM 850

Channel 128-Occupied Bandwidth (-26dBc BW)




Channel 190-Occupied Bandwidth (-26dBc BW)



Date: 6.SEP.2010 03:31:34

Channel 251-Occupied Bandwidth (-26dBc BW)




Date: 6.SEP.2010 03:32:01

GPRS 850(-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc BW)(kHz)
824.2	312.500
836.6	310.897
848.8	309.295

GPRS 850

Channel 128-Occupied Bandwidth (-26dBc BW)




Channel 190-Occupied Bandwidth (-26dBc BW)



Date: 6.SEP.2010 03:49:54

Channel 251-Occupied Bandwidth (-26dBc BW)




Date: 6.SEP.2010 03:50:22

EGPRS 850(-26dBc) (Modulation type: GMSK)

Frequency(MHz)	Occupied Bandwidth (-26dBc BW)(kHz)
824.2	307.692
836.6	310.897
848.8	309.295


EGPRS 850

Channel 128-Occupied Bandwidth (-26dBc BW)




Date: 6.SEP.2010 04:06:47

Channel 190-Occupied Bandwidth (-26dBc BW)



Date: 6.SEP.2010 04:07:14

Channel 251-Occupied Bandwidth (-26dBc BW)




Date: 6.SEP.2010 04:07:41

PCS 1900(-26dBc)

Frequency(MHz)	Occupied Bandwidth (-26dBc BW)(kHz)
1850.2	309.295
1880.0	310.897
1909.8	307.692


PCS 1900

Channel 512-Occupied Bandwidth (-26dBc BW)




Date: 6.SEP.2010 03:40:25

Channel 661-Occupied Bandwidth (-26dBc BW)



Date: 6.SEP.2010 03:40:52

Channel 810-Occupied Bandwidth (-26dBc BW)




Date: 6.SEP.2010 03:41:19

GPRS 1900(-26dBc)

Frequency(MHz)	Occupied Bandwidth (-26dBc BW)(kHz)
1850.2	307.692
1880.0	310.897
1909.8	309.295


GPRS 1900

Channel 512-Occupied Bandwidth (-26dBc BW)




Date: 6.SEP.2010 03:59:52

Channel 661-Occupied Bandwidth (-26dBc BW)



Date: 6.SEP.2010 04:00:19

Channel 810-Occupied Bandwidth (-26dBc BW)




Date: 6.SEP.2010 04:00:46

EGPRS 1900(-26dBc) (Modulation type: GMSK)

Frequency(MHz)	Occupied Bandwidth (-26dBc BW)(kHz)
1850.2	312.500
1880.0	310.897
1909.8	312.500


EGPRS 1900

Channel 512-Occupied Bandwidth (-26dBc BW)




Date: 6.SEP.2010 04:35:46

Channel 661-Occupied Bandwidth (-26dBc BW)



Date: 6.SEP.2010 04:36:13

Channel 810-Occupied Bandwidth (-26dBc BW)




Date: 6.SEP.2010 04:36:40

A.7 BAND EDGE COMPLIANCE (\$22.917(b)/\$24.238(b))


GSM 850

LOW BAND EDGE BLOCK-A (GSM850)-Channel 128




Date: 6.SEP.2010 03:32:30

HIGH BAND EDGE BLOCK-C (GSM850) -Channel 251




Date: 6.SEP.2010 03:32:59

GPRS 850 LOW BAND EDGE BLOCK-A (GSM850)-Channel 128




Date: 6.SEP.2010 03:50:50

HIGH BAND EDGE BLOCK-C (GSM850) –Channel 251




Date: 6.SEP.2010 03:51:19

EGPRS 850 (Modulation type: GMSK)
LOW BAND EDGE BLOCK-A (GSM850)-Channel 128



Date: 6.SEP.2010 04:08:10


HIGH BAND EDGE BLOCK-C (GSM850) –Channel 251



Date: 6.SEP.2010 04:08:39


PCS 1900

LOW BAND EDGE BLOCK-A (PCS-1900)-Channel 512



Date: 6.SEP.2010 03:41:48


HIGH BAND EDGE BLOCK-C (PCS-1900) -Channel 810



Date: 6.SEP.2010 03:42:17


GPRS 1900

LOW BAND EDGE BLOCK-A (PCS-1900)-Channel 512




Date: 6.SEP.2010 04:01:15

HIGH BAND EDGE BLOCK-C (PCS-1900) -Channel 810




Date: 6.SEP.2010 04:01:44

EGPRS 1900 (Modulation type: GMSK)
LOW BAND EDGE BLOCK-A (PCS-1900)-Channel 512



Date: 6.SEP.2010 04:37:09

HIGH BAND EDGE BLOCK-C (PCS-1900) -Channel 810



Date: 6.SEP.2010 04:37:38

A.8 CONDUCTED SPURIOUS EMISSION (§2.1057/§22.917/§24.238)

A.8.1 Measurement Method

The following steps outline the procedure used to measure the conducted emissions from the EUT.

1. Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the equipment of PCS1900 band, this equates to a frequency range of 30 MHz to 19.1 GHz, data taken from 30 MHz to 20 GHz. For GSM850, data taken from 30 MHz to 9 GHz.
2. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.

GSM850 Transmitter

Channel	Frequency (MHz)
128	824.2
190	836.6
251	848.8

PCS1900 Transmitter

Channel	Frequency (MHz)
512	1850.2
661	1880.0
810	1909.8

A. 8.2 Measurement Limit

Sec. 24.238 Emission Limits.

(a) On any frequency outside frequency band of the USPCS spectrum, the power of any emission shall be attenuated below the transmitter power (P, in Watts) by at least $43+10\log(P)$ dB. For all power levels +30 dBm to 0 dBm, this becomes a constant specification limit of -13 dBm.

A. 8.3 Measurement result


GSM850

Harmonic	Tx ch. 128 Freq. (MHz)	Level (dBm)	Tx ch. 190 Freq. (MHz)	Level (dBm)	Tx ch. Freq. (MHz) 251	Level (dBm)
2	1648.4	nf	1673.2	nf	1697.6	nf
3	2472.6	nf	2509.8	nf	2546.4	nf
4	3296.8	nf	3346.4	nf	3395.2	nf
5	4121	nf	4183	nf	4244	nf
6	4945.2	nf	5019.6	nf	5092.8	nf
7	5769.4	nf	5856.2	nf	5941.6	nf
8	6593.6	nf	6692.8	nf	6790.4	nf
9	7417.8	nf	7529.4	nf	7639.2	nf
10	8242	nf	8366	nf	8488	nf
nf: Noise floor						

A.8.3.1 Channel 128: 30MHz – 4GHz

Spurious emission limit –13dBm.


NOTE: peak above the limit line is the carrier frequency.



Date: 6.SEP.2010 03:33:28

A.8.3.2 Channel 128: 4GHz – 10GHz

Spurious emission limit –13dBm.




Date: 6.SEP.2010 03:33:56

A.8.3.3 Channel 190: 30MHz – 4GHz

Spurious emission limit –13dBm


NOTE: peak above the limit line is the carrier frequency.



Date: 6.SEP.2010 03:34:25

A.8.3.4 Channel 190: 4GHz –10GHz

Spurious emission limit –13dBm




Date: 6.SEP.2010 03:34:53

A.8.3.5 Channel 251: 30MHz – 4GHz

Spurious emission limit –13dBm.


NOTE: peak above the limit line is the carrier frequency.



Date: 6.SEP.2010 03:35:22

A.8.3.6 Channel 251: 4GHz – 10GHz


Spurious emission limit –13dBm.



Date: 6.SEP.2010 03:35:51

A.8.3.7 Idle mode: 30MHz – 4GHz


Spurious emission limit –13dBm.



Date: 6.SEP.2010 03:36:19

A.8.3.8 Idle mode: 4GHz – 10GHz

Spurious emission limit –13dBm.



Date: 6.SEP.2010 03:36:48


PCS1900

Harmonic	Tx ch. 512 Freq. (MHz)	Level (dBm)	Tx ch. 661 Freq. (MHz)	Level (dBm)	Tx ch. 810 Freq. (MHz)	Level (dBm)
2	3700.4	nf	3760	nf	3819.6	nf
3	5550.6	nf	5640	nf	5729.4	nf
4	7400.8	nf	7520	nf	7639.2	nf
5	9251.0	nf	9400	nf	9549.0	nf
6	11101.2	nf	11280	nf	11458.8	nf
7	12951.4	nf	13160	nf	13368.6	nf
8	14801.6	nf	15040	nf	15278.4	nf
9	16651.8	nf	16920	nf	17188.2	nf
10	18502.0	nf	18800	nf	19098.0	nf
nf: Noise floor						

A. 8.3.9 Channel 512: 30MHz – 4GHz

Spurious emission limit –13dBm.


NOTE: peak above the limit line is the carrier frequency.



Date: 6.SEP.2010 03:42:46

A. 8.3.10 Channel 512: 4GHz – 20GHz

Spurious emission limit –13dBm.




Date: 6.SEP.2010 03:43:14

A. 8.3.11 Channel 661: 30MHz – 4GHz

Spurious emission limit –13dBm


NOTE: peak above the limit line is the carrier frequency.



Date: 6.SEP.2010 03:43:43

A. 8.3.12 Channel 661: 4GHz –20GHz

Spurious emission limit –13dBm




Date: 6.SEP.2010 03:44:11

A. 8.3.13 Channel 810: 30MHz – 4GHz

Spurious emission limit –13dBm.


NOTE: peak above the limit line is the carrier frequency.



Date: 6.SEP.2010 03:44:40

A. 8.3.14 Channel 810: 4GHz – 20GHz


Spurious emission limit –13dBm.



Date: 6.SEP.2010 03:45:09

A. 8.3.15 Idle mode: 30MHz – 4GHz


Spurious emission limit –13dBm.



Date: 6.SEP.2010 03:45:37

A. 8.3.16 Idle mode: 4GHz – 20GHz

Spurious emission limit -13dBm.



Date: 6.SEP.2010 03:46:05

END OF REPORT