



TEST REPORT

No. 2011TAR206

for

TCT Mobile Limited

HSDPA/UMTS dual band / GSM four bands mobile phone

Model Name: Brandy Lite A

Marketing Name: one touch 908A

FCC ID : RAD169

with

Hardware Version: PIO

Software Version: V61S

Issued Date: 2011-06-07

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of TMC Beijing.

Test Laboratory:

DAR accreditation (DIN EN ISO/IEC 17025): No. DGA-PL-114/01-02

FCC 2.948 Listed: No.733176

IC O.A.T.S listed: No.6629A-1

TMC Beijing, Telecommunication Metrology Center of Ministry of Industry and Information Technology

No. 52, Huayuan Bei Road, Haidian District, Beijing, P. R. China 100191

Tel:+86(0)10-62304633 , Fax:+86(0)10-62304633 Email:welcome@emcite.com. www.emcite.com

©Copyright. All rights reserved by TMC Beijing.

CONTENTS

1. TEST LABORATORY.....	3
1.1. TESTING LOCATION	3
1.2. TESTING ENVIRONMENT	3
1.3. PROJECT DATA.....	3
1.4. SIGNATURE	3
2. CLIENT INFORMATION.....	4
2.1. APPLICANT INFORMATION.....	4
2.2. MANUFACTURER INFORMATION.....	4
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	5
3.1. ABOUT EUT	5
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	5
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST.....	5
4. REFERENCE DOCUMENTS	6
4.1. REFERENCE DOCUMENTS FOR TESTING	6
5. LABORATORY ENVIRONMENT	7
6. SUMMARY OF TEST RESULTS.....	8
7. TEST EQUIPMENTS UTILIZED.....	9
ANNEX A: MEASUREMENT RESULTS	10

1. Test Laboratory

1.1. Testing Location

Company Name: TMC Beijing, Telecommunication Metrology Center of MIIT
Address: No 52, Huayuan beilu, Haidian District, Beijing, P. R. China
Postal Code: 100191
Telephone: 00861062304633
Fax: 00861062304633


1.2. Testing Environment

Normal Temperature: 15-35℃
Relative Humidity: 20-75%

1.3. Project data

Testing Start Date: Apr 29, 2011
Testing End Date: May 13, 2011

1.4. Signature




Liu Baodian

(Prepared this test report)



Sun Xiangqian

(Reviewed this test report)



Lu Bingsong

**Deputy Director of the laboratory
(Approved this test report)**

2. Client Information

2.1. Applicant Information

Company Name: TCT Mobile Limited
Address /Post: 5F, E building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,
Pudong Area Shanghai, P.R. China.
City: Shanghai
Postal Code: 201203
Country: China
Telephone: +86-21-61460890
Fax: +86-21-61460602

2.2. Manufacturer Information

Company Name: TCT Mobile Limited
Address /Post: 5F, E building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,
Pudong Area Shanghai, P.R. China.
City: Shanghai
Postal Code: 201203
Country: China
Telephone: +86-21-61460890
Fax: +86-21-61460602

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	HSDPA/UMTS dual band / GSM four bands mobile phone
Model Name	one touch 908A
FCC ID	RAD169
Extreme vol. Limits	3.5VDC to 4.2VDC (nominal: 3.7VDC)

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of Telecommunication Metrology Center of MII of People's Republic of China.

3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version
EUT1	012633000040737	PIO	V61S

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description	SN
AE1	Travel Adapter	/
AE2	Travel Adapter	/
AE3	Travel Adapter	/
AE4	Battery	/
AE5	USB Cable	/
AE6	USB Cable	/

AE1

Model	CBA3001AG0C1
Manufacturer	BYD
Length of DC line	With 10cm USB Connector

AE2

Model	CBA3001AG0C2
Manufacturer	Tenpao
Length of DC line	With 10cm USB Connector

AE3

Model	CBA3000AG0C1
Manufacturer	Tenpao
Length of DC line	/

AE4

Model	CAB31P0000C1
Manufacturer	BYD
Capacitance	1300mAh
Nominal Voltage	3.7V

AE5

Model	CDA3122001C1
Manufacturer	Juwei
Length of DC line	150cm

AE6

Model	CDA3122001C2
Manufacturer	Shenhuai
Length of DC line	150cm

*AE ID: is used to identify the test sample in the lab internally.*AE ID: is used to identify the test sample in the lab internally.

EUT set-ups

EUT set-up No.	Combination of EUT and AE	Remarks
Set.1	EUT1+ AE1+AE4+AE5/AE6	--
Set.2	EUT1+ AE2+AE4+AE5/AE6	--
Set.3	EUT1+ AE3+AE4+AE5/AE6	--

4. Reference Documents

4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 15, Subpart B	Radio frequency devices	July 10, 2008
ANSI C63.4	Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	Edition 2003

5. LABORATORY ENVIRONMENT

Semi-anechoic chamber (23 meters×17meters×10meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω
Normalised site attenuation (NSA)	< ±3.2 dB, 10 m distance, from 30 to 1000 MHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 2000 MHz

Control room did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. =30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω

Conducted chamber did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω

Fully-anechoic chamber (6.8 meters×3.08 meters×3.53 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω
Uniformity of field strength	Between 0 and 6 dB, from 80 to 2000 MHz

6. SUMMARY OF TEST RESULTS

Abbreviations used in this clause:	
P	Pass
NA	Not applicable
F	Fail

Clause	List	Clause in FCC rules	Verdict
1	Radiated Emission	15.109(a)	P
2	Conducted Emission	15.107(a)	P

7. Test Equipments Utilized

NO.	Description	TYPE	SERIES NUMBER	MANUFACTURE	CAL DUE DATE
1	Test Receiver	ESCI	100344	R&S	2012-03-12
2	Test Receiver	ESCI	100766	R&S	2011-12-06
3	Test Receiver	ESI40	831564/002	R&S	2012-02-12
4	BiLog Antenna	VUL9163	9163-302	Schwarzbeck	2012-02-10
5	Signal Generator	SMB100A	102063	R&S	2012-03-05
6	LISN	ESH2-Z5	829991/012	R&S	2012-04-20
7	Universal Radio Communication Tester	CMU200	100680	R&S	2011-09-05
8	Dual-Ridge Waveguide Horn Antenna	3115	6914	EMCO	2012-01-18
9	PC	OPTIPLEX 755	3908243625	DELL	N/A
10	Monitor	E178FPc	CN-OWR979-64 180-7AJ-D2MS	DELL	N/A
11	Printer	DeskJet D2368	TH72E12G7Q	HP	N/A
12	Keyboard	L100	CN0RH6596589 07ATOI40	DELL	N/A
13	Mouse	VR-301	6927225500198	XINGYU	N/A

ANNEX A: MEASUREMENT RESULTS

A.1 Radiated Emission (§15.109(a))

A.1.1 Method of measurement

The field strength of radiated emissions from the unintentional radiator (USB mode of MS and charging mode of MS) at a distance of 3 meters is tested. Tested in accordance with the procedures of ANSI C63.4 - 2003, section 8.3.

A.1.2 EUT Operating Mode:

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations. The MS is operating in the USB mode and charging mode. During the test MS is connected to a PC via a USB cable in the case of USB mode and is connected to a charger in the case of charging mode. The model of the PC is DELL OPTIPLEX 755, and the serial number of the PC is 3908243625. The software is used to let the PC keep on copying data to MS, reading and erasing the data after copy action was finished.

A.1.3 Measurement Limit

Frequency of emission (MHz)	Field strength (microvolts/meter)
30-88	100
88-216	150
216-960	200
Above 960	500

A.1.4 Test Condition

Frequency of emission (MHz)	RBW/VBW	Sweep Time(s)
30-1000	100KHz/300KHz	5
1000-4000	1MHz/1MHz	15

A.1.5 Measurement Results

A "reference path loss" is established and the A_{RPL} is the attenuation of "reference path loss", and including the gain of receive antenna and the path loss.

The measurement results are obtained as described below:

$$\text{Result} = P_{\text{Mea}} + F_A + G_{\text{PL}}$$

Where

F_A : Receive Antenna Factor

G_{PL} : Cable Loss

P_{Mea} : The measurement result on receiver.

Charging Mode(set.1)

Frequency(MHz)	Result(dBuV/m)	G_{PL} (dB)	F_A (dB/m)	P_{Mea} (dBuV)	Polarity
3911.824	51.51	-19.8	33.4	37.91	HORIZONTAL
3703.407	51.22	-19.4	33.4	37.22	HORIZONTAL
3701.403	51.07	-19.4	33.4	37.07	VERTICAL
3959.92	51.06	-19.7	33.4	37.36	VERTICAL
3767.535	50.99	-19.6	33.4	37.19	HORIZONTAL
3649.299	50.97	-19.7	33.4	37.27	VERTICAL

Charging Mode(set.2)

Frequency(MHz)	Result(dBuV/m)	G_{PL} (dB)	F_A (dB/m)	P_{Mea} (dBuV)	Polarity
3581.162	51.5	-19.6	33.4	37.7	HORIZONTAL
3701.403	51.46	-19.4	33.4	37.46	VERTICAL
3601.202	51.39	-19.6	33.4	37.59	HORIZONTAL
3551.102	51.25	-19.5	33.4	37.35	VERTICAL
3539.078	51.21	-19.4	33.4	37.21	VERTICAL
3486.974	51.15	-19.6	31.2	39.55	VERTICAL

Charging Mode(set.3)

Frequency(MHz)	Result(dBuV/m)	G_{PL} (dB)	F_A (dB/m)	P_{Mea} (dBuV)	Polarity
3549.098	51.53	-19.5	33.4	37.63	VERTICAL
3871.743	51.01	-19.6	33.4	37.21	VERTICAL
3430.862	50.94	-19.6	31.2	39.34	HORIZONTAL
3977.956	50.82	-19.4	33.4	36.82	HORIZONTAL
3559.118	50.76	-19.5	33.4	36.86	HORIZONTAL
3913.828	50.76	-19.8	33.4	37.16	HORIZONTAL

USB Mode

Frequency(MHz)	Result(dBuV/m)	G_{PL} (dB)	F_A (dB/m)	P_{mea} (dBuV)	Polarity
3741.483	51.68	-19.7	33.4	37.98	VERTICAL
3697.395	51.62	-19.5	33.4	37.72	HORIZONTAL
3695.391	51.32	-19.5	33.4	37.42	HORIZONTAL
3665.331	51.27	-19.7	33.4	37.57	VERTICAL
2246.493	51.11	-19.6	27.5	43.21	HORIZONTAL
3663.327	51.08	-19.7	33.4	37.38	VERTICAL

Charging Mode




Figure A.1 Radiated Emission from 30MHz to 1GHz (set.1)




Figure A.2 Radiated Emission from 1GHz to 4GHz(set.1)




Figure A.3 Radiated Emission from 30MHz to 1GHz (set.2)




Figure A.4 Radiated Emission from 1GHz to 4GHz(set.2)




Figure A.5 Radiated Emission from 30MHz to 1GHz (set.3)




Figure A.6 Radiated Emission from 30MHz to 1GHz (set.3)

USB Mode




Figure A.7 Radiated Emission from 30MHz to 1GHz




Figure A.8 Radiated Emission from 1GHz to 4GHz

A.2 Conducted Emission (§15.107(a))

A.2.1 Method of measurement

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits. Tested in accordance with the procedures of ANSI C63.4 - 2003, section 7.2.

A.2.2 EUT Operating Mode:

The MS is operating in the USB mode and charging mode. During the test MS is connected to a PC via a USB cable in the case of USB mode and is connected to a charger in the case of charging mode. The model of the PC is DELL OPTIPLEX 755, and the serial number of the PC is 3908243625. The software is used to let the PC keep on copying data to MS, reading and erasing the data after copy action was finished.

A.2.3 Measurement Limit

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
*Decreases with the logarithm of the frequency		

A.2.4 Test Condition in charging mode

Voltage (V)	Frequency (Hz)
120	60

RBW	Sweep Time(s)
9kHz	1

A.2.4 Measurement Results

Charging Mode




Figure A.9 Conducted Emission(set.1)

MEASUREMENT RESULT: "11A02832_CC1_fin QP"

Frequency	Level	Transd	Limit	Margin	Line	PE
MHz	dBμV	dB	dBμV	dB		
1.035000	25.50	10.1	56	30.5	N	GND
1.080000	29.60	10.1	56	26.4	N	GND
1.125000	38.90	10.1	56	17.1	L1	GND
1.500000	39.00	10.1	56	17.0	L1	GND
1.550000	33.50	10.1	56	22.5	L1	GND
1.595000	36.60	10.1	56	19.4	L1	GND

MEASUREMENT RESULT: "11A02832_CC1_fin AV"

Frequency	Level	Transd	Limit	Margin	Line	PE
MHz	dBμV	dB	dBμV	dB		
0.420000	37.20	10.1	47	10.2	L1	GND
0.470000	34.80	10.1	47	11.8	L1	GND
0.655000	34.70	10.1	46	11.3	L1	GND
0.700000	33.50	10.1	46	12.5	L1	GND
0.750000	31.80	10.1	46	14.2	L1	GND
0.795000	31.80	10.1	46	14.2	L1	GND

Charging Mode




Figure A.10 Conducted Emission(set.2)

MEASUREMENT RESULT: "11A02832_CC2_fin QP"

Frequency	Level	Transd	Limit	Margin	Line	PE
MHz	dBμV	dB	dBμV	dB	/	/
1.640000	51.70	10.1	56	4.3	L1	GND
1.675000	52.00	10.1	56	4.0	L1	GND
1.720000	52.20	10.1	56	3.8	L1	GND
1.760000	51.70	10.1	56	4.3	L1	GND
1.805000	50.60	10.1	56	5.4	L1	GND
1.925000	46.50	10.1	56	9.5	N	GND

MEASUREMENT RESULT: "11A02832_CC2_fin AV"

Frequency	Level	Transd	Limit	Margin	Line	PE
MHz	dBμV	dB	dBμV	dB	/	/
1.320000	44.00	10.1	46	2.0	L1	GND
1.400000	44.60	10.1	46	1.4	L1	GND
1.640000	42.90	10.1	46	3.1	L1	GND
1.720000	44.80	10.1	46	1.2	L1	GND
1.760000	44.80	10.1	46	1.2	L1	GND
1.840000	42.80	10.1	46	3.2	L1	GND




Figure A.11 Conducted Emission(set.3)

MEASUREMENT RESULT: "11A02832_CC3_fin QP"

Frequency	Level	Transd	Limit	Margin	Line	PE
MHz	dBμV	dB	dBμV	dB	/	/
0.155000	53.80	10.1	66	11.9	L1	GND
0.860000	41.80	10.1	56	14.2	L1	GND
1.285000	42.10	10.1	56	13.9	L1	GND
2.102280	46.20	10.1	56	9.8	L1	GND
2.155365	42.70	10.1	56	13.3	L1	GND
3.196243	41.90	10.1	56	14.1	L1	GND

MEASUREMENT RESULT: "11A02832_CC3_fin AV"

Frequency	Level	Transd	Limit	Margin	Line	PE
MHz	dBμV	dB	dBμV	dB	/	/
0.160000	38.30	10.1	56	17.1	N	GND
0.430000	32.60	10.1	47	14.6	L1	GND
0.860000	31.80	10.1	46	14.2	L1	GND
1.210000	30.90	10.1	46	15.1	L1	GND
2.102280	34.60	10.1	46	11.4	L1	GND
3.196243	30.00	10.1	46	16.0	L1	GND

USB Mode




Figure A.12 Conducted Emission

MEASUREMENT RESULT: "11A02832_CC4_fin QP"

Frequency	Level	Transd	Limit	Margin	Line	PE
MHz	dBμV	dB	dBμV	dB	/	/
0.265000	40.90	10.1	61	20.4	L1	GND
0.755000	34.20	10.1	56	21.8	L1	GND
0.830000	35.90	10.1	56	20.1	L1	GND
1.300000	36.80	10.1	56	19.2	L1	GND
1.375000	36.40	10.1	56	19.6	L1	GND
4.669394	34.10	10.2	56	21.9	L1	GND

MEASUREMENT RESULT: "11A02832_CC4_fin AV"

Frequency	Level	Transd	Limit	Margin	Line	PE
MHz	dBμV	dB	dBμV	dB	/	/
0.265000	39.20	10.1	51	12.1	L1	GND
0.715000	33.90	10.1	46	12.1	L1	GND
0.755000	34.30	10.1	46	11.7	L1	GND
0.830000	34.70	10.1	46	11.3	L1	GND
1.300000	33.80	10.1	46	12.2	L1	GND
1.375000	33.30	10.1	46	12.7	L1	GND

END OF REPORT