



# OET 65

# TEST REPORT

|                       |                                                    |
|-----------------------|----------------------------------------------------|
| <b>Product Name</b>   | HSDPA/UMTS dual band / GSM four bands mobile phone |
| <b>Model</b>          | Brandy Lite A                                      |
| <b>Marketing Name</b> | one touch 908A                                     |
| <b>FCC ID</b>         | RAD169                                             |
| <b>Client</b>         | TCT Mobile Limited                                 |

**TA Technology (Shanghai) Co., Ltd.**



## GENERAL SUMMARY

|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |       |               |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|---------------|
| Product Name          | HSDPA/UMTS dual band / GSM four bands mobile phone                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Model | Brandy Lite A |
| FCC ID                | RAD169                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |       |               |
| Report No.            | RZA1105-0800SAR                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |       |               |
| Client                | TCT Mobile Limited                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |       |               |
| Manufacturer          | TCT Mobile Limited                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |       |               |
| Reference Standard(s) | <p><b>IEEE Std C95.1, 1999:</b> IEEE Standard for Safety Levels with Respect to Human Exposure to Radiofrequency Electromagnetic Fields, 3 kHz to 300 GHz.</p> <p><b>IEEE Std 1528™-2003:</b> IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.</p> <p><b>SUPPLEMENT C Edition 01-01 to OET BULLETIN 65 Edition 97-01 June 2001 including DA 02-1438, published June 2002:</b> Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields Additional Information for Evaluation Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions.</p> <p><b>KDB 941225 D06 Hot Spot SAR v01</b> SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities</p> |       |               |
| Conclusion            | <p>This portable wireless equipment has been measured in all cases requested by the relevant standards. Test results in Chapter 7 of this test report are below limits specified in the relevant standards.</p> <p>General Judgment: <b>Pass</b></p> <p>(Stamp)</p> <p>Date of issue: June 3<sup>rd</sup>, 2011</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |       |               |
| Comment               | The test result only responds to the measured sample.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |       |               |

Approved by 杨伟中  
Yang Weizhong

Revised by 凌敏宝  
Ling Minbao

Performed by 沈辰  
Shen Chen



## TABLE OF CONTENT

|                                                                                         |    |
|-----------------------------------------------------------------------------------------|----|
| 1. General Information .....                                                            | 5  |
| 1.1. Notes of the Test Report.....                                                      | 5  |
| 1.2. Testing Laboratory .....                                                           | 5  |
| 1.3. Applicant Information .....                                                        | 6  |
| 1.4. Manufacturer Information.....                                                      | 6  |
| 1.5. Information of EUT.....                                                            | 7  |
| 1.6. The Maximum SAR <sub>1g</sub> Values and Conducted Power of each tested band ..... | 8  |
| 1.7. Test Date .....                                                                    | 9  |
| 2. Operational Conditions during Test .....                                             | 10 |
| 2.1. General Description of Test Procedures .....                                       | 10 |
| 2.2. GSM Test Configuration .....                                                       | 10 |
| 2.3. WCDMA Test Configuration .....                                                     | 11 |
| 2.3.1. Output Power Verification .....                                                  | 11 |
| 2.3.2. Head SAR Measurements .....                                                      | 11 |
| 2.3.3. Body SAR Measurements .....                                                      | 11 |
| 2.4. HSDPA Test Configuration .....                                                     | 11 |
| 2.5. WIFI Test Configuration .....                                                      | 14 |
| 2.6. Test Positions.....                                                                | 15 |
| 2.6.1. Against Phantom Head .....                                                       | 15 |
| 2.6.2. Body Worn Configuration.....                                                     | 15 |
| 3. SAR Measurements System Configuration .....                                          | 16 |
| 3.1. SAR Measurement Set-up .....                                                       | 16 |
| 3.2. DASY4 E-field Probe System .....                                                   | 17 |
| 3.2.1. EX3DV4 Probe Specification .....                                                 | 17 |
| 3.2.2. E-field Probe Calibration .....                                                  | 18 |
| 3.3. Other Test Equipment .....                                                         | 18 |
| 3.3.1. Device Holder for Transmitters .....                                             | 18 |
| 3.3.2. Phantom .....                                                                    | 19 |
| 3.4. Scanning Procedure .....                                                           | 19 |
| 3.5. Data Storage and Evaluation .....                                                  | 21 |
| 3.5.1. Data Storage.....                                                                | 21 |
| 3.5.2. Data Evaluation by SEMCAD .....                                                  | 21 |
| 3.6. System Check.....                                                                  | 24 |
| 3.7. Equivalent Tissues .....                                                           | 25 |
| 4. Laboratory Environment.....                                                          | 26 |
| 5. Characteristics of the Test.....                                                     | 27 |
| 5.1. Applicable Limit Regulations .....                                                 | 27 |
| 5.2. Applicable Measurement Standards .....                                             | 27 |
| 6. Conducted Output Power Measurement .....                                             | 28 |
| 6.1. Summary .....                                                                      | 28 |
| 6.2. Conducted Power Results .....                                                      | 28 |



---

|                                                           |     |
|-----------------------------------------------------------|-----|
| 7. Test Results .....                                     | 30  |
| 7.1. Dielectric Performance.....                          | 30  |
| 7.2. System Check Results.....                            | 31  |
| 7.3. Summary of Measurement Results.....                  | 32  |
| 7.3.1. GSM 850 (GPRS/EGPRS).....                          | 32  |
| 7.3.2. GSM 1900 (GPRS/EGPRS).....                         | 34  |
| 7.3.3. WCDMA Band II (WCDMA/HSDPA).....                   | 36  |
| 7.3.4. WCDMA Band V (WCDMA/HSDPA) .....                   | 38  |
| 7.3.5. Bluetooth/WiFi Function.....                       | 40  |
| 8. Measurement Uncertainty .....                          | 45  |
| 9. Main Test Instruments .....                            | 47  |
| ANNEX A: Test Layout .....                                | 48  |
| ANNEX B: System Check Results .....                       | 52  |
| ANNEX C: Graph Results .....                              | 58  |
| ANNEX D: Probe Calibration Certificate .....              | 175 |
| ANNEX E: D835V2 Dipole Calibration Certificate .....      | 186 |
| ANNEX F: D1900V2 Dipole Calibration Certificate .....     | 195 |
| ANNEX G: D2450V2 Dipole Calibration Certificate.....      | 204 |
| ANNEX H: DAE4 Calibration Certificate.....                | 213 |
| ANNEX I: The EUT Appearances and Test Configuration ..... | 218 |
| ANNEX J: Schematic Diagram of Antenna.....                | 226 |



## **1. General Information**

### **1.1. Notes of the Test Report**

**TA Technology (Shanghai) Co., Ltd.** guarantees the reliability of the data presented in this test report, which is the results of measurements and tests performed for the items under test on the date and under the conditions stated in this test report and is based on the knowledge and technical facilities available at TA Technology (Shanghai) Co., Ltd. at the time of execution of the test.

**TA Technology (Shanghai) Co., Ltd.** is liable to the client for the maintenance by its personnel of the confidentiality of all information related to the items under test and the results of the test. This report only refers to the item that has undergone the test.

This report standalone dose not constitute or imply by its own an approval of the product by the certification Bodies or competent Authorities. This report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of **TA Technology (Shanghai) Co., Ltd.** and the Accreditation Bodies, if it applies.

If the electrical report is inconsistent with the printed one, it should be subject to the latter.

### **1.2. Testing Laboratory**

Company: TA Technology (Shanghai) Co., Ltd.  
Address: No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China  
City: Shanghai  
Post code: 201201  
Country: P. R. China  
Contact: Yang Weizhong  
Telephone: +86-021-50791141/2/3  
Fax: +86-021-50791141/2/3-8000  
Website: <http://www.ta-shanghai.com>  
E-mail: [yangweizhong@ta-shanghai.com](mailto:yangweizhong@ta-shanghai.com)



### **1.3. Applicant Information**

Company: TCT Mobile Limited  
Address: 5F, E building, No. 232, Liang Jing Road ZhangJiang High-Tech Park, Pudong  
Area Shanghai, P.R. China. 201203  
City: Shanghai  
Postal Code: 201203  
Country: P.R. China  
Contact: Gong Zhizhou  
Telephone: 0086-21-6146089  
Fax: 0086-21-61460602

### **1.4. Manufacturer Information**

Company: TCT Mobile Limited  
Address: 5F, E building, No. 232, Liang Jing Road ZhangJiang High-Tech Park, Pudong  
Area Shanghai, P.R. China. 201203  
City: Shanghai  
Postal Code: 201203  
Country: P.R. China  
Telephone: 0086-21-6146089  
Fax: 0086-21-61460602



## 1.5. Information of EUT

### General Information

|                                        |                                                                                                             |                 |                 |
|----------------------------------------|-------------------------------------------------------------------------------------------------------------|-----------------|-----------------|
| Device Type :                          | Portable Device                                                                                             |                 |                 |
| Exposure Category:                     | Uncontrolled Environment / General Population                                                               |                 |                 |
| Product Name:                          | HSDPA/UMTS dual band / GSM four bands mobile phone                                                          |                 |                 |
| Brand:                                 | ALCATEL                                                                                                     |                 |                 |
| IMEI:                                  | 012633000040513                                                                                             |                 |                 |
| Hardware Version:                      | PIO                                                                                                         |                 |                 |
| Software Version:                      | V61H                                                                                                        |                 |                 |
| Antenna Type:                          | Internal Antenna                                                                                            |                 |                 |
| Device Operating Configurations :      |                                                                                                             |                 |                 |
| Supporting Mode(s):                    | GSM 850/GSM 1900/WCDMA Band II/ WCDMA Band V; (tested)<br>WiFi; (tested)<br>GSM 900/GSM 1800;<br>Bluetooth; |                 |                 |
| Test Modulation:                       | (GSM)GMSK; (WCDMA)QPSK                                                                                      |                 |                 |
| Device Class:                          | B                                                                                                           |                 |                 |
| HSDPA UE Category:                     | 8                                                                                                           |                 |                 |
| GPRS Multislot Class(12):              | Max Number of Timeslots in Uplink                                                                           | 4               |                 |
|                                        | Max Number of Timeslots in Downlink                                                                         | 4               |                 |
|                                        | Max Total Timeslot                                                                                          | 5               |                 |
| EGPRS Multislot Class(12):             | Max Number of Timeslots in Uplink                                                                           | 4               |                 |
|                                        | Max Number of Timeslots in Downlink                                                                         | 4               |                 |
|                                        | Max Total Timeslot                                                                                          | 5               |                 |
| Operating Frequency Range(s):          | Mode                                                                                                        | Tx (MHz)        | Rx (MHz)        |
|                                        | GSM 850                                                                                                     | 824.2 ~ 848.8   | 869.2 ~ 893.8   |
|                                        | GSM 1900                                                                                                    | 1850.2 ~ 1909.8 | 1930.2 ~ 1989.8 |
|                                        | WCDMA Band II                                                                                               | 1852.4 ~ 1907.6 | 1932.4 ~ 1987.6 |
|                                        | WCDMA Band V                                                                                                | 826.4 ~ 846.6   | 871.4 ~ 891.6   |
| Power Class:                           | GSM 850: 4, tested with power level 5                                                                       |                 |                 |
|                                        | GSM 1900: 1, tested with power level 0                                                                      |                 |                 |
|                                        | WCDMA Band II: 3, tested with power control all up bits                                                     |                 |                 |
|                                        | WCDMA Band V: 3, tested with power control all up bits                                                      |                 |                 |
| Test Channel:<br>(Low - Middle - High) | 128 - 190 - 251                                                                                             | (GSM 850)       | (tested)        |
|                                        | 512 - 661 - 810                                                                                             | (GSM 1900)      | (tested)        |
|                                        | 9262 - 9400 - 9538                                                                                          | (WCDMA Band II) | (tested)        |
|                                        | 4132 - 4183 - 4233                                                                                          | (WCDMA Band V)  | (tested)        |
|                                        | 1 - 6 - 11                                                                                                  | (WiFi)          | (tested)        |



## Auxiliary Equipment Details

### AE:Battery

Model: /  
Manufacturer: BYD  
S/N: CAB31P0000C1

Equipment Under Test (EUT) is a model of HSDPA/UMTS dual band / GSM four bands mobile phone. The device has an internal antenna for GSM/WCDMA Tx/Rx, and the other is BT/WiFi antenna that can be used for Tx/Rx. It has Personal Wireless Routers (hot spots) function. The detail about Mobile phone and Lithium Battery is in chapter 1.5 in this report. SAR is tested for GSM 850, GSM 1900, WCDMA Band II, WCDMA Band V and WiFi.

The sample under test was selected by the Client.

Components list please refer to documents of the manufacturer.

## 1.6. The Maximum SAR<sub>1g</sub> Values and Conducted Power of each tested band

### Head Configuration

| Mode          | Channel   | Position     | SAR <sub>1g</sub> (W/kg) |
|---------------|-----------|--------------|--------------------------|
| GSM 850       | High/251  | Right, Cheek | <b>0.786</b>             |
| GSM 1900      | Low/512   | Left, Cheek  | <b>0.496</b>             |
| WCDMA Band II | Low/9262  | Left, Cheek  | <b>0.957</b>             |
| WCDMA Band V  | High/4233 | Right, Cheek | <b>0.864</b>             |
| WiFi          | Middle/6  | Right, Cheek | <b>0.363</b>             |

### Body Worn Configuration

| Mode              | Channel     | Separation distance | SAR <sub>1g</sub> (W/kg) |
|-------------------|-------------|---------------------|--------------------------|
| 4-slots GPRS 850  | High/251    | 15mm                | <b>0.751</b>             |
| 4-slots GPRS 1900 | Low/512     | 15mm                | <b>0.458</b>             |
| WCDMA Band II     | Low/9262    | 15mm                | <b>0.544</b>             |
| WCDMA Band V      | Middle/4183 | 15mm                | <b>0.741</b>             |
| WiFi              | Middle/6    | 15mm                | <b>0.094</b>             |





**Hot spot Mode**

| Mode              | Channel     | Separation distance | SAR <sub>1g</sub> (W/kg) |
|-------------------|-------------|---------------------|--------------------------|
| 4-slots GPRS 850  | Low/128     | 10mm                | <b>1.030</b>             |
| 4-slots GPRS 1900 | Low/512     | 10mm                | <b>0.736</b>             |
| WCDMA Band II     | Low/9262    | 10mm                | <b>0.965</b>             |
| WCDMA Band V      | Middle/4183 | 10mm                | <b>0.918</b>             |
| WiFi              | Low/1       | 10mm                | <b>0.173</b>             |

**Maximum Power**

| Band          |                | Max Conducted Power<br>(dBm) | Max Average Power<br>(dBm) |
|---------------|----------------|------------------------------|----------------------------|
| GSM 850       | GSM            | <b>32.79</b>                 | <b>23.76</b>               |
|               | GPRS, 4-slots  | <b>28.28</b>                 | <b>25.27</b>               |
|               | EGPRS, 4-slots | <b>28.30</b>                 | <b>25.29</b>               |
| GSM 1900      | GSM            | <b>29.36</b>                 | <b>20.33</b>               |
|               | GPRS, 4-slots  | <b>25.62</b>                 | <b>22.61</b>               |
|               | EGPRS, 4-slots | <b>25.64</b>                 | <b>22.63</b>               |
| WCDMA Band II |                | <b>22.48</b>                 | <b>/</b>                   |
| WCDMA Band V  |                | <b>23.11</b>                 | <b>/</b>                   |

Note: The detail Power refer to Table 10 (Power Measurement Results).

**1.7. Test Date**

The test is performed from May 21, 2011 to June 1, 2011.



## 2. Operational Conditions during Test

### 2.1. General Description of Test Procedures

A communication link is set up with a System Simulator (SS) by air link, and a call is established. The Absolute Radiofrequency Channel Number (ARFCN) is allocated to 128, 190 and 251 in the case of GSM 850, to 512, 661 and 810 in the case of GSM 1900, to 9262, 9400 and 9538 in the case of WCDMA Band II, to 4132, 4183 and 4233 in the case of WCDMA Band V. The EUT is commanded to operate at maximum transmitting power.

Connection to the EUT is established via air interface with E5515C, and the EUT is set to maximum output power by E5515C. The EUT battery must be fully charged and checked periodically during the test to ascertain uniform power output. The antenna connected to the output of the base station simulator shall be placed at least 50 cm away from the EUT. The signal transmitted by the simulator to the antenna feeding point shall be lower than the output power level of the EUT by at least 30 dB.

### 2.2. GSM Test Configuration

SAR tests for GSM 850 and GSM 1900, a communication link is set up with a System Simulator (SS) by air link. Using E5515C the power lever is set to “5” in SAR of GSM 850, set to “0” in SAR of GSM 1900. Since the GPRS class is 12 for this EUT, it has at most 4 timeslots in uplink and at most 4 timeslots in downlink, the maximum total timeslots is 5; the EGPRS class is 12 for this EUT, it has at most 4 timeslots in uplink and at most 4 timeslots in downlink, the maximum total timeslots is 5.

When SAR tests for EGPRS mode is necessary, GMSK modulation should be used to minimize SAR measurement error due to higher peak-to-average power (PAR) ratios inherent in 8-PSK.

According to specification 3GPP TS 51.010, the maximum power of the GSM can do the power reduction for the multi-slot. The allowed power reduction in the multi-slot configuration is as following:

**Table 1: The allowed power reduction in the multi-slot configuration**

| Number of timeslots in uplink assignment | Permissible nominal reduction of maximum output power,(dB) |
|------------------------------------------|------------------------------------------------------------|
| 1                                        | 0                                                          |
| 2                                        | 0 to 3,0                                                   |
| 3                                        | 1,8 to 4,8                                                 |
| 4                                        | 3,0 to 6,0                                                 |



## 2.3. WCDMA Test Configuration

### 2.3.1. Output Power Verification

Maximum output power is verified on the High, Middle and Low channel according to the procedures described in section 5.2 of 3GPP TS 34. 121, using the appropriate RMC or AMR with TPC(transmit power control) set to all "1's" for WCDMA/HSDPA. Results for all applicable physical channel configuration (DPCCH, DPDCH<sub>n</sub> and spreading codes, HSDPA) should be tabulated in the SAR report. All configuration that are not supported by the DUT or can not be measured due to technical or equipment limitations should be clearly identified.

### 2.3.2. Head SAR Measurements

SAR for head exposure configurations in voice mode is measured using a 12.2kbps RMC with TPC bits configured to all "1's". SAR in AMR configurations is not required when the maximum average output of each RF channel for 12.2kbps AMR is less than 1/4 dB higher than that measured in 12.2 kbps RMC. Otherwise, SAR is measured on the maximum output channel in 12.2kbps AMR with a 3.4 kbps SRB( Signaling radio bearer) using the exposure configuration that results in the highest SAR in 12.2kbps RMC for that RF channel.

### 2.3.3. Body SAR Measurements

SAR for body exposure configurations in voice and data modes is measured using 12.2kbps RMC with TPC bits configured to all "1's". SAR for other spreading codes and multiple DPDCH<sub>n</sub>, when supported by the DUT, are not required when the maximum average output of each RF channel, for each spreading code and DPDCH<sub>n</sub> configuration, are less than 1/4 dB higher than those measured in 12.2kbps RMC. Otherwise, SAR is measured on the maximum output channel with an applicable RMC configuration for the corresponding spreading code or DPDCH<sub>n</sub> using the exposure configuration that results in the highest SAR with 12.2 kbps RMC. When more than 2 DPDCH<sub>n</sub> are supported by the DUT, it may be necessary to configure additional DPDCH<sub>n</sub> for a DUT using FTM (Factory Test Mode) or other chipset based test approaches with parameters similar to those used in 384 kbps and 768 kbps RMC.

## 2.4. HSDPA Test Configuration

SAR for body exposure configurations is measured according to the "Body SAR Measurements" procedures of 3G device. In addition, body SAR is also measured for HSDPA when the maximum average output of each RF channel with HSDPA active is at least 1/4 dB higher than that measured without HSDPA using 12.2kbps RMC or the maximum SAR 12.2kbps RMC is above 75% of the SAR limit. Body SAR for HSDPA is measured using an FRC with H-Set 1 in Sub-test 1 and a 12.2kbps RMC configured in Test Loop Mode 1, using the highest body SAR configuration in 12.2 kbps RMC without HSDPA.

HSDPA should be configured according to the UE category of a test device. The number of HS-DSCH/HS-PDSCHs, HARQ processes, minimum inter-TTI interval, transport block sizes and RV coding sequence are defined by the H-set. To maintain a consistent test configuration and stable transmission condition, QPSK is used in the H-set for SAR testing. HS-DPCCH should be configured with a CQI feedback cycle of 4 ms with a CQI repetition factor of 2 to maintain a constant rate of active CQI slots. DPCCH and DPDCH gain factors( $\beta_c, \beta_d$ ), and HS-DPCCH power offset



parameters( $\Delta_{ACK}$ ,  $\Delta_{NACK}$ ,  $\Delta_{CQI}$ ) should be set according to values indicated in the Table below. The CQI value is determined by the UE category, transport block size, number of HS-PDSCHs and modulation used in the H-set.

**Table 2: Subtests for UMTS Release 5 HSDPA**

| Sub-set | $\beta_c$         | $\beta_d$         | $\beta_d$<br>(SF) | $\beta_c/\beta_d$ | $\beta_{hs}$<br>(note 1, note 2) | CM(dB)<br>(note 3) | MPR(dB) |
|---------|-------------------|-------------------|-------------------|-------------------|----------------------------------|--------------------|---------|
| 1       | 2/15              | 15/15             | 64                | 2/15              | 4/15                             | 0.0                | 0.0     |
| 2       | 12/15<br>(note 4) | 15/15<br>(note 4) | 64                | 12/15<br>(note 4) | 24/15                            | 1.0                | 0.0     |
| 3       | 15/15             | 8/15              | 64                | 15/8              | 30/15                            | 1.5                | 0.5     |
| 4       | 15/15             | 4/15              | 64                | 15/4              | 30/15                            | 1.5                | 0.5     |

Note1:  $\Delta_{ACK}$ ,  $\Delta_{NACK}$  and  $\Delta_{CQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs}/\beta_c = 30/15 \Leftrightarrow \beta_{hs} = 30/15 * \beta_c$

Note2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1.A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA,  $\Delta_{ACK}$  and  $\Delta_{NACK} = 8$  ( $A_{hs} = 30/15$ ) with  $\beta_{hs} = 30/15 * \beta_c$ , and  $\Delta_{CQI} = 7$  ( $A_{hs} = 24/15$ ) with  $\beta_{hs} = 24/15 * \beta_c$ .

Note3: CM=1 for  $\beta_c/\beta_d = 12/15$ ,  $\beta_{hs}/\beta_c = 24/15$ . For all other combinations of DPDCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.

Note 4: For subtest 2 the  $\beta_c/\beta_d$  ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TFC1, TF1) to  $\beta_c = 11/15$  and  $\beta_d = 15/15$ .

**Table 3: Settings of required H-Set 1 QPSK in HSDPA mode**

| Parameter                             | Unit      | Value |
|---------------------------------------|-----------|-------|
| Nominal Avg. Inf. Bit Rate            | kbps      | 534   |
| Inter-TTI Distance                    | TTI's     | 3     |
| Number of HARQ Processes              | Processes | 2     |
| Information Bit Payload ( $N_{INF}$ ) | Bits      | 3202  |
| Number Code Blocks                    | Blocks    | 1     |
| Binary Channel Bits Per TTI           | Bits      | 4800  |
| Total Available SML's in UE           | SML's     | 19200 |
| Number of SML's per HARQ Proc.        | SML's     | 9600  |
| Coding Rate                           | /         | 0.67  |
| Number of Physical Channel Codes      | Codes     | 5     |
| Modulation                            | /         | QPSK  |



Table 4: HSDPA UE category

| HS-DSCH Category | Maximum HS-DSCH Codes Received | Minimum Inter-TTI Interval | Maximum Transport Bits/HS-DSCH | Total Channel |
|------------------|--------------------------------|----------------------------|--------------------------------|---------------|
| 1                | 5                              | 3                          | 7298                           | 19200         |
| 2                | 5                              | 3                          | 7298                           | 28800         |
| 3                | 5                              | 2                          | 7298                           | 28800         |
| 4                | 5                              | 2                          | 7298                           | 38400         |
| 5                | 5                              | 1                          | 7298                           | 57600         |
| 6                | 5                              | 1                          | 7298                           | 67200         |
| 7                | 10                             | 1                          | 14411                          | 115200        |
| 8                | 10                             | 1                          | 14411                          | 134400        |
| 9                | 15                             | 1                          | 25251                          | 172800        |
| 10               | 15                             | 1                          | 27952                          | 172800        |
| 11               | 5                              | 2                          | 3630                           | 14400         |
| 12               | 5                              | 1                          | 3630                           | 28800         |
| 13               | 15                             | 1                          | 34800                          | 259200        |
| 14               | 15                             | 1                          | 42196                          | 259200        |
| 15               | 15                             | 1                          | 23370                          | 345600        |
| 16               | 15                             | 1                          | 27952                          | 345600        |

Table 5: UE maximum output powers with HS-DPCCH (Release 5 Only)

| Ratio of $\beta_c$ to $\beta_d$ for all values of $\beta_{hs}$ | Power Class 3 |                | Power Class 4 |                |
|----------------------------------------------------------------|---------------|----------------|---------------|----------------|
|                                                                | Power (dBm)   | Tolerance (dB) | Power (dBm)   | Tolerance (dB) |
| $1/15 \leq \beta_c/\beta_d \leq 12/15$                         | +24           | +1/-3          | +21           | +2/-2          |
| $13/15 \leq \beta_c/\beta_d \leq 15/8$                         | +23           | +2/-3          | +20           | +3/-2          |
| $15/7 \leq \beta_c/\beta_d \leq 15/0$                          | +22           | +3/-3          | +19           | +4/-2          |



## 2.5. WIFI Test Configuration

For the 802.11b/g SAR tests, a communication link is set up with the test mode software for WIFI mode test. The Absolute Radio Frequency Channel Number (ARFCN) is allocated to 1, 6 and 11 respectively in the case of 2450 MHz. During the test, at the each test frequency channel, the EUT is operated at the RF continuous emission mode. Each channel should be tested at the lowest data rate. Testing at higher data rates is not required when the maximum average output power is less than 0.25dB higher than those measured at the lowest data rate.

802.11b/g operating modes are tested independently according to the service requirements in each frequency band. 802.11b/g modes are tested on channels 1, 6, 11; however, if output power reduction is necessary for channels 1 and /or 11 to meet restricted band requirements the highest output channels closest to each of these channels must be tested instead.

SAR is not required for 802.11g channels when the maximum average output power is less than 0.25dB higher than that measured on the corresponding 802.11b channels. When the maximum average output channel in each frequency band is not included in the “default test channels”, the maximum channel should be tested instead of an adjacent “default test channels”, these are referred to as the “required test channels” and are illustrated in Table 6.

Table 6: “Default Test Channels”

| Mode      | GHz   | Channel         | Turbo Channel | “Default Test Channels” |         |      |  |
|-----------|-------|-----------------|---------------|-------------------------|---------|------|--|
|           |       |                 |               | 15.247                  |         | UNII |  |
|           |       |                 |               | 802.11b                 | 802.11g |      |  |
| 802.11b/g | 2.412 | 1 <sup>#</sup>  |               | √                       | *       |      |  |
|           | 2.437 | 6               | 6             | √                       | *       |      |  |
|           | 2.462 | 11 <sup>#</sup> |               | √                       | *       |      |  |

Note: <sup>#</sup>=when output power is reduced for channel 1 and /or 11 to meet restricted band requirements the highest out put channels closet to each of these channels should be tested.

√= “default test channels”

\* =possible 802.11g channels with maximum average output 0.25dB>=the “default test channels”



## **2.6. Test Positions**

### **2.6.1. Against Phantom Head**

Measurements were made in “cheek” and “tilt” positions on both the left hand and right hand sides of the phantom.

The positions used in the measurements were according to IEEE 1528 - 2003 "IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate(SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques".

### **2.6.2. Body Worn Configuration**

Body-worn operating configurations should be tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in normal use configurations. Devices with a headset output should be tested with a headset connected to the device. The distance between the device and the phantom was kept 15mm.

Based upon KDB941225 D06, when the antenna-to-edge distance is greater than 2.5cm, such position does not need to be tested. The distance between the device and the phantom was kept 10mm of wireless routers.



### 3. SAR Measurements System Configuration

#### 3.1. SAR Measurement Set-up

The DASY4 system for performing compliance tests consists of the following items:

- A standard high precision 6-axis robot (Stäubli RX family) with controller and software. An arm extension for accommodating the data acquisition electronics (DAE).
- A dosimetric probe, i.e. an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
- A data acquisition electronic (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- A unit to operate the optical surface detector which is connected to the EOC.
- The Electro-Optical Coupler (EOC) performs the conversion from the optical into a digital electric signal of the DAE. The EOC is connected to the DASY4 measurement server.
- The DASY4 measurement server, which performs all real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operation. A computer operating Windows 2003
- DASY4 software and SEMCAD data evaluation software.
- Remote control with teach panel and additional circuitry for robot safety such as warning lamps, etc.
- The generic twin phantom enabling the testing of left-hand and right-hand usage.
- The device holder for handheld mobile phones.
- Tissue simulating liquid mixed according to the given recipes.
- System validation dipoles allowing to validate the proper functioning of the system.




Figure 1 SAR Lab Test Measurement Set-up





### 3.2. DASY4 E-field Probe System

The SAR measurements were conducted with the dosimetric probe EX3DV4 (manufactured by SPEAG), designed in the classical triangular configuration and optimized for dosimetric evaluation.

#### 3.2.1. EX3DV4 Probe Specification


|               |                                                                                                                                                                                                               |
|---------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Construction  | Symmetrical design with triangular core<br>Built-in shielding against static charges<br>PEEK enclosure material (resistant to organic solvents, e.g., DGBE)                                                   |
| Calibration   | ISO/IEC 17025 calibration service available                                                                                                                                                                   |
| Frequency     | 10 MHz to > 6 GHz<br>Linearity: $\pm 0.2$ dB<br>(30 MHz to 6 GHz)                                                                                                                                             |
| Directivity   | $\pm 0.3$ dB in HSL (rotation around probe axis) $\pm 0.5$ dB in tissue material (rotation normal to probe axis)                                                                                              |
| Dynamic Range | 10 $\mu$ W/g to > 100 mW/g Linearity:<br><br>$\pm 0.2$ dB (noise: typically < 1 $\mu$ W/g)                                                                                                                    |
| Dimensions    | Overall length: 330 mm (Tip: 20 mm)<br>Tip diameter: 2.5 mm (Body: 12 mm)<br>Typical distance from probe tip to dipole centers: 1 mm                                                                          |
| Application   | High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields).<br>Only probe which enables compliance testing for frequencies up to 6 GHz with precision of better 30%. |



Figure 2.EX3DV4 E-field Probe



Figure 3. EX3DV4 E-field probe



### 3.2.2. E-field Probe Calibration

Each probe is calibrated according to a dosimetric assessment procedure with accuracy better than  $\pm 10\%$ . The spherical isotropy was evaluated and found to be better than  $\pm 0.25\text{dB}$ . The sensitivity parameters (NormX, NormY, NormZ), the diode compression parameter (DCP) and the conversion factor (ConvF) of the probe are tested.

The free space E-field from amplified probe outputs is determined in a test chamber. This is performed in a TEM cell for frequencies below 1 GHz, and in a wave guide above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is then rotated 360 degrees.

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated brain tissue. The measured free space E-field in the medium correlates to temperature rise in a dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

$$\text{SAR} = C \frac{\Delta T}{\Delta t}$$

Where:  $\Delta t$  = Exposure time (30 seconds),

C = Heat capacity of tissue (brain or muscle),

$\Delta T$  = Temperature increase due to RF exposure.

Or

$$\text{SAR} = \frac{|E|^2 \sigma}{\rho}$$

Where:

$\sigma$  = Simulated tissue conductivity,

$\rho$  = Tissue density ( $\text{kg/m}^3$ ).

### 3.3. Other Test Equipment

#### 3.3.1. Device Holder for Transmitters


The DASY device holder is designed to cope with the different positions given in the standard.

It has two scales for device rotation (with respect to the body axis) and device inclination (with respect to the line between the ear reference points). The rotation centers for both scales is the ear reference point (ERP). Thus the device needs no repositioning when changing the angles.

The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.



Figure 4 Device Holder



### 3.3.2. Phantom

The Generic Twin Phantom is constructed of a fiberglass shell integrated in a wooden Figure. The shape of the shell is based on data from an anatomical study designed to determine the maximum exposure in at least 90% of all users. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents the evaporation of the liquid. Reference markings on the Phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot.

|                 |                                        |
|-----------------|----------------------------------------|
| Shell Thickness | 2±0.1 mm                               |
| Filling Volume  | Approx. 20 liters                      |
| Dimensions      | 810 x 1000 x 500 mm (H x L x W)        |
|                 | Available                      Special |



Figure 5 Generic Twin Phantom

### 3.4. Scanning Procedure

The DASY4 installation includes predefined files with recommended procedures for measurements and validation. They are read-only document files and destined as fully defined but unmeasured masks. All test positions (head or body-worn) are tested with the same configuration of test steps differing only in the grid definition for the different test positions.

- The “reference” and “drift” measurements are located at the beginning and end of the batch process. They measure the field drift at one single point in the liquid over the complete procedure. The indicated drift is mainly the variation of the DUT’s output power and should vary max.  $\pm 5\%$ .
- The “surface check” measurement tests the optical surface detection system of the DASY4 system by repeatedly detecting the surface with the optical and mechanical surface detector and comparing the results. The output gives the detecting heights of both systems, the difference between the two systems and the standard deviation of the detection repeatability. Air bubbles or refraction in the liquid due to separation of the sugar-water mixture gives poor repeatability (above  $\pm 0.1\text{mm}$ ). To prevent wrong results tests are only executed when the liquid is free of air bubbles. The difference between the optical surface detection and the actual surface depends on the probe and is specified with each probe. (It does not depend on the surface reflectivity or the probe angle to the surface within  $\pm 30^\circ$ .)
- Area Scan  
The Area Scan is used as a fast scan in two dimensions to find the area of high field values before running a detailed measurement around the hot spot. Before starting the area scan a grid



spacing of 15 mm x 15 mm is set. During the scan the distance of the probe to the phantom remains unchanged.

After finishing area scan, the field maxima within a range of 2 dB will be ascertained.

- **Zoom Scan**

Zoom Scans are used to estimate the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. The default Zoom Scan is done by 7x7x7 points within a cube whose base is centered around the maxima found in the preceding area scan.

- **Spatial Peak Detection**

The procedure for spatial peak SAR evaluation has been implemented and can determine values of masses of 1g and 10g, as well as for user-specific masses. The DASY4 system allows evaluations that combine measured data and robot positions, such as:

- maximum search
- extrapolation
- boundary correction
- peak search for averaged SAR

During a maximum search, global and local maxima searches are automatically performed in 2-D after each Area Scan measurement with at least 6 measurement points. It is based on the evaluation of the local SAR gradient calculated by the Quadratic Shepard's method. The algorithm will find the global maximum and all local maxima within -2 dB of the global maxima for all SAR distributions.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. Several measurements at different distances are necessary for the extrapolation. Extrapolation routines require at least 10 measurement points in 3-D space. They are used in the Zoom Scan to obtain SAR values between the lowest measurement points and the inner phantom surface. The routine uses the modified Quadratic Shepard's method for extrapolation. For a grid using 7x7x7 measurement points with 5mm resolution amounting to 343 measurement points, the uncertainty of the extrapolation routines is less than 1% for 1g and 10g cubes.

- A Z-axis scan measures the total SAR value at the x-and y-position of the maximum SAR value found during the cube 7x7x7 scan. The probe is moved away in z-direction from the bottom of the SAM phantom in 5mm steps.



### 3.5. Data Storage and Evaluation

#### 3.5.1. Data Storage

The DASY4 software stores the acquired data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors), together with all necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files with the extension “.DA4”. The software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of incorrect parameter settings. For example, if a measurement has been performed with a wrong crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be re-evaluated.

The measured data can be visualized or exported in different units or formats, depending on the selected probe type ([V/m], [A/m], [°C], [mW/g], [mW/cm²], [dBrel], etc.). Some of these units are not available in certain situations or show meaningless results, e.g., a SAR output in a lossless media will always be zero. Raw data can also be exported to perform the evaluation with other software packages.

#### 3.5.2. Data Evaluation by SEMCAD

The SEMCAD software automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

|                    |                           |                                       |
|--------------------|---------------------------|---------------------------------------|
| Probe parameters:  | - Sensitivity             | Normi, $a_{i0}$ , $a_{i1}$ , $a_{i2}$ |
|                    | - Conversion factor       | ConvF <sub>i</sub>                    |
|                    | - Diode compression point | Dcp <sub>i</sub>                      |
| Device parameters: | - Frequency               | f                                     |
|                    | - Crest factor            | cf                                    |
| Media parameters:  | - Conductivity            |                                       |
|                    | - Density                 |                                       |

These parameters must be set correctly in the software. They can be found in the component documents or they can be imported into the software from the configuration files issued for the DASY4 components. In the direct measuring mode of the multimeter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics.



If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot c f / d c p_i$$

With  $V_i$  = compensated signal of channel i (i = x, y, z)

$U_i$  = input signal of channel i (i = x, y, z)

$cf$  = crest factor of exciting field (DASY parameter)

$dcp_i$  = diode compression point (DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

E-field probes:  $E_i = (V_i / Norm_i \cdot ConvF)^{1/2}$

H-field probes:  $H_i = (V_i)^{1/2} \cdot (a_{i0} + a_{i1}f + a_{i2}f^2) / f$

With  $V_i$  = compensated signal of channel i (i = x, y, z)

$Norm_i$  = sensor sensitivity of channel i (i = x, y, z)  
[mV/(V/m)<sup>2</sup>] for E-field Probes

$ConvF$  = sensitivity enhancement in solution

$a_{ij}$  = sensor sensitivity factors for H-field probes

$f$  = carrier frequency [GHz]

$E_i$  = electric field strength of channel i in V/m

$H_i$  = magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = (E_x^2 + E_y^2 + E_z^2)^{1/2}$$

The primary field data are used to calculate the derived field units.

$$SAR = (E_{tot}^2 \cdot \rho) / (2 \cdot 1000)$$



with **SAR** = local specific absorption rate in mW/g

**$E_{tot}$**  = total field strength in V/m

**$\sigma$**  = conductivity in [mho/m] or [Siemens/m]

**$\rho$**  = equivalent tissue density in g/cm<sup>3</sup>

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid. The power flow density is calculated assuming the excitation field to be a free space field.

$$P_{pwe} = E_{tot}^2 / 3770 \quad \text{or} \quad P_{pwe} = H_{tot}^2 \cdot 37.7$$

with  **$P_{pwe}$**  = equivalent power density of a plane wave in mW/cm<sup>2</sup>

**$E_{tot}$**  = total electric field strength in V/m

**$H_{tot}$**  = total magnetic field strength in A/m



### 3.6. System Check

The manufacturer calibrates the probes annually. Dielectric parameters of the tissue simulates were measured every day using the dielectric probe kit and the network analyzer. A system check measurement was made following the determination of the dielectric parameters of the simulates, using the dipole validation kit. A power level of 250 mW was supplied to the dipole antenna, which was placed under the flat section of the twin SAM phantom. The system check results (dielectric parameters and SAR values) are given in the table 13 and table 14.

System check results have to be equal or near the values determined during dipole calibration with the relevant liquids and test system ( $\pm 10\%$ ).

System check is performed regularly on all frequency bands where tests are performed with the DASY4 system.




Figure 6 System Check Set-up





### 3.7. Equivalent Tissues

The liquid is consisted of water, salt, Glycol, Sugar, Preventol and Cellulose. The liquid has previously been proven to be suited for worst-case. The table 7 and table 8 show the detail solution. It's satisfying the latest tissue dielectric parameters requirements proposed by the OET 65.

Table 7: Composition of the Head Tissue Equivalent Matter

| MIXTURE%                              | FREQUENCY(Brain) 835MHz               |
|---------------------------------------|---------------------------------------|
| Water                                 | 41.45                                 |
| Sugar                                 | 56                                    |
| Salt                                  | 1.45                                  |
| Preventol                             | 0.1                                   |
| Cellulose                             | 1.0                                   |
| Dielectric Parameters<br>Target Value | f=835MHz $\epsilon=41.5$ $\sigma=0.9$ |

| MIXTURE%                              | FREQUENCY(Brain) 1900MHz                |
|---------------------------------------|-----------------------------------------|
| Water                                 | 55.242                                  |
| Glycol monobutyl                      | 44.452                                  |
| Salt                                  | 0.306                                   |
| Dielectric Parameters<br>Target Value | f=1900MHz $\epsilon=40.0$ $\sigma=1.40$ |

| MIXTURE%                              | FREQUENCY(Brain) 2450MHz                 |
|---------------------------------------|------------------------------------------|
| Water                                 | 62.7                                     |
| Glycol                                | 36.8                                     |
| Salt                                  | 0.5                                      |
| Dielectric Parameters<br>Target Value | f=2450MHz $\epsilon=39.20$ $\sigma=1.80$ |

Table 8: Composition of the Body Tissue Equivalent Matter

| MIXTURE%                              | FREQUENCY(Body) 835MHz                 |
|---------------------------------------|----------------------------------------|
| Water                                 | 52.5                                   |
| Sugar                                 | 45                                     |
| Salt                                  | 1.4                                    |
| Preventol                             | 0.1                                    |
| Cellulose                             | 1.0                                    |
| Dielectric Parameters<br>Target Value | f=835MHz $\epsilon=55.2$ $\sigma=0.97$ |



| MIXTURE%                              | FREQUENCY (Body) 1900MHz                |
|---------------------------------------|-----------------------------------------|
| Water                                 | 69.91                                   |
| Glycol monobutyl                      | 29.96                                   |
| Salt                                  | 0.13                                    |
| Dielectric Parameters<br>Target Value | f=1900MHz $\epsilon=53.3$ $\sigma=1.52$ |

| MIXTURE%                              | FREQUENCY(Body) 2450MHz                  |
|---------------------------------------|------------------------------------------|
| Water                                 | 73.2                                     |
| Glycol                                | 26.7                                     |
| Salt                                  | 0.1                                      |
| Dielectric Parameters<br>Target Value | f=2450MHz $\epsilon=52.70$ $\sigma=1.95$ |

## 4. Laboratory Environment

Table 9: The Ambient Conditions during Test

|                                                                                                                                                                                                 |                           |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|
| Temperature                                                                                                                                                                                     | Min. = 20°C, Max. = 25 °C |
| Relative humidity                                                                                                                                                                               | Min. = 30%, Max. = 70%    |
| Ground system resistance                                                                                                                                                                        | < 0.5 $\Omega$            |
| Ambient noise is checked and found very low and in compliance with requirement of standards.<br>Reflection of surrounding objects is minimized and in compliance with requirement of standards. |                           |



## **5. Characteristics of the Test**

### **5.1. Applicable Limit Regulations**

**IEEE Std C95.1, 1999:** IEEE Standard for Safety Levels with Respect to Human Exposure to Radiofrequency Electromagnetic Fields, 3 kHz to 300 GHz.

### **5.2. Applicable Measurement Standards**

**IEEE Std 1528™-2003:** IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.

**SUPPLEMENT C Edition 01-01 to OET BULLETIN 65 Edition 97-01 June 2001 including DA 02-1438, published June 2002:** Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields Additional Information for Evaluation Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions.

**KDB 941225 D06 Hot Spot SAR v01** SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities



## 6. Conducted Output Power Measurement

### 6.1. Summary

The DUT is tested using an E5515C communications tester as controller unit to set test channels and maximum output power to the DUT, as well as for measuring the conducted power. Conducted output power was measured using an integrated RF connector and attached RF cable. This result contains conducted output power for the EUT.

### 6.2. Conducted Power Results

Table 10: Conducted Power Measurement Results

| GSM 850      |          | Conducted Power(dBm) |             |             |         | Average power(dBm) |              |              |
|--------------|----------|----------------------|-------------|-------------|---------|--------------------|--------------|--------------|
|              |          | Channel 128          | Channel 190 | Channel 251 |         | Channel 128        | Channel 190  | Channel 251  |
| GSM          | Results  | 32.79                | 32.77       | 32.71       | -9.03dB | 23.76              | 23.74        | 23.68        |
| GPRS (GMSK)  | 1TXslot  | 32.81                | 32.77       | 32.74       | -9.03dB | 23.78              | 23.74        | 23.71        |
|              | 2TXslots | 30.91                | 30.85       | 30.86       | -6.02dB | 24.89              | 24.83        | 24.84        |
|              | 3TXslots | 29.35                | 29.31       | 29.31       | -4.26dB | 25.09              | 25.05        | 25.05        |
|              | 4TXslots | 28.28                | 28.27       | 28.26       | -3.01dB | <b>25.27</b>       | <b>25.26</b> | <b>25.25</b> |
| EGPRS (GMSK) | 1TXslot  | 32.77                | 32.79       | 32.71       | -9.03dB | 23.74              | 23.76        | 23.68        |
|              | 2TXslots | 30.91                | 30.89       | 30.84       | -6.02dB | 24.89              | 24.87        | 24.82        |
|              | 3TXslots | 29.35                | 29.34       | 29.3        | -4.26dB | 25.09              | 25.08        | 25.04        |
|              | 4TXslots | 28.3                 | 28.29       | 28.24       | -3.01dB | <b>25.29</b>       | <b>25.28</b> | <b>25.23</b> |
| GSM 1900     |          | Conducted Power(dBm) |             |             |         | Average power(dBm) |              |              |
|              |          | Channel 512          | Channel 661 | Channel 810 |         | Channel 512        | Channel 661  | Channel 810  |
| GSM          | Results  | 29.13                | 29.36       | 29.28       | -9.03dB | 20.1               | 20.33        | 20.25        |
| GPRS (GMSK)  | 1TXslot  | 29.18                | 29.35       | 29.28       | -9.03dB | 20.15              | 20.32        | 20.25        |
|              | 2TXslots | 27.97                | 28.11       | 28.05       | -6.02dB | 21.95              | 22.09        | 22.03        |
|              | 3TXslots | 26.55                | 26.63       | 26.54       | -4.26dB | 22.29              | 22.37        | 22.28        |
|              | 4TXslots | 25.52                | 25.62       | 25.52       | -3.01dB | <b>22.51</b>       | <b>22.61</b> | <b>22.51</b> |
| EGPRS (GMSK) | 1TXslot  | 29.11                | 29.35       | 29.25       | -9.03dB | 20.08              | 20.32        | 20.22        |
|              | 2TXslots | 27.9                 | 28.12       | 28.01       | -6.02dB | 21.88              | 22.1         | 21.99        |
|              | 3TXslots | 26.49                | 26.65       | 26.51       | -4.26dB | 22.23              | 22.39        | 22.25        |
|              | 4TXslots | 25.47                | 25.64       | 25.49       | -3.01dB | <b>22.46</b>       | <b>22.63</b> | <b>22.48</b> |

Note:

1) Division Factors

To average the power, the division factor is as follows:

1 TX- slot = 1 transmit time slot out of 8 time slots



=> conducted power divided by (8/1) => -9.03 dB

2) TX- slots = 2 transmit time slots out of 8 time slots

=> conducted power divided by (8/2) => -6.02 dB

3) TX- slots = 3 transmit time slots out of 8 time slots

=> conducted power divided by (8/3) => -4.26 dB

4) TX- slots = 4 transmit time slots out of 8 time slots

=> conducted power divided by (8/4) => -3.01 dB

2) Average power numbers

The maximum power numbers are marks in bold.

| WCDMA Band II       | Conducted Power (dBm) |              |              |
|---------------------|-----------------------|--------------|--------------|
|                     | Channel 9262          | Channel 9400 | Channel 9538 |
| 12.2kbps RMC        | 21.6                  | 22.48        | 22.22        |
| 64kbps RMC          | 21.54                 | 22.45        | 22.19        |
| 144kbps RMC         | 21.59                 | 22.43        | 22.17        |
| 384kbps RMC         | 21.56                 | 22.43        | 22.16        |
| WCDMA Band II HSDPA | Conducted Power (dBm) |              |              |
|                     | Channel 9262          | Channel 9400 | Channel 9538 |
| Sub - Test 1        | 21.56                 | 22.4         | 22.15        |
| Sub - Test 2        | 21.49                 | 22.32        | 22.08        |
| Sub - Test 3        | 21.14                 | 21.97        | 21.69        |
| Sub - Test 4        | 21.1                  | 21.91        | 21.67        |
| WCDMA Band V        | Conducted Power (dBm) |              |              |
|                     | Channel 4132          | Channel 4183 | Channel 4233 |
| 12.2kbps RMC        | 23.1                  | 22.97        | 23.08        |
| 64kbps RMC          | 23.1                  | 22.92        | 23.08        |
| 144kbps RMC         | 23.11                 | 22.94        | 23.1         |
| 384kbps RMC         | 23.09                 | 22.98        | 23           |
| WCDMA Band V HSDPA  | Conducted Power (dBm) |              |              |
|                     | Channel 4132          | Channel 4183 | Channel 4233 |
| Sub - Test 1        | 22.95                 | 22.82        | 22.91        |
| Sub - Test 2        | 22.79                 | 22.64        | 22.83        |
| Sub - Test 3        | 22.25                 | 22.15        | 22.33        |
| Sub - Test 4        | 22.22                 | 22.14        | 22.27        |



## 7. Test Results

### 7.1. Dielectric Performance

Table 11: Dielectric Performance of Head Tissue Simulating Liquid

| Frequency         | Description                      | Dielectric Parameters  |                      | Temp<br>℃ |
|-------------------|----------------------------------|------------------------|----------------------|-----------|
|                   |                                  | $\epsilon_r$           | $\sigma(\text{s/m})$ |           |
| 835MHz<br>(head)  | Target value<br>$\pm 5\%$ window | 41.50<br>39.43 — 43.58 | 0.90<br>0.86 — 0.95  | /         |
|                   | Measurement value<br>2011-5-22   | 41.76                  | 0.90                 | 21.7      |
| 1900MHz<br>(head) | Target value<br>$\pm 5\%$ window | 40.00<br>38.00 — 42.00 | 1.40<br>1.33 — 1.47  | /         |
|                   | Measurement value<br>2011-5-24   | 39.89                  | 1.45                 | 21.8      |
| 2450MHz<br>(head) | Target value<br>$\pm 5\%$ window | 39.20<br>37.24 — 41.16 | 1.80<br>1.71 — 1.89  | /         |
|                   | Measurement value<br>2011-6-1    | 39.10                  | 1.81                 | 21.8      |

Table 12: Dielectric Performance of Body Tissue Simulating Liquid

| Frequency         | Description                      | Dielectric Parameters  |                      | Temp<br>℃ |
|-------------------|----------------------------------|------------------------|----------------------|-----------|
|                   |                                  | $\epsilon_r$           | $\sigma(\text{s/m})$ |           |
| 835MHz<br>(body)  | Target value<br>$\pm 5\%$ window | 55.20<br>52.44 — 57.96 | 0.97<br>0.92 — 1.02  | /         |
|                   | Measurement value<br>2011-5-21   | 56.25                  | 0.99                 | 21.7      |
| 1900MHz<br>(body) | Target value<br>$\pm 5\%$ window | 53.30<br>50.64 — 55.97 | 1.52<br>1.44 — 1.60  | /         |
|                   | Measurement value<br>2011-5-23   | 51.98                  | 1.56                 | 21.8      |
| 2450MHz<br>(body) | Target value<br>$\pm 5\%$ window | 52.70<br>50.07 — 55.34 | 1.95<br>1.85 — 2.05  | /         |
|                   | Measurement value<br>2011-6-1    | 51.19                  | 1.94                 | 21.9      |



## 7.2. System Check Results

Table 13: System Check for Head Tissue Simulating Liquid

| Frequency | Description                             | SAR(W/kg)           |                     | Dielectric Parameters |                | Temp |
|-----------|-----------------------------------------|---------------------|---------------------|-----------------------|----------------|------|
|           |                                         | 10g                 | 1g                  | $\epsilon_r$          | $\sigma$ (s/m) | °C   |
| 835MHz    | Recommended result<br>$\pm 10\%$ window | 1.56<br>1.40 — 1.72 | 2.39<br>2.15 — 2.63 | 41.2                  | 0.89           | /    |
|           | Measurement value<br>2011-5-22          | 1.58                | 2.40                | 41.76                 | 0.90           | 21.7 |
| 1900MHz   | Recommended result<br>$\pm 10\%$ window | 5.22<br>4.70 — 5.74 | 10<br>9.00 — 11.00  | 39.5                  | 1.44           | /    |
|           | Measurement value<br>2011-5-24          | 5.30                | 10.33               | 39.89                 | 1.45           | 21.8 |
| 2450 MHz  | Recommended result<br>$\pm 10\%$ window | 6.24<br>5.62 — 6.86 | 13.3<br>11.97—14.63 | 38.7                  | 1.77           | /    |
|           | Measurement value<br>2011-6-1           | 6.52                | 14.06               | 39.10                 | 1.81           | 21.8 |

Note: 1. The graph results see ANNEX B.


2. Recommended Values used derive from the calibration certificate and 250 mW is used as feeding power to the calibrated dipole.

Table 14: System Check for Body Tissue Simulating Liquid

| Frequency | Description                             | SAR(W/kg)           |                      | Dielectric Parameters |                | Temp |
|-----------|-----------------------------------------|---------------------|----------------------|-----------------------|----------------|------|
|           |                                         | 10g                 | 1g                   | $\epsilon_r$          | $\sigma$ (s/m) | °C   |
| 835MHz    | Recommended result<br>$\pm 10\%$ window | 1.63<br>1.47 — 1.79 | 2.49<br>2.24 — 2.74  | 54.6                  | 0.98           | /    |
|           | Measurement value<br>2011-5-21          | 1.64                | 2.54                 | 56.25                 | 0.99           | 21.7 |
| 1900 MHz  | Recommended result<br>$\pm 10\%$ window | 5.52<br>4.97 — 6.07 | 10.3<br>9.27 — 11.33 | 53.5                  | 1.54           | /    |
|           | Measurement value<br>2011-5-23          | 5.36                | 10.20                | 51.98                 | 1.56           | 21.8 |
| 2450 MHz  | Recommended result<br>$\pm 10\%$ window | 5.97<br>5.37 — 6.57 | 13<br>11.7—14.3      | 51.8                  | 2.01           | /    |
|           | Measurement value<br>2011-6-1           | 6.48                | 14.01                | 51.19                 | 1.94           | 21.9 |

Note: 1. The graph results see ANNEX B.

2. Target Values used derive from the calibration certificate and 250 mW is used as feeding power to the Calibrated dipole.



### 7.3. Summary of Measurement Results

#### 7.3.1. GSM 850 (GPRS/EGPRS)

Table 15: SAR Values [GSM 850 (GPRS/EGPRS)]

| Limit of SAR                                              |            | 10 g Average             | 1 g Average     | Power Drift      | Graph Results |
|-----------------------------------------------------------|------------|--------------------------|-----------------|------------------|---------------|
|                                                           |            | 2.0 W/kg                 | 1.6 W/kg        | ± 0.21 dB        |               |
| Different Test Position                                   | Channel    | Measurement Result(W/kg) |                 | Power Drift (dB) |               |
|                                                           |            | 10 g Average             | 1 g Average     |                  |               |
| Test Position of Head                                     |            |                          |                 |                  |               |
| Left hand, Touch Cheek                                    | Middle/190 | 0.500                    | 0.688           | -0.094           | Figure 13     |
| Left hand, Tilt 15 Degree                                 | Middle/190 | 0.235                    | 0.310           | -0.011           | Figure 14     |
| Right hand, Touch Cheek                                   | High/251   | 0.585                    | 0.786           | -0.017           | Figure 15     |
|                                                           | Middle/190 | 0.541                    | 0.729           | -0.087           | Figure 16     |
|                                                           | Low/128    | 0.558                    | 0.746           | -0.030           | Figure 17     |
| Right hand, Tilt 15 Degree                                | Middle/190 | 0.247                    | 0.328           | -0.019           | Figure 18     |
| Test position of Body (Distance 15mm)                     |            |                          |                 |                  |               |
| Towards Ground (GSM)                                      | Middle/190 | 0.359                    | 0.513           | 0.073            | Figure 19     |
| Towards Ground (2TXslots)                                 | Middle/190 | 0.465                    | 0.638           | -0.011           | Figure 20     |
| Towards Ground (3TXslots)                                 | Middle/190 | 0.490                    | 0.673           | -0.063           | Figure 21     |
| Towards Ground (4TXslots)                                 | High/251   | 0.534                    | 0.751           | -0.034           | Figure 22     |
|                                                           | Middle/190 | 0.511                    | 0.702           | -0.016           | Figure 23     |
|                                                           | Low/128    | 0.515(max.cube)          | 0.716(max.cube) | 0.010            | Figure 24     |
| Towards Phantom(4TXslots)                                 | Middle/190 | 0.439                    | 0.594           | -0.023           | Figure 25     |
| Worst Case Position of Body with Earphone (Distance 15mm) |            |                          |                 |                  |               |
| Towards Ground (GSM)                                      | High/251   | 0.436                    | 0.602           | -0.077           | Figure 26     |

Note: 1.The value with blue color is the maximum SAR Value of each test band.

2. Upper and lower frequencies were measured at the worst position.

3. The SAR test shall be performed at the high, middle and low frequency channels of each operating mode. If the SAR measured at mid-band channel for each test configuration is at least 3.0 dB lower than the SAR limit ( $< 0.8\text{W/kg}$ ), testing at the high and low channels is optional.

4. When SAR tests for EGPRS mode is necessary, GMSK modulation should be used to minimize SAR measurement error due to higher peak-to-average power (PAR) ratios inherent in 8-PSK.

5. The (max.cube) labeling indicates that during the grid scanning an additional peak was found which was within 2.0dB of the highest peak. The value of the highest cube is given in the table above.





**Table 16: SAR Values [GSM 850(wireless routers incorporated in device)]**

| Limit of SAR                                                 |            | 10 g Average             | 1 g Average     | Power      | Graph Results |
|--------------------------------------------------------------|------------|--------------------------|-----------------|------------|---------------|
|                                                              |            | 2.0 W/kg                 | 1.6 W/kg        | ± 0.21 dB  |               |
| Different Test Position                                      | Channel    | Measurement Result(W/kg) |                 | Power      |               |
|                                                              |            | 10 g Average             | 1 g Average     | Drift (dB) |               |
| Test position of Body (Distance 10mm)                        |            |                          |                 |            |               |
| Towards Ground(4TXslots)                                     | High/251   | 0.710(max.cube)          | 0.984(max.cube) | -0.052     | Figure 27     |
|                                                              | Middle/190 | 0.716                    | 1.020           | -0.065     | Figure 28     |
|                                                              | Low/128    | 0.697(max.cube)          | 1.030(max.cube) | -0.064     | Figure 29     |
| Towards Phantom (4TXslots)                                   | Middle/190 | 0.567                    | 0.768           | 0.003      | Figure 30     |
| Left Edge(4TXslots)                                          | Middle/190 | 0.317                    | 0.461           | -0.006     | Figure 31     |
| Right Edge(4TXslots)                                         | Middle/190 | 0.381                    | 0.549           | -0.033     | Figure 32     |
| Top Edge(4TXslots)                                           | N/A        | N/A                      | N/A             | N/A        | N/A           |
| Bottom Edge(4TXslots)                                        | Middle/190 | 0.078                    | 0.146           | -0.039     | Figure 33     |
| Worst Case Position of Body with EGPRS (GMSK, Distance 10mm) |            |                          |                 |            |               |
| Towards Ground(4TXslots)                                     | Low/128    | 0.734(max.cube)          | 1.010(max.cube) | -0.018     | Figure 34     |

Note: 1. The value with blue color is the maximum SAR Value of each test band.

2. Upper and lower frequencies were measured at the worst position.
3. WWAN antenna is located at bottom edge; antenna-to-top edge distance is more than 2.5 cm(see ANNEX I). Based upon KDB941225 D06, when the antenna-to-edge distance is greater than 2.5cm, such position does not need to be tested. Top Edge is excluded from hotspot mode SAR evaluation.
4. The (max.cube) labeling indicates that during the grid scanning an additional peak was found which was within 2.0dB of the highest peak. The value of the highest cube is given in the table above.



### 7.3.2. GSM 1900 (GPRS/EGPRS)

Table 17: SAR Values [GSM 1900(GPRS/EGPRS)]

| Limit of SAR                                              |            | 10 g Average             | 1 g Average     | Power Drift      | Graph Results |
|-----------------------------------------------------------|------------|--------------------------|-----------------|------------------|---------------|
|                                                           |            | 2.0 W/kg                 | 1.6 W/kg        | ± 0.21 dB        |               |
| Different Test Position                                   | Channel    | Measurement Result(W/kg) |                 | Power Drift (dB) |               |
|                                                           |            | 10 g Average             | 1 g Average     |                  |               |
| Test Position of Head                                     |            |                          |                 |                  |               |
| Left hand, Touch cheek                                    | High/810   | 0.252                    | 0.427           | 0.171            | Figure 35     |
|                                                           | Middle/661 | 0.245                    | 0.416           | 0.024            | Figure 36     |
|                                                           | Low/512    | 0.294                    | 0.496           | -0.044           | Figure 37     |
| Left hand, Tilt 15 Degree                                 | Middle/661 | 0.111                    | 0.176           | -0.058           | Figure 38     |
| Right hand, Touch cheek                                   | Middle/661 | 0.240(max.cube)          | 0.375(max.cube) | -0.062           | Figure 39     |
| Right hand, Tilt 15 Degree                                | Middle/661 | 0.115                    | 0.184           | -0.006           | Figure 40     |
| Test position of Body (Distance 15mm)                     |            |                          |                 |                  |               |
| Towards Ground (GSM)                                      | Middle/661 | 0.137                    | 0.233           | -0.046           | Figure 41     |
| Towards Ground (2TXslots)                                 | Middle/661 | 0.198                    | 0.335           | -0.034           | Figure 42     |
| Towards Ground (3TXslots)                                 | Middle/661 | 0.213                    | 0.358           | -0.022           | Figure 43     |
| Towards Ground (4TXslots)                                 | High/810   | 0.229                    | 0.390           | 0.003            | Figure 44     |
|                                                           | Middle/661 | 0.228                    | 0.387           | 0.030            | Figure 45     |
|                                                           | Low/512    | 0.270                    | 0.458           | -0.044           | Figure 46     |
| Towards Phantom (4TXslots)                                | Middle/661 | 0.168(max.cube)          | 0.297(max.cube) | -0.116           | Figure 47     |
| Worst Case Position of Body with Earphone (Distance 15mm) |            |                          |                 |                  |               |
| Towards Ground (GSM)                                      | Low/512    | 0.128                    | 0.215           | 0.015            | Figure 48     |

Note: 1.The value with blue color is the maximum SAR Value of each test band.

2. Upper and lower frequencies were measured at the worst position.

3. The SAR test shall be performed at the high, middle and low frequency channels of each operating mode. If the SAR measured at mid-band channel for each test configuration is at least 3.0 dB lower than the SAR limit (< 0.8W/kg), testing at the high and low channels is optional.

4. When SAR tests for EGPRS mode is necessary, GMSK modulation should be used to minimize SAR measurement error due to higher peak-to-average power (PAR) ratios inherent in 8-PSK.

5. The (max.cube) labeling indicates that during the grid scanning an additional peak was found which was within 2.0dB of the highest peak. The value of the highest cube is given in the table above.




Table 18: SAR Values [GSM 1900(wireless routers incorporated in device)]

| Limit of SAR                                                |            | 10 g Average             | 1 g Average | Power      | Graph Results |
|-------------------------------------------------------------|------------|--------------------------|-------------|------------|---------------|
|                                                             |            | 2.0 W/kg                 | 1.6 W/kg    | ± 0.21 dB  |               |
| Different Test Position                                     | Channel    | Measurement Result(W/kg) |             | Power      |               |
|                                                             |            | 10 g Average             | 1 g Average | Drift (dB) |               |
| Test position of Body (Distance 10mm)                       |            |                          |             |            |               |
| Towards Ground (4TXslots)                                   | High/810   | 0.365                    | 0.643       | -0.026     | Figure 49     |
|                                                             | Middle/661 | 0.358                    | 0.630       | -0.045     | Figure 50     |
|                                                             | Low/512    | 0.422                    | 0.736       | 0.036      | Figure 51     |
| Towards Phantom (4TXslots)                                  | Middle/661 | 0.255                    | 0.453       | -0.087     | Figure 52     |
| Left Edge(4TXslots)                                         | Middle/661 | 0.124                    | 0.217       | -0.053     | Figure 53     |
| Right Edge(4TXslots)                                        | Middle/661 | 0.096                    | 0.173       | -0.042     | Figure 54     |
| Top Edge(4TXslots)                                          | N/A        | N/A                      | N/A         | N/A        | N/A           |
| Bottom Edge(4TXslots)                                       | Middle/661 | 0.192                    | 0.342       | -0.114     | Figure 55     |
| Worst Case Position of Body with EGPRS(GMSK, Distance 10mm) |            |                          |             |            |               |
| Towards Ground (4TXslots)                                   | Low/512    | 0.421                    | 0.736       | 0.015      | Figure 56     |

Note: 1.The value with blue color is the maximum SAR Value of each test band.

2. Upper and lower frequencies were measured at the worst position.

3. WWAN antenna is located at bottom edge; antenna-to-top edge distance is more than 2.5 cm(see ANNEX I). Based upon KDB941225 D06, when the antenna-to-edge distance is greater than 2.5cm, such position does not need to be tested. Top Edge is excluded from hotspot mode SAR evaluation..



### 7.3.3. WCDMA Band II (WCDMA/HSDPA)

Table 19: SAR Values [WCDMA Band II (WCDMA/HSDPA)]

| Limit of SAR                                              |             | 10 g Average             | 1 g Average     | Power Drift | Graph Results |
|-----------------------------------------------------------|-------------|--------------------------|-----------------|-------------|---------------|
|                                                           |             | 2.0 W/kg                 | 1.6 W/kg        | ± 0.21 dB   |               |
| Different Test Position                                   | Channel     | Measurement Result(W/kg) |                 | Power Drift |               |
|                                                           |             | 10 g Average             | 1 g Average     | (dB)        |               |
| Test Position of Head                                     |             |                          |                 |             |               |
| Left Hand, Touch Cheek                                    | High/9538   | 0.535                    | 0.901           | 0.000       | Figure 57     |
|                                                           | Middle/9400 | 0.535                    | 0.909           | 0.063       | Figure 58     |
|                                                           | Low/9262    | 0.571                    | 0.957           | 0.073       | Figure 59     |
| Left Hand, Tilt 15 Degree                                 | Middle/9400 | 0.252                    | 0.396           | -0.124      | Figure 60     |
| Right Hand, Touch Cheek                                   | High/9538   | 0.492(max.cube)          | 0.780(max.cube) | -0.079      | Figure 61     |
|                                                           | Middle/9400 | 0.554(max.cube)          | 0.877(max.cube) | -0.034      | Figure 62     |
|                                                           | Low/9262    | 0.573(max.cube)          | 0.892(max.cube) | 0.025       | Figure 63     |
| Right Hand, Tilt 15 Degree                                | Middle/9400 | 0.236                    | 0.375           | 0.033       | Figure 64     |
| Test Position of Body (Distance 15mm)                     |             |                          |                 |             |               |
| Towards Ground                                            | High/9538   | 0.296                    | 0.502           | 0.045       | Figure 65     |
|                                                           | Middle/9400 | 0.298                    | 0.509           | -0.024      | Figure 66     |
|                                                           | Low/9262    | 0.320                    | 0.544           | -0.055      | Figure 67     |
| Towards Phantom                                           | Middle/9400 | 0.221(max.cube)          | 0.383(max.cube) | 0.058       | Figure 68     |
| Worst Case Position of Body with Earphone (Distance 15mm) |             |                          |                 |             |               |
| Towards Ground                                            | Low/9262    | 0.241                    | 0.402           | 0.080       | Figure 69     |

Note: 1. The value with blue color is the maximum SAR Value of each test band.

2. Upper and lower frequencies were measured at the worst position.

3. The SAR test shall be performed at the high, middle and low frequency channels of each operating mode. If the SAR measured at mid-band channel for each test configuration is at least 3.0 dB lower than the SAR limit (< 0.8W/kg), testing at the high and low channels is optional.

4. The (max.cube) labeling indicates that during the grid scanning an additional peak was found which was within 2.0dB of the highest peak. The value of the highest cube is given in the table above.



Table 20: SAR Values [WCDMA Band II (wireless routers incorporated in device)]

| Limit of SAR                                           |             | 10 g Average             | 1 g Average     | Power      | Graph Results |
|--------------------------------------------------------|-------------|--------------------------|-----------------|------------|---------------|
|                                                        |             | 2.0 W/kg                 | 1.6 W/kg        | ± 0.21     |               |
| Different Test Position                                | Channel     | Measurement Result(W/kg) |                 | Power      |               |
|                                                        |             | 10 g Average             | 1 g Average     | Drift (dB) |               |
| Test position of Body (Distance 10mm)                  |             |                          |                 |            |               |
| Towards Ground                                         | High/9538   | 0.536                    | 0.938           | 0.046      | Figure 70     |
|                                                        | Middle/9400 | 0.547                    | 0.955           | 0.048      | Figure 71     |
|                                                        | Low/9262    | 0.554                    | 0.965           | 0.058      | Figure 72     |
| Towards Phantom                                        | Middle/9400 | 0.345(max.cube)          | 0.612(max.cube) | 0.056      | Figure 73     |
| Left Edge                                              | Middle/9400 | 0.164                    | 0.286           | 0.025      | Figure 74     |
| Right Edge                                             | Middle/9400 | 0.125                    | 0.214           | 0.030      | Figure 75     |
| Top Edge                                               | N/A         | N/A                      | N/A             | N/A        | N/A           |
| Bottom Edge                                            | Middle/9400 | 0.233                    | 0.411           | 0.070      | Figure 76     |
| Worst Case Position of Body with HSDPA (Distance 10mm) |             |                          |                 |            |               |
| Towards Ground                                         | Low/9262    | 0.364                    | 0.637           | 0.150      | Figure 77     |

Note: 1.The value with blue color is the maximum SAR Value of each test band.

- Upper and lower frequencies were measured at the worst position.
- WWAN antenna is located at bottom edge; antenna-to-top edge distance is more than 2.5 cm(see ANNEX I). Based upon KDB941225 D06, when the antenna-to-edge distance is greater than 2.5cm, such position does not need to be tested. Top Edge is excluded from hotspot mode SAR evaluation.
- The (max.cube) labeling indicates that during the grid scanning an additional peak was found which was within 2.0dB of the highest peak. The value of the highest cube is given in the table above.



#### 7.3.4. WCDMA Band V (WCDMA/HSDPA)

Table 21: SAR Values [WCDMA Band V (WCDMA/HSDPA)]

| Limit of SAR                                              |             | 10 g Average             | 1 g Average | Power Drift      | Graph Results |
|-----------------------------------------------------------|-------------|--------------------------|-------------|------------------|---------------|
|                                                           |             | 2.0 W/kg                 | 1.6 W/kg    | ± 0.21 dB        |               |
| Different Test Position                                   | Channel     | Measurement Result(W/kg) |             | Power Drift (dB) |               |
|                                                           |             | 10 g Average             | 1 g Average |                  |               |
| Test Position of Head                                     |             |                          |             |                  |               |
| Left Hand, Touch Cheek                                    | Middle/4183 | 0.456                    | 0.620       | -0.030           | Figure 78     |
| Left Hand, Tilt 15 Degree                                 | Middle/4183 | 0.265                    | 0.350       | 0.047            | Figure 79     |
| Right Hand, Touch Cheek                                   | High/4233   | 0.639                    | 0.864       | 0.089            | Figure 80     |
|                                                           | Middle/4183 | 0.642                    | 0.863       | -0.106           | Figure 81     |
|                                                           | Low/4132    | 0.580                    | 0.779       | -0.014           | Figure 82     |
| Right Hand, Tilt 15 Degree                                | Middle/4183 | 0.301                    | 0.398       | 0.015            | Figure 83     |
| Test Position of Body (Distance 15mm)                     |             |                          |             |                  |               |
| Towards Ground                                            | High/4233   | 0.476                    | 0.657       | -0.022           | Figure 84     |
|                                                           | Middle/4183 | 0.537                    | 0.741       | 0.084            | Figure 85     |
|                                                           | Low/4132    | 0.448                    | 0.616       | -0.026           | Figure 86     |
| Towards Phantom                                           | Middle/4183 | 0.417                    | 0.566       | -0.020           | Figure 87     |
| Worst Case Position of Body with Earphone (Distance 15mm) |             |                          |             |                  |               |
| Towards Ground                                            | Middle/4183 | 0.521                    | 0.711       | -0.004           | Figure 88     |

Note: 1. The value with blue color is the maximum SAR Value of each test band.

- Upper and lower frequencies were measured at the worst position.
- The SAR test shall be performed at the high, middle and low frequency channels of each operating mode. If the SAR measured at mid-band channel for each test configuration is at least 3.0 dB lower than the SAR limit ( $< 0.8\text{W/kg}$ ), testing at the high and low channels is optional.



Table 22: SAR Values [WCDMA Band V (wireless routers incorporated in device)]

| Limit of SAR                                           |             | 10 g Average             | 1 g Average     | Power      | Graph Results |
|--------------------------------------------------------|-------------|--------------------------|-----------------|------------|---------------|
|                                                        |             | 2.0 W/kg                 | 1.6 W/kg        | ± 0.21     |               |
| Different Test Position                                | Channel     | Measurement Result(W/kg) |                 | Power      |               |
|                                                        |             | 10 g Average             | 1 g Average     | Drift (dB) |               |
| Test position of Body (Distance 10mm)                  |             |                          |                 |            |               |
| Towards Ground                                         | High/4233   | 0.510(max.cube)          | 0.795(max.cube) | 0.044      | Figure 89     |
|                                                        | Middle/4183 | 0.660(max.cube)          | 0.918(max.cube) | -0.015     | Figure 90     |
|                                                        | Low/4132    | 0.562(max.cube)          | 0.781(max.cube) | 0.027      | Figure 91     |
| Towards Phantom                                        | Middle/4183 | 0.578                    | 0.780           | -0.015     | Figure 92     |
| Left Edge                                              | Middle/4183 | 0.301                    | 0.438           | 0.014      | Figure 93     |
| Right Edge                                             | Middle/4183 | 0.347                    | 0.497           | 0.001      | Figure 94     |
| Top Edge                                               | N/A         | N/A                      | N/A             | N/A        | N/A           |
| Bottom Edge                                            | Middle/4183 | 0.061                    | 0.112           | -0.083     | Figure 95     |
| Worst Case Position of Body with HSDPA (Distance 10mm) |             |                          |                 |            |               |
| Towards Ground                                         | Middle/4183 | 0.498                    | 0.689           | -0.009     | Figure 96     |


Note: 1.The value with blue color is the maximum SAR Value of each test band.

- Upper and lower frequencies were measured at the worst position.
- WWAN antenna is located at bottom edge; antenna-to-top edge distance is more than 2.5 cm(see ANNEX I). Based upon KDB941225 D06, when the antenna-to-edge distance is greater than 2.5cm, such position does not need to be tested. Top Edge is excluded from hotspot mode SAR evaluation.
- The (max.cube) labeling indicates that during the grid scanning an additional peak was found which was within 2.0dB of the highest peak. The value of the highest cube is given in the table above.



### 7.3.5. Bluetooth/WiFi Function

The distance between BT/WIFI antenna and GSM/WCDMA antenna is  $>5\text{cm}$ . The location of the antennas inside mobile phone is shown in Annex I:



The output power of BT antenna is as following:

| Channel            | Ch 0<br>2402 MHz | Ch 39<br>2441 MHz | Ch 78<br>2480 MHz |
|--------------------|------------------|-------------------|-------------------|
| GFSK(dBm)          | 6.14             | 7.33              | 8.41              |
| EDR2M-4_DQPSK(dBm) | 6.73             | 8.15              | 8.91              |
| EDR3M-8DPSK(dBm)   | 4.39             | 5.79              | 6.70              |

The output power of WIFI antenna is as following:

| Mode    | Channel | Data rate<br>(Mbps) | AV Power (dBm) |
|---------|---------|---------------------|----------------|
| 802.11b | 1       | 1                   | 15.62          |
|         |         | 2                   | 15.69          |
|         |         | 5.5                 | 15.29          |
|         |         | 11                  | 14.80          |
|         | 6       | 1                   | 15.55          |
|         |         | 2                   | 15.70          |
|         |         | 5.5                 | 15.37          |
|         |         | 11                  | 14.87          |
|         | 11      | 1                   | 16.10          |
|         |         | 2                   | 16.23          |
|         |         | 5.5                 | 15.82          |





TA Technology (Shanghai) Co., Ltd.  
Test Report

Report No.: RZA1105-0800SAR

Page 41 of 226

|              |    |      |       |
|--------------|----|------|-------|
| 802.11g      | 1  | 11   | 15.95 |
|              |    | 6    | 13.19 |
|              |    | 9    | 12.91 |
|              |    | 12   | 12.73 |
|              |    | 18   | 12.22 |
|              |    | 24   | 11.82 |
|              |    | 36   | 11.10 |
|              |    | 48   | 10.60 |
|              |    | 54   | 10.39 |
|              | 6  | 6    | 13.40 |
|              |    | 9    | 13.11 |
|              |    | 12   | 12.88 |
|              |    | 18   | 12.36 |
|              |    | 24   | 11.90 |
|              |    | 36   | 11.30 |
|              |    | 48   | 10.57 |
|              |    | 54   | 10.38 |
|              | 11 | 6    | 13.92 |
|              |    | 9    | 13.38 |
|              |    | 12   | 13.23 |
|              |    | 18   | 12.80 |
|              |    | 24   | 12.33 |
|              |    | 36   | 11.61 |
|              |    | 48   | 11.03 |
|              |    | 54   | 10.90 |
| 802.11n HT20 | 1  | MCS0 | 13.22 |
|              |    | MCS1 | 12.56 |
|              |    | MCS2 | 11.90 |
|              |    | MCS3 | 11.68 |
|              |    | MCS4 | 10.97 |
|              |    | MCS5 | 10.31 |
|              |    | MCS6 | 10.10 |
|              |    | MCS7 | 9.92  |
|              | 6  | MCS0 | 13.11 |
|              |    | MCS1 | 12.63 |
|              |    | MCS2 | 12.00 |
|              |    | MCS3 | 11.63 |
|              |    | MCS4 | 10.90 |
|              |    | MCS5 | 10.45 |
|              |    | MCS6 | 10.27 |
|              |    | MCS7 | 9.98  |
|              | 11 | MCS0 | 13.40 |
|              |    | MCS1 | 12.91 |



|  |  |      |       |
|--|--|------|-------|
|  |  | MCS2 | 12.40 |
|  |  | MCS3 | 12.06 |
|  |  | MCS4 | 11.35 |
|  |  | MCS5 | 10.86 |
|  |  | MCS6 | 10.50 |
|  |  | MCS7 | 10.39 |

Note: 1. KDB 248227-SAR is not required for 802.11g/n channels when the maximum average output power is less than ¼ dB higher than measured on the corresponding 802.11b channels.

#### Output Power Thresholds for Unlicensed Transmitters

|                                                                                                         | 2.45 | 5.15 - 5.35 | 5.47 - 5.85 | GHz |
|---------------------------------------------------------------------------------------------------------|------|-------------|-------------|-----|
| P <sub>Ref</sub>                                                                                        | 12   | 6           | 5           | mW  |
| Device output power should be rounded to the nearest mW to compare with values specified in this table. |      |             |             |     |

#### Stand-alone SAR

According to the output power measurement result and the distance between BT/WIFI antenna and GSM/WCDMA antenna we can draw the conclusion that:

stand-alone SAR are not required for BT, because the output power of BT transmitter is  $\leq 2P_{Ref}=13.8\text{dBm}$  and its antenna is  $>5\text{cm}$  from GSM/WCDMA antenna.

stand-alone SAR are required for WIFI, because the output power of WIFI transmitter is  $\geq 2P_{Ref}=13.8\text{dBm}$  and its antenna is  $>5\text{cm}$  from other antenna.



Table 23: SAR Values (802.11b)

| Limit of SAR (W/kg)                                      |          | 10 g Average             | 1g Average | Power Drift (dB) | Graph Results |
|----------------------------------------------------------|----------|--------------------------|------------|------------------|---------------|
|                                                          |          | 2.0                      | 1.6        | ± 0.21           |               |
| Different Test Position                                  | Channel  | Measurement Result(W/kg) |            | Power Drift (dB) |               |
|                                                          |          | 10 g Average             | 1g Average |                  |               |
| Test position of Head                                    |          |                          |            |                  |               |
| Left hand, Touch cheek                                   | Middle/6 | 0.083                    | 0.165      | -0.046           | Figure 97     |
| Left hand, Tilt 15 Degree                                | Middle/6 | 0.082                    | 0.165      | 0.107            | Figure 98     |
| Right hand, Touch cheek                                  | High/11  | 0.152                    | 0.327      | 0.000            | Figure 99     |
|                                                          | Middle/6 | 0.168                    | 0.363      | 0.050            | Figure 100    |
|                                                          | Low/1    | 0.150                    | 0.321      | 0.156            | Figure 101    |
| Right hand, Tilt 15 Degree                               | Middle/6 | 0.122                    | 0.260      | 0.115            | Figure 102    |
| Test position of Body (Distance 15mm)                    |          |                          |            |                  |               |
| Towards Ground                                           | High/11  | 0.047                    | 0.088      | 0.121            | Figure 103    |
|                                                          | Middle/6 | 0.048                    | 0.094      | -0.141           | Figure 104    |
|                                                          | Low/1    | 0.045                    | 0.083      | 0.056            | Figure 105    |
| Towards phantom                                          | Middle/6 | 0.021                    | 0.037      | 0.080            | Figure 106    |
| Worst case position of Body with Earphone(Distance 15mm) |          |                          |            |                  |               |
| Towards Ground                                           | Middle/6 | 0.019                    | 0.035      | -0.096           | Figure 107    |

Note: 1. The value with blue color is the maximum SAR Value of each test band.

- Upper and lower frequencies were measured at the worst position.
- The SAR test shall be performed at the high, middle and low frequency channels of each operating mode. If the SAR measured at mid-band channel for each test configuration is at least 3.0 dB lower than the SAR limit ( $< 0.8\text{W/kg}$ ), testing at the high and low channels is optional.
- KDB 248227-SAR is not required for 802.11g/n channels when the maximum average output power is less than  $\frac{1}{4}$  dB higher than measured on the corresponding 802.11b channels.



Table 24: SAR Values [802.11b (wireless routers incorporated in device)]

| Limit of SAR                          |          | 10 g Average             | 1 g Average | Power            | Graph Results |
|---------------------------------------|----------|--------------------------|-------------|------------------|---------------|
|                                       |          | 2.0 W/kg                 | 1.6 W/kg    | ± 0.21 dB        |               |
| Different Test Position               | Channel  | Measurement Result(W/kg) |             | Power Drift (dB) |               |
|                                       |          | 10 g Average             | 1 g Average |                  |               |
| Test position of Body (Distance 10mm) |          |                          |             |                  |               |
| Towards Ground                        | High/11  | 0.080                    | 0.157       | 0.146            | Figure 108    |
|                                       | Middle/6 | 0.081                    | 0.155       | 0.066            | Figure 109    |
|                                       | Low/1    | 0.091                    | 0.173       | 0.182            | Figure 110    |
| Towards Phantom                       | Middle/6 | 0.033                    | 0.061       | -0.007           | Figure 111    |
| Left Edge                             | Middle/6 | 0.026                    | 0.048       | 0.141            | Figure 112    |
| Right Edge                            | Middle/6 | 0.008                    | 0.014       | -0.142           | Figure 113    |
| Top Edge                              | Middle/6 | 0.036                    | 0.069       | -0.051           | Figure 114    |
| Bottom Edge                           | N/A      | N/A                      | N/A         | N/A              | N/A           |

Note: 1.The value with blue color is the maximum SAR Value of each test band.

- Upper and lower frequencies were measured at the worst position.
- WLAN antenna is located at Left edge; antenna-to-bottom edge distance is more than 2.5 cm(see ANNEX I). Based upon KDB941225 D06, when the antenna-to-edge distance is greater than 2.5cm, such position does not need to be tested. Bottom Edge is excluded from hotspot mode SAR evaluation.
- KDB 248227-SAR is not required for 802.11g/n channels when the maximum average output power is less than ¼ dB higher than measured on the corresponding 802.11b channels.

### Simultaneous SAR

About BT and GSM/WCDMA Antenna, because GSM/WCDMA antenna is >5cm from BT Antenna, stand-alone SAR are not required for BT, so Simultaneous SAR are not required for GSM/WCDMA and BT Antenna.

About WIFI and GSM/WCDMA Antenna, because GSM/WCDMA antenna is >5cm from WIFI Antenna, Max (SAR<sub>GSM/WCDMA</sub>+ SAR<sub>WIFI</sub>)= 0.892W/kg +0.363 W/kg =1.255 W/kg <1.6 W/kg, so Simultaneous SAR are not required for GSM/WCDMA and WIFI Antenna.

About BT and WiFi can't simultaneous transmit.



## 8. Measurement Uncertainty

| No.                 | source                                                                           | Type | Uncertainty Value (%) | Probability Distribution | k          | c <sub>i</sub> | Standard ncertainty u <sub>i</sub> (%) | Degree of freedom V <sub>eff</sub> or v <sub>i</sub> |
|---------------------|----------------------------------------------------------------------------------|------|-----------------------|--------------------------|------------|----------------|----------------------------------------|------------------------------------------------------|
| 1                   | System repetivity                                                                | A    | 0.5                   | N                        | 1          | 1              | 0.5                                    | 9                                                    |
| Measurement system  |                                                                                  |      |                       |                          |            |                |                                        |                                                      |
| 2                   | -probe calibration                                                               | B    | 5.9                   | N                        | 1          | 1              | 5.9                                    | ∞                                                    |
| 3                   | -axial isotropy of the probe                                                     | B    | 4.7                   | R                        | $\sqrt{3}$ | $\sqrt{0.5}$   | 1.9                                    | ∞                                                    |
| 4                   | - Hemispherical isotropy of the probe                                            | B    | 9.4                   | R                        | $\sqrt{3}$ | $\sqrt{0.5}$   | 3.9                                    | ∞                                                    |
| 6                   | -boundary effect                                                                 | B    | 1.9                   | R                        | $\sqrt{3}$ | 1              | 1.1                                    | ∞                                                    |
| 7                   | -probe linearity                                                                 | B    | 4.7                   | R                        | $\sqrt{3}$ | 1              | 2.7                                    | ∞                                                    |
| 8                   | - System detection limits                                                        | B    | 1.0                   | R                        | $\sqrt{3}$ | 1              | 0.6                                    | ∞                                                    |
| 9                   | -readout Electronics                                                             | B    | 1.0                   | N                        | 1          | 1              | 1.0                                    | ∞                                                    |
| 10                  | -response time                                                                   | B    | 0                     | R                        | $\sqrt{3}$ | 1              | 0                                      | ∞                                                    |
| 11                  | -integration time                                                                | B    | 4.32                  | R                        | $\sqrt{3}$ | 1              | 2.5                                    | ∞                                                    |
| 12                  | -noise                                                                           | B    | 0                     | R                        | $\sqrt{3}$ | 1              | 0                                      | ∞                                                    |
| 13                  | -RF Ambient Conditions                                                           | B    | 3                     | R                        | $\sqrt{3}$ | 1              | 1.73                                   | ∞                                                    |
| 14                  | -Probe Positioner Mechanical Tolerance                                           | B    | 0.4                   | R                        | $\sqrt{3}$ | 1              | 0.2                                    | ∞                                                    |
| 15                  | -Probe Positioning with respect to Phantom Shell                                 | B    | 2.9                   | R                        | $\sqrt{3}$ | 1              | 1.7                                    | ∞                                                    |
| 16                  | -Extrapolation, interpolation and Integration Algorithms for Max. SAR Evaluation | B    | 3.9                   | R                        | $\sqrt{3}$ | 1              | 2.3                                    | ∞                                                    |
| Test sample Related |                                                                                  |      |                       |                          |            |                |                                        |                                                      |
| 17                  | -Test Sample Positioning                                                         | A    | 2.9                   | N                        | 1          | 1              | 4.92                                   | 71                                                   |
| 18                  | -Device Holder Uncertainty                                                       | A    | 4.1                   | N                        | 1          | 1              | 4.1                                    | 5                                                    |
| 19                  | -Output Power Variation - SAR drift measurement                                  | B    | 5.0                   | R                        | $\sqrt{3}$ | 1              | 2.9                                    | ∞                                                    |
| Physical parameter  |                                                                                  |      |                       |                          |            |                |                                        |                                                      |
| 20                  | -phantom                                                                         | B    | 4.0                   | R                        | $\sqrt{3}$ | 1              | 2.3                                    | ∞                                                    |



# TA Technology (Shanghai) Co., Ltd. Test Report

Report No.: RZA1105-0800SAR

Page 46 of 226

|                                                    |                                                |                                             |      |   |            |      |       |          |
|----------------------------------------------------|------------------------------------------------|---------------------------------------------|------|---|------------|------|-------|----------|
| 21                                                 | -liquid conductivity (deviation from target)   | B                                           | 5.0  | R | $\sqrt{3}$ | 0.64 | 1.8   | $\infty$ |
| 22                                                 | -liquid conductivity (measurement uncertainty) | B                                           | 0.77 | N | 1          | 0.64 | 0.493 | 9        |
| 23                                                 | -liquid permittivity (deviation from target)   | B                                           | 5.0  | R | $\sqrt{3}$ | 0.6  | 1.7   | $\infty$ |
| 24                                                 | -liquid permittivity (measurement uncertainty) | B                                           | 0.29 | N | 1          | 0.6  | 0.174 | 9        |
| Combined standard uncertainty                      |                                                | $u_c' = \sqrt{\sum_{i=1}^{21} c_i^2 u_i^2}$ |      |   |            |      | 11.36 |          |
| Expanded uncertainty (confidence interval of 95 %) |                                                | $u_e = 2u_c$                                |      | N | k=2        |      | 22.72 |          |



## 9. Main Test Instruments


Table 25: List of Main Instruments

| No. | Name                   | Type           | Serial Number | Calibration Date         | Valid Period |
|-----|------------------------|----------------|---------------|--------------------------|--------------|
| 01  | Network analyzer       | Agilent 8753E  | US37390326    | September 13, 2010       | One year     |
| 02  | Dielectric Probe Kit   | Agilent 85070E | US44020115    | No Calibration Requested |              |
| 03  | Power meter            | Agilent E4417A | GB41291714    | March 12, 2011           | One year     |
| 04  | Power sensor           | Agilent N8481H | MY50350004    | September 26, 2010       | One year     |
| 05  | Signal Generator       | HP 8341B       | 2730A00804    | September 13, 2010       | One year     |
| 06  | Amplifier              | IXA-020        | 0401          | No Calibration Requested |              |
| 07  | BTS                    | E5515C         | MY48360988    | December 3, 2010         | One year     |
| 08  | E-field Probe          | EX3DV4         | 3677          | November 24, 2010        | One year     |
| 09  | DAE                    | DAE4           | 871           | November 18, 2010        | One year     |
| 10  | Validation Kit 835MHz  | D835V2         | 4d092         | January 14, 2010         | Two years    |
| 11  | Validation Kit 1900MHz | D1900V2        | 5d018         | June 15, 2010            | Two years    |
| 12  | Validation Kit 2450MHz | D2450V2        | 712           | February 19, 2010        | Two years    |

\*\*\*\*\*END OF REPORT BODY\*\*\*\*\*



## ANNEX A: Test Layout




Picture 1: Specific Absorption Rate Test Layout






Picture 2: Liquid depth in the flat Phantom (835MHz, 15.4cm depth)




Picture 3: Liquid depth in the head Phantom (835MHz, 15.3cm depth)



Picture 4: Liquid depth in the flat Phantom (1900 MHz, 15.2cm depth)



Picture 5: liquid depth in the head Phantom (1900 MHz, 15.3cm depth)



Picture 6: Liquid depth in the flat Phantom (2450 MHz, 15.3cm depth)



Picture 7: Liquid depth in the head Phantom (2450 MHz, 15.4cm depth)



## ANNEX B: System Check Results

### System Performance Check at 835 MHz Head TSL

**DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 4d092**

Date/Time: 5/22/2011 6:45:13 PM

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 835 \text{ MHz}$ ;  $\sigma = 0.90 \text{ mho/m}$ ;  $\epsilon_r = 41.76$ ;  $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature:  $22.3^\circ\text{C}$       Liquid Temperature:  $21.7^\circ\text{C}$

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(9.5, 9.5, 9.5); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**d=15mm, Pin=250mW/Area Scan (101x121x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

Maximum value of SAR (interpolated) =  $2.56 \text{ mW/g}$

**d=15mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $51.1 \text{ V/m}$ ; Power Drift =  $-0.037 \text{ dB}$

Peak SAR (extrapolated) =  $3.54 \text{ W/kg}$

**SAR(1 g) =  $2.40 \text{ mW/g}$ ; SAR(10 g) =  $1.58 \text{ mW/g}$**

Maximum value of SAR (measured) =  $2.63 \text{ mW/g}$




Figure 7 System Performance Check 835MHz 250mW



### System Performance Check at 835 MHz Body TSL

**DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 4d092**

Date/Time: 5/21/2011 8:34:20 AM

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 835 \text{ MHz}$ ;  $\sigma = 0.99 \text{ mho/m}$ ;  $\epsilon_r = 56.25$ ;  $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature:  $22.3^\circ\text{C}$       Liquid Temperature:  $21.7^\circ\text{C}$

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(10.33, 10.33, 10.33); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**d=15mm, Pin=250mW/Area Scan (61x121x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) =  $2.72 \text{ mW/g}$

**d=15mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value =  $50.9 \text{ V/m}$ ; Power Drift =  $0.023 \text{ dB}$

Peak SAR (extrapolated) =  $3.63 \text{ W/kg}$

**SAR(1 g) =  $2.54 \text{ mW/g}$ ; SAR(10 g) =  $1.64 \text{ mW/g}$**

Maximum value of SAR (measured) =  $2.72 \text{ mW/g}$




Figure 8 System Performance Check 835MHz 250mW



### System Performance Check at 1900 MHz Head TSL

**DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN: 5d018**

Date/Time: 5/24/2011 2:01:34 PM

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.45$  mho/m;  $\epsilon_r = 39.89$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.8 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.94, 7.94, 7.94); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**d=10mm, Pin=250mW/Area Scan (51x81x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 12.7 mW/g

**d=10mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 81.0 V/m; Power Drift = -0.068 dB

Peak SAR (extrapolated) = 18.9 W/kg

**SAR(1 g) = 10.33 mW/g; SAR(10 g) = 5.30 mW/g**

Maximum value of SAR (measured) = 11.53 mW/g




Figure 9 System Performance Check 1900MHz 250mW



### System Performance Check at 1900 MHz Body TSL

**DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN: 5d018**

Date/Time: 5/23/2011 8:36:19 AM

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.56$  mho/m;  $\epsilon_r = 51.98$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.8 °C

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.77, 7.77, 7.77); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**d=10mm, Pin=250mW/Area Scan (41x71x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 11.9 mW/g

**d=10mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 80.8 V/m; Power Drift = -0.063 dB

Peak SAR (extrapolated) = 17.6 W/kg

**SAR(1 g) = 10.20 mW/g; SAR(10 g) = 5.36 mW/g**

Maximum value of SAR (measured) = 11.05 mW/g




Figure 10 System Performance Check 1900MHz 250mW





### System Performance Check at 2450 MHz Head TSL

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN: 712**

Date/Time: 6/1/2011 4:51:36 PM

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.81$  mho/m;  $\epsilon_r = 39.10$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.8 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.32, 7.32, 7.32); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**d=10mm, Pin=250mW/Area Scan (61x101x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 21.4 mW/g

**d=10mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 67.0 V/m; Power Drift = 0.010 dB

Peak SAR (extrapolated) = 28.0 W/kg

**SAR(1 g) = 14.06 mW/g; SAR(10 g) = 6.52 mW/g**

Maximum value of SAR (measured) = 15.68 mW/g




Figure 11 System Performance Check 2450MHz 250mW





### System Performance Check at 2450 MHz Body TSL

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN: 712**

Date/Time: 6/1/2011 3:36:36 PM

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.94$  mho/m;  $\epsilon_r = 51.19$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.9 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.46, 7.46, 7.46); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**d=10mm, Pin=250mW/Area Scan (61x101x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 21.5 mW/g


**d=10mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 71.0 V/m; Power Drift = 0.011 dB

Peak SAR (extrapolated) = 28.2 W/kg

**SAR(1 g) = 14.01 mW/g; SAR(10 g) = 6.48 mW/g**

Maximum value of SAR (measured) = 19.82 mW/g



0 dB = 19.82mW/g

Figure 12 System Performance Check 2450MHz 250mW



## ANNEX C: Graph Results

### GSM 850 Left Cheek Middle

Date/Time: 5/22/2011 9:00:27 PM

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium parameters used:  $f = 837$  MHz;  $\sigma = 0.905$  mho/m;  $\epsilon_r = 41.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(9.5, 9.5, 9.5); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Cheek Middle/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.728 mW/g

**Cheek Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.91 V/m; Power Drift = -0.094 dB

Peak SAR (extrapolated) = 0.864 W/kg

**SAR(1 g) = 0.688 mW/g; SAR(10 g) = 0.500 mW/g**

Maximum value of SAR (measured) = 0.737 mW/g




Figure 13 Left Hand Touch Cheek GSM 850 Channel 190



### GSM 850 Left Tilt Middle

Date/Time: 5/22/2011 9:13:38 PM

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium parameters used:  $f = 837$  MHz;  $\sigma = 0.905$  mho/m;  $\epsilon_r = 41.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(9.5, 9.5, 9.5); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Tilt Middle/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.326 mW/g

**Tilt Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 13.6 V/m; Power Drift = -0.011 dB

Peak SAR (extrapolated) = 0.373 W/kg

**SAR(1 g) = 0.310 mW/g; SAR(10 g) = 0.235 mW/g**

Maximum value of SAR (measured) = 0.324 mW/g




Figure 14 Left Hand Tilt 15° GSM 850 Channel 190



### GSM 850 Right Cheek High

Date/Time: 5/22/2011 8:17:26 PM

Communication System: GSM 850; Frequency: 848.8 MHz; Duty Cycle: 1:8.3

Medium parameters used:  $f = 849$  MHz;  $\sigma = 0.915$  mho/m;  $\epsilon_r = 41.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(9.5, 9.5, 9.5); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Cheek High/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.849 mW/g


**Cheek High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.92 V/m; Power Drift = -0.017 dB

Peak SAR (extrapolated) = 0.940 W/kg

**SAR(1 g) = 0.786 mW/g; SAR(10 g) = 0.585 mW/g**

Maximum value of SAR (measured) = 0.830 mW/g






Figure 15 Right Hand Touch Cheek GSM 850 Channel 251



### GSM 850 Right Cheek Middle

Date/Time: 5/22/2011 8:04:35 PM

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium parameters used:  $f = 837$  MHz;  $\sigma = 0.905$  mho/m;  $\epsilon_r = 41.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(9.5, 9.5, 9.5); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Cheek Middle/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.787 mW/g

**Cheek Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.59 V/m; Power Drift = -0.087 dB

Peak SAR (extrapolated) = 0.884 W/kg

**SAR(1 g) = 0.729 mW/g; SAR(10 g) = 0.541 mW/g**

Maximum value of SAR (measured) = 0.768 mW/g




Figure 16 Right Hand Touch Cheek GSM 850 Channel 190



### GSM 850 Right Cheek Low

Date/Time: 5/22/2011 8:31:35 PM

Communication System: GSM 850; Frequency: 824.2 MHz; Duty Cycle: 1:8.3

Medium parameters used (interpolated):  $f = 824.2$  MHz;  $\sigma = 0.894$  mho/m;  $\epsilon_r = 41.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(9.5, 9.5, 9.5); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Cheek Low/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.798 mW/g

**Cheek Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.81 V/m; Power Drift = -0.030 dB

Peak SAR (extrapolated) = 0.885 W/kg

**SAR(1 g) = 0.746 mW/g; SAR(10 g) = 0.558 mW/g**

Maximum value of SAR (measured) = 0.776 mW/g




Figure 17 Right Hand Touch Cheek GSM 850 Channel 128



### GSM 850 Right Tilt Middle

Date/Time: 5/22/2011 8:44:54 PM

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium parameters used:  $f = 837$  MHz;  $\sigma = 0.905$  mho/m;  $\epsilon_r = 41.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(9.5, 9.5, 9.5); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Tilt Middle/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.343 mW/g

**Tilt Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 13.6 V/m; Power Drift = -0.019 dB

Peak SAR (extrapolated) = 0.390 W/kg

**SAR(1 g) = 0.328 mW/g; SAR(10 g) = 0.247 mW/g**

Maximum value of SAR (measured) = 0.344 mW/g




Figure 18 Right Hand Tilt 15° GSM 850 Channel 190





### GSM 850 Towards Ground Middle

Date/Time: 5/21/2011 10:06:35 PM

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium parameters used:  $f = 837$  MHz;  $\sigma = 0.996$  mho/m;  $\epsilon_r = 56.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(10.33, 10.33, 10.33); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Ground Middle/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.516 mW/g

**Towards Ground Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.45 V/m; Power Drift = 0.073 dB

Peak SAR (extrapolated) = 1.19 W/kg

**SAR(1 g) = 0.513 mW/g; SAR(10 g) = 0.359 mW/g**

Maximum value of SAR (measured) = 0.525 mW/g




Figure 19 Body, Towards Ground, GSM 850 Channel 190



### GSM 850 GPRS (2TXslots) Towards Ground Middle

Date/Time: 5/21/2011 8:56:40 PM

Communication System: GSM850 + GPRS(2Up); Frequency: 836.6 MHz; Duty Cycle: 1:4.15

Medium parameters used:  $f = 837$  MHz;  $\sigma = 0.996$  mho/m;  $\epsilon_r = 56.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(10.33, 10.33, 10.33); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Cheek Middle/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.672 mW/g

**Cheek Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.72 V/m; Power Drift = -0.011 dB

Peak SAR (extrapolated) = 0.809 W/kg

**SAR(1 g) = 0.638 mW/g; SAR(10 g) = 0.465 mW/g**

Maximum value of SAR (measured) = 0.677 mW/g




Figure 20 Body, Towards Ground, GSM 850 GPRS (2TXslots) Channel 190



### GSM 850 GPRS (3TXslots) Towards Ground Middle

Date/Time: 5/21/2011 9:09:17 PM

Communication System: GSM850 + GPRS(3Up); Frequency: 836.6 MHz; Duty Cycle: 1:2.767

Medium parameters used:  $f = 837$  MHz;  $\sigma = 0.996$  mho/m;  $\epsilon_r = 56.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(10.33, 10.33, 10.33); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Cheek Middle/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.703 mW/g

**Cheek Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.0 V/m; Power Drift = -0.063 dB

Peak SAR (extrapolated) = 0.858 W/kg

**SAR(1 g) = 0.673 mW/g; SAR(10 g) = 0.490 mW/g**

Maximum value of SAR (measured) = 0.714 mW/g




Figure 21 Body, Towards Ground, GSM 850 GPRS (3TXslots) Channel 190



### GSM 850 GPRS (4TXslots) Towards Ground High

Date/Time: 5/21/2011 9:53:11 PM

Communication System: GSM850 + GPRS(4Up); Frequency: 848.8 MHz; Duty Cycle: 1:2.075

Medium parameters used:  $f = 849 \text{ MHz}$ ;  $\sigma = 1.01 \text{ mho/m}$ ;  $\epsilon_r = 56.1$ ;  $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature:  $22.3^\circ\text{C}$  Liquid Temperature:  $21.5^\circ\text{C}$

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(10.33, 10.33, 10.33); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Ground High/Area Scan (51x91x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

Maximum value of SAR (interpolated) =  $0.856 \text{ mW/g}$


**Towards Ground High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $10.6 \text{ V/m}$ ; Power Drift =  $-0.034 \text{ dB}$

Peak SAR (extrapolated) =  $0.964 \text{ W/kg}$

**SAR(1 g) =  $0.751 \text{ mW/g}$ ; SAR(10 g) =  $0.534 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.800 \text{ mW/g}$






Figure 22 Body, Towards Ground, GSM 850 GPRS (4TXslots) Channel 251



### GSM 850 GPRS (4TXslots) Towards Ground Middle

Date/Time: 5/21/2011 9:21:55 PM

Communication System: GSM850 + GPRS(4Up); Frequency: 836.6 MHz; Duty Cycle: 1:2.075

Medium parameters used:  $f = 837$  MHz;  $\sigma = 0.996$  mho/m;  $\epsilon_r = 56.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(10.33, 10.33, 10.33); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Ground Middle/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.746 mW/g

**Towards Ground Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.3 V/m; Power Drift = -0.016 dB

Peak SAR (extrapolated) = 0.892 W/kg

**SAR(1 g) = 0.702 mW/g; SAR(10 g) = 0.511 mW/g**

Maximum value of SAR (measured) = 0.744 mW/g




Figure 23 Body, Towards Ground, GSM 850 GPRS (4TXslots) Channel 190



### GSM 850 GPRS (4TXslots) Towards Ground Low

Date/Time: 5/21/2011 9:35:27 PM

Communication System: GSM850 + GPRS(4Up); Frequency: 824.2 MHz; Duty Cycle: 1:2.075

Medium parameters used (interpolated):  $f = 824.2$  MHz;  $\sigma = 0.985$  mho/m;  $\epsilon_r = 56.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(10.33, 10.33, 10.33); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Ground Low/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.806 mW/g

**Towards Ground Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.2 V/m; Power Drift = 0.010 dB

Peak SAR (extrapolated) = 0.917 W/kg

**SAR(1 g) = 0.716 mW/g; SAR(10 g) = 0.515 mW/g**

Maximum value of SAR (measured) = 0.754 mW/g

**Towards Ground Low/Zoom Scan (7x7x7)/Cube 1:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.2 V/m; Power Drift = 0.010 dB

Peak SAR (extrapolated) = 0.829 W/kg

**SAR(1 g) = 0.624 mW/g; SAR(10 g) = 0.427 mW/g**

Maximum value of SAR (measured) = 0.704 mW/g




Figure 24 Body, Towards Ground, GSM 850 GPRS (4TXslots) Channel 128



### GSM 850 GPRS (4TXslots) Towards Phantom Middle

Date/Time: 5/21/2011 10:22:15 PM

Communication System: GSM850 + GPRS(4Up); Frequency: 836.6 MHz; Duty Cycle: 1:2.075

Medium parameters used:  $f = 837$  MHz;  $\sigma = 0.996$  mho/m;  $\epsilon_r = 56.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(10.33, 10.33, 10.33); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Phantom Middle/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.629 mW/g

**Towards Phantom Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.27 V/m; Power Drift = -0.023 dB

Peak SAR (extrapolated) = 0.742 W/kg

**SAR(1 g) = 0.594 mW/g; SAR(10 g) = 0.439 mW/g**

Maximum value of SAR (measured) = 0.629 mW/g




Figure 25 Body, Towards Phantom, GSM 850 GPRS (4TXslots) Channel 190





### GSM 850 with Earphone Towards Ground High

Date/Time: 5/21/2011 9:54:09 AM

Communication System: GSM 850; Frequency: 848.8 MHz; Duty Cycle: 1:8.3

Medium parameters used:  $f = 849$  MHz;  $\sigma = 1.01$  mho/m;  $\epsilon_r = 56.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(10.33, 10.33, 10.33); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Ground High/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.635 mW/g

**Towards Ground High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.63 V/m; Power Drift = -0.077 dB

Peak SAR (extrapolated) = 0.769 W/kg

**SAR(1 g) = 0.602 mW/g; SAR(10 g) = 0.436 mW/g**

Maximum value of SAR (measured) = 0.642 mW/g




Figure 26 Body with Earphone, Towards Ground, GSM 850 Channel 251



### GSM 850 GPRS (4TXslots) (Hot spots) Towards Ground High

Date/Time: 5/21/2011 12:46:57 PM

Communication System: GSM850 + GPRS(4Up); Frequency: 848.8 MHz; Duty Cycle: 1:2.075

Medium parameters used:  $f = 849 \text{ MHz}$ ;  $\sigma = 1.01 \text{ mho/m}$ ;  $\epsilon_r = 56.1$ ;  $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature:  $22.3^\circ\text{C}$  Liquid Temperature:  $21.5^\circ\text{C}$

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(10.33, 10.33, 10.33); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Ground High/Area Scan (51x91x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

Maximum value of SAR (interpolated) =  $1.04 \text{ mW/g}$

**Towards Ground High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $28.9 \text{ V/m}$ ; Power Drift =  $-0.052 \text{ dB}$

Peak SAR (extrapolated) =  $1.28 \text{ W/kg}$

**SAR(1 g) =  $0.984 \text{ mW/g}$ ; SAR(10 g) =  $0.710 \text{ mW/g}$**

Maximum value of SAR (measured) =  $1.04 \text{ mW/g}$

**Towards Ground High/Zoom Scan (7x7x7)/Cube 1:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $28.9 \text{ V/m}$ ; Power Drift =  $-0.052 \text{ dB}$

Peak SAR (extrapolated) =  $1.11 \text{ W/kg}$

**SAR(1 g) =  $0.837 \text{ mW/g}$ ; SAR(10 g) =  $0.548 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.972 \text{ mW/g}$




Figure 27 Body, Towards Ground, GSM 850 GPRS (4TXslots) Channel 251



### GSM 850 GPRS (4TXslots) (Hot spots) Towards Ground Middle

Date/Time: 5/21/2011 8:27:08 PM

Communication System: GSM850 + GPRS(4Up); Frequency: 836.6 MHz; Duty Cycle: 1:2.075

Medium parameters used:  $f = 837$  MHz;  $\sigma = 0.996$  mho/m;  $\epsilon_r = 56.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(10.33, 10.33, 10.33); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Ground Middle/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.10 mW/g

**Towards Ground Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 30.4 V/m; Power Drift = -0.065 dB

Peak SAR (extrapolated) = 1.31 W/kg

**SAR(1 g) = 1.02 mW/g; SAR(10 g) = 0.716 mW/g**

Maximum value of SAR (measured) = 1.08 mW/g




Figure 28 Body, Towards Ground, GSM 850 GPRS (4TXslots) Channel 190



### GSM 850 GPRS (4TXslots) (Hot spots) Towards Ground Low

Date/Time: 5/21/2011 1:13:38 PM

Communication System: GSM850 + GPRS(4Up); Frequency: 824.2 MHz; Duty Cycle: 1:2.075

Medium parameters used (interpolated):  $f = 824.2$  MHz;  $\sigma = 0.985$  mho/m;  $\epsilon_r = 56.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(10.33, 10.33, 10.33); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Ground Low/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.19 mW/g

**Towards Ground Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 30.0 V/m; Power Drift = -0.064 dB

Peak SAR (extrapolated) = 2.51 W/kg

**SAR(1 g) = 1.03 mW/g; SAR(10 g) = 0.697 mW/g**

Maximum value of SAR (measured) = 1.07 mW/g


**Towards Ground Low/Zoom Scan (7x7x7)/Cube 1:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 30.0 V/m; Power Drift = -0.064 dB

Peak SAR (extrapolated) = 1.32 W/kg

**SAR(1 g) = 1.01 mW/g; SAR(10 g) = 0.717 mW/g**

Maximum value of SAR (measured) = 1.08 mW/g







Figure 29 Body, Towards Ground, GSM 850 GPRS (4TXslots) Channel 128



### GSM 850 GPRS (4TXslots) (Hot spots) Towards Phantom Middle

Date/Time: 5/21/2011 12:13:43 PM

Communication System: GSM850 + GPRS(4Up); Frequency: 836.6 MHz; Duty Cycle: 1:2.075

Medium parameters used:  $f = 837$  MHz;  $\sigma = 0.996$  mho/m;  $\epsilon_r = 56.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(10.33, 10.33, 10.33); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Phantom Middle/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.807 mW/g

**Towards Phantom Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 26.2 V/m; Power Drift = 0.003 dB

Peak SAR (extrapolated) = 0.939 W/kg

**SAR(1 g) = 0.768 mW/g; SAR(10 g) = 0.567 mW/g**

Maximum value of SAR (measured) = 0.811 mW/g




Figure 30 Body, Towards Phantom, GSM 850 GPRS (4TXslots) Channel 190



### GSM 850 GPRS (4TXslots) (Hot spots) Left Edge Middle

Date/Time: 5/21/2011 11:16:20 AM

Communication System: GSM850 + GPRS(4Up); Frequency: 836.6 MHz; Duty Cycle: 1:2.075

Medium parameters used:  $f = 837$  MHz;  $\sigma = 0.996$  mho/m;  $\epsilon_r = 56.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(10.33, 10.33, 10.33); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Left Edge Middle/Area Scan (41x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.492 mW/g

**Left Edge Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 22.9 V/m; Power Drift = -0.006 dB

Peak SAR (extrapolated) = 0.627 W/kg

**SAR(1 g) = 0.461 mW/g; SAR(10 g) = 0.317 mW/g**

Maximum value of SAR (measured) = 0.497 mW/g




Figure 31 Body, Left Edge, GSM 850 GPRS (4TXslots) Channel 190



### GSM 850 GPRS (4TXslots) (Hot spots) Right Edge Middle

Date/Time: 5/21/2011 11:56:40 AM

Communication System: GSM850 + GPRS(4Up); Frequency: 836.6 MHz; Duty Cycle: 1:2.075

Medium parameters used:  $f = 837$  MHz;  $\sigma = 0.996$  mho/m;  $\epsilon_r = 56.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(10.33, 10.33, 10.33); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Right Edge Middle/Area Scan (41x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.586 mW/g

**Right Edge Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 24.7 V/m; Power Drift = -0.033 dB

Peak SAR (extrapolated) = 0.738 W/kg

**SAR(1 g) = 0.549 mW/g; SAR(10 g) = 0.381 mW/g**

Maximum value of SAR (measured) = 0.591 mW/g




Figure 32 Body, Right Edge, GSM 850 GPRS (4TXslots) Channel 190





### GSM 850 GPRS (4TXslots) (Hot spots) Bottom Edge Middle

Date/Time: 5/21/2011 12:30:09 PM

Communication System: GSM850 + GPRS(4Up); Frequency: 836.6 MHz; Duty Cycle: 1:2.075

Medium parameters used:  $f = 837$  MHz;  $\sigma = 0.996$  mho/m;  $\epsilon_r = 56.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(10.33, 10.33, 10.33); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Bottom Edge Middle/Area Scan (41x61x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.163 mW/g

**Bottom Edge Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 13.1 V/m; Power Drift = -0.039 dB

Peak SAR (extrapolated) = 0.348 W/kg

**SAR(1 g) = 0.146 mW/g; SAR(10 g) = 0.078 mW/g**

Maximum value of SAR (measured) = 0.160 mW/g




Figure 33 Body, Bottom Edge, GSM 850 GPRS (4TXslots) Channel 190



### GSM 850 EGPRS (4TXslots) (hot spots) Towards Ground Low

Date/Time: 5/21/2011 1:33:44 PM

Communication System: GSM850 + EGPRS(4Up); Frequency: 824.2 MHz; Duty Cycle: 1:2.075

Medium parameters used (interpolated):  $f = 824.2$  MHz;  $\sigma = 0.985$  mho/m;  $\epsilon_r = 56.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(10.33, 10.33, 10.33); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Ground Low/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.09 mW/g

**Towards Ground Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 29.9 V/m; Power Drift = -0.018 dB

Peak SAR (extrapolated) = 1.33 W/kg

**SAR(1 g) = 0.994 mW/g; SAR(10 g) = 0.646 mW/g**

Maximum value of SAR (measured) = 1.06 mW/g

**Towards Ground Low/Zoom Scan (7x7x7)/Cube 1:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 29.9 V/m; Power Drift = -0.018 dB

Peak SAR (extrapolated) = 1.31 W/kg

**SAR(1 g) = 1.01 mW/g; SAR(10 g) = 0.734 mW/g**

Maximum value of SAR (measured) = 1.07 mW/g




Figure 34 Body, Towards Ground, GSM 850 EGPRS (4TXslots) Channel 128



### GSM 1900 Left Cheek High

Date/Time: 5/24/2011 7:06:20 PM

Communication System: PCS 1900; Frequency: 1909.8 MHz; Duty Cycle: 1:8.3

Medium parameters used:  $f = 1910$  MHz;  $\sigma = 1.45$  mho/m;  $\epsilon_r = 39.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.94, 7.94, 7.94); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Cheek High/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.494 mW/g

**Cheek High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.22 V/m; Power Drift = 0.171 dB

Peak SAR (extrapolated) = 0.635 W/kg

**SAR(1 g) = 0.427 mW/g; SAR(10 g) = 0.252 mW/g**

Maximum value of SAR (measured) = 0.470 mW/g




Figure 35 Left Hand Touch Cheek GSM 1900 Channel 810



### GSM 1900 Left Cheek Middle

Date/Time: 5/24/2011 3:55:37 PM

Communication System: PCS 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.43$  mho/m;  $\epsilon_r = 40$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.94, 7.94, 7.94); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Cheek Middle/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.467 mW/g

**Cheek Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.81 V/m; Power Drift = 0.024 dB

Peak SAR (extrapolated) = 0.609 W/kg

**SAR(1 g) = 0.416 mW/g; SAR(10 g) = 0.245 mW/g**

Maximum value of SAR (measured) = 0.454 mW/g




Figure 36 Left Hand Touch Cheek GSM 1900 Channel 661



### GSM 1900 Left Cheek Low

Date/Time: 5/24/2011 7:19:07 PM

Communication System: PCS 1900; Frequency: 1850.2 MHz; Duty Cycle: 1:8.3

Medium parameters used (interpolated):  $f = 1850.2$  MHz;  $\sigma = 1.4$  mho/m;  $\epsilon_r = 40.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.94, 7.94, 7.94); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Cheek Low/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.565 mW/g


**Cheek Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.71 V/m; Power Drift = -0.044 dB

Peak SAR (extrapolated) = 0.727 W/kg

**SAR(1 g) = 0.496 mW/g; SAR(10 g) = 0.294 mW/g**

Maximum value of SAR (measured) = 0.540 mW/g






Figure 37 Left Hand Touch Cheek GSM 1900 Channel 512



### GSM 1900 Left Tilt Middle

Date/Time: 5/24/2011 7:32:30 PM

Communication System: PCS 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.43$  mho/m;  $\epsilon_r = 40$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.94, 7.94, 7.94); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Tilt Middle/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.217 mW/g

**Tilt Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.45 V/m; Power Drift = -0.058 dB

Peak SAR (extrapolated) = 0.236 W/kg

**SAR(1 g) = 0.176 mW/g; SAR(10 g) = 0.111 mW/g**

Maximum value of SAR (measured) = 0.186 mW/g




Figure 38 Left Hand Tilt 15° GSM 1900 Channel 661



### GSM 1900 Right Cheek Middle

Date/Time: 5/24/2011 6:12:59 PM

Communication System: PCS 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.43$  mho/m;  $\epsilon_r = 40$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.94, 7.94, 7.94); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Cheek Middle/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.397 mW/g

**Cheek Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.93 V/m; Power Drift = -0.062 dB

Peak SAR (extrapolated) = 0.486 W/kg

**SAR(1 g) = 0.375 mW/g; SAR(10 g) = 0.240 mW/g**

Maximum value of SAR (measured) = 0.398 mW/g

**Cheek Middle/Zoom Scan (7x7x7)/Cube 1:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.93 V/m; Power Drift = -0.062 dB

Peak SAR (extrapolated) = 0.455 W/kg

**SAR(1 g) = 0.333 mW/g; SAR(10 g) = 0.217 mW/g**

Maximum value of SAR (measured) = 0.368 mW/g




Figure 39 Right Hand Touch Cheek GSM 1900 Channel 661





### GSM 1900 Right Tilt Middle

Date/Time: 5/24/2011 6:33:03 PM

Communication System: PCS 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.43$  mho/m;  $\epsilon_r = 40$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.94, 7.94, 7.94); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Tilt Middle/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.214 mW/g

**Tilt Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.9 V/m; Power Drift = -0.006 dB

Peak SAR (extrapolated) = 0.254 W/kg

**SAR(1 g) = 0.184 mW/g; SAR(10 g) = 0.115 mW/g**

Maximum value of SAR (measured) = 0.202 mW/g




Figure 40 Right Hand Tilt 15° GSM 1900 Channel 661



### GSM 1900 Towards Ground Middle

Date/Time: 5/23/2011 9:56:37 AM

Communication System: PCS 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.54$  mho/m;  $\epsilon_r = 52$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.77, 7.77, 7.77); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Ground Middle/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.262 mW/g

**Towards Ground Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.17 V/m; Power Drift = -0.046 dB

Peak SAR (extrapolated) = 0.415 W/kg

**SAR(1 g) = 0.233 mW/g; SAR(10 g) = 0.137 mW/g**

Maximum value of SAR (measured) = 0.246 mW/g




Figure 41 Body, Towards Ground, GSM 1900 Channel 661



### GSM 1900 GPRS (2TXslots) Towards Ground Middle

Date/Time: 5/23/2011 10:09:36 AM

Communication System: PCS 1900+GPRS(2Up); Frequency: 1880 MHz; Duty Cycle: 1:4.15

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.54$  mho/m;  $\epsilon_r = 52$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.77, 7.77, 7.77); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Ground Middle/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.382 mW/g

**Towards Ground Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.82 V/m; Power Drift = -0.034 dB

Peak SAR (extrapolated) = 0.581 W/kg

**SAR(1 g) = 0.335 mW/g; SAR(10 g) = 0.198 mW/g**

Maximum value of SAR (measured) = 0.356 mW/g




Figure 42 Body, Towards Ground, GSM 1900 GPRS (2TXslots) Channel 661



### GSM 1900 GPRS (3TXslots) Towards Ground Middle

Date/Time: 5/23/2011 10:22:03 AM

Communication System: PCS 1900+GPRS(3Up); Frequency: 1880 MHz; Duty Cycle: 1:2.767

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.54$  mho/m;  $\epsilon_r = 52$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.77, 7.77, 7.77); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Ground Middle/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.412 mW/g

**Towards Ground Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.2 V/m; Power Drift = -0.022 dB

Peak SAR (extrapolated) = 0.586 W/kg

**SAR(1 g) = 0.358 mW/g; SAR(10 g) = 0.213 mW/g**

Maximum value of SAR (measured) = 0.384 mW/g




Figure 43 Body, Towards Ground, GSM 1900 GPRS (3TXslots) Channel 661



### GSM 1900 GPRS (4TXslots) Towards Ground High

Date/Time: 5/23/2011 10:46:55 AM

Communication System: PCS 1900+GPRS(4Up); Frequency: 1909.8 MHz; Duty Cycle: 1:2.075

Medium parameters used:  $f = 1910$  MHz;  $\sigma = 1.57$  mho/m;  $\epsilon_r = 52$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.77, 7.77, 7.77); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Ground High/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.442 mW/g

**Towards Ground High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.5 V/m; Power Drift = 0.003 dB

Peak SAR (extrapolated) = 0.697 W/kg

**SAR(1 g) = 0.390 mW/g; SAR(10 g) = 0.229 mW/g**

Maximum value of SAR (measured) = 0.413 mW/g




Figure 44 Body, Towards Ground, GSM 1900 GPRS (4TXslots) Channel 810



### GSM 1900 GPRS (4TXslots) Towards Ground Middle

Date/Time: 5/23/2011 10:34:27 AM

Communication System: PCS 1900+GPRS(4Up); Frequency: 1880 MHz; Duty Cycle: 1:2.075

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.54$  mho/m;  $\epsilon_r = 52$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.77, 7.77, 7.77); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Ground Middle/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.439 mW/g

**Towards Ground Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.5 V/m; Power Drift = 0.030 dB

Peak SAR (extrapolated) = 0.686 W/kg

**SAR(1 g) = 0.387 mW/g; SAR(10 g) = 0.228 mW/g**

Maximum value of SAR (measured) = 0.407 mW/g




Figure 45 Body, Towards Ground, GSM 1900 GPRS (4TXslots) Channel 661



### GSM 1900 GPRS (4TXslots) Towards Ground Low

Date/Time: 5/23/2011 10:59:40 AM

Communication System: PCS 1900+GPRS(4Up); Frequency: 1850.2 MHz; Duty Cycle: 1:2.075

Medium parameters used (interpolated):  $f = 1850.2$  MHz;  $\sigma = 1.51$  mho/m;  $\epsilon_r = 52.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.77, 7.77, 7.77); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Ground Low/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.516 mW/g


**Towards Ground Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.4 V/m; Power Drift = -0.044 dB

Peak SAR (extrapolated) = 0.802 W/kg

**SAR(1 g) = 0.458 mW/g; SAR(10 g) = 0.270 mW/g**

Maximum value of SAR (measured) = 0.485 mW/g






Figure 46 Body, Towards Ground, GSM 1900 GPRS (4TXslots) Channel 512





### GSM 1900 GPRS (4TXslots) Towards Phantom Middle

Date/Time: 5/23/2011 1:01:33 PM

Communication System: PCS 1900+GPRS(4Up); Frequency: 1880 MHz; Duty Cycle: 1:2.075

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.54$  mho/m;  $\epsilon_r = 52$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.77, 7.77, 7.77); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Phantom Middle/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.336 mW/g

**Towards Phantom Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.4 V/m; Power Drift = -0.116 dB

Peak SAR (extrapolated) = 0.549 W/kg

**SAR(1 g) = 0.297 mW/g; SAR(10 g) = 0.168 mW/g**

Maximum value of SAR (measured) = 0.311 mW/g

**Towards Phantom Middle/Zoom Scan (7x7x7)/Cube 1:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.4 V/m; Power Drift = -0.116 dB

Peak SAR (extrapolated) = 0.345 W/kg

**SAR(1 g) = 0.213 mW/g; SAR(10 g) = 0.136 mW/g**

Maximum value of SAR (measured) = 0.226 mW/g




Figure 47 Body, Towards Phantom, GSM 1900 GPRS (4TXslots) Channel 661



### GSM 1900 with Earphone Towards Ground Low

Date/Time: 5/23/2011 7:46:26 PM

Communication System: PCS 1900; Frequency: 1850.2 MHz; Duty Cycle: 1:8.3

Medium parameters used (interpolated):  $f = 1850.2$  MHz;  $\sigma = 1.51$  mho/m;  $\epsilon_r = 52.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.77, 7.77, 7.77); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Ground Low/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.240 mW/g

**Towards Ground Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.06 V/m; Power Drift = 0.015 dB

Peak SAR (extrapolated) = 0.374 W/kg

**SAR(1 g) = 0.215 mW/g; SAR(10 g) = 0.128 mW/g**

Maximum value of SAR (measured) = 0.230 mW/g




Figure 48 Body with Earphone, Towards Ground, GSM 1900 Channel 512



### GSM 1900 GPRS (4TXslots) (Hot spots) Towards Ground High

Date/Time: 5/23/2011 5:27:10 PM

Communication System: PCS 1900+GPRS(4Up); Frequency: 1909.8 MHz; Duty Cycle: 1:2.075

Medium parameters used:  $f = 1910$  MHz;  $\sigma = 1.57$  mho/m;  $\epsilon_r = 52$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.77, 7.77, 7.77); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Ground High/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.689 mW/g

**Towards Ground High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.8 V/m; Power Drift = -0.026 dB

Peak SAR (extrapolated) = 1.18 W/kg

**SAR(1 g) = 0.643 mW/g; SAR(10 g) = 0.365 mW/g**

Maximum value of SAR (measured) = 0.679 mW/g




Figure 49 Body, Towards Ground, GSM 1900 GPRS (4TXslots) Channel 810



### GSM 1900 GPRS (4TXslots) (Hot spots) Towards Ground Middle

Date/Time: 5/23/2011 5:14:50 PM

Communication System: PCS 1900+GPRS(4Up); Frequency: 1880 MHz; Duty Cycle: 1:2.075

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.54$  mho/m;  $\epsilon_r = 52$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.77, 7.77, 7.77); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Ground Middle/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.682 mW/g

**Towards Ground Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.3 V/m; Power Drift = -0.045 dB

Peak SAR (extrapolated) = 1.19 W/kg

**SAR(1 g) = 0.630 mW/g; SAR(10 g) = 0.358 mW/g**

Maximum value of SAR (measured) = 0.661 mW/g




Figure 50 Body, Towards Ground, GSM 1900 GPRS (4TXslots) Channel 661



### GSM 1900 GPRS (4TXslots) (Hot spots) Towards Ground Low

Date/Time: 5/23/2011 5:40:10 PM

Communication System: PCS 1900+GPRS(4Up); Frequency: 1850.2 MHz; Duty Cycle: 1:2.075

Medium parameters used (interpolated):  $f = 1850.2$  MHz;  $\sigma = 1.51$  mho/m;  $\epsilon_r = 52.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.77, 7.77, 7.77); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Ground Low/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.792 mW/g


**Towards Ground Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 12.6 V/m; Power Drift = 0.036 dB

Peak SAR (extrapolated) = 1.33 W/kg

**SAR(1 g) = 0.736 mW/g; SAR(10 g) = 0.422 mW/g**

Maximum value of SAR (measured) = 0.759 mW/g






Figure 51 Body, Towards Ground, GSM 1900 GPRS (4TXslots) Channel 512



### GSM 1900 GPRS (4TXslots) (Hot spots) Towards Phantom Middle

Date/Time: 5/23/2011 2:54:17 PM

Communication System: PCS 1900+GPRS(4Up); Frequency: 1880 MHz; Duty Cycle: 1:2.075

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.54$  mho/m;  $\epsilon_r = 52$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.77, 7.77, 7.77); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Phantom Middle/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.520 mW/g

**Towards Phantom Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.3 V/m; Power Drift = -0.087 dB

Peak SAR (extrapolated) = 0.842 W/kg

**SAR(1 g) = 0.453 mW/g; SAR(10 g) = 0.255 mW/g**

Maximum value of SAR (measured) = 0.487 mW/g




Figure 52 Body, Towards Phantom, GSM 1900 GPRS (4TXslots) Channel 661



### GSM 1900 GPRS (4TXslots) (Hot spots) Left Edge Middle

Date/Time: 5/23/2011 3:18:16 PM

Communication System: PCS 1900+GPRS(4Up); Frequency: 1880 MHz; Duty Cycle: 1:2.075

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.54$  mho/m;  $\epsilon_r = 52$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.77, 7.77, 7.77); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Left Edge Middle/Area Scan (41x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.238 mW/g

**Left Edge Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.4 V/m; Power Drift = -0.053 dB

Peak SAR (extrapolated) = 0.477 W/kg

**SAR(1 g) = 0.217 mW/g; SAR(10 g) = 0.124 mW/g**

Maximum value of SAR (measured) = 0.232 mW/g




Figure 53 Body, Left Edge, GSM 1900 GPRS (4TXslots) Channel 661





### GSM 1900 GPRS (4TXslots) (Hot spots) Right Edge Middle

Date/Time: 5/23/2011 4:29:26 PM

Communication System: PCS 1900+GPRS(4Up); Frequency: 1880 MHz; Duty Cycle: 1:2.075

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.54$  mho/m;  $\epsilon_r = 52$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.77, 7.77, 7.77); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Right Edge Middle/Area Scan (41x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.202 mW/g

**Right Edge Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.73 V/m; Power Drift = -0.042 dB

Peak SAR (extrapolated) = 0.310 W/kg

**SAR(1 g) = 0.173 mW/g; SAR(10 g) = 0.096 mW/g**

Maximum value of SAR (measured) = 0.189 mW/g




Figure 54 Body, Right Edge, GSM 1900 GPRS (4TXslots) Channel 661



### GSM 1900 GPRS (4TXslots) (Hot spots) Bottom Edge Middle

Date/Time: 5/23/2011 4:48:34 PM

Communication System: PCS 1900+GPRS(4Up); Frequency: 1880 MHz; Duty Cycle: 1:2.075

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.54$  mho/m;  $\epsilon_r = 52$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.77, 7.77, 7.77); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Bottom Edge Middle/Area Scan (41x61x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.384 mW/g

**Bottom Edge Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 15.9 V/m; Power Drift = -0.114 dB

Peak SAR (extrapolated) = 0.616 W/kg

**SAR(1 g) = 0.342 mW/g; SAR(10 g) = 0.192 mW/g**

Maximum value of SAR (measured) = 0.375 mW/g




Figure 55 Body, Bottom Edge, GSM 1900 GPRS (4TXslots) Channel 661



### GSM 1900 EGPRS (4TXslots) (hot spots) Towards Ground Low

Date/Time: 5/23/2011 5:55:21 PM

Communication System: PCS 1900+EGPRS(4Up); Frequency: 1850.2 MHz; Duty Cycle: 1:2.075

Medium parameters used (interpolated):  $f = 1850.2$  MHz;  $\sigma = 1.51$  mho/m;  $\epsilon_r = 52.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.77, 7.77, 7.77); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Ground Low/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.788 mW/g

**Towards Ground Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 12.6 V/m; Power Drift = 0.015 dB

Peak SAR (extrapolated) = 1.34 W/kg

**SAR(1 g) = 0.736 mW/g; SAR(10 g) = 0.421 mW/g**

Maximum value of SAR (measured) = 0.759 mW/g




Figure 56 Body, Towards Ground, GSM 1900 EGPRS (4TXslots) Channel 512



### WCDMA Band II Left Cheek High

Date/Time: 5/24/2011 5:06:04 PM

Communication System: WCDMA Band II; Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1908 \text{ MHz}$ ;  $\sigma = 1.45 \text{ mho/m}$ ;  $\epsilon_r = 39.9$ ;  $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature:  $22.3^\circ\text{C}$  Liquid Temperature:  $21.5^\circ\text{C}$

Phantom section: Left Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.94, 7.94, 7.94); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Cheek High/Area Scan (51x91x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

Maximum value of SAR (interpolated) =  $1.05 \text{ mW/g}$

**Cheek High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $7.10 \text{ V/m}$ ; Power Drift =  $0.000 \text{ dB}$

Peak SAR (extrapolated) =  $1.33 \text{ W/kg}$

**SAR(1 g) =  $0.901 \text{ mW/g}$ ; SAR(10 g) =  $0.535 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.995 \text{ mW/g}$




Figure 57 Left Hand Touch Cheek WCDMA Band II Channel 9538



### WCDMA Band II Left Cheek Middle

Date/Time: 5/24/2011 3:36:55 PM

Communication System: WCDMA Band II; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.43$  mho/m;  $\epsilon_r = 40$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.94, 7.94, 7.94); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Cheek Middle/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.04 mW/g

**Cheek Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.81 V/m; Power Drift = 0.063 dB

Peak SAR (extrapolated) = 1.32 W/kg

**SAR(1 g) = 0.909 mW/g; SAR(10 g) = 0.535 mW/g**

Maximum value of SAR (measured) = 1.01 mW/g




Figure 58 Left Hand Touch Cheek WCDMA Band II Channel 9400



### WCDMA Band II Left Cheek Low

Date/Time: 5/24/2011 5:34:56 PM

Communication System: WCDMA Band II; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 1852.4$  MHz;  $\sigma = 1.4$  mho/m;  $\epsilon_r = 40$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.94, 7.94, 7.94); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Cheek Low/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.07 mW/g


**Cheek Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.01 V/m; Power Drift = 0.073 dB

Peak SAR (extrapolated) = 1.40 W/kg

**SAR(1 g) = 0.957 mW/g; SAR(10 g) = 0.571 mW/g**

Maximum value of SAR (measured) = 1.05 mW/g






Figure 59 Left Hand Touch Cheek WCDMA Band II Channel 9262



### WCDMA Band II Left Tilt Middle

Date/Time: 5/24/2011 5:48:48 PM

Communication System: WCDMA Band II; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.43$  mho/m;  $\epsilon_r = 40$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.94, 7.94, 7.94); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Tilt Middle/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.482 mW/g

**Tilt Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.3 V/m; Power Drift = -0.124 dB

Peak SAR (extrapolated) = 0.530 W/kg

**SAR(1 g) = 0.396 mW/g; SAR(10 g) = 0.252 mW/g**

Maximum value of SAR (measured) = 0.416 mW/g




Figure 60 Left Hand Tilt 15° WCDMA Band II Channel 9400





### WCDMA Band II Right Cheek High

Date/Time: 5/24/2011 4:10:08 PM

Communication System: WCDMA Band II; Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1908$  MHz;  $\sigma = 1.45$  mho/m;  $\epsilon_r = 39.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.94, 7.94, 7.94); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Cheek High/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.815 mW/g

**Cheek High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 12.2 V/m; Power Drift = -0.079 dB

Peak SAR (extrapolated) = 1.02 W/kg

**SAR(1 g) = 0.780 mW/g; SAR(10 g) = 0.492 mW/g**

Maximum value of SAR (measured) = 0.836 mW/g

**Cheek High/Zoom Scan (7x7x7)/Cube 1:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 12.2 V/m; Power Drift = -0.079 dB

Peak SAR (extrapolated) = 0.918 W/kg

**SAR(1 g) = 0.682 mW/g; SAR(10 g) = 0.444 mW/g**

Maximum value of SAR (measured) = 0.766 mW/g




Figure 61 Right Hand Touch Cheek WCDMA Band II Channel 9538



### WCDMA Band II Right Cheek Middle

Date/Time: 5/24/2011 3:21:49 PM

Communication System: WCDMA Band II; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.43$  mho/m;  $\epsilon_r = 40$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.94, 7.94, 7.94); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Cheek Middle 2/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.938 mW/g

**Cheek Middle 2/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.3 V/m; Power Drift = -0.034 dB

Peak SAR (extrapolated) = 1.15 W/kg

**SAR(1 g) = 0.877 mW/g; SAR(10 g) = 0.554 mW/g**

Maximum value of SAR (measured) = 0.933 mW/g

**Cheek Middle 2/Zoom Scan (7x7x7)/Cube 1:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.3 V/m; Power Drift = -0.034 dB

Peak SAR (extrapolated) = 1.02 W/kg

**SAR(1 g) = 0.752 mW/g; SAR(10 g) = 0.482 mW/g**

Maximum value of SAR (measured) = 0.814 mW/g




Figure 62 Right Hand Touch Cheek WCDMA Band II Channel 9400



### WCDMA Band II Right Cheek Low

Date/Time: 5/24/2011 4:29:11 PM

Communication System: WCDMA Band II; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 1852.4$  MHz;  $\sigma = 1.4$  mho/m;  $\epsilon_r = 40$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.94, 7.94, 7.94); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Cheek Low/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.932 mW/g

**Cheek Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 12.2 V/m; Power Drift = 0.025 dB

Peak SAR (extrapolated) = 1.15 W/kg

**SAR(1 g) = 0.892 mW/g; SAR(10 g) = 0.573 mW/g**

Maximum value of SAR (measured) = 0.956 mW/g

**Cheek Low/Zoom Scan (7x7x7)/Cube 1:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 12.2 V/m; Power Drift = 0.025 dB

Peak SAR (extrapolated) = 1.02 W/kg

**SAR(1 g) = 0.764 mW/g; SAR(10 g) = 0.491 mW/g**

Maximum value of SAR (measured) = 0.843 mW/g




Figure 63 Right Hand Touch Cheek WCDMA Band II Channel 9262



### WCDMA Band II Right Tilt Middle

Date/Time: 5/24/2011 4:49:01 PM

Communication System: WCDMA Band II; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.43$  mho/m;  $\epsilon_r = 40$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.94, 7.94, 7.94); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Tilt Middle/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.436 mW/g

**Tilt Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 16.3 V/m; Power Drift = 0.033 dB

Peak SAR (extrapolated) = 0.504 W/kg

**SAR(1 g) = 0.375 mW/g; SAR(10 g) = 0.236 mW/g**

Maximum value of SAR (measured) = 0.408 mW/g




Figure 64 Right Hand Tilt 15° WCDMA Band II Channel 9400



## WCDMA Band II Towards Ground High

Date/Time: 5/23/2011 11:27:26 AM

Communication System: WCDMA Band II; Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1908$  MHz;  $\sigma = 1.57$  mho/m;  $\epsilon_r = 52$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.77, 7.77, 7.77); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Ground High/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.563 mW/g

**Towards Ground High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 12.0 V/m; Power Drift = 0.045 dB

Peak SAR (extrapolated) = 0.890 W/kg

**SAR(1 g) = 0.502 mW/g; SAR(10 g) = 0.296 mW/g**

Maximum value of SAR (measured) = 0.529 mW/g




Figure 65 Body, Towards Ground, WCDMA Band II Channel 9538



### WCDMA Band II Towards Ground Middle

Date/Time: 5/23/2011 11:14:31 AM

Communication System: WCDMA Band II; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.54$  mho/m;  $\epsilon_r = 52$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.77, 7.77, 7.77); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Ground Middle/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.564 mW/g

**Towards Ground Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 12.0 V/m; Power Drift = -0.024 dB

Peak SAR (extrapolated) = 0.902 W/kg

**SAR(1 g) = 0.509 mW/g; SAR(10 g) = 0.298 mW/g**

Maximum value of SAR (measured) = 0.537 mW/g




Figure 66 Body, Towards Ground, WCDMA Band II Channel 9400



## WCDMA Band II Towards Ground Low

Date/Time: 5/23/2011 11:39:49 AM

Communication System: WCDMA Band II; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 1852.4$  MHz;  $\sigma = 1.51$  mho/m;  $\epsilon_r = 52.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.77, 7.77, 7.77); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Ground Low/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.621 mW/g


**Towards Ground Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 12.4 V/m; Power Drift = -0.055 dB

Peak SAR (extrapolated) = 0.947 W/kg

**SAR(1 g) = 0.544 mW/g; SAR(10 g) = 0.320 mW/g**

Maximum value of SAR (measured) = 0.576 mW/g






Figure 67 Body, Towards Ground, WCDMA Band II Channel 9262





## WCDMA Band II Towards Phantom Middle

Date/Time: 5/23/2011 1:21:03 PM

Communication System: WCDMA Band II; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.54$  mho/m;  $\epsilon_r = 52$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.77, 7.77, 7.77); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Phantom Middle/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.430 mW/g

**Towards Phantom Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.6 V/m; Power Drift = 0.058 dB

Peak SAR (extrapolated) = 0.703 W/kg

**SAR(1 g) = 0.383 mW/g; SAR(10 g) = 0.221 mW/g**

Maximum value of SAR (measured) = 0.410 mW/g

**Towards Phantom Middle/Zoom Scan (7x7x7)/Cube 1:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.6 V/m; Power Drift = 0.058 dB

Peak SAR (extrapolated) = 0.440 W/kg

**SAR(1 g) = 0.274 mW/g; SAR(10 g) = 0.175 mW/g**

Maximum value of SAR (measured) = 0.290 mW/g




Figure 68 Body, Towards Phantom, WCDMA Band II Channel 9400



### WCDMA Band II with Earphone Towards Ground Low

Date/Time: 5/23/2011 8:04:09 PM

Communication System: WCDMA Band II; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 1852.4$  MHz;  $\sigma = 1.51$  mho/m;  $\epsilon_r = 52.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.77, 7.77, 7.77); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Ground Low/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.451 mW/g

**Towards Ground Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.1 V/m; Power Drift = 0.080 dB

Peak SAR (extrapolated) = 0.695 W/kg

**SAR(1 g) = 0.402 mW/g; SAR(10 g) = 0.241 mW/g**

Maximum value of SAR (measured) = 0.432 mW/g




Figure 69 Body with Earphone, Towards Ground, WCDMA Band II Channel 9262



### WCDMA Band II (Hot spots) Towards Ground High

Date/Time: 5/23/2011 6:42:22 PM

Communication System: WCDMA Band II; Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1908 \text{ MHz}$ ;  $\sigma = 1.57 \text{ mho/m}$ ;  $\epsilon_r = 52$ ;  $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature:  $22.3^\circ\text{C}$       Liquid Temperature:  $21.5^\circ\text{C}$

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.77, 7.77, 7.77); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Ground High/Area Scan (51x91x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

Maximum value of SAR (interpolated) =  $1.07 \text{ mW/g}$

**Towards Ground High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $12.4 \text{ V/m}$ ; Power Drift =  $0.046 \text{ dB}$

Peak SAR (extrapolated) =  $1.71 \text{ W/kg}$

**SAR(1 g) =  $0.938 \text{ mW/g}$ ; SAR(10 g) =  $0.536 \text{ mW/g}$**

Maximum value of SAR (measured) =  $1.00 \text{ mW/g}$




Figure 70 Body, Towards Ground, WCDMA Band II Channel 9538



### WCDMA Band II (Hot spots) Towards Ground Middle

Date/Time: 5/23/2011 6:29:44 PM

Communication System: WCDMA Band II; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.54$  mho/m;  $\epsilon_r = 52$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.77, 7.77, 7.77); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Ground Middle/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.10 mW/g

**Towards Ground Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 13.2 V/m; Power Drift = 0.048 dB

Peak SAR (extrapolated) = 1.72 W/kg

**SAR(1 g) = 0.955 mW/g; SAR(10 g) = 0.547 mW/g**

Maximum value of SAR (measured) = 1.02 mW/g




Figure 71 Body, Towards Ground, WCDMA Band II Channel 9400



### WCDMA Band II (Hot spots) Towards Ground Low

Date/Time: 5/23/2011 6:14:07 PM

Communication System: WCDMA Band II; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 1852.4$  MHz;  $\sigma = 1.51$  mho/m;  $\epsilon_r = 52.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.77, 7.77, 7.77); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Ground Low/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.10 mW/g


**Towards Ground Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 13.9 V/m; Power Drift = 0.058 dB

Peak SAR (extrapolated) = 1.74 W/kg

**SAR(1 g) = 0.965 mW/g; SAR(10 g) = 0.554 mW/g**

Maximum value of SAR (measured) = 1.03 mW/g






Figure 72 Body, Towards Ground, WCDMA Band II Channel 9262



### WCDMA Band II (Hot spots) Towards Phantom Middle

Date/Time: 5/23/2011 2:33:08 PM

Communication System: WCDMA Band II; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.54$  mho/m;  $\epsilon_r = 52$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.77, 7.77, 7.77); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Phantom Middle/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.679 mW/g

**Towards Phantom Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 12.9 V/m; Power Drift = 0.056 dB

Peak SAR (extrapolated) = 1.15 W/kg

**SAR(1 g) = 0.612 mW/g; SAR(10 g) = 0.345 mW/g**

Maximum value of SAR (measured) = 0.655 mW/g

**Towards Phantom Middle/Zoom Scan (7x7x7)/Cube 1:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 12.9 V/m; Power Drift = 0.056 dB

Peak SAR (extrapolated) = 0.635 W/kg

**SAR(1 g) = 0.404 mW/g; SAR(10 g) = 0.262 mW/g**

Maximum value of SAR (measured) = 0.426 mW/g




Figure 73 Body, Towards Phantom, WCDMA Band II Channel 9400



### WCDMA Band II (Hot spots) Left Edge Middle

Date/Time: 5/23/2011 3:33:27 PM

Communication System: WCDMA Band II; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.54$  mho/m;  $\epsilon_r = 52$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.77, 7.77, 7.77); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Left Edge Middle/Area Scan (41x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.305 mW/g

**Left Edge Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.7 V/m; Power Drift = 0.025 dB

Peak SAR (extrapolated) = 0.518 W/kg

**SAR(1 g) = 0.286 mW/g; SAR(10 g) = 0.164 mW/g**

Maximum value of SAR (measured) = 0.305 mW/g




Figure 74 Body, Left Edge, WCDMA Band II Channel 9400





### WCDMA Band II (Hot spots) Right Edge Middle

Date/Time: 5/23/2011 4:17:43 PM

Communication System: WCDMA Band II; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.54$  mho/m;  $\epsilon_r = 52$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.77, 7.77, 7.77); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Right Edge Middle/Area Scan (41x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.243 mW/g

**Right Edge Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.6 V/m; Power Drift = 0.030 dB

Peak SAR (extrapolated) = 0.378 W/kg

**SAR(1 g) = 0.214 mW/g; SAR(10 g) = 0.125 mW/g**

Maximum value of SAR (measured) = 0.231 mW/g




Figure 75 Body, Right Edge, WCDMA Band II Channel 9400



### WCDMA Band II (Hot spots) Bottom Edge Middle

Date/Time: 5/23/2011 5:00:52 PM

Communication System: WCDMA Band II; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.54$  mho/m;  $\epsilon_r = 52$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.77, 7.77, 7.77); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Bottom Edge Middle/Area Scan (41x61x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.461 mW/g

**Bottom Edge Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 17.3 V/m; Power Drift = 0.070 dB

Peak SAR (extrapolated) = 0.740 W/kg

**SAR(1 g) = 0.411 mW/g; SAR(10 g) = 0.233 mW/g**

Maximum value of SAR (measured) = 0.446 mW/g




Figure 76 Body, Bottom Edge, WCDMA Band II Channel 9400



### WCDMA Band II HSDPA (Hot spots) Towards Ground Low

Date/Time: 5/23/2011 8:46:12 PM

Communication System: WCDMA Band II+HSDPA; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 1852.4$  MHz;  $\sigma = 1.51$  mho/m;  $\epsilon_r = 52.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.77, 7.77, 7.77); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Ground Low/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.703 mW/g

**Towards Ground Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.5 V/m; Power Drift = 0.150 dB

Peak SAR (extrapolated) = 1.15 W/kg

**SAR(1 g) = 0.637 mW/g; SAR(10 g) = 0.364 mW/g**

Maximum value of SAR (measured) = 0.691 mW/g




Figure 77 Body, Towards Ground, WCDMA Band II HSDPA ,Channel 9262



### WCDMA Band V Left Cheek Middle

Date/Time: 5/22/2011 10:51:37 PM

Communication System: WCDMA Band V; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 837$  MHz;  $\sigma = 0.905$  mho/m;  $\epsilon_r = 41.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(9.5, 9.5, 9.5); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Cheek Middle/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.666 mW/g

**Cheek Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.47 V/m; Power Drift = -0.030 dB

Peak SAR (extrapolated) = 0.781 W/kg

**SAR(1 g) = 0.620 mW/g; SAR(10 g) = 0.456 mW/g**

Maximum value of SAR (measured) = 0.656 mW/g




Figure 78 Left Hand Touch Cheek WCDMA Band V Channel 4183



### WCDMA Band V Left Tilt Middle

Date/Time: 5/22/2011 9:29:34 PM

Communication System: WCDMA Band V; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 837$  MHz;  $\sigma = 0.905$  mho/m;  $\epsilon_r = 41.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(9.5, 9.5, 9.5); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Tilt Middle/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.366 mW/g

**Tilt Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 14.4 V/m; Power Drift = 0.047 dB

Peak SAR (extrapolated) = 0.418 W/kg

**SAR(1 g) = 0.350 mW/g; SAR(10 g) = 0.265 mW/g**

Maximum value of SAR (measured) = 0.366 mW/g




Figure 79 Left Hand Tilt 15° WCDMA Band V Channel 4183



### WCDMA Band V Right Cheek High

Date/Time: 5/22/2011 10:20:27 PM

Communication System: WCDMA Band V; Frequency: 846.6 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 847$  MHz;  $\sigma = 0.914$  mho/m;  $\epsilon_r = 41.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(9.5, 9.5, 9.5); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Cheek High/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.921 mW/g


**Cheek High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.1 V/m; Power Drift = 0.089 dB

Peak SAR (extrapolated) = 1.05 W/kg

**SAR(1 g) = 0.864 mW/g; SAR(10 g) = 0.639 mW/g**

Maximum value of SAR (measured) = 0.921 mW/g






Figure 80 Right Hand Touch Cheek WCDMA Band V Channel 4233



### WCDMA Band V Right Cheek Middle

Date/Time: 5/22/2011 9:53:48 PM

Communication System: WCDMA Band V; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 837$  MHz;  $\sigma = 0.905$  mho/m;  $\epsilon_r = 41.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(9.5, 9.5, 9.5); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Cheek Middle/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.916 mW/g

**Cheek Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.4 V/m; Power Drift = -0.106 dB

Peak SAR (extrapolated) = 1.04 W/kg

**SAR(1 g) = 0.863 mW/g; SAR(10 g) = 0.642 mW/g**

Maximum value of SAR (measured) = 0.913 mW/g




Figure 81 Right Hand Touch Cheek WCDMA Band V Channel 4183





### WCDMA Band V Right Cheek Low

Date/Time: 5/22/2011 10:07:32 PM

Communication System: WCDMA Band V; Frequency: 826.4 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 826.4$  MHz;  $\sigma = 0.895$  mho/m;  $\epsilon_r = 41.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(9.5, 9.5, 9.5); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Cheek Low/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.804 mW/g

**Cheek Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.65 V/m; Power Drift = -0.014 dB

Peak SAR (extrapolated) = 0.939 W/kg

**SAR(1 g) = 0.779 mW/g; SAR(10 g) = 0.580 mW/g**

Maximum value of SAR (measured) = 0.822 mW/g




Figure 82 Right Hand Touch Cheek WCDMA Band V Channel 4132



### WCDMA Band V Right Tilt Middle

Date/Time: 5/22/2011 10:33:45 PM

Communication System: WCDMA Band V; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 837$  MHz;  $\sigma = 0.905$  mho/m;  $\epsilon_r = 41.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(9.5, 9.5, 9.5); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Tilt Middle/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.412 mW/g

**Tilt Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 14.8 V/m; Power Drift = 0.015 dB

Peak SAR (extrapolated) = 0.470 W/kg

**SAR(1 g) = 0.398 mW/g; SAR(10 g) = 0.301 mW/g**

Maximum value of SAR (measured) = 0.419 mW/g




Figure 83 Right Hand Tilt 15° WCDMA Band V Channel 4183



### WCDMA Band V Towards Ground High

Date/Time: 5/21/2011 3:10:23 PM

Communication System: WCDMA Band V; Frequency: 846.6 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 847$  MHz;  $\sigma = 1.01$  mho/m;  $\epsilon_r = 56.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(10.33, 10.33, 10.33); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Ground High/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.693 mW/g

**Towards Ground High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.53 V/m; Power Drift = -0.022 dB

Peak SAR (extrapolated) = 0.839 W/kg

**SAR(1 g) = 0.657 mW/g; SAR(10 g) = 0.476 mW/g**

Maximum value of SAR (measured) = 0.697 mW/g




Figure 84 Body, Towards Ground, WCDMA Band V Channel 4233



## WCDMA Band V Towards Ground Middle

Date/Time: 5/21/2011 2:46:05 PM

Communication System: WCDMA Band V; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 837$  MHz;  $\sigma = 0.996$  mho/m;  $\epsilon_r = 56.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(10.33, 10.33, 10.33); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Ground Middle/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.776 mW/g


**Towards Ground Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.0 V/m; Power Drift = 0.084 dB

Peak SAR (extrapolated) = 0.946 W/kg

**SAR(1 g) = 0.741 mW/g; SAR(10 g) = 0.537 mW/g**

Maximum value of SAR (measured) = 0.790 mW/g






Figure 85 Body, Towards Ground, WCDMA Band V Channel 4183



### WCDMA Band V Towards Ground Low

Date/Time: 5/21/2011 2:58:16 PM

Communication System: WCDMA Band V; Frequency: 826.4 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 826.4$  MHz;  $\sigma = 0.987$  mho/m;  $\epsilon_r = 56.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(10.33, 10.33, 10.33); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Ground Low/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.648 mW/g

**Towards Ground Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.22 V/m; Power Drift = -0.026 dB

Peak SAR (extrapolated) = 0.789 W/kg

**SAR(1 g) = 0.616 mW/g; SAR(10 g) = 0.448 mW/g**

Maximum value of SAR (measured) = 0.656 mW/g




Figure 86 Body, Towards Ground, WCDMA Band V Channel 4132



### WCDMA Band V Towards Phantom Middle

Date/Time: 5/21/2011 2:22:45 PM

Communication System: WCDMA Band V; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 837$  MHz;  $\sigma = 0.996$  mho/m;  $\epsilon_r = 56.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(10.33, 10.33, 10.33); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Phantom Middle/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.596 mW/g

**Towards Phantom Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.81 V/m; Power Drift = -0.020 dB

Peak SAR (extrapolated) = 0.703 W/kg

**SAR(1 g) = 0.566 mW/g; SAR(10 g) = 0.417 mW/g**

Maximum value of SAR (measured) = 0.599 mW/g




Figure 87 Body, Towards Phantom, WCDMA Band V Channel 4183



### WCDMA Band V with Earphone Towards Ground Middle

Date/Time: 5/21/2011 10:07:26 AM

Communication System: WCDMA Band V; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 837$  MHz;  $\sigma = 0.996$  mho/m;  $\epsilon_r = 56.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(10.33, 10.33, 10.33); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Ground Middle/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.756 mW/g

**Towards Ground Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.5 V/m; Power Drift = -0.004 dB

Peak SAR (extrapolated) = 0.896 W/kg

**SAR(1 g) = 0.711 mW/g; SAR(10 g) = 0.521 mW/g**

Maximum value of SAR (measured) = 0.751 mW/g




Figure 88 Body with Earphone, Towards Ground, WCDMA Band V Channel 4183





### WCDMA Band V (Hot spots)Towards Ground High

Date/Time: 5/21/2011 7:44:15 PM

Communication System: WCDMA Band V; Frequency: 846.6 MHz;Duty Cycle: 1:1

Medium parameters used:  $f = 847 \text{ MHz}$ ;  $\sigma = 1.01 \text{ mho/m}$ ;  $\epsilon_r = 56.2$ ;  $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature:22.3 °C      Liquid Temperature: 21.5°C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(10.33, 10.33, 10.33); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Ground High/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.865 mW/g

**Towards Ground High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 25.4 V/m; Power Drift = 0.044 dB

Peak SAR (extrapolated) = 1.18 W/kg

**SAR(1 g) = 0.745 mW/g; SAR(10 g) = 0.515 mW/g**

Maximum value of SAR (measured) = 0.805 mW/g

**Towards Ground High/Zoom Scan (7x7x7)/Cube 1:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 25.4 V/m; Power Drift = 0.044 dB

Peak SAR (extrapolated) = 1.03 W/kg

**SAR(1 g) = 0.795 mW/g; SAR(10 g) = 0.570 mW/g**

Maximum value of SAR (measured) = 0.845 mW/g




Figure 89 Body, Towards Ground, WCDMA Band V Channel 4233



### WCDMA Band V (Hot spots)Towards Ground Middle

Date/Time: 5/21/2011 7:10:27 PM

Communication System: WCDMA Band V; Frequency: 836.6 MHz;Duty Cycle: 1:1

Medium parameters used:  $f = 837 \text{ MHz}$ ;  $\sigma = 0.996 \text{ mho/m}$ ;  $\epsilon_r = 56.2$ ;  $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature:22.3 °C      Liquid Temperature: 21.5°C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(10.33, 10.33, 10.33); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Ground Middle/Area Scan (51x91x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 1.14 mW/g

**Towards Ground Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 29.1 V/m; Power Drift = -0.015 dB

Peak SAR (extrapolated) = 1.37 W/kg

**SAR(1 g) = 0.866 mW/g; SAR(10 g) = 0.601 mW/g**

Maximum value of SAR (measured) = 0.933 mW/g


**Towards Ground Middle/Zoom Scan (7x7x7)/Cube 1:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 29.1 V/m; Power Drift = -0.015 dB

Peak SAR (extrapolated) = 1.19 W/kg

**SAR(1 g) = 0.918 mW/g; SAR(10 g) = 0.660 mW/g**

Maximum value of SAR (measured) = 0.974 mW/g







Figure 90 Body, Towards Ground, WCDMA Band V Channel 4183



### WCDMA Band V (Hot spots)Towards Ground Low

Date/Time: 5/21/2011 8:02:14 PM

Communication System: WCDMA Band V; Frequency: 826.4 MHz;Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 826.4$  MHz;  $\sigma = 0.987$  mho/m;  $\epsilon_r = 56.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature:22.3 °C      Liquid Temperature: 21.5°C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(10.33, 10.33, 10.33); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Ground Low/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.864 mW/g

**Towards Ground Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 25.1 V/m; Power Drift = 0.027 dB

Peak SAR (extrapolated) = 1.17 W/kg

**SAR(1 g) = 0.743 mW/g; SAR(10 g) = 0.517 mW/g**

Maximum value of SAR (measured) = 0.805 mW/g

**Towards Ground Low/Zoom Scan (7x7x7)/Cube 1:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 25.1 V/m; Power Drift = 0.027 dB

Peak SAR (extrapolated) = 1.01 W/kg

**SAR(1 g) = 0.781 mW/g; SAR(10 g) = 0.562 mW/g**

Maximum value of SAR (measured) = 0.831 mW/g




Figure 91 Body, Towards Ground, WCDMA Band V Channel 4132



### WCDMA Band V (Hot spots)Towards Phantom Middle

Date/Time: 5/21/2011 1:56:16 PM

Communication System: WCDMA Band V; Frequency: 836.6 MHz;Duty Cycle: 1:1

Medium parameters used:  $f = 837$  MHz;  $\sigma = 0.996$  mho/m;  $\epsilon_r = 56.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature:22.3 °C      Liquid Temperature: 21.5°C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(10.33, 10.33, 10.33); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Phantom Middle/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.818 mW/g

**Towards Phantom Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 26.4 V/m; Power Drift = -0.015 dB

Peak SAR (extrapolated) = 0.954 W/kg

**SAR(1 g) = 0.780 mW/g; SAR(10 g) = 0.578 mW/g**

Maximum value of SAR (measured) = 0.825 mW/g




Figure 92 Body, Towards Phantom, WCDMA Band V Channel 4183



### WCDMA Band V (Hot spots) Left Edge Middle

Date/Time: 5/21/2011 11:32:34 AM

Communication System: WCDMA Band V; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 837$  MHz;  $\sigma = 0.996$  mho/m;  $\epsilon_r = 56.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(10.33, 10.33, 10.33); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Left Edge Middle/Area Scan (41x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.466 mW/g

**Left Edge Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 22.2 V/m; Power Drift = 0.014 dB

Peak SAR (extrapolated) = 0.596 W/kg

**SAR(1 g) = 0.438 mW/g; SAR(10 g) = 0.301 mW/g**

Maximum value of SAR (measured) = 0.471 mW/g




Figure 93 Body, Left Edge, WCDMA Band V Channel 4183



### WCDMA Band V (Hot spots) Right Edge Middle

Date/Time: 5/21/2011 11:45:17 AM

Communication System: WCDMA Band V; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 837$  MHz;  $\sigma = 0.996$  mho/m;  $\epsilon_r = 56.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(10.33, 10.33, 10.33); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Right Edge Middle/Area Scan (41x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.529 mW/g

**Right Edge Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 23.5 V/m; Power Drift = 0.001 dB

Peak SAR (extrapolated) = 0.662 W/kg

**SAR(1 g) = 0.497 mW/g; SAR(10 g) = 0.347 mW/g**

Maximum value of SAR (measured) = 0.532 mW/g




Figure 94 Body, Right Edge, WCDMA Band V Channel 4183



### WCDMA Band V (Hot spots) Bottom Edge Middle

Date/Time: 5/21/2011 3:27:06 PM

Communication System: WCDMA Band V; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 837$  MHz;  $\sigma = 0.996$  mho/m;  $\epsilon_r = 56.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(10.33, 10.33, 10.33); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Bottom Edge Middle/Area Scan (41x61x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.120 mW/g

**Bottom Edge Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.4 V/m; Power Drift = -0.083 dB

Peak SAR (extrapolated) = 0.274 W/kg

**SAR(1 g) = 0.112 mW/g; SAR(10 g) = 0.061 mW/g**

Maximum value of SAR (measured) = 0.119 mW/g




Figure 95 Body, Bottom Edge, WCDMA Band V Channel 4183





### WCDMA Band V HSDPA (Hot spots) Towards Ground Middle

Date/Time: 5/21/2011 3:45:07 PM

Communication System: WCDMA Band V+HSDPA; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 837$  MHz;  $\sigma = 0.996$  mho/m;  $\epsilon_r = 56.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(10.33, 10.33, 10.33); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Ground Middle/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.753 mW/g

**Towards Ground Middle/Zoom Scan (7x7x7)/Cube 1:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 23.6 V/m; Power Drift = -0.009 dB

Peak SAR (extrapolated) = 0.886 W/kg

**SAR(1 g) = 0.689 mW/g; SAR(10 g) = 0.498 mW/g**

Maximum value of SAR (measured) = 0.729 mW/g




Figure 96 Body, Towards Ground, WCDMA Band V HSDPA, Channel 4183



### 802.11b Left Cheek Middle

Date/Time: 6/1/2011 6:42:31 PM

Communication System: 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2437 \text{ MHz}$ ;  $\sigma = 1.8 \text{ mho/m}$ ;  $\epsilon_r = 39.2$ ;  $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature:  $22.3^\circ\text{C}$       Liquid Temperature:  $21.5^\circ\text{C}$

Phantom section: Left Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.32, 7.32, 7.32); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Cheek Middle/Area Scan (51x91x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

Maximum value of SAR (interpolated) =  $0.182 \text{ mW/g}$

**Cheek Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $8.01 \text{ V/m}$ ; Power Drift =  $-0.046 \text{ dB}$

Peak SAR (extrapolated) =  $0.368 \text{ W/kg}$

**SAR(1 g) =  $0.165 \text{ mW/g}$ ; SAR(10 g) =  $0.083 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.178 \text{ mW/g}$




Figure 97 Left Hand Touch Cheek 802.11b Channel 6



### 802.11b Left Tilt Middle

Date/Time: 6/1/2011 6:57:35 PM

Communication System: 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2437$  MHz;  $\sigma = 1.8$  mho/m;  $\epsilon_r = 39.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.32, 7.32, 7.32); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Tilt Middle/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.174 mW/g

**Tilt Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.88 V/m; Power Drift = 0.107 dB

Peak SAR (extrapolated) = 0.349 W/kg

**SAR(1 g) = 0.165 mW/g; SAR(10 g) = 0.082 mW/g**

Maximum value of SAR (measured) = 0.175 mW/g




Figure 98 Left Hand Tilt 15° 802.11b Channel 6



### 802.11b Right Cheek High

Date/Time: 6/1/2011 7:17:55 PM

Communication System: 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2462 \text{ MHz}$ ;  $\sigma = 1.83 \text{ mho/m}$ ;  $\epsilon_r = 39.1$ ;  $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature:  $22.3^\circ\text{C}$       Liquid Temperature:  $21.5^\circ\text{C}$

Phantom section: Right Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.32, 7.32, 7.32); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Cheek High/Area Scan (51x91x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

Maximum value of SAR (interpolated) =  $0.349 \text{ mW/g}$

**Cheek High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $5.76 \text{ V/m}$ ; Power Drift =  $0.000 \text{ dB}$

Peak SAR (extrapolated) =  $0.750 \text{ W/kg}$

**SAR(1 g) =  $0.327 \text{ mW/g}$ ; SAR(10 g) =  $0.152 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.361 \text{ mW/g}$




Figure 99 Right Hand Touch Cheek 802.11b Channel 11



### 802.11b Right Cheek Middle

Date/Time: 6/1/2011 6:13:16 PM

Communication System: 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2437 \text{ MHz}$ ;  $\sigma = 1.8 \text{ mho/m}$ ;  $\epsilon_r = 39.2$ ;  $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature:  $22.3^\circ\text{C}$  Liquid Temperature:  $21.5^\circ\text{C}$

Phantom section: Right Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.32, 7.32, 7.32); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Cheek Middle/Area Scan (51x91x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

Maximum value of SAR (interpolated) =  $0.374 \text{ mW/g}$


**Cheek Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $5.88 \text{ V/m}$ ; Power Drift =  $0.050 \text{ dB}$

Peak SAR (extrapolated) =  $0.831 \text{ W/kg}$

**SAR(1 g) =  $0.363 \text{ mW/g}$ ; SAR(10 g) =  $0.168 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.405 \text{ mW/g}$






Figure 100 Right Hand Touch Cheek 802.11b Channel 6



### 802.11b Right Cheek Low

Date/Time: 6/1/2011 7:31:55 PM

Communication System: 802.11b; Frequency: 2412 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2412$  MHz;  $\sigma = 1.77$  mho/m;  $\epsilon_r = 39.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.32, 7.32, 7.32); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Cheek Low/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.348 mW/g

**Cheek Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.30 V/m; Power Drift = 0.156 dB

Peak SAR (extrapolated) = 0.732 W/kg

**SAR(1 g) = 0.321 mW/g; SAR(10 g) = 0.150 mW/g**

Maximum value of SAR (measured) = 0.350 mW/g




Figure 101 Right Hand Touch Cheek 802.11b Channel 1



### 802.11b Right Tilt Middle

Date/Time: 6/1/2011 6:25:47 PM

Communication System: 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2437$  MHz;  $\sigma = 1.8$  mho/m;  $\epsilon_r = 39.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.32, 7.32, 7.32); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Tilt Middle/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.254 mW/g

**Tilt Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.67 V/m; Power Drift = 0.115 dB

Peak SAR (extrapolated) = 0.600 W/kg

**SAR(1 g) = 0.260 mW/g; SAR(10 g) = 0.122 mW/g**

Maximum value of SAR (measured) = 0.279 mW/g




Figure 102 Right Hand Tilt 15° 802.11b Channel 6





### 802.11b Towards Ground High

Date/Time: 6/1/2011 8:46:31 PM

Communication System: 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2462 \text{ MHz}$ ;  $\sigma = 1.96 \text{ mho/m}$ ;  $\epsilon_r = 51.2$ ;  $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature:  $22.3^\circ\text{C}$       Liquid Temperature:  $21.5^\circ\text{C}$

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.46, 7.46, 7.46); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Ground High/Area Scan (51x91x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

Maximum value of SAR (interpolated) =  $0.098 \text{ mW/g}$

**Towards Ground High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $5.96 \text{ V/m}$ ; Power Drift =  $0.121 \text{ dB}$

Peak SAR (extrapolated) =  $0.199 \text{ W/kg}$

**SAR(1 g) =  $0.088 \text{ mW/g}$ ; SAR(10 g) =  $0.047 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.092 \text{ mW/g}$




Figure 103 Body, Towards Ground, 802.11b Channel 11



### 802.11b Towards Ground Middle

Date/Time: 6/1/2011 8:30:32 PM

Communication System: 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2437$  MHz;  $\sigma = 1.93$  mho/m;  $\epsilon_r = 51.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.46, 7.46, 7.46); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Ground Middle/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.101 mW/g


**Towards Ground Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 6.10 V/m; Power Drift = -0.141 dB

Peak SAR (extrapolated) = 0.211 W/kg

**SAR(1 g) = 0.094 mW/g; SAR(10 g) = 0.048 mW/g**

Maximum value of SAR (measured) = 0.098 mW/g






Figure 104 Body, Towards Ground, 802.11b Channel 6



### 802.11b Towards Ground Low

Date/Time: 6/1/2011 9:00:08 PM

Communication System: 802.11b; Frequency: 2412 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2412$  MHz;  $\sigma = 1.89$  mho/m;  $\epsilon_r = 51.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.46, 7.46, 7.46); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Ground Low/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.088 mW/g

**Towards Ground Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.93 V/m; Power Drift = 0.056 dB

Peak SAR (extrapolated) = 0.186 W/kg

**SAR(1 g) = 0.083 mW/g; SAR(10 g) = 0.045 mW/g**

Maximum value of SAR (measured) = 0.088 mW/g




Figure 105 Body, Towards Ground, 802.11b Channel 1



### 802.11b Towards Phantom Middle

Date/Time: 6/1/2011 8:15:34 PM

Communication System: 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2437$  MHz;  $\sigma = 1.93$  mho/m;  $\epsilon_r = 51.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.46, 7.46, 7.46); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Phantom Middle/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.042 mW/g

**Towards Phantom Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 4.07 V/m; Power Drift = 0.080 dB

Peak SAR (extrapolated) = 0.077 W/kg

**SAR(1 g) = 0.037 mW/g; SAR(10 g) = 0.021 mW/g**

Maximum value of SAR (measured) = 0.039 mW/g




Figure 106 Body, Towards Phantom, 802.11b Channel 6



### 802.11b with Earphone Towards Ground Middle

Date/Time: 6/1/2011 9:14:43 PM

Communication System: 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2437 \text{ MHz}$ ;  $\sigma = 1.93 \text{ mho/m}$ ;  $\epsilon_r = 51.2$ ;  $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature:  $22.3^\circ\text{C}$       Liquid Temperature:  $21.5^\circ\text{C}$

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.46, 7.46, 7.46); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Ground Middle/Area Scan (51x91x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

Maximum value of SAR (interpolated) =  $0.039 \text{ mW/g}$

**Towards Ground Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $3.63 \text{ V/m}$ ; Power Drift =  $-0.096 \text{ dB}$

Peak SAR (extrapolated) =  $0.085 \text{ W/kg}$

**SAR(1 g) =  $0.035 \text{ mW/g}$ ; SAR(10 g) =  $0.019 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.037 \text{ mW/g}$




Figure 107 Body with earphone, Towards Ground, 802.11b Channel 6



### 802.11b (Hot spots) Towards Ground High

Date/Time: 6/1/2011 11:24:58 PM

Communication System: 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2462$  MHz;  $\sigma = 1.96$  mho/m;  $\epsilon_r = 51.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.46, 7.46, 7.46); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Ground High/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.160 mW/g

**Towards Ground High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.05 V/m; Power Drift = 0.146 dB

Peak SAR (extrapolated) = 0.373 W/kg

**SAR(1 g) = 0.157 mW/g; SAR(10 g) = 0.080 mW/g**

Maximum value of SAR (measured) = 0.161 mW/g




Figure 108 Body, Towards Ground, 802.11b Channel 11



### 802.11b (Hot spots) Towards Ground Middle

Date/Time: 6/1/2011 11:11:43 PM

Communication System: 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2437$  MHz;  $\sigma = 1.93$  mho/m;  $\epsilon_r = 51.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.46, 7.46, 7.46); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Ground Middle/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.161 mW/g

**Towards Ground Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.05 V/m; Power Drift = 0.066 dB

Peak SAR (extrapolated) = 0.371 W/kg

**SAR(1 g) = 0.155 mW/g; SAR(10 g) = 0.081 mW/g**

Maximum value of SAR (measured) = 0.160 mW/g




Figure 109 Body, Towards Ground, 802.11b Channel 6





### 802.11b (Hot spots) Towards Ground Low

Date/Time: 6/1/2011 11:39:41 PM

Communication System: 802.11b; Frequency: 2412 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2412$  MHz;  $\sigma = 1.89$  mho/m;  $\epsilon_r = 51.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.46, 7.46, 7.46); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Ground Low/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.175 mW/g


**Towards Ground Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.28 V/m; Power Drift = 0.182 dB

Peak SAR (extrapolated) = 0.403 W/kg

**SAR(1 g) = 0.173 mW/g; SAR(10 g) = 0.091 mW/g**

Maximum value of SAR (measured) = 0.178 mW/g






Figure 110 Body, Towards Ground, 802.11b Channel 1



### 802.11b (Hot spots) Towards Phantom Middle

Date/Time: 6/1/2011 10:55:39 PM

Communication System: 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2437$  MHz;  $\sigma = 1.93$  mho/m;  $\epsilon_r = 51.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.46, 7.46, 7.46); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Towards Phantom Middle/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.067 mW/g

**Towards Phantom Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.72 V/m; Power Drift = -0.007 dB

Peak SAR (extrapolated) = 0.130 W/kg

**SAR(1 g) = 0.061 mW/g; SAR(10 g) = 0.033 mW/g**

Maximum value of SAR (measured) = 0.066 mW/g




Figure 111 Body, Towards Phantom, 802.11b Channel 6



### 802.11b (Hot spots) Left Edge Middle

Date/Time: 6/1/2011 10:04:51 PM

Communication System: 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2437 \text{ MHz}$ ;  $\sigma = 1.93 \text{ mho/m}$ ;  $\epsilon_r = 51.2$ ;  $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature:  $22.3^\circ\text{C}$       Liquid Temperature:  $21.5^\circ\text{C}$

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.46, 7.46, 7.46); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Left Edge Middle/Area Scan (41x91x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

Maximum value of SAR (interpolated) =  $0.050 \text{ mW/g}$

**Left Edge Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $5.16 \text{ V/m}$ ; Power Drift =  $0.141 \text{ dB}$

Peak SAR (extrapolated) =  $0.104 \text{ W/kg}$

**SAR(1 g) =  $0.048 \text{ mW/g}$ ; SAR(10 g) =  $0.026 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.050 \text{ mW/g}$




Figure 112 Body, Left Edge, 802.11b Channel 6



### 802.11b (Hot spots) Right Edge Middle

Date/Time: 6/1/2011 9:48:24 PM

Communication System: 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2437$  MHz;  $\sigma = 1.93$  mho/m;  $\epsilon_r = 51.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.46, 7.46, 7.46); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Right Edge Middle/Area Scan (41x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.014 mW/g

**Right Edge Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.61 V/m; Power Drift = -0.142 dB

Peak SAR (extrapolated) = 0.028 W/kg

**SAR(1 g) = 0.014 mW/g; SAR(10 g) = 0.008 mW/g**

Maximum value of SAR (measured) = 0.014 mW/g




Figure 113 Body, Right Edge, 802.11b Channel 6



### 802.11b (Hot spots) Top Edge Middle

Date/Time: 6/1/2011 10:23:17 PM

Communication System: 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2437$  MHz;  $\sigma = 1.93$  mho/m;  $\epsilon_r = 51.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.3 °C      Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY4 Configuration:

Probe: EX3DV4 - SN3677; ConvF(7.46, 7.46, 7.46); Calibrated: 11/24/2010

Electronics: DAE4 Sn871; Calibrated: 11/18/2010

Phantom: SAM000 T01; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Top Edge Middle/Area Scan (41x61x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.075 mW/g

**Top Edge Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.58 V/m; Power Drift = -0.051 dB

Peak SAR (extrapolated) = 0.153 W/kg

**SAR(1 g) = 0.069 mW/g; SAR(10 g) = 0.036 mW/g**

Maximum value of SAR (measured) = 0.075 mW/g




Figure 114 Body, Top Edge, 802.11b Channel 6



## ANNEX D: Probe Calibration Certificate

Calibration Laboratory of  
Schmid & Partner  
Engineering AG  
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst  
C Service suisse d'étalonnage  
S Servizio svizzero di taratura  
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 108

Client **TA-SH (Auden)**

Certificate No: **EX3-3677\_Nov10**

### CALIBRATION CERTIFICATE

Object **EX3DV4 - SN:3677**

Calibration procedure(s) **QA CAL-01.v6, QA CAL-14.v3, QA CAL-23.v3 and QA CAL-25.v2  
Calibration procedure for dosimetric E-field probes**

Calibration date: **November 24, 2010**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature ( $22 \pm 3$ )°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards          | ID #            | Cal Date (Certificate No.)        | Scheduled Calibration  |
|----------------------------|-----------------|-----------------------------------|------------------------|
| Power meter E4419B         | GB41293874      | 1-Apr-10 (No. 217-01136)          | Apr-11                 |
| Power sensor E4412A        | MY41495277      | 1-Apr-10 (No. 217-01136)          | Apr-11                 |
| Power sensor E4412A        | MY41498087      | 1-Apr-10 (No. 217-01136)          | Apr-11                 |
| Reference 3 dB Attenuator  | SN: S5054 (3c)  | 30-Mar-10 (No. 217-01159)         | Mar-11                 |
| Reference 20 dB Attenuator | SN: S5086 (20b) | 30-Mar-10 (No. 217-01161)         | Mar-11                 |
| Reference 30 dB Attenuator | SN: S5129 (30b) | 30-Mar-10 (No. 217-01160)         | Mar-11                 |
| Reference Probe ES3DV2     | SN: 3013        | 30-Dec-09 (No. ES3-3013_Dec09)    | Dec-10                 |
| DAE4                       | SN: 660         | 20-Apr-10 (No. DAE4-660_Apr10)    | Apr-11                 |
| Secondary Standards        | ID #            | Check Date (in house)             | Scheduled Check        |
| RF generator HP 8648C      | US3642U01700    | 4-Aug-99 (in house check Oct-09)  | In house check: Oct-11 |
| Network Analyzer HP 8753E  | US37390585      | 18-Oct-01 (in house check Oct-10) | In house check: Oct-11 |

|                |                              |                                      |               |
|----------------|------------------------------|--------------------------------------|---------------|
| Calibrated by: | Name<br><b>Katja Pokovic</b> | Function<br><b>Technical Manager</b> | Signature<br> |
| Approved by:   | Name<br><b>Niels Kuster</b>  | Function<br><b>Quality Manager</b>   | Signature<br> |

Issued: November 25, 2010

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.





Calibration Laboratory of  
Schmid & Partner  
Engineering AG  
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst  
C Service suisse d'étalonnage  
S Servizio svizzero di taratura  
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 108

#### Glossary:

|                          |                                                                                                                                                         |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| TSL                      | tissue simulating liquid                                                                                                                                |
| NORM <sub>x,y,z</sub>    | sensitivity in free space                                                                                                                               |
| ConvF                    | sensitivity in TSL / NORM <sub>x,y,z</sub>                                                                                                              |
| DCP                      | diode compression point                                                                                                                                 |
| CF                       | crest factor (1/duty_cycle) of the RF signal                                                                                                            |
| A, B, C                  | modulation dependent linearization parameters                                                                                                           |
| Polarization $\phi$      | $\phi$ rotation around probe axis                                                                                                                       |
| Polarization $\vartheta$ | $\vartheta$ rotation around an axis that is in the plane normal to probe axis (at measurement center),<br>i.e., $\vartheta = 0$ is normal to probe axis |

#### Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

#### Methods Applied and Interpretation of Parameters:

- NORM<sub>x,y,z</sub>:** Assessed for E-field polarization  $\vartheta = 0$  ( $f \leq 900$  MHz in TEM-cell;  $f > 1800$  MHz: R22 waveguide). NORM<sub>x,y,z</sub> are only intermediate values, i.e., the uncertainties of NORM<sub>x,y,z</sub> does not effect the E<sup>2</sup>-field uncertainty inside TSL (see below ConvF).
- NORM(*f*)<sub>x,y,z</sub> = NORM<sub>x,y,z</sub> \* frequency\_response** (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP<sub>x,y,z</sub>:** DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- A<sub>x,y,z</sub>; B<sub>x,y,z</sub>; C<sub>x,y,z</sub>; VR<sub>x,y,z</sub>:** A, B, C are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters:** Assessed in flat phantom using E-field (or Temperature Transfer Standard for  $f \leq 800$  MHz) and inside waveguide using analytical field distributions based on power measurements for  $f > 800$  MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM<sub>x,y,z</sub> \* ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from  $\pm 50$  MHz to  $\pm 100$  MHz.
- Spherical isotropy (3D deviation from isotropy):** in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset:** The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.





EX3DV4 SN:3677

November 24, 2010

# Probe EX3DV4

## SN:3677

|                  |                    |
|------------------|--------------------|
| Manufactured:    | September 9, 2008  |
| Last calibrated: | September 23, 2009 |
| Recalibrated:    | November 24, 2010  |

Calibrated for DASY/EASY Systems

(Note: non-compatible with DASY2 system!)



EX3DV4 SN:3677

November 24, 2010

### DASY/EASY - Parameters of Probe: EX3DV4 SN:3677

#### Basic Calibration Parameters

|                                                           | Sensor X | Sensor Y | Sensor Z | Unc (k=2)    |
|-----------------------------------------------------------|----------|----------|----------|--------------|
| Norm ( $\mu\text{V}/(\text{V}/\text{m})^2$ ) <sup>A</sup> | 0.41     | 0.47     | 0.39     | $\pm 10.1\%$ |
| DCP (mV) <sup>B</sup>                                     | 96.8     | 98.9     | 98.8     |              |

#### Modulation Calibration Parameters

| UID   | Communication System Name | PAR  |   | A<br>dB | B<br>dBuV | C    | VR<br>mV | Unc <sup>E</sup><br>(k=2) |
|-------|---------------------------|------|---|---------|-----------|------|----------|---------------------------|
| 10000 | CW                        | 0.00 | X | 0.00    | 0.00      | 1.00 | 143.2    | $\pm 2.4\%$               |
|       |                           |      | Y | 0.00    | 0.00      | 1.00 | 140.9    |                           |
|       |                           |      | Z | 0.00    | 0.00      | 1.00 | 135.8    |                           |

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

<sup>A</sup> The uncertainties of NormX, Y, Z do not affect the E<sup>2</sup>-field uncertainty inside TSL (see Pages 5 and 6).

<sup>B</sup> Numerical linearization parameter: uncertainty not required.

<sup>E</sup> Uncertainty is determined using the maximum deviation from linear response applying rectangular distribution and is expressed for the square of the field value.



EX3DV4 SN:3677

November 24, 2010

## DASY/EASY - Parameters of Probe: EX3DV4 SN:3677

### Calibration Parameter Determined in Head Tissue Simulating Media

| f [MHz] | Validity [MHz] <sup>c</sup> | Permittivity | Conductivity | ConvF X | ConvF Y | ConvF Z | Alpha | Depth Unc (k=2) |
|---------|-----------------------------|--------------|--------------|---------|---------|---------|-------|-----------------|
| 450     | ± 50 / ± 100                | 43.5 ± 5%    | 0.87 ± 5%    | 10.04   | 10.04   | 10.04   | 0.09  | 1.00 ± 13.3%    |
| 835     | ± 50 / ± 100                | 41.5 ± 5%    | 0.90 ± 5%    | 9.50    | 9.50    | 9.50    | 0.72  | 0.64 ± 11.0%    |
| 1750    | ± 50 / ± 100                | 40.1 ± 5%    | 1.37 ± 5%    | 8.22    | 8.22    | 8.22    | 0.72  | 0.59 ± 11.0%    |
| 1900    | ± 50 / ± 100                | 40.0 ± 5%    | 1.40 ± 5%    | 7.94    | 7.94    | 7.94    | 0.81  | 0.57 ± 11.0%    |
| 2450    | ± 50 / ± 100                | 39.2 ± 5%    | 1.80 ± 5%    | 7.32    | 7.32    | 7.32    | 0.47  | 0.75 ± 11.0%    |

<sup>c</sup> The validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2). The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.



EX3DV4 SN:3677

November 24, 2010

## DASY/EASY - Parameters of Probe: EX3DV4 SN:3677

### Calibration Parameter Determined in Body Tissue Simulating Media

| f [MHz] | Validity [MHz] <sup>C</sup> | Permittivity | Conductivity | ConvF X | ConvF Y | ConvF Z | Alpha | Depth Unc (k=2) |
|---------|-----------------------------|--------------|--------------|---------|---------|---------|-------|-----------------|
| 450     | ± 50 / ± 100                | 56.7 ± 5%    | 0.94 ± 5%    | 10.62   | 10.62   | 10.62   | 0.02  | 1.00 ± 13.3%    |
| 750     | ± 50 / ± 100                | 55.5 ± 5%    | 0.96 ± 5%    | 10.14   | 10.14   | 10.14   | 0.59  | 0.72 ± 11.0%    |
| 835     | ± 50 / ± 100                | 55.2 ± 5%    | 0.97 ± 5%    | 10.33   | 10.33   | 10.33   | 0.20  | 2.06 ± 11.0%    |
| 1450    | ± 50 / ± 100                | 54.0 ± 5%    | 1.30 ± 5%    | 8.47    | 8.47    | 8.47    | 0.99  | 0.53 ± 11.0%    |
| 1750    | ± 50 / ± 100                | 53.4 ± 5%    | 1.49 ± 5%    | 8.02    | 8.02    | 8.02    | 0.63  | 0.67 ± 11.0%    |
| 1900    | ± 50 / ± 100                | 53.3 ± 5%    | 1.52 ± 5%    | 7.77    | 7.77    | 7.77    | 0.69  | 0.67 ± 11.0%    |
| 2100    | ± 50 / ± 100                | 53.2 ± 5%    | 1.62 ± 5%    | 8.04    | 8.04    | 8.04    | 0.16  | 1.44 ± 11.0%    |
| 2450    | ± 50 / ± 100                | 52.7 ± 5%    | 1.95 ± 5%    | 7.46    | 7.46    | 7.46    | 0.99  | 0.49 ± 11.0%    |
| 3500    | ± 50 / ± 100                | 51.3 ± 5%    | 3.31 ± 5%    | 6.61    | 6.61    | 6.61    | 0.28  | 1.40 ± 13.1%    |

<sup>C</sup> The validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2). The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.