



TEST REPORT

No. 2013TAR607

for

TCT Mobile Limited

HSUPA/HSDPA/UMTS triband/GSM quadband mobile phone

Model Name: Yaris-4.5 US 1SIM ATV

Marketing Name: ONE TOUCH 5036A

FCC ID: RAD412

with

Hardware Version: proto

Software Version: vF06

Issued Date: 2013-09-13

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of TMC Beijing.

Test Laboratory:

DAR accreditation (DIN EN ISO/IEC 17025): No. D-PL-12123-01-01

FCC 2.948 Listed: No.733176

IC O.A.T.S listed: No.6629B

TMC Beijing, Telecommunication Metrology Center of Ministry of Industry and Information Technology

3/F Shou Xiang Technology Building, No.51 Xueyuan Road, Hai Dian District, Beijing, P. R. China,100191.

Tel:+86(0)10-62304633-2604, Fax:+86(0)10-62304633, Email:welcome@emcite.com, web: www.emcite.com

CONTENTS

| | |
|---|-----------|
| 1. TEST LABORATORY | 3 |
| 1.1. TESTING LOCATION | 3 |
| 1.2. TESTING ENVIRONMENT | 3 |
| 1.3. PROJECT DATA | 3 |
| 1.4. SIGNATURE | 3 |
| 2. CLIENT INFORMATION..... | 4 |
| 2.1. APPLICANT INFORMATION..... | 4 |
| 2.2. MANUFACTURER INFORMATION..... | 4 |
| 3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) | 5 |
| 3.1. ABOUT EUT | 5 |
| 3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST | 5 |
| 3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST | 5 |
| 3.4. NORMAL ACCESSORY SETTING..... | 6 |
| 3.5. GENERAL DESCRIPTION | 6 |
| 4. REFERENCE DOCUMENTS | 7 |
| 4.1. REFERENCE DOCUMENTS FOR TESTING..... | 7 |
| 5. LABORATORY ENVIRONMENT..... | 8 |
| 6. SUMMARY OF TEST RESULTS | 9 |
| 7. TEST EQUIPMENTS UTILIZED | 10 |
| ANNEX A: MEASUREMENT RESULTS..... | 11 |
| A.1 OUTPUT POWER..... | 11 |
| A.2 EMISSION LIMIT..... | 15 |
| A.3 CONDUCTED EMISSION | 20 |
| A.4 FREQUENCY STABILITY | 27 |
| A.5 OCCUPIED BANDWIDTH | 29 |
| A.6 EMISSION BANDWIDTH | 33 |
| A.7 BAND EDGE COMPLIANCE..... | 37 |
| A.8 CONDUCTED SPURIOUS EMISSION | 39 |

1. Test Laboratory

1.1. Testing Location

Company Name: TMC Beijing, Telecommunication Metrology Center of MIIT
Address: 3/F Shou Xiang Technology Building, No.51 Xueyuan Road, Hai
Dian District, Beijing, P. R. China
Postal Code: 100191
Telephone: 00861062304633
Fax: 00861062304633


1.2. Testing Environment

Normal Temperature: 15-35°C
Relative Humidity: 20-75%


1.3. Project data

Testing Start Date: 2013-08-15
Testing End Date: 2013-09-10

1.4. Signature



Zi Xiaogang
(Prepared this test report)



Sun Xiangqian
(Reviewed this test report)



Lu Bingsong
Deputy Director of the laboratory
(Approved this test report)

2. Client Information

2.1. Applicant Information

Company Name: TCT Mobile Limited
Address /Post: 5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,
Pudong Area Shanghai, P.R. China.
City: Shanghai
Postal Code: 201203
Country: China
Contact Person: Gong Zhizhou
Contact Email: zhizhou.gong@jrdcom.com
Telephone: 0086-21-61460890
Fax: 0086-21-61460602

2.2. Manufacturer Information

Company Name: TCT Mobile Limited
Address /Post: 5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,
Pudong Area Shanghai, P.R. China.
City: Shanghai
Postal Code: 201203
Country: China
Telephone: 0086-21-61460890
Fax: 0086-21-61460602

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

| | |
|-------------------------|---|
| Description | HSUPA/HSDPA/UMTS triband/GSM quadband mobile phone |
| Model Name | Yaris-4.5 US 1SIM ATV |
| Marketing Name | ONE TOUCH 5036A |
| FCC ID | RAD412 |
| Frequency | GSM 850MHz; PCS 1900MHz; WCDMA Band V;WCDMA BAND II |
| HSDPA category | 10 |
| HSUPA category | 6 |
| Antenna | Integrated |
| Power supply | Battery or Charger (AC Adaptor) |
| Output power | 25.44dBm maximum EIRP measured for Band II |
| Extreme vol. Limits | 3.5VDC to 4.2VDC (nominal: 3.8VDC) |
| Extreme temp. Tolerance | -30°C to +50°C |

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of Telecommunication Metrology Center of MIIT of People's Republic of China.

3.2. Internal Identification of EUT used during the test

| EUT ID* | IMEI | HW Version | SW Version |
|----------------|-----------------|-------------------|-------------------|
| N20 | 013822000000358 | proto | vF06 |
| N19 | 013822000000077 | proto | vF06 |

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

| AE ID* | Description | |
|---------------|--------------------|---|
| AE1 | Battery | / |
| AE2 | Battery | / |
| AE3 | Travel charger | / |
| AE4 | Travel charger | / |

AE1

| | |
|-----------------|--------------|
| Model | CAB32E0000C1 |
| Manufacturer | BYD |
| Capacitance | 1800 mAh |
| Nominal voltage | 3.7V |

AE2

| | |
|--------------|--------------|
| Model | CAB32E0000C2 |
| Manufacturer | SCUD |
| Capacitance | 1800 mAh |

| | |
|-----------------|--------------|
| Nominal voltage | 3.7V |
| AE3 | |
| Model | CBA3007AG0C1 |
| Manufacturer | BYD |
| Length of cable | / |
| AE4 | |
| Model | CBA3007AG0C2 |
| Manufacturer | Tenpao |
| Length of cable | / |

*AE ID: is used to identify the test sample in the lab internally..

3.4. Normal Accessory setting

Fully charged battery was used during the test.

3.5. General Description

The Equipment Under Test (EUT) is a model of HSUPA/HSDPA/UMTS triband/GSM quadband mobile phone with integrated antenna. Manual and specifications of the EUT were provided to fulfil the test. Samples undergoing test were selected by the Client.

4. Reference Documents

4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

| Reference | Title | Version |
|----------------|--|--------------------|
| ANSI/TIA-603-C | Land Mobile FM or PM Communications Equipment Measurement and Performance Standards | 2004 |
| ANSI C63.4 | Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz | 2003 |
| FCC Part 2 | FREQUENCY ALLOCATIONS AND RADIO TREATY MATTERS; GENERAL RULES AND REGULATIONS | 10-1-12 Edition |
| FCC Part 24 | PERSONAL COMMUNICATIONS SERVICES | 10-1-12 Edition |
| FCC Part 22 | PUBLIC MOBILE SERVICES | 10-1-12 Edition |
| FCC Part 27 | MISCELLANEOUS WIRELESS COMMUNICATIONS SERVICES | 10-1-12 Edition |
| KDB971168 D01 | Procedures for Compliance Measurement of the Fundamental Emission Power of Licensed Wideband (> 1 MHz) Digital Transmission Systems | 2011 |

5. LABORATORY ENVIRONMENT

Control room / conducted chamber did not exceed following limits along the EMC testing:

| | |
|--------------------------|----------------------------|
| Temperature | Min. = 15 °C, Max. = 35 °C |
| Relative humidity | Min. = 20 %, Max. = 80 % |
| Shielding effectiveness | > 110 dB |
| Electrical insulation | > 2 MΩ |
| Ground system resistance | < 0.5 Ω |

Fully-anechoic chamber 2 (8.6 meters X 6.1 meters X 3.85 meters) did not exceed following limits along the EMC testing:

| | |
|---|---|
| Temperature | Min. = 15 °C, Max. = 30 °C |
| Relative humidity | Min. = 35 %, Max. = 60 % |
| Shielding effectiveness | > 110 dB |
| Electrical insulation | > 2 MΩ |
| Ground system resistance | < 1 Ω |
| Site voltage standing-wave ratio (S_{VSWR}) | Between 0 and 6 dB, from 1GHz to 18GHz |
| Uniformity of field strength | Between 0 and 6 dB, from 80 to 4000 MHz |

Semi-anechoic chamber 2 / Fully-anechoic chamber 3 (10 meters X 6.7 meters X 6.15 meters) did not exceed following limits along the EMC testing:

| | |
|---|---|
| Temperature | Min. = 15 °C, Max. = 30 °C |
| Relative humidity | Min. = 35 %, Max. = 60 % |
| Shielding effectiveness | > 100 dB |
| Electrical insulation | > 2 MΩ |
| Ground system resistance | < 0.5 Ω |
| Normalised site attenuation (NSA) | < ±3.5 dB, 3 m distance |
| Site voltage standing-wave ratio (S_{VSWR}) | Between 0 and 6 dB, from 1GHz to 18GHz |
| Uniformity of field strength | Between 0 and 6 dB, from 80 to 3000 MHz |

6. SUMMARY OF TEST RESULTS

WCDMA Band V

| Items | Test Name | Section in this report | Verdict |
|-------|-----------------------------|------------------------|---------|
| 1 | Output Power | A.1 | P |
| 2 | Emission Limit | A.2 | P |
| 3 | CONDUCTED EMISSION | A.3 | P |
| 4 | Frequency Stability | A.4 | P |
| 5 | Occupied Bandwidth | A.5 | P |
| 6 | Emission Bandwidth | A.6 | P |
| 7 | Band Edge Compliance | A.7 | P |
| 8 | Conducted Spurious Emission | A.8 | P |
| 9 | PEAK-TO-AVERAGE POWER RATIO | A.9 | P |

WCDMA Band II

| Items | Test Name | Section in this report | Verdict |
|-------|-----------------------------|------------------------|---------|
| 1 | Output Power | A.1 | P |
| 2 | Emission Limit | A.2 | P |
| 3 | CONDUCTED EMISSION | A.3 | P |
| 4 | Frequency Stability | A.4 | P |
| 5 | Occupied Bandwidth | A.5 | P |
| 6 | Emission Bandwidth | A.6 | P |
| 7 | Band Edge Compliance | A.7 | P |
| 8 | Conducted Spurious Emission | A.8 | P |
| 9 | PEAK-TO-AVERAGE POWER RATIO | A.9 | P |

7. Test Equipments Utilized

| NO. | Description | TYPE | SERIES NUMBER | MANUFACTURE | CAL DUE DATE |
|-----|--------------------------------------|-----------|---------------|--------------|--------------|
| 1 | Test Receiver | ESCI | 100344 | R&S | 2014-03-28 |
| 2 | Test Receiver | ESU26 | 100376 | R&S | 2013-11-07 |
| 3 | EMI Antenna | VULB 9163 | 514 | Schwarzbeck | 2014-11-10 |
| 4 | EMI Antenna | 3117 | 00139065 | ETS-Lindgren | 2014-07-31 |
| 5 | LISN | ESH2-Z5 | 829991/012 | R&S | 2014-04-15 |
| 6 | Universal Radio Communication Tester | CMU200 | 102228 | R&S | 2014-06-23 |
| 7 | Universal Radio Communication Tester | E5515C | MY48361083 | Agilent | 2014-03-16 |
| 8 | Spectrum Analyzer | E4440A | MY48250642 | Agilent | 2014-03-04 |
| 9 | EMI Antenna | 9117 | 177 | Schwarzbeck | 2014-06-29 |
| 10 | EMI Antenna | VULB 9163 | 482 | Schwarzbeck | 2014-02-17 |
| 11 | EMI Antenna | 3117 | 00119024 | ETS-Lindgren | 2014-02-02 |
| 12 | EMI Antenna | 3117 | 00058889 | ETS-Lindgren | 2014-02-02 |
| 13 | Signal Generator | N5183A | MY49060052 | Agilent | 2014-03-18 |
| 14 | Climatic chamber | PL-2G | 343074 | ESPEC | 2014-05-11 |

ANNEX A: MEASUREMENT RESULTS

A.1 OUTPUT POWER

A.1.1 Summary

During the process of testing, the EUT was controlled via Rhode & Schwarz Digital Radio Communication tester (CMU-200) to ensure max power transmission and proper modulation.

This result contains peak output power and EIRP measurements for the EUT. In all cases, output power is within the specified limits.

A.1.2 Conducted

A.1.2.1 Method of Measurements

The EUT was set up for the max output power with pseudo random data modulation.

The power was measured with Rhode & Schwarz Digital Radio Communication tester (CMU-200).

These measurements were done at 3 frequencies, 826.4MHz, 836.6MHz and 846.6MHz for WCDMA Band V; 1852.4MHz, 1880.0MHz and 1907.6MHz for WCDMA Band II (bottom, middle and top of operational frequency range).

Limit

A.1.2.2 Test Condition

| RBW | VBW | Sweep Time | Span |
|-------|-------|------------|-------|
| 10MHz | 10MHz | 800ms | 50MHz |

WCDMA Band V

Measurement result

| WCDMA | CH | Frequency(MHz) | output power(dBm) |
|----------|------|----------------|-------------------|
| (Band V) | 4132 | 826.4 | 23.00 |
| | 4183 | 836.6 | 22.92 |
| | 4233 | 846.6 | 23.07 |

WCDMA Band II

Measurement result

| WCDMA | CH | Frequency(MHz) | output power(dBm) |
|-----------|------|----------------|-------------------|
| (Band II) | 9262 | 1852.4 | 22.88 |
| | 9400 | 1880.0 | 22.83 |
| | 9538 | 1907.6 | 22.69 |

A.1.3 Radiated

A.1.3.1 Description

This is the test for the maximum radiated power from the EUT.


Rule Part 24.232(b) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power" and 24.232(c) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage."

Rule Part 22.913(a) specifies "The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts." Rule Part 27.50(d)(2) specifies, "Fixed, mobile, and portable (handheld) stations operating in the 1710–1755 MHz band are limited to a peak EIRP of 1 watt."


A.1.3.2 Method of Measurement

The measurements procedures in TIA-603C-2004 are used.

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the

reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (P_{cl}), the Substitution Antenna Gain (G_a) and the Amplifier Gain (P_{Ag}) should be recorded after test.

The measurement results are obtained as described below:

$$\text{Power(EIRP)} = P_{Mea} - P_{Ag} - P_{cl} - G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15\text{dBi}$.

WCDMA Band V-ERP

Limits

| | |
|--------------|----------------------|
| | Burst Peak ERP (dBm) |
| WCDMA Band V | 38.45dBm (7W) |

Measurement result

| Frequency (MHz) | P _{mea} (dBm) | Cable Loss(dB) | P _{Ag} (dB) | Antenna Gain(dBi) | Correction(dB) | RMS ERP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------------------|----------------|----------------------|-------------------|----------------|---------------|-------------|-------------|--------------|
| 826.40 | -26.60 | 2.07 | -53.00 | 0.85 | 2.15 | 21.33 | 38.45 | 17.12 | H |
| 836.60 | -26.22 | 2.08 | -53.00 | 0.90 | 2.15 | 21.65 | 38.45 | 16.80 | H |
| 846.60 | -25.82 | 2.09 | -53.00 | 0.94 | 2.15 | 22.00 | 38.45 | 16.45 | H |

Frequency: 846.6MHz

Peak ERP(dBm)= P_{Mea}(-25.82dBm)- P_{cl}(2.09dB)- P_{Ag}(-53.00dB)-G_a (0.94dB)-2.15dB=22.00dBm

ANALYZER SETTINGS: RBW = VBW = 5MHz

WCDMA Band II-EIRP

Limits

| | |
|---------------|-----------------------|
| | Burst Peak EIRP (dBm) |
| WCDMA Band II | 33dBm (2W) |

Measurement result

| Frequency (MHz) | P _{mea} (dBm) | Cable Loss(dB) | P _{Ag} (dB) | Antenna Gain(dBi) | RMS EIRP(dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------------------|----------------|----------------------|-------------------|---------------|-------------|-------------|--------------|
| 1852.40 | -28.48 | 3.18 | -50.00 | -4.55 | 22.89 | 33.00 | 10.11 | H |
| 1880.00 | -27.46 | 3.11 | -50.00 | -4.43 | 23.86 | 33.00 | 9.14 | H |
| 1907.60 | -25.69 | 3.18 | -50.00 | -4.31 | 25.44 | 33.00 | 7.56 | H |

Frequency: 1907.6MHz

Peak EIRP(dBm)= P_{Mea}(-25.69dBm)- P_{cl}(3.18dB)- P_{Ag}(-50.00dB)-G_a (-4.31dB) =25.44dBm

ANALYZER SETTINGS: RBW = VBW = 5MHz

A.2 EMISSION LIMIT


A.2.1 Measurement Method

The measurements procedures in TIA-603C-2004 are used.


The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment. The resolution bandwidth is set as outlined in Part 24.238, Part 22.917. The spectrum was scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of WCDMA Band II and WCDMA Band V.

The procedure of radiated spurious emissions is as follows:

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (P_r).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the

substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. The Path loss (P_{pl}) between the Signal Source with the Substitution Antenna and the Substitution Antenna Gain (G_a) should be recorded after test.

A amplifier should be connected in for the test.

The Path loss (P_{pl}) is the summation of the cable loss and the gain of the amplifier.

The measurement results are obtained as described below:

$$\text{Power(EIRP)} = P_{Mea} - P_{pl} - G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15\text{dBi}$.

A.2.2 Measurement Limit

Part 24.238 , Part 22.917 and Part 27.53 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

A.2.3 Measurement Results

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of WCDMA Band II (1852.4MHz, 1880.0MHz and 1907.6MHz) , WCDMA Band V(826.4MHz, 836.6MHz and 846.6MHz). It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the WCDMA Band II, WCDMA Band V into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this.

WCDMA BAND V Mode Channel 4132/826.4MHz

| Frequency(MHz) | P _{Mea} (dBm) | Path Loss | Antenna Gain | Correction (dB) | Peak ERP(dBm) | Limit (dBm) | Margin (dB) | Polarization |
|----------------|------------------------|-----------|--------------|-----------------|---------------|-------------|-------------|--------------|
| 1655.09 | -48.60 | 2.93 | -5.42 | 2.15 | -48.26 | -13.00 | 35.26 | V |
| 3305.55 | -59.66 | 4.18 | -7.43 | 2.15 | -58.56 | -13.00 | 45.56 | V |
| 3793.18 | -62.57 | 4.55 | -8.25 | 2.15 | -61.02 | -13.00 | 48.02 | H |
| 4397.48 | -62.65 | 4.82 | -8.74 | 2.15 | -60.88 | -13.00 | 47.88 | H |
| 5073.92 | -62.23 | 5.20 | -9.74 | 2.15 | -59.84 | -13.00 | 46.84 | H |
| 6152.65 | -61.41 | 5.85 | -10.32 | 2.15 | -59.09 | -13.00 | 46.09 | H |

WCDMA BAND V Mode Channel 4183/836.6MHz

| Frequency(MHz) | P _{Mea} (dBm) | Path Loss | Antenna Gain | Correction (dB) | Peak ERP(dBm) | Limit (dBm) | Margin (dB) | Polarization |
|----------------|------------------------|-----------|--------------|-----------------|---------------|-------------|-------------|--------------|
| 3101.71 | -62.87 | 4.00 | -6.94 | 2.15 | -62.08 | -13.00 | 49.08 | H |
| 3473.05 | -66.17 | 4.24 | -7.84 | 2.15 | -64.72 | -13.00 | 51.72 | H |
| 4868.55 | -63.45 | 5.11 | -9.46 | 2.15 | -61.25 | -13.00 | 48.25 | H |
| 6454.72 | -61.61 | 5.86 | -10.56 | 2.15 | -59.06 | -13.00 | 46.06 | H |
| 8114.65 | -59.85 | 6.86 | -11.97 | 2.15 | -56.89 | -13.00 | 43.89 | H |
| 9562.49 | -60.47 | 7.76 | -12.58 | 2.15 | -57.80 | -13.00 | 44.80 | H |

WCDMA BAND V Mode Channel 4233/846.6MHz

| Frequency(MHz) | P _{Mea} (dBm) | Path Loss | Antenna Gain | Correction (dB) | Peak ERP(dBm) | Limit (dBm) | Margin (dB) | Polarization |
|----------------|------------------------|-----------|--------------|-----------------|---------------|-------------|-------------|--------------|
| 3370.59 | -63.89 | 4.22 | -7.59 | 2.15 | -62.67 | -13.00 | 49.67 | H |
| 3911.85 | -63.91 | 4.51 | -8.39 | 2.15 | -62.18 | -13.00 | 49.18 | V |
| 5094.59 | -61.80 | 5.21 | -9.76 | 2.15 | -59.40 | -13.00 | 46.40 | H |
| 6495.21 | -60.71 | 5.97 | -10.60 | 2.15 | -58.23 | -13.00 | 45.23 | V |
| 7005.18 | -60.59 | 6.28 | -11.10 | 2.15 | -57.92 | -13.00 | 44.92 | H |
| 8654.94 | -62.28 | 7.47 | -12.32 | 2.15 | -59.58 | -13.00 | 46.58 | H |

WCDMA BAND II Mode Channel 9262/1852.4MHz

| Frequency(MHz) | P _{Mea} (dBm) | Path Loss | Antenna Gain | Peak EIRP(dBm) | Limit (dBm) | Margin (dB) | Polarization |
|----------------|------------------------|-----------|--------------|----------------|-------------|-------------|--------------|
| 3702.42 | -51.13 | 4.44 | -8.14 | -47.43 | -13.00 | 34.43 | H |
| 5553.61 | -35.94 | 5.45 | -10.02 | -31.37 | -13.00 | 18.37 | V |
| 7404.63 | -47.97 | 6.42 | -11.34 | -43.05 | -13.00 | 30.05 | V |
| 9255.74 | -58.35 | 7.66 | -12.60 | -53.41 | -13.00 | 40.41 | V |
| 12959.31 | -52.44 | 8.89 | -13.25 | -48.08 | -13.00 | 35.08 | H |
| 14808.73 | -47.00 | 9.67 | -13.54 | -43.13 | -13.00 | 30.13 | V |

WCDMA BAND II Mode Channel 9400/1880MHz

| Frequency (MHz) | P _{Mea} (dBm) | Path Loss | Antenna Gain | Peak EIRP(dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------------------|-----------|--------------|----------------|-------------|-------------|--------------|
| 3758.14 | -52.65 | 4.53 | -8.21 | -48.97 | -13.00 | 35.97 | H |
| 5636.33 | -34.84 | 5.46 | -10.05 | -30.25 | -13.00 | 17.25 | V |
| 7514.83 | -49.61 | 6.73 | -11.41 | -44.93 | -13.00 | 31.93 | V |
| 8729.13 | -61.49 | 7.40 | -12.38 | -56.51 | -13.00 | 43.51 | H |
| 10082.73 | -60.54 | 8.21 | -12.42 | -56.33 | -13.00 | 43.33 | V |
| 15017.06 | -56.55 | 9.68 | -13.50 | -52.73 | -13.00 | 39.73 | H |

WCDMA BAND II Mode Channel 9538/1907.6MHz

| Frequency(MHz) | P _{Mea} (dBm) | Path Loss | Antenna Gain | Peak EIRP(dBm) | Limit (dBm) | Margin (dB) | Polarization |
|----------------|------------------------|-----------|--------------|----------------|-------------|-------------|--------------|
| 3812.98 | -54.13 | 4.48 | -8.28 | -50.33 | -13.00 | 37.33 | H |
| 5726.44 | -32.69 | 5.54 | -10.09 | -28.14 | -13.00 | 15.14 | V |
| 7625.46 | -49.64 | 6.83 | -11.53 | -44.94 | -13.00 | 31.94 | V |
| 10115.92 | -61.20 | 8.11 | -12.42 | -56.89 | -13.00 | 43.89 | V |
| 13350.31 | -53.45 | 9.10 | -13.65 | -48.90 | -13.00 | 35.90 | H |
| 14898.26 | -54.51 | 9.67 | -13.52 | -50.66 | -13.00 | 37.66 | V |

A.3 CONDUCTED EMISSION


The measurement procedure in ANSI C63.4-2003 is used. Conducted Emission is measured with travel charger.

A.3.1 Limit

| Frequency of Emission (MHz) | Conducted Limit (dB μ V) | |
|-----------------------------|------------------------------|-----------|
| | Quasi -Peak | Average |
| 0.15 – 0.5 | 66 to 56* | 56 to 46* |
| 0.5 – 5 | 56 | 46 |
| 5 – 30 | 60 | 50 |

* Decreases with logarithm of the frequency

A.3.2 Measurement result
WCDMA Band V




Final Result 1

| Frequency (MHz) | QuasiPeak (dBµV) | PE | Line | Corr. (dB) | Margin (dB) | Limit (dBµV) |
|-----------------|------------------|-----|------|------------|-------------|--------------|
| 2.359501 | 41.4 | GND | N | 9.9 | 14.6 | 56.0 |
| 2.391001 | 42.9 | GND | N | 9.9 | 13.1 | 56.0 |
| 2.454001 | 42.7 | GND | N | 9.9 | 13.3 | 56.0 |
| 2.809501 | 44.3 | GND | N | 9.9 | 11.7 | 56.0 |
| 2.890501 | 42.6 | GND | N | 9.9 | 13.4 | 56.0 |
| 2.935501 | 42.0 | GND | N | 9.9 | 14.0 | 56.0 |

Final Result 2

| Frequency (MHz) | CAverage (dBµV) | PE | Line | Corr. (dB) | Margin (dB) | Limit (dBµV) |
|-----------------|-----------------|-----|------|------------|-------------|--------------|
| 1.923001 | 30.7 | GND | N | 9.9 | 15.3 | 46.0 |
| 2.283001 | 31.2 | GND | N | 9.9 | 14.8 | 46.0 |
| 2.454001 | 27.9 | GND | N | 9.9 | 18.1 | 46.0 |
| 2.859001 | 33.0 | GND | N | 9.9 | 13.0 | 46.0 |
| 2.998501 | 31.6 | GND | N | 9.9 | 14.4 | 46.0 |
| 3.232501 | 31.8 | GND | N | 9.9 | 14.2 | 46.0 |

WCDMA Band V




Final Result 1

| Frequency (MHz) | QuasiPeak (dBµV) | PE | Line | Corr. (dB) | Margin (dB) | Limit (dBµV) |
|-----------------|------------------|-----|------|------------|-------------|--------------|
| 3.039001 | 44.0 | GND | N | 9.9 | 12.0 | 56.0 |
| 3.057001 | 44.1 | GND | N | 9.9 | 11.9 | 56.0 |
| 3.070501 | 44.4 | GND | N | 9.9 | 11.6 | 56.0 |
| 3.133501 | 44.2 | GND | N | 9.9 | 11.8 | 56.0 |
| 3.210001 | 43.6 | GND | N | 9.9 | 12.4 | 56.0 |
| 3.412501 | 43.4 | GND | N | 9.9 | 12.6 | 56.0 |

Final Result 2

| Frequency (MHz) | CAverage (dBµV) | PE | Line | Corr. (dB) | Margin (dB) | Limit (dBµV) |
|-----------------|-----------------|-----|------|------------|-------------|--------------|
| 3.007501 | 31.9 | GND | N | 9.9 | 14.1 | 46.0 |
| 3.070501 | 33.3 | GND | N | 9.9 | 12.7 | 46.0 |
| 3.133501 | 33.7 | GND | N | 9.9 | 12.3 | 46.0 |
| 3.165001 | 33.5 | GND | N | 9.9 | 12.5 | 46.0 |
| 3.241501 | 30.7 | GND | N | 9.9 | 15.3 | 46.0 |
| 3.444001 | 31.8 | GND | N | 9.9 | 14.2 | 46.0 |

WCDMA Band II




Final Result 1

| Frequency (MHz) | QuasiPeak (dBμV) | PE | Line | Corr. (dB) | Margin (dB) | Limit (dBμV) |
|-----------------|------------------|-----|------|------------|-------------|--------------|
| 2.373001 | 43.3 | GND | N | 9.9 | 12.7 | 56.0 |
| 2.436001 | 41.8 | GND | N | 9.9 | 14.2 | 56.0 |
| 2.512501 | 43.2 | GND | N | 9.9 | 12.8 | 56.0 |
| 2.575501 | 42.8 | GND | N | 9.9 | 13.2 | 56.0 |
| 2.715001 | 42.9 | GND | N | 9.9 | 13.1 | 56.0 |
| 2.841001 | 43.0 | GND | N | 9.9 | 13.0 | 56.0 |

Final Result 2

| Frequency (MHz) | CAverage (dBμV) | PE | Line | Corr. (dB) | Margin (dB) | Limit (dBμV) |
|-----------------|-----------------|-----|------|------------|-------------|--------------|
| 2.157001 | 29.6 | GND | N | 9.9 | 16.4 | 46.0 |
| 2.359501 | 32.5 | GND | N | 9.9 | 13.5 | 46.0 |
| 2.841001 | 28.7 | GND | N | 9.9 | 17.3 | 46.0 |
| 3.043501 | 31.5 | GND | N | 9.9 | 14.5 | 46.0 |
| 3.354001 | 32.3 | GND | N | 9.9 | 13.7 | 46.0 |
| 3.385501 | 31.9 | GND | N | 9.9 | 14.1 | 46.0 |

WCDMA Band II




Final Result 1

| Frequency (MHz) | QuasiPeak (dBµV) | PE | Line | Corr. (dB) | Margin (dB) | Limit (dBµV) |
|-----------------|------------------|-----|------|------------|-------------|--------------|
| 2.283001 | 42.3 | GND | N | 9.9 | 13.7 | 56.0 |
| 2.580001 | 41.6 | GND | N | 9.9 | 14.4 | 56.0 |
| 2.625001 | 42.5 | GND | N | 9.9 | 13.5 | 56.0 |
| 2.656501 | 43.0 | GND | N | 9.9 | 13.0 | 56.0 |
| 2.688001 | 42.9 | GND | N | 9.9 | 13.1 | 56.0 |
| 2.706001 | 43.3 | GND | N | 9.9 | 12.7 | 56.0 |

Final Result 2

| Frequency (MHz) | CAverage (dBµV) | PE | Line | Corr. (dB) | Margin (dB) | Limit (dBµV) |
|-----------------|-----------------|-----|------|------------|-------------|--------------|
| 1.063501 | 29.4 | GND | N | 9.9 | 16.6 | 46.0 |
| 2.611501 | 31.1 | GND | N | 9.9 | 14.9 | 46.0 |
| 2.656501 | 32.1 | GND | N | 9.9 | 13.9 | 46.0 |
| 2.665501 | 32.3 | GND | N | 9.9 | 13.7 | 46.0 |
| 2.688001 | 32.5 | GND | N | 9.9 | 13.5 | 46.0 |
| 2.728501 | 32.4 | GND | N | 9.9 | 13.6 | 46.0 |

MP3




Final Result 1

| Frequency (MHz) | QuasiPeak (dBµV) | PE | Line | Corr. (dB) | Margin (dB) | Limit (dBµV) |
|-----------------|------------------|-----|------|------------|-------------|--------------|
| 2.395501 | 42.0 | GND | N | 9.9 | 14.0 | 56.0 |
| 2.454001 | 43.3 | GND | N | 9.9 | 12.7 | 56.0 |
| 2.485501 | 42.3 | GND | N | 9.9 | 13.7 | 56.0 |
| 2.503501 | 42.6 | GND | N | 9.9 | 13.4 | 56.0 |
| 2.751001 | 42.5 | GND | N | 9.9 | 13.5 | 56.0 |
| 2.814001 | 43.2 | GND | N | 9.9 | 12.8 | 56.0 |

Final Result 2

| Frequency (MHz) | CAverage (dBµV) | PE | Line | Corr. (dB) | Margin (dB) | Limit (dBµV) |
|-----------------|-----------------|-----|------|------------|-------------|--------------|
| 2.503501 | 32.0 | GND | N | 9.9 | 14.0 | 46.0 |
| 2.643001 | 29.9 | GND | N | 9.9 | 16.1 | 46.0 |
| 2.782501 | 32.9 | GND | N | 9.9 | 13.1 | 46.0 |
| 2.845501 | 32.2 | GND | N | 9.9 | 13.8 | 46.0 |
| 3.048001 | 32.6 | GND | N | 9.9 | 13.4 | 46.0 |
| 3.219001 | 32.2 | GND | N | 9.9 | 13.8 | 46.0 |

Camera



Final Result 1

| Frequency (MHz) | QuasiPeak (dBµV) | PE | Line | Corr. (dB) | Margin (dB) | Limit (dBµV) |
|-----------------|------------------|-----|------|------------|-------------|--------------|
| 2.076001 | 40.8 | GND | N | 9.9 | 15.2 | 56.0 |
| 2.310001 | 42.7 | GND | N | 9.9 | 13.3 | 56.0 |
| 2.449501 | 43.7 | GND | N | 9.9 | 12.3 | 56.0 |
| 2.512501 | 43.0 | GND | N | 9.9 | 13.0 | 56.0 |
| 2.544001 | 42.8 | GND | N | 9.9 | 13.2 | 56.0 |
| 2.949001 | 42.4 | GND | N | 9.9 | 13.6 | 56.0 |

Final Result 2

| Frequency (MHz) | CAverage (dBµV) | PE | Line | Corr. (dB) | Margin (dB) | Limit (dBµV) |
|-----------------|-----------------|-----|------|------------|-------------|--------------|
| 2.265001 | 29.6 | GND | N | 9.9 | 16.4 | 46.0 |
| 2.310001 | 30.2 | GND | N | 9.9 | 15.8 | 46.0 |
| 2.404501 | 29.3 | GND | N | 9.9 | 16.7 | 46.0 |
| 2.778001 | 31.8 | GND | N | 9.9 | 14.2 | 46.0 |
| 2.949001 | 32.2 | GND | N | 9.9 | 13.8 | 46.0 |
| 3.322501 | 31.9 | GND | N | 9.9 | 14.1 | 46.0 |

A.4 FREQUENCY STABILITY

A.4.1 Method of Measurement

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMU200 DIGITAL RADIO COMMUNICATION TESTER.

1. Measure the carrier frequency at room temperature.
2. Subject the EUT to overnight soak at -30°C.
3. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on mid channel of WCDMA Band V and WCDMA Band II, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
4. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
5. Remeasure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments remeasuring carrier frequency at each voltage. Pause at nominal voltage for 1 1/2 hours unpowered, to allow any self-heating to stabilize, before continuing.
6. Subject the EUT to overnight soak at +50°C.
7. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
8. Repeat the above measurements at 10 C increments from +50°C to -30°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

A.4.2 Measurement Limit

A.4.2.1 For Hand carried battery powered equipment

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.5VDC and 4.2VDC, with a nominal voltage of 3.8VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress. These voltages represent a tolerance of -10 % and +12.5 %. For the purposes of measuring frequency stability these voltage limits are to be used.

A.4.2.2 For equipment powered by primary supply voltage

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the

fundamental emission stays within the authorized frequency block. For this EUT section 2.1055(d)(1) applies. This requires varying primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

A.4.3 Measurement results

WCDMA Band V

Frequency Error vs Voltage

| Voltage(V) | Frequency error(Hz) | Frequency error(ppm) |
|------------|---------------------|----------------------|
| 3.5 | -5 | 0.006 |
| 3.8 | -7 | 0.009 |
| 4.2 | -9 | 0.011 |

Frequency Error vs Temperature

| temperature(°C) | Frequency error(Hz) | Frequency error(ppm) |
|-----------------|---------------------|----------------------|
| -30 | 4 | 0.005 |
| -20 | 5 | 0.006 |
| -10 | -5 | 0.006 |
| 0 | 8 | 0.009 |
| 10 | 6 | 0.008 |
| 20 | 8 | 0.010 |
| 30 | -6 | 0.008 |
| 40 | 6 | 0.007 |
| 50 | 11 | 0.014 |

WCDMA Band II

Frequency Error vs Voltage

| Voltage(V) | Frequency error(Hz) | Frequency error(ppm) |
|------------|---------------------|----------------------|
| 3.5 | -16 | 0.008 |
| 3.8 | 5 | 0.003 |
| 4.2 | -18 | 0.010 |

Frequency Error vs Temperature

| temperature(°C) | Frequency error(Hz) | Frequency error(ppm) |
|-----------------|---------------------|----------------------|
| -30 | -11 | 0.006 |
| -20 | 13 | 0.007 |
| -10 | -17 | 0.009 |
| 0 | 10 | 0.005 |
| 10 | 5 | 0.003 |
| 20 | 16 | 0.008 |
| 30 | -17 | 0.009 |
| 40 | 10 | 0.006 |
| 50 | -11 | 0.006 |

A.5 OCCUPIED BANDWIDTH

A.5.1 Occupied Bandwidth Results


Similar to conducted emissions; occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of WCDMA Band II and WCDMA Band V. The table below lists the measured 99% BW. Spectrum analyzer plots are included on the following pages.

WCDMA Band II (99% BW)

| Frequency(MHz) | Occupied Bandwidth (99% BW)(MHz) |
|----------------|-----------------------------------|
| 1852.4 | 4.167 |
| 1880.0 | 4.167 |
| 1907.6 | 4.167 |


WCDMA Band II

Channel 9262-Occupied Bandwidth (99% BW)




Date: 29.AUG.2013 15:06:38

Channel 9400-Occupied Bandwidth (99% BW)



Date: 29.AUG.2013 15:07:13

Channel 9538-Occupied Bandwidth (99% BW)




Date: 29.AUG.2013 15:07:48

WCDMA Band V(99% BW)

| Frequency(MHz) | Occupied Bandwidth (99% BW)(MHz) |
|----------------|-----------------------------------|
| 826.4 | 4.167 |
| 836.6 | 4.151 |
| 846.6 | 4.167 |


WCDMA Band V

Channel 4132-Occupied Bandwidth (99% BW)




Date: 29.AUG.2013 15:24:25

Channel 4183-Occupied Bandwidth (99% BW)



Date: 29.AUG.2013 15:24:59

Channel 4233-Occupied Bandwidth (99% BW)



Date: 29.AUG.2013 15:25:34

A.6 EMISSION BANDWIDTH

A.6.1 Emission Bandwidth Results


Similar to conducted emissions; Emission bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of WCDMA Band II and WCDMA Band V. Table below lists the measured 100% BW. Spectrum analyzer plots are included on the following pages.

WCDMA Band II (100% BW)

| Frequency(MHz) | Emission Bandwidth (100% BW)(MHz) |
|----------------|------------------------------------|
| 1852.4 | 4.487 |
| 1880.0 | 4.503 |
| 1907.6 | 4.503 |


WCDMA Band II

Channel 9262-Emission Bandwidth (100% BW)




Date: 29.AUG.2013 15:08:24

Channel 9400-Emission Bandwidth (100% BW)



Date: 29.AUG.2013 15:08:58

Channel 9538-Emission Bandwidth (100% BW)




Date: 29.AUG.2013 15:09:33

WCDMA Band V(100% BW)

| Frequency(MHz) | Emission Bandwidth (100% BW)(MHz) |
|----------------|------------------------------------|
| 826.40 | 4.487 |
| 836.60 | 4.487 |
| 846.60 | 4.487 |


WCDMA Band V

Channel 4132-Emission Bandwidth (100% BW)




Date: 29.AUG.2013 15:26:10

Channel 4183-Emission Bandwidth (100% BW)



Date: 29.AUG.2013 15:26:44

Channel 4233-Emission Bandwidth (100% BW)




Date: 29.AUG.2013 15:27:19

A.7 BAND EDGE COMPLIANCE


WCDMA Band II

LOW BAND EDGE BLOCK-A (WCDMA Band II)-Channel 9262




Date: 29.AUG.2013 15:09:49

HIGH BAND EDGE BLOCK-C (WCDMA Band II) -Channel 9538




Date: 29.AUG.2013 15:10:05

WCDMA Band V
LOW BAND EDGE BLOCK-A (WCDMA Band V)-Channel 4132



Date: 29.AUG.2013 15:27:35

HIGH BAND EDGE BLOCK-C (WCDMA Band V) -Channel 4233



Date: 29.AUG.2013 15:27:51

A.8 CONDUCTED SPURIOUS EMISSION

A.8.1 Measurement Method

The following steps outline the procedure used to measure the conducted emissions from the EUT.

1. Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the equipment of WCDMA Band II, this equates to a frequency range of 30 MHz to 19.1 GHz, data taken from 30 MHz to 20 GHz. For WCDMA Band V, data taken from 30 MHz to 10GHz.
2. The sweep time is set automatically by instrument itself. That should be the optimal sweep time for the span and the RBW. If the sweep time is too short, that is sweep is too fast, the sweep result is not accurate; If the sweep time is too long, that is sweep is too low, some frequency components may be lost. The instrument will give a optimal sweep time according the selected span and RBW.
3. The procedure to get the conducted spurious emission is as follows:
The trace mode is set to MaxHold to get the highest signal at each frequency;
Wait 25 seconds;
Get the result.
4. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.

WCDMA Band II Transmitter

| Channel | Frequency (MHz) |
|---------|-----------------|
| 9262 | 1852.40 |
| 9400 | 1880.00 |
| 9538 | 1907.60 |

WCDMA Band V Transmitter

| Channel | Frequency (MHz) |
|---------|-----------------|
| 4132 | 826.40 |
| 4183 | 836.60 |
| 4233 | 846.60 |

A. 8.2 Measurement Limit

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.


The specification that emissions shall be attenuated below the transmitter power (P) by at least $43 + 10 \log (P)$ dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

A.8.3 Measurement result

WCDMA Band II

A. 8.3.1 Channel 9262: 30MHz –1GHz

Spurious emission limit –13dBm.




Date: 29.AUG.2013 15:10:36

A.8.3.2 Channel 9262: 1GHz –2.5GHz


Spurious emission limit –13dBm.

NOTE: peak above the limit line is the carrier frequency.




Date: 29.AUG.2013 15:11:04

A.8.3.3 Channel 9262: 2.5GHz –7.5GHz
Spurious emission limit –13dBm.




Date: 29.AUG.2013 15:11:33

A.8.3.4 Channel 9262: 7.5GHz –10GHz
Spurious emission limit –13dBm.




Date: 29.AUG.2013 15:12:01

A.8.3.5 Channel 9262: 10GHz –15GHz
Spurious emission limit –13dBm.




Date: 29.AUG.2013 15:12:29

A.8.3.6 Channel 9262: 15GHz –20GHz
Spurious emission limit –13dBm.



Date: 29.AUG.2013 15:12:57


A. 8.3.7 Channel 9400: 30MHz –1GHz
Spurious emission limit –13dBm.



Date: 29.AUG.2013 15:13:28


A.8.3.8 Channel 9400: 1GHz –2.5GHz
Spurious emission limit –13dBm.

NOTE: peak above the limit line is the carrier frequency.




Date: 29.AUG.2013 15:13:56

A.8.3.9 Channel 9400: 2.5GHz –7.5GHz
Spurious emission limit –13dBm.




Date: 29.AUG.2013 15:14:25

A.8.3.10 Channel 9400: 7.5GHz –10GHz
Spurious emission limit –13dBm.




Date: 29.AUG.2013 15:14:53

A.8.3.11 Channel 9400: 10GHz –15GHz
Spurious emission limit –13dBm.




Date: 29.AUG.2013 15:15:21

A.8.3.12 Channel 9400: 15GHz –20GHz
Spurious emission limit –13dBm.



Date: 29.AUG.2013 15:15:49


A. 8.3.13 Channel 9538: 30MHz –1GHz
Spurious emission limit –13dBm.



Date: 29.AUG.2013 15:16:20


A.8.3.14 Channel 9538: 1GHz –2.5GHz
Spurious emission limit –13dBm.

NOTE: peak above the limit line is the carrier frequency.




Date: 29.AUG.2013 15:16:48

A.8.3.15 Channel 9538: 2.5GHz –7.5GHz
Spurious emission limit –13dBm.




Date: 29.AUG.2013 15:17:16

A.8.3.16 Channel 9538: 7.5GHz –10GHz
Spurious emission limit –13dBm.




Date: 29.AUG.2013 15:17:45

A.8.3.17 Channel 9538: 10GHz –15GHz
Spurious emission limit –13dBm.




Date: 29.AUG.2013 15:18:13

A.8.3.18 Channel 9538: 15GHz –20GHz
Spurious emission limit –13dBm.




Date: 29.AUG.2013 15:18:41

A. 8.3.19 Idle mode: 30MHz –1GHz
Spurious emission limit –13dBm.




Date: 29.AUG.2013 15:19:10

A.8.3.20 Idle mode: 1GHz –2.5GHz
Spurious emission limit –13dBm.




Date: 29.AUG.2013 15:19:38

A.8.3.21 Idle mode: 2.5GHz –7.5GHz
Spurious emission limit –13dBm.




Date: 29.AUG.2013 15:20:06

A.8.3.22 Idle mode: 7.5GHz –10GHz
Spurious emission limit –13dBm.




Date: 29.AUG.2013 15:20:34

A.8.3.23 Idle mode: 10GHz –15GHz
Spurious emission limit –13dBm.



Date: 29.AUG.2013 15:21:03

A.8.3.24 Idle mode: 15GHz –20GHz
Spurious emission limit –13dBm.




Date: 29.AUG.2013 15:21:31

WCDMA Band V

A. 8.3.25 Channel 4132: 30MHz –1GHz

Spurious emission limit –13dBm.


NOTE: peak above the limit line is the carrier frequency.



Date: 29.AUG.2013 15:28:22


A. 8.3.26 Channel 4132: 1GHz – 2.5GHz

Spurious emission limit –13dBm.




Date: 29.AUG.2013 15:28:50

A. 8.3.27 Channel 4132: 2.5GHz –7.5GHz
Spurious emission limit –13dBm.



Date: 29.AUG.2013 15:29:18

A. 8.3.28 Channel 4132: 7.5GHz – 10GHz
Spurious emission limit –13dBm.




Date: 29.AUG.2013 15:29:47

A. 8.3.29 Channel 4183: 30MHz –1GHz

Spurious emission limit –13dBm.


NOTE: peak above the limit line is the carrier frequency.



Date: 29.AUG.2013 15:30:18


A.8.3.30 Channel 4183: 1GHz – 2.5GHz

Spurious emission limit –13dBm.




Date: 29.AUG.2013 15:30:46

A. 8.3.31 Channel 4183: 2.5GHz – 7.5GHz
Spurious emission limit –13dBm.



Date: 29.AUG.2013 15:31:14

A. 8.3.32 Channel 4183: 7.5GHz – 10GHz
Spurious emission limit –13dBm.




Date: 29.AUG.2013 15:31:42

A. 8.3.33 Channel 4233: 30MHz –1GHz

Spurious emission limit –13dBm.


NOTE: peak above the limit line is the carrier frequency.



Date: 29.AUG.2013 15:32:13


A. 8.3.34 Channel 4233: 1GHz – 2.5GHz

Spurious emission limit –13dBm.




Date: 29.AUG.2013 15:32:41

A. 8.3.35 Channel 4233: 2.5GHz –7.5GHz
Spurious emission limit –13dBm.




Date: 29.AUG.2013 15:33:09

A. 8.3.36 Channel 4233: 7.5GHz – 10GHz
Spurious emission limit –13dBm.




Date: 29.AUG.2013 15:33:37

A. 8.3.37 Idle mode: 30MHz – 1GHz
Spurious emission limit -13dBm.




Date: 29.AUG.2013 15:34:07

A.8.3.38 Idle mode: 1GHz – 2.5GHz
Spurious emission limit -13dBm.




Date: 29.AUG.2013 15:34:35

A.8.3.39 Idle mode: 2.5GHz – 7.5GHz
Spurious emission limit -13dBm.



Date: 29.AUG.2013 15:35:03

A.8.3.40 Idle mode: 7.5GHz – 10GHz
Spurious emission limit -13dBm.



Date: 29.AUG.2013 15:35:31

END OF REPORT