



# FCC RF Test Report

**APPLICANT** : TCT Mobile Limited  
**EQUIPMENT** : Tablet PC  
**BRAND NAME** : ALCATEL ONETOUCH  
**MODEL NAME** : I221  
**MARKETING NAME** : ALCATEL ONETOUCH PIXI 8  
**FCC ID** : RAD504  
**STANDARD** : FCC Part 15 Subpart C §15.247  
**CLASSIFICATION** : (DTS) Digital Transmission System

The product was received on May 07, 2014 and testing was completed on Jun. 20, 2014. We, SPORTON INTERNATIONAL (SHENZHEN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (SHENZHEN) INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager



**SPORTON INTERNATIONAL (SHENZHEN) INC.**

No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P.R.C.



## TABLE OF CONTENTS

|  |           |
|--|-----------|
| REVISION HISTORY.....  | 3         |
| SUMMARY OF TEST RESULT .....                                     | 4         |
| <b>1 GENERAL DESCRIPTION.....</b>                                | <b>5</b>  |
| 1.1 Applicant.....   | 5         |
| 1.2 Manufacturer.....  | 5         |
| 1.3 Product Feature of Equipment Under Test.....                 | 5         |
| 1.4 Product Specification subjective to this standard .....      | 5         |
| 1.5 Modification of EUT .....                                    | 6         |
| 1.6 Testing Location .....                                       | 6         |
| 1.7 Applicable Standards.....                                    | 6         |
| <b>2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....</b>         | <b>7</b>  |
| 2.1 Descriptions of Test Mode.....                               | 7         |
| 2.2 Test Mode.....   | 8         |
| 2.3 Connection Diagram of Test System.....                       | 9         |
| 2.4 Support Unit used in test configuration and system.....      | 10        |
| 2.5 EUT Operation Test Setup .....                               | 10        |
| 2.6 Measurement Results Explanation Example.....                 | 10        |
| <b>3 TEST RESULT .....</b>                                       | <b>11</b> |
| 3.1 6dB Bandwidth Measurement .....                              | 11        |
| 3.2 Peak Output Power Measurement .....                          | 14        |
| 3.3 Power Spectral Density Measurement .....                     | 16        |
| 3.4 Conducted Band Edges and Spurious Emission Measurement ..... | 22        |
| 3.5 Radiated Band Edges and Spurious Emission Measurement .....  | 31        |
| 3.6 AC Conducted Emission Measurement.....                       | 42        |
| 3.7 Antenna Requirements.....                                    | 46        |
| <b>4 LIST OF MEASURING EQUIPMENT.....</b>                        | <b>47</b> |
| <b>5 UNCERTAINTY OF EVALUATION.....</b>                          | <b>48</b> |
| <b>APPENDIX A. SETUP PHOTOGRAPHS</b>                             |           |





### SUMMARY OF TEST RESULT

| Report Section | FCC Rule           | Description                                | Limit                 | Result | Remark                                    |
|----------------|--------------------|--|-----------------------|--------|---|
| 3.1            | 15.247(a)(2)       | 6dB Bandwidth                              | $\geq 0.5\text{MHz}$  | Pass   | -   |
| 3.2            | 15.247(b)(1)       | Peak Output Power                          | $\leq 30\text{dBm}$   | Pass   | -   |
| 3.3            | 15.247(e)          | Power Spectral Density                     | $\leq 8\text{dBm}$    | Pass   | -   |
| 3.4            | 15.247(d)          | Conducted Band Edges and Spurious Emission | $\leq 20\text{dBc}$   | Pass   | -   |
| 3.5            | 15.247(d)          | Radiated Band Edges and Spurious Emission  | 15.209(a) & 15.247(d) | Pass   | Under limit<br>10.68 dB at<br>104.690 MHz |
| 3.6            | 15.207             | AC Conducted Emission                      | 15.207(a)             | Pass   | Under limit<br>11.60 dB at<br>0.380 MHz   |
| 3.7            | 15.203 & 15.247(b) | Antenna Requirement                        | N/A                   | Pass   | -   |



# 1 General Description

## 1.1 Applicant

**TCT Mobile Limited**

5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park, Pudong Area Shanghai, P.R. China. 201203

## 1.2 Manufacturer

**TCT Mobile Limited**

5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park, Pudong Area Shanghai, P.R. China. 201203

## 1.3 Product Feature of Equipment Under Test

| Product Feature                 |   |
|---------------------------------|---|
| Equipment                       | Tablet PC   |
| Brand Name                      | ALCATEL ONETOUCH  |
| Model Name                      | I221  |
| Marketing Name                  | ALCATEL ONETOUCH PIXI 8   |
| FCC ID                          | RAD504  |
| EUT supports Radios application | WLAN 2.4GHz 802.11b/g/n HT20/HT40<br>Bluetooth v3.0 + EDR/Bluetooth v4.0 LE |
| HW Version                      | V05   |
| SW Version                      | D28   |
| EUT Stage                       | Production Unit   |

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

## 1.4 Product Specification subjective to this standard

| Product Specification subjective to this standard |  |
|---|--|
| Tx/Rx Frequency Range                             | 2402 MHz ~ 2480 MHz                            |
| Number of Channels                                | 40   |
| Carrier Frequency of Each Channel                 | 40 Channel(37 hopping + 3 advertising channel) |
| Maximum Output Power to Antenna                   | -1.67 dBm (0.0007 W)                           |
| Antenna Type                                      | IFA Antenna with gain 1.90 dBi                 |
| Type of Modulation                                | Bluetooth v4.0 LE : GFSK                       |



### 1.5 Modification of EUT

No modifications are made to the EUT during all test items.

### 1.6 Testing Location

|                           |  |           |         |                             |
|---------------------------|--|-----------|---------|-----------------------------|
| <b>Test Site</b>          | SPORTON INTERNATIONAL (SHENZHEN) INC.  |           |         |                             |
| <b>Test Site Location</b> | No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P.R.C.<br>TEL: +86-755- 3320-2398 |           |         |                             |
| <b>Test Site No.</b>      | <b>Sporton Site No.</b>  |           |         | <b>FCC Registration No.</b> |
|                           | TH01-SZ  | 03CH01-SZ | CO01-SZ | 831040                      |

### 1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.247
- FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02
- ANSI C63.4-2003

**Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



## 2 Test Configuration of Equipment Under Test

### 2.1 Descriptions of Test Mode

The RF output power was recorded in the following table:

| Channel | Frequency | Bluetooth v4.0 LE RF Output Power |
|---------|-----------|-----------------------------------|
|         |           | Data Rate / Modulation            |
|         |           | GFSK                              |
|         |           | 1Mbps                             |
| Ch00    | 2402MHz   | -1.74 dBm                         |
| Ch19    | 2440MHz   | -1.72 dBm                         |
| Ch39    | 2480MHz   | <b>-1.67</b> dBm                  |

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). Pre-scanned tests, X, Y, Z in three orthogonal panels to determine the final configuration (Y plane as worst plane) from all possible combinations.
  
- b. AC power line Conducted Emission was tested under maximum output power.




## 2.2 Test Mode

The following summary table is showing all test modes to demonstrate in compliance with the standard.


| Summary table of Test Cases  |   |
|--|---|
| Test Item  | Data Rate / Modulation  |
|  | Bluetooth v4.0 LE / GFSK  |
| Conducted TCs  | Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps  |
|  | Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps  |
|  | Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps  |
| Radiated TCs   | Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps  |
|  | Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps  |
|  | Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps  |
| AC Conducted Emission  | Mode 1: Bluetooth Link + WLAN Link + USB Cable (Charging from Adapter) + Earphone |
| <b>Remark:</b> For radiated TCs, all the test modes are performed with adapter, earphone, USB cable and battery 1, only the worst mode (CH39) based on battery 1 need to verify battery 2. |   |

## 2.3 Connection Diagram of Test System

<Bluetooth v4.0 LE Tx Mode>



<AC Conducted Emission Mode>



## 2.4 Support Unit used in test configuration and system

| Item | Equipment          | Trade Name | Model Name | FCC ID     | Data Cable        | Power Cord   |
|------|--------------------|------------|------------|------------|-------------------|--|
| 1.   | WLAN AP            | D-Link     | DIR-815    | KA2IR815A1 | N/A               | Unshielded, 1.8 m  |
| 2.   | Notebook           | Lenovo     | G480       | FCC DoC    | N/A               | AC I/P:<br>Unshielded, 1.2 m<br>DC O/P:<br>Shielded, 1.8 m |
| 3.   | Bluetooth Earphone | Nokia      | BH-108     | PYAHS-107W | N/A               | N/A  |
| 4.   | Earphone           | Lenovo     | SH100      | FCC DoC    | Unshielded, 1.6 m | N/A  |

## 2.5 EUT Operation Test Setup

For Bluetooth v4.0 LE function, the engineering test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

## 2.6 Measurement Results Explanation Example

**For all conducted test items:**

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss + attenuator factor.*

Following shows an offset computation example with cable loss 7.5 dB and 10dB attenuator.

$$\begin{aligned} \text{Offset (dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 7.5 + 10 = 17.5 \text{ (dB)} \end{aligned}$$

### 3 Test Result

#### 3.1 6dB Bandwidth Measurement

##### 3.1.1 Limit of 6dB Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


##### 3.1.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

##### 3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. Measure and record the results in the test report.

##### 3.1.4 Test Setup






3.1.5 Test Result of 6dB Bandwidth

|                 |                   |                     |         |
|-----------------|-------------------|---------------------|---------|
| Test Mode :     | Bluetooth v4.0 LE | Temperature :       | 24~26°C |
| Test Engineer : | Ting You          | Relative Humidity : | 50~53%  |

| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) | 6dB Bandwidth Min. Limit (MHz) | Pass/Fail |
|---------|-----------------|---------------------|--------------------------------|-----------|
| 00      | 2402            | 0.700               | 0.5                            | Pass      |
| 19      | 2440            | 0.698               | 0.5                            | Pass      |
| 39      | 2480            | 0.700               | 0.5                            | Pass      |


6 dB Bandwidth Plot on Channel 00



Date: 18.JUN.2014 22:12:35




### 6 dB Bandwidth Plot on Channel 19



Date: 18.JUN.2014 22:16:49

### 6 dB Bandwidth Plot on Channel 39



Date: 18.JUN.2014 22:21:04

## 3.2 Peak Output Power Measurement

### 3.2.1 Limit of Peak Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


### 3.2.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

### 3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v03r02.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

### 3.2.4 Test Setup





3.2.5 Test Result of Peak Output Power

|                 |                   |                     |         |
|-----------------|-------------------|---------------------|---------|
| Test Mode :     | Bluetooth v4.0 LE | Temperature :       | 24~26°C |
| Test Engineer : | Ting You          | Relative Humidity : | 50~53%  |

| Channel | Frequency (MHz) | RF Power (dBm) |                   |           |
|---------|-----------------|----------------|-------------------|-----------|
|         |                 | GFSK           | Max. Limits (dBm) | Pass/Fail |
|         |                 | 1 Mbps         |                   |           |
| 00      | 2402            | -1.74          | 30.00             | Pass      |
| 19      | 2440            | -1.72          | 30.00             | Pass      |
| 39      | 2480            | -1.67          | 30.00             | Pass      |

### 3.3 Power Spectral Density Measurement

#### 3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


#### 3.3.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

#### 3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

#### 3.3.4 Test Setup





3.3.5 Test Result of Power Spectral Density

|                 |                   |                     |         |
|-----------------|-------------------|---------------------|---------|
| Test Mode :     | Bluetooth v4.0 LE | Temperature :       | 24~26°C |
| Test Engineer : | Ting You          | Relative Humidity : | 50~53%  |

| Channel | Frequency (MHz) | Power Density    |                | Max. Limits (dBm/3kHz) | Pass/Fail |
|---------|-----------------|------------------|----------------|------------------------|-----------|
|         |                 | PSD/100kHz (dBm) | PSD/3kHz (dBm) |                        |           |
| 00      | 2402            | -4.67            | -19.18         | 8                      | Pass      |
| 19      | 2440            | -4.75            | -19.31         | 8                      | Pass      |
| 39      | 2480            | -4.52            | -19.09         | 8                      | Pass      |


Note:

1. Measured power density (dBm) has offset with cable loss.
2. The Measured power density (dBm)/ 100kHz is reference level and used as 20dBc down for Conducted Band Edges and Conducted Spurious Emission limit line.



### 3.3.6 Test Result of Power Spectral Density Plots (100kHz)


PSD 100kHz Plot on Channel 00



Date: 18.JUN.2014 22:13:04




PSD 100kHz Plot on Channel 19



Date: 18.JUN.2014 22:17:18

PSD 100kHz Plot on Channel 39




Date: 18.JUN.2014 22:21:33






PSD 3kHz Plot on Channel 19



Date: 18.JUN.2014 22:17:09

PSD 3kHz Plot on Channel 39



Date: 18.JUN.2014 22:21:24

## 3.4 Conducted Band Edges and Spurious Emission Measurement

### 3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.


### 3.4.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

### 3.4.3 Test Procedure

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

### 3.4.4 Test Setup






### 3.4.5 Test Result of Conducted Band Edges

|                |                   |                     |          |
|----------------|-------------------|---------------------|----------|
| Test Mode :    | Bluetooth v4.0 LE | Temperature :       | 24~26°C  |
| Test Channel : | 00 and 39         | Relative Humidity : | 50~53%   |
|                |                   | Test Engineer :     | Ting You |


Low Band Edge Plot on Channel 00



Date: 18.JUN.2014 22:13:18



High Band Edge Plot on Channel 39




Date: 18.JUN.2014 22:21:47



### 3.4.6 Test Result of Conducted Spurious Emission

|                |                   |                     |          |
|----------------|-------------------|---------------------|----------|
| Test Mode :    | Bluetooth v4.0 LE | Temperature :       | 24~26°C  |
| Test Channel : | 00                | Relative Humidity : | 50~53%   |
|                |                   | Test Engineer :     | Ting You |


Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00



Date: 18.JUN.2014 22:13:37



### Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00




Date: 18.JUN.2014 22:13:56



|                |                   |                     |          |
|----------------|-------------------|---------------------|----------|
| Test Mode :    | Bluetooth v4.0 LE | Temperature :       | 24~26°C  |
| Test Channel : | 19                | Relative Humidity : | 50~53%   |
|                |                   | Test Engineer :     | Ting You |


Conducted Spurious Emission Plot on Bluetooth LE 1Mbps  
GFSK Channel 19



Date: 18.JUN.2014 22:17:38



### Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19




Date: 18.JUN.2014 22:17:57



|                |                   |                     |          |
|----------------|-------------------|---------------------|----------|
| Test Mode :    | Bluetooth v4.0 LE | Temperature :       | 24~26°C  |
| Test Channel : | 39                | Relative Humidity : | 50~53%   |
|                |                   | Test Engineer :     | Ting You |


Conducted Spurious Emission Plot on Bluetooth LE 1Mbps  
GFSK Channel 39



Date: 18.JUN.2014 22:22:06



### Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39



Date: 18.JUN.2014 22:22:25



### 3.5 Radiated Band Edges and Spurious Emission Measurement

#### 3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

| Frequency (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-----------------|-----------------------------------|-------------------------------|
| 0.009 – 0.490   | 2400/F(kHz)                       | 300                           |
| 0.490 – 1.705   | 24000/F(kHz)                      | 30                            |
| 1.705 – 30.0    | 30                                | 30                            |
| 30 – 88         | 100                               | 3                             |
| 88 – 216        | 150                               | 3                             |
| 216 - 960       | 200                               | 3                             |
| Above 960       | 500                               | 3                             |

#### 3.5.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.




### 3.5.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
  - (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Set RBW=100 kHz for  $f < 1$  GHz;  $VBW \geq RBW$ ; Sweep = auto; Detector function = peak; Trace = max hold;
  - (3) Set RBW = 1 MHz, VBW= 3MHz for  $f \geq 1$  GHz for peak measurement.  
For average measurement:
    - $VBW = 10$  Hz, when duty cycle is no less than 98 percent.
    - $VBW \geq 1/T$ , when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.


| Band              | Duty Cycle(%) | T(ms) | 1/T(kHz) | VBW Setting |
|-------------------|---------------|-------|----------|-------------|
| Bluetooth v4.0 LE | 59.74         | 0.374 | 2.674    | 3kHz        |

### 3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



### 3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.



3.5.6 Test Result of Radiated Spurious at Band Edges

For Battery 1:

|                |        |                     |            |
|----------------|--------|---------------------|------------|
| Test Mode :    | Mode 1 | Temperature :       | 23~25°C    |
| Test Channel : | 00     | Relative Humidity : | 48~52%     |
|                |        | Test Engineer :     | Kaer Huang |

| ANTENNA POLARITY : HORIZONTAL |                    |                         |                            |                         |                             |                         |                            |                      |                         |         |
|-------------------------------|--------------------|-------------------------|----------------------------|-------------------------|-----------------------------|-------------------------|----------------------------|----------------------|-------------------------|---------|
| Frequency<br>( MHz )          | Level<br>(dBμV /m) | Over<br>Limit<br>( dB ) | Limit<br>Line<br>(dBμV /m) | Read<br>Level<br>(dBμV) | Antenna<br>Factor<br>( dB ) | Cable<br>Loss<br>( dB ) | Preamp<br>Factor<br>( dB ) | Ant<br>Pos<br>( cm ) | Table<br>Pos<br>( deg ) | Remark  |
| 2338.17                       | 49.57              | -24.43                  | 74                         | 40.1                    | 31.72                       | 5.53                    | 27.78                      | 193                  | 141                     | Peak    |
| 2378.22                       | 38.41              | -15.59                  | 54                         | 28.66                   | 31.9                        | 5.59                    | 27.74                      | 193                  | 141                     | Average |

| ANTENNA POLARITY : VERTICAL |                    |                         |                            |                         |                             |                         |                            |                      |                         |         |
|-----------------------------|--------------------|-------------------------|----------------------------|-------------------------|-----------------------------|-------------------------|----------------------------|----------------------|-------------------------|---------|
| Frequency<br>( MHz )        | Level<br>(dBμV /m) | Over<br>Limit<br>( dB ) | Limit<br>Line<br>(dBμV /m) | Read<br>Level<br>(dBμV) | Antenna<br>Factor<br>( dB ) | Cable<br>Loss<br>( dB ) | Preamp<br>Factor<br>( dB ) | Ant<br>Pos<br>( cm ) | Table<br>Pos<br>( deg ) | Remark  |
| 2352.12                     | 48.9               | -25.1                   | 74                         | 39.29                   | 31.81                       | 5.56                    | 27.76                      | 100                  | 305                     | Peak    |
| 2374.98                     | 38.4               | -15.6                   | 54                         | 28.65                   | 31.9                        | 5.59                    | 27.74                      | 100                  | 305                     | Average |

|                |        |                     |            |
|----------------|--------|---------------------|------------|
| Test Mode :    | Mode 3 | Temperature :       | 23~25°C    |
| Test Channel : | 39     | Relative Humidity : | 48~52%     |
|                |        | Test Engineer :     | Kaer Huang |

| ANTENNA POLARITY : HORIZONTAL |                    |                         |                            |                         |                             |                         |                            |                      |                         |         |
|-------------------------------|--------------------|-------------------------|----------------------------|-------------------------|-----------------------------|-------------------------|----------------------------|----------------------|-------------------------|---------|
| Frequency<br>( MHz )          | Level<br>(dBμV /m) | Over<br>Limit<br>( dB ) | Limit<br>Line<br>(dBμV /m) | Read<br>Level<br>(dBμV) | Antenna<br>Factor<br>( dB ) | Cable<br>Loss<br>( dB ) | Preamp<br>Factor<br>( dB ) | Ant<br>Pos<br>( cm ) | Table<br>Pos<br>( deg ) | Remark  |
| 2485.48                       | 50.16              | -23.84                  | 74                         | 39.71                   | 32.41                       | 5.71                    | 27.67                      | 109                  | 334                     | Peak    |
| 2483.74                       | 38.98              | -15.02                  | 54                         | 28.53                   | 32.41                       | 5.71                    | 27.67                      | 109                  | 334                     | Average |

| ANTENNA POLARITY : VERTICAL |                    |                         |                            |                         |                             |                         |                            |                      |                         |         |
|-----------------------------|--------------------|-------------------------|----------------------------|-------------------------|-----------------------------|-------------------------|----------------------------|----------------------|-------------------------|---------|
| Frequency<br>( MHz )        | Level<br>(dBμV /m) | Over<br>Limit<br>( dB ) | Limit<br>Line<br>(dBμV /m) | Read<br>Level<br>(dBμV) | Antenna<br>Factor<br>( dB ) | Cable<br>Loss<br>( dB ) | Preamp<br>Factor<br>( dB ) | Ant<br>Pos<br>( cm ) | Table<br>Pos<br>( deg ) | Remark  |
| 2499.61                     | 49.24              | -24.76                  | 74                         | 38.65                   | 32.5                        | 5.74                    | 27.65                      | 196                  | 55                      | Peak    |
| 2483.8                      | 38.91              | -15.09                  | 54                         | 28.46                   | 32.41                       | 5.71                    | 27.67                      | 196                  | 55                      | Average |



For Battery 2:

|                |        |                     |            |
|----------------|--------|---------------------|------------|
| Test Mode :    | Mode 3 | Temperature :       | 23~25°C    |
| Test Channel : | 39     | Relative Humidity : | 48~52%     |
|                |        | Test Engineer :     | Kaer Huang |

| ANTENNA POLARITY : HORIZONTAL |                     |                         |                             |                         |                             |                         |                            |                      |                         |         |
|-------------------------------|---------------------|-------------------------|-----------------------------|-------------------------|-----------------------------|-------------------------|----------------------------|----------------------|-------------------------|---------|
| Frequency<br>( MHz )          | Level<br>(dBμV /m ) | Over<br>Limit<br>( dB ) | Limit<br>Line<br>(dBμV /m ) | Read<br>Level<br>(dBμV) | Antenna<br>Factor<br>( dB ) | Cable<br>Loss<br>( dB ) | Preamp<br>Factor<br>( dB ) | Ant<br>Pos<br>( cm ) | Table<br>Pos<br>( deg ) | Remark  |
| 2489.23                       | 49.64               | -24.36                  | 74                          | 39.1                    | 32.5                        | 5.71                    | 27.67                      | 105                  | 240                     | Peak    |
| 2483.5                        | 38.65               | -15.35                  | 54                          | 28.2                    | 32.41                       | 5.71                    | 27.67                      | 105                  | 240                     | Average |

| ANTENNA POLARITY : VERTICAL |                     |                         |                             |                         |                             |                         |                            |                      |                         |         |
|-----------------------------|---------------------|-------------------------|-----------------------------|-------------------------|-----------------------------|-------------------------|----------------------------|----------------------|-------------------------|---------|
| Frequency<br>( MHz )        | Level<br>(dBμV /m ) | Over<br>Limit<br>( dB ) | Limit<br>Line<br>(dBμV /m ) | Read<br>Level<br>(dBμV) | Antenna<br>Factor<br>( dB ) | Cable<br>Loss<br>( dB ) | Preamp<br>Factor<br>( dB ) | Ant<br>Pos<br>( cm ) | Table<br>Pos<br>( deg ) | Remark  |
| 2485.6                      | 49.79               | -24.21                  | 74                          | 39.34                   | 32.41                       | 5.71                    | 27.67                      | 128                  | 260                     | Peak    |
| 2484.3                      | 38.95               | -15.05                  | 54                          | 28.5                    | 32.41                       | 5.71                    | 27.67                      | 128                  | 260                     | Average |



3.5.7 Test Result of Radiated Spurious Emission (30MHz ~ 10<sup>th</sup> Harmonic)

Note: Pre-scanned all test modes and only choose the worst case mode recorded in the test report for radiated spurious emission below 1GHz.

For Battery 1:

|                 |  |                     |            |
|-----------------|--|---------------------|------------|
| Test Mode :     | Mode 1   | Temperature :       | 23~25°C    |
| Test Channel :  | 00   | Relative Humidity : | 48~52%     |
| Test Engineer : | Kaer Huang   | Polarization :      | Horizontal |
| Remark :        | 1. 2402 MHz is fundamental signal which can be ignored.<br>2. Average measurement was not performed if peak level went lower than the average limit. |                     |            |

| Frequency ( MHz ) | Level ( dBμV/m ) | Over Limit ( dB ) | Limit Line ( dBμV/m ) | Read Level ( dBμV ) | Antenna Factor ( dB ) | Cable Loss ( dB ) | Preamp Factor ( dB ) | Ant Pos ( cm ) | Table Pos ( deg ) | Remark  |
|-------------------|------------------|-------------------|-----------------------|---------------------|-----------------------|-------------------|----------------------|----------------|-------------------|---------|
| 2402              | 89.05            | -                 | -                     | 79.17               | 31.98                 | 5.62              | 27.72                | 193            | 141               | Peak    |
| 2402              | 88.21            | -                 | -                     | 78.33               | 31.98                 | 5.62              | 27.72                | 193            | 141               | Average |
| 4804              | 34.34            | -39.66            | 74                    | 49.78               | 33.78                 | 8.33              | 57.55                | 119            | 148               | Peak    |

Note: Other harmonics are lower than background noise.

|                 |  |                     |          |
|-----------------|--|---------------------|----------|
| Test Mode :     | Mode 1   | Temperature :       | 23~25°C  |
| Test Channel :  | 00   | Relative Humidity : | 48~52%   |
| Test Engineer : | Kaer Huang   | Polarization :      | Vertical |
| Remark :        | 1. 2402 MHz is fundamental signal which can be ignored.<br>2. Average measurement was not performed if peak level went lower than the average limit. |                     |          |

| Frequency ( MHz ) | Level ( dBμV/m ) | Over Limit ( dB ) | Limit Line ( dBμV/m ) | Read Level ( dBμV ) | Antenna Factor ( dB ) | Cable Loss ( dB ) | Preamp Factor ( dB ) | Ant Pos ( cm ) | Table Pos ( deg ) | Remark  |
|-------------------|------------------|-------------------|-----------------------|---------------------|-----------------------|-------------------|----------------------|----------------|-------------------|---------|
| 2402              | 85.88            | -                 | -                     | 76                  | 31.98                 | 5.62              | 27.72                | 100            | 305               | Peak    |
| 2402              | 85.78            | -                 | -                     | 75.9                | 31.98                 | 5.62              | 27.72                | 100            | 305               | Average |
| 4804              | 33.98            | -40.02            | 74                    | 49.42               | 33.78                 | 8.33              | 57.55                | 119            | 148               | Peak    |

Note: Other harmonics are lower than background noise.



|                        |  |                            |            |
|------------------------|--|----------------------------|------------|
| <b>Test Mode :</b>     | Mode 2   | <b>Temperature :</b>       | 23~25°C    |
| <b>Test Channel :</b>  | 19   | <b>Relative Humidity :</b> | 48~52%     |
| <b>Test Engineer :</b> | Kaer Huang   | <b>Polarization :</b>      | Horizontal |
| <b>Remark :</b>        | 1. 2440 MHz is fundamental signal which can be ignored.<br>2. Average measurement was not performed if peak level went lower than the average limit. |                            |            |

| Frequency<br>( MHz ) | Level<br>( dBμV/m ) | Over<br>Limit<br>( dB ) | Limit<br>Line<br>( dBμV/m ) | Read<br>Level<br>( dBμV ) | Antenna<br>Factor<br>( dB ) | Cable<br>Loss<br>( dB ) | Preamp<br>Factor<br>( dB ) | Ant<br>Pos<br>( cm ) | Table<br>Pos<br>( deg ) | Remark  |
|----------------------|---------------------|-------------------------|-----------------------------|---------------------------|-----------------------------|-------------------------|----------------------------|----------------------|-------------------------|---------|
| 2440                 | 92.89               | -                       | -                           | 82.71                     | 32.24                       | 5.65                    | 27.71                      | 137                  | 317                     | Peak    |
| 2440                 | 92.1                | -                       | -                           | 81.92                     | 32.24                       | 5.65                    | 27.71                      | 137                  | 317                     | Average |
| 4880                 | 34.33               | -39.67                  | 74                          | 49.41                     | 33.93                       | 8.41                    | 57.42                      | 110                  | 245                     | Peak    |
| 7320                 | 34.31               | -39.69                  | 74                          | 47.57                     | 33.9                        | 10                      | 57.16                      | 184                  | 225                     | Peak    |

**Note:** Other harmonics are lower than background noise.

|                        |  |                            |          |
|------------------------|--|----------------------------|----------|
| <b>Test Mode :</b>     | Mode 2   | <b>Temperature :</b>       | 23~25°C  |
| <b>Test Channel :</b>  | 19   | <b>Relative Humidity :</b> | 48~52%   |
| <b>Test Engineer :</b> | Kaer Huang   | <b>Polarization :</b>      | Vertical |
| <b>Remark :</b>        | 1. 2440 MHz is fundamental signal which can be ignored.<br>2. Average measurement was not performed if peak level went lower than the average limit. |                            |          |

| Frequency<br>( MHz ) | Level<br>( dBμV/m ) | Over<br>Limit<br>( dB ) | Limit<br>Line<br>( dBμV/m ) | Read<br>Level<br>( dBμV ) | Antenna<br>Factor<br>( dB ) | Cable<br>Loss<br>( dB ) | Preamp<br>Factor<br>( dB ) | Ant<br>Pos<br>( cm ) | Table<br>Pos<br>( deg ) | Remark  |
|----------------------|---------------------|-------------------------|-----------------------------|---------------------------|-----------------------------|-------------------------|----------------------------|----------------------|-------------------------|---------|
| 2440                 | 88.29               | -                       | -                           | 78.11                     | 32.24                       | 5.65                    | 27.71                      | 100                  | 313                     | Peak    |
| 2440                 | 87.91               | -                       | -                           | 77.73                     | 32.24                       | 5.65                    | 27.71                      | 100                  | 313                     | Average |
| 4880                 | 33.93               | -40.07                  | 74                          | 49.01                     | 33.93                       | 8.41                    | 57.42                      | 110                  | 245                     | Peak    |
| 7320                 | 35.29               | -38.71                  | 74                          | 48.55                     | 33.9                        | 10                      | 57.16                      | 184                  | 225                     | Peak    |

**Note:** Other harmonics are lower than background noise.



|                        |  |                            |            |
|------------------------|--|----------------------------|------------|
| <b>Test Mode :</b>     | Mode 3   | <b>Temperature :</b>       | 23~25°C    |
| <b>Test Channel :</b>  | 39   | <b>Relative Humidity :</b> | 48~52%     |
| <b>Test Engineer :</b> | Kaer Huang   | <b>Polarization :</b>      | Horizontal |
| <b>Remark :</b>        | 1. 2480 MHz is fundamental signal which can be ignored.<br>2. Average measurement was not performed if peak level went lower than the average limit. |                            |            |

| Frequency<br>( MHz ) | Level<br>( dBμV/m ) | Over<br>Limit<br>( dB ) | Limit<br>Line<br>(dBμV/m ) | Read<br>Level<br>(dBμV) | Antenna<br>Factor<br>( dB ) | Cable<br>Loss<br>( dB ) | Preamp<br>Factor<br>( dB ) | Ant<br>Pos<br>( cm ) | Table<br>Pos<br>( deg ) | Remark  |
|----------------------|---------------------|-------------------------|----------------------------|-------------------------|-----------------------------|-------------------------|----------------------------|----------------------|-------------------------|---------|
| 104.69               | 23.23               | -20.27                  | 43.5                       | 40.28                   | 11.6                        | 1.29                    | 29.94                      | 100                  | 50                      | Peak    |
| 193.93               | 15.62               | -27.88                  | 43.5                       | 35.03                   | 8.86                        | 1.67                    | 29.94                      | -                    | -                       | Peak    |
| 410.24               | 21.07               | -24.93                  | 46                         | 32.26                   | 16.4                        | 2.33                    | 29.92                      | -                    | -                       | Peak    |
| 622.67               | 23.31               | -22.69                  | 46                         | 31.81                   | 18.6                        | 2.82                    | 29.92                      | -                    | -                       | Peak    |
| 838.01               | 24.72               | -21.28                  | 46                         | 30.82                   | 20.6                        | 3.23                    | 29.93                      | -                    | -                       | Peak    |
| 973.81               | 25.45               | -28.55                  | 54                         | 30.74                   | 21.18                       | 3.47                    | 29.94                      | -                    | -                       | Peak    |
| 2480                 | 95.94               | -                       | -                          | 85.49                   | 32.41                       | 5.71                    | 27.67                      | 109                  | 334                     | Peak    |
| 2480                 | 95.1                | -                       | -                          | 84.65                   | 32.41                       | 5.71                    | 27.67                      | 109                  | 334                     | Average |
| 4960                 | 35.37               | -38.63                  | 74                         | 50.02                   | 34.12                       | 8.49                    | 57.26                      | 150                  | 135                     | Peak    |
| 7440                 | 35.01               | -38.99                  | 74                         | 48.04                   | 33.97                       | 10.04                   | 57.04                      | 175                  | 260                     | Peak    |

**Note:** Other harmonics are lower than background noise.



|                        |  |                            |          |
|------------------------|--|----------------------------|----------|
| <b>Test Mode :</b>     | Mode 3   | <b>Temperature :</b>       | 23~25°C  |
| <b>Test Channel :</b>  | 39   | <b>Relative Humidity :</b> | 48~52%   |
| <b>Test Engineer :</b> | Kaer Huang   | <b>Polarization :</b>      | Vertical |
| <b>Remark :</b>        | 1. 2480 MHz is fundamental signal which can be ignored.<br>2. Average measurement was not performed if peak level went lower than the average limit. |                            |          |

| Frequency<br>( MHz ) | Level<br>( dBμV/m ) | Over<br>Limit<br>( dB ) | Limit<br>Line<br>(dBμV/m ) | Read<br>Level<br>(dBμV) | Antenna<br>Factor<br>( dB ) | Cable<br>Loss<br>( dB ) | Preamp<br>Factor<br>( dB ) | Ant<br>Pos<br>( cm ) | Table<br>Pos<br>( deg ) | Remark  |
|----------------------|---------------------|-------------------------|----------------------------|-------------------------|-----------------------------|-------------------------|----------------------------|----------------------|-------------------------|---------|
| 33.88                | 27.68               | -12.32                  | 40                         | 40.11                   | 16.7                        | 0.8                     | 29.93                      | -                    | -                       | Peak    |
| 104.69               | 32.82               | -10.68                  | 43.5                       | 49.87                   | 11.6                        | 1.29                    | 29.94                      | 100                  | 50                      | Peak    |
| 406.36               | 20.53               | -25.47                  | 46                         | 31.91                   | 16.22                       | 2.32                    | 29.92                      | -                    | -                       | Peak    |
| 618.79               | 22.98               | -23.02                  | 46                         | 31.48                   | 18.6                        | 2.82                    | 29.92                      | -                    | -                       | Peak    |
| 749.74               | 25.04               | -20.96                  | 46                         | 31.31                   | 20.6                        | 3.06                    | 29.93                      | -                    | -                       | Peak    |
| 867.11               | 25.67               | -20.33                  | 46                         | 31.51                   | 20.8                        | 3.29                    | 29.93                      | -                    | -                       | Peak    |
| 2480                 | 91.05               | -                       | -                          | 80.6                    | 32.41                       | 5.71                    | 27.67                      | 196                  | 55                      | Peak    |
| 2480                 | 90.33               | -                       | -                          | 79.88                   | 32.41                       | 5.71                    | 27.67                      | 196                  | 55                      | Average |
| 4960                 | 34.05               | -39.95                  | 74                         | 48.7                    | 34.12                       | 8.49                    | 57.26                      | 150                  | 135                     | Peak    |
| 7440                 | 35.5                | -38.5                   | 74                         | 48.53                   | 33.97                       | 10.04                   | 57.04                      | 175                  | 260                     | Peak    |

**Note:** Other harmonics are lower than background noise.



For Battery 2:

|                        |  |                            |            |
|------------------------|--|----------------------------|------------|
| <b>Test Mode :</b>     | Mode 3   | <b>Temperature :</b>       | 23~25°C    |
| <b>Test Channel :</b>  | 39   | <b>Relative Humidity :</b> | 48~52%     |
| <b>Test Engineer :</b> | Kaer Huang   | <b>Polarization :</b>      | Horizontal |
| <b>Remark :</b>        | 1. 2480 MHz is fundamental signal which can be ignored.<br>2. Average measurement was not performed if peak level went lower than the average limit. |                            |            |

| Frequency<br>( MHz ) | Level<br>( dBμV/m ) | Over<br>Limit<br>( dB ) | Limit<br>Line<br>( dBμV/m ) | Read<br>Level<br>( dBμV ) | Antenna<br>Factor<br>( dB ) | Cable<br>Loss<br>( dB ) | Preamp<br>Factor<br>( dB ) | Ant<br>Pos<br>( cm ) | Table<br>Pos<br>( deg ) | Remark  |
|----------------------|---------------------|-------------------------|-----------------------------|---------------------------|-----------------------------|-------------------------|----------------------------|----------------------|-------------------------|---------|
| 2480                 | 96.21               | -                       | -                           | 85.76                     | 32.41                       | 5.71                    | 27.67                      | 105                  | 240                     | Peak    |
| 2480                 | 95.23               | -                       | -                           | 84.78                     | 32.41                       | 5.71                    | 27.67                      | 105                  | 240                     | Average |
| 4960                 | 36.12               | -37.88                  | 74                          | 50.77                     | 34.12                       | 8.49                    | 57.26                      | 100                  | 150                     | Peak    |
| 7440                 | 36.23               | -37.77                  | 74                          | 49.26                     | 33.97                       | 10.04                   | 57.04                      | 110                  | 246                     | Peak    |

**Note:** Other harmonics are lower than background noise.

|                        |  |                            |          |
|------------------------|--|----------------------------|----------|
| <b>Test Mode :</b>     | Mode 3   | <b>Temperature :</b>       | 23~25°C  |
| <b>Test Channel :</b>  | 39   | <b>Relative Humidity :</b> | 48~52%   |
| <b>Test Engineer :</b> | Kaer Huang   | <b>Polarization :</b>      | Vertical |
| <b>Remark :</b>        | 1. 2480 MHz is fundamental signal which can be ignored.<br>2. Average measurement was not performed if peak level went lower than the average limit. |                            |          |

| Frequency<br>( MHz ) | Level<br>( dBμV/m ) | Over<br>Limit<br>( dB ) | Limit<br>Line<br>( dBμV/m ) | Read<br>Level<br>( dBμV ) | Antenna<br>Factor<br>( dB ) | Cable<br>Loss<br>( dB ) | Preamp<br>Factor<br>( dB ) | Ant<br>Pos<br>( cm ) | Table<br>Pos<br>( deg ) | Remark  |
|----------------------|---------------------|-------------------------|-----------------------------|---------------------------|-----------------------------|-------------------------|----------------------------|----------------------|-------------------------|---------|
| 2480                 | 91.23               | -                       | -                           | 80.78                     | 32.41                       | 5.71                    | 27.67                      | 128                  | 260                     | Peak    |
| 2480                 | 90.12               | -                       | -                           | 79.67                     | 32.41                       | 5.71                    | 27.67                      | 128                  | 260                     | Average |
| 4960                 | 34.98               | -39.02                  | 74                          | 49.63                     | 34.12                       | 8.49                    | 57.26                      | 100                  | 360                     | Peak    |
| 7440                 | 36.31               | -37.69                  | 74                          | 49.34                     | 33.97                       | 10.04                   | 57.04                      | 110                  | 210                     | Peak    |

**Note:** Other harmonics are lower than background noise.



### 3.6 AC Conducted Emission Measurement

#### 3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

| Frequency of emission (MHz) | Conducted limit (dB $\mu$ V) |           |
|-----------------------------|------------------------------|-----------|
|                             | Quasi-peak                   | Average   |
| 0.15-0.5                    | 66 to 56*                    | 56 to 46* |
| 0.5-5                       | 56                           | 46        |
| 5-30                        | 60                           | 50        |

\*Decreases with the logarithm of the frequency.


#### 3.6.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

#### 3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

### 3.6.4 Test Setup




AMN = Artificial mains network (LISN)  
AE = Associated equipment  
EUT = Equipment under test  
ISN = Impedance stabilization network



3.6.5 Test Result of AC Conducted Emission

|                 |               |                     |         |
|-----------------|---------------|---------------------|---------|
| Test Mode :     | Mode 1        | Temperature :       | 21~22°C |
| Test Engineer : | Jack Tian     | Relative Humidity : | 41~42%  |
| Test Voltage :  | 120Vac / 60Hz | Phase :             | Line    |
| Function Type : | 错误!未找到引用源。    |                     |         |




Site : CO01-SZ  
 Condition: FCC 15C\_QP LISN\_L\_20140304 LINE

|     | Freq | Level | Over Limit | Limit Line | Read Level | LISN Factor | Cable Loss | Remark  |
|-----|------|-------|------------|------------|------------|-------------|------------|---------|
|     | MHz  | dBuV  | dB         | dBuV       | dBuV       | dB          | dB         |         |
| 1 * | 0.38 | 36.65 | -11.60     | 48.25      | 26.19      | 0.28        | 10.18      | Average |
| 2   | 0.38 | 43.65 | -14.60     | 58.25      | 33.19      | 0.28        | 10.18      | QP      |
| 3   | 1.01 | 23.81 | -22.19     | 46.00      | 13.40      | 0.26        | 10.15      | Average |
| 4   | 1.01 | 35.31 | -20.69     | 56.00      | 24.90      | 0.26        | 10.15      | QP      |
| 5   | 2.04 | 29.42 | -16.58     | 46.00      | 19.00      | 0.23        | 10.19      | Average |
| 6   | 2.04 | 40.32 | -15.68     | 56.00      | 29.90      | 0.23        | 10.19      | QP      |
| 7   | 3.40 | 29.56 | -16.44     | 46.00      | 19.00      | 0.34        | 10.22      | Average |
| 8   | 3.40 | 41.56 | -14.44     | 56.00      | 31.00      | 0.34        | 10.22      | QP      |
| 9   | 3.60 | 29.27 | -16.73     | 46.00      | 18.70      | 0.35        | 10.22      | Average |
| 10  | 3.60 | 38.47 | -17.53     | 56.00      | 27.90      | 0.35        | 10.22      | QP      |
| 11  | 3.78 | 28.88 | -17.12     | 46.00      | 18.30      | 0.36        | 10.22      | Average |
| 12  | 3.78 | 39.98 | -16.02     | 56.00      | 29.40      | 0.36        | 10.22      | QP      |



|                 |               |                     |         |
|-----------------|---------------|---------------------|---------|
| Test Mode :     | Mode 1        | Temperature :       | 21~22°C |
| Test Engineer : | Jack Tian     | Relative Humidity : | 41~42%  |
| Test Voltage :  | 120Vac / 60Hz | Phase :             | Neutral |
| Function Type : | 错误!未找到引用源。    |                     |         |



Site : CO01-SZ  
 Condition: FCC 15C\_QP LISN\_N\_20140304 NEUTRAL

|     | Freq  | Level | Over   | Limit | Read  | LISN   | Cable |         |
|-----|-------|-------|--------|-------|-------|--------|-------|---------|
|     | MHz   | dBuV  | Limit  | Line  | Level | Factor | Loss  | Remark  |
|     |       |       | dB     | dBuV  | dBuV  | dB     | dB    |         |
| 1   | 0.17  | 35.96 | -19.20 | 55.16 | 25.29 | 0.33   | 10.34 | Average |
| 2   | 0.17  | 48.36 | -16.80 | 65.16 | 37.69 | 0.33   | 10.34 | QP      |
| 3   | 0.38  | 33.16 | -15.14 | 48.30 | 22.60 | 0.38   | 10.18 | Average |
| 4   | 0.38  | 41.76 | -16.54 | 58.30 | 31.20 | 0.38   | 10.18 | QP      |
| 5   | 0.43  | 33.26 | -14.03 | 47.29 | 22.71 | 0.39   | 10.16 | Average |
| 6 * | 0.43  | 43.46 | -13.83 | 57.29 | 32.91 | 0.39   | 10.16 | QP      |
| 7   | 2.09  | 27.27 | -18.73 | 46.00 | 16.70 | 0.38   | 10.19 | Average |
| 8   | 2.09  | 38.47 | -17.53 | 56.00 | 27.90 | 0.38   | 10.19 | QP      |
| 9   | 3.35  | 26.86 | -19.14 | 46.00 | 16.20 | 0.44   | 10.22 | Average |
| 10  | 3.35  | 38.26 | -17.74 | 56.00 | 27.60 | 0.44   | 10.22 | QP      |
| 11  | 18.33 | 24.08 | -25.92 | 50.00 | 11.80 | 1.68   | 10.60 | Average |
| 12  | 18.33 | 38.08 | -21.92 | 60.00 | 25.80 | 1.68   | 10.60 | QP      |



## **3.7 Antenna Requirements**

### **3.7.1 Standard Applicable**

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

### **3.7.2 Antenna Anti-Replacement Construction**

An embedded-in antenna design is used.

### **3.7.3 Antenna Gain**

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



## 4 List of Measuring Equipment

| Instrument                        | Manufacturer         | Model No. | Serial No.   | Characteristics | Calibration Date | Test Date     | Due Date      | Remark                |
|-----------------------------------|----------------------|-----------|--------------|-----------------|------------------|---------------|---------------|-----------------------|
| Spectrum Analyzer                 | R&S                  | FSP30     | 101400       | 9kHz~30GHz      | Mar. 03, 2014    | Jun. 18, 2014 | Mar. 02, 2015 | Conducted (TH01-SZ)   |
| Spectrum Analyzer                 | R&S                  | FSV40     | 101078       | 10Hz~40GHz      | May 08, 2014     | Jun. 18, 2014 | May 07, 2015  | Conducted (TH01-SZ)   |
| Power Meter                       | Anritsu              | ML2495A   | 1218010      | 13dBm~-20dBm    | Mar. 03, 2014    | Jun. 18, 2014 | Mar. 02, 2015 | Conducted (TH01-SZ)   |
| Power Sensor                      | Anritsu              | MA2411B   | 1207253      | 0.3GHz~40GHz    | Mar. 03, 2014    | Jun. 18, 2014 | Mar. 02, 2015 | Conducted (TH01-SZ)   |
| ESCIO TEST Receiver               | R&S                  | ESCI      | 100724       | 9kHz~3GHz       | Feb. 21, 2014    | Jun. 20, 2014 | Feb. 20, 2015 | Radiation (03CH01-SZ) |
| Spectrum Analyzer                 | Agilent Technologies | N9038A    | MY52260185   | 20Hz~26.5GHz    | May 26, 2014     | Jun. 20, 2014 | May 25, 2015  | Radiation (03CH01-SZ) |
| Loop Antenna                      | R&S                  | HFH2-Z2   | 100354       | 9kHz~30MHz      | May 09, 2014     | Jun. 20, 2014 | May 08, 2015  | Radiation (03CH01-SZ) |
| Bilog Antenna                     | TESEQ                | CBL 6112D | 23188        | 30MHz~2GHz      | Oct. 26, 2013    | Jun. 20, 2014 | Oct. 25, 2014 | Radiation (03CH01-SZ) |
| Double Ridge Horn Antenna         | ETS Lindgren         | 3117      | 00119436     | 1GHz~18GHz      | Oct. 26, 2013    | Jun. 20, 2014 | Oct. 25, 2014 | Radiation (03CH01-SZ) |
| Double Ridged Horn Antenna        | COM-POWER            | AH-840    | 101073       | 18GHz~40GHz     | Jan. 27, 2014    | Jun. 20, 2014 | Jan. 26, 2015 | Radiation (03CH01-SZ) |
| Amplifier                         | ADVANTEST            | BB525C    | E9007003     | 9kHz~3000MHz    | Feb. 21, 2014    | Jun. 20, 2014 | Feb. 20, 2015 | Radiation (03CH01-SZ) |
| Amplifier                         | Yiai                 | AV3860B   | 04030        | 2GHz~26.5GHz    | May 08, 2014     | Jun. 20, 2014 | May 07, 2015  | Radiation (03CH01-SZ) |
| AC Source(AVR)                    | Chroma               | 61601     | 616010001985 | 100Vac~250Vac   | Mar. 25, 2014    | Jun. 20, 2014 | Mar. 24, 2015 | Radiation (03CH01-SZ) |
| Turn Table                        | EM Electronics       | EM 1000   | N/A          | 0~360 degree    | NCR              | Jun. 20, 2014 | NCR           | Radiation (03CH01-SZ) |
| Antenna Mast                      | EM Electronics       | EM 1000   | N/A          | 1 m~4 m         | NCR              | Jun. 20, 2014 | NCR           | Radiation (03CH01-SZ) |
| ESCIO TEST Receiver               | R&S                  | ESCI      | 100724       | 9kHz~3GHz       | Feb. 21, 2014    | Jun. 06, 2014 | Feb. 20, 2015 | Conduction (CO01-SZ)  |
| AC LISN                           | EMCO                 | 3816/2SH  | 00103912     | 9kHz~30MHz      | Mar. 04, 2014    | Jun. 06, 2014 | Mar. 03, 2015 | Conduction (CO01-SZ)  |
| AC LISN (for auxiliary equipment) | EMCO                 | 3816/2SH  | 00103892     | 9kHz~30MHz      | Mar. 04, 2014    | Jun. 06, 2014 | Mar. 03, 2015 | Conduction (CO01-SZ)  |
| AC Power Source                   | Chroma               | 61602     | 616020000891 | 100Vac~250Vac   | Dec. 17, 2013    | Jun. 06, 2014 | Dec. 16, 2014 | Conduction (CO01-SZ)  |



## 5 Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

|   |      |
|---|------|
| Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ ) | 2.31 |
|---|------|

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

|   |      |
|---|------|
| Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ ) | 3.90 |
|---|------|