



FCC RF Test Report

APPLICANT : TCT Mobile Limited
EQUIPMENT : Tablet PC
BRAND NAME : ALCATEL ONETOUCH
MODEL NAME : I216A
MARKETING NAME : ALCATEL ONETOUCH PIXI 7
FCC ID : RAD512
STANDARD : FCC 47 CFR Part 2, 22(H), 24(E)
CLASSIFICATION : PCS Licensed Transmitter (PCB)

The product was received on Jun. 30, 2014 and testing was completed on Aug. 22, 2014. We, SPORTON INTERNATIONAL (SHENZHEN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA / EIA-603-C-2004 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (SHENZHEN) INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL (SHENZHEN) INC.

No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P.R.C.



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant.....	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test	5
1.4 Product Specification subjective to this standard.....	6
1.5 Modification of EUT	7
1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator	7
1.7 Testing Location	7
1.8 Applicable Standards	8
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	9
2.1 Test Mode.....	9
2.2 Connection Diagram of Test System	11
2.3 Support Unit used in test configuration	11
2.4 Measurement Results Explanation Example	12
3 TEST RESULT	13
3.1 Conducted Output Power Measurement.....	13
3.2 Peak-to-Average Ratio	15
3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement	24
3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement.....	30
3.5 Band Edge Measurement.....	50
3.6 Conducted Spurious Emission Measurement.....	63
3.7 Field Strength of Spurious Radiation Measurement	80
3.8 Frequency Stability Measurement.....	100
4 LIST OF MEASURING EQUIPMENT	105
5 UNCERTAINTY OF EVALUATION	106
APPENDIX A. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG463001	Rev. 01	Initial issue of report	Aug. 28, 2014

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	§2.1046	Conducted Output Power	N/A	PASS	-
3.2	§24.232(d)	Peak-to-Average Ratio	<13 dB	PASS	-
3.3	§22.913(a)(2)	Effective Radiated Power	< 7 Watts	PASS	-
3.3	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
3.4	§2.1049 §22.917(b) §24.238(b)	Occupied Bandwidth	N/A	PASS	-
3.5	§2.1051 §22.917(a) §24.238(a)	Band Edge Measurement	$< 43 + 10 \log_{10}(P[\text{Watts}])$	PASS	-
3.6	§2.1051 §22.917(a) §24.238(a)	Conducted Spurious Emission	$< 43 + 10 \log_{10}(P[\text{Watts}])$	PASS	-
3.7	§2.1053 §22.917(a) §24.238(a)	Field Strength of Spurious Radiation	$< 43 + 10 \log_{10}(P[\text{Watts}])$	PASS	Under limit 18.77 dB at 1697.600 MHz
3.8	§2.1055 §22.355 §24.235	Frequency Stability for Temperature & Voltage	< 2.5 ppm	PASS	-



1 General Description

1.1 Applicant

TCT Mobile Limited

5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park, Pudong Area Shanghai, P.R. China. 201203

1.2 Manufacturer

TCT Mobile Limited

5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park, Pudong Area Shanghai, P.R. China. 201203

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Tablet PC
Brand Name	ALCATEL ONETOUCH
Model Name	I216A
Marketing Name	ALCATEL ONETOUCH PIXI 7
FCC ID	RAD512
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/HSPA+(Downlink Only)/ WLAN 2.4GHz 802.11b/g/n HT20/HT40/ Bluetooth v3.0 +EDR/ Bluetooth v4.0 LE
HW Version	v04
SW Version	CDF
EUT Stage	Production Unit

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification subjective to this standard

Product Specification subjective to this standard	
Tx Frequency	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz
Rx Frequency	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band II: 1932.4 MHz ~ 1987.6 MHz
Maximum Output Power to Antenna	GSM850 : 33.04 dBm GSM1900 : 30.05 dBm WCDMA Band V : 22.90 dBm WCDMA Band II : 23.08 dBm
Antenna Type	Monopole Antenna
Type of Modulation	GSM: GMSK GPRS: GMSK EDGE: GMSK / 8PSK WCDMA: QPSK (Uplink) HSDPA: QPSK (Uplink) HSUPA: QPSK (Uplink) HSPA+: 16QAM (Downlink Only)

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W)	Frequency Tolerance (ppm)	Emission Designator
Part 22	GSM850 GSM	GMSK	0.81	0.033 ppm	249KGXW
Part 22	GSM850 EDGE class 8	8PSK	0.22	0.033 ppm	245KG7W
Part 22	WCDMA Band V RMC 12.2Kbps	QPSK	0.11	0.012 ppm	4M18F9W
Part 24	GSM1900 GSM	GMSK	0.96	0.031 ppm	250KGXW
Part 24	GSM1900 EDGE class 8	8PSK	0.11	0.031 ppm	250KG7W
Part 24	WCDMA Band II RMC 12.2Kbps	QPSK	0.23	0.007 ppm	4M17F9W

1.7 Testing Location

Test Site	SPORTON INTERNATIONAL (SHENZHEN) INC.		
Test Site Location	No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P.R.C. TEL: +86-755-3320-2398		
Test Site No.	Sporton Site No.		FCC Registration No.
	TH01-SZ	03CH01-SZ	831040

Test Site	SPORTON INTERNATIONAL (SHENZHEN) INC.		
Test Site Location	No. 101, Complex Building C, Guanlong Village, Xili Town, Nanshan District, Shenzhen, Guangdong, P.R.C. TEL: +86-755-8637-9589 FAX: +86-755-8637-9595		
Test Site No.	Sporton Site No.		
	OTA01-SZ		



1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC 47 CFR Part 2, 22(H), 24(E)
- ♦ ANSI / TIA / EIA-603-C-2004
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v02r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v02r01 with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.

Radiated emissions were investigated as following frequency range:

1. 30 MHz to 9000 MHz for GSM850 and WCDMA Band V.
2. 30 MHz to 19000 MHz for GSM1900 and WCDMA Band II.

All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	■ GSM Link ■ EDGE class 8 Lin	■ GSM Link ■ EDGE class 8 Link
GSM 1900	■ GSM Link ■ EDGE class 8 Link	■ GSM Link ■ EDGE class 8 Link
WCDMA Band V	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band II	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link

Note: The maximum power levels are chosen to test as the worst case configuration as follows:

GSM mode for GMSK modulation,

EDGE multi-slot class 8 mode for 8PSK modulation,

RMC 12.2Kbps mode for WCDMA band V,

RMC 12.2Kbps mode for WCDMA band II, only these modes were used for all tests.




Conducted Power Measurement Results:

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GSM	32.98	33.01	33.04	30.03	30.04	30.05
GPRS class 8	32.97	33.00	33.03	30.00	30.01	30.02
GPRS class 10	31.27	31.33	31.37	28.32	28.33	28.34
GPRS class 11	29.29	29.34	29.37	26.35	26.36	26.38
GPRS class 12	27.86	27.92	27.97	24.90	24.92	24.95
EGPRS class 8	27.26	27.12	27.05	26.07	26.04	25.89
EGPRS class 10	26.08	25.91	25.87	24.98	24.95	24.78
EGPRS class 11	24.85	24.70	24.64	23.83	23.82	23.64
EGPRS class 12	23.65	23.46	23.43	22.61	22.58	22.41

Conducted Power (*Unit: dBm)						
Band	WCDMA Band V			WCDMA Band II		
Channel	4132	4182	4233	9262	9400	9538
Frequency	826.4	836.4	846.6	1852.4	1880.0	1907.6
AMR 12.2Kbps	22.72	22.89	22.82	23.00	23.05	22.97
RMC 12.2Kbps	22.75	22.90	22.85	23.01	23.08	22.99
HSDPA Subtest-1	21.87	21.96	21.92	22.16	22.21	22.13
HSDPA Subtest-2	21.86	21.94	21.90	22.13	22.19	22.11
HSDPA Subtest-3	21.44	21.54	21.46	21.68	21.77	21.65
HSDPA Subtest-4	21.42	21.53	21.48	21.71	21.76	21.69
HSUPA Subtest-1	19.78	19.85	19.82	19.95	19.98	19.96
HSUPA Subtest-2	19.87	19.97	19.91	20.01	20.04	20.02
HSUPA Subtest-3	20.68	20.73	20.71	20.83	20.87	20.86
HSUPA Subtest-4	19.43	19.50	19.49	19.54	19.59	19.57
HSUPA Subtest-5	20.46	20.58	20.52	20.80	20.85	20.84

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	TOPWORD	3303DR	N/A	N/A	Unshielded, 1.8 m



2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 7.0 dB and a 10 dB attenuator.

Example:

$$\begin{aligned}\text{Offset (dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 7.0 + 10 = 17.0 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.

3.1.4 Test Setup



3.1.5 Test Result of Conducted Output Power

Cellular Band									
Modes	GSM850 (GSM)			GSM850 (EDGE class 8)			WCDMA Band V (RMC 12.2Kbps)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8	826.4	836.4	846.6
Conducted Power (dBm)	32.98	33.01	33.04	27.26	27.12	27.05	22.75	22.90	22.85
Conducted Power (Watts)	1.99	2.00	2.01	0.53	0.52	0.51	0.19	0.19	0.19

PCS Band									
Modes	GSM1900 (GSM)			GSM1900 (EDGE class 8)			WCDMA Band II (RMC 12.2Kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8	1852.4	1880	1907.6
Conducted Power (dBm)	30.03	30.04	30.05	26.07	26.04	25.89	23.01	23.08	22.99
Conducted Power (Watts)	1.01	1.01	1.01	0.40	0.40	0.39	0.20	0.20	0.20

Note: Maximum burst average power for GSM, and maximum average power for WCDMA

3.2 Peak-to-Average Ratio

3.2.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows FCC KDB 971168 v02r01 Section 5.7.1.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. For GSM/EGPRS operating modes:
 - a. Set EUT in maximum power output.
 - b. Set the RBW = 1MHz, VBW = 3MHz, Peak detector on spectrum analyzer for first trace.
 - c. Set the RBW = 1MHz, VBW = 3MHz, RMS detector on spectrum analyzer for second trace.
 - d. The wanted burst signal is triggered by spectrum analyzer, and measured respectively the peak level and Mean level without burst-off time, after system simulator has synchronized with the spectrum analyzer.
4. For UMTS operating modes:
 - a. Set the CCDF (Complementary Cumulative Distribution Function) option on the spectrum analyzer.
 - b. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.

3.2.4 Test Setup



3.2.5 Test Result of Peak-to-Average Ratio


PCS Band									
Modes	GSM1900 (GSM)			GSM1900 (EDGE class 8)			WCDMA Band II (RMC 12.2Kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8	1852.4	1880	1907.6
Peak-to-Average Ratio (dB)	0.29	0.29	0.29	2.66	2.70	2.72	3.01	3.01	2.90



3.2.6 Test Result (Plots) of Peak-to-Average Ratio


Band :	GSM 1900	Test Mode :	GSM Link (GMSK)
--------	----------	-------------	-----------------

Peak-to-Average Ratio on Channel 512 (1850.2 MHz)



Date: 31.JUL.2014 17:19:00


Peak-to-Average Ratio on Channel 661 (1880.0 MHz)



Date: 31.JUL.2014 17:20:10



Peak-to-Average Ratio on Channel 810 (1909.8 MHz)




Date: 31.JUL.2014 17:22:21




Band :	GSM 1900	Test Mode :	EDGE class 8 Link (8PSK)
--------	----------	-------------	--------------------------

Peak-to-Average Ratio on Channel 512 (1850.2 MHz)




Peak-to-Average Ratio on Channel 661 (1880.0 MHz)





Peak-to-Average Ratio on Channel 810 (1909.8 MHz)




Date: 31.JUL.2014 17:37:54




Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	---------------	-------------	--------------------------

Peak-to-Average Ratio on Channel 9262 (1852.4 MHz)



Date: 31.JUL.2014 15:04:13


Peak-to-Average Ratio on Channel 9400 (1880.0 MHz)



Date: 31.JUL.2014 15:05:35



Peak-to-Average Ratio on Channel 9538 (1907.6 MHz)



Date: 31. JUL. 2014 15:06:22

3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

3.3.1 Description of the ERP/EIRP Measurement

The substitution method, in ANSI / TIA / EIA-603-C-2004, was used for ERP/EIRP measurement, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v02r01. The ERP of mobile transmitters must not exceed 7 Watts and the EIRP of mobile transmitters are limited to 2 Watts.


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows FCC KDB 971168 v02r01 Section 5.2.1. (for CDMA/WCDMA), Section 5.2.2.2 (for GSM/GPRS/EDGE) and ANSI / TIA-603-C-2004 Section 2.2.17.
2. The EUT was placed on a turntable 1.5 meters high in a fully anechoic chamber.
3. The EUT was placed 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. GSM operating modes: Set RBW= 1MHz, VBW= 3MHz, RMS detector over burst;
UMTS operating modes: Set RBW= 100 kHz, VBW= 300 kHz, RMS detector over frame, and use channel power option with bandwidth=5MHz, per KDB 971168 D01.
5. The table was rotated 360 degrees to determine the position of the highest radiated power.
6. The height of the receiving antenna is adjusted to look for the maximum ERP/EIRP.
7. Taking the record of maximum ERP/EIRP.
8. A dipole antenna was substituted in place of the EUT and was driven by a signal generator.
9. The conducted power at the terminal of the dipole antenna is measured.
10. Repeat step 3 to step 5 to get the maximum ERP/EIRP of the substitution antenna.
11. $ERP/EIRP = P_s + E_t - E_s + G_s = P_s + R_t - R_s + G_s$
 P_s (dBm) : Input power to substitution antenna.
 G_s (dBi or dBd) : Substitution antenna Gain.
 $E_t = R_t + AF$
 $E_s = R_s + AF$
 AF (dB/m) : Receive antenna factor
 R_t : The highest received signal in spectrum analyzer for EUT.
 R_s : The highest received signal in spectrum analyzer for substitution antenna.

3.3.4 Test Setup



3.3.5 Test Result of ERP

GSM850 (GSM) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-18.80	-48.12	0.00	-1.08	28.24	0.67
836.40	-19.11	-48.28	0.00	-0.93	28.24	0.67
848.80	-19.27	-48.35	0.00	-0.76	28.32	0.68
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-18.49	-47.97	0.00	-1.08	28.40	0.69
836.40	-18.24	-48.01	0.00	-0.93	28.84	0.77
848.80	-18.20	-48.05	0.00	-0.76	29.09	0.81

GSM850 (EDGE class 8) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-24.82	-48.12	0.00	-1.08	22.22	0.17
836.40	-24.93	-48.28	0.00	-0.93	22.42	0.17
848.80	-24.91	-48.35	0.00	-0.76	22.68	0.19
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-24.29	-47.97	0.00	-1.08	22.60	0.18
836.40	-24.08	-48.01	0.00	-0.93	23.00	0.20
848.80	-23.80	-48.05	0.00	-0.76	23.49	0.22

WCDMA Band V (RMC 12.2Kbps) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
826.40	-28.97	-48.12	0.00	-1.08	18.07	0.06
836.40	-29.49	-48.28	0.00	-0.93	17.86	0.06
846.60	-27.88	-48.35	0.00	-0.76	19.71	0.09
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
826.40	-28.40	-47.97	0.00	-1.08	18.49	0.07
836.40	-28.70	-48.01	0.00	-0.93	18.38	0.07
846.60	-26.96	-48.05	0.00	-0.76	20.33	0.11

3.3.6 Test Result of EIRP

GSM1900 (GSM) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-26.21	-51.88	0.00	1.96	27.63	0.58
1880.00	-26.98	-52.99	0.00	2.00	28.01	0.63
1909.80	-27.65	-54.28	0.00	1.98	28.61	0.73
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-24.65	-52.13	0.00	1.96	29.44	0.88
1880.00	-25.36	-53.17	0.00	2.00	29.81	0.96
1909.80	-26.53	-54.13	0.00	1.98	29.58	0.91

GSM1900 (EDGE class 8) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-35.41	-51.88	0.00	1.96	18.44	0.07
1880.00	-36.19	-52.99	0.00	2.00	18.80	0.08
1909.80	-37.14	-54.28	0.00	1.98	19.12	0.08
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-33.91	-52.13	0.00	1.96	20.18	0.10
1880.00	-34.64	-53.17	0.00	2.00	20.53	0.11
1909.80	-36.05	-54.13	0.00	1.98	20.06	0.10



WCDMA Band II (RMC 12.2Kbps) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1852.40	-32.82	-51.88	0.00	1.96	21.02	0.13
1880.00	-33.10	-52.99	0.00	2.00	21.89	0.15
1907.60	-34.34	-54.28	0.00	1.98	21.92	0.16
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1852.40	-31.26	-52.13	0.00	1.96	22.83	0.19
1880.00	-31.57	-53.17	0.00	2.00	23.60	0.23
1907.60	-33.07	-54.13	0.00	1.98	23.04	0.20

3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.4.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB 971168 v02r01 Section 4.2.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of the EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The 99% occupied bandwidth were measured, set RBW= 1% of span, VBW= 3*RBW, sample detector, trace maximum hold.
5. The 26dB bandwidth were measured, set RBW= 1% of EBW, VBW= 3*RBW, peak detector, trace maximum hold.

3.4.4 Test Setup



3.4.5 Test Result of 99% Occupied Bandwidth and 26dB Bandwidth

Cellular Band						
Modes	GSM850 (GSM)			GSM850 (EDGE class 8)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8
99% OBW (kHz)	248.914	246.020	247.467	243.125	244.570	241.678
26dB BW (kHz)	311.100	309.700	306.800	299.600	293.800	298.100

PCS Band						
Modes	GSM1900 (GSM)			GSM1900 (EDGE class 8)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8
99% OBW (kHz)	248.910	250.360	247.470	248.914	247.467	250.361
26dB BW (kHz)	306.800	314.000	302.500	289.400	305.400	306.800

Cellular Band			
Modes	WCDMA Band V (RMC 12.2Kbps)		
Channel	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	826.4	836.4	846.6
99% OBW (MHz)	4.182	4.167	4.153
26dB BW (MHz)	4.689	4.689	4.674


PCS Band			
Modes	WCDMA Band II (RMC 12.2Kbps)		
Channel	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1852.4	1880	1907.6
99% OBW (MHz)	4.167	4.167	4.153
26dB BW (MHz)	4.689	4.674	4.674



3.4.6 Test Result (Plots) of 99% Occupied Bandwidth and 26dB Bandwidth


Band :	GSM 850	Test Mode :	GSM Link (GMSK)
--------	---------	-------------	-----------------

99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 31.JUL.2014 09:26:44


26dB Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 31.JUL.2014 09:16:38




99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 31.JUL.2014 09:27:45


26dB Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 31.JUL.2014 09:19:27




99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)



Date: 31.JUL.2014 09:30:10

26dB Bandwidth Plot on Channel 251 (848.8 MHz)




Date: 31.JUL.2014 09:22:19




Band :	GSM 850	Test Mode :	EDGE class 8 Link (8PSK)
--------	---------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)




26dB Bandwidth Plot on Channel 128 (824.2 MHz)






99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 31.JUL.2014 11:41:45


26dB Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 31.JUL.2014 11:35:31




99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)



Date: 31.JUL.2014 11:38:01

26dB Bandwidth Plot on Channel 251 (848.8 MHz)




Date: 31.JUL.2014 11:36:25




Band :	GSM 1900	Test Mode :	GSM Link (GMSK)
--------	----------	-------------	-----------------

99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 31.JUL.2014 10:07:26


26dB Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 31.JUL.2014 10:00:15




99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 31.JUL.2014 10:06:09


26dB Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 31.JUL.2014 10:01:39




99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)



Date: 31.JUL.2014 10:05:18

26dB Bandwidth Plot on Channel 810 (1909.8 MHz)




Date: 31.JUL.2014 10:02:18




Band :	GSM 1900	Test Mode :	EDGE class 8 Link (8PSK)
--------	----------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 31.JUL.2014 10:54:47


26dB Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 31.JUL.2014 10:48:47




99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)




Date: 31.JUL.2014 10:54:07

26dB Bandwidth Plot on Channel 661 (1880.0 MHz)




Date: 31.JUL.2014 10:49:57

99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)



Date: 31.JUL.2014 10:52:04

26dB Bandwidth Plot on Channel 810 (1909.8 MHz)




Date: 31.JUL.2014 10:50:39




Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	--------------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 4132 (826.4 MHz)



Date: 31.JUL.2014 14:04:16


26dB Bandwidth Plot on Channel 4132 (826.4 MHz)



Date: 31.JUL.2014 13:56:59




99% Occupied Bandwidth Plot on Channel 4182 (836.4 MHz)



Date: 31.JUL.2014 14:01:56


26dB Bandwidth Plot on Channel 4182 (836.4 MHz)



Date: 31.JUL.2014 13:58:52




99% Occupied Bandwidth Plot on Channel 4233 (846.6 MHz)



Date: 31.JUL.2014 14:00:54

26dB Bandwidth Plot on Channel 4233 (846.6 MHz)




Date: 31.JUL.2014 13:59:37




Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	---------------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 9262 (1852.4 MHz)



Date: 31.JUL.2014 14:34:39


26dB Bandwidth Plot on Channel 9262 (1852.4 MHz)



Date: 31.JUL.2014 14:26:21




99% Occupied Bandwidth Plot on Channel 9400 (1880.0 MHz)



Date: 31.JUL.2014 14:31:19


26dB Bandwidth Plot on Channel 9400 (1880.0 MHz)



Date: 31.JUL.2014 14:27:09




99% Occupied Bandwidth Plot on Channel 9538 (1907.6 MHz)



Date: 31.JUL.2014 14:29:50

26dB Bandwidth Plot on Channel 9538 (1907.6 MHz)



Date: 31.JUL.2014 14:27:57

3.5 Band Edge Measurement

3.5.1 Description of Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.


3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The testing follows FCC KDB 971168 v02r01 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The band edges of low and high channels for the highest RF powers were measured.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$


3.5.4 Test Setup



3.5.5 Test Result (Plots) of Conducted Band Edge

Band :	GSM850	Test Mode :	GSM Link (GMSK)
Correction Factor :	0.16dB	Maximum 26dB Bandwidth :	0.311MHz
Band Edge :	-16.40dBm	Measurement Value :	-16.56dBm


Lower Band Edge Plot on Channel 128 (824.2 MHz)



1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


Band :	GSM850	Test Mode :	GSM Link (GMSK)
Correction Factor :	0.16dB	Maximum 26dB Bandwidth :	0.311MHz
Band Edge :	-15.83dBm	Measurement Value :	-15.99dBm

Higher Band Edge Plot on Channel 251 (848.8 MHz)




1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)

Band :	GSM850	Test Mode :	EDGE class 8 Link (8PSK)
Correction Factor :	-0.01dB	Maximum 26dB Bandwidth :	0.300MHz
Band Edge :	-21.80dBm	Measurement Value :	-21.79dBm

Lower Band Edge Plot on Channel 128 (824.2 MHz)





Band :	GSM850	Test Mode :	EDGE class 8 Link (8PSK)
Correction Factor :	-0.01dB	Maximum 26dB Bandwidth :	0.300MHz
Band Edge :	-21.20dBm	Measurement Value :	-21.19dBm

Higher Band Edge Plot on Channel 251 (848.8 MHz)

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


Band :	GSM1900	Test Mode :	GSM Link (GMSK)
Correction Factor :	0.20dB	Maximum 26dB Bandwidth :	0.314MHz
Band Edge :	-17.90dBm	Measurement Value :	-18.10dBm

Lower Band Edge Plot on Channel 512 (1850.2 MHz)


1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	GSM1900	Test Mode :	GSM Link (GMSK)
Correction Factor :	0.20dB	Maximum 26dB Bandwidth :	0.314MHz
Band Edge :	-18.37dBm	Measurement Value :	-18.57dBm


Higher Band Edge Plot on Channel 810 (1909.8 MHz)

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	GSM1900	Test Mode :	EDGE class 8 Link (8PSK)
Correction Factor :	0.10dB	Maximum 26dB Bandwidth :	0.307MHz
Band Edge :	-24.57dBm	Measurement Value :	-24.67dBm

Lower Band Edge Plot on Channel 512 (1850.2 MHz)



1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)




Band :	GSM1900	Test Mode :	EDGE class 8 Link (8PSK)
Correction Factor :	0.10dB	Maximum 26dB Bandwidth :	0.307MHz
Band Edge :	-26.51dBm	Measurement Value :	-26.61dBm

Higher Band Edge Plot on Channel 810 (1909.8 MHz)

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)




Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link (QPSK)
Correction Factor :	-3.29dB	Maximum 26dB Bandwidth :	4.689MHz
Band Edge :	-28.56dBm	Measurement Value :	-25.27dBm

Lower Band Edge Plot on Channel 4132 (826.4 MHz)


1. $Correction\ Factor(dB) = 10\log(1\% \text{ Emission } BW/RBW)$
2. $Band\ Edge = Measurement\ Value + Correction\ Factor(dB)$

Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link (QPSK)
Correction Factor :	-3.29dB	Maximum 26dB Bandwidth :	4.689MHz
Band Edge :	-28.49dBm	Measurement Value :	-25.20dBm

Higher Band Edge Plot on Channel 4233 (846.6 MHz)



1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)

Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)
Correction Factor :	-3.29dB	Maximum 26dB Bandwidth :	4.689MHz
Band Edge :	-28.53dBm	Measurement Value :	-25.24dBm

Lower Band Edge Plot on Channel 9262 (1852.4 MHz)


1. $Correction\ Factor(dB) = 10\log(1\% \text{ Emission } BW/RBW)$
2. $Band\ Edge = Measurement\ Value + Correction\ Factor(dB)$

Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)
Correction Factor :	-3.29dB	Maximum 26dB Bandwidth :	4.689MHz
Band Edge :	-27.79dBm	Measurement Value :	-24.50dBm

Higher Band Edge Plot on Channel 9538 (1907.6 MHz)


3.6 Conducted Spurious Emission Measurement

3.6.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The testing follows FCC KDB 971168 v02r01 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator.
The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)]$ (dB)
 $= [30 + 10\log(P)]$ (dBm) - $[43 + 10\log(P)]$ (dB)
 $= -13\text{dBm}$.

3.6.4 Test Setup






3.6.5 Test Result (Plots) of Conducted Spurious Emission


Band :	GSM850	Channel :	CH189
Test Mode :	GSM Link (GMSK)	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 31.JUL.2014 09:47:15


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 1.AUG.2014 09:50:42




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 31.JUL.2014 09:53:07


Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 31.JUL.2014 09:54:13



Band :	GSM850	Channel :	CH189
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz


Date: 31.JUL.2014 11:48:23

Conducted Spurious Emission Plot between 1GHz ~ 3GHz

Date: 31.JUL.2014 11:54:45




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 31.JUL.2014 11:55:44


Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 31.JUL.2014 11:56:22



Band :	GSM1900	Channel :	CH661
Test Mode :	GSM Link (GMSK)	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz


Date: 31.JUL.2014 10:13:28

Conducted Spurious Emission Plot between 1GHz ~ 3GHz

Date: 31.JUL.2014 10:12:56




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 31.JUL.2014 10:36:04


Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 31.JUL.2014 10:37:18




Conducted Spurious Emission Plot between 13.6GHz ~ 19.2GHz






Band :	GSM1900	Channel :	CH661
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz


Date: 31.JUL.2014 10:47:20

Conducted Spurious Emission Plot between 1GHz ~ 3GHz

Date: 31.JUL.2014 10:46:49




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 31.JUL.2014 10:45:36


Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 31.JUL.2014 10:44:51




Conducted Spurious Emission Plot between 13.6GHz ~ 19.2GHz






Band :	WCDMA Band V	Channel :	CH4182
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 31.JUL.2014 13:52:23


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 31.JUL.2014 13:51:05




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 31.JUL.2014 13:50:09


Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 31.JUL.2014 13:48:51



Band :	WCDMA Band II	Channel :	CH9400
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz


Date: 31.JUL.2014 14:55:16

Conducted Spurious Emission Plot between 1GHz ~ 3GHz

Date: 31.JUL.2014 14:54:37




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 31.JUL.2014 14:53:12


Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 31.JUL.2014 14:52:06



Conducted Spurious Emission Plot between 13.6GHz ~ 19.2GHz



3.7 Field Strength of Spurious Radiation Measurement

3.7.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

3.7.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.7.3 Test Procedures


1. The testing follows FCC KDB 971168 v02r01 Section 5.8 and ANSI / TIA-603-C-2004 Section 2.2.12.
2. The EUT was placed on a rotatable wooden table 0.8 meters above the ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11. $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
12. $ERP \text{ (dBm)} = EIRP - 2.15$
13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
14. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$

3.7.4 Test Setup

For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.7.5 Test Result of Field Strength of Spurious Radiated

Band :	GSM850 for CH128				Temperature :	23~25°C			
Test Mode :	GSM Link (GMSK)				Relative Humidity :	48~52%			
Test Engineer :	Gavin Zhang				Polarization :	Horizontal			
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
1648.4	-33.16	-13	-20.16	-50.65	-35.98	0.73	5.70	H	Pass
2472.6	-46.59	-13	-33.59	-69.56	-48.95	0.91	5.42	H	Pass
3296.8	-61.31	-13	-48.31	-72.18	-65.95	1.07	7.86	H	Pass

Band :	GSM850 for CH128					Temperature :	23~25°C		
Test Mode :	GSM Link (GMSK)					Relative Humidity :	48~52%		
Test Engineer :	Gavin Zhang					Polarization :	Vertical		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1648.4	-37.48	-13	-24.48	-51.94	-40.30	0.73	5.70	V	Pass
2472.6	-50.21	-13	-37.21	-70.31	-52.57	0.91	5.42	V	Pass
3296.8	-59.72	-13	-46.72	-71.90	-64.36	1.07	7.86	V	Pass



Band :	GSM850 for CH189	Temperature :	23~25°C						
Test Mode :	GSM Link (GMSK)	Relative Humidity :	48~52%						
Test Engineer :	Gavin Zhang	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit	Reading	Power	loss	Gain	(H/V)	
(dB)	(dB)	(dB)	(dB)	(dBm)	(dBm)	(dB)	(dBi)		
1672	-32.73	-13	-19.73	-49.55	-35.70	0.88	6.00	H	Pass
2510	-44.76	-13	-31.76	-67.86	-47.37	1.08	5.84	H	Pass
3346	-61.57	-13	-48.57	-72.17	-65.94	1.14	7.66	H	Pass

Band :	GSM850 for CH189	Temperature :	23~25°C						
Test Mode :	GSM Link (GMSK)	Relative Humidity :	48~52%						
Test Engineer :	Gavin Zhang	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit	Reading	Power	loss	Gain	(H/V)	
(dB)	(dB)	(dB)	(dB)	(dBm)	(dBm)	(dB)	(dBi)		
1672	-37.63	-13	-24.63	-51.55	-40.60	0.88	6.00	V	Pass
2510	-49.87	-13	-36.87	-69.82	-52.48	1.08	5.84	V	Pass
3346	-60.45	-13	-47.45	-72.28	-64.82	1.14	7.66	V	Pass



Band :	GSM850 for CH251	Temperature :	23~25℃						
Test Mode :	GSM Link (GMSK)	Relative Humidity :	48~52%						
Test Engineer :	Gavin Zhang	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1697.6	-31.77	-13	-18.77	-48.47	-34.76	0.75	5.89	H	Pass
2546.4	-42.70	-13	-29.70	-66.79	-45.41	1.12	5.98	H	Pass
3395.2	-60.78	-13	-47.78	-71.98	-65.18	1.25	7.80	H	Pass

Band :	GSM850 for CH251	Temperature :	23~25°C						
Test Mode :	GSM Link (GMSK)	Relative Humidity :	48~52%						
Test Engineer :	Gavin Zhang	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit	Reading	Power	loss	Gain	(H/V)	
(dB)	(dB)	(dB)	(dB)	(dBm)	(dBm)	(dB)	(dBi)		
1697.6	-35.91	-13	-22.91	-50.29	-38.90	0.75	5.89	V	Pass
2546.4	-49.46	-13	-36.46	-69.82	-52.17	1.12	5.98	V	Pass
3395.2	-59.44	-13	-46.44	-71.87	-63.84	1.25	7.80	V	Pass



Band :	GSM850 for CH128	Temperature :	23~25°C						
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	48~52%						
Test Engineer :	Gavin Zhang	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1648.4	-52.15	-13	-39.15	-66.23	-54.97	0.73	5.70	H	Pass
2472.6	-48.20	-13	-35.20	-70.46	-50.56	0.91	5.42	H	Pass
3296.8	-61.11	-13	-48.11	-71.98	-65.75	1.07	7.86	H	Pass

Band :	GSM850 for CH128	Temperature :	23~25°C						
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	48~52%						
Test Engineer :	Gavin Zhang	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1648.4	-56.01	-13	-43.01	-67.16	-58.83	0.73	5.70	V	Pass
2472.6	-50.66	-13	-37.66	-70.56	-53.02	0.91	5.42	V	Pass
3296.8	-59.64	-13	-46.64	-71.82	-64.28	1.07	7.86	V	Pass



Band :	GSM850 for CH189	Temperature :	23~25°C						
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	48~52%						
Test Engineer :	Gavin Zhang	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit	Reading	Power	loss	Gain	(H/V)	
1672	-42.00	-13	-29.00	-58.34	-44.97	0.88	6.00	H	Pass
2510	-48.00	-13	-35.00	-70.10	-50.61	1.08	5.84	H	Pass
3346	-61.53	-13	-48.53	-72.13	-65.90	1.14	7.66	H	Pass

Band :	GSM850 for CH189	Temperature :	23~25°C						
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	48~52%						
Test Engineer :	Gavin Zhang	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1672	-43.21	-13	-30.21	-56.56	-46.18	0.88	6.00	V	Pass
2510	-50.58	-13	-37.58	-70.22	-53.19	1.08	5.84	V	Pass
3346	-60.63	-13	-47.63	-72.46	-65.00	1.14	7.66	V	Pass



Band :	GSM850 for CH251	Temperature :	23~25°C						
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	48~52%						
Test Engineer :	Gavin Zhang	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1697.6	-51.16	-13	-38.16	-65.86	-54.15	0.75	5.89	H	Pass
2546.4	-47.80	-13	-34.80	-70.39	-50.51	1.12	5.98	H	Pass
3395.2	-60.52	-13	-47.52	-71.72	-64.92	1.25	7.80	H	Pass

Band :	GSM850 for CH251	Temperature :	23~25°C						
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	48~52%						
Test Engineer :	Gavin Zhang	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1697.6	-58.49	-13	-45.49	-69.47	-61.48	0.75	5.89	V	Pass
2546.4	-48.19	-13	-35.19	-69.05	-50.90	1.12	5.98	V	Pass
3395.2	-59.20	-13	-46.20	-71.63	-63.60	1.25	7.80	V	Pass



Band :	GSM1900 for CH512	Temperature :	23~25°C						
Test Mode :	GSM Link (GMSK)	Relative Humidity :	48~52%						
Test Engineer :	Gavin Zhang	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit	Reading	Power	loss	Gain		
			(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
3700.4	-61.35	-13	-48.35	-72.90	-68.10	1.2	7.95	H	Pass
5550.6	-56.83	-13	-43.83	-74.22	-64.93	1.5	9.60	H	Pass
7400.8	-53.63	-13	-40.63	-75.21	-63.82	1.7	11.89	H	Pass

Band :	GSM1900 for CH512	Temperature :	23~25°C						
Test Mode :	GSM Link (GMSK)	Relative Humidity :	48~52%						
Test Engineer :	Gavin Zhang	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit	Reading	Power	loss	Gain		
			(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
3700.4	-58.84	-13	-45.84	-73.27	-65.59	1.2	7.95	V	Pass
5550.6	-57.08	-13	-44.08	-73.56	-65.18	1.5	9.6	V	Pass
7400.8	-53.56	-13	-40.56	-75.45	-63.75	1.7	11.89	V	Pass



Band :	GSM1900 for CH661	Temperature :	23~25°C						
Test Mode :	GSM Link (GMSK)	Relative Humidity :	48~52%						
Test Engineer :	Gavin Zhang	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit	Reading	Power	loss	Gain	(H/V)	
			(dB)	(dBm)	(dBm)	(dB)	(dBi)		
3760	-60.53	-13	-47.53	-72.68	-67.27	1.28	8.02	H	Pass
5640	-55.44	-13	-42.44	-73.43	-63.86	1.58	10.00	H	Pass
7520	-51.94	-13	-38.94	-73.88	-62.26	1.78	12.10	H	Pass

Band :	GSM1900 for CH661	Temperature :	23~25°C						
Test Mode :	GSM Link (GMSK)	Relative Humidity :	48~52%						
Test Engineer :	Gavin Zhang	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit	Reading	Power	loss	Gain	(H/V)	
(dB)			(dB)	(dBm)	(dBm)	(dB)	(dBi)		
3760	-57.99	-13	-44.99	-73.02	-64.73	1.28	8.02	V	Pass
5640	-56.18	-13	-43.18	-73.26	-64.60	1.58	10	V	Pass
7520	-53.11	-13	-40.11	-75.36	-63.43	1.78	12.1	V	Pass



Band :	GSM1900 for CH810	Temperature :	23~25°C						
Test Mode :	GSM Link (GMSK)	Relative Humidity :	48~52%						
Test Engineer :	Gavin Zhang	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
3819.6	-61.52	-13	-48.52	-73.09	-68.29	1.23	8.00	H	Pass
5729.4	-55.42	-13	-42.42	-73.22	-63.55	1.52	9.65	H	Pass
7639.2	-53.31	-13	-40.31	-75.55	-63.49	1.82	12.00	H	Pass

Band :	GSM1900 for CH810	Temperature :	23~25°C						
Test Mode :	GSM Link (GMSK)	Relative Humidity :	48~52%						
Test Engineer :	Gavin Zhang	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit	Reading	Power	loss	Gain		
			(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
3819.6	-58.65	-13	-45.65	-73.1	-65.42	1.23	8	V	Pass
5729.4	-56.75	-13	-43.75	-73.64	-64.88	1.52	9.65	V	Pass
7639.2	-52.64	-13	-39.64	-75.19	-62.82	1.82	12	V	Pass



Band :	GSM1900 for CH512	Temperature :	23~25°C						
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	48~52%						
Test Engineer :	Gavin Zhang	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
3700.4	-62.25	-13	-49.25	-73.80	-69.00	1.2	7.95	H	Pass
5550.6	-56.67	-13	-43.67	-74.06	-64.77	1.5	9.60	H	Pass
7400.8	-54.33	-13	-41.33	-75.91	-64.52	1.7	11.89	H	Pass

Band :	GSM1900 for CH512	Temperature :	23~25°C						
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	48~52%						
Test Engineer :	Gavin Zhang	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
3700.4	-57.38	-13	-44.38	-71.81	-64.13	1.2	7.95	V	Pass
5550.6	-57.47	-13	-44.47	-73.95	-65.57	1.5	9.6	V	Pass
7400.8	-54.47	-13	-41.47	-76.36	-64.66	1.7	11.89	V	Pass



Band :	GSM1900 for CH661	Temperature :	23~25°C						
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	48~52%						
Test Engineer :	Gavin Zhang	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit	Reading	Power	loss	Gain	(H/V)	
(dB)	(dB)	(dB)	(dB)	(dBm)	(dBm)	(dB)	(dBi)		
3760	-60.96	-13	-47.96	-73.11	-67.70	1.28	8.02	H	Pass
5640	-55.89	-13	-42.89	-73.88	-64.31	1.58	10.00	H	Pass
7520	-53.84	-13	-40.84	-75.78	-64.16	1.78	12.10	H	Pass

Band :	GSM1900 for CH661	Temperature :	23~25°C						
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	48~52%						
Test Engineer :	Gavin Zhang	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over Limit	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	(dB)	Reading	Power	loss	Gain	(H/V)	
3760	-58.37	-13	-45.37	-73.4	-65.11	1.28	8.02	V	Pass
5640	-55.57	-13	-42.57	-72.65	-63.99	1.58	10	V	Pass
7520	-53.87	-13	-40.87	-76.12	-64.19	1.78	12.1	V	Pass



Band :	GSM1900 for CH810	Temperature :	23~25°C						
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	48~52%						
Test Engineer :	Gavin Zhang	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
3819.6	-62.05	-13	-49.05	-73.62	-68.82	1.23	8.00	H	Pass
5729.4	-55.74	-13	-42.74	-73.54	-63.87	1.52	9.65	H	Pass
7639.2	-53.82	-13	-40.82	-76.06	-64.00	1.82	12.00	H	Pass

Band :	GSM1900 for CH810	Temperature :	23~25°C						
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	48~52%						
Test Engineer :	Gavin Zhang	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over Limit	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	(dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
3819.6	-59.45	-13	-46.45	-73.9	-66.22	1.23	8	V	Pass
5729.4	-56.95	-13	-43.95	-73.84	-65.08	1.52	9.65	V	Pass
7639.2	-53.70	-13	-40.70	-76.25	-63.88	1.82	12	V	Pass



Band :	WCDMA Band V for CH4132	Temperature :	23~25°C						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	48~52%						
Test Engineer :	Gavin Zhang	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1652.8	-55.35	-13	-42.35	-69.07	-58.34	0.81	5.95	H	Pass
2479.2	-47.92	-13	-34.92	-69.61	-50.37	1.2	5.80	H	Pass
3305.6	-61.60	-13	-48.60	-72.20	-65.90	1.25	7.70	H	Pass

Band :	WCDMA Band V for CH4132	Temperature :	23~25°C						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	48~52%						
Test Engineer :	Gavin Zhang	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1652.8	-58.06	-13	-45.06	-69.49	-61.05	0.81	5.95	V	Pass
2479.2	-48.93	-13	-35.93	-68.77	-51.38	1.20	5.80	V	Pass
3305.6	-60.18	-13	-47.18	-72.01	-64.48	1.25	7.70	V	Pass



Band :	WCDMA Band V for CH4182	Temperature :	23~25°C						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	48~52%						
Test Engineer :	Gavin Zhang	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit	Reading	Power	loss	Gain	(H/V)	
(dB)	(dB)	(dB)	(dB)	(dBm)	(dBm)	(dB)	(dBi)		
1672	-56.62	-13	-43.62	-69.54	-59.59	0.88	6.00	H	Pass
2510	-47.92	-13	-34.92	-70.06	-50.53	1.08	5.84	H	Pass
3346	-61.60	-13	-48.60	-72.20	-65.97	1.14	7.66	H	Pass

Band :	WCDMA Band V for CH4182	Temperature :	23~25°C						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	48~52%						
Test Engineer :	Gavin Zhang	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit	Reading	Power	loss	Gain	(H/V)	
(dB)			(dB)	(dBm)	(dBm)	(dB)	(dBi)		
1672	-59.39	-13	-46.39	-70.02	-62.36	0.88	6.00	V	Pass
2510	-52.07	-13	-39.07	-70.89	-54.68	1.08	5.84	V	Pass
3346	-60.50	-13	-47.50	-72.33	-64.87	1.14	7.66	V	Pass



Band :	WCDMA Band V for CH4233	Temperature :	23~25°C						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	48~52%						
Test Engineer :	Gavin Zhang	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1693.2	-55.82	-13	-42.82	-69.36	-59.15	0.82	6.30	H	Pass
2539.8	-49.02	-13	-36.02	-70.45	-51.63	1.08	5.84	H	Pass
3386.4	-61.14	-13	-48.14	-72.03	-65.26	1.23	7.50	H	Pass

Band :	WCDMA Band V for CH4233	Temperature :	23~25°C						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	48~52%						
Test Engineer :	Gavin Zhang	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit	Reading	Power	loss	Gain	(H/V)	
(dB)	(dB)	(dB)	(dB)	(dBm)	(dBm)	(dB)	(dBi)		
1693.2	-58.33	-13	-45.33	-69.58	-61.66	0.82	6.30	V	Pass
2539.8	-51.75	-13	-38.75	-70.72	-54.36	1.08	5.84	V	Pass
3386.4	-60.15	-13	-47.15	-72.27	-64.27	1.23	7.50	V	Pass



Band :	WCDMA Band II for CH9262	Temperature :	23~25°C						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	48~52%						
Test Engineer :	Gavin Zhang	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
3704.8	-61.11	-13	-48.11	-72.97	-67.96	1.35	8.20	H	Pass
5557.2	-55.20	-13	-42.20	-72.93	-63.81	1.65	10.26	H	Pass
7409.6	-53.62	-13	-40.62	-76.06	-63.96	1.82	12.16	H	Pass

Band :	WCDMA Band II for CH9262	Temperature :	23~25°C						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	48~52%						
Test Engineer :	Gavin Zhang	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit	Reading	Power	loss	Gain	(H/V)	
(dB)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)		
3704.8	-58.50	-13	-45.50	-73.24	-65.35	1.35	8.2	V	Pass
5557.2	-57.21	-13	-44.21	-74.03	-65.82	1.65	10.26	V	Pass
7409.6	-53.35	-13	-40.35	-76.1	-63.69	1.82	12.16	V	Pass



Band :	WCDMA Band II for CH9400	Temperature :	23~25°C						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	48~52%						
Test Engineer :	Gavin Zhang	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
3760	-61.51	-13	-48.51	-73.66	-68.25	1.28	8.02	H	Pass
5640	-55.83	-13	-42.83	-73.82	-64.25	1.58	10.00	H	Pass
7520	-54.24	-13	-41.24	-76.18	-64.56	1.78	12.10	H	Pass

Band :	WCDMA Band II for CH9400					Temperature :	23~25°C		
Test Mode :	RMC 12.2Kbps Link (QPSK)					Relative Humidity :	48~52%		
Test Engineer :	Gavin Zhang					Polarization :	Vertical		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
3760	-58.94	-13	-45.94	-73.97	-65.68	1.28	8.02	V	Pass
5640	-56.42	-13	-43.42	-73.5	-64.84	1.58	10	V	Pass
7520	-53.82	-13	-40.82	-76.07	-64.14	1.78	12.1	V	Pass



Band :	WCDMA Band II for CH9538	Temperature :	23~25°C						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	48~52%						
Test Engineer :	Gavin Zhang	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit	Reading	Power	loss	Gain		
			(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
3815.2	-61.78	-13	-48.78	-73.93	-68.52	1.28	8.02	H	Pass
5722.8	-55.65	-13	-42.65	-73.64	-64.07	1.58	10.00	H	Pass
7630.4	-53.84	-13	-40.84	-75.78	-64.16	1.78	12.10	H	Pass

Band :	WCDMA Band II for CH9538	Temperature :	23~25°C						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	48~52%						
Test Engineer :	Gavin Zhang	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over Limit	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	(dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
3815.2	-58.69	-13	-45.69	-73.72	-65.43	1.28	8.02	V	Pass
5722.8	-56.68	-13	-43.68	-73.76	-65.10	1.58	10	V	Pass
7630.4	-53.56	-13	-40.56	-75.81	-63.88	1.78	12.1	V	Pass

3.8 Frequency Stability Measurement

3.8.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.8.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.8.3 Test Procedures for Temperature Variation

1. The testing follows FCC KDB 971168 v02r01 Section 9.0.
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C steps up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.8.4 Test Procedures for Voltage Variation

1. The testing follows FCC KDB 971168 v02r01 Section 9.0.
2. The EUT was placed in a temperature chamber at $25\pm 5^{\circ}\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
4. The variation in frequency was measured for the worst case.

3.8.5 Test Setup



3.8.6 Test Result of Temperature Variation

Band :	GSM 850	Channel :	189
Limit (ppm) :	2.5	Frequency :	836.4 MHz

Temperature (°C)	GSM		EDGE class 8		Result
	Freq. Dev. (Hz)	Deviation (ppm)	Freq. Dev. (Hz)	Deviation (ppm)	
-30	13	+0.015	17	+0.020	PASS
-20	13	+0.015	16	+0.019	
-10	18	+0.021	18	+0.021	
0	19	+0.022	18	+0.021	
10	23	+0.027	19	+0.022	
20(Ref.)	24	+0.028	16	+0.019	
30	25	+0.029	17	+0.020	
40	27	+0.032	20	+0.024	
50	28	+0.033	28	+0.033	

Band :	GSM 1900	Channel :	661
Limit (ppm) :	within authorized band	Frequency :	1880.0 MHz

Temperature (°C)	GSM		EDGE class 8		Result
	Freq. Dev. (Hz)	Deviation (ppm)	Freq. Dev. (Hz)	Deviation (ppm)	
-30	49	+0.026	24	+0.013	PASS
-20	45	+0.024	27	+0.014	
-10	44	+0.023	29	+0.015	
0	38	+0.020	31	+0.016	
10	41	+0.022	38	+0.020	
20(Ref.)	36	+0.019	39	+0.021	
30	43	+0.023	41	+0.022	
40	52	+0.027	49	+0.026	
50	58	+0.031	58	+0.031	

Note: The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

Band :	WCDMA Band V	Channel :	4182
Limit (ppm) :	2.5	Frequency :	836.4 MHz

Temperature (°C)	RMC 12.2Kbps		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	10	+0.012	PASS
-20	7	+0.008	
-10	5	+0.006	
0	4	+0.005	
10	4	+0.005	
20(Ref.)	3	+0.004	
30	4	+0.005	
40	3	+0.004	
50	3	+0.004	

Band :	WCDMA Band II	Channel :	9400
Limit (ppm) :	within authorized band	Frequency :	1880.0 MHz

Temperature (°C)	RMC 12.2Kbps		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	9	+0.005	PASS
-20	10	+0.005	
-10	9	+0.005	
0	10	+0.005	
10	11	+0.006	
20(Ref.)	11	+0.006	
30	11	+0.006	
40	12	+0.006	
50	12	+0.006	

Note: The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

3.8.7 Test Result of Voltage Variation

Band & Channel	Mode	Voltage (Volt)	Freq. Dev. (Hz)	Deviation (ppm)	Limit (ppm)	Result
GSM 850 CH189	GSM	3.9	24	+0.028	2.5 (Note 3.)	PASS
		BEP	26	+0.031		
		4.2	24	+0.028		
	EDGE class 8	3.9	16	+0.019		
		BEP	20	+0.024		
		4.2	17	+0.020		
GSM 1900 CH661	GSM	3.9	36	+0.019		
		BEP	39	+0.021		
		4.2	40	+0.021		
	EDGE class 8	3.9	39	+0.021		
		BEP	42	+0.022		
		4.2	45	+0.024		
WCDMA Band V CH4182	RMC 12.2Kbps	3.9	3	+0.004		
		BEP	2	+0.002		
		4.2	3	+0.004		
WCDMA Band II CH9400	RMC 12.2Kbps	3.9	11	+0.006		
		BEP	9	+0.005		
		4.2	13	+0.007		

Note:

1. Normal Voltage = 3.9V.
2. Battery End Point (BEP) = 3.5 V.
3. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Jun. 17, 2013	Jul. 31, 2014~ Aug. 08, 2014	Jun. 16, 2014	Conducted (TH01-SZ)
Thermal Chamber	Hongzhan	LP-150U	HD20120425	-40℃~150℃	Feb. 21, 2014	Jul. 31, 2014~ Aug. 08, 2014	Feb. 20, 2015	Conducted (TH01-SZ)
ESCIO TEST Receiver	R&S	ESCI	100724	9kHz~3GHz	Feb. 21, 2014	Aug. 22, 2014	Feb. 20, 2015	Radiation (03CH01-SZ)
Spectrum Analyzer	Agilent Technologies	N9038A	MY52260185	20Hz~26.5GHz	May 26, 2014	Aug. 22, 2014	May 25, 2015	Radiation (03CH01-SZ)
Bilog Antenna	TESEQ	CBL 6112D	23188	30MHz~2GHz	Oct. 26, 2013	Aug. 22, 2014	Oct. 25, 2014	Radiation (03CH01-SZ)
Double Ridge Horn Antenna	ETS Lindgren	3117	00119436	1GHz~18GHz	Oct. 26, 2013	Aug. 22, 2014	Oct. 25, 2014	Radiation (03CH01-SZ)
Double Ridged Horn Antenna	COM-POWER	AH-840	101073	18GHz~40GHz	Jan. 27, 2014	Aug. 22, 2014	Jan. 26, 2015	Radiation (03CH01-SZ)
Amplifier	ADVANTEST	BB525C	E9007003	9kHz~3000MHz	Feb. 21, 2014	Aug. 22, 2014	Feb. 20, 2015	Radiation (03CH01-SZ)
Amplifier	Yiai	AV3860B	04030	2GHz~26.5GHz	May 08, 2014	Aug. 22, 2014	May 07, 2015	Radiation (03CH01-SZ)
AC Source(AVR)	Chroma	61601	616010001985	100Vac~250Vac	Mar. 25, 2014	Aug. 22, 2014	Mar. 24, 2015	Radiation (03CH01-SZ)
Turn Table	EM Electronics	EM 1000	N/A	0~360 degree	NCR	Aug. 22, 2014	NCR	Radiation (03CH01-SZ)
Antenna Mast	EM Electronics	EM 1000	N/A	1 m~4 m	NCR	Aug. 22, 2014	NCR	Radiation (03CH01-SZ)
Spectrum Analyzer	R&S	FSP 7	100818	9kHz~7GHz	Sep. 03, 2013	Jul. 25, 2014	Sep. 02, 2014	ERP/EIRP (OTA01-SZ)
Quad-Ridged Horn	ETS-Lindgren	3164-08	00102954	700MHz~10000M Hz	NCR	Jul. 25, 2014	NCR	ERP/EIRP (OTA01-SZ)
Multi-Devices Controller	ETS-Lindgren	2090-OPT1	00108147	N/A	NCR	Jul. 25, 2014	NCR	ERP/EIRP (OTA01-SZ)
Switch Control Mainframe	Agilent	3499A	MY42005451	N/A	NCR	Jul. 25, 2014	NCR	ERP/EIRP (OTA01-SZ)



5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	3.9
--	-----