

FCC SAR Test Report

FCC ID: RAS-MT7921

Project No.	:	2203C055
Equipment	:	2TX 11ax(WiFi6)+BLE Combo Card
Brand Name	:	MediaTek
Test Model	:	MT7921
Series Model	:	N/A
Date of Receipt	:	Mar. 09, 2022
Date of Test	:	May 09, 2022 ~ May 10, 2022
Issued Date	:	May 23, 2022
Report Version	:	R00
Test Sample	:	Engineering Sample No.: DG2022042761, DG2022042762.
Standard(s)	:	Please refer to page 2.
Applicant	:	MediaTek Inc.
Address	:	No.1,Dusing 1st Rd., Hsinchu Science Park Hsinchu City 30078 Taiwan

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.



Prepared by : Seven Lu



Approved by : Herbort Liu



TESTING CERT #5123.02

Add: No. 3 Jinshagang 1st Rd. Shixia, Dalang Town Dongguan City, Guangdong 523792 People's Republic of China

Tel: +86-769-8318-3000

Web: www.newbtl.com

Standard(s)	<p>: ANSI Std C95.1-1992 Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz - 300 GHz. (IEEE Std C95.1-1991)</p> <p>IEEE Std 1528-2013 Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques</p> <p>KDB616217 D04 SAR for laptop and tablets v01r02 KDB447498 D04 Interim General RF Exposure Guidance v01 KDB248227 D01 802.11 Wi-Fi SAR v02r02 KDB865664 D01 SAR measurement 100 MHz to 6 GHz v01r04 KDB865664 D02 SAR Reporting v01r02 KDB690783 D01 SAR Listings on Grants v01r03</p>
--------------------	--

Declaration

BTL represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with standards traceable to international standard(s) and/or national standard(s).

BTL's reports apply only to the specific samples tested under conditions. It is manufacturer's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

The report must not be used by the client to claim product certification, approval, or endorsement by NIST, A2LA, or any agency of the U.S. Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and ourselves, the test report shall not be reproduced, except in full, without our written approval.

BTL's laboratory quality assurance procedures are in compliance with the **ISO/IEC 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

BTL is not responsible for the sampling stage, so the results only apply to the sample as received.

The information, data and test plan are provided by manufacturer which may affect the validity of results, so it is manufacturer's responsibility to ensure that the apparatus meets the essential requirements of applied standards and in all the possible configurations as representative of its intended use.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Please note that the measurement uncertainty is provided for informational purpose only and are not use in determining the Pass/Fail results.

Table of Contents	Page
REPORT ISSUED HISTORY	6
1 . GENERAL INFORMATION	7
1.1 STATEMENT OF COMPLIANCE	7
1.2 LABORATORY ENVIRONMENT	7
1.3 GENERAL DESCRIPTION OF EUT	8
1.4 MAIN TEST INSTRUMENTS	10
2 . RF EMISSIONS MEASUREMENT	11
2.1 TEST FACILITY	11
2.2 MEASUREMENT UNCERTAINTY	11
3 . SAR MEASUREMENTS SYSTEM CONFIGURATION	12
3.1 SAR MEASUREMENT SET-UP	12
3.1.1 TEST SETUP LAYOUT	12
3.2 DASY5 E-FIELD PROBE SYSTEM	13
3.2.1 PROBE SPECIFICATION	13
3.2.2 E-FIELD PROBE CALIBRATION	14
3.2.3 OTHER TEST EQUIPMENT	15
3.2.4 SCANNING PROCEDURE	16
3.2.5 SPATIAL PEAK SAR EVALUATION	17
3.2.6 DATA STORAGE AND EVALUATION	18
3.2.7 DATA EVALUATION BY SEMCAD	19
4 . SYSTEM VERIFICATION PROCEDURE	21
4.1 TISSUE VERIFICATION	21
4.2 SYSTEM CHECK	22
4.3 SYSTEM CHECK PROCEDURE	22
5 . SAR MEASUREMENT VARIABILITY AND UNCERTAINTY	23
5.1 SAR MEASUREMENT VARIABILITY	23
6 . OPERATIONAL CONDITIONS DURING TEST	24
6.1 SAR TEST CONFIGURATION	24
6.1.1 WIFI TEST CONFIGURATION	24
6.2 TEST POSITION	27
6.2.1 NOTEBOOK MODE	27
7 . TEST RESULT	29
7.1 CONDUCTED POWER RESULTS	29
7.1.1 CONDUCTED POWER MEASUREMENTS OF BT	29
7.1.2 CONDUCTED POWER MEASUREMENTS OF WIFI	30

Table of Contents	Page
7.2 SAR TEST RESULTS	45
7.2.1 SAR MEASUREMENT RESULT	46
7.3 MULTIPLE TRANSMITTER EVALUATION	48
7.3.1 STAND-ALONE SAR TEST EXCLUSION	48
7.3.2 SIMULTANEOUS TRANSMISSION CONDITIONS	49
APPENDIX	51
1. TEST LAYOUT	51
Appendix A. SAR Plots of System Verification	
Appendix B. SAR Plots of SAR Measurement	
Appendix C. Calibration Certificate	
Appendix D. Photographs of the Test Set-Up	

REPORT ISSUED HISTORY

Report No.	Version	Description	Issued Date	Note
BTL-FCC SAR-3-2203C055	R00	Original Report.	May 23, 2022	Valid

1. GENERAL INFORMATION

1.1 STATEMENT OF COMPLIANCE

Mode	Highest Reported Body SAR-1g (W/kg)
2.4G WLAN	0.220
5.2G WLAN	0.193
5.3G WLAN	0.232
5.6G WLAN	0.691
5.8G WLAN	0.629
Bluetooth	0.053

Note: The device is in compliance with Specific Absorption Rate (SAR) for general population uncontrolled exposure limits according to the FCC rule §2.1093, the ANSI C95.1:1992/IEEE C95.1:1991, the NCRP Report Number 86 for uncontrolled environment, and had been tested in accordance with the measurement methods and procedures specified in IEEE Std 1528-2013.

1.2 LABORATORY ENVIRONMENT

Temperature	Min. = 20°C, Max. = 24°C
Relative humidity	Min. = 30%, Max. = 70%
Ground system resistance	< 0.5Ω
Ambient noise is checked and found very low and in compliance with requirement of standards. Reflection of surrounding objects is minimized and in compliance with requirement of standards.	

1.3 GENERAL DESCRIPTION OF EUT

Equipment	2TX 11ax(WiFi6)+BLE Combo Card								
Brand Name	MediaTek								
Test Model	MT7921								
Series Model	N/A								
Model Difference(s)	N/A								
Modulation	WiFi(DSSS/OFDM/OFDMA), BT(GFSK/π/4-DQPSK/8-DPSK)								
Operation Frequency Range(s)	Band	TX (MHz)		RX (MHz)					
	Bluetooth	2400~2483.5							
	WLAN	2400~2483.5							
		5150~5250							
		5250~5350							
		5470~5725							
		5725~5850							
Test Channels (low-mid-high)	0-39-78 (BT)								
	0-19-39 (BLE)								
	1-2-6-10-11-12-13 (2.4G WiFi 802.11b/g/ac VHT20/ax HE20)								
	3-4-6-8-9-10-11 (2.4G WiFi 802.11ac VHT40/ax HE40)								
	Band	5.2G WiFi	5.3G WiFi	5.6G WiFi	5.8G WiFi				
	802.11a/ac VHT20 /ax HE20	36-40-48	52-60-64	100-116-140	149-157-165				
	802.11ac VHT40 /ax HE40	38-46	54-62	102-110-134	151-159				
	802.11ac VHT80 /ax HE80	42	58	106-122	155				
Antenna Information	Ant.	Brand	P/N	Type	Frequency Range (MHz)	Gain (dBi)			
	Main Ant	ShenZhen ZhongTianXun Communication Technolgy Shares Co.,LTD (ZTX)	2.00005087	PIFA Antenna	2400-2500	1.51			
					5150-5350	1.71			
					5470-5725	1.93			
					5725-5850	1.92			
	Aux Ant		2.00005087	PIFA Antenna	2400-2500	1.47			
					5150-5350	1.07			
					5470-5725	1.65			
					5725-5850	1.65			
	Main Ant	Shenzhen South Star Technology Co., LTD (South Star)	N12-7822-R0A	PIFA Antenna	2400-2500	0.31			
					5150-5350	0.89			
					5470-5725	1.71			
					5725-5850	-0.24			
	Aux Ant		N12-7822-R0A	PIFA Antenna	2400-2500	-0.17			
					5150-5350	1.52			
					5470-5725	1.68			
					5725-5850	-0.83			
Other Information									
Battery Information	Band / Model		1# Supplier / Model: Simplo / L20M4PE1 2# Supplier / Model: Celxpert / L20C4PE1 3# Supplier / Model: LGC / L20L4PE1						
	Power Rating		DC 15.36V, 4734mAh						

Note:

1) Implementation in the following platform

Model name: Lenovo Slim 7 16ARH7, Lenovo Slim 7 16ARH7xxxxxx,

(The "x" in the model name can be 0 to 9, A to Z, a to z, "-" or blank, it represents different sales customer code, all models only name difference)

Product name: Notebook Computer

Brand name: Lenovo

2) Because the SAR test result is far below the limit value of 50%, and the power rating is the same, we estimate that the impact of replacing the battery on SAR is small, so we only test the battery: LGC / L20L4PE1.

1.4 MAIN TEST INSTRUMENTS

Item	Equipment	Manufacturer	Model	Serial No.	Cal. Date	Cal. Interval
1	Data Acquisition Electronics	Speag	DAE4	1423	Jan. 21, 2022	1 Year
2	Data Acquisition Electronics	Speag	DAE4	1390	Dec. 29, 2021	1 Year
3	E-field Probe	Speag	EX3DV4	7693	Nov. 03, 2021	1 Year
4	System Validation Dipole	Speag	D2450V2	919	May 28, 2021	3 Years
5	System Validation Dipole	Speag	D5GHzV2	1160	May 27, 2021	3 Years
6	ELI Phantom	Speag	ELI Phantom V5.0	1222	N/A	N/A
7	ELI Phantom	Speag	ELI Phantom V5.0	1128	N/A	N/A
8	Power Amplifier	Mini-Circuits	ZHL-42W+	QA1333003	Dec. 26, 2021	1 Year
9	Power Amplifier	Mini-Circuits	ZVE-8G+	520701341	Feb. 19, 2022	1 Year
10	DC Source metter	ltek	IT6154	0061041267682 01001	Jul. 24, 2021	1 Year
11	Signal Analyzer	R&S	FSV7	103120	Jul. 10, 2021	1 Year
12	Vector Network Analyzer	Agilent	E5071C	MY46102965	Feb. 19, 2022	1 Year
13	Signal Generator	Agilent	N5172B	MY53050758	Feb. 19, 2022	1 Year
14	Smart Power Sensor	R&S	NRP-Z21	102209	Feb. 19, 2022	1 Year
15	3.5mm Economy Calibration Kit	Agilent	85052D	MY43252246	Dec. 14, 2021	1 Year
16	Dielectric Assessment Kit	Speag	DAK-3.5	1226	N/A	N/A
17	Directional Coupler	Woken	TS-PCC0M-05	0107090019	Feb. 19, 2022	1 Year
18	Coupler	Woken	0110A05601O-10	COM5BNW1A2	Feb. 19, 2022	1 Year
19	Digital Themometer	TES	TES-1310	210706071	Dec. 07, 2021	1 Year

Note:

1. "N/A" denotes no model name, serial No. or calibration specified.
- 2.

1) Per KDB865664 D01 requirements for dipole calibration, the test laboratory has adopted three-year extended calibration interval. Each measured dipole is expected to evaluate with the following criteria at least on annual interval in Appendix C.

- a) There is no physical damage on the dipole;
- b) System check with specific dipole is within 10% of calibrated value;
- c) The most recent return-loss result, measured at least annually, deviates by no more than 20% from the previous measurement;
- d) The most recent measurement of the real or imaginary parts of the impedance, measured at least annually is within 5Ω from the previous measurement.

2) Network analyzer probe calibration against air, distilled water and a short block performed before measuring liquid parameters.

2. RF EMISSIONS MEASUREMENT

2.1 TEST FACILITY

The test facilities used to collect the test data in this report is SAR room at the location of Room 108, Building 2, No.1, Yile Road, Songshan Lake Zone, Dongguan City, Guangdong, People's Republic of China. BTL's Designation Number for FCC: CN1240.

2.2 MEASUREMENT UNCERTAINTY

Note: Per KDB865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. The equivalent ratio (1.5/1.6) is applied to extremity and occupational exposure conditions.


3. SAR MEASUREMENTS SYSTEM CONFIGURATION

3.1 SAR MEASUREMENT SET-UP

The DASY5 system for performing compliance tests consists of the following items:

1. A standard high precision 6-axis robot (Stäubli RX family) with controller and software. An arm extension for accommodating the data acquisition electronics (DAE).
2. A dosimetric probe, i.e. an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
3. A data acquisition electronic (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
4. A unit to operate the optical surface detector which is connected to the EOC.
5. The Electro-Optical Coupler (EOC) performs the conversion from the optical into a digital electric signal of the DAE. The EOC is connected to the DASY5 measurement server.
6. The DASY5 measurement server, which performs all real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operation. A computer operating Windows.
7. DASY5 software and SEMCAD data evaluation software.
8. Remote control with teach panel and additional circuitry for robot safety such as warning lamps, etc.
9. The generic twin phantom enabling the testing of left-hand and right-hand usage.
10. The device holder for handheld mobile phones.
11. Tissue simulating liquid mixed according to the given recipes.
12. System validation dipoles allowing to validate the proper functioning of the system.

3.1.1 TEST SETUP LAYOUT



3.2 DASY5 E-FIELD PROBE SYSTEM

The SAR measurements were conducted with the dosimetric probe EX3DV4 (manufactured by SPEAG), designed in the classical triangular configuration and optimized for dosimetric evaluation.

3.2.1 PROBE SPECIFICATION

EX3DV4

Construction	Symmetrical design with triangular core Interleaved sensors Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)
Calibration	ISO/IEC 17025 calibration service available
Frequency	10 MHz to 6 GHz Linearity: ± 0.2 dB (30 MHz to 6 GHz)
Directivity	± 0.3 dB in HSL (rotation around probe axis) ± 0.5 dB in tissue material (rotation normal to probe axis)
Dynamic Range	10 μ W/g to > 100 mW/g Linearity: ± 0.2 dB
Dimensions	Overall length: 330 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Distance from probe tip to dipole centers: 1.0 mm



E-field Probe

3.2.2 E-FIELD PROBE CALIBRATION

Each probe is calibrated according to a dosimetric assessment procedure with accuracy better than $\pm 10\%$. The spherical isotropy was evaluated and found to be better than $\pm 0.25\text{dB}$. The sensitivity parameters (NormX, NormY, NormZ), the diode compression parameter (DCP) and the conversion factor (ConvF) of the probe are tested.

The free space E-field from amplified probe outputs is determined in a test chamber. This is performed in a TEM cell for frequencies bellow 1 GHz, and in a wave guide above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is then rotated 360 degrees.

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated brain tissue. The measured free space E-field in the medium correlates to temperature rise in a dielectric medium. For temperature correlation calibration a RF transparent thermostat-based temperature probe is used in conjunction with the E-field probe.

$$\text{SAR} = C \frac{\Delta T}{\Delta t}$$

Where: Δt =Exposure time (30 seconds),

C =Heat capacity of tissue (brain or muscle),

ΔT =Temperature increase due to RF exposure.

$$\text{Or SAR} = \frac{|E|^2 \sigma}{\rho}$$

Where: σ = Simulated Tissue Conductivity,

ρ =Tissue density (kg/m³).

3.2.3 OTHER TEST EQUIPMENT


3.2.3.1. Device Holder for Transmitters

Construction: Simple but effective and easy-to-use extension for Mounting Device that facilitates the testing of larger devices (e.g., laptops, cameras, etc.) It is light weight and fits easily on the upper part of the Mounting Device in place of the phone positioner. The extension is fully compatible with the Twin SAM, ELI and SAM v6.0 Phantoms.

Material: POM, Acrylic glass, Foam

3.2.3.2 Phantom

Model	ELI Phantom
Construction	Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI is fully compatible with the IEC 62209-2 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles.
Shell Thickness	2±0.1 mm
Filling Volume	Approx. 30 liters
Dimensions	Length: 600 mm; Width: 190mm Height: adjustable feet
Available	Special



3.2.4 SCANNING PROCEDURE

The DASY5 installation includes predefined files with recommended procedures for measurements and validation. They are read-only document files and destined as fully defined but unmeasured masks. All test positions (head or body-worn) are tested with the same configuration of test steps differing only in the grid definition for the different test positions.

The “reference” and “drift” measurements are located at the beginning and end of the batch process. They measure the field drift at one single point in the liquid over the complete procedure. The indicated drift is mainly the variation of the DUT’s output power and should vary max. $\pm 5\%$.

The “surface check” measurement tests the optical surface detection system of the DASY5 system by repeatedly detecting the surface with the optical and mechanical surface detector and comparing the results. The output gives the detecting heights of both systems, the difference between the two systems and the standard deviation of the detection repeatability. Air bubbles or refraction in the liquid due to separation of the sugar-water mixture gives poor repeatability (above $\pm 0.1\text{mm}$). To prevent wrong results tests are only executed when the liquid is free of air bubbles. The difference between the optical surface detection and the actual surface depends on the probe and is specified with each probe. (It does not depend on the surface reflectivity or the probe angle to the surface within $\pm 30^\circ$.)

- Area Scan

The “area scan” measures the SAR above the DUT or verification dipole on a parallel plane to the surface. It is used to locate the approximate location of the peak SAR with 2D spline interpolation. The robot performs a stepped movement along one grid axis while the local electrical field strength is measured by the probe. The probe is touching the surface of the SAM during acquisition of measurement values. The standard scan uses large grid spacing for faster measurement. Standard grid spacing for head measurements is 15 mm in x- and y- dimension ($\leq 2\text{GHz}$), 12 mm in x- and y- dimension (2-4 GHz) and 10mm in x- and y- dimension (4-6GHz). If a finer resolution is needed, the grid spacing can be reduced. Grid spacing and orientation have no influence on the SAR result. For special applications where the standard scan method does not find the peak SAR within the grid, e.g. mobile phones with flip cover, the grid can be adapted in orientation.

- Zoom Scan

A “zoom scan” measures the field in a volume around the 2D peak SAR value acquired in the previous “coarse” scan. This is a fine grid with maximum scan spatial resolution: $\Delta x_{\text{zoom}}, \Delta y_{\text{zoom}} \leq 2\text{GHz} \leq 8\text{mm}$, $2-4\text{GHz} \leq 5\text{ mm}$ and $4-6\text{ GHz} \leq 4\text{mm}$; $\Delta z_{\text{zoom}} \leq 3\text{GHz} \leq 5\text{ mm}$, $3-4\text{ GHz} \leq 4\text{mm}$ and $4-6\text{GHz} \leq 2\text{mm}$ where the robot additionally moves the probe along the z-axis away from the bottom of the Phantom. DASY is also able to perform repeated zoom scans if more than 1 peak is found during area scan. In this document, the evaluated peak 1g and 10g averaged SAR values are shown in the 2D-graphics in Appendix B. Test results relevant for the specified standard (see chapter 1.4.) are shown in table form in chapter 7.2.

A Z-axis scan measures the total SAR value at the x-and y-position of the maximum SAR value found during the cube scan. The probe is moved away in z-direction from the bottom of the SAM phantom in 2 mm steps. This measurement shows the continuity of the liquid and can - depending in the field strength – also show the liquid depth.

The following table summarizes the area scan and zoom scan resolutions per FCC KDB 865664D01:

Frequency	Maximun Area Scan resolution ($\Delta x_{\text{area}}, \Delta y_{\text{area}}$)	Maximun Zoom Scan spatial resolution ($\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$)	Maximun Zoom Scan spatial resolution			Minimum zoom scan volume (x,y,z)
			Uniform Grid		Graded Grad	
			$\Delta z_{\text{Zoom}}(n)$	$\Delta z_{\text{Zoom}}(1)^*$	$\Delta z_{\text{Zoom}}(n>1)^*$	
$\leq 2\text{GHz}$	$\leq 15\text{mm}$	$\leq 8\text{mm}$	$\leq 5\text{mm}$	$\leq 4\text{mm}$	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	$\geq 30\text{mm}$
2-3GHz	$\leq 12\text{mm}$	$\leq 5\text{mm}$	$\leq 5\text{mm}$	$\leq 4\text{mm}$	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	$\geq 30\text{mm}$
3-4GHz	$\leq 12\text{mm}$	$\leq 5\text{mm}$	$\leq 4\text{mm}$	$\leq 3\text{mm}$	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	$\geq 28\text{mm}$
4-5GHz	$\leq 10\text{mm}$	$\leq 4\text{mm}$	$\leq 3\text{mm}$	$\leq 2.5\text{mm}$	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	$\geq 25\text{mm}$
5-6GHz	$\leq 10\text{mm}$	$\leq 4\text{mm}$	$\leq 2\text{mm}$	$\leq 2\text{mm}$	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	$\geq 22\text{mm}$

3.2.5 SPATIAL PEAK SAR EVALUATION

The spatial peak SAR - value for 1 and 10 g is evaluated after the Cube measurements have been done. The basis of the evaluation are the SAR values measured at the points of the fine cube grid consisting of 5 x 5 x 7 points (with 8mm horizontal resolution) or 7 x 7 x 7 points (with 5mm horizontal resolution) or 8 x 8 x 7 points (with 4mm horizontal resolution). The algorithm that finds the maximal averaged volume is separated into three different stages.

- The data between the dipole center of the probe and the surface of the phantom are extrapolated. This data cannot be measured since the center of the dipole is 2.7 mm away from the tip of the probe and the distance between the surface and the lowest measuring point is about 1 mm (see probe calibration sheet). The extrapolated data from a cube measurement can be visualized by selecting "Graph Evaluated".
- The maximum interpolated value is searched with a straight-forward algorithm. Around this maximum the SAR - values averaged over the spatial volumes (1g or 10 g) are computed using the 3d-spline interpolation algorithm. If the volume cannot be evaluated (i.e., if a part of the grid was cut off by the boundary of the measurement area) the evaluation will be started on the corners of the bottom plane of the cube.
- All neighboring volumes are evaluated until no neighboring volume with a higher average value is found.

Extrapolation

The extrapolation is based on a least square algorithm [W. Gander, Computer mathematic, p.168-180]. Through the points in the first 3 cm along the z-axis, polynomials of order four are calculated. These polynomials are then used to evaluate the points between the surface and the probe tip. The points, calculated from the surface, have a distance of 1 mm from each other.

Interpolation

The interpolation of the points is done with a 3d-Spline. The 3d-Spline is composed of three one-dimensional splines with the "Not a knot"-condition [W. Gander, Computer mathematic, p.141-150] (x, y and z -direction) [Numerical Recipes in C, Second Edition, p.123ff].

Volume Averaging

At First the size of the cube is calculated. Then the volume is integrated with the trapezoidal algorithm. 8000 points (20x20x20) are interpolated to calculate the average.

Advanced Extrapolation

DASY5 uses the advanced extrapolation option which is able to compensate boundary effects on E-field probes.

3.2.6 DATA STORAGE AND EVALUATION

3.2.6.1 Data Storage

The DASY5 software stores the acquired data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors), together with all necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files with the extension "DAE". The software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of incorrect parameter settings. For example, if a measurement has been performed with a wrong crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be re-evaluated.

The measured data can be visualized or exported in different units or formats, depending on the selected probe type ([V/m], [A/m], [°C], [mW/g], [mW/cm²], [dBrel], etc.). Some of these units are not available in certain situations or show meaningless results, e.g., a SAR output in a lossless media will always be zero. Raw data can also be exported to perform the evaluation with other software packages.

3.2.7 DATA EVALUATION BY SEMCAD

The SEMCAD software automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Probe parameters:	Sensitivity	Normi, aj0, aj1, aj2
	Conversion factor	ConvFi
	Diode compression point	Dcp <i>i</i>
Device parameters:	Frequency	f
	Crest factor	cf
Media parameters:	Conductivity	
	Density	

These parameters must be set correctly in the software. They can be found in the component documents or they can be imported into the software from the configuration files issued for the DASY5 components. In the direct measuring mode of the multi meter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics.

If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot cf / dcp_i$$

With	V_i = compensated signal of channel <i>i</i>	(<i>i</i> = x, y, z)
	U_i = input signal of channel <i>i</i>	(<i>i</i> = x, y, z)
	cf = crest factor of exciting field	(DASY parameter)
	dcp <i>i</i> = diode compression point	(DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

$$\text{E-field probes: } E_i = (V_i / \text{Norm}_i \cdot \text{ConvF})^{1/2}$$

$$\text{H-field probes: } H_i = (V_i)^{1/2} \cdot (a_{i0} + a_{i1}f + a_{i2}f^2) / f$$

With V_i = compensated signal of channel i ($i = x, y, z$)

Norm_i = sensor sensitivity of channel i ($i = x, y, z$)
 $[mV/(V/m)]^2$ for E-field Probes

ConvF = sensitivity enhancement in solution

a_{ij} = sensor sensitivity factors for H-field probes

f = carrier frequency [GHz]

E_i = electric field strength of channel i in V/m

H_i = magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{\text{tot}} = (E_X^2 + E_Y^2 + E_Z^2)^{1/2}$$

The primary field data are used to calculate the derived field units.

$$\text{SAR} = (E_{\text{tot}})^2 \cdot \sigma / (\rho \cdot 1000)$$

With SAR = local specific absorption rate in mW/g

E_{tot} = total field strength in V/m
 = conductivity in [mho/m] or [Siemens/m]
 = equivalent tissue density in g/cm³

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid. The power flow density is calculated assuming the excitation field to be a free space field.

$$P_{\text{pwe}} = E_{\text{tot}}^2 / 3770 \text{ or } P_{\text{pwe}} = H_{\text{tot}}^2 \cdot 37.7$$

With P_{pwe} = equivalent power density of a plane wave in mW/cm²

E_{tot} = total field strength in V/m

H_{tot} = total magnetic field strength in A/m

4. SYSTEM VERIFICATION PROCEDURE

4.1 TISSUE VERIFICATION

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine if the dielectric parameters are within the tolerances of the specified target values. The measured conductivity and relative permittivity should be within $\pm 5\%$ of the target values.

The following materials are used for producing the tissue-equivalent materials.

Tissue Type	Bactericide	DGBE	HEC	NaCl	Sucrose	Triton X-100	Water	Diethylene Glycol Mono-hexylether
Head 2450	-	45.0	-	0.1	-	-	54.9	-
Head 5G	-	-	-	-	-	17.2	65.5	17.3

Salt: 99+% Pure Sodium Chloride; Sugar: 98+% Pure Sucrose; Water: De-ionized, 16M + resistivity
HEC: Hydroxyethyl Cellulose; DGBE: 99+% Di(ethylene glycol) butyl ether,[2-(2-butoxyethoxy)ethanol]
Triton X-100(ultra pure): Polyethylene glycol mono [4-(1,1,3,3-tetramethylbutyl)phenyl]ether

Tissue Verification									
Tissue Type	Frequency (MHz)	Liquid Temp. (°C)	Conductivity (σ)	Permittivity (ϵ_r)	Targeted Conductivity (σ)	Targeted Permittivity (ϵ_r)	Deviation Conductivity (σ) (%)	Deviation Permittivity (ϵ_r) (%)	Date
Head	2450	22.3	1.836	39.612	1.80	39.2	2.00	1.05	May 09, 2022
Head	5250	22.5	4.793	35.791	4.71	36.0	1.76	-0.44	May 10, 2022
Head	5600	22.5	5.269	34.976	5.07	35.5	3.93	-1.48	May 10, 2022
Head	5750	22.5	5.391	34.571	5.22	35.4	3.28	-2.20	May 10, 2022

Note:

- 1)The dielectric parameters of the tissue-equivalent liquid should be measured under similar ambient conditions and within 2 °C of the conditions expected during the SAR evaluation to satisfy protocol requirements.
- 2)KDB 865664 was ensured to be applied for probe calibration frequencies greater than or equal to 50MHz of the EUT frequencies.
- 3)The above measured tissue parameters were used in the DASY software to perform interpolation via the DASY software to determine actual dielectric parameters at the test frequencies. The SAR test plots may slightly differ from the table above since the DASY rounds to three significant digits.

4.2 SYSTEM CHECK

The system check is performed for verifying the accuracy of the complete measurement system and performance of the software. The system check is performed with tissue equivalent material according to IEEE P1528 (described above). The following table shows system check results for all frequency bands and tissue liquids used during the tests.


System Check	Date	Frequency (MHz)	Targeted SAR 1g (W/kg)	Measured SAR 1g (W/kg)	normalized SAR 1g (W/kg)	Deviation (%)	Dipole S/N
Head	May 09, 2022	2450	52.10	12.90	51.60	-0.96	919
Head	May 10, 2022	5250	78.00	8.11	81.10	3.97	1160
Head	May 10, 2022	5600	80.60	8.38	83.80	3.97	1160
Head	May 10, 2022	5750	76.50	7.64	76.40	-0.13	1160

4.3 SYSTEM CHECK PROCEDURE

The system check is performed by using a system check dipole which is positioned parallel to the planar part of the SAM phantom at the reference point. The distance of the dipole to the SAM phantom is determined by a plexiglass spacer. The dipole is connected to the signal source consisting of signal generator and amplifier via a directional coupler, N-connector cable and adaption to SMA. It is fed with a power of 250mW (below 3GHz) or 100mW (3-6GHz). To adjust this power a power meter is used.

The power sensor is connected to the cable before the system check to measure the power at this point and do adjustments at the signal generator. At the outputs of the directional coupler both return loss as well as forward power are controlled during the system check to make sure that emitted power at the dipole is kept constant. This can also be checked by the power drift measurement after the test.

System check results have to be equal or near the values determined during dipole calibration (target SAR in table above) with the relevant liquids and test system ($\pm 10\%$).



5. SAR MEASUREMENT VARIABILITY AND UNCERTAINTY

5.1 SAR MEASUREMENT VARIABILITY

Per KDB865664 D01 SAR measurement 100 MHz to 6 GHz, SAR measurement variability must be assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. The additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

- 1) Repeated measurement is not required when the original highest measured SAR is $< 0.80 \text{ W/kg}$; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is $\geq 0.80 \text{ W/kg}$, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is $\geq 1.45 \text{ W/kg}$ ($\sim 10\%$ from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is $\geq 1.5 \text{ W/kg}$ and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

The same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds.

The detailed repeated measurement results are shown in Section 7.2.


6. OPERATIONAL CONDITIONS DURING TEST

6.1 SAR TEST CONFIGURATION

6.1.1 WIFI TEST CONFIGURATION

For WLAN / BT SAR testing, WLAN / BT engineering testing software installed on the DUT can provide continuous transmitting RF signal.

For WiFi SAR testing, a communication link is set up with the test mode software for WiFi mode test. During the test, at the each test frequency channel, the EUT is operated at the RF continuous emission mode. The test procedures in KDB 248227 D01 are applied.



6.1.1.1 2.4G SAR Test Requirements

802.11b DSSS SAR Test Requirements

SAR is measured for 2.4 GHz 802.11b DSSS using either a fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

- 1) When the reported SAR of the highest measured maximum output power channel for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.
- 2) When the reported SAR is > 0.8 W/kg, SAR is required for that exposure configuration using the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel; i.e., all channels require testing.

2.4 GHz 802.11g/n OFDM SAR Test Exclusion Requirements

When SAR measurement is required for 2.4 GHz 802.11g/n OFDM configurations, the measurement and test reduction procedures for OFDM are applied. SAR is not required for the following 2.4 GHz OFDM conditions.

- 1) When KDB Publication 447498 SAR test exclusion applies to the OFDM configuration.
- 2) When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.

SAR Test Requirements for OFDM configurations

When SAR measurement is required for 2.4 GHz 802.11g/n OFDM configurations, each stand alone. And frequency aggregated band is considered separately for SAR test reduction. In applying the initial test configuration and subsequent test configuration procedures, the 802.11 transmission configuration with the highest specified maximum output power and the channel within a test configuration with the highest measured maximum output power should be clearly distinguished to apply the procedures.

6.1.1.2 5G SAR Test Requirements

◊ U-NII-1 and U-NII-2A Band

For devices that operate in both U-NII-1 and U-NII-2A bands, when the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition); otherwise, both bands are tested independently for SAR. When different maximum output power is specified for the bands, begin SAR measurement in the band with higher specified maximum output power. The highest reported SAR for the tested configuration is adjusted by the ratio of lower to higher specified maximum output power for the two bands. When the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for the band with lower maximum output power in that test configuration; otherwise, both bands are tested independently for SAR.

◊ U-NII-2C, U-NII-3 Bands

The frequency range covered by these bands is 380 MHz (5.47 – 5.85 GHz), which requires a minimum of at least two SAR probe calibration frequency points to support SAR measurements. When Terminal Doppler Weather Radar (TDWR) restriction applies, the channels at 5.60 – 5.65 GHz in U-NII-2C band must be disabled with acceptable mechanisms and documented in the equipment certification.

Unless band gap channels are permanently disabled, they must be considered for SAR testing. To maintain SAR measurement accuracy and to facilitate test reduction, the channels in U-NII-2C band above 5.65 GHz may be grouped with the 5.8 GHz channels in U-NII-3 or §15.247 band to enable two SAR probe calibration frequency points to cover the bands, including the band gap channels.¹¹ When band gap channels are supported and the bands are not aggregated for SAR testing, band gap channels must be considered independently in each band according to the normally required OFDM SAR measurement and probe calibration frequency points requirements.

6.1.1.3 OFDM transmission mode and SAR test channel selection

For the 2.4GHz and 5GHz bands, when the same maximum output power was specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration with the largest channel bandwidth, lowest order modulation and lowest data rate. When the maximum output power of a channel is the same for equivalent OFDM configurations (for example 802.11a, 802.11n and 802.11ac, or 802.11g and 802.11n, with the same channel bandwidth, modulation, and data rate, etc.), the lower order 802.11 mode (i.e. 802.11a then 802.11n and 802.11ac, or 802.11g then 802.11n) is used for SAR measurement. When the maximum output power are the same for multiple test channels, either according to the default or additional power measurement requirements, SAR is measured using the channel closest to the middle of the frequency band or aggregated band. When there are multiple channels with the same maximum output power, SAR is measured using the higher number channel.

6.1.1.4 Initial test configuration procedure


For OFDM, in both 2.4G and 5GHz bands, an initial test configuration is determined for each frequency band and aggregated band, according to the transmission mode with the highest maximum output power specified for SAR measurements. When the same maximum output power is specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration(s) with the largest channel bandwidth, lowest order modulation, and lowest data rate. If the average RF output powers of the highest identical transmission modes are within 0.25 dB of each other, mid channel of the transmission mode with highest average RF output powers is the initial test channel. Otherwise, the channel of the transmission mode with the highest average RF output power will be the initial test configuration.

When the reported SAR is ≤ 0.8 W/kg, no additional measurements on other test channels are required. Otherwise, SAR is evaluated using the subsequent highest average RF output channel until the reported SAR result is ≤ 1.2 W/kg or all channels are measured. When there are multiple untested channels having the same subsequent highest average RF output power, the channel with higher frequency from the lowest 802.11 mode is considered for SAR measurement.

6.2 TEST POSITION


6.2.1 NOTEBOOK MODE

This DUT was tested in 2 different positions. They are back of keyboard and back of screen as illustrated below:



a) Portable computer with back of keyboard and back of screen.

The location of the antenna for notebook mode is as below:



The SAR measurement positions of each band are as below:

Antenna	Back of Keyboard	Back of Screen
Main Ant	Yes	Yes
Aux Ant	Yes	Yes

For feet and edge bumpers or similar protrusions incorporated in laptop and tablet host devices, if the antenna location can be positioned against the user during normal use and the additional separation introduced by such protrusions between the outer housing and a flat phantom is > 5 mm or when the reported SAR with the protrusions in place is > 1.2 W/kg, a KDB inquiry is required to determine if additional SAR measurements in more conservative test configurations are necessary. The KDB inquiry is not required if the feet, bumpers or protrusions can be easily removed with no other modifications to enable SAR testing with the device in direct contact with the phantom.



7. TEST RESULT

7.1 CONDUCTED POWER RESULTS

7.1.1 CONDUCTED POWER MEASUREMENTS OF BT

BT	Average Conducted Power(dBm)			
	Max.	CH0	CH39	CH78
	Tune up	2402MHz	2441MHz	2480MHz
DH5	11.50	10.44	10.64	10.66
2DH5	8.50	7.94	8.14	8.09
3DH5	8.50	7.91	8.19	8.07

BT	Average Conducted Power(dBm)			
	Max.	CH0	CH19	CH39
	Tune up	2402MHz	2440MHz	2480MHz
BLE(1M)	11.50	10.20	10.30	10.35
BLE(2M)	11.50	10.26	10.43	10.53

Note:

- 1) The Average conducted power of Bluetooth is measured with RMS detector.
- 2) The tested channel results are marks in bold.

7.1.2 CONDUCTED POWER MEASUREMENTS OF WIFI

1. Conducted power measurements of 2.4G WiFi

Band	Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	Max. Tune up	Average Power(dBm)
2.4G WIFI _1TX _Main Ant	802.11b	1	2412	1	16.50	16.37
		2	2417		16.50	16.15
		6	2437		16.50	16.28
		10	2457		16.50	16.41
		11	2462		16.50	16.14
		12	2467		16.50	16.29
		13	2472		16.50	16.08
	802.11g	1	2412	6	16.50	16.14
		2	2417		16.50	16.36
		6	2437		16.50	16.05
		10	2457		16.50	16.11
		11	2462		16.50	16.38
		12	2467		16.50	16.26
		13	2472		16.50	16.19
	802.11ac VHT20	1	2412	HT0	16.50	16.39
		2	2417		16.50	16.24
		6	2437		16.50	16.36
		10	2457		16.50	16.19
		11	2462		16.50	16.28
		12	2467		16.50	16.13
		13	2472		16.50	16.05
		3	2422		16.50	16.18
	802.11ac VHT40	4	2427	HT0	16.50	16.31
		6	2437		16.50	16.27
		8	2447		16.50	16.06
		9	2452		16.50	16.38
		10	2457		16.50	16.21
		11	2462		16.50	16.14

Band	Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	Max. Tune up	Average Power(dBm)
2.4G WIFI _1TX _Main Ant	802.11ax HE20	1	2412	MCS0	16.50	16.15
		2	2417		16.50	16.23
		6	2437		16.50	16.27
		10	2457		16.50	16.36
		11	2462		16.50	16.21
		12	2467		16.50	16.18
		13	2472		16.50	16.27
	802.11ax HE40	3	2422	MCS0	16.50	16.31
		4	2427		16.50	16.40
		6	2437		16.50	16.40
		8	2447		16.50	16.25
		9	2452		16.50	16.27
		10	2457		16.50	16.25
		11	2462		16.50	16.05

Band	Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	Max. Tune up	Average Power(dBm)
2.4G WIFI _1TX _Aux Ant	802.11b	1	2412	1	16.50	16.30
		2	2417		16.50	16.29
		6	2437		16.50	16.45
		10	2457		16.50	16.15
		11	2462		16.50	16.37
		12	2467		16.50	16.22
		13	2472		16.50	16.21
	802.11g	1	2412	6	16.50	16.34
		2	2417		16.50	16.21
		6	2437		16.50	16.29
		10	2457		16.50	16.33
		11	2462		16.50	16.10
		12	2467		16.50	16.25
		13	2472		16.50	16.22
	802.11ac VHT20	1	2412	HT0	16.50	16.19
		2	2417		16.50	16.37
		6	2437		16.50	16.21
		10	2457		16.50	16.13
		11	2462		16.50	16.20
		12	2467		16.50	16.06
		13	2472		16.50	16.31
	802.11ac VHT40	3	2422	HT0	16.50	16.24
		4	2427		16.50	16.35
		6	2437		16.50	16.22
		8	2447		16.50	16.15
		9	2452		16.50	16.29
		10	2457		16.50	16.16
		11	2462		16.50	16.25

Band	Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	Max. Tune up	Average Power(dBm)
2.4G WIFI _1TX _Aux Ant	802.11ax HE20	1	2412	MCS0	16.50	16.38
		2	2417		16.50	16.42
		6	2437		16.50	16.18
		10	2457		16.50	16.19
		11	2462		16.50	16.31
		12	2467		16.50	16.08
		13	2472		16.50	16.06
	802.11ax HE40	3	2422	MCS0	16.50	16.31
		4	2427		16.50	16.23
		6	2437		16.50	16.32
		8	2447		16.50	16.08
		9	2452		16.50	16.41
		10	2457		16.50	16.31
		11	2462		16.50	16.25

Band	Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	ANT Main Average Power(dBm)	ANT Aux Average Power(dBm)	Max. Tune up	Total Average Power(dBm)
2.4G WIFI _2TX _Main Ant + Aux Ant	802.11b	1	2412	1	13.37	13.30	16.50	16.35
		2	2417		13.15	13.29	16.50	16.23
		6	2437		13.28	13.45	16.50	16.38
		10	2457		13.41	13.15	16.50	16.29
		11	2462		13.14	13.37	16.50	16.27
		12	2467		13.29	13.22	16.50	16.27
		13	2472		13.08	13.21	16.50	16.16
	802.11g	1	2412	6	13.14	13.34	16.50	16.25
		2	2417		13.36	13.21	16.50	16.30
		6	2437		13.05	13.29	16.50	16.18
		10	2457		13.11	13.33	16.50	16.23
		11	2462		13.38	13.10	16.50	16.25
		12	2467		13.26	13.25	16.50	16.27
		13	2472		13.19	13.22	16.50	16.22
	802.11ac VHT20	1	2412	HT8	13.39	13.19	16.50	16.30
		2	2417		13.24	13.37	16.50	16.32
		6	2437		13.36	13.21	16.50	16.30
		10	2457		13.19	13.13	16.50	16.17
		11	2462		13.28	13.20	16.50	16.25
		12	2467		13.13	13.06	16.50	16.11
		13	2472		13.05	13.31	16.50	16.19
	802.11ac VHT40	3	2422	HT8	13.18	13.24	16.50	16.22
		4	2427		13.31	13.35	16.50	16.34
		6	2437		13.27	13.22	16.50	16.26
		8	2447		13.06	13.15	16.50	16.12
		9	2452		13.38	13.29	16.50	16.35
		10	2457		13.21	13.16	16.50	16.20
		11	2462		13.14	13.25	16.50	16.21

Band	Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	ANT Main Average Power(dBm)	ANT Aux Average Power(dBm)	Max. Tune up	Total Average Power(dBm)
2.4G WIFI _2TX _Main Ant + Aux Ant	802.11ax HE20	1	2412	MCS8	13.15	13.38	16.50	16.28
		2	2417		13.23	13.42	16.50	16.34
		6	2437		13.27	13.18	16.50	16.24
		10	2457		13.36	13.19	16.50	16.29
		11	2462		13.21	13.31	16.50	16.27
		12	2467		13.18	13.08	16.50	16.14
		13	2472		13.27	13.06	16.50	16.18
	802.11ax HE40	3	2422	MCS8	13.31	13.31	16.50	16.32
		4	2427		13.40	13.23	16.50	16.33
		6	2437		13.40	13.32	16.50	16.37
		8	2447		13.25	13.08	16.50	16.18
		9	2452		13.27	13.41	16.50	16.35
		10	2457		13.25	13.31	16.50	16.29
		11	2462		13.05	13.25	16.50	16.16

Note:

- 1) The Average conducted power of 2.4G WiFi is measured with RMS detector.
- 2) Per KDB248227 D01, for 2.4G WiFi, the highest measured maximum output power Channel for DSSS modes (802.11b) was selected for SAR measurement. SAR for OFDM modes (2.4GHz 802.11g/n) was not required. When the highest reported SAR for DSSS is adjusted by the ratio of OFDM modes (802.11g/n) to DSSS modes (802.11b) specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.
- 3) The tested channel results are marked in bold.

2. Conducted power measurements of 5.2G WiFi

Band	Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	Max. Tune up	Average Power(dBm)
5.2G WIFI _1TX _Main Ant	802.11a	36	5180	6	16.00	15.61
		40	5200		16.00	15.69
		48	5240		16.00	15.78
	802.11ac VHT20	36	5180	VHT0	16.00	15.59
		40	5200		16.00	15.63
		48	5240		16.00	15.76
	802.11ac VHT40	38	5190	VHT0	16.00	15.80
		46	5230		16.00	15.83
	802.11ac VHT80	42	5210	VHT0	16.00	15.88
	802.11ax HE20	36	5180	MCS0	16.00	15.66
		40	5200		16.00	15.78
		48	5240		16.00	15.65
	802.11ax HE40	38	5190	MCS0	16.00	15.64
		46	5230		16.00	15.55
	802.11ax HE80	42	5210	MCS0	16.00	15.81

Band	Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	Max. Tune up	Average Power(dBm)
5.2G WIFI _1TX _Aux Ant	802.11a	36	5180	6	16.00	15.59
		40	5200		16.00	15.64
		48	5240		16.00	15.78
	802.11ac VHT20	36	5180	VHT0	16.00	15.55
		40	5200		16.00	15.92
		48	5240		16.00	15.58
	802.11ac VHT40	38	5190	VHT0	16.00	15.85
		46	5230		16.00	15.83
	802.11ac VHT80	42	5210	VHT0	16.00	15.93
	802.11ax HE20	36	5180	MCS0	16.00	15.83
		40	5200		16.00	15.76
		48	5240		16.00	15.68
	802.11ax HE40	38	5190	MCS0	16.00	15.92
		46	5230		16.00	15.92
	802.11ax HE80	42	5210	MCS0	16.00	15.90

Band	Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	ANT Main Average Power(dBm)	ANT Aux Average Power(dBm)	Max. Tune up	Total Average Power(dBm)
5.2G WIFI _2TX _Main Ant + Aux Ant	802.11a	36	5180	6	12.61	12.59	16.00	15.61
		40	5200		12.69	12.64	16.00	15.68
		48	5240		12.78	12.78	16.00	15.79
	802.11ac VHT20	36	5180	HT8	12.59	12.55	16.00	15.58
		40	5200		12.63	12.92	16.00	15.79
		48	5240		12.76	12.58	16.00	15.68
	802.11ac VHT40	38	5190	VHT8	12.80	12.85	16.00	15.84
		46	5230		12.83	12.83	16.00	15.84
	802.11ac VHT80	42	5210	VHT8	12.63	12.61	16.00	15.63
	802.11ax HE20	36	5180	MCS8	12.66	12.83	16.00	15.76
		40	5200		12.78	12.76	16.00	15.78
		48	5240		12.65	12.68	16.00	15.68
	802.11ax HE40	38	5190	MCS8	12.64	12.92	16.00	15.79
		46	5230		12.55	12.92	16.00	15.75
	802.11ax HE80	42	5210	MCS8	12.88	12.93	16.00	15.92

Note:

- 1) The Average conducted power of 5.2G WiFi is measured with RMS detector.
- 2) The tested channel results are marks in bold.

3. Conducted power measurements of 5.3G WiFi

Band	Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	Max. Tune up	Average Power(dBm)
5.3G WIFI _1TX _Main Ant	802.11a	52	5260	6	16.00	15.62
		60	5300		16.00	15.89
		64	5320		16.00	15.71
	802.11ac VHT20	52	5260	VHT0	16.00	15.81
		60	5300		16.00	15.72
		64	5320		16.00	15.55
	802.11ac VHT40	54	5270	VHT0	16.00	15.71
		62	5310		16.00	15.87
	802.11ac VHT80	58	5290	VHT0	16.00	15.92
	802.11ax HE20	52	5260	MCS0	16.00	15.72
		60	5300		16.00	15.89
		64	5320		16.00	15.91
	802.11ax HE40	54	5270	MCS0	16.00	15.64
		62	5310		16.00	15.54
	802.11ax HE80	58	5290	MCS0	16.00	15.73

Band	Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	Max. Tune up	Average Power(dBm)
5.3G WIFI _1TX _Aux Ant	802.11a	52	5260	6	16.00	15.81
		60	5300		16.00	15.84
		64	5320		16.00	15.78
	802.11ac VHT20	52	5260	VHT0	16.00	15.67
		60	5300		16.00	15.60
		64	5320		16.00	15.64
	802.11ac VHT40	54	5270	VHT0	16.00	15.67
		62	5310		16.00	15.82
	802.11ac VHT80	58	5290	VHT0	16.00	15.87
	802.11ax HE20	52	5260	MCS0	16.00	15.72
		60	5300		16.00	15.66
		64	5320		16.00	15.76
	802.11ax HE40	54	5270	MCS0	16.00	15.59
		62	5310		16.00	15.66
	802.11ax HE80	58	5290	MCS0	16.00	15.82

Band	Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	ANT Main Average Power(dBm)	ANT Aux Average Power(dBm)	Max. Tune up	Total Average Power(dBm)
5.3G WIFI _2TX _Main Ant + Aux Ant	802.11a	52	5260	6	12.62	12.81	16.00	15.73
		60	5300		12.89	12.84	16.00	15.88
		64	5320		12.71	12.78	16.00	15.76
	802.11ac VHT20	52	5260	VHT8	12.81	12.67	16.00	15.75
		60	5300		12.72	12.60	16.00	15.67
		64	5320		12.55	12.64	16.00	15.61
	802.11ac VHT40	54	5270	VHT8	12.71	12.67	16.00	15.70
		62	5310		12.87	12.82	16.00	15.86
	802.11ac VHT80	58	5290	VHT8	12.73	12.77	16.00	15.76
	802.11ax HE20	52	5260	MCS8	12.72	12.72	16.00	15.73
		60	5300		12.89	12.66	16.00	15.79
		64	5320		12.91	12.76	16.00	15.85
	802.11ax HE40	54	5270	MCS8	12.64	12.59	16.00	15.63
		62	5310		12.54	12.66	16.00	15.61
	802.11ax HE80	58	5290	MCS8	12.92	12.87	16.00	15.91

Note:

- 1) The Average conducted power of 5.3G WiFi is measured with RMS detector.
- 2) The tested channel results are marks in bold.

4. Conducted power measurements of 5.6G WiFi

Band	Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	Max. Tune up	Average Power(dBm)
5.6G WIFI _1TX _Main Ant	802.11a	100	5500	6	16.00	15.58
		116	5580		16.00	15.61
		140	5700		16.00	15.66
	802.11ac VHT20	100	5500	VHT0	16.00	15.73
		116	5580		16.00	15.70
		140	5700		16.00	15.74
	802.11ac VHT40	102	5510	VHT0	16.00	15.68
		110	5550		16.00	15.76
		134	5670		16.00	15.75
	802.11ac VHT80	106	5530	VHT0	16.00	15.66
		122	5610		16.00	15.76
	802.11ax HE20	100	5500	MCS0	16.00	15.71
		116	5580		16.00	15.65
		140	5700		16.00	15.57
	802.11ax HE40	102	5510	MCS0	16.00	15.68
		110	5550		16.00	15.54
		134	5670		16.00	15.55
	802.11ax HE80	106	5530	MCS0	16.00	15.66
		122	5610		16.00	15.70

Band	Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	Max. Tune up	Average Power(dBm)
5.6G WIFI _1TX _Aux Ant	802.11a	100	5500	6	16.00	15.66
		116	5580		16.00	15.69
		140	5700		16.00	15.59
	802.11ac VHT20	100	5500	VHT0	16.00	15.59
		116	5580		16.00	15.61
		140	5700		16.00	15.74
	802.11ac VHT40	102	5510	VHT0	16.00	15.74
		110	5550		16.00	15.58
		134	5670		16.00	15.69
	802.11ac VHT80	106	5530	VHT0	16.00	15.77
		122	5610		16.00	15.78
	802.11ax HE20	100	5500	MCS0	16.00	15.58
		116	5580		16.00	15.63
		140	5700		16.00	15.58
	802.11ax HE40	102	5510	MCS0	16.00	15.59
		110	5550		16.00	15.75
		134	5670		16.00	15.65
	802.11ax HE80	106	5530	MCS0	16.00	15.77
		122	5610		16.00	15.73

Band	Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	ANT Main Average Power(dBm)	ANT Aux Average Power(dBm)	Max. Tune up	Total Average Power(dBm)
5.6G WiFi 2TX	802.11a	100	5500	6	12.88	12.66	16.00	15.78
		116	5580		12.81	12.69	16.00	15.76
		140	5700		12.66	12.80	16.00	15.74
	802.11ac VHT20	100	5500	VHT8	12.73	12.59	16.00	15.67
		116	5580		12.80	12.61	16.00	15.72
		140	5700		12.74	12.74	16.00	15.75
	802.11ac VHT40	102	5510	VHT8	12.92	12.74	16.00	15.84
		110	5550		12.76	12.58	16.00	15.68
		134	5670		12.75	12.69	16.00	15.73
	802.11ac VHT80	106	5530	VHT8	12.57	12.79	16.00	15.69
		122	5610		12.87	12.69	16.00	15.79
	802.11ax HE20	100	5500	MCS8	12.87	12.58	16.00	15.74
		116	5580		12.65	12.88	16.00	15.78
		140	5700		12.57	12.58	16.00	15.59
	802.11ax HE40	102	5510	MCS8	12.68	12.59	16.00	15.65
		110	5550		12.54	12.75	16.00	15.66
		134	5670		12.55	12.85	16.00	15.71
	802.11ax HE80	106	5530	MCS8	12.66	12.77	16.00	15.73
		122	5610		12.76	12.78	16.00	15.78

Note:

- 1) The Average conducted power of 5.6G WiFi is measured with RMS detector.
- 2) The tested channel results are marks in bold.

5. Conducted power measurements of 5.8G WiFi

Band	Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	Max. Tune up	Average Power(dBm)
5.8G WIFI _1TX _Main Ant	802.11a	149	5745	6	16.00	15.55
		157	5785		16.00	15.71
		165	5825		16.00	15.83
	802.11ac VHT20	149	5745	VHT0	16.00	15.73
		157	5785		16.00	15.77
		165	5825		16.00	15.54
	802.11ac VHT40	151	5755	VHT0	16.00	15.70
		159	5795		16.00	15.71
	802.11ac VHT80	155	5775	VHT0	16.00	15.89
	802.11ax HE20	149	5745	MCS0	16.00	15.80
		157	5785		16.00	15.86
		165	5825		16.00	15.54
	802.11ax HE40	151	5755	MCS0	16.00	15.65
		159	5795		16.00	15.55
	802.11ax HE80	155	5775	MCS0	16.00	15.82

Band	Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	Max. Tune up	Average Power(dBm)
5.8G WIFI _1TX _Aux Ant	802.11a	149	5745	6	16.00	15.88
		157	5785		16.00	15.64
		165	5825		16.00	15.66
	802.11ac VHT20	149	5745	VHT0	16.00	15.79
		157	5785		16.00	15.65
		165	5825		16.00	15.90
	802.11ac VHT40	151	5755	VHT0	16.00	15.81
		159	5795		16.00	15.76
	802.11ac VHT80	155	5775	VHT0	16.00	15.97
	802.11ax HE20	149	5745	MCS0	16.00	15.58
		157	5785		16.00	15.84
		165	5825		16.00	15.91
	802.11ax HE40	151	5755	MCS0	16.00	15.77
		159	5795		16.00	15.59
	802.11ax HE80	155	5775	MCS0	16.00	15.84

Band	Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	ANT Main Average Power(dBm)	ANT Aux Average Power(dBm)	Max. Tune up	Total Average Power(dBm)
5.8G WIFI _2TX _Main Ant + Aux Ant	802.11a	149	5745	6	12.55	12.88	16.00	15.73
		157	5785		12.71	12.64	16.00	15.69
		165	5825		12.83	12.66	16.00	15.76
	802.11ac VHT20	149	5745	VHT8	12.73	12.79	16.00	15.77
		157	5785		12.77	12.65	16.00	15.72
		165	5825		12.54	12.90	16.00	15.73
	802.11ac VHT40	151	5755	VHT8	12.70	12.81	16.00	15.77
		159	5795		12.71	12.76	16.00	15.75
	802.11ac VHT80	155	5775	VHT8	12.86	12.84	16.00	15.86
	802.11ax HE20	149	5745	MCS8	12.80	12.58	16.00	15.70
		157	5785		12.86	12.84	16.00	15.86
		165	5825		12.54	12.91	16.00	15.74
	802.11ax HE40	151	5755	MCS8	12.65	12.77	16.00	15.72
		159	5795		12.55	12.59	16.00	15.58
	802.11ax HE80	155	5775	MCS8	12.89	12.97	16.00	15.94

Note:

- 1) The Average conducted power of 5.8G WiFi is measured with RMS detector.
- 2) The tested channel results are marks in bold.

7.2 SAR TEST RESULTS

General Notes:

- 1) Per KDB447498 D01, all measurement SAR results are scaled to the maximum tune-up tolerance limit to demonstrate compliant.
- 2) Per KDB447498 D01, testing of other required channels within the operating mode of a frequency band is not required when the reported 1-g or 10-g SAR for the mid-band or highest output power channel is: $\leq 0.8 \text{ W/kg}$ or 2.0 W/kg , for 1-g or 10-g respectively, when the transmission band is $\leq 100 \text{ MHz}$. When the maximum output power variation across the required test channels is $> \frac{1}{2} \text{ dB}$, instead of the middle channel, the highest output power channel must be used.
- 3) Per KDB865664 D01, for each frequency band, repeated SAR measurement is required only when the measured SAR is $\geq 0.8 \text{ W/kg}$; if the deviation among the repeated measurement is $\leq 20\%$, and the measured SAR $< 1.45 \text{ W/kg}$, only one repeated measurement is required.
- 4) Per KDB941225 D06, the DUT Dimension is bigger than $9 \text{ cm} \times 5 \text{ cm}$, so 10mm is chosen as the test separation distance for Hotspot mode. When the antenna-to-edge distance is greater than 2.5cm, such position does not need to be tested.
- 5) Per KDB648474 D04, SAR is evaluated without a headset connected to the device. When the standalone reported body-worn SAR is $\leq 1.2 \text{ W/kg}$, no additional SAR evaluations using a headset are required.
- 6) Per KDB865664 D02, SAR plot is only required for the highest measured SAR in each exposure configuration, wireless mode and frequency band combination; Plots are also required when the measured SAR is $> 1.5 \text{ W/kg}$, or $> 7.0 \text{ W/kg}$ for occupational exposure. The published RF exposure KDB procedures may require additional plots; for example, to support SAR to peak location separation ratio test exclusion and/or volume scan post-processing.

WLAN Notes:

1. For exposure conditions with multiple test positions, such as handset operating next to the ear, devices with hotspot mode, procedures for initial test position can be applied. Using the transmission mode determined by the DSSS procedure or initial test configuration, area scans are measured for all positions in an exposure condition. The test position with the highest extrapolated (peak) SAR is used as the initial test position. When the reported SAR of the initial test position is $\leq 0.4 \text{ W/kg}$, further SAR measurement is not required for the other (remaining) test positions. Otherwise, SAR is evaluated at the subsequent highest peak SAR position until the reported SAR result is $\leq 0.8 \text{ W/kg}$ or all test positions are measured.
2. Justification for test configurations for WLAN per KDB Publication 248227 for 2.4GHZ WIFI single transmission chain operations, the highest measured maximum output power Channel for DSSS was selected for SAR measurement. SAR for OFDM modes (2.4GHz 802.11g/n) was not required due to the maximum allowed powers and the highest reported DSSS SAR. See Section 7.1 for more information.
3. Justification for test configurations for WLAN per KDB Publication 248227 for 5GHZ WIFI single transmission chain operations, the initial test configuration was selected according to the transmission mode with the highest maximum allowed power. Other transmission modes were not investigated since the highest reported SAR for initial test configuration adjusted by the ratio of maximum output powers is less than 1.2W/kg. See Section 7.1 for more information.

7.2.1 SAR MEASUREMENT RESULT

1. SAR test results of WiFi 2.4G

Test No.	Band	Channel	Test Position	Separation Distance (cm)	Ant	Ant Vendor	Data Rate	Duty Cycle (%)	Maximum Tune-up (dBm)	Conducted Power (dBm)	Power Drift (dB)	SAR 1g (W/kg)	SAR 10g (W/kg)	Reported 1g SAR
W01	802.11b	6	Back of Screen	2.5	Aux	ZTX	1	99.43	16.5	16.45	-0.02	<0.001	<0.001	<0.001
W02	802.11b	6	Back of Keyboard	0	Aux	ZTX	1	99.43	16.5	16.45	0.1	0.131	0.059	0.147
W03	802.11b	6	Back of Keyboard	0	Aux	South Star	1	99.43	16.5	16.45	0.06	0.156	0.070	0.175
W08	802.11b	10	Back of Screen	2.5	Main	ZTX	1	99.43	16.5	16.41	0.01	<0.001	<0.001	<0.001
W09	802.11b	10	Back of Keyboard	0	Main	ZTX	1	99.43	16.5	16.41	0.06	0.194	0.093	0.220
W10	802.11b	10	Back of Keyboard	0	Main	South Star	1	99.43	16.5	16.41	0.02	0.181	0.085	0.205

Note: The value with boldface is the maximum SAR Value of each test band.

2. SAR test results of BT

Test No.	Band	Channel	Test Position	Separation Distance (cm)	Ant	Ant Vendor	Data Rate	Duty Cycle (%)	Maximum Tune-up (dBm)	Conducted Power (dBm)	Power Drift (dB)	SAR 1g (W/kg)	SAR 10g (W/kg)	Reported 1g SAR
B01	BT DH5	78	Back of Screen	2.5	Aux	ZTX	-	76.57	11.5	10.66	0.15	<0.001	<0.001	<0.001
B02	BT DH5	78	Back of Keyboard	0	Aux	ZTX	-	76.57	11.5	10.66	0.02	0.036	0.012	0.043
B03	BT DH5	78	Back of Keyboard	0	Aux	South Star	-	76.57	11.5	10.66	-0.04	0.043	0.017	0.053

Note: The value with boldface is the maximum SAR Value of each test band.

3. SAR test results of WiFi 5G


Test No.	Band	Channel	Test Position	Separation Distance (cm)	Ant	Ant Vendor	Data Rate	Duty Cycle (%)	Maximum Tune-up (dBm)	Conducted Power (dBm)	Power Drift (dB)	SAR 1g (W/kg)	SAR 10g (W/kg)	Reported 1g SAR
W15	802.11ac VHT80	42	Back of Screen	2.5	Aux	ZTX	VHT0	85.02	16.0	15.93	-0.05	0.005	0.002	0.006
W16	802.11ac VHT80	42	Back of Keyboard	0	Aux	ZTX	VHT0	85.02	16.0	15.93	0.16	0.132	0.040	0.150
W17	802.11ac VHT80	42	Back of Keyboard	0	Aux	South Star	VHT0	85.02	16.0	15.93	0.01	0.148	0.051	0.168
W20	802.11ac VHT80	42	Back of Screen	2.5	Main	ZTX	VHT0	85.02	16.0	15.88	-0.07	0.027	0.009	0.031
W21	802.11ac VHT80	42	Back of Keyboard	0	Main	ZTX	VHT0	85.02	16.0	15.88	0.01	0.160	0.054	0.184
W22	802.11ac VHT80	42	Back of Keyboard	0	Main	South Star	VHT0	85.02	16.0	15.88	-0.04	0.168	0.053	0.193
W25	802.11ac VHT80	58	Back of Screen	2.5	Aux	ZTX	VHT0	85.02	16.0	15.87	-0.05	0.035	0.009	0.040
W26	802.11ac VHT80	58	Back of Keyboard	0	Aux	ZTX	VHT0	85.02	16.0	15.87	0.03	0.145	0.043	0.167
W27	802.11ac VHT80	58	Back of Keyboard	0	Aux	South Star	VHT0	85.02	16.0	15.87	0	0.201	0.059	0.232
W30	802.11ac VHT80	58	Back of Screen	2.5	Main	ZTX	VHT0	85.02	16.0	15.92	0.09	0.021	0.007	0.024
W31	802.11ac VHT80	58	Back of Keyboard	0	Main	ZTX	VHT0	85.02	16.0	15.92	-0.02	0.116	0.039	0.132
W32	802.11ac VHT80	58	Back of Keyboard	0	Main	South Star	VHT0	85.02	16.0	15.92	0.02	0.103	0.033	0.117
W35	802.11ac VHT80	122	Back of Screen	2.5	Aux	ZTX	VHT0	85.02	16.0	15.78	0.01	0.010	0.004	0.012
W36	802.11ac VHT80	122	Back of Keyboard	0	Aux	ZTX	VHT0	85.02	16.0	15.78	-0.01	0.564	0.159	0.664
W37	802.11ac VHT80	122	Back of Keyboard	0	Aux	South Star	VHT0	85.02	16.0	15.78	0.12	0.559	0.153	0.658
W40	802.11ac VHT80	122	Back of Screen	2.5	Main	ZTX	VHT0	85.02	16.0	15.76	-0.01	<0.001	<0.001	<0.001
W41	802.11ac VHT80	122	Back of Keyboard	0	Main	ZTX	VHT0	85.02	16.0	15.76	-0.16	0.544	0.143	0.643
W42	802.11ac VHT80	122	Back of Keyboard	0	Main	South Star	VHT0	85.02	16.0	15.76	0.03	0.584	0.165	0.691
W45	802.11ac VHT80	155	Back of Screen	2.5	Aux	ZTX	VHT0	85.02	16.0	15.97	-0.3	0.055	0.020	0.062
W46	802.11ac VHT80	155	Back of Keyboard	0	Aux	ZTX	VHT0	85.02	16.0	15.97	0.07	0.457	0.139	0.515
W47	802.11ac VHT80	155	Back of Keyboard	0	Aux	South Star	VHT0	85.02	16.0	15.97	0.12	0.558	0.163	0.629
W50	802.11ac VHT80	155	Back of Screen	2.5	Main	ZTX	VHT0	85.02	16.0	15.89	0.02	0.092	0.037	0.106
W51	802.11ac VHT80	155	Back of Keyboard	0	Main	ZTX	VHT0	85.02	16.0	15.89	0.07	0.376	0.102	0.432
W52	802.11ac VHT80	155	Back of Keyboard	0	Main	South Star	VHT0	85.02	16.0	15.89	-0.01	0.430	0.118	0.493

Note: The value with boldface is the maximum SAR Value of each test band.

7.3 MULTIPLE TRANSMITTER EVALUATION

The following tables list information which is relevant for the decision if a simultaneous transmit evaluation is necessary according to FCC KDB 447498D01 General RF Exposure Guidance v06.

The location of the antennas inside the EUT is shown as below picture:



7.3.1 STAND-ALONE SAR TEST EXCLUSION

Per FCC KDB 447498D01, SAR compliance for simultaneous transmission must be considered when the maximum duration of overlapping transmissions, including network hand-offs, is greater than 30 seconds. This device contains multiple transmitters that may operate simultaneously, and therefore requires a simultaneous transmission analysis.

The Simultaneous Transmission Possibilities of this device are as below:

No.	Configuration	Body
1	WLAN 2.4G Main Ant + WLAN 2.4G Aux Ant	Yes
2	WLAN 5.2G Main Ant + WLAN 5.2G Aux Ant	Yes
3	WLAN 5.3G Main Ant + WLAN 5.3G Aux Ant	Yes
4	WLAN 5.6G Main Ant + WLAN 5.6G Aux Ant	Yes
5	WLAN 5.8G Main Ant + WLAN 5.8G Aux Ant	Yes
6	WLAN 2.4G Main Ant + BT Aux Ant	Yes
7	WLAN 5.2G Main Ant + BT Aux Ant	Yes
8	WLAN 5.3G Main Ant + BT Aux Ant	Yes
9	WLAN 5.6G Main Ant + BT Aux Ant	Yes
10	WLAN 5.8G Main Ant + BT Aux Ant	Yes

Note: Only the Aux Ant supports BT function.

7.3.2 SIMULTANEOUS TRANSMISSION CONDITIONS

About WIFI and Bluetooth transmit simultaneously

Band	Position	Back of Screen	Back of Keyboard
Main Ant	WiFi 2.4G	<0.001	0.220
Aux Ant	WiFi 2.4G	<0.001	0.175
	MAX $\sum \text{SAR}_{1g}$	<0.001	0.395

Band	Position	Back of Screen	Back of Keyboard
Main Ant	WiFi 5.2G	0.031	0.193
Aux Ant	WiFi 5.2G	0.006	0.168
	MAX $\sum \text{SAR}_{1g}$	0.037	0.361

Band	Position	Back of Screen	Back of Keyboard
Main Ant	WiFi 5.3G	0.024	0.132
Aux Ant	WiFi 5.3G	0.040	0.232
	MAX $\sum \text{SAR}_{1g}$	0.064	0.364

Band	Position	Back of Screen	Back of Keyboard
Main Ant	WiFi 5.6G	<0.001	0.691
Aux Ant	WiFi 5.6G	0.012	0.664
	MAX $\sum \text{SAR}_{1g}$	0.012	1.355

Band	Position	Back of Screen	Back of Keyboard
Main Ant	WiFi 5.8G	0.106	0.493
Aux Ant	WiFi 5.8G	0.062	0.629
	MAX $\sum \text{SAR}_{1g}$	0.168	1.122

Band	Position	Back of Screen	Back of Keyboard
Main Ant	WiFi 2.4G	<0.001	0.220
Aux Ant	BT	<0.001	0.053
	MAX \sum SAR _{1g}	<0.001	0.273


Band	Position	Back of Screen	Back of Keyboard
Main Ant	WiFi 5.2G	0.031	0.193
Aux Ant	BT	<0.001	0.053
	MAX \sum SAR _{1g}	0.031	0.246

Band	Position	Back of Screen	Back of Keyboard
Main Ant	WiFi 5.3G	0.024	0.132
Aux Ant	BT	<0.001	0.053
	MAX \sum SAR _{1g}	0.024	0.185

Band	Position	Back of Screen	Back of Keyboard
Main Ant	WiFi 5.6G	<0.001	0.691
Aux Ant	BT	<0.001	0.053
	MAX \sum SAR _{1g}	<0.001	0.744

Band	Position	Back of Screen	Back of Keyboard
Main Ant	WiFi 5.8G	0.106	0.493
Aux Ant	BT	<0.001	0.053
	MAX \sum SAR _{1g}	0.106	0.546

Note: Thus SAR_{MAX.total}=1.355W/kg <1.6W/kg, so Simultaneous SAR are not required for Main Ant and Aux Ant.

APPENDIX**1. TEST LAYOUT****Specific Absorption Rate Test Layout****Liquid depth in the flat Phantom (≥ 15 cm depth)**

HSL_2300MHz-2700MHz_Body_15.6cm HSL_5000MHz-6000MHz_Body_15.4cm



Appendix A. SAR Plots of System Verification

(Pls See BTL-FCC SAR-3-2203C055_Appendix A.)

Appendix B. SAR Plots of SAR Measurement

(Pls See BTL-FCC SAR-3-2203C055_Appendix B.)

Appendix C. Calibration Certificate

(Pls See BTL-FCC SAR-3-2203C055_Appendix C.)

Appendix D. Photographs of the Test Set-Up

(Pls See BTL-FCC SAR-3-2203C055_Appendix D.)

End of Test Report