

TEST REPORT

Applicant: MediaTek Inc.
Address: No. 1, Dusing 1st Rd. Hsinchu Science Park
Hsinchu City 30078 Taiwan
Equipment Type: 2TX 11ax (WiFi6E) + BT/BLE Combo Card
Model Name: MT7922A22M
Brand Name: MediaTek
FCC ID: RAS-MT7922A22M
Test Standard: FCC 47 CFR Part 2.1093
(refer section 3.1)
Maximum SAR: Body 2.4GHz(1 g): 1.03 W/kg
Body 5GHz(1 g): 1.19 W/kg
Test Date: Mar. 26, 2022 - Mar. 29, 2022
Date of Issue: Apr. 24, 2022

ISSUED BY:

Shenzhen BALUN Technology Co., Ltd.

Tested by: Zhang Jiwei

Checked by: Liyao Zong

Approved by: Wei Yanquan
(Chief Engineer)

Zhang Jiwei

Liyao. Zong

Wei Yanquan

Revision History

Version	Issue Date	Revisions Content
<u>Rev. 01</u>	<u>Apr. 19, 2022</u>	<u>Initial Issue</u>
<u>Rev. 02</u>	<u>Apr. 24, 2022</u>	<u>Added section 3.3.2</u>

TABLE OF CONTENTS

1	GENERAL INFORMATION.....	4
1.1	Identification of the Testing Laboratory	4
1.2	Identification of the Responsible Testing Location	4
2	PRODUCT INFORMATION	5
2.1	Applicant Information	5
2.2	Manufacturer Information.....	5
2.3	General Description for Equipment under Test (EUT).....	5
2.4	Ancillary Equipment.....	6
2.5	Technical Information	7
3	SUMMARY OF TEST RESULT	8
3.1	Test Standards	8
3.2	Device Category and SAR Limit	9
3.3	Test Result Summary	10
3.4	Test Uncertainty	11
4	MEASUREMENT SYSTEM	12
4.1	Specific Absorption Rate (SAR) Definition	12
4.2	DASY SAR System	13
5	SYSTEM VERIFICATION	22
5.1	Purpose of System Check	22
5.2	System Check Setup	22
6	TEST POSITION CONFIGURATIONS	23
6.1	Laptop Exposure Condition.....	23
6.2	Tablet Exposure Condition.....	24
7	MEASUREMENT PROCEDURE	25

7.1	Measurement Process Diagram	25
7.2	SAR Scan General Requirement	26
7.3	Measurement Procedure	27
7.4	Area & Zoom Scan Procedure	27
8	CONDUCTED RF OUPUT POWER	28
8.1	WIFI.....	28
8.2	Bluetooth	48
8.3	Power reduction mechanism.....	50
9	TEST EXCLUSION CONSIDERATION	52
9.1	Laptop Mode antenna location sketch	52
9.2	Tablet Mode antenna location sketch	53
9.3	SAR Test Consideration Table	54
10	TEST RESULT	58
10.1	Bluetooth	58
10.2	WIFI 2.4GHz.....	58
10.3	WIFI 5GHz.....	59
11	SAR Measurement Variability	60
12	SIMULTANEOUS TRANSMISSION.....	61
12.1	Simultaneous Transmission Mode Considerations	61
12.2	Sum SAR of Simultaneous Transmission	62
13	TEST EQUIPMENTS LIST	69
ANNEX A	SIMULATING LIQUID VERIFICATION RESULT	70
ANNEX B	SYSTEM CHECK RESULT	71
ANNEX C	TEST DATA.....	76
ANNEX D	EUT EXTERNAL PHOTOS.....	94
ANNEX E	SAR TEST SETUP PHOTOS	94
ANNEX F	CALIBRATION REPORT	94
ANNEX G	Gravity-Sensor Conducted Power Test Results	94

1 GENERAL INFORMATION

1.1 Identification of the Testing Laboratory

Company Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1/F, Baisha Science and Technology Park, Shahe West Road, Nanshan District, ShenZhen, GuangDong Province, China
Phone Number	+86 755 6685 0100

1.2 Identification of the Responsible Testing Location

Test Location	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1/F, Baisha Science and Technology Park, Shahe West Road, Nanshan District, ShenZhen, GuangDong Province, China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196.
Description	All measurement facilities used to collect the measurement data are located at Block B, 1/F, Baisha Science and Technology Park, Shahe West Road, Nanshan District, ShenZhen, GuangDong Province, China.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	MediaTek Inc.
Address	No. 1, Dusing 1st Rd. Hsinchu Science Park Hsinchu City 30078 Taiwan

2.2 Manufacturer Information

Manufacturer	N/A
Address	N/A

2.3 General Description for Equipment under Test (EUT)

EUT Name	2TX 11ax (WiFi6E) + BT/BLE Combo Card
Model Name Under Test	MT7922A22M
Series Model Name	N/A
Description of Model name differentiation	N/A
Hardware Version	N/A
Software Version	N/A
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.3.1 Host Information:

Product Name	notebook computer
Model Name	Yoga 7 14IAL7, Yoga 7 14ARB7
Brand Name	Lenovo

2.3.2 Antenna Information:

Antenna Port	Model Name	Antenna Manufacturer	Antenna Type	Antenna Gain (dBi)								
				2.4 GHz	5.15 - 5.25 GHz	5.25 - 5.35 GHz	5.47 - 5.725 GHz	5.725 - 5.85 GHz	5.925 - 6.425 GHz	6.425 - 6.525 GHz	6.525 - 6.875 GHz	6.875 - 7.125 GHz
Main Antenna	DC33001 XQ00	AWAN	PIFA	1.95	1.92	0.33	1.15	-0.30	1.42	-0.80	-0.53	-0.18
Auxiliary Antenna	DC33001 XQ10		PIFA	1.66	1.02	-1.60	0.96	-0.20	2.83	0.08	-0.15	-0.66
Main Antenna	DC33001 XN00	INPAQ	PIFA	1.95	1.92	0.33	1.15	-0.30	1.42	-0.80	-0.53	-0.18
Auxiliary Antenna	DC33001 XN10		PIFA	1.66	1.02	-1.60	0.96	-0.20	2.83	0.08	-0.15	-0.66

Note: The report only shown the antenna which matches the antenna with the highest antenna gain.

2.4 Ancillary Equipment

Note: Not application.

2.5 Technical Information

Network and Wireless connectivity	Bluetooth (BR+EDR+BLE) 2.4G WIFI 802.11b, 802.11g, 802.11n(HT20/40), VHT20/40 and 802.11ax(HE20/40) 5G WIFI 802.11a, 802.11n(HT20/40), 802.11ac(VHT20/40/80/160) and 802.11ax(HE20/40/80/160), U-NII-1/2A/2C/3 6G WIFI 802.11a, 802.11ax(HE20/40/80/160) U-NII-5/6/7/8
-----------------------------------	--

The requirement for the following technical information of the EUT was tested in this report:

Operating Mode	2.4G WLAN, 5G WLAN, Bluetooth	
Frequency Range	802.11b/g	2412 MHz ~ 2472 MHz
	802.11n(HT20/HT40)	2412 MHz ~ 2472 MHz
	VHT20/VHT40	2412 MHz ~ 2472 MHz
	802.11ax(HE20/HE40)	2412 MHz ~ 2472 MHz
	802.11a	5150 MHz ~ 5250 MHz
		5250 MHz ~ 5350 MHz
		5470 MHz ~ 5725 MHz
		5725 MHz ~ 5850 MHz
	802.11n(HT20/HT40)	5150 MHz ~ 5250 MHz
		5250 MHz ~ 5350 MHz
		5470 MHz ~ 5725 MHz
		5725 MHz ~ 5850 MHz
	802.11ac(VHT20/VHT40/VHT80)	5150 MHz ~ 5250 MHz
		5250 MHz ~ 5350 MHz
		5470 MHz ~ 5725 MHz
		5725 MHz ~ 5850 MHz
	802.11ax(HE20/HE40/HE80)	5150 MHz ~ 5250 MHz
		5250 MHz ~ 5350 MHz
		5470 MHz ~ 5725 MHz
		5725 MHz ~ 5850 MHz
	802.11ac(VHT160)	5150 MHz ~ 5250 MHz
		5250 MHz ~ 5350 MHz
		5470 MHz ~ 5725 MHz
	802.11ax(HE160)	5150 MHz ~ 5250 MHz
		5250 MHz ~ 5350 MHz
		5470 MHz ~ 5725 MHz
	Bluetooth	2402 MHz ~ 2480 MHz
Antenna Type	WLAN: PIFA Antenna Bluetooth: PIFA Antenna	
Hotspot Function	N/A	
Exposure Category	General Population/Uncontrolled exposure	
EUT Stage	Portable Device	
Product	Type	
	☒ Production unit	☐ Identical prototype

3 SUMMARY OF TEST RESULT

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 2.1093	Radiofrequency radiation exposure evaluation: portable devices
2	ANSI C95.1-1992	IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz
3	IEEE Std. 1528-2013	Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
4	FCC KDB 447498 D04	RF Exposure Procedures and Equipment Authorization Policies for Mobile and Portable Devices
5	FCC KDB 865664 D01 v01r04	SAR Measurement 100 MHz to 6 GHz
6	FCC KDB 865664 D02 v01r02	RF Exposure Reporting
7	KDB 248227 D01 v02r02	SAR Guidance for IEEE 802.11 (Wi-Fi) Transmitters
8	KDB 616217 D04v01r02	SAR for laptop and tablets

3.2 Device Category and SAR Limit

This device belongs to portable device category because its radiating structure is allowed to be used within 20 centimeters of the body of the user.

Limit for General Population/Uncontrolled exposure should be applied for this device, it is 1.6 W/kg as averaged over any 1 gram of tissue.

Table of Exposure Limits:

Body Position	SAR Value (W/Kg)	
	General Population/ Uncontrolled Exposure	Occupational/ Controlled Exposure
Whole-Body SAR (averaged over the entire body)	0.08	0.4
Partial-Body SAR (averaged over any 1 gram of tissue)	1.60	8.0
SAR for hands, wrists, feet and ankles (averaged over any 10 grams of tissue)	4.0	20.0

NOTE:

General Population/Uncontrolled Exposure: Locations where there is the exposure of individuals who have no knowledge or control of their exposure. General population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

Occupational/Controlled Exposure: Locations where there is exposure that may be incurred by persons who are aware of the potential for exposure. In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

3.3 Test Result Summary

3.3.1 Highest SAR (1 g Value)

Band	Antenna	Maximum Scaled SAR (W/kg)	Maximum Report SAR (W/kg)
		Body	Body
2.4G WLAN	Main	0.80	1.19
2.4G WLAN	Aux.	1.03	
5.3G WLAN	Main	1.19	
5.3G WLAN	Aux.	1.19	
5.6G WLAN	Main	1.13	
5.6G WLAN	Aux.	1.01	
5.8G WLAN	Main	1.09	
5.8G WLAN	Aux.	0.87	
Bluetooth	Aux.	0.42	
Limit (W/kg)		1.60	
Verdict		Pass	

3.3.2 Highest SAR of Simultaneous Transmission (1 g Value)

Test Mode	Position	Mode	Max. 1g SAR	1g Sum SAR	SPLSR	SPLSR
			(W/kg)	(W/kg)	(Yes/No)	/
Body (Separation 0 mm)						
Laptop	Bottom Side	5.3 G WLAN (Main Antenna)	1.191	2.768	Yes	0.02
		5.3 G WLAN (Auxiliary Antenna)	1.158			
		Bluetooth (Auxiliary Antenna)	0.419			
Table	Bottom Edge	5.3 G WLAN (Main Antenna)	1.173	2.747	Yes	0.02
		5.3 G WLAN (Auxiliary Antenna)	1.185			
		Bluetooth (Auxiliary Antenna)	0.389			

3.4 Test Uncertainty

According to KDB 865664 D01, when the highest measured 1 g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis is not required in SAR reports submitted for equipment approval.

The maximum 1 g SAR for the EUT in this report is 1.191 W/kg, which is lower than 1.5 W/kg, so the extensive SAR measurement uncertainty analysis is not required in this report.

4 MEASUREMENT SYSTEM

4.1 Specific Absorption Rate (SAR) Definition

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg) SAR measurement can be related to the electrical field in the tissue by


$$SAR = \frac{\sigma E^2}{\rho}$$

Where: σ is the conductivity of the tissue,

ρ is the mass density of the tissue and E is the RMS electrical field strength.

4.2 DASY SAR System

4.2.1 DASY SAR System Diagram



The DASY5 system for performing compliance tests consists of the following items:

1. A standard high precision 6-axis robot (Stäubli RX family) with controller and software. An arm extension for accommodating the data acquisition electronics (DAE).
2. A dosimetric probe, i.e. an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
3. A data acquisition electronic (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
4. A unit to operate the optical surface detector which is connected to the EOC.
5. The Electro-Optical Coupler (EOC) performs the conversion from the optical into a digital electric signal of the DAE. The EOC is connected to the DASY5 measurement server.
6. The DASY5 measurement server, which performs all real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operation.
7. DASY5 software and SEMCAD data evaluation software.
8. Remote control with teach panel and additional circuitry for robot safety such as warning lamps, etc.
9. The generic twin phantom enabling the testing of left-hand and right-hand usage.
10. The device holder for handheld mobile phones.
11. Tissue simulating liquid mixed according to the given recipes.
12. System validation dipoles allowing to validate the proper functioning of the system.

4.2.2 Robot

The Dasy SAR system uses the high precision robots. Symmetrical design with triangular core Built-in optical fiber for surface detection system For the 6-axis controller system, Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents). The robot series have many features that are important for our application:



- High precision
(repeatability ± 0.02 mm)
- High reliability
(industrial design)
- Low maintenance costs
(virtually maintenance free due to direct drive gears; no belt drives)
- Jerk-free straight movements
(brush less synchron motors; no stepper motors)
- Low ELF interference
(motor control _elds shielded via the closed metallic construction shields)

4.2.3 E-Field Probe

The probe is specially designed and calibrated for use in liquids with high permittivities for the measurements the Specific Dosimetric E-Field Probe EX3DV4-SN: 3717 with following specifications is used.

Construction	Symmetrical design with triangular core Built-in optical fiber for surface detection systemBuilt-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., glycolether)
Calibration	ISO/IEC 17025 calibration service available
Frequency	10 MHz to 6 GHz; Linearity: ± 0.2 dB (30 MHz to 6 GHz)
Directivity	± 0.2 dB in HSL (rotation around probe axis) ; ± 0.4 dB in HSL (rotation normal to probe axis)
Dynamic range	5 μ W/g to > 100 mW/g; Linearity: ± 0.2 dB
Dimensions	Overall length: 337 mm (Tip: 9 mm) Tip diameter: 2.5 mm (Body: 10 mm) Distance from probe tip to dipole centers: 1.0 mm
Application	General dosimetry up to 3 GHz Compliance tests of mobile phones Fast automatic scanning in arbitrary phantoms (EX3DV4)

E-Field Probe Calibration Process

Probe calibration is realized, in compliance with CENELEC EN 62209-1/-2 and IEEE 1528 std, with CALISAR, Antennessa proprietary calibration system. The calibration is performed with the EN 62209-1/2 annexe technique using reference guide at the five frequencies.

4.2.4 Data Acquisition Electronics

The data acquisition electronics (DAE) consist of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock.



- Input Impedance: 200MΩ
- The Inputs: Symmetrical and Floating
- Common Mode Rejection: Above 80dB

4.2.5 Phantoms

For the measurements the Specific Anthropomorphic Mannequin (SAM) defined by the IEEE SCC-34/SC2 group is used. The phantom is a polyurethane shell integrated in a wooden table. The thickness of the phantom amounts to 2mm +/- 0.2mm. It enables the dosimetric evaluation of left and right phone usage and includes an additional flat phantom part for the simplified performance check. The phantom set-up includes a cover, which prevents the evaporation of the liquid.



- Left hand
- Right hand
- Flat phantom

Photo of Phantom SN1859



Serial Number	Material	Length	Height
SN 1859 SAM	Vinylester, glass fiber reinforced	1000	500

Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with the latest draft of the standard IEC 62209 Part II and all known tissue simulating liquids. ELI4 has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points.



• Flat phantom

Photo of Phantom SN1012



Serial Number	Shell Thickness (mm)	Major ellipse axis (mm)	Minor axis (mm)
SN 1012 ELI4	2.0 ± 0.2	600	500

4.2.6 Device Holder

The DASY5 device holder has two scales for device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear openings). The plane between the ear openings and the mouth tip has a rotation angle of 65° . The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. This device holder is used for standard mobile phones or PDA's only. If necessary an additional support of polystyrene material is used. Larger DUT's (e.g. notebooks) cannot be tested using this device holder. Instead a support of bigger polystyrene cubes and thin polystyrene plates is used to position the DUT in all relevant positions to find and measure spots with maximum SAR values. Therefore those devices are normally only tested at the flat part of the SAM.




The positioning system allows obtaining cheek and tilting position with a very good accuracy. Incompliance with CENELEC, the tilt angle uncertainty is lower than 1° .

4.2.7 Simulating Liquid

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5%.

Head Liquid Depth



Body Liquid Depth



The following table gives the recipes for tissue simulating liquid and the theoretical Conductivity/Permittivity.

Head (Reference IEEE1528)								
Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity σ (S/m)	Permittivity ϵ
750	41.1	57.0	0.2	1.4	0.2	0	0.89	41.9
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
900	40.3	57.9	0.2	1.4	0.2	0	0.97	41.5
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.4	40.0
2450	55.0	0	0	0.1	0	44.9	1.80	39.2
2600	54.9	0	0	0.1	0	45.0	1.96	39.0
Frequency (MHz)	Water (%)	Hexyl Carbitol (%)			Triton X-100 (%)		Conductivity σ (S/m)	Permittivity ϵ
5200	62.52	17.24			17.24		4.66	36.0
5800	62.52	17.24			17.24		5.27	35.3
Body (From instrument manufacturer)								
Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity σ (S/m)	Permittivity ϵ
750	51.7	47.2	0	0.9	0.1	0	0.96	55.5
835	50.8	48.2	0	0.9	0.1	0	0.97	55.2
900	50.8	48.2	0	0.9	0.1	0	1.05	55.0
1800, 1900, 2000	70.2	0	0	0.4	0	29.4	1.52	53.3
2450	68.6	0	0	0.1	0	31.3	1.95	52.7
2600	68.2	0	0	0.1	0	31.7	2.16	52.5
Frequency(MHz)	Water	DGBE			Salt		Conductivity	Permittivity

		(%)	(%)	σ (S/m)	ε
5200	78.60	21.40	/	5.54	47.86
5800	78.50	21.40	0.1	6.0	48.20


5 SYSTEM VERIFICATION

5.1 Purpose of System Check

The system performance check verifies that the system operates within its specifications. System and operator errors can be detected and corrected. It is recommended that the system performance check be performed prior to any usage of the system in order to guarantee reproducible results. The system performance check uses normal SAR measurements in a simplified setup with a well characterized source. This setup was selected to give a high sensitivity to all parameters that might fail or vary over time. The system check does not intend to replace the calibration of the components, but indicates situations where the system uncertainty is exceeded due to drift or failure.

5.2 System Check Setup


In the simplified setup for system evaluation, the EUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave that comes from a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The equipment setup is shown below:



6 TEST POSITION CONFIGURATIONS

6.1 Laptop Exposure Condition

This DUT should consider one position which is bottom of laptop touching with phantom 0 mm air gap and the screen portion of the device shall be an open position at a 90° angle.



6.2 Tablet Exposure Condition

This DUT was tested in two different positions. They are back of keyboard and bottom edge in these positions, the surface of DUT is touching with phantom 0mm.





Fig Illustration for Lap-touching Position

7 MEASUREMENT PROCEDURE

7.1 Measurement Process Diagram



7.2 SAR Scan General Requirement

Probe boundary effect error compensation is required for measurements with the probe tip closer than half a probe tip diameter to the phantom surface. Both the probe tip diameter and sensor offset distance must satisfy measurement protocols; to ensure probe boundary effect errors are minimized and the higher fields closest to the phantom surface can be correctly measured and extrapolated to the phantom surface for computing 1 g SAR. Tolerances of the post-processing algorithms must be verified by the test laboratory for the scan resolutions used in the SAR measurements, according to the reference distribution functions specified in IEEE Std 1528-2013.

			≤3GHz	>3GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			5±1 mm	½·δ·ln(2)±0.5 mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location			30°±1°	20°±1°
Maximum area scan spatial resolution: Δx Area , Δy Area			≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3–4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: Δx Zoom , Δy Zoom			≤ 2 GHz: ≤ 8 mm 2 –3 GHz: ≤ 5 mm*	3–4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: Δz Zoom (n)		≤ 5 mm	3–4 GHz: ≤ 4 mm
				4–5 GHz: ≤ 3 mm
				5–6 GHz: ≤ 2 mm
	graded grid	Δz Zoom (1): between 1st two points closest to phantom surface	≤ 4 mm	3–4 GHz: ≤ 3 mm
				4–5 GHz: ≤ 2.5 mm
		Δz Zoom (n>1): between subsequent points	≤ 1.5·Δz Zoom (n-1)	
Minimum zoom scan volume	x, y, z		≥30 mm	3–4 GHz: ≥ 28 mm
				4–5 GHz: ≥ 25 mm
				5–6 GHz: ≥ 22 mm

Note:

1. δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.
2. * When zoom scan is required and the reported SAR from the area scan based 1 g SAR estimation procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.

7.3 Measurement Procedure

The following steps are used for each test position

- a. Establish a call with the maximum output power with a base station simulator. The connection between the mobile and the base station simulator is established via air interface
- b. Measurement of the local E-field value at a fixed location. This value serves as a reference value for calculating a possible power drift.
- c. Measurement of the SAR distribution with a grid of 8 to 16mm * 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme.
- d. Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or 8 * 5 or 8*4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

7.4 Area & Zoom Scan Procedure

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. Area scan and zoom scan resolution setting follows KDB 865664 D01v01r04 quoted below.

When the 1 g SAR of the highest peak is within 2 dB of the SAR limit, additional zoom scans are required for other peaks within 2 dB of the highest peak that have not been included in any zoom scan to ensure there is no increase in SAR.

8 CONDUCTED RF OUTPUT POWER

8.1 WIFI

8.1.1 2.4G WIFI (Main Antenna)(Laptop)

Band (GHz)	Mode	Channel	Freq. (MHz)	Conducted Power (dBm)	Tune-up Limit (dBm)	SAR Test Require.
2.4 (2.4~2.4835)	802.11b	1	2412	14.76	15.00	Yes
		6	2437	14.80	15.00	Yes
		11	2462	14.62	15.00	Yes
		12	2467	14.66	15.00	No
		13	2472	14.71	15.00	No
	802.11g	1	2412	14.62	15.00	No
		6	2437	14.69	15.00	No
		11	2462	14.94	15.00	No
		12	2467	14.37	15.00	No
		13	2472	11.43	12.50	No
	802.11n(HT20)	1	2412	14.51	15.00	No
		6	2437	14.60	15.00	No
		11	2462	14.84	15.00	No
		12	2467	13.73	15.00	No
		13	2472	9.44	10.00	No
	802.11n(HT40)	3	2422	14.48	15.00	No
		6	2437	14.52	15.00	No
		9	2452	14.29	15.00	No
		10	2457	11.77	13.50	No
		11	2462	9.41	10.00	No
	VHT(20 MHz)	1	2412	14.65	15.00	No
		6	2437	14.72	15.00	No
		11	2462	14.94	15.00	No
		12	2467	13.86	15.00	No
		13	2472	9.49	10.00	No
	VHT(40 MHz)	3	2422	14.58	15.00	No
		6	2437	14.57	15.00	No
		9	2452	14.34	15.00	No
		10	2457	11.91	13.50	No
		11	2462	9.45	10.00	No
	802.11ax(HE20)	1	2412	14.52	15.00	No
		6	2437	14.53	15.00	No
		11	2462	14.79	15.00	No

		12	2467	13.74	15.00	No
		13	2472	9.92	10.00	No
	802.11ax(HE40)	3	2422	14.79	15.00	No
		6	2437	14.82	15.00	No
		9	2452	14.64	15.00	No
		10	2457	12.06	13.00	No
		11	2462	9.66	10.50	No

Note: According KDB 248227 D01 SAR is not required for the following 2.4 GHz OFDM conditions. When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.

Adjusted SAR = Report SAR * (max power (OFDM)/ max power (DSSS)) = 1.025 * (31.62mW/31.62mW) = 1.025 W/Kg, so the 2.4G OFDM SAR test is not required.

8.1.2 2.4G WIFI (Aux. Antenna)(Laptop)

Band (GHz)	Mode	Channel	Freq. (MHz)	Conducted Power (dBm)	Tune-up Limit (dBm)	SAR Test Require.
2.4 (2.4~2.4835)	802.11b	1	2412	14.75	15.00	Yes
		6	2437	14.67	15.00	Yes
		11	2462	14.91	15.00	Yes
		12	2467	14.61	15.00	No
		13	2472	14.60	15.00	No
	802.11g	1	2412	14.78	15.00	No
		6	2437	14.87	15.00	No
		11	2462	14.79	15.00	No
		12	2467	14.75	15.00	No
		13	2472	12.13	12.50	No
	802.11n(HT20)	1	2412	14.33	15.00	No
		6	2437	14.62	15.00	No
		11	2462	14.39	15.00	No
		12	2467	14.18	15.00	No
		13	2472	9.48	10.00	No
	802.11n(HT40)	3	2422	14.52	15.00	No
		6	2437	14.56	15.00	No
		9	2452	14.44	15.00	No
		10	2457	13.02	13.50	No
		11	2462	10.21	11.00	No
	VHT(20 MHz)	1	2412	14.49	15.00	No
		6	2437	14.65	15.00	No
		11	2462	14.49	15.00	No
		12	2467	14.33	15.00	No
		13	2472	9.62	10.00	No
	VHT(40 MHz)	3	2422	14.66	15.00	No
		6	2437	14.65	15.00	No
		9	2452	14.57	15.00	No
		10	2457	13.11	13.50	No
		11	2462	10.37	11.00	No
	802.11ax(HE20)	1	2412	14.62	15.00	No
		6	2437	14.73	15.00	No
		11	2462	14.56	15.00	No
		12	2467	14.53	15.00	No
		13	2472	10.25	11.00	No
	802.11ax(HE40)	3	2422	14.98	15.00	No

		6	2437	14.45	15.00	No
		9	2452	14.46	15.00	No
		10	2457	12.84	13.50	No
		11	2462	10.80	11.50	No

Note: According KDB 248227 D01 SAR is not required for the following 2.4 GHz OFDM conditions. When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.

Adjusted SAR = Report SAR * (max power (OFDM)/ max power (DSSS)) = $1.025 * (31.62\text{mW}/31.62\text{mW}) = 1.025$ W/Kg, so the 2.4G OFDM SAR test is not required.

8.1.3 5G WIFI (Main Antenna)(Laptop)

Band (GHz)	Mode	Channel	Freq. (MHz)	Conducted Power (dBm)	Tune-up Power Limit (dBm)	SAR Test Require.
5.2 (5.15~5.25)	802.11a	36	5180	11.20	12.50	No
		40	5200	11.12	12.50	No
		48	5240	10.92	12.50	No
	802.11n(HT20)	36	5180	11.05	12.50	No
		40	5200	10.96	12.50	No
		48	5240	11.25	12.50	No
	802.11n(HT40)	38	5190	12.18	12.50	No
		46	5230	12.45	12.50	No
	802.11ac(VHT20)	36	5180	10.86	12.50	No
		40	5200	10.98	12.50	No
		48	5240	10.94	12.50	No
	802.11ac(VHT40)	38	5190	12.23	12.50	No
		46	5230	12.30	12.50	No
	802.11ac(VHT80)	42	5210	12.16	12.50	No
	802.11ac(VHT160)	50	5250	12.34	12.50	No
	802.11ax(HE20)	36	5180	11.10	12.50	No
		40	5200	11.29	12.50	No
		48	5240	11.37	12.50	No
5.3 (5.25~5.35)	802.11a	52	5260	12.42	12.50	No
		60	5300	12.39	12.50	No
		64	5320	12.47	12.50	No
	802.11n(HT20)	52	5260	12.44	12.50	No
		60	5300	12.31	12.50	No
		64	5320	12.46	12.50	No
	802.11n(HT40)	54	5270	12.13	12.50	No
		62	5310	12.40	12.50	No
	802.11ac(VHT20)	52	5260	12.32	12.50	No
		60	5300	11.97	12.50	No
		64	5320	12.17	12.50	No
	802.11ac(VHT40)	54	5270	12.14	12.50	No
		62	5310	12.47	12.50	No
	802.11ac(VHT80)	58	5290	12.19	12.50	Yes
	802.11ax(HE20)	52	5260	12.43	12.50	No
		60	5300	12.16	12.50	No
		64	5320	12.25	12.50	No

	802.11ax(HE40)	54	5270	12.32	12.50	No
		62	5310	11.86	12.50	No
	802.11ax(HE80)	58	5290	12.43	12.50	No
5.6 (5.47~5.725)	802.11a	100	5500	12.74	13.00	No
		116	5580	12.56	13.00	No
		140	5700	12.62	13.00	No
		144	5720	12.66	13.00	No
	802.11n(HT20)	100	5500	12.69	13.00	No
		116	5580	12.41	13.00	No
		140	5700	12.64	13.00	No
		144	5720	12.57	13.00	No
	802.11n(HT40)	102	5510	12.83	13.00	No
		110	5550	12.86	13.00	No
		134	5670	12.97	13.00	No
		142	5710	12.95	13.00	No
	802.11ac(VHT20)	100	5500	12.94	13.00	No
		116	5580	12.72	13.00	No
		140	5700	12.74	13.00	No
		144	5720	12.73	13.00	No
	802.11ac(VHT40)	102	5510	12.79	13.00	No
		110	5550	12.86	13.00	No
		134	5670	12.96	13.00	No
		142	5710	12.87	13.00	No
	802.11ac(VHT80)	106	5530	12.77	13.00	No
		122	5610	12.56	13.00	No
		138	5690	12.86	13.00	No
	802.11ac(VHT160)	144	5570	12.76	13.00	Yes
	802.11ax(HE20)	100	5500	12.47	13.00	No
		116	5580	12.77	13.00	No
		140	5700	12.97	13.00	No
		144	5720	12.87	13.00	No
	802.11ax(HE40)	102	5510	12.42	13.00	No
		110	5550	12.65	13.00	No
		134	5670	12.62	13.00	No
		142	5710	12.55	13.00	No
	802.11ax(HE80)	106	5530	12.94	13.00	No
		122	5610	12.92	13.00	No
		138	5690	12.60	13.00	No
	802.11ac(HE160)	144	5570	12.97	13.00	No
5.8 (5.725~5.85)	802.11a	149	5745	13.63	14.00	No
		157	5785	13.72	14.00	No
		165	5825	13.62	14.00	No
	802.11n(HT20)	149	5745	13.55	14.00	No

		157	5785	13.60	14.00	No
		165	5825	13.70	14.00	No
	802.11n(HT40)	151	5755	13.54	14.00	No
		159	5795	13.70	14.00	No
	802.11ac(VHT20)	149	5745	13.74	14.00	No
		157	5785	13.79	14.00	No
		165	5825	13.77	14.00	No
	802.11ac(VHT40)	151	5755	13.57	14.00	No
		159	5795	13.84	14.00	No
	802.11ac(VHT80)	155	5775	13.89	14.00	Yes
	802.11ax(HE20)	149	5745	13.84	14.00	No
		157	5785	13.91	14.00	No
		165	5825	13.93	14.00	No
	802.11ax(HE40)	151	5755	13.70	14.00	No
		159	5795	13.63	14.00	No
	802.11ax(HE80)	155	5775	13.66	14.00	No

Note: When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition); otherwise, each band is tested independently for SAR.

8.1.4 5G WIFI (Aux. Antenna)(Laptop)

Band (GHz)	Mode	Channel	Freq. (MHz)	Conducted Power (dBm)	Tune-up Power Limit (dBm)	SAR Test Require.
5.2 (5.15~5.25)	802.11a	36	5180	11.24	12.50	No
		40	5200	11.27	12.50	No
		48	5240	10.98	12.50	No
	802.11n(HT20)	36	5180	10.81	12.50	No
		40	5200	11.26	12.50	No
		48	5240	11.32	12.50	No
	802.11n(HT40)	38	5190	12.46	12.50	No
		46	5230	12.31	12.50	No
	802.11ac(VHT20)	36	5180	10.83	12.50	No
		40	5200	11.19	12.50	No
		48	5240	11.26	12.50	No
	802.11ac(VHT40)	38	5190	12.31	12.50	No
		46	5230	11.99	12.50	No
	802.11ac(VHT80)	42	5210	12.07	12.50	No
	802.11ac(VHT160)	50	5250	12.09	12.50	No
	802.11ax(HE20)	36	5180	11.21	12.50	No
		40	5200	11.31	12.50	No
		48	5240	11.45	12.50	No
	802.11ax(HE40)	38	5190	12.30	12.50	No
		46	5230	11.76	12.50	No
	802.11ax(HE80)	42	5210	11.99	12.50	No
	802.11ax(HE160)	50	5250	12.42	12.50	No
5.3 (5.25~5.35)	802.11a	52	5260	12.31	12.50	No
		60	5300	12.30	12.50	No
		64	5320	12.39	12.50	No
	802.11n(HT20)	52	5260	12.36	12.50	No
		60	5300	12.23	12.50	No
		64	5320	12.22	12.50	No
	802.11n(HT40)	54	5270	12.32	12.50	No
		62	5310	12.02	12.50	No
	802.11ac(VHT20)	52	5260	12.32	12.50	No
		60	5300	12.13	12.50	No
		64	5320	12.34	12.50	No
	802.11ac(VHT40)	54	5270	12.43	12.50	No
		62	5310	12.37	12.50	No
	802.11ac(VHT80)	58	5290	11.77	12.50	Yes
	802.11ax(HE20)	52	5260	12.03	12.50	No
		60	5300	11.76	12.50	No
		64	5320	11.93	12.50	No

	802.11ax(HE40)	54	5270	12.32	12.50	No
		62	5310	12.16	12.50	No
	802.11ax(HE80)	58	5290	12.07	12.50	No
5.6 (5.47~5.725)	802.11a	100	5500	12.43	13.00	No
		116	5580	12.89	13.00	No
		140	5700	12.43	13.00	No
		144	5720	12.93	13.00	No
	802.11n(HT20)	100	5500	12.97	13.00	No
		116	5580	12.81	13.00	No
		140	5700	12.46	13.00	No
		144	5720	12.87	13.00	No
	802.11n(HT40)	102	5510	12.70	13.00	No
		110	5550	12.87	13.00	No
		134	5670	12.96	13.00	No
		142	5710	12.91	13.00	No
	802.11ac(VHT20)	100	5500	12.40	13.00	No
		116	5580	12.73	13.00	No
		140	5700	12.80	13.00	No
		144	5720	12.53	13.00	No
	802.11ac(VHT40)	102	5510	12.54	13.00	No
		110	5550	12.47	13.00	No
		134	5670	12.70	13.00	No
		142	5710	12.96	13.00	No
	802.11ac(VHT80)	106	5530	12.72	13.00	No
		122	5610	12.63	13.00	No
		138	5690	12.67	13.00	No
	802.11ac(VHT160)	144	5570	12.51	13.00	Yes
	802.11ax(HE20)	100	5500	12.57	13.00	No
		116	5580	12.94	13.00	No
		140	5700	12.49	13.00	No
		144	5720	12.93	13.00	No
	802.11ax(HE40)	102	5510	12.89	13.00	No
		110	5550	12.57	13.00	No
		134	5670	12.50	13.00	No
		142	5710	12.71	13.00	No
	802.11ax(HE80)	106	5530	12.42	13.00	No
		122	5610	12.96	13.00	No
		138	5690	12.52	13.00	No
	802.11ac(HE160)	144	5570	12.73	13.00	No
5.8 (5.725~5.85)	802.11a	149	5745	13.96	14.00	No
		157	5785	13.44	14.00	No
		165	5825	13.53	14.00	No
	802.11n(HT20)	149	5745	13.92	14.00	No

		157	5785	13.90	14.00	No
		165	5825	12.84	14.00	No
	802.11n(HT40)	151	5755	13.77	14.00	No
		159	5795	13.52	14.00	No
	802.11ac(VHT20)	149	5745	13.91	14.00	No
		157	5785	13.83	14.00	No
		165	5825	13.47	14.00	No
	802.11ac(VHT40)	151	5755	13.63	14.00	No
		159	5795	13.78	14.00	No
	802.11ac(VHT80)	155	5775	13.71	14.00	Yes
	802.11ax(HE20)	149	5745	13.93	14.00	No
		157	5785	13.91	14.00	No
		165	5825	13.54	14.00	No
	802.11ax(HE40)	151	5755	13.54	14.00	No
		159	5795	13.55	14.00	No
	802.11ax(HE80)	155	5775	13.70	14.00	No

Note: When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition); otherwise, each band is tested independently for SAR.

8.1.5 2.4G WIFI (Main Antenna)(Tablet)

Band (GHz)	Mode	Channel	Freq. (MHz)	Conducted Power (dBm)	Tune-up Limit (dBm)	SAR Test Require.
2.4 (2.4~2.4835)	802.11b	1	2412	14.76	15.00	Yes
		6	2437	14.80	15.00	Yes
		11	2462	14.62	15.00	Yes
		12	2467	14.66	15.00	No
		13	2472	14.71	15.00	No
	802.11g	1	2412	14.62	15.00	No
		6	2437	14.69	15.00	No
		11	2462	14.94	15.00	No
		12	2467	14.37	15.00	No
		13	2472	11.43	12.50	No
	802.11n(HT20)	1	2412	14.51	15.00	No
		6	2437	14.60	15.00	No
		11	2462	14.84	15.00	No
		12	2467	13.73	15.00	No
		13	2472	9.44	10.00	No
	802.11n(HT40)	3	2422	14.48	15.00	No
		6	2437	14.52	15.00	No
		9	2452	14.29	15.00	No
		10	2457	11.77	13.50	No
		11	2462	9.41	10.00	No
	VHT(20 MHz)	1	2412	14.65	15.00	No
		6	2437	14.72	15.00	No
		11	2462	14.94	15.00	No
		12	2467	13.86	15.00	No
		13	2472	9.49	10.00	No
	VHT(40 MHz)	3	2422	14.58	15.00	No
		6	2437	14.57	15.00	No
		9	2452	14.34	15.00	No
		10	2457	11.91	13.50	No
		11	2462	9.45	10.00	No
	802.11ax(HE20)	1	2412	14.52	15.00	No
		6	2437	14.53	15.00	No
		11	2462	14.79	15.00	No
		12	2467	13.74	15.00	No
		13	2472	9.92	10.00	No
	802.11ax(HE40)	3	2422	14.79	15.00	No

		6	2437	14.82	15.00	No
		9	2452	14.64	15.00	No
		10	2457	12.06	13.00	No
		11	2462	9.66	10.50	No

Note: According KDB 248227 D01 SAR is not required for the following 2.4 GHz OFDM conditions. When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.

Adjusted SAR = Report SAR * (max power (OFDM)/ max power (DSSS)) = 1.025 * (31.62mW/31.62mW) = 1.025 W/Kg, so the 2.4G OFDM SAR test is not required.

8.1.6 2.4G WIFI (Aux. Antenna)(Tablet)

Band (GHz)	Mode	Channel	Freq. (MHz)	Conducted Power (dBm)	Tune-up Limit (dBm)	SAR Test Require.
2.4 (2.4~2.4835)	802.11b	1	2412	14.75	15.00	Yes
		6	2437	14.67	15.00	Yes
		11	2462	14.91	15.00	Yes
		12	2467	14.61	15.00	No
		13	2472	14.60	15.00	No
	802.11g	1	2412	14.78	15.00	No
		6	2437	14.87	15.00	No
		11	2462	14.79	15.00	No
		12	2467	14.75	15.00	No
		13	2472	12.13	12.50	No
	802.11n(HT20)	1	2412	14.33	15.00	No
		6	2437	14.62	15.00	No
		11	2462	14.39	15.00	No
		12	2467	14.18	15.00	No
		13	2472	9.48	10.00	No
	802.11n(HT40)	3	2422	14.52	15.00	No
		6	2437	14.56	15.00	No
		9	2452	14.44	15.00	No
		10	2457	13.02	13.50	No
		11	2462	10.21	11.00	No
	VHT(20 MHz)	1	2412	14.49	15.00	No
		6	2437	14.65	15.00	No
		11	2462	14.49	15.00	No
		12	2467	14.33	15.00	No
		13	2472	9.62	10.00	No
	VHT(40 MHz)	3	2422	14.66	15.00	No
		6	2437	14.65	15.00	No
		9	2452	14.57	15.00	No
		10	2457	13.11	13.50	No
		11	2462	10.37	11.00	No
	802.11ax(HE20)	1	2412	14.62	15.00	No
		6	2437	14.73	15.00	No
		11	2462	14.56	15.00	No
		12	2467	14.53	15.00	No
		13	2472	10.25	11.00	No
	802.11ax(HE40)	3	2422	14.98	15.00	No

		6	2437	14.45	15.00	No
		9	2452	14.46	15.00	No
		10	2457	12.84	13.50	No
		11	2462	10.80	11.50	No

Note: According KDB 248227 D01 SAR is not required for the following 2.4 GHz OFDM conditions. When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg. Adjusted SAR = Report SAR * (max power (OFDM)/ max power (DSSS)) = 1.025 * (31.62mW/31.62mW) = 1.025 W/Kg, so the 2.4G OFDM SAR test is not required.

8.1.7 5G WIFI (Main Antenna)(Tablet)

Band (GHz)	Mode	Channel	Freq. (MHz)	Conducted Power (dBm)	Tune-up Power Limit (dBm)	SAR Test Require.
5.2 (5.15~5.25)	802.11a	36	5180	11.20	11.50	No
		40	5200	11.12	11.50	No
		48	5240	10.92	11.50	No
	802.11n(HT20)	36	5180	11.05	11.50	No
		40	5200	10.96	11.50	No
		48	5240	11.25	11.50	No
	802.11n(HT40)	38	5190	11.06	11.50	No
		46	5230	11.45	11.50	No
	802.11ac(VHT20)	36	5180	10.86	11.50	No
		40	5200	10.98	11.50	No
		48	5240	10.94	11.50	No
	802.11ac(VHT40)	38	5190	11.04	11.50	No
		46	5230	11.12	11.50	No
	802.11ac(VHT80)	42	5210	11.04	11.50	No
	802.11ac(VHT160)	50	5250	11.20	11.50	No
	802.11ax(HE20)	36	5180	11.10	11.50	No
		40	5200	11.29	11.50	No
		48	5240	11.37	11.50	No
5.3 (5.25~5.35)	802.11a	52	5260	11.27	11.50	No
		60	5300	11.21	11.50	No
		64	5320	11.28	11.50	No
	802.11n(HT20)	52	5260	11.39	11.50	No
		60	5300	11.12	11.50	No
		64	5320	11.42	11.50	No
	802.11n(HT40)	54	5270	11.10	11.50	No
		62	5310	11.21	11.50	No
	802.11ac(VHT20)	52	5260	11.15	11.50	No
		60	5300	10.79	11.50	No
		64	5320	11.00	11.50	No
	802.11ac(VHT40)	54	5270	10.96	11.50	No
		62	5310	11.43	11.50	No
	802.11ac(VHT80)	58	5290	11.01	11.50	Yes
	802.11ax(HE20)	52	5260	11.24	11.50	No
		60	5300	11.13	11.50	No
		64	5320	11.23	11.50	No

	802.11ax(HE40)	54	5270	11.21	11.50	No
		62	5310	10.72	11.50	No
	802.11ax(HE80)	58	5290	11.37	11.50	No
5.6 (5.47~5.725)	802.11a	100	5500	11.06	11.50	No
		116	5580	10.06	10.50	No
		140	5700	9.94	10.50	No
		144	5720	9.98	10.50	No
	802.11n(HT20)	100	5500	10.08	10.50	No
		116	5580	9.88	10.50	No
		140	5700	10.09	10.50	No
		144	5720	9.94	10.50	No
	802.11n(HT40)	102	5510	10.33	10.50	No
		110	5550	10.17	10.50	No
		134	5670	10.41	10.50	No
		142	5710	10.29	10.50	No
	802.11ac(VHT20)	100	5500	10.29	10.50	No
		116	5580	10.07	10.50	No
		140	5700	10.13	10.50	No
		144	5720	10.21	10.50	No
	802.11ac(VHT40)	102	5510	10.26	10.50	No
		110	5550	10.22	10.50	No
		134	5670	10.33	10.50	No
		142	5710	10.35	10.50	No
	802.11ac(VHT80)	106	5530	10.24	10.50	No
		122	5610	10.04	10.50	No
		138	5690	10.19	10.50	No
	802.11ac(VHT160)	144	5570	10.17	10.50	Yes
	802.11ax(HE20)	100	5500	9.80	10.50	No
		116	5580	10.23	10.50	No
		140	5700	10.32	10.50	No
		144	5720	10.24	10.50	No
	802.11ax(HE40)	102	5510	9.79	10.50	No
		110	5550	10.04	10.50	No
		134	5670	10.02	10.50	No
		142	5710	9.88	10.50	No
	802.11ax(HE80)	106	5530	10.30	10.50	No
		122	5610	10.33	10.50	No
		138	5690	9.98	10.50	No
	802.11ac(HE160)	144	5570	10.78	11.50	No
5.8 (5.725~5.85)	802.11a	149	5745	10.98	11.50	No
		157	5785	11.12	11.50	No
		165	5825	11.08	11.50	No
	802.11n(HT20)	149	5745	10.95	11.50	No

		157	5785	11.00	11.50	No
		165	5825	11.00	11.50	No
	802.11n(HT40)	151	5755	10.94	11.50	No
		159	5795	11.01	11.50	No
	802.11ac(VHT20)	149	5745	11.08	11.50	No
		157	5785	11.28	11.50	No
		165	5825	11.15	11.50	No
	802.11ac(VHT40)	151	5755	11.05	11.50	No
		159	5795	11.23	11.50	No
	802.11ac(VHT80)	155	5775	11.37	11.50	Yes
	802.11ax(HE20)	149	5745	11.33	11.50	No
		157	5785	11.37	11.50	No
		165	5825	11.25	11.50	No
	802.11ax(HE40)	151	5755	11.07	11.50	No
		159	5795	10.97	11.50	No
	802.11ax(HE80)	155	5775	11.14	11.50	No

Note: When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition); otherwise, each band is tested independently for SAR.

8.1.8 5G WIFI (Aux. Antenna)(Tablet)

Band (GHz)	Mode	Channel	Freq. (MHz)	Conducted Power (dBm)	Tune-up Power Limit (dBm)	SAR Test Require.
5.2 (5.15~5.25)	802.11a	36	5180	11.24	11.50	No
		40	5200	11.27	11.50	No
		48	5240	10.98	11.50	No
	802.11n(HT20)	36	5180	10.81	11.50	No
		40	5200	11.26	11.50	No
		48	5240	11.32	11.50	No
	802.11n(HT40)	38	5190	11.32	11.50	No
		46	5230	11.18	11.50	No
	802.11ac(VHT20)	36	5180	10.83	11.50	No
		40	5200	11.19	11.50	No
		48	5240	11.26	11.50	No
	802.11ac(VHT40)	38	5190	11.16	11.50	No
		46	5230	10.87	11.50	No
	802.11ac(VHT80)	42	5210	11.03	11.50	No
	802.11ac(VHT160)	50	5250	10.92	11.50	No
	802.11ax(HE20)	36	5180	11.21	11.50	No
		40	5200	11.31	11.50	No
		48	5240	11.45	11.50	No
	802.11ax(HE40)	38	5190	11.16	11.50	No
		46	5230	10.56	11.50	No
	802.11ax(HE80)	42	5210	10.94	11.50	No
	802.11ax(HE160)	50	5250	11.31	11.50	No
5.3 (5.25~5.35)	802.11a	52	5260	11.13	11.50	No
		60	5300	11.16	11.50	No
		64	5320	11.29	11.50	No
	802.11n(HT20)	52	5260	11.29	11.50	No
		60	5300	11.23	11.50	No
		64	5320	11.22	11.50	No
	802.11n(HT40)	54	5270	11.26	11.50	No
		62	5310	10.90	11.50	No
	802.11ac(VHT20)	52	5260	11.27	11.50	No
		60	5300	11.04	11.50	No
		64	5320	11.16	11.50	No
	802.11ac(VHT40)	54	5270	11.43	11.50	No
		62	5310	11.35	11.50	No
	802.11ac(VHT80)	58	5290	10.67	11.50	Yes
	802.11ax(HE20)	52	5260	10.92	11.50	No
		60	5300	10.58	11.50	No
		64	5320	10.87	11.50	No

	802.11ax(HE40)	54	5270	11.30	11.50	No
		62	5310	11.04	11.50	No
	802.11ax(HE80)	58	5290	11.04	11.50	No
5.6 (5.47~5.725)	802.11a	100	5500	9.77	10.50	No
		116	5580	10.38	10.50	No
		140	5700	9.76	10.50	No
		144	5720	10.36	10.50	No
	802.11n(HT20)	100	5500	10.27	10.50	No
		116	5580	10.23	10.50	No
		140	5700	9.94	10.50	No
		144	5720	10.27	10.50	No
	802.11n(HT40)	102	5510	10.02	10.50	No
		110	5550	10.24	10.50	No
		134	5670	10.34	10.50	No
		142	5710	10.35	10.50	No
	802.11ac(VHT20)	100	5500	9.78	10.50	No
		116	5580	10.09	10.50	No
		140	5700	10.19	10.50	No
		144	5720	9.91	10.50	No
	802.11ac(VHT40)	102	5510	9.95	10.50	No
		110	5550	9.91	10.50	No
		134	5670	10.01	10.50	No
		142	5710	10.40	10.50	No
	802.11ac(VHT80)	106	5530	10.13	10.50	No
		122	5610	9.98	10.50	No
		138	5690	10.11	10.50	No
	802.11ac(VHT160)	144	5570	9.99	10.50	Yes
	802.11ax(HE20)	100	5500	9.98	10.50	No
		116	5580	10.38	10.50	No
		140	5700	9.81	10.50	No
		144	5720	10.25	10.50	No
	802.11ax(HE40)	102	5510	10.21	10.50	No
		110	5550	10.03	10.50	No
		134	5670	9.97	10.50	No
		142	5710	10.12	10.50	No
	802.11ax(HE80)	106	5530	9.91	10.50	No
		122	5610	10.36	10.50	No
		138	5690	10.01	10.50	No
	802.11ac(HE160)	144	5570	11.09	11.50	No
5.8 (5.725~5.85)	802.11a	149	5745	11.43	11.50	No
		157	5785	11.41	11.50	No
		165	5825	10.88	11.50	No
	802.11n(HT20)	149	5745	11.41	11.50	No

		157	5785	11.32	11.50	No
		165	5825	11.28	11.50	No
	802.11n(HT40)	151	5755	11.14	11.50	No
		159	5795	10.93	11.50	No
	802.11ac(VHT20)	149	5745	11.25	11.50	No
		157	5785	11.24	11.50	No
		165	5825	10.82	11.50	No
	802.11ac(VHT40)	151	5755	10.93	11.50	No
		159	5795	11.23	11.50	No
	802.11ac(VHT80)	155	5775	11.10	11.50	Yes
	802.11ax(HE20)	149	5745	11.28	11.50	No
		157	5785	11.38	11.50	No
		165	5825	11.04	11.50	No
	802.11ax(HE40)	151	5755	11.04	11.50	No
		159	5795	11.00	11.50	No
	802.11ax(HE80)	155	5775	11.02	11.50	No

Note: When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition); otherwise, each band is tested independently for SAR.

8.2 Bluetooth

8.2.1 Bluetooth (Aux. Antenna)(Laptop)

Mode	GFSK			$\pi/4$ -DQPSK		
Channel	0	39	78	0	39	78
Frequency (MHz)	2402	2441	2480	2402	2441	2480
Conducted Power (dBm)	12.60	12.50	13.09	9.55	9.33	9.95
Tune-Up Limit (dBm)	13.50	13.50	13.50	10.50	10.50	10.50
SAR Test Require	YES	YES	YES	NO	NO	NO
Mode	8-DPSK			/		
Channel	0	39	78	/	/	/
Frequency (MHz)	2402	2441	2480	/	/	/
Conducted Power (dBm)	9.54	9.33	9.92	/	/	/
Tune-Up Limit (dBm)	10.50	10.50	10.50	/	/	/
SAR Test Require	NO	NO	NO	/	/	/
Mode	BLE-1Mbps			BLE-2Mbps		
Channel	0	19	39	0	19	39
Frequency (MHz)	2402	2440	2480	2402	2440	2480
Conducted Power (dBm)	12.63	12.60	12.29	12.85	12.76	12.38
Tune-Up Limit (dBm)	13.50	13.50	13.50	13.50	13.50	13.50
SAR Test Require	NO	NO	NO	NO	NO	NO
Note: Since Bluetooth BR mode is the maximum output power mode, SAR measurements were performed with test software using DH5 modulation, and SAR measurement is not required for the EDR and LE. When the secondary mode is $\leq \frac{1}{4}$ dB higher than the primary mode.						

8.2.2 Bluetooth (Aux. Antenna)(Tablet)


Mode	GFSK			$\pi/4$ -DQPSK		
Channel	0	39	78	0	39	78
Frequency (MHz)	2402	2441	2480	2402	2441	2480
Conducted Power (dBm)	10.25	10.29	10.20	9.55	9.33	9.95
Tune-Up Limit (dBm)	10.50	10.50	10.50	10.50	10.50	10.50
SAR Test Require	YES	YES	YES	NO	NO	NO
Mode	8-DPSK			/		
Channel	0	39	78	/	/	/
Frequency (MHz)	2402	2441	2480	/	/	/
Conducted Power (dBm)	9.54	9.33	9.92	/	/	/
Tune-Up Limit (dBm)	10.50	10.50	10.50	/	/	/
SAR Test Require	NO	NO	NO	/	/	/
Mode	BLE-1Mbps			BLE-2Mbps		
Channel	0	19	39	0	19	39
Frequency (MHz)	2402	2440	2480	2402	2440	2480
Conducted Power (dBm)	9.66	9.61	9.35	9.81	9.79	9.41
Tune-Up Limit (dBm)	10.50	10.50	10.50	10.50	10.50	10.50
SAR Test Require	NO	NO	NO	NO	NO	NO

Note: Since Bluetooth BR mode is the maximum output power mode, SAR measurements were performed with test software using DH5 modulation, and SAR measurement is not required for the EDR and LE. When the secondary mode is $\leq \frac{1}{4}$ dB higher than the primary mode.

Note: The Bluetooth duty cycle is 76.88 % as following figure, according to 2016 Oct. TCB workshop for Bluetooth SAR scaling need further consideration and the maximum duty cycle is 100%, therefore the actual duty cycle will be scaled up to 100% for Bluetooth reported SAR calculation.

Duty Cycle

Bluetooth-GFSK



8.3 Power reduction mechanism

This device operates at high power in Laptop mode and low power in Tablet modes. A gravity sensor is used to detect and trigger changes in operating modes.

The G-sensor can detect angle change and sent data to the Embedded Controller (EC) in the Tablet to determine the operating mode according to below table.

Operating Mode	Power Level
Laptop	High Power
Tablet	Low Power

WLAN Tune up Power Table				
WLAN Mode	Laptop Mode High Power		Tablet Mode Low Power	
	Ant. Main Max. Tuen-up power(dBm)	Ant. Aux. Max. Tuen-up power(dBm)	Ant. Main Max. Tuen-up power(dBm)	Ant. Aux. Max. Tuen-up power(dBm)
2.4G WLAN 802.11b	15.0	15.0	15.0	15.0
2.4G WLAN 802.11g	15.0	15.0	15.0	15.0
2.4G WLAN HT20	15.0	15.0	15.0	15.0
2.4G WLAN HT40	15.0	15.0	15.0	15.0
2.4G WLAN VHT20	15.0	15.0	15.0	15.0
2.4G WLAN VHT40	15.0	15.0	15.0	15.0
2.4G WLAN 802.11ax20	15.0	15.0	15.0	15.0
2.4G WLAN 802.11ax40	15.0	15.0	15.0	15.0
5.2G WLAN 802.11a	12.5	12.5	11.5	11.5
5.2 WLAN 802.11n20	12.5	12.5	11.5	11.5
5.2 WLAN 802.11n40	12.5	12.5	11.5	11.5
5.2 WLAN 802.11ac20	12.5	12.5	11.5	11.5
5.2 WLAN 802.11ac40	12.5	12.5	11.5	11.5
5.2 WLAN 802.11ac80	12.5	12.5	11.5	11.5
5.2 WLAN 802.11ac160	12.5	12.5	11.5	11.5
5.2 WLAN 802.11ax20	12.5	12.5	11.5	11.5
5.2 WLAN 802.11ax40	12.5	12.5	11.5	11.5
5.2 WLAN 802.11ax80	12.5	12.5	11.5	11.5
5.2 WLAN 802.11ax160	12.5	12.5	11.5	11.5
5.3 WLAN 802.11a	12.5	12.5	11.5	11.5
5.3 WLAN 802.11n20	12.5	12.5	11.5	11.5
5.3 WLAN 802.11n40	12.5	12.5	11.5	11.5
5.3 WLAN 802.11ac20	12.5	12.5	11.5	11.5

5.3 WLAN 802.11ac40	12.5	12.5	11.5	11.5
5.3 WLAN 802.11ac80	12.5	12.5	11.5	11.5
5.3 WLAN 802.11ax20	12.5	12.5	11.5	11.5
5.3 WLAN 802.11ax40	12.5	12.5	11.5	11.5
5.3 WLAN 802.11ax80	12.5	12.5	11.5	11.5
5.6 WLAN 802.11a	13.0	13.0	10.5	10.5
5.6 WLAN 802.11n20	13.0	13.0	10.5	10.5
5.6 WLAN 802.11n40	13.0	13.0	10.5	10.5
5.6 WLAN 802.11ac20	13.0	13.0	10.5	10.5
5.6 WLAN 802.11ac40	13.0	13.0	10.5	10.5
5.6 WLAN 802.11ac80	13.0	13.0	10.5	10.5
5.6 WLAN 802.11ac160	13.0	13.0	10.5	10.5
5.6 WLAN 802.11ax20	13.0	13.0	10.5	10.5
5.6 WLAN 802.11ax40	13.0	13.0	10.5	10.5
5.6 WLAN 802.11ax80	13.0	13.0	10.5	10.5
5.6 WLAN 802.11ax160	13.0	13.0	10.5	10.5
5.8 WLAN 802.11a	14.0	14.0	11.5	11.5
5.8 WLAN 802.11n20	14.0	14.0	11.5	11.5
5.8 WLAN 802.11n40	14.0	14.0	11.5	11.5
5.8 WLAN 802.11ac20	14.0	14.0	11.5	11.5
5.8 WLAN 802.11ac40	14.0	14.0	11.5	11.5
5.8 WLAN 802.11ac80	14.0	14.0	11.5	11.5
5.8 WLAN 802.11ax20	14.0	14.0	11.5	11.5
5.8 WLAN 802.11ax40	14.0	14.0	11.5	11.5
5.8 WLAN 802.11ax80	14.0	14.0	11.5	11.5
Bluetooth	/	13.5	/	10.5

Note 1: The operating mode is sent by EC to the Wi-Fi Driver, which reads the applicable power levels from the power table in the BIOS ROM for the WLAN module to establish transmit power.

Note 2: According to 2019 and 2021 TCB Workshop measurement guidance, the Tune-up information please refer to section 8.1 and conducted power measurement results please refer to Appendix G "Gravity-Sensor Conducted Power Test Results".


Note 3: Selected the mode that require SAR testing (Bluetooth DH5) for power measurement, and the measurement channel was select channel 39.

Note 4: Selected the mode that require SAR testing (802.11ac 80) for power measurement, and the measurement channel was select channel 106.

9 TEST EXCLUSION CONSIDERATION


9.1 Laptop Mode antenna location sketch

NB Mode *Side View*




9.2 Tablet Mode antenna location sketch

Tablet Mode *Side View*



Tablet Mode *Front View*



9.3 SAR Test Consideration Table

According with FCC KDB 447498 D04, Appendix B, The SAR-based exemption formula applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold Pth (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). The following table shows the power threshold from 5mm to 50mm.

Power Thresholds (mW)					
Frequency (MHz)	At separation distance of ≤ 5 mm	At separation distance of 10 mm	At separation distance of 15 mm	At separation distance of 20 mm	At separation distance of 25 mm
300	39 mW	65 mW	88 mW	110 mW	129 mW
450	22 mW	44 mW	67 mW	89 mW	112 mW
835	9 mW	25 mW	44 mW	66 mW	90 mW
1900	3 mW	12 mW	26 mW	44 mW	66 mW
2450	3 mW	10 mW	22 mW	38 mW	59 mW
3600	2 mW	8 mW	18 mW	32 mW	49 mW
5800	1 mW	6 mW	14 mW	25 mW	40 mW
Frequency (MHz)	At separation distance of 30 mm	At separation distance of 35 mm	At separation distance of 40 mm	At separation distance of 45 mm	At separation distance of 50 mm
300	148 mW	166 mW	184 mW	201 mW	217 mW
450	135 mW	158 mW	180 mW	203 mW	226 mW
835	116 mW	145 mW	175 mW	207 mW	240 mW
1900	92 mW	122 mW	157 mW	195 mW	236 mW
2450	83 mW	111 mW	143 mW	179 mW	219 mW
3600	71 mW	96 mW	125 mW	158 mW	195 mW
5800	58 mW	80 mW	106 mW	136 mW	169 mW

9.3.1 Laptop mode SAR Test Consideration

Main Antenna

Test Position Configurations	Mode	WLAN 2.4GHz	WLAN 5.2&5.3GHz	WLAN 5.6GHz	WLAN 5.8GHz
Calculated Frequency(MHz)		2462	5320	5710	5825
Bottom Side of Laptop	Distance to User (mm)	4.48	4.48	4.48	4.48
	Max. Peak Power (dBm)	15.00	12.50	13.00	14.00
	Max. Peak Power (mW)	31.62	17.78	19.95	25.12
	Exclusion Threshold (mW)	2.22	1.17	1.11	1.09
	SAR Test Required	Yes	Yes	Yes	Yes
Back Side (with keyboard)	Distance to User (mm)	4.3	4.3	4.3	4.3
	Max. Peak Power (dBm)	15.00	11.50	10.50	11.50
	Max. Peak Power (mW)	31.62	14.13	11.22	14.13
	Exclusion Threshold (mW)	2.05	1.08	1.02	1.00
	SAR Test Required	Yes	Yes	Yes	Yes
Left Edge	Distance to User (mm)	252.7	252.7	252.7	252.7
	Max. Peak Power (dBm)	15.00	11.50	10.50	11.50
	Max. Peak Power (mW)	31.62	14.13	11.22	14.13
	Exclusion Threshold (mW)	4775.74	4966.33	4984.21	4989.26
	SAR Test Required	No	No	No	No
Right Edge	Distance to User (mm)	49.7	49.7	49.7	49.7
	Max. Peak Power (dBm)	15.00	11.50	10.50	11.50
	Max. Peak Power (mW)	31.62	14.13	11.22	14.13
	Exclusion Threshold (mW)	216.22	171.29	167.66	166.66
	SAR Test Required	No	No	No	No
Top Edge	Distance to User (mm)	250	250	250	250
	Max. Peak Power (dBm)	15.00	11.50	10.50	11.50
	Max. Peak Power (mW)	31.62	14.13	11.22	14.13
	Exclusion Threshold (mW)	4679.10	4857.09	4873.77	4878.48
	SAR Test Required	No	No	No	No
Bottom Edge	Distance to User (mm)	0.7	0.7	0.7	0.7
	Max. Peak Power (dBm)	15.00	11.50	10.50	11.50
	Max. Peak Power (mW)	31.62	14.13	11.22	14.13
	Exclusion Threshold (mW)	0.06	0.03	0.02	0.02
	SAR Test Required	Yes	Yes	Yes	Yes

Aux. Antenna

Test Position Configurations	Mode	Bluetooth	WLAN 2.4GHz	WLAN 5.2&5.3GHz	WLAN 5.6GHz	WLAN 5.8GHz
Calculated Frequency(MHz)		2480	2462	5320	5710	5825
Bottom Side of Laptop	Distance to User (mm)	4.48	4.48	4.48	4.48	4.48
	Max. Peak Power (dBm)	13.50	15.00	12.50	13.00	14.00
	Max. Peak Power (mW)	22.39	31.62	17.78	19.95	25.12
	Exclusion Threshold (mW)	2.20	2.22	1.17	1.11	1.09
	SAR Test Required	Yes	Yes	Yes	Yes	Yes
Back Side (with keyboard)	Distance to User (mm)	4.3	4.3	4.3	4.3	4.3
	Max. Peak Power (dBm)	10.50	15.00	11.50	10.50	11.50
	Max. Peak Power (mW)	11.22	31.62	14.13	11.22	14.13
	Exclusion Threshold (mW)	2.04	2.05	1.08	1.02	1.00
	SAR Test Required	Yes	Yes	Yes	Yes	Yes
Left Edge	Distance to User (mm)	49.7	49.7	49.7	49.7	49.7
	Max. Peak Power (dBm)	10.50	15.00	11.50	10.50	11.50
	Max. Peak Power (mW)	11.22	31.62	14.13	11.22	14.13
	Exclusion Threshold (mW)	215.75	216.22	171.29	167.66	166.66
	SAR Test Required	No	No	No	No	No
Right Edge	Distance to User (mm)	252.7	252.7	252.7	252.7	252.7
	Max. Peak Power (dBm)	10.50	15.00	11.50	10.50	11.50
	Max. Peak Power (mW)	11.22	31.62	14.13	11.22	14.13
	Exclusion Threshold (mW)	4777.51	4775.74	4966.33	4984.21	4989.26
	SAR Test Required	No	No	No	No	No
Top Edge	Distance to User (mm)	250	250	250	250	250
	Max. Peak Power (dBm)	10.50	15.00	11.50	10.50	11.50
	Max. Peak Power (mW)	11.22	31.62	14.13	11.22	14.13
	Exclusion Threshold (mW)	4680.75	4679.10	4857.09	4873.77	4878.48
	SAR Test Required	No	No	No	No	No
Bottom Edge	Distance to User (mm)	0.7	0.7	0.7	0.7	0.7
	Max. Peak Power (dBm)	10.50	15.00	11.50	10.50	11.50
	Max. Peak Power (mW)	11.22	31.62	14.13	11.22	14.13
	Exclusion Threshold (mW)	0.06	0.06	0.03	0.02	0.02
	SAR Test Required	Yes	Yes	Yes	Yes	Yes

Note:

- Maximum power is the source-based time-average power and represents the maximum RF output power including tune-up tolerance among production units
- Per KDB 447498 D04, for larger devices, the test separation distance of adjacent edge configuration is determined by the closest separation between the antenna and the user.
- Per KDB 447498 D04, standalone SAR test exclusion threshold is applied; If the distance of the antenna to the user is <

5mm, 5mm is used to determine SAR exclusion threshold

4. Per KDB 447498 D04, for separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive), the threshold Pth (mW) is given by Following:

$$P_{th}(mW) = \begin{cases} ERP_{20cm}(d/20cm)^x & d \leq 20cm \\ ERP_{20cm} & 20cm < d \leq 40cm \end{cases}$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20cm}\sqrt{f}} \right)$$

- f(GHz) is the RF channel transmit frequency in GHz
- d is the separation distance (cm), The result is rounded to one decimal place for comparison
- ERP_{20cm} are determined by:

$$ERP_{20cm}(mW) = f(x) = \begin{cases} 2040f & 0.3GHz \leq f < 1.5GHz \\ 3060 & 1.5GHz \leq f \leq 6GHz \end{cases}$$

- Per KDB 248227 D01, choose the highest output power channel to test SAR and determine further SAR exclusion.8. For each frequency band, testing at higher data rates and higher order modulations is not required when the maximum average output power for each of these configurations is less than 1/4dB higher than those measured at the lowest data rate
- Per KDB 248227 D01 SAR is not required for the following 2.4 GHz OFDM conditions.
 - When KDB Publication 447498 D04 SAR test exclusion applies to the OFDM configuration.
 - When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.
- Per KDB 248227 D01 SAR is not required for the following U-NII-1 and U-NII-2A bands conditions.
 - When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition); otherwise, each band is tested independently for SAR.
 - When different maximum output power is specified for the bands, begin SAR measurement in the band with higher specified maximum output power. The highest reported SAR for the tested configuration is adjusted by the ratio of lower to higher specified maximum output power for the two bands. When the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for the band with lower maximum output power in that test configuration; otherwise, each band is tested independently for SAR.

10 TEST RESULT

10.1 Bluetooth

Mode	Antenna	Test State	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	Duty cycle	Duty Factor	1g Scaled SAR (W/kg)	Meas. No.
Body															
DH5	Aux.	Laptop	Bottom Side	0	78	2480	0.18	0.250	13.09	13.50	1.099	76.88	1.301	0.357	/
				0	0	2402	-0.01	0.260	12.60	13.50	1.230	76.88	1.301	0.416	/
				0	39	2441	0.03	0.256	12.50	13.50	1.259	76.88	1.301	0.419	1#
		Tablet	Back of keyboard	0	39	2441	0.00	0.185	10.29	10.50	1.050	76.88	1.301	0.253	/
			Bottom Edge	0	39	2441	0.09	0.285	10.29	10.50	1.050	76.88	1.301	0.389	2#
				0	0	2402	-0.02	0.269	10.25	10.50	1.059	76.88	1.301	0.371	/
				0	78	2480	0.03	0.256	10.20	10.50	1.072	76.88	1.301	0.357	/
				Note: Refer to ANNEX C for the detailed test data for each test configuration.											

10.2 WIFI 2.4GHz

Mode	Antenna	Test State	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	Duty cycle	Duty Factor	1g Scaled SAR (W/kg)	Meas. No.
Body															
802.11b	Main	Laptop	Bottom Side	0	6	2437	0.11	0.233	14.80	15.00	1.047	99.40	1.006	0.245	3#
				0	1	2412	-0.10	0.226	14.76	15.00	1.057	99.40	1.006	0.240	/
				0	11	2462	-0.09	0.220	14.62	15.00	1.091	99.40	1.006	0.242	/
	Aux.	Laptop	Bottom Side	0	11	2462	0.11	0.465	14.91	15.00	1.021	99.40	1.006	0.478	4#
				0	1	2412	0.02	0.420	14.75	15.00	1.059	99.40	1.006	0.448	/
				0	6	2437	0.05	0.419	14.67	15.00	1.079	99.40	1.006	0.455	/
	Main	Tablet	Back of keyboard	0	6	2437	-0.08	0.428	14.80	15.00	1.047	99.40	1.006	0.451	/
			Bottom Edge	0	6	2437	0.08	0.755	14.80	15.00	1.047	99.40	1.006	0.795	5#
				0	1	2412	-0.13	0.730	14.76	15.00	1.057	99.40	1.006	0.776	/
				0	11	2462	0.08	0.718	14.62	15.00	1.091	99.40	1.006	0.788	/
	Aux.	Tablet	Back of keyboard	0	11	2462	0.12	0.561	14.64	15.00	1.086	99.40	1.006	0.613	/
			Bottom Edge	0	11	2462	0.18	0.938	14.64	15.00	1.086	99.40	1.006	1.025	6#
				0	1	2412	-0.10	0.788	14.46	15.00	1.132	99.40	1.006	0.898	/
				0	6	2437	0.11	0.877	14.43	15.00	1.140	99.40	1.006	1.006	/
Note: Refer to ANNEX C for the detailed test data for each test configuration.															

10.3WIFI 5GHz

Fre. Band	Mode	Antenna	Test State	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	Duty cycle	Duty Factor	1g Scaled SAR (W/kg)	Meas. No.
Body																
5.3G	802.11 ac80	Main	Laptop	Bottom Side	0	58	5290	0.16	1.000	12.19	12.50	1.074	90.20	1.109	1.191	7#
		Aux.	Laptop	Bottom Side	0	58	5290	0.13	0.883	11.77	12.50	1.183	90.20	1.109	1.158	8#
5.6G	802.11 ac160	Main	Laptop	Bottom Side	0	114	5570	-0.04	0.873	12.76	13.00	1.057	89.50	1.117	1.031	9#
		Aux.	Laptop	Bottom Side	0	114	5570	0.05	0.753	12.51	13.00	1.119	89.50	1.117	0.942	10#
5.8G	802.11 ac80	Main	Laptop	Bottom Side	0	155	5775	-0.12	0.923	13.89	14.00	1.026	90.20	1.109	1.050	11#
		Aux.	Laptop	Bottom Side	0	155	5775	-0.04	0.583	13.71	14.00	1.069	90.20	1.109	0.691	12#
5.3G	802.11 ac80	Main	Tablet	Back of keyboard	0	58	5290	0.14	0.244	11.01	11.50	1.119	90.20	1.109	0.303	/
				Bottom Edge	0	58	5290	-0.14	0.945	11.01	11.50	1.119	90.20	1.109	1.173	13#
		Aux.	Tablet	Back of keyboard	0	58	5290	0.02	0.301	10.67	11.50	1.211	90.20	1.109	0.404	/
				Bottom Edge	0	58	5290	-0.03	0.883	10.67	11.50	1.211	90.20	1.109	1.185	14#
5.6G	802.11 ac160	Main	Tablet	Back of eyboard	0	114	5570	0.15	0.105	10.17	10.50	1.079	89.50	1.117	0.127	/
				Bottom Edge	0	114	5570	0.16	0.938	10.17	10.50	1.079	89.50	1.117	1.131	15#
		Aux.	Tablet	Back of keyboard	0	114	5570	0.05	0.134	9.99	10.50	1.125	89.50	1.117	0.168	/
				Bottom Edge	0	114	5570	-0.19	0.800	9.99	10.50	1.125	89.50	1.117	1.005	16#
5.3G	802.11 ac80	Main	Tablet	Back of keyboard	0	155	5775	-0.03	0.196	11.37	11.50	1.030	90.20	1.109	0.224	/
				Bottom Edge	0	155	5775	-0.16	0.956	11.37	11.50	1.030	90.20	1.109	1.092	17#
		Aux.	Tablet	Back of keyboard	0	155	5775	0.19	0.151	11.10	11.50	1.096	90.20	1.109	0.184	/
				Bottom Edge	0	155	5775	-0.02	0.719	11.10	11.50	1.096	90.20	1.109	0.874	18#
Note: Refer to ANNEX C for the detailed test data for each test configuration.																

11 SAR Measurement Variability

According to KDB 865664 D01, SAR measurement variability was assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. Alternatively, if the highest measured SAR for both head and body tissue-equivalent media are ≤ 1.45 W/kg and the ratio of these highest SAR values, i.e., largest divided by smallest value, is ≤ 1.10 , the highest SAR configuration for either head or body tissue-equivalent medium may be used to perform the repeated measurement. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR repeated measurement procedure:

1. When the highest measured SAR is < 0.80 W/kg, repeated measurement is not required.
2. When the highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
3. If the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 , or when the original or repeated measurement is ≥ 1.45 W/kg, perform a second repeated measurement.
4. If the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 , and the original, first or second repeated measurement is ≥ 1.5 W/kg, perform a third repeated measurement.

Frequency Band (MHz)	Wireless Band	Antenna	RF Exposure Conditions	Test Position	Highest Measured SAR (W/kg)	Repeated SAR (Yes/No)	Highest Measured SAR (W/kg)	Largest to Smallest SAR Ratio
2462	802.11 b	Aux.	Body	Bottom Edge	0.938	Yes	0.899	1.04
2437	802.11 b	Aux.	Body	Bottom Edge	0.877	Yes	0.856	1.02
5290	802.11 b	Main	Body	Bottom Edge	1.000	Yes	0.942	1.06
5290	802.11 ac80	Aux.	Body	Bottom Side	0.883	Yes	0.845	1.04
5570	802.11 ac160	Main	Body	Bottom Side	0.873	Yes	0.847	1.03
5775	802.11 ac80	Main	Body	Bottom Side	0.923	Yes	0.883	1.05
5290	802.11 ac80	Main	Body	Bottom Side	0.945	Yes	0.917	1.03
5290	802.11 ac80	Aux.	Body	Bottom Side	0.883	Yes	0.876	1.01
5570	802.11 ac160	Main	Body	Bottom Edge	0.938	Yes	0.921	1.02
5570	802.11 ac160	Aux.	Body	Bottom Edge	0.800	Yes	0.754	1.06
5775	802.11 ac80	Main	Body	Bottom Edge	0.956	Yes	0.939	1.02

Note: The ratio of largest to smallest SAR for the original and first repeated measurements is < 1.20 , the second repeated measurement is not required.

12 SIMULTANEOUS TRANSMISSION

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna. When the sum of SAR 1g of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit (SAR 1g 1.6 W/kg), the simultaneous transmission SAR is not required. When the sum of SAR 1g is greater than the SAR limit (SAR 1g 1.6 W/kg), SAR test exclusion is determined by the SAR to Peak Location Ratio (SPLSR).

According KDB 447498 D04, simultaneous transmission:

- a) $SPLSR = (SAR1 + SAR2)^{1.5} / R_i$ (min. separation distance, mm), and the peak separation distance is determined from the square root of $[(x1-x2)^2 + (y1-y2)^2 + (z1-z2)^2]$, where (x1, y1, z1) and (x2, y2, z2) are the coordinates of the extrapolated peak SAR locations in the zoom scan.
SAR1 is the highest reported or estimated SAR for the first of a pair of simultaneous transmitting antennas, in a specific test operating mode and exposure condition.
SAR2 is the highest reported or estimated SAR for the second of a pair of simultaneous transmitting antennas, in a specific test operating mode and exposure condition as the first.
- b) If $SPLSR \leq 0.04$, simultaneously transmission SAR measurement is not necessary.
- c) Simultaneously transmission SAR measurement, and the reported multi-band SAR < 1.6W/kg.

12.1 Simultaneous Transmission Mode Considerations

NO.	Mode	Body
1	2.4 G WLAN (Main Antenna)	+ 2.4 G WLAN (Auxiliary Antenna)
2	2.4 G WLAN (Main Antenna)	+ Bluetooth (Auxiliary Antenna)
3	5 G WLAN (Main Antenna)	+ 5 G WLAN (Auxiliary Antenna)
4	5 G WLAN (Main Antenna)	+ Bluetooth (Auxiliary Antenna)
5	5 G WLAN (Auxiliary Antenna)	+ Bluetooth (Auxiliary Antenna)
6	5 G WLAN (Main Antenna)	+ 5 G WLAN (Auxiliary Antenna) + Bluetooth (Auxiliary Antenna)

Note:

1. The EUT supports the Auxiliary antenna with TX/RX diversity function for WLAN and Bluetooth, the Main antenna with TX/RX diversity function for WLAN.
2. WLAN 2.4GHz and Bluetooth will not be transmitting from the Auxiliary antenna at same time.

12.2 Sum SAR of Simultaneous Transmission

12.2.1 Highest Bluetooth and WLAN Sum Body SAR of Simultaneous Transmission


Laptop Mode						
Test Mode	Position	Mode	Max. 1g SAR	1g Sum SAR	SPLSR	SPLSR
			(W/kg)	(W/kg)	(Yes/No)	Num.
Body (Separation 0 mm)						
Laptop	Bottom Side	2.4 G WLAN (Main Antenna)	0.245	0.664	No	/
		Bluetooth (Auxiliary Antenna)	0.419			
		2.4 G WLAN (Main Antenna)	0.245	0.723	No	/
		2.4 G WLAN (Auxiliary Antenna)	0.478			
		5.3 G WLAN (Main Antenna)	1.191	1.610	Yes	1#
		Bluetooth (Auxiliary Antenna)	0.419			
		5.3 G WLAN (Auxiliary Antenna)	1.158	1.577	No	/
		Bluetooth (Auxiliary Antenna)	0.419			
		5.3 G WLAN (Main Antenna)	1.191	2.349	Yes	2#
		5.3 G WLAN (Auxiliary Antenna)	1.158			
		5.3 G WLAN (Main Antenna)	1.191	2.768	Yes	3#
		5.3 G WLAN (Auxiliary Antenna)	1.158			
		Bluetooth (Auxiliary Antenna)	0.419			
		5.6 G WLAN (Main Antenna)	1.031	1.450	No	/
		Bluetooth (Auxiliary Antenna)	0.419			
		5.6 G WLAN (Auxiliary Antenna)	0.942	1.361	No	/
		Bluetooth (Auxiliary Antenna)	0.419			
		5.6 G WLAN (Main Antenna)	1.031	1.973	Yes	4#
		5.6 G WLAN (Auxiliary Antenna)	0.942			
		5.6 G WLAN (Main Antenna)	1.031	2.392	Yes	5#
		5.6 G WLAN (Auxiliary Antenna)	0.942			
		Bluetooth (Auxiliary Antenna)	0.419			
		5.8 G WLAN (Main Antenna)	1.050	1.469	No	/
		Bluetooth (Auxiliary Antenna)	0.419			
		5.8 G WLAN (Auxiliary Antenna)	0.691	1.110	No	/
		Bluetooth (Auxiliary Antenna)	0.419			
		5.8 G WLAN (Main Antenna)	1.050	1.741	Yes	6#
		5.8 G WLAN (Auxiliary Antenna)	0.691			
		5.8 G WLAN (Main Antenna)	1.050	2.160	Yes	7#
		5.8 G WLAN (Auxiliary Antenna)	0.691			
		Bluetooth (Auxiliary Antenna)	0.419			

Table Mode						
Test Mode	Position	Mode	Max. 1g SAR	1g Sum SAR	SPLSR	SPLSR
			(W/kg)	(W/kg)	(Yes/No)	Num.
Body (Separation 0 mm)						
Table	Back of keyboard	2.4 G WLAN (Main Antenna)	0.451	0.704	No	/
		Bluetooth (Auxiliary Antenna)	0.253			
		2.4 G WLAN (Main Antenna)	0.451	1.064	No	/
		2.4 G WLAN (Auxiliary Antenna)	0.613			
		5.3 G WLAN (Main Antenna)	0.303	0.556	No	/
		Bluetooth (Auxiliary Antenna)	0.253			
		5.3 G WLAN (Auxiliary Antenna)	0.404	0.657	No	/
		Bluetooth (Auxiliary Antenna)	0.253			
		5.3 G WLAN (Main Antenna)	0.303	0.707	No	/
		5.3 G WLAN (Auxiliary Antenna)	0.404			
		5.3 G WLAN (Main Antenna)	0.303	0.960	No	/
		5.3 G WLAN (Auxiliary Antenna)	0.404			
		Bluetooth (Auxiliary Antenna)	0.253	0.380	No	/
		5.6 G WLAN (Main Antenna)	0.127			
		Bluetooth (Auxiliary Antenna)	0.253	0.421	No	/
		5.6 G WLAN (Auxiliary Antenna)	0.168			
		Bluetooth (Auxiliary Antenna)	0.253	0.295	No	/
		5.6 G WLAN (Main Antenna)	0.127			
		5.6 G WLAN (Auxiliary Antenna)	0.168	0.548	No	/
		5.6 G WLAN (Main Antenna)	0.127			
		5.6 G WLAN (Auxiliary Antenna)	0.168	0.477	No	/
		Bluetooth (Auxiliary Antenna)	0.253			
		5.8 G WLAN (Main Antenna)	0.224	0.437	No	/
		Bluetooth (Auxiliary Antenna)	0.253			
		5.8 G WLAN (Auxiliary Antenna)	0.184	0.408	No	/
		Bluetooth (Auxiliary Antenna)	0.253			
		5.8 G WLAN (Main Antenna)	0.224	0.661	No	/
		5.8 G WLAN (Auxiliary Antenna)	0.184			
		Bluetooth (Auxiliary Antenna)	0.253	1.820	Yes	8#
	Bottom Edge	2.4 G WLAN (Main Antenna)	0.795			
		Bluetooth (Auxiliary Antenna)	0.389			
		2.4 G WLAN (Main Antenna)	0.795			
		2.4 G WLAN (Auxiliary Antenna)	1.025			
		5.3 G WLAN (Main Antenna)	1.173	1.562	No	/


		Bluetooth (Auxiliary Antenna)	0.389			
		5.3 G WLAN (Auxiliary Antenna)	1.185	1.574	No	/
		Bluetooth (Auxiliary Antenna)	0.389			
		5.3 G WLAN (Main Antenna)	1.173	2.358	Yes	9#
		5.3 G WLAN (Auxiliary Antenna)	1.185			
		5.3 G WLAN (Main Antenna)	1.173	2.747	Yes	10#
		5.3 G WLAN (Auxiliary Antenna)	1.185			
		Bluetooth (Auxiliary Antenna)	0.389			
		5.6 G WLAN (Main Antenna)	1.131	1.520	No	/
		Bluetooth (Auxiliary Antenna)	0.389			
		5.6 G WLAN (Auxiliary Antenna)	1.005	1.394	No	/
		Bluetooth (Auxiliary Antenna)	0.389			
		5.6 G WLAN (Main Antenna)	1.131	2.136	Yes	11#
		5.6 G WLAN (Auxiliary Antenna)	1.005			
		5.6 G WLAN (Main Antenna)	1.131	2.525	Yes	12#
		5.6 G WLAN (Auxiliary Antenna)	1.005			
		Bluetooth (Auxiliary Antenna)	0.389			
		5.8 G WLAN (Main Antenna)	1.092	1.481	No	/
		Bluetooth (Auxiliary Antenna)	0.389			
		5.8 G WLAN (Auxiliary Antenna)	0.874	1.263	No	/
		Bluetooth (Auxiliary Antenna)	0.389			
		5.8 G WLAN (Main Antenna)	1.092	1.966	Yes	13#
		5.8 G WLAN (Auxiliary Antenna)	0.874			
		2.4 G WLAN (Main Antenna)	0.451	2.355	Yes	14#
		Bluetooth (Auxiliary Antenna)	0.253			
		2.4 G WLAN (Main Antenna)	0.451			

SPLSR Analysis 1#

Test Mode	Position	Antenna	Reported 1g Max. SAR (W/kg)	Coordinates (m)			1g Sum SAR (W/kg)	3D Distance (mm)	SPLSR	Simultaneous SAR Test (Yes/No)
				X	Y	Z				
Laptop	Bottom Side	Main WLAN 5.3G	1.191	0.008	0.115	-0.177	222.1	1.61	0.01	No
		Bluetooth	0.419	0.002	-0.107	-0.175				


**SPLSR Analysis 2#&3#**

Test Mode	Position	Antenna	Reported 1g Max. SAR (W/kg)	Coordinates (m)			1g Sum SAR (W/kg)	3D Distance (mm)	SPLSR	Simultaneous SAR Test (Yes/No)
				X	Y	Z				
Laptop	Bottom Side	Main WLAN 5.3G	1.191	0.008	0.115	-0.177	218.0	2.35	0.02	No
		Aux. WLAN 5.3G	1.158	0.004	-0.103	-0.178				




SPLSR Analysis 4#&5#

Test Mode	Position	Antenna	Reported 1g Max. SAR (W/kg)	Coordinates (m)			1g Sum SAR (W/kg)	3D Distance (mm)	SPLSR	Simultaneous SAR Test (Yes/No)
				X	Y	Z				
Laptop	Bottom Side	Main WLAN 5.6G	1.031	0.013	0.114	-0.177	217.2	1.97	0.01	No
		Aux. WLAN 5.6G	0.942	0.004	-0.103	-0.178				


**SPLSR Analysis 6#&7#**

Test Mode	Position	Antenna	Reported 1g Max. SAR (W/kg)	Coordinates (m)			1g Sum SAR (W/kg)	3D Distance (mm)	SPLSR	Simultaneous SAR Test (Yes/No)
				X	Y	Z				
Laptop	Bottom Side	Main WLAN 5.8G	1.050	0.007	0.114	-0.177	217.0	1.74	0.01	No
		Aux. WLAN 5.8G	0.691	0.004	-0.103	-0.178				




SPLSR Analysis 8#

Test Mode	Position	Antenna	Reported 1g Max. SAR (W/kg)	Coordinates (m)			1g Sum SAR (W/kg)	3D Distance (mm)	SPLSR	Simultaneous SAR Test (Yes/No)
				X	Y	Z				
Tablet	Bottom Edge	Main WLAN 2.4G	0.795	0.013	0.121	-0.176	211.1	1.82	0.01	No
		Aux. WLAN 2.4G	1.025	0.0082	-0.09	-0.176				


**SPLSR Analysis 9#&10#**

Test Mode	Position	Antenna	Reported 1g Max. SAR (W/kg)	Coordinates (m)			1g Sum SAR (W/kg)	3D Distance (mm)	SPLSR	Simultaneous SAR Test (Yes/No)
				X	Y	Z				
Tablet	Bottom Edge	Main WLAN 5.3G	1.173	0.016	0.118	-0.178	218.0	2.36	0.02	No
		Aux. WLAN 5.3G	1.185	0.012	-0.1	-0.178				




SPLSR Analysis 11#&12#

Test Mode	Position	Antenna	Reported 1g Max. SAR (W/kg)	Coordinates (m)			1g Sum SAR (W/kg)	3D Distance (mm)	SPLSR	Simultaneous SAR Test (Yes/No)
				X	Y	Z				
Tablet	Bottom Edge	Main WLAN 5.6G	1.131	0.017	0.115	-0.178	214.1	2.14	0.01	No
		Aux. WLAN 5.6G	1.005	0.011	-0.099	-0.178				

**SPLSR Analysis 13#&14#**

Test Mode	Position	Antenna	Reported 1g Max. SAR (W/kg)	Coordinates (m)			1g Sum SAR (W/kg)	3D Distance (mm)	SPLSR	Simultaneous SAR Test (Yes/No)
				X	Y	Z				
Tablet	Bottom Edge	Main WLAN 5.8G	1.092	0.017	0.119	-0.178	218.1	1.97	0.01	No
		Aux. WLAN 5.8G	0.874	0.011	-0.099	-0.178				



13 TEST EQUIPMENTS LIST

Description	Manufacturer	Model	Serial No./Version	Cal. Date	Cal. Due
PC	Dell	N/A	N/A	N/A	N/A
Test Software	Speag	DASY5	52.8.8.1222	N/A	N/A
2450MHz Validation Dipole	Speag	D2450V2	SN: 952	2021/05/19	2024/05/18
5GHz Validation Dipole	Speag	D5GHzV2	SN: 1200	2021/05/18	2024/05/17
E-Field Probe	Speag	EX3DV4	SN: 3717	2021/06/07	2022/06/06
Data Acquisition Electronics	Speag	DAE4	SN: 1226	2021/05/17	2022/05/16
Signal Generator	R&S	SMB100A	177746	2021/08/24	2022/08/23
Power Meter	R&S	NRVD-B2	7250BJ-0112/2011	2021/09/08	2022/09/07
Power Sensor	R&S	NRV-Z4	100381	2021/09/08	2022/09/07
Power Sensor	R&S	NRV-Z2	100211	2021/09/08	2022/09/07
Network Analyzer	Agilent	5071C	MY46103472	2021/12/29	2022/12/28
Thermometer	Elitech	RC-4HC	EF720B004820	2021/12/01	2022/11/30
Power Amplifier	SATIMO	6552B	22374	N/A	N/A
Dielectric Probe Kit	SATIMO	SCLMP	SN 25/13 OCPG56	N/A	N/A
Phantom1	Speag	SAM	SN: 1859	N/A	N/A
Phantom2	Speag	ELI4	SN: 1012	N/A	N/A
Attenuator	COM-MW	ZA-S1-31	1305003187	N/A	N/A
Directional coupler	AA-MCS	AAMCS-UDC	000272	N/A	N/A

Note: For dipole antennas, BALUN has adopted 3 years as calibration intervals, and on annual basis, every measurement dipole has been evaluated and is in compliance with the following criteria:

1. There is no physical damage on the dipole;
2. System validation with specific dipole is within 10% of calibrated value;
3. Return-loss in within 20% of calibrated measurement.
4. Impedance (real or imaginary parts) in within 5 Ohms of calibrated measurement.

ANNEX A SIMULATING LIQUID VERIFICATION RESULT

The dielectric parameters of the liquids were verified prior to the SAR evaluation using an SCLMP Dielectric Probe Kit.

Date	Liquid Type	Fre. (MHz)	Temp. (°C)	Meas. Conductivity (σ) (S/m)	Meas. Permittivity (ϵ)	Target Conductivity (σ) (S/m)	Target Permittivity (ϵ)	Conductivity Tolerance (%)	Permittivity Tolerance (%)
2022.03.26	Head	2450	21.3	1.81	39.66	1.80	39.20	0.56	1.17
2022.03.27	Head	5250	21.8	4.70	35.76	4.66	35.99	0.86	-0.64
2022.03.28	Head	5600	21.5	5.05	35.11	5.07	35.53	-0.39	-1.18
2022.03.29	Head	5750	21.6	5.18	35.52	5.27	35.30	-1.71	0.62
Note: The tolerance limit of Conductivity and Permittivity is $\pm 5\%$.									

ANNEX B SYSTEM CHECK RESULT

Comparing to the original SAR value provided by SPEAG, the validation data should be within its specification of 10 % (for 1 g).

Date	Liquid Type	Freq. (MHz)	Power (mW)	Measured SAR (W/kg)	Normalized SAR (W/kg)	Dipole SAR (W/kg)	Tolerance (%)
2022.03.26	Head	2450	100	5.020	50.20	52.60	-4.56
2022.03.27	Head	5250	100	7.810	78.10	73.90	5.68
2022.03.28	Head	5600	100	8.260	82.60	80.30	2.86
2022.03.29	Head	5750	100	8.050	80.50	76.90	4.68

Note: The tolerance limit of System validation $\pm 10\%$.

System Performance Check Data (2450MHz)

Date: 2022.03.26

Communication System Band: D2450 (2450.0 MHz); Frequency: 2450 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.805$ S/m; $\epsilon_r = 39.656$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature: 22.4 Liquid Temperature: 21.3

DASY5 Configuration:

- Probe: EX3DV4 - SN3717; ConvF(7.15, 7.15, 7.15); Calibrated: 2021.06.07;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1226; Calibrated: 2021.05.17
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:1012
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

CW 2450 100mw/Area Scan (101x101x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 5.77 W/kg


CW 2450 100mw/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 56.82 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 11.2 W/kg

SAR(1 g) = 5.02 W/kg; SAR(10 g) = 2.26 W/kg

Maximum value of SAR (measured) = 5.71 W/kg



0 dB = 5.71 W/kg

System Performance Check Data (5250MHz)

Date: 2022.03.27

Communication System Band: D5GHz (5000.0 - 6000.0 MHz); Frequency: 5250 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5250$ MHz; $\sigma = 4.703$ S/m; $\epsilon_r = 35.761$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature: 22.6 Liquid Temperature: 21.8

DASY5 Configuration:

- Probe: EX3DV4 - SN3717; ConvF(5.17, 5.17, 5.17); Calibrated: 2021.06.07;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1226; Calibrated: 2021.05.17
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:1012
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

CW 5250 100mW/Area Scan (101x101x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 8.11 W/kg


CW 5250 100mW/Zoom Scan (7x7x21)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 36.45 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 31.6 W/kg

SAR(1 g) = 7.81 W/kg; SAR(10 g) = 2.24 W/kg

Maximum value of SAR (measured) = 19.7 W/kg



0 dB = 19.7 W/kg

System Performance Check Data (5600MHz)

Date: 2022.03.28

Communication System Band: D5GHz (5000.0 - 6000.0 MHz); Frequency: 5600 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5600$ MHz; $\sigma = 5.049$ S/m; $\epsilon_r = 35.11$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature: 22.4 Liquid Temperature: 21.5

DASY5 Configuration:

- Probe: EX3DV4 - SN3717; ConvF(4.74, 4.74, 4.74); Calibrated: 2021.06.07;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1226; Calibrated: 2021.05.17
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:1012
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

CW 5600 100mW /Area Scan (81x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 9.13 W/kg


CW 5600 100mW /Zoom Scan (7x7x15)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 22.86 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 38.23 W/kg

SAR(1 g) = 8.26 W/kg; SAR(10 g) = 2.35 W/kg

Maximum value of SAR (measured) = 16.5 W/kg



0 dB = 16.5 W/kg

System Performance Check Data (5750MHz)

Date: 2022.03.29

Communication System Band: D5GHz (5000.0 - 6000.0 MHz); Frequency: 5750 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5750$ MHz; $\sigma = 5.179$ S/m; $\epsilon_r = 35.52$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature: 22.6 Liquid Temperature: 21.6

DASY5 Configuration:

- Probe: EX3DV4 - SN3717; ConvF(4.76, 4.76, 4.76); Calibrated: 2021.06.07;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1226; Calibrated: 2021.05.17
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:1012
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

CW 5750 100mW/Area Scan (81x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 8.93 W/kg


CW 5750 100mW/Zoom Scan (7x7x15)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 41.11 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 36.5 W/kg

SAR(1 g) = 8.05 W/kg; SAR(10 g) = 2.22 W/kg

Maximum value of SAR (measured) = 15.1 W/kg



0 dB = 15.1 W/kg

ANNEX C TEST DATA

Meas.1 Body Plane with Bottom Side 0mm on 39 Channel in Bluetooth mode Auxiliary

Date: 2022.03.26

Communication System Band: BT; Frequency: 2441 MHz; Duty Cycle: 1:1.301

Medium parameters used (interpolated): $f = 2441$ MHz; $\sigma = 1.793$ S/m; $\epsilon_r = 39.732$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature: 22.4 Liquid Temperature: 21.3

DASY5 Configuration:

- Probe: EX3DV4 - SN3717; ConvF(7.15, 7.15, 7.15); Calibrated: 2021.06.07;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1226; Calibrated: 2021.05.17
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:1012
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch39/Area Scan (91x91x1): Interpolated grid: $dx=1.200$ mm, $dy=1.200$ mm

Maximum value of SAR (interpolated) = 0.307 W/kg


Ch39/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 0.3510 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.637 W/kg

SAR(1 g) = 0.256 W/kg; SAR(10 g) = 0.108 W/kg

Maximum value of SAR (measured) = 0.327 W/kg



0 dB = 0.327 W/kg

Meas.2 Body Plane with Bottom Edge 0mm on 39 Channel in Bluetooth mode Auxiliary

Date: 2022.03.26

Communication System Band: BT; Frequency: 2441 MHz; Duty Cycle: 1:1.301

Medium parameters used (interpolated): $f = 2441$ MHz; $\sigma = 1.793$ S/m; $\epsilon_r = 39.732$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature: 22.4 Liquid Temperature: 21.3

DASY5 Configuration:

- Probe: EX3DV4 - SN3717; ConvF(7.15, 7.15, 7.15); Calibrated: 2021.06.07;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1226; Calibrated: 2021.05.17
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:1012
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch39/Area Scan (91x91x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 0.345 W/kg


Ch39/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 0 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 0.719 W/kg

SAR(1 g) = 0.285 W/kg; SAR(10 g) = 0.117 W/kg

Maximum value of SAR (measured) = 0.322 W/kg



Meas.3 Body Plane with Bottom Side 0mm on 6 Channel in IEEE802.11b mode with Antenna Main

Date: 2022.03.26

Communication System Band: 2.4G; Frequency: 2437 MHz; Duty Cycle: 1:1.006

Medium parameters used (interpolated): $f = 2437$ MHz; $\sigma = 1.771$ S/m; $\epsilon_r = 39.84$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature: 22.4 Liquid Temperature: 21.3

DASY5 Configuration:

- Probe: EX3DV4 - SN3717; ConvF(7.15, 7.15, 7.15); Calibrated: 2021.06.07;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1226; Calibrated: 2021.05.17
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:1012
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch6/Area Scan (91x91x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 0.266 W/kg


Ch6/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 0 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 0.513 W/kg

SAR(1 g) = 0.233 W/kg; SAR(10 g) = 0.103 W/kg

Maximum value of SAR (measured) = 0.274 W/kg



Meas.4 Body Plane with Bottom Side 0mm on 11 Channel in IEEE802.11b mode with Antenna Auxiliary

Date: 2022.03.26

Communication System Band: 2.4G; Frequency: 2462 MHz; Duty Cycle: 1:1.006

Medium parameters used (interpolated): $f = 2462$ MHz; $\sigma = 1.815$ S/m; $\epsilon_r = 39.58$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature: 22.4 Liquid Temperature: 21.3

DASY5 Configuration:

- Probe: EX3DV4 - SN3717; ConvF(7.15, 7.15, 7.15); Calibrated: 2021.06.07;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1226; Calibrated: 2021.05.17
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:1012
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch11/Area Scan (91x91x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 0.577 W/kg


Ch11/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 0.4050 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 1.04 W/kg

SAR(1 g) = 0.465 W/kg; SAR(10 g) = 0.200 W/kg

Maximum value of SAR (measured) = 0.556 W/kg



Meas.5 Body Plane with Bottom Edge 0mm on 6 Channel in IEEE802.11b mode with Antenna Main

Date: 2022.03.26

Communication System Band: 2.4G; Frequency: 2437 MHz; Duty Cycle: 1:1.006

Medium parameters used (interpolated): $f = 2437$ MHz; $\sigma = 1.771$ S/m; $\epsilon_r = 39.84$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature: 22.4 Liquid Temperature: 21.3

DASY5 Configuration:

- Probe: EX3DV4 - SN3717; ConvF(7.15, 7.15, 7.15); Calibrated: 2021.06.07;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1226; Calibrated: 2021.05.17
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:1012
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch6/Area Scan (91x91x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 0.854 W/kg


Ch6/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 0 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 1.99 W/kg

SAR(1 g) = 0.755 W/kg; SAR(10 g) = 0.314 W/kg

Maximum value of SAR (measured) = 0.854 W/kg



Meas.6 Body Plane with Bottom Edge 0mm on 11 Channel in IEEE802.11b mode with Antenna Auxiliary

Date: 2022.03.26

Communication System Band: 2.4G; Frequency: 2462 MHz; Duty Cycle: 1:1.006

Medium parameters used (interpolated): $f = 2462$ MHz; $\sigma = 1.815$ S/m; $\epsilon_r = 39.58$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature: 22.4 Liquid Temperature: 21.3

DASY5 Configuration:

- Probe: EX3DV4 - SN3717; ConvF(7.15, 7.15, 7.15); Calibrated: 2021.06.07;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1226; Calibrated: 2021.05.17
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:1012
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch11/Area Scan (91x91x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 1.09 W/kg


Ch11/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 0 V/m; Power Drift = 0.18 dB

Peak SAR (extrapolated) = 2.35 W/kg

SAR(1 g) = 0.938 W/kg; SAR(10 g) = 0.399 W/kg

Maximum value of SAR (measured) = 1.15 W/kg



Meas.7 Body Plane with Bottom Side 0mm on 58 Channel in IEEE802.11ac80 mode with Antenna Main

Date: 2022.03.27

Communication System Band: 5.3G; Frequency: 5290 MHz; Duty Cycle: 1:1.109

Medium parameters used (interpolated): $f = 5290$ MHz; $\sigma = 4.79$ S/m; $\epsilon_r = 35.224$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature: 22.6 Liquid Temperature: 21.8

DASY5 Configuration:

- Probe: EX3DV4 - SN3717; ConvF(5.17, 5.17, 5.17); Calibrated: 2021.06.07;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1226; Calibrated: 2021.05.17
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:1012
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch58/Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Maximum value of SAR (interpolated) = 1.93 W/kg


Ch58/Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 3.660 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 5.38 W/kg

SAR(1 g) = 1 W/kg; SAR(10 g) = 0.304 W/kg

Maximum value of SAR (measured) = 2.31 W/kg



Meas.8 Body Plane with Bottom Side 0mm on 58 Channel in IEEE802.11ac80 mode with Antenna Auxiliary

Date: 2022.03.27

Communication System Band: 5.3G; Frequency: 5290 MHz; Duty Cycle: 1:1.109

Medium parameters used (interpolated): $f = 5290$ MHz; $\sigma = 4.79$ S/m; $\epsilon_r = 35.224$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature: 22.6 Liquid Temperature: 21.8

DASY5 Configuration:

- Probe: EX3DV4 - SN3717; ConvF(5.17, 5.17, 5.17); Calibrated: 2021.06.07;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1226; Calibrated: 2021.05.17
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:1012
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch58/Area Scan (111x111x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 1.61 W/kg


Ch58/Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 0.9570 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 3.59 W/kg

SAR(1 g) = 0.883 W/kg; SAR(10 g) = 0.236 W/kg

Maximum value of SAR (measured) = 1.85 W/kg



Meas.9 Body Plane with Bottom Side 0mm on 114 Channel in IEEE802.11ac160 mode with Antenna Main

Date: 2022.03.28

Communication System Band: 5.6G; Frequency: 5570 MHz; Duty Cycle: 1:1.117

Medium parameters used (interpolated): $f = 5570$ MHz; $\sigma = 4.939$ S/m; $\epsilon_r = 35.886$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature: 22.4 Liquid Temperature: 21.5

DASY5 Configuration:

- Probe: EX3DV4 - SN3717; ConvF(4.74, 4.74, 4.74); Calibrated: 2021.06.07;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1226; Calibrated: 2021.05.17
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:1012
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch114/Area Scan (111x111x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 1.43 W/kg


Ch114/Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 0 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 3.73 W/kg

SAR(1 g) = 0.873 W/kg; SAR(10 g) = 0.214 W/kg

Maximum value of SAR (measured) = 1.55 W/kg



Meas.10 Body Plane with Bottom Side 0mm on 114 Channel in IEEE802.11ac160 mode with Antenna Auxiliary

Date: 2022.03.28

Communication System Band: 5.6G; Frequency: 5570 MHz; Duty Cycle: 1:1.117

Medium parameters used (interpolated): $f = 5570$ MHz; $\sigma = 4.939$ S/m; $\epsilon_r = 35.886$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature: 22.4 Liquid Temperature: 21.5

DASY5 Configuration:

- Probe: EX3DV4 - SN3717; ConvF(4.74, 4.74, 4.74); Calibrated: 2021.06.07;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1226; Calibrated: 2021.05.17
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:1012
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch114/Area Scan (111x111x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 1.33 W/kg


Ch114/Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 0 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 3.28 W/kg

SAR(1 g) = 0.753 W/kg; SAR(10 g) = 0.202 W/kg

Maximum value of SAR (measured) = 1.56 W/kg



Meas.11 Body Plane with Bottom Side 0mm on 155 Channel in IEEE802.11ac80 mode with Antenna Main

Date: 2022.03.29

Communication System Band: 5.8G; Frequency: 5775 MHz; Duty Cycle: 1:1.109

Medium parameters used (interpolated): $f = 5775$ MHz; $\sigma = 5.226$ S/m; $\epsilon_r = 35.205$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature:22.6 Liquid Temperature:21.6

DASY5 Configuration:

- Probe: EX3DV4 - SN3717; ConvF(4.76, 4.76, 4.76); Calibrated: 2021.06.07;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1226; Calibrated: 2021.05.17
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:1012
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch155/Area Scan (111x111x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 1.29 W/kg


Ch155/Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 3.810 V/m; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 4.12 W/kg

SAR(1 g) = 0.923 W/kg; SAR(10 g) = 0.307 W/kg

Maximum value of SAR (measured) = 1.47 W/kg



Meas.12 Body Plane with Bottom Side 0mm on 155 Channel in IEEE802.11ac80 mode with Antenna Auxiliary

Date: 2022.03.29

Communication System Band: 5.8G; Frequency: 5775 MHz; Duty Cycle: 1:1.109

Medium parameters used (interpolated): $f = 5775$ MHz; $\sigma = 5.226$ S/m; $\epsilon_r = 35.205$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature:22.6 Liquid Temperature:21.6

DASY5 Configuration:

- Probe: EX3DV4 - SN3717; ConvF(4.76, 4.76, 4.76); Calibrated: 2021.06.07;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1226; Calibrated: 2021.05.17
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:1012
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch155/Area Scan (111x111x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 1.10 W/kg


Ch155/Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 0 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 2.69 W/kg

SAR(1 g) = 0.583 W/kg; SAR(10 g) = 0.146 W/kg

Maximum value of SAR (measured) = 1.29 W/kg



Meas.13 Body Plane with Bottom Edge 0mm on 58 Channel in IEEE802.11ac80 mode with Antenna Main

Date: 2022.03.27

Communication System Band: 5.3G; Frequency: 5290 MHz; Duty Cycle: 1:1.109

Medium parameters used (interpolated): $f = 5290$ MHz; $\sigma = 4.79$ S/m; $\epsilon_r = 35.224$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature: 22.6 Liquid Temperature: 21.8

DASY5 Configuration:

- Probe: EX3DV4 - SN3717; ConvF((5.17, 5.17, 5.17)); Calibrated: 2021.06.07;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1226; Calibrated: 2021.05.17
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:1012
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch58/Area Scan (111x111x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 3.10 W/kg


Ch58/Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 0 V/m; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 6.74 W/kg

SAR(1 g) = 0.945 W/kg; SAR(10 g) = 0.240 W/kg

Maximum value of SAR (measured) = 2.99 W/kg



Meas.14 Body Plane with Bottom Edge 0mm on 58 Channel in IEEE802.11ac80 mode with Antenna Auxiliary

Date: 2022.03.27

Communication System Band: 5.3G; Frequency: 5290 MHz; Duty Cycle: 1:1.109

Medium parameters used (interpolated): $f = 5290$ MHz; $\sigma = 4.79$ S/m; $\epsilon_r = 35.224$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature: 22.6 Liquid Temperature: 21.8

DASY5 Configuration:

- Probe: EX3DV4 - SN3717; ConvF(5.17, 5.17, 5.17); Calibrated: 2021.06.07;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1226; Calibrated: 2021.05.17
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:1012
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch58/Area Scan (111x111x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 1.61 W/kg


Ch58/Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 0.9570 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 3.59 W/kg

SAR(1 g) = 0.883 W/kg; SAR(10 g) = 0.236 W/kg

Maximum value of SAR (measured) = 1.85 W/kg



0 dB = 1.85 W/kg

Meas.15 Body Plane with Bottom Edge 0mm on 114 Channel in IEEE802.11ac160 mode with Antenna Main

Date: 2022.03.28

Communication System Band: 5.6G; Frequency: 5570 MHz; Duty Cycle: 1:1.117

Medium parameters used (interpolated): $f = 5570$ MHz; $\sigma = 4.939$ S/m; $\epsilon_r = 35.886$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature: 22.4 Liquid Temperature: 21.5

DASY5 Configuration:

- Probe: EX3DV4 - SN3717; ConvF(4.74, 4.74, 4.74); Calibrated: 2021.06.07;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1226; Calibrated: 2021.05.17
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:1012
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch114/Area Scan (111x111x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 1.57 W/kg


Ch114/Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 0 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 4.50 W/kg

SAR(1 g) = 0.938 W/kg; SAR(10 g) = 0.375 W/kg

Maximum value of SAR (measured) = 1.97 W/kg



Meas.16 Body Plane with Bottom Edge 0mm on 114 Channel in IEEE802.11ac160 mode with Antenna Auxiliary

Date: 2022.03.28

Communication System Band: 5.6G; Frequency: 5570 MHz; Duty Cycle: 1:1.117

Medium parameters used (interpolated): $f = 5570$ MHz; $\sigma = 4.939$ S/m; $\epsilon_r = 35.886$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature:22.4 Liquid Temperature:21.5

DASY5 Configuration:

- Probe: EX3DV4 - SN3717; ConvF(4.74, 4.74, 4.74); Calibrated: 2021.06.07;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1226; Calibrated: 2021.05.17
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:1012
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch114/Area Scan (111x111x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 1.57 W/kg


Ch114/Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 0 V/m; Power Drift = -0.19 dB

Peak SAR (extrapolated) = 4.50 W/kg

SAR(1 g) = 0.800 W/kg; SAR(10 g) = 0.182 W/kg

Maximum value of SAR (measured) = 1.97 W/kg



0 dB = 1.97 W/kg

Meas.17 Body Plane with Bottom Edge 0mm on 155 Channel in IEEE802.11ac80 mode with Antenna Main

Date: 2022.03.29

Communication System Band: 5.8G; Frequency: 5775 MHz; Duty Cycle: 1:1.109

Medium parameters used (interpolated): $f = 5775$ MHz; $\sigma = 5.226$ S/m; $\epsilon_r = 35.205$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature:22.6 Liquid Temperature:21.6

DASY5 Configuration:

- Probe: EX3DV4 - SN3717; ConvF(4.76, 4.76, 4.76); Calibrated: 2021.06.07;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1226; Calibrated: 2021.05.17
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:1012
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch155/Area Scan (101x111x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 2.21 W/kg


Ch155/Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 6.921 V/m; Power Drift = -0.16 dB

Peak SAR (extrapolated) = 5.45 W/kg

SAR(1 g) = 0.956 W/kg; SAR(10 g) = 0.223 W/kg

Maximum value of SAR (measured) = 2.20 W/kg



0 dB = 2.20 W/kg

Meas.18 Body Plane with Bottom Edge 0mm on 155 Channel in IEEE802.11ac80 mode with Antenna Auxiliary

Date: 2022.03.29

Communication System Band: 5.8G; Frequency: 5775 MHz; Duty Cycle: 1:1.109

Medium parameters used (interpolated): $f = 5775$ MHz; $\sigma = 5.226$ S/m; $\epsilon_r = 35.205$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature:22.6 Liquid Temperature:21.6

DASY5 Configuration:

- Probe: EX3DV4 - SN3717; ConvF(4.76, 4.76, 4.76); Calibrated: 2021.06.07;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1226; Calibrated: 2021.05.17
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:1012
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch155/Area Scan (101x111x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 1.43 W/kg


Ch155/Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 11.05 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 4.25 W/kg

SAR(1 g) = 0.719 W/kg; SAR(10 g) = 0.161 W/kg

Maximum value of SAR (measured) = 1.77 W/kg



0 dB = 1.77 W/kg

ANNEX D EUT EXTERNAL PHOTOS

Please refer the document “BL-SZ2220095-AW.pdf”.

ANNEX E SAR TEST SETUP PHOTOS

Please refer the document “BL-SZ2220095-AS-1.pdf”.

ANNEX F CALIBRATION REPORT

Please refer the document “CALIBRATION REPORT.pdf”.

ANNEX G Gravity-Sensor Conducted Power Test Results

Please refer the document “Gravity-Sensor Conducted Power Test Results-703.pdf”.

Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--