

FCC Report

(Mobile Phone)

Applicant: HK TIANRUIXIANG COMMUNICATION EQUIPMENT LIMITED

Address of Applicant: RM. 5C Shuisong Building, Tairan Eight Road, Chegongmiao, Futian District, Shenzhen, China

Equipment Under Test (EUT)

Product Name: Smart Phone

Model No.: A9, A13, A9B

FCC ID: RFOA9

Applicable standards: FCC CFR Title 47 Part 2: 2012
FCC CFR Title 47 Part22 Subpart H: 2012
FCC CFR Title 47 Part24 Subpart E: 2012

Date of sample receipt: August 07, 2013


Date of Test: August 07-21, 2013

Date of report issued: August 27, 2013

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Robinson Lo
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the GTS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of GTS International Electrical Approvals or testing done by GTS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by GTS International Electrical Approvals in writing.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

2 Version

Version No.	Date	Description
00	August 27, 2013	Original

Prepared By:

Hank. Yan

Date:

August 27, 2013

Project Engineer

Check By:

Hans. Hu

Date:

August 27, 2013

Reviewer

3 Contents

	Page
.....	1
2 VERSION.....	2
3 CONTENTS.....	3
4 TEST SUMMARY.....	4
5 GENERAL INFORMATION.....	5
5.1 CLIENT INFORMATION.....	5
5.2 GENERAL DESCRIPTION OF EUT.....	5
5.3 RELATED SUBMITTAL(S) / GRANT (S).....	7
5.4 TEST METHODOLOGY.....	7
5.5 TEST FACILITY.....	7
5.6 TEST LOCATION.....	7
6 TEST INSTRUMENTS LIST.....	8
7 SYSTEM TEST CONFIGURATION.....	9
7.1 TEST MODE.....	9
7.2 CONFIGURATION OF TESTED SYSTEM.....	10
7.3 CONDUCTED PEAK OUTPUT POWER.....	11
7.4 OCCUPY BANDWIDTH.....	13
7.5 MODULATION CHARACTERISTIC.....	20
7.6 OUT OF BAND EMISSION AT ANTENNA TERMINALS.....	20
7.7 ERP, EIRP MEASUREMENT.....	25
7.8 FIELD STRENGTH OF SPURIOUS RADIATION MEASUREMENT.....	32
7.9 FREQUENCY STABILITY V.S. TEMPERATURE MEASUREMENT.....	37
7.10 FREQUENCY STABILITY V.S. VOLTAGE MEASUREMENT.....	40

4 Test Summary

Test Item	Section in CFR 47	Result
RF Exposure (SAR)	Part 1.1307 Part 2.1093	Pass* (Please refer to SAR Report)
RF Output Power	Part 2.1046 Part 22.913 (a)(2) Part 24.232 (c)	Pass
Modulation Characteristics	Part 2.1047	Pass
99% & -26 dB Occupied Bandwidth	Part 2.1049 Part 22.917 Part 24.238	Pass
Spurious Emissions at Antenna Terminal	Part 2.1051 Part 22.917 (a) Part 24.238 (a)	Pass
Field Strength of Spurious Radiation	Part 2.1053 Part 22.917 (a) Part 24.238 (a)	Pass
Out of band emission, Band Edge	Part 22.917 (a) Part 24.238 (a)	Pass
Frequency stability vs. temperature	Part 2.1055(a)(1)(b)	Pass
Frequency stability vs. voltage	Part 2.1055(d)(1)(2)	Pass

Pass: The EUT complies with the essential requirements in the standard.

5 General Information

5.1 Client Information

Applicant:	HK TIANRUIXIANG COMMUNICATION EQUIPMENT LIMITED
Address of Applicant:	RM. 5C Shuisong Building, Tairan Eight Road, Chegongmiao, Futian District, Shenzhen, China
Manufacturer:	HK TIANRUIXIANG COMMUNICATION EQUIPMENT LIMITED
Address of Manufacturer:	RM. 5C Shuisong Building, Tairan Eight Road, Chegongmiao, Futian District, Shenzhen, China

5.2 General Description of EUT

Product Name:	Smart Phone
Trade mark:	A9, A13, A9B
Support Networks:	GSM, GPRS, EGPRS, WCDMA
Support Bands:	GSM850, PCS1900, WCDMA Band II
TX Frequency:	GSM850: 824.20MHz-848.80MHz PCS1900: 1850.20MHz-1909.80MHz WCDMA Band II: 1852.40MHz -1907.60MHz
GPRS Class:	12
EGPRS Class:	12
Modulation type:	GSM/GPRS: GMSK EGPRS: GMSK / 8PSK WCDMA Band II: QPSK
IMEI:	356473050000011
Hardware Version:	X235-MB-V6.1
Software Version:	X235_36D_ENTEL_EN_SA_BT_FM_TV_JAVA_WIFI_SP0A18_TP_FLASH 12864_LCD240X400_V01_20121208_1105
Antenna type:	Integral antenna
Antenna gain:	-2dBi(GSM900) -2dBi(DCS1800)
AC adapter:	Model : MLC0008 Input: AC 100-240V, 50/60Hz, 0.3A Output: DC 5.0V, 1A
Power supply:	Type: lithium-ion 3.7V 1100mAh Voltage: DC 3.7V

Operation Frequency List:

GSM 850		PCS1900		WCDMA Band II	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
128	824.20	512	1850.20	9262	1852.40
129	824.40	513	1850.40	9263	1852.60
⋮	⋮	⋮	⋮	⋮	⋮
189	836.40	660	1879.80	9399	1879.80
190	836.60	661	1880.00	9400	1880.00
191	836.80	662	1880.20	9401	1880.20
⋮	⋮	⋮	⋮	⋮	⋮
250	848.60	809	1909.60	9537	1907.40
251	848.80	810	1909.80	9538	1907.60

Regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Final test channel:

GSM 850		PCS1900		WCDMA Band II	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
128	824.20	512	1850.20	9262	1852.40
190	836.60	661	1880.00	9400	1880.00
251	848.80	810	1909.80	9538	1907.60

5.3 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is filing to comply with Section Part 22 subpart H and Part 24 subpart E of the FCC CFR 47 Rules.

5.4 Test Methodology

Both conducted and radiated testing were performed according to the procedures document on TIA/EIA 603 and FCC CFR 47.1046, 2.1047, 2.1049, 2.1051, 2.1053, 2.1055 and 2.1057

5.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS —Registration No.: CNAS L5775**

CNAS has accredited Global United Technology Services Co., Ltd. To ISO/IEC 17025 General Requirements for the competence of testing and calibration laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **FCC —Registration No.: 600491**

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 600491, June 28, 2013.

- **Industry Canada (IC) —Registration No.: 9079A-2**

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A-2, June 26, 2013.

5.6 Test Location

All tests were performed at:

Global United Technology Services Co., Ltd.

Address: 2nd Floor, Block No.2, Laodong Industrial Zone, Xixiang Road Baoan District, Shenzhen, China

Tel: 0755-27798480

Fax: 0755-27798960

6 Test Instruments list

Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	Mar. 29 2013	Mar. 28 2014
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	Jul. 02 2013	Jul. 01 2014
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	Feb. 24 2013	Feb. 23 2014
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	9120D-829	GTS208	June 28 2013	June 27 2014
6	Horn Antenna	ETS-LINDGREN	3160	GTS217	Mar. 29 2013	Mar. 28 2014
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
8	Coaxial Cable	GTS	N/A	GTS213	Mar. 30 2013	Mar. 29 2014
9	Coaxial Cable	GTS	N/A	GTS211	Mar. 30 2013	Mar. 29 2014
10	Coaxial cable	GTS	N/A	GTS210	Mar. 30 2013	Mar. 29 2014
11	Coaxial Cable	GTS	N/A	GTS212	Mar. 30 2013	Mar. 29 2014
12	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	Jul. 02 2013	Jul. 01 2014
13	Amplifier(2GHz-20GHz)	HP	8349B	GTS206	Jul. 02 2013	Jul. 01 2014
14	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June 28 2013	June 27 2014
15	Band filter	Amindeon	82346	GTS219	Mar. 30 2013	Mar. 29 2014
16	Universal radio communication tester	Rohde & Schwarz	CMU200	GTS235	May 10 2013	May 09 2014
17	Signal Generator	Rohde & Schwarz	SML03	GTS236	May 10 2013	May 09 2014
18	Temp. Humidity/ Barometer	Oregon Scientific	BA-888	GTS248	May 10 2013	May 09 2014
19	D.C. Power Supply	Instek	PS-3030	GTS232	NA	NA
20	Splitter	Agilent	11636B	GTS237	May 10 2013	May 09 2014
21	Power meter	Rohde & Schwarz	NRVS	GTS238	May 10 2013	May 09 2014
22	Spectrum Analyzer	Agilent	E4440A	GTS533	Dec. 6, 2012	Dec. 5, 2013

7 System test configuration

7.1 Test mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission.

Test modes		
Band	Radiated	Conducted
GSM 850	■ GSM link	■ GSM link
	■ EGPRS 8 link	■ EGPRS 8 link
PCS 1900	■ GSM link	■ GSM link
	■ EGPRS 8 link	■ EGPRS 8 link
WCDMA BandV	■ RMC 12.2Kbps link	■ RMC 12.2Kbps link


Note: The maximum power levels are GSM mode for GMSK link, EGPRS multi-slot class 8 mode for 8PSK link, RMC12.2Kbps mode for WCDMA band V. only these modes were used for all tests.

The conducted power tables are as follows:


Conducted Power (dBm)						
Band	GSM850			PCS1900		
Channel	128	190	251	512	661	810
Frequency	824.20	836.60	848.80	1850.20	1880.00	1909.80
GSM (GMSK, 1 TX slot)	31.96	32.15	32.37	28.95	29.10	29.57
GPRS (GMSK, 1 TX slot)	31.94	32.14	32.34	28.93	29.09	29.55
GPRS (GMSK, 2 TX slot)	31.19	31.39	31.59	28.16	28.34	28.80
GPRS (GMSK, 3 TX slot)	29.22	29.42	29.62	26.19	26.37	26.83
GPRS (GMSK, 4 TX slot)	27.12	27.32	27.52	24.09	24.27	24.73
EGPRS(GMSK, 1 TX slot)	31.90	32.10	32.30	28.87	29.05	29.51
EGPRS(GMSK, 2 TX slot)	31.17	31.37	31.57	28.14	28.32	28.78
EGPRS(GMSK, 3 TX slot)	29.17	29.37	29.57	26.14	26.32	26.78
EGPRS(GMSK, 4 TX slot)	27.13	27.33	27.53	24.10	24.28	24.74
EGPRS (8PSK, 1 TX slot)	26.54	26.75	26.93	24.28	24.53	24.89
EGPRS (8PSK, 2 TX slot)	25.18	25.48	25.79	23.10	23.31	23.63
EGPRS (8PSK, 3 TX slot)	23.05	23.34	23.52	21.85	21.98	22.25
EGPRS (8PSK, 4 TX slot)	22.11	22.27	22.49	20.95	21.02	21.34

Conducted Power			
Band	WCDMA Band II		
Channel	9262	9400	9538
Frequency	1852.4	1880.0	1907.6
RMC 12.2Kbps	24.13	24.65	23.26
RMC 64Kbps	24.09	24.59	23.22
RMC 144Kbps	24.10	24.61	23.19
RMC 384Kbps	24.07	24.57	23.17
HSDPA Subtest-1	24.11	24.64	23.24
HSDPA Subtest-2	24.1	24.62	23.23
HSDPA Subtest-3	24.08	24.61	23.21
HSDPA Subtest-4	24.07	24.59	23.19
HSUPA Subtest-1	24.12	24.63	23.25
HSUPA Subtest-2	24.09	24.62	23.23
HSUPA Subtest-3	24.07	24.61	23.22
HSUPA Subtest-4	24.06	24.59	23.19
HSUPA Subtest-5	24.05	24.56	23.18
AMR	24.11	24.60	23.24

7.2 Configuration of Tested System




7.3 Conducted Peak Output Power

Test Requirement:	FCC part22.913(a) and FCC part24.232(b)
Test Method:	FCC part2.1046
Limit:	GSM850,: 7W PCS1900, WCDMA Band II: 2W
Test setup:	 <i>Note: Measurement setup for testing on Antenna connector</i>
Test Procedure:	1. The transmitter output port was connected to base station. 2. The RF output of EUT was connected to the power meter by RF cable and attenuator, the path loss was compensated to the results for each measurement. 3. Set EUT at maximum power through base station. 4. Select lowest, middle, and highest channels for each band and different modulation. 5. Measure the maximum burst average power.
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data

EUT Mode	Channel	Frequency (MHz)	PK power (dBm)	Limit (dBm)	Result
GSM 850 (GSM link)	128	824.20	31.96	38.45	Pass
	190	836.60	32.15		
	251	848.80	32.37		
GSM 850 (EGPRS 8 link)	128	824.20	26.54	38.45	Pass
	190	836.60	26.75		
	251	848.80	26.93		
PCS 1900 (GSM link)	512	1850.20	28.95	33.01	Pass
	661	1880.00	29.10		
	810	1909.80	29.57		
PCS 1900 (EGPRS 8 link)	512	1850.20	24.28	33.01	Pass
	661	1880.00	24.53		
	810	1909.80	24.89		
WCDMA Band II (RMC 12.2Kbps link)	9262	1852.4	24.13	33.01	Pass
	9400	1880.0	24.65		
	9538	1907.6	23.26		

7.4 Occupy Bandwidth


Test Requirement:	FCC part22.913(a) and FCC part24.232(b)
Test Method:	FCC part2.1049
Test setup:	 <i>Note: Measurement setup for testing on Antenna connector</i>
Test Procedure:	1. The EUT's output RF connector was connected with a short cable to the spectrum analyzer 2. RBW was set to about 1% of emission BW, VBW= 3 times RBW. 3. -26dBc display line was placed on the screen (or 99% bandwidth), the occupied bandwidth is the delta frequency between the two points where the display line intersects the signal trace.
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data


EUT Mode	Channel	Frequency (MHz)	99% Occupy bandwidth (KHz)	-26dB bandwidth (KHz)
GSM 850 (GSM link)	128	824.20	246.23	321.41
	190	836.60	243.04	313.94
	251	848.80	245.03	321.99
GSM 850 (EGPRS 8 link)	128	824.20	243.54	319.62
	190	836.60	243.44	318.74
	251	848.80	243.99	322.83
PCS 1900 (GSM link)	512	1850.20	243.99	322.09
	661	1880.00	243.62	320.10
	810	1909.80	243.15	313.11
PCS 1900 (EGPRS 8 link)	512	1850.20	243.82	324.45
	661	1880.00	243.44	322.14
	810	1909.80	243.18	322.40
WCDMA Band II (RMC 12.2Kbps link)	9262	1852.4	4203.00	4748.00
	9400	1880.0	4146.70	4673.00
	9538	1907.6	4192.30	4743.00

Test plot as follows:


Test band:	GSM 850 (GSM link)
------------	--------------------



Lowest channel




Middle channel




Highest channel:


Test band:	GSM 850 (EGPRS 8 link)
------------	------------------------



Lowest channel




Middle channel




Highest channel:


Test band:	PCS 1900 (GSM link)
------------	---------------------



Lowest channel




Middle channel




Highest channel:


Test band:	PCS 1900 (EGPRS 8 link)
------------	-------------------------



Lowest channel




Middle channel




Highest channel:


Test band:	WCDMA Band II (RMC 12.2Kbps link)
------------	-----------------------------------



Lowest channel



Middle channel




Highest channel:

7.5 MODULATION CHARACTERISTIC

According to FCC § 2.1047(d), Part 22H & 24E there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.



7.6 Out of band emission at antenna terminals

Test Requirement:	FCC part22.917(a) and FCC part24.238(a)
Test Method:	FCC part2.1051
Limit:	-13dBm
Test setup:	 <i>Note: Measurement setup for testing on Antenna connector</i>
Test Procedure:	1 The RF output of the transceiver was connected to a spectrum analyzer through appropriate attenuation. 2 The resolution bandwidth of the spectrum analyzer was set at 1MHz, sufficient scans were taken to show the out of band Emissions if any up to 10th harmonic. 3 For the out of band: Set the RBW, VBW = 1MHz, Start=30MHz, Stop= 10th harmonic. 4 Band Edge Requirements: In the 1 MHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 1 percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to measure the out of band Emissions.
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed



Test plot as follows:

Test Mode:



GSM 850 (GSM link)



Lowest channel





Middle channel





Highest channel



Test Mode:	PCS1900 (GSM link)
------------	--------------------



Lowest channel





Middle channel





Highest channel

Test Mode:



WCDMA Band II (RMC 12.2Kbps link)



Lowest channel




Middle channel




Highest channel

Band Edge:




Lowest channel

Highest channel



Lowest channel




Highest channel



Lowest channel

Highest channel

7.7 ERP, EIRP Measurement

Test Requirement:	FCC part22.913(a) and FCC part24.232(b)
Test Method:	FCC part2.1046
Limit:	GSM850 7W ERP PCS1900 2W EIRP
Test setup:	Below 1GHz  Above 1GHz  Substituted method: 

Test Procedure:	1. The EUT was placed on an non-conductive turntable using a non-conductive support. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and EMI spectrum analyzer. 2. During the measurement, the EUT was communication with the station. The highest emission was recorded with the rotation of the turntable and the lowering of the test antenna from 4m to 1m. The reading was recorded and the field strength (E in dBuV/m) was calculated. 3. ERP in frequency band 824.2 –848.80.8MHz were measured using a substitution method. The EUT was replaced by dipole antenna connected, the S.G. output was recorded and ERP was calculated as follows: $\text{ERP} = \text{S.G. output (dBm)} + \text{Antenna Gain (dBd)} - \text{Cable Loss (dB)}$ 4. EIRP in frequency band 1850.2 –1909.8MHz were measured using a substitution method. The EUT was replaced by or horn antenna connected, the S.G. output was recorded and EIRP was calculated as follows: $\text{EIRP} = \text{S.G. output (dBm)} + \text{Antenna Gain (dBi)} - \text{Cable Loss (dB)}$
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data

EUT mode	Channel	EUT Pol.	Antenna Pol.	ERP(dBm)	Limit (dBm)	Result
GSM850 (GSM link)	Lowest	H	V	33.13	38.45	Pass
			H	30.14		
		E1	V	24.91		
			H	30.57		
		E2	V	24.23		
			H	28.45		
	Middle	H	V	33.46	38.45	Pass
			H	30.60		
		E1	V	25.48		
			H	31.18		
		E2	V	26.04		
			H	29.18		
	Highest	H	V	33.85	38.45	Pass
			H	30.22		
		E1	V	25.29		
			H	29.94		
		E2	V	23.84		
			H	29.35		




EUT mode	Channel	EUT Pol.	Antenna Pol.	ERP(dBm)	Limit (dBm)	Result
GSM850 (EGPRS 8 link)	Lowest	H	V	27.39	38.45	Pass
			H	24.31		
		E1	V	18.90		
			H	24.75		
		E2	V	18.20		
			H	22.56		
	Middle	H	V	27.53	38.45	Pass
			H	24.57		
		E1	V	19.29		
			H	25.18		
		E2	V	19.87		
			H	23.11		
	Highest	H	V	27.75	38.45	Pass
			H	24.00		
		E1	V	18.91		
			H	23.71		
		E2	V	17.42		
			H	23.11		

EUT mode	Channel	EUT Pol.	Antenna Pol.	EIRP (dBm)	Limit (dBm)	Result
PCS1900 (GSM link)	Lowest	H	V	29.27	33.01	Pass
			H	26.59		
		E1	V	21.90		
			H	26.98		
		E2	V	21.29		
			H	25.07		
	Middle	H	V	29.62	33.01	Pass
			H	27.05		
		E1	V	22.47		
			H	27.58		
		E2	V	22.97		
			H	25.78		
	Highest	H	V	30.07	33.01	Pass
			H	26.81		
		E1	V	22.40		
			H	26.56		
		E2	V	21.10		
			H	26.04		

EUT mode	Channel	EUT Pol.	Antenna Pol.	EIRP (dBm)	Limit (dBm)	Result
PCS1900 (EGPRS 8 link)	Lowest	H	V	24.95	33.01	Pass
			H	21.74		
		E1	V	16.11		
			H	22.20		
		E2	V	15.38		
			H	19.92		
	Middle	H	V	25.27	33.01	Pass
			H	22.19		
		E1	V	16.70		
			H	22.82		
		E2	V	17.29		
			H	20.67		
	Highest	H	V	25.64	33.01	Pass
			H	21.73		
		E1	V	16.44		
			H	21.44		
		E2	V	14.88		
			H	20.81		

EUT mode	Channel	EUT Pol.	Antenna Pol.	EIRP(dBm)	Limit (dBm)	Result
WCDMA Band II	Lowest	H	V	25.38	33.01	Pass
			H	23.47		
		E1	V	20.12		
			H	23.74		
		E2	V	19.69		
			H	22.39		
	Middle	H	V	25.73	33.01	Pass
			H	23.90		
		E1	V	20.63		
			H	24.27		
		E2	V	20.98		
			H	22.99		
	Highest	H	V	24.59	33.01	Pass
			H	22.27		
		E1	V	19.11		
			H	22.09		
		E2	V	18.19		
			H	21.71		

7.8 Field strength of spurious radiation measurement

Test Requirement:	FCC part22.917(a) and FCC part24.238(a)
Test Method:	FCC part2.1053
Limit:	-13dBm
Test setup:	Below 1GHz  Above 1GHz  Substituted method: 

Test Procedure:	1. The EUT was placed on an non-conductive turntable using a non-conductive support. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and EMI spectrum analyzer. 2. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations. 3. The frequency range up to tenth harmonic was investigated for each of three fundamental frequency (low, middle and high channels). Once spurious emission was identified, the power of the emission was determined using the substitution method. 4. The spurious emissions attenuation was calculated as the difference between radiated power at the fundamental frequency and the spurious emissions frequency. $\text{ERP / EIRP} = \text{S.G. output (dBm)} + \text{Antenna Gain(dB/dBi)} - \text{Cable Loss (dB)}$
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data

Test mode:	GSM850		Test channel:	Lowest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
1648.40	Vertical	-40.27	-13.00	Pass
2472.60	V	-42.40		
3296.80	V	-44.15		
4121.00	V	-45.86		
4945.20	V	---		
1648.40	Horizontal	-44.36	-13.00	Pass
2472.60	H	-47.38		
3296.80	H	-48.58		
4121.00	H	-50.69		
4945.20	H	---		
Test mode:	GSM850		Test channel:	Middle
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
1673.20	Vertical	-41.13	-13.00	Pass
2509.80	V	-43.79		
3346.40	V	-45.97		
4183.00	V	-48.10		
5019.60	V	---		
1673.20	Horizontal	-46.23	-13.00	Pass
2509.80	H	-49.99		
3346.40	H	-51.49		
4183.00	H	-54.12		
5019.60	H	---		
Test mode:	GSM850		Test channel:	Highest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
1697.60	Vertical	-41.53	-13.00	Pass
2546.40	V	-44.31		
3395.20	V	-46.59		
4244.00	V	-48.82		
5092.80	V	---		
1697.60	Horizontal	-46.87	-13.00	Pass
2546.40	H	-50.80		
3395.20	H	-52.37		
4244.00	H	-55.12		
5092.80	H	---		

Remark :

1. The emission behaviour belongs to narrowband spurious emission.
2. Remark"---" means that the emission level is too low to be measured
3. The emission levels of below 1 GHz are very lower than the limit and not show in test report.

Test mode:	PCS1900		Test channel:	Lowest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
3700.40	Vertical	-39.76	-13.00	Pass
5550.60	V	-42.33		
7400.80	V	-44.43		
9251.00	V	-46.49		
11101.20	V	---		
3700.40	Horizontal	-44.69	-13.00	Pass
5550.60	H	-48.32		
7400.80	H	-49.77		
9251.00	H	-52.31		
11101.20	H	---		
Test mode:	PCS1900		Test channel:	Middle
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
3760.00	Vertical	-38.59	-13.00	Pass
5640.00	V	-40.59		
7520.00	V	-42.23		
9400.00	V	-43.84		
11280.00	V	---		
3760.00	Horizontal	-42.43	-13.00	Pass
5640.00	H	-45.26		
7520.00	H	-46.39		
9400.00	H	-48.37		
11280.00	H	---		
Test mode:	PCS1900		Test channel:	Highest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
3819.60	Vertical	-38.15	-13.00	Pass
5729.40	V	-40.28		
7639.20	V	-42.03		
9549.00	V	-43.74		
11458.80	V	---		
3819.60	Horizontal	-42.24	-13.00	Pass
5729.40	H	-45.26		
7639.20	H	-46.46		
9549.00	H	-48.57		
11458.80	H	---		

Remark:


1. The emission behaviour belongs to narrowband spurious emission.
2. Remark"---" means that the emission level is too low to be measured
3. The emission levels of below 1 GHz are very lower than the limit and not show in test report.

Test mode:	WCDMA Band II		Test channel:	Lowest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
3704.80	Vertical	-39.39	-13.00	Pass
5557.20	V	-42.43		
7409.60	V	-44.93		
9262.00	V	-47.37		
11114.40	V	---		
3704.80	Horizontal	-45.23	-13.00	Pass
5557.20	H	-49.53		
7409.60	H	-51.25		
9262.00	H	-54.26		
11114.40	H	---		
Test mode:	WCDMA Band II		Test channel:	Middle
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
3760.00	Vertical	-40.14	-13.00	Pass
5640.00	V	-43.03		
7520.00	V	-45.40		
9400.00	V	-47.72		
11280.00	V	---		
3760.00	Horizontal	-45.69	-13.00	Pass
5640.00	H	-49.78		
7520.00	H	-51.41		
9400.00	H	-54.27		
11280.00	H	---		
Test mode:	WCDMA Band II		Test channel:	Highest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
3815.20	Vertical	-39.25	-13.00	Pass
5722.80	V	-41.95		
7630.40	V	-44.16		
9538.00	V	-46.33		
11445.60	V	---		
3815.20	Horizontal	-44.43	-13.00	Pass
5722.80	H	-48.25		
7630.40	H	-49.77		
9538.00	H	-52.44		
11445.60	H	---		

Remark :

1. The emission behaviour belongs to narrowband spurious emission.
2. Remark"---" means that the emission level is too low to be measured
3. The emission levels of below 1 GHz are very lower than the limit and not show in test report.

7.9 Frequency stability V.S. Temperature measurement


Test Requirement:	FCC Part2.1055(a)(1)(b)
Test Method:	FCC Part2.1055(a)(1)(b)
Limit:	2.5ppm
Test setup:	 Note : Measurement setup for testing on Antenna connector
Test procedure:	1. The equipment under test was connected to an external DC power supply and input rated voltage. 2. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. 3. The EUT was placed inside the temperature chamber. 4. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 25°C operating frequency as reference frequency. 5. Turn EUT off and set the chamber temperature to –20°C. After the temperature stabilized for approximately 30 minutes recorded the frequency. 6. Repeat step measure with 10°C increased per stage until the highest temperature of +50°C reached.
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data

Reference Frequency: GSM850 (GSM link) Middle channel=190 channel=836.6MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.70	-30	28	0.0339	2.5	Pass
	-20	25	0.0303		
	-10	21	0.0250		
	0	19	0.0232		
	10	18	0.0215		
	20	15	0.0179		
	30	19	0.0232		
	40	22	0.0268		
	50	21	0.0250		
Reference Frequency: GSM850 (EGPRS 8 link) Middle channel=190 channel=836.6MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.70	-30	28	0.0332	2.5	Pass
	-20	25	0.0304		
	-10	22	0.0261		
	0	21	0.0246		
	10	19	0.0232		
	20	17	0.0203		
	30	21	0.0246		
	40	23	0.0275		
	50	24	0.0282		

Reference Frequency: PCS1900 (GSM link) Middle channel=661 channel=1880MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error			Result
		Hz	ppm		
3.70	-30	51	0.0274	2.5	Pass
	-20	48	0.0254		
	-10	42	0.0225		
	0	40	0.0215		
	10	39	0.0206		
	20	35	0.0186		
	30	40	0.0215		
	40	44	0.0235		
	50	42	0.0225		
Reference Frequency: PCS1900 (EGPRS 8 link) Middle channel=661 channel=1880MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error			Result
		Hz	ppm		
3.70	-30	47	0.0247	2.5	Pass
	-20	44	0.0231		
	-10	39	0.0207		
	0	38	0.0199		
	10	36	0.0191		
	20	33	0.0176		
	30	36	0.0191		
	40	41	0.0215		
	50	41	0.0219		
Reference Frequency: WCDMA Band II Middle channel=9400 channel=1880.0MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.70	-30	49	0.0258	2.5	Pass
	-20	44	0.0235		
	-10	38	0.0200		
	0	36	0.0189		
	10	33	0.0177		
	20	29	0.0154		
	30	36	0.0189		
	40	40	0.0212		
	50	38	0.0200		

7.10 Frequency stability V.S. Voltage measurement

Test Requirement:	FCC Part2.1055(d)(1)(2)
Test Method:	FCC Part2.1055(d)(1)(2)
Limit:	2.5ppm
Test setup:	 Note : Measurement setup for testing on Antenna connector
Test procedure:	1. Set chamber temperature to 25 °C . Use a variable DC power source to power the EUT and set the voltage to rated voltage. 2. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency. 3. Reduce the input voltage to specified extreme voltage variation (+/- 15%) and endpoint, record the maximum frequency change.
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data

Reference Frequency: GSM850 (GSM link) Middle channel=190 channel=836.6MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.25	17	0.0208	2.5	Pass
	3.70	15	0.0179		
	3.40	20	0.0236		
Reference Frequency: GSM850 (EGPRS 8 link) Middle channel=190 channel=836.6MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.25	19	0.0221	2.5	Pass
	3.70	17	0.0203		
	3.40	20	0.0239		
Reference Frequency: PCS1900 (GSM link) Middle channel=661 channel=1880MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.25	39	0.0197	2.5	Pass
	3.70	35	0.0223		
	3.40	37	0.0207		
Reference Frequency: PCS1900 (EGPRS 8 link) Middle channel=661 channel=1880MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.25	36	0.0197	2.5	Pass
	3.70	33	0.0223		
	3.40	35	0.0207		
Reference Frequency: WCDMA Band II Middle channel=940 channel=1880.0MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.25	34	0.0197	2.5	Pass
	3.70	29	0.0223		
	3.40	32	0.0207		

-----end-----