



**MEASUREMENT REPORT**  
**FCC PART 15.247 Bluetooth**

**Applicant Name:**

Sirius XM Radio Inc.  
1500 Eckington Place, NE  
Washington, DC 20002  
United States

**Date of Testing:**

7/14-9/28/2021

**Test Site/Location:**

PCTEST Lab. Columbia, MD, USA

**Test Report Serial No.:**

1M2107130077-02-R3.RS2

<b>FCC ID:</b>	<b>RS2SXVRBT1</b>
<b>IC:</b>	<b>5750A-SXVRBT1C</b>
<b>APPLICANT:</b>	<b>Sirius XM Radio Inc.</b>

**Application Type:**

Certification

**Model:**

SXVRBT1

**EUT Type:**

Satellite Radio with FM Transmitter and Bluetooth

**Max. RF Output Power:**

13.032 mW (11.15 dBm) Peak Conducted

**Frequency Range:**

2402 – 2480MHz

**Type of Modulation:**

GFSK,  $\pi/4$ -DQPSK, 8DPSK

**FCC Classification:**

FCC Part 15 Spread Spectrum Transmitter (DSS)

**FCC Rule Part(s):**

Part 15 Subpart C (15.247)

**ISED Rule Part(s):**

RSS-247 Issue 2

**Test Procedure(s):**

ANSI C63.10-2013, KDB 558074 D01 v05r02

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013. Test results reported herein relate only to the item(s) tested.

This revised Test Report (S/N: 1M3107130077-02-R3.RS2) supersedes and replaces the previously issued test report (S/N: 1M3107130077-02-R2.RS2) on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Randy Ortanez  
President



FCC ID: RS2SXVRBT1	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	 SiriusXM SATELLITE RADIO	Approved by: Technical Manager
Test Report S/N: 1M2107130077-02-R3.RS2	Test Dates: 7/14-9/28/2021	EUT Type: Satellite Radio with FM Transmitter and Bluetooth		Page 1 of 47

## TABLE OF CONTENTS

1.0	INTRODUCTION .....	3
1.1	Scope .....	3
1.2	PCTEST Test Location.....	3
1.3	Test Facility / Accreditations.....	3
2.0	PRODUCT INFORMATION.....	4
2.1	Equipment Description .....	4
2.2	Device Capabilities .....	4
2.3	Antenna Description .....	4
2.4	Test Configuration .....	5
2.5	Software and Firmware .....	5
2.6	EMI Suppression Device(s)/Modifications .....	5
3.0	DESCRIPTION OF TESTS .....	6
3.1	Evaluation Procedure .....	6
3.2	Radiated Emissions.....	6
3.3	Environmental Conditions.....	6
4.0	ANTENNA REQUIREMENTS .....	7
5.0	MEASUREMENT UNCERTAINTY .....	8
6.0	TEST EQUIPMENT CALIBRATION DATA .....	9
7.0	TEST RESULTS.....	10
7.1	Summary .....	10
7.2	20dB Bandwidth Measurement .....	11
7.3	Output Power Measurement.....	17
7.4	Band Edge Compliance.....	23
7.5	Carrier Frequency Separation .....	26
7.6	Time of Occupancy.....	28
7.7	Number of Hopping Channels .....	30
7.8	Conducted Spurious Emissions.....	32
7.9	Radiated Spurious Emission Measurements – Above 1GHz.....	36
7.10	Radiated Restricted Band Edge Measurements.....	43
7.11	Radiated Spurious Emissions Measurements – Below 1GHz .....	44
8.0	CONCLUSION.....	47

FCC ID: RS2SXVRBT1	 Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2107130077-02-R3.RS2	Test Dates: 7/14-9/28/2021	EUT Type: Satellite Radio with FM Transmitter and Bluetooth		Page 2 of 47

## 1.0 INTRODUCTION

### 1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

### 1.2 PCTEST Test Location

These measurement tests were conducted at the PCTEST facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014.

### 1.3 Test Facility / Accreditations

**Measurements were performed at PCTEST located in Columbia, MD 21046, U.S.A.**

- PCTEST is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- PCTEST facility is a registered (2451B) test laboratory with the site description on file with ISED.

FCC ID: RS2SXVRBT1	 PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	 SiriusXM SATELLITE RADIO	Approved by: Technical Manager
Test Report S/N: 1M2107130077-02-R3.RS2	Test Dates: 7/14-9/28/2021	EUT Type: Satellite Radio with FM Transmitter and Bluetooth		Page 3 of 47

## 2.0 PRODUCT INFORMATION

### 2.1 Equipment Description

The Equipment Under Test (EUT) is the **Sirius XM Radio Inc. Satellite Radio with FM Transmitter and Bluetooth FCC ID: RS2SXVRBT1**. The test data contained in this report pertains only to the emissions due to the EUT's Bluetooth transmitter.

- This Bluetooth module has been tested by a Bluetooth Qualification Lab, and we confirm the following:
  - A) The hopping sequence is pseudorandom
  - B) All channels are used equally on average
  - C) The receiver input bandwidth equals the transmit bandwidth
  - D) The receiver hops in sequence with the transmit signal
- 15.247(g): In accordance with the Bluetooth Industry Standard, the system is designed to comply with all of the regulations in Section 15.247 when the transmitter is presented with a continuous data (or information) system.
- 15.247(h): In accordance with the Bluetooth Industry Standard, the system does not coordinate its channels selection/hopping sequence with other frequency hopping systems for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters.
- 15.247(h): The EUT employs Adaptive Frequency Hopping (AFH) which identifies sources of interference namely devices operating in 802.11 WLAN and excludes them from the list of available channels. The process of re-mapping reduces the number of test channels from 79 channels to a minimum number of 20 channels.

**Test Device Serial No.:** XQ51UD4Y, Y90VXD8E

### 2.2 Device Capabilities

This device contains the following capabilities:

FM Transmitter and Bluetooth

Ch.	Frequency (MHz)
00	2402
:	:
39	2441
:	:
78	2480

**Table 2-1. Frequency/ Channel Operations**

**Note:** This device is capable of operating in hopping and non-hopping mode. The EUT can hop between 79 different channels in the 2400 – 2483.5MHz band.

### 2.3 Antenna Description

Following antenna was used for the testing.

Frequency [GHz]	Antenna Gain (dBi)
2.4	2.66

**Table 2-2. Antenna Peak Gain**

**Note:** This device is capable of operating in hopping and non-hopping mode. The EUT can hop between 79 different channels in the 2400 – 2483.5MHz band.

FCC ID: RS2SXVRBT1	 PCTEST <sup>®</sup> Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	 SATELLITE RADIO	Approved by: Technical Manager
Test Report S/N: 1M2107130077-02-R3.RS2	Test Dates: 7/14-9/28/2021	EUT Type: Satellite Radio with FM Transmitter and Bluetooth		Page 4 of 47

## 2.4 Test Configuration

The EUT was tested per the guidance of ANSI C63.10-2013. ANSI C63.10-2013 was also used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing. See Sections 3.2 for radiated emissions test setups, and 7.2, 7.3, 7.4, 7.5, 7.6, 7.7, and 7.8 for antenna port conducted emissions test setups.

## 2.5 Software and Firmware

The test was conducted with firmware version 00.05.02 installed on the EUT.

## 2.6 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: RS2SXVRBT1	 PCTEST <sup>®</sup> Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	 SiriusXM SATELLITE RADIO	Approved by: Technical Manager
Test Report S/N: 1M2107130077-02-R3.RS2	Test Dates: 7/14-9/28/2021	EUT Type: Satellite Radio with FM Transmitter and Bluetooth		Page 5 of 47

## 3.0 DESCRIPTION OF TESTS

### 3.1 Evaluation Procedure

The measurement procedure described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10-2013) was used in the measurement of the EUT.

**Deviation from measurement procedure.....**None

### 3.2 Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. An 80cm tall test table made of Styrodur is placed on top of the turn table. For measurements above 1GHz, an additional Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33 depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

All radiated measurements are performed in a chamber that meets the site requirements per ANSI C63.4-2014. Additionally, radiated emissions below 30MHz are also validated on an Open Area Test Site to assert correlation with the chamber measurements per the requirements of KDB 474788 D01.

### 3.3 Environmental Conditions

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

FCC ID: RS2SXVRBT1	 Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2107130077-02-R3.RS2	Test Dates: 7/14-9/28/2021	EUT Type: Satellite Radio with FM Transmitter and Bluetooth		Page 6 of 47

## 4.0 ANTENNA REQUIREMENTS

### Excerpt from §15.203 of the FCC Rules/Regulations:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

- The FM transmit antenna used with the Satellite Radio uses a unique coupling.
- There are no provisions for connection to an external antenna.

### Conclusion:

The EUT complies with the requirement of §15.203.

FCC ID: RS2SXVRBT1	 <b>PCTEST®</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	 <b>SiriusXM</b> SATELLITE RADIO	Approved by: Technical Manager
Test Report S/N: 1M2107130077-02-R3.RS2	Test Dates: 7/14-9/28/2021	EUT Type: Satellite Radio with FM Transmitter and Bluetooth		Page 7 of 47

## 5.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013. All measurement uncertainty values are shown with a coverage factor of  $k = 2$  to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the  $U_{CISPR}$  measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty ( $\pm$ dB)
Conducted Bench Top Measurements	1.13
Conducted Disturbance	3.09
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

FCC ID: RS2SXVRBT1	 PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	 SiriusXM SATELLITE RADIO	Approved by: Technical Manager
Test Report S/N: 1M2107130077-02-R3.RS2	Test Dates: 7/14-9/28/2021	EUT Type: Satellite Radio with FM Transmitter and Bluetooth		Page 8 of 47

## 6.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	N9030A	PXA Signal Analyzer	9/2/2020	Annual	12/2/2021	MY55410501
Emco	3115	Horn Antenna (1-18GHz)	6/18/2020	Biennial	6/18/2022	9704-5182
Rohde & Schwarz	ESU26	EMI Test Receiver (26.5GHz)	5/25/2021	Annual	5/25/2022	100342
Rohde & Schwarz	SFUNIT-Rx	Shielded Filter Unit	6/23/2021	Annual	6/23/2022	102134
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	7/27/2020	Biennial	7/27/2022	A051107
Schwarzbeck	UHA 9105	Dipole Antenna	N/A	N/A	N/A	9105-2404

**Table 6-1. Annual Test Equipment Calibration Schedule**

FCC ID: RS2SXVRBT1	 Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2107130077-02-R3.RS2	Test Dates: 7/14-9/28/2021	EUT Type: Satellite Radio with FM Transmitter and Bluetooth		Page 9 of 47

## 7.0 TEST RESULTS

### 7.1 Summary

Company Name: Sirius XM Radio Inc.  
 FCC ID: RS2SXVRBT1  
 Method/System: Frequency Hopping Spread Spectrum (FHSS)  
 Number of Channels: 79

FCC Part Section(s)	RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
15.247(a)(1)(iii)	RSS-247 [5.1(1)]	20dB Bandwidth	N/A	CONDUCTED	PASS	Section 7.2
15.247(b)(1)	RSS-247 [5.4(2)]	Peak Transmitter Output Power	< 1 Watt if $\geq$ 75 non-overlapping channels used		PASS	Section 7.3
15.247(a)(1)	RSS-247 [5.1(2)]	Channel Separation	> 2/3 of 20 dB BW for systems with Output Power < 125mW		PASS	Section 7.5
15.247(a)(1)(iii)	RSS-247 [5.1(4)]	Number of Channels	> 15 Channels		PASS	Section 7.7
15.247(a)(1)(iii)	RSS-247 [5.1(4)]	Time of Occupancy	< 0.4 sec in 31.6 sec period		PASS	Section 7.6
15.247(d)	RSS-247 [5.5]	Band Edge / Out-of-Band Emissions	Conducted > 20dBc		PASS	Section 7.4, Section 7.8
15.205 15.209	RSS-Gen [8.9]	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209 (RSS-247 limits)	RADIATED	PASS	Section 7.9, Section 7.10, Section 7.11

Table 7-1. Summary of Test Results

#### Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "BT Auto," Version 3.5.
- 5) For radiated band edge, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "Chamber Automation," Version 1.3.1.

FCC ID: RS2SXVRBT1	 Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	 SATELLITE RADIO	Approved by: Technical Manager
Test Report S/N: 1M2107130077-02-R3.RS2	Test Dates: 7/14-9/28/2021	EUT Type: Satellite Radio with FM Transmitter and Bluetooth		Page 10 of 47

## 7.2 20dB Bandwidth Measurement

§15.247 (a.1.iii); RSS-247 [5.1(1)]

### Test Overview and Limit

The bandwidth at 20dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the receive antenna while the EUT is operating in transmission mode at the appropriate frequencies.

### Test Procedure Used

ANSI C63.10-2013 – Section 6.9.2

### Test Settings

1. The signal analyzers' automatic bandwidth measurement capability of the spectrum analyzer was used to perform the 20dB bandwidth measurement. The "X" dB bandwidth parameter was set to X = 20. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% OBW
3. VBW  $\geq 3 \times$  RBW
4. Reference level set to keep signal from exceeding maximum input mixer level for linear operation.
5. Detector = Peak
6. Trace mode = max hold
7. Sweep = auto couple
8. The trace was allowed to stabilize

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-1. Test Instrument & Measurement Setup**


### Test Notes

None

FCC ID: RS2SXVRBT1	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	 SIRIUSXM SATELLITE RADIO	Approved by: Technical Manager
Test Report S/N: 1M2107130077-02-R3.RS2	Test Dates: 7/14-9/28/2021	EUT Type: Satellite Radio with FM Transmitter and Bluetooth		Page 11 of 47


Frequency [MHz]	Data Rate [Mbps]	Mod.	Channel No.	20dB Bandwidth Test Results [kHz]
2402	1.0	GFSK	0	943.0
2441	1.0	GFSK	39	937.6
2480	1.0	GFSK	78	942.4
2402	2.0	$\pi/4$ -DQPSK	0	1370.0
2441	2.0	$\pi/4$ -DQPSK	39	1371.0
2480	2.0	$\pi/4$ -DQPSK	78	1371.0
2402	3.0	8DPSK	0	1355.0
2441	3.0	8DPSK	39	1354.0
2480	3.0	8DPSK	78	1365.0

Table 7-2. Conducted 20dB Bandwidth Measurements




Plot 7-1. 20dB Bandwidth Plot (Bluetooth, 1Mbps – Ch. 0)

FCC ID: RS2SXVRBT1	 <b>PCTEST</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	 <b>SiriusXM</b> SATELLITE RADIO	Approved by: Technical Manager
Test Report S/N: 1M2107130077-02-R3.RS2	Test Dates: 7/14-9/28/2021	EUT Type: Satellite Radio with FM Transmitter and Bluetooth		Page 12 of 47




Plot 7-2. 20dB Bandwidth Plot (Bluetooth, 1Mbps – Ch. 39)




Plot 7-3. 20dB Bandwidth Plot (Bluetooth, 1Mbps – Ch. 78)

FCC ID: RS2SXVRBT1	<b>PCTEST®</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2107130077-02-R3.RS2	Test Dates: 7/14-9/28/2021	EUT Type: Satellite Radio with FM Transmitter and Bluetooth		Page 13 of 47




Plot 7-4. 20dB Bandwidth Plot (Bluetooth, 2Mbps – Ch. 0)



Plot 7-5. 20dB Bandwidth Plot (Bluetooth, 2Mbps – Ch. 39)

FCC ID: RS2SXVRBT1	<b>PCTEST®</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2107130077-02-R3.RS2	Test Dates: 7/14-9/28/2021	EUT Type: Satellite Radio with FM Transmitter and Bluetooth		Page 14 of 47



Plot 7-6. 20dB Bandwidth Plot (Bluetooth, 2Mbps – Ch. 78)




Plot 7-7. 20dB Bandwidth Plot (Bluetooth, 3Mbps – Ch. 0)

FCC ID: RS2SXVRBT1	<b>PCTEST</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2107130077-02-R3.RS2	Test Dates: 7/14-9/28/2021	EUT Type: Satellite Radio with FM Transmitter and Bluetooth		Page 15 of 47



Plot 7-8. 20dB Bandwidth Plot (Bluetooth, 3Mbps – Ch. 39)



Plot 7-9. 20dB Bandwidth Plot (Bluetooth, 3Mbps – Ch. 78)

FCC ID: RS2SXVRBT1	 PCTEST® Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	 SiriusXM SATELLITE RADIO	Approved by: Technical Manager
Test Report S/N: 1M2107130077-02-R3.RS2	Test Dates: 7/14-9/28/2021	EUT Type: Satellite Radio with FM Transmitter and Bluetooth		Page 16 of 47

## 7.3 Output Power Measurement

§15.247 (b.1); RSS-247 [5.4(2)]

### Test Overview and Limits

Measurement is made while the EUT is operating in non-hopping transmission mode. The powers shown below were measured using a spectrum analyzer with a Bluetooth signaling test set (Agilent Model: N4010A) used only to maintain a Bluetooth link with the EUT. Average power measurements are performed using the analyzer's "burst power" function with RBW = 3MHz. The burst power function triggers on a single set burst set to maximum power and measures the maximum average power on the on-time.

***The maximum permissible output power is 1 Watt.***

### Test Procedure Used

ANSI C63.10-2013 – Section 7.8.5

ANSI C63.10-2013 – Section 11.9.2.3.2 method AVGPM-G

### Test Settings

#### Peak Power Measurement

1. Span = approximately 5x 20dB bandwidth, centered on hopping channel
2. RBW > 20dB bandwidth of emission being measured
3. VBW  $\geq$  RBW
4. Sweep = auto
5. Detector = peak
6. Trace mode = max hold
7. The trace was allowed to stabilize

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-2. Test Instrument & Measurement Setup**


Method AVGPM-G (Average Power Measurement)

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter. The trace was averaged over 100 traces to obtain the final measured average power.

FCC ID: RS2SXVRBT1	 <b>PCTEST®</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2107130077-02-R3.RS2	Test Dates: 7/14-9/28/2021	EUT Type: Satellite Radio with FM Transmitter and Bluetooth		Page 17 of 47

Frequency [MHz]	Data Rate [Mbps]	Mod.	Channel No.	Peak Conducted Power	
				[dBm]	[mW]
2402	1.0	GFSK	0	10.70	11.735
2441	1.0	GFSK	39	11.15	13.032
2480	1.0	GFSK	78	10.59	11.447
2402	2.0	$\pi/4$ -DQPSK	0	6.93	4.928
2441	2.0	$\pi/4$ -DQPSK	39	6.52	4.485
2480	2.0	$\pi/4$ -DQPSK	78	6.94	4.947
2402	3.0	8DPSK	0	7.58	5.725
2441	3.0	8DPSK	39	7.29	5.359
2480	3.0	8DPSK	78	7.49	5.610

Table 7-3. Conducted Output Power Measurements



Plot 7-10. Peak Conducted Power (1Mbps – Ch. 0)

FCC ID: RS2SXVRBT1	 <b>PCTEST®</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	 <b>SiriusXM</b> SATELLITE RADIO	Approved by: Technical Manager
Test Report S/N: 1M2107130077-02-R3.RS2	Test Dates: 7/14-9/28/2021	EUT Type: Satellite Radio with FM Transmitter and Bluetooth		Page 18 of 47




Plot 7-11. Peak Conducted Power (1Mbps – Ch. 39)



Plot 7-12. Peak Conducted Power (1Mbps – Ch. 78)

FCC ID: RS2SXVRBT1	 Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2107130077-02-R3.RS2	Test Dates: 7/14-9/28/2021	EUT Type: Satellite Radio with FM Transmitter and Bluetooth		Page 19 of 47



Plot 7-13. Peak Conducted Power (2Mbps – Ch. 0)



Plot 7-14. Peak Conducted Power (2Mbps – Ch. 39)

FCC ID: RS2SXVRBT1	<b>PCTEST®</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2107130077-02-R3.RS2	Test Dates: 7/14-9/28/2021	EUT Type: Satellite Radio with FM Transmitter and Bluetooth		Page 20 of 47




Plot 7-15. Peak Conducted Power (2Mbps – Ch. 78)



Plot 7-16. Peak Conducted Power (3Mbps – Ch. 0)

FCC ID: RS2SXVRBT1	 <b>PCTEST</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	 <b>SiriusXM</b> SATELLITE RADIO	Approved by: Technical Manager
Test Report S/N: 1M2107130077-02-R3.RS2	Test Dates: 7/14-9/28/2021	EUT Type: Satellite Radio with FM Transmitter and Bluetooth		Page 21 of 47



Plot 7-17. Peak Conducted Power (3Mbps – Ch. 39)



Plot 7-18. Peak Conducted Power (3Mbps – Ch. 78)

FCC ID: RS2SXVRBT1	<b>PCTEST</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2107130077-02-R3.RS2	Test Dates: 7/14-9/28/2021	EUT Type: Satellite Radio with FM Transmitter and Bluetooth		Page 22 of 47

## 7.4 Band Edge Compliance

§15.247 (d); RSS-247 [5.5]

### Test Overview and Limits

EUT operates in hopping and non-hopping transmission mode. Measurement is taken at the highest point located outside of the emission bandwidth. ***The maximum permissible out-of-band emission level is 20 dBc.***

### Test Procedure Used

ANSI C63.10-2013 – Section 6.10.4

### Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW = 100kHz
4. VBW = 300kHz
5. Detector = Peak
6. Number of sweep points  $\geq 2 \times \text{Span/RBW}$
7. Trace mode = max hold
8. Sweep time = auto couple
9. The trace was allowed to stabilize

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-3. Test Instrument & Measurement Setup**

### Test Notes

Out of band conducted spurious emissions at the band edge were investigated for all data rates in hopping and non-hopping modes. The worst case emissions were found with the EUT transmitting at 3 Mbps. Band edge emissions were also investigated with the EUT transmitting in all data rates. Plots of the worst case emissions are shown below.

FCC ID: RS2SXVRBT1	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	 SIRIUSXM SATELLITE RADIO	Approved by: Technical Manager
Test Report S/N: 1M2107130077-02-R3.RS2	Test Dates: 7/14-9/28/2021	EUT Type: Satellite Radio with FM Transmitter and Bluetooth		Page 23 of 47




Plot 7-19. Band Edge Plot (Bluetooth with Hopping Disabled, 1 Mbps – Ch. 0)




Plot 7-20. Band Edge Plot (Bluetooth with Hopping Disabled, 1 Mbps – Ch. 78)

FCC ID: RS2SXVRBT1	<b>PCTEST</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2107130077-02-R3.RS2	Test Dates: 7/14-9/28/2021	EUT Type: Satellite Radio with FM Transmitter and Bluetooth		Page 24 of 47



Plot 7-21. Band Edge Plot (Bluetooth with Hopping Enabled, 1 Mbps – Ch. 0)



Plot 7-22. Band Edge Plot (Bluetooth with Hopping Enabled, 1 Mbps – Ch. 78)

FCC ID: RS2SXVRBT1	<b>PCTEST®</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2107130077-02-R3.RS2	Test Dates: 7/14-9/28/2021	EUT Type: Satellite Radio with FM Transmitter and Bluetooth		Page 25 of 47

## 7.5 Carrier Frequency Separation

§15.247 (a.1); RSS-247 [5.1(2)]

### Test Overview and Limit

Measurement is made with EUT operating in hopping mode. ***The minimum permissible channel separation for this system is 2/3 the value of the 20dB BW.***

### Test Procedure Used

ANSI C63.10-2013 – Section 7.8.2

### Test Settings

1. Span = Wide enough to capture peaks of two adjacent channels
2. RBW = 30% of channel spacing. Adjust as necessary to best identify center of each individual channel
3. VBW  $\geq$  RBW
4. Sweep = Auto
5. Detector = Peak
6. Trace mode = max hold
7. The trace was allowed to stabilize.
8. Marker-delta function used to determine separation between peaks of the adjacent channels

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-4. Test Instrument & Measurement Setup**

### Test Notes

The EUT complies with the minimum channel separation requirement when it is operating in 1x/EDR mode using 79 channels and when operating in AFH mode using 20 channels.

FCC ID: RS2SXVRBT1	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	 SIRIUSXM SATELLITE RADIO	Approved by: Technical Manager
Test Report S/N: 1M2107130077-02-R3.RS2	Test Dates: 7/14-9/28/2021	EUT Type: Satellite Radio with FM Transmitter and Bluetooth		Page 26 of 47

Frequency [MHz]	Data Rate [Mbps]	Mod.	Channel No.	Min. Channel Separation [MHz]
2402	1.0	GFSK	0	0.630
2441	1.0	GFSK	39	0.631
2480	1.0	GFSK	78	0.631
2402	2.0	$\pi/4$ -DQPSK	0	0.924
2441	2.0	$\pi/4$ -DQPSK	39	0.913
2480	2.0	$\pi/4$ -DQPSK	78	0.915
2402	3.0	8DPSK	0	0.924
2441	3.0	8DPSK	39	0.904
2480	3.0	8DPSK	78	0.905

Table 7-4. Minimum Channel Separation



Plot 7-23. Channel Spacing Plot (Bluetooth)

FCC ID: RS2SXVRBT1	 <b>PCTEST</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	 <b>SiriusXM</b> SATELLITE RADIO	Approved by: Technical Manager
Test Report S/N: 1M2107130077-02-R3.RS2	Test Dates: 7/14-9/28/2021	EUT Type: Satellite Radio with FM Transmitter and Bluetooth		Page 27 of 47

## 7.6 Time of Occupancy

§15.247 (a.1.iii); RSS-247 [5.1(4)]

### Test Overview and Limit

Measurement is made while EUT is operating in hopping mode with the spectrum analyzer set to zero span. ***The maximum permissible time of occupancy is 400 ms within a period of 400ms multiplied by the number of hopping channels employed.***

### Test Procedure Used

ANSI C63.10-2013 – Section 7.8.4

### Test Settings

1. Span = zero span, centered on a hopping channel
2. RBW  $\leq$  channel spacing and  $\gg 1/T$ , where T is expected dwell time per channel
3. Sweep = as necessary to capture entire dwell time. Second plot may be required to demonstrate two successive hops on a channel
4. Trigger is set with appropriate trigger delay to place pulse near the center of the plot
5. Detector = peak
6. Trace mode = max hold
7. Marker-delta function used to determine transmit time per hop

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




**Figure 7-5. Test Instrument & Measurement Setup**

### Test Notes

None

FCC ID: RS2SXVRBT1	 <b>PCTEST®</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2107130077-02-R3.RS2	Test Dates: 7/14-9/28/2021	EUT Type: Satellite Radio with FM Transmitter and Bluetooth		Page 28 of 47



Plot 7-24. Time of Occupancy Plot (Bluetooth)

### Bluetooth Time of Occupancy Calculation

Typically, Bluetooth 1x/EDR mode has a channel hopping rate of 1600 hops/s. Since 1x/EDR modes use 5 transmit and 1 receive slot, for a total of 6 slots, the Bluetooth transmitter is actually hopping at a rate of  $1600 / 6 = 266.67$  hops/s/slot

- $400\text{ms} \times 79$  hopping channels = 31.6 sec (Time of Occupancy Limit)
- Worst case BT has 266.67 hops/second (for 1x/EDR modes with DH5 operation)
- $266.67 \text{ hops/second} / 79 \text{ channels} = 3.38 \text{ hops/second}$  (# of hops/second on one channel)
- $3.38 \text{ hops/second/channel} \times 31.6 \text{ seconds} = 106.67 \text{ hops}$  (# hops over a 31.6 second period)
- $106.67 \text{ hops} \times 2.885 \text{ ms/channel} = 307.74 \text{ ms}$  (worst case dwell time for one channel in 1x/EDR modes)

With AFH, the number of channels is reduced to a minimum of 20 channels and the channel hopping rate is reduced by 50% to 800 hops/s. AFH mode also uses 6 total slots so the Bluetooth transmitter hops at a rate of  $800 / 6 = 133.3$  hops/s/slot

- $400\text{ms} \times 20$  hopping channels = 8 sec (Time of Occupancy Limit)
- Worst case BT has 133.3 hops/second/slot (for AFH mode with DH5 operation)
- $133.3 \text{ hops/s} / 20 \text{ channels} = 6.67 \text{ hops/second}$  (# of hops/second on one channel)
- $6.67 \text{ hops/s} / \text{channel} \times 8 \text{ seconds} = 53.34 \text{ hops}$  (# hops over a 8 second period)
- $53.34 \text{ hops} \times 2.885 \text{ ms/channel} = 153.89 \text{ ms}$  (worst case dwell time for one channel in AFH mode)

FCC ID: RS2SXVRBT1	<b>PCTEST</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	SiriusXM SATELLITE RADIO	Approved by: Technical Manager
Test Report S/N: 1M2107130077-02-R3.RS2	Test Dates: 7/14-9/28/2021	EUT Type: Satellite Radio with FM Transmitter and Bluetooth		Page 29 of 47

## 7.7 Number of Hopping Channels

§15.247 (a.1.iii); RSS-247 [5.1(4)]

### Test Overview and Limit

Measurement is made while EUT is operating in hopping mode. ***This frequency hopping system must employ a minimum of 15 hopping channels.***

### Test Procedure Used

ANSI C63.10-2013 – Section 7.8.3

### Test Settings

1. Span = frequency of band of operation (divided into two plots)
2. RBW < 30% of channel spacing or 20dB bandwidth, whichever is smaller.
3. VBW  $\geq$  RBW
4. Sweep = auto
5. Detector = peak
6. Trace mode = max hold
7. Trace was allowed to stabilize

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




**Figure 7-6. Test Instrument & Measurement Setup**


### Test Notes

The frequency spectrum was broken up into two sub-ranges to clearly show all of the hopping frequencies. In AFH mode, this device operates using 20 channels so the requirement for minimum number of hopping channels is satisfied.

FCC ID: RS2SXVRBT1	 <b>PCTEST®</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2107130077-02-R3.RS2	Test Dates: 7/14-9/28/2021	EUT Type: Satellite Radio with FM Transmitter and Bluetooth		Page 30 of 47



Plot 7-25. Low End Spectrum Channel Hopping Plot (Bluetooth)



Plot 7-26. High End Spectrum Channel Hopping Plot (Bluetooth)

FCC ID: RS2SXVRBT1	 Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2107130077-02-R3.RS2	Test Dates: 7/14-9/28/2021	EUT Type: Satellite Radio with FM Transmitter and Bluetooth		Page 31 of 47

## 7.8 Conducted Spurious Emissions

§15.247 (d); RSS-247 [5.5]

### Test Overview and Limit

Conducted out-of-band spurious emissions were investigated from 30MHz up to 25GHz to include the 10<sup>th</sup> harmonic of the fundamental transmit frequency. **The maximum permissible out-of-band emission level is 20 dBc.**

### Test Procedure Used

ANSI C63.10-2013 – Section 7.8.8

### Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 25GHz (separated into two plots per channel)
2. RBW = 1MHz\* (See note below)
3. VBW = 3MHz
4. Detector = Peak
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




**Figure 7-7. Test Instrument & Measurement Setup**

### Test Notes

Out-of-band conducted spurious emissions were investigated for all data rates and the worst case emissions were found with the EUT transmitting at 1Mbps. The display line shown in the following plots is the limit at 20dB below the fundamental emission level measured in a 100kHz bandwidth. However, the traces in the following plots are measured with a 1MHz RBW to reduce test time, so the display line may not necessarily appear to be 20dB below the level of the fundamental in a 1MHz bandwidth.

FCC ID: RS2SXVRBT1	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	 SIRIUSXM SATELLITE RADIO	Approved by: Technical Manager
Test Report S/N: 1M2107130077-02-R3.RS2	Test Dates: 7/14-9/28/2021	EUT Type: Satellite Radio with FM Transmitter and Bluetooth		Page 32 of 47




Plot 7-27. Conducted Spurious Plot (Bluetooth, 1Mbps – Ch. 0)




Plot 7-28. Conducted Spurious Plot (Bluetooth, 1Mbps – Ch. 0)

FCC ID: RS2SXVRBT1	<b>PCTEST®</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2107130077-02-R3.RS2	Test Dates: 7/14-9/28/2021	EUT Type: Satellite Radio with FM Transmitter and Bluetooth		Page 33 of 47




Plot 7-29. Conducted Spurious Plot (Bluetooth, 1Mbps – Ch. 39)




Plot 7-30. Conducted Spurious Plot (Bluetooth, 1Mbps – Ch. 39)

FCC ID: RS2SXVRBT1	<b>PCTEST</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2107130077-02-R3.RS2	Test Dates: 7/14-9/28/2021	EUT Type: Satellite Radio with FM Transmitter and Bluetooth		Page 34 of 47



Plot 7-31. Conducted Spurious Plot (Bluetooth, 1Mbps – Ch. 78)



Plot 7-32. Conducted Spurious Plot (Bluetooth, 1Mbps – Ch. 78)

FCC ID: RS2SXVRBT1	<b>PCTEST</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2107130077-02-R3.RS2	Test Dates: 7/14-9/28/2021	EUT Type: Satellite Radio with FM Transmitter and Bluetooth		Page 35 of 47

## 7.9 Radiated Spurious Emission Measurements – Above 1GHz

§15.205 §15.209 §15.247 (d); RSS-Gen [8.9]

### Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at maximum power and at the appropriate frequencies. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

***All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 6 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-5 per Section 15.209 and RSS-Gen (8.9).***

Frequency	Field Strength [ $\mu$ V/m]	Measured Distance [Meters]
Above 960.0 MHz	500	3

**Table 7-5. Radiated Limits**

### Test Procedure Used

ANSI C63.10-2013 – Section 6.6.4.3

### Test Settings

#### Average Field Strength Measurements per Section 4.1.4.2.3 of ANSI C63.10-2013

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW =  $1\text{kHz} \geq 1/\tau \text{ Hz}$ , where  $\tau$  = pulse width in seconds
4. Averaging type was set to RMS to ensure that video filtering was applied in the power domain
5. Detector = peak
6. Sweep time = auto
7. Trace mode = max hold
8. Trace was allowed to stabilize

#### Peak Field Strength Measurements per Section 4.1.4.2.2 of ANSI C63.10-2013

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW is set depending on measurement frequency, as specified in Table 7-6 below
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

FCC ID: RS2SXVRBT1	 PCTEST® Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2107130077-02-R3.RS2	Test Dates: 7/14-9/28/2021	EUT Type: Satellite Radio with FM Transmitter and Bluetooth		Page 36 of 47

Frequency	RBW
9 – 150kHz	200 – 300Hz
0.15 – 30MHz	9 – 10kHz
30 – 1000MHz	100 – 120kHz
> 1000MHz	1MHz

Table 7-6. RBW as a Function of Frequency

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-8. Radiated Test Setup >1GHz

### Test Notes

1. All emissions lying in restricted bands specified in §15.205 and Section 8.10 of RSS-Gen are below the limit shown in Table 7-5.
2. No significant radiated emissions were found in the 2310 - 2390MHz restricted band.
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. This unit was tested while powered by an DC power source.
5. The spectrum is measured from 9kHz to the 10<sup>th</sup> harmonic and the worst-case emissions are reported.
6. The duty cycle correction factor was not applied to noise floor measurements.
7. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. Any emissions found to be within 20dB of the limit are fully investigated and the results are shown in this section.
8. The "-" shown in the following RSE tables are used to denote a noise floor measurement.

FCC ID: RS2SXVRBT1	<b>PCTEST</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2107130077-02-R3.RS2	Test Dates: 7/14-9/28/2021	EUT Type: Satellite Radio with FM Transmitter and Bluetooth		Page 37 of 47

## Sample Calculation

- Field Strength Level [ $\text{dB}_{\mu\text{V/m}}$ ] = Analyzer Level [ $\text{dBm}$ ] + 107 + AFCL [ $\text{dB/m}$ ] + Duty Cycle Correction [ $\text{dB}$ ]
- AFCL [ $\text{dB/m}$ ] = Antenna Factor [ $\text{dB/m}$ ] + Cable Loss [ $\text{dB}$ ]
- Margin [ $\text{dB}$ ] = Field Strength Level [ $\text{dB}_{\mu\text{V/m}}$ ] – Limit [ $\text{dB}_{\mu\text{V/m}}$ ]


## Duty Cycle Correction Factor Calculation

- Channel hop rate = 800 hops/second (AFH Mode)
- Adjusted channel hop rate for DH5 mode = 133.33 hops/second
- Time per channel hop = 1 / 133.33 hops/second = 7.50 ms
- Time to cycle through all channels = 7.50 x 20 channels = 150 ms
- Number of times transmitter hits on one channel = 100 ms / 150 ms = 1 time(s)
- Worst case dwell time = 7.5 ms
- Duty cycle correction factor =  $20\log_{10}(7.5\text{ms}/100\text{ms}) = -22.5 \text{ dB}$


FCC ID: RS2SXVRBT1	 PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	 SiriusXM SATELLITE RADIO	Approved by: Technical Manager
Test Report S/N: 1M2107130077-02-R3.RS2	Test Dates: 7/14-9/28/2021	EUT Type: Satellite Radio with FM Transmitter and Bluetooth		Page 38 of 47

## Radiated Spurious Emission Measurements

§15.205 §15.209 §15.247 (d); RSS-Gen [8.9]




**Plot 7-33. Radiated Spurious Plot above 1GHz (BT - Ch. 0)**



**Plot 7-34. Radiated Spurious Plot above 1GHz (BT – Ch. 39)**

FCC ID: RS2SXVRBT1	<b>PCTEST®</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2107130077-02-R3.RS2	Test Dates: 7/14-9/28/2021	EUT Type: Satellite Radio with FM Transmitter and Bluetooth		Page 39 of 47



**Plot 7-35. Radiated Spurious Plot above 1GHz (BT – Ch. 78)**

FCC ID: RS2SXVRBT1	<b>PCTEST</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2107130077-02-R3.RS2	Test Dates: 7/14-9/28/2021	EUT Type: Satellite Radio with FM Transmitter and Bluetooth		Page 40 of 47

## Radiated Spurious Emission Measurements

§15.205 §15.209 §15.247 (d); RSS-Gen [8.9]

Worst Case Mode:	Bluetooth
Worst Case Data Rate:	1 Mbps
Measurement Distance:	3 Meters
Operating Frequency:	2402MHz
Channel:	0

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Duty Cycle Correction [dB]	Field Strength [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]
4804.00	Avg	H	255	77	-40.65	4.69	-22.50	48.54	53.98	-5.44
4804.00	Peak	H	255	77	-40.43	4.69	0.00	71.26	73.98	-2.72
12010.00	Avg	H	189	116	-65.76	14.77	-22.50	33.51	53.98	-20.47
12010.00	Peak	H	189	116	-60.12	14.77	0.00	61.65	73.98	-12.33

**Table 7-7. Radiated Measurements**

Worst Case Mode:	Bluetooth
Worst Case Data Rate:	1 Mbps
Measurement Distance:	3 Meters
Operating Frequency:	2441MHz
Channel:	39

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Duty Cycle Correction [dB]	Field Strength [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]
4882.00	Avg	H	147	77	-38.06	4.87	-22.50	51.31	53.98	-2.67
4882.00	Peak	H	147	77	-38.93	4.87	0.00	72.94	73.98	-1.04
7323.00	Avg	H	285	272	-60.17	8.39	-22.50	32.72	53.98	-21.26
7323.00	Peak	H	285	272	-57.50	8.39	0.00	57.89	73.98	-16.09
12205.00	Avg	H	186	209	-64.10	13.86	-22.50	34.26	53.98	-19.72
12205.00	Peak	H	186	209	-61.13	13.86	0.00	59.73	73.98	-14.25

**Table 7-8. Radiated Measurements**

FCC ID: RS2SXVRBT1	 Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2107130077-02-R3.RS2	Test Dates: 7/14-9/28/2021	EUT Type: Satellite Radio with FM Transmitter and Bluetooth		Page 41 of 47

## Radiated Spurious Emission Measurements

§15.205 §15.209 §15.247 (d); RSS-Gen [8.9]

Worst Case Mode:	Bluetooth
Worst Case Data Rate:	1 Mbps
Measurement Distance:	3 Meters
Operating Frequency:	2480MHz
Channel:	78

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Duty Cycle Correction [dB]	Field Strength [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]
4960.00	Avg	H	183	178	-42.56	5.50	-22.50	47.44	53.98	-6.54
4960.00	Peak	H	183	178	-41.11	5.50	0.00	71.39	73.98	-2.59
7440.00	Avg	H	268	140	-51.75	7.93	-22.50	40.69	53.98	-13.29
7440.00	Peak	H	268	140	-48.83	7.93	0.00	66.10	73.98	-7.87
12400.00	Avg	H	175	159	-69.50	14.25	-22.50	29.26	53.98	-24.72
12400.00	Peak	H	175	159	-59.70	14.25	0.00	61.55	73.98	-12.42

**Table 7-9. Radiated Measurements**

FCC ID: RS2SXVRBT1	 <b>PCTEST®</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	 <b>SiriusXM</b> SATELLITE RADIO	Approved by: Technical Manager
Test Report S/N: 1M2107130077-02-R3.RS2	Test Dates: 7/14-9/28/2021	EUT Type: Satellite Radio with FM Transmitter and Bluetooth		Page 42 of 47

## 7.10 Radiated Restricted Band Edge Measurements


§15.205 §15.209 §15.247 (d); RSS-Gen [8.9]

The radiated restricted band edge measurements are measured with an EMI test receiver connected to the receive antenna while the EUT is transmitting. Two different amplitude offsets were used depending on whether peak or average measurements were measured. The average measurements use a duty cycle correction factor (DCCF).


The amplitude offset shown in the following plots for average measurements was calculated using the formula:

$$\text{Offset (dB)} = (\text{Antenna Factor} + \text{Cable Loss} + \text{Attenuator}) - \text{Preamplifier Gain} + \text{DCCF}$$

Worst Case Mode:	Bluetooth
Worst Case Data Rate:	1 Mbps
Measurement Distance:	3 Meters
Operating Frequency:	2480MHz
Channel:	78



**Plot 7-36. Radiated Restricted Upper Band Edge Measurement (Average)**



**Plot 7-37. Radiated Restricted Upper Band Edge Measurement (Peak)**

FCC ID: RS2SXVRBT1	 <b>PCTEST®</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	 <b>SiriusXM</b> SATELLITE RADIO	Approved by: Technical Manager
Test Report S/N: 1M2107130077-02-R3.RS2	Test Dates: 7/14-9/28/2021	EUT Type: Satellite Radio with FM Transmitter and Bluetooth		Page 43 of 47

## 7.11 Radiated Spurious Emissions Measurements – Below 1GHz

§15.209; RSS-Gen [8.9]

### Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

***All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 6 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-10 per Section 15.209 and RSS-Gen (8.9).***

Frequency	Field Strength [ $\mu$ V/m]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

**Table 7-10. Radiated Limits**

### Test Procedures Used

ANSI C63.10-2013

### Test Settings


#### Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: RS2SXVRBT1	 Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2107130077-02-R3.RS2	Test Dates: 7/14-9/28/2021	EUT Type: Satellite Radio with FM Transmitter and Bluetooth		Page 44 of 47

## Test Setup

The EUT and measurement equipment were set up as shown in the diagrams below.



**Figure 7-9. Radiated Test Setup < 1GHz**


## Test Notes

1. All emissions lying in restricted bands specified in §15.205 and RSS-Gen (8.10) are below the limit shown in Table 7-10.
2. The broadband receive antenna is manipulated through vertical and horizontal polarizations during the tests. The EUT is manipulated through three orthogonal planes.
3. This unit was tested while powered by an DC power source.
4. The spectrum is investigated using a peak detector and final measurements are recorded using CISPR quasi peak detector. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
5. Emissions were measured at a 3 meter test distance.
6. Emissions are investigated while operating on the center channel of the mode, band, and modulation that produced the worst case results during the transmitter spurious emissions testing.
7. No spurious emissions were detected within 20dB of the limit below 30MHz.
8. The results recorded using the broadband antenna is known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.
9. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. There were no emissions detected in the 30MHz – 1GHz frequency range, as shown in the subsequent plots.

FCC ID: RS2SXVRBT1	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	 SiriusXM SATELLITE RADIO	Approved by: Technical Manager
Test Report S/N: 1M2107130077-02-R3.RS2	Test Dates: 7/14-9/28/2021	EUT Type: Satellite Radio with FM Transmitter and Bluetooth		Page 45 of 47

## Radiated Spurious Emissions Measurements (Below 1GHz)

### §15.209; RSS-Gen [8.9]



Plot 7-38. Radiated Spurious Plot below 1GHz

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turtable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]
49.60	Quasi-Peak	V	101	163	-94.13	13.80	26.67	40.00	-13.33
159.05	Quasi-Peak	V	118	302	-97.53	17.58	27.05	43.52	-16.47
311.95	Quasi-Peak	V	207	261	-94.50	18.33	30.83	46.02	-15.19
360.00	Quasi-Peak	H	255	14	-93.86	19.07	31.75	46.02	-14.27
450.00	Quasi-Peak	V	228	112	-90.25	20.97	34.11	46.02	-11.91
836.80	Quasi-Peak	V	102	82	-97.67	25.07	41.82	46.02	-4.20

Table 7-11. Radiated Spurious Emissions Below 1GHz

FCC ID: RS2SXVRBT1	 Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2107130077-02-R3.RS2	Test Dates: 7/14-9/28/2021	EUT Type: Satellite Radio with FM Transmitter and Bluetooth		Page 46 of 47

## 8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Sirius XM Radio Inc. Satellite Radio with FM Transmitter and Bluetooth FCC ID: RS2SXVRBT1** is in compliance with Part 15 Subpart C (15.247) of the FCC Rules.

FCC ID: RS2SXVRBT1	 Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	 SATELLITE RADIO	Approved by: Technical Manager
Test Report S/N: 1M2107130077-02-R3.RS2	Test Dates: 7/14-9/28/2021	EUT Type: Satellite Radio with FM Transmitter and Bluetooth		Page 47 of 47