

TEST REPORT

REPORT NUMBER: B08GC5372-FCC-BT

ON

Type of Equipment: GSM/GPRS Mobile Phone (Tri Band GSM
850/1800/1900) handheld Cellular phone
Type of Designation: M3EQ
Manufacturer: Ezze Mobile Tech.,Inc

ACCORDING TO
FCC Part 15, FREQUENCY Hopping Spread Spectrum
Transceiver

PART 15 subpart C 15.247

China Telecommunication Technology Labs.

Month date, year
June, 15, 2008

Signature



He Guili
Director

FCC ID: RV2M3E
Report Date: 2008-06-15

Test Firm Name: China Telecommunication Technology Labs
Registration Number: 840587

Statement

The measurements shown in this report were made in accordance with the procedures described on test pages. All reported tests were carried out on a sample equipment to demonstrate limited compliance with FCC Parts 15, subpart C 15.247. The sample tested was found to comply with the requirements defined in the applied rules.

CONTENTS

1 GENERAL INFORMATION	4
1.1 NOTES	4
1.2 TESTERS	5
1.3 TESTING LABORATORY INFORMATION	7
1.4 DETAILS OF APPLICANT OR MANUFACTURER	8
2 TEST ITEM	9
2.1 GENERAL INFORMATION	9
2.2 OUTLINE OF EUT	9
2.3 MODIFICATIONS INCORPORATED IN EUT	9
2.4 EQUIPMENT CONFIGURATION	9
2.5 OTHER INFORMATION	10
3 SUMMARY OF TEST RESULTS	11
4 TEST RESULTS	12
4.1 PEAK POWER	12
4.2 BAND EDGES (CONDUCTED)	15
4.3 BAND EDGES MEASUREMENT (RADIATED)	18
4.4 FREQUENCY SEPARATION	23
4.5 NUMBER OF HOPPING FREQUENCY	26
4.6 TIME OF OCCUPANCY	28
4.7 SPURIOUS MEASUREMENT (CONDUCTED)	31
4.8 RADIATED SPURIOUS MEASUREMENT	34
4.9 POWER LINE CONDUCTED EMISSIONS	36
ANNEX A EUT PHOTOS	38
ANNEX B DEVIATIONS FROM PRESCRIBED TEST METHODS	44

1 General Information

1.1 Notes

All reported tests were carried out on a sample equipment to demonstrate limited compliance with FCC Parts 15, subpart C 15.247.

The test results of this test report relate exclusively to the item(s) tested as specified in section 2.


The following deviation from, additions to, or exclusions from the test specifications have been made. See Annex B.


China Telecommunication Technology Labs.(CTTL) authorizes the applicant or manufacturer (see section 1.4) to reproduce this report provided, and the test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of director of CTTL Mr. He Guili.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. CTTL accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report.


1.2 Testers

Name: Lv Ke
Position: Engineer
Department: Department of EMC test
Duration of the test: 2008-06-01 and 2008-06-03
Signature: 

Name: Yuan Yuan
Position: Engineer
Department: Department of EMC test
Duration of the test: 2008-06-05
Signature: 

Name: Li Guoqing
Position: Engineer
Department: Department of EMC test
Duration of the test: 2008-06-01
Signature: 

Editor of this test report:

Name: Li Guoqing
Position: Engineer
Department: Department of EMC test
Date: 2008-06-15
Signature: 

FCC Parts 15 subpart C 15.247
Equipment: M3EQ

REPORT NO.: B08GC5372-FCC-BT

Technical responsibility for area of testing:


Name: Zou Dongyi

Position: Manager

Department: Department of EMC test

Date: 2008-06-15

Signature:



1.3 Testing Laboratory information

1.3.1 Location

Name: China Telecommunication Technology Labs.
Address: No. 11, Yue Tan Nan Jie, Xi Cheng District
BEIJING
P. R. CHINA, 100083
Tel: +86 10 68094053
Fax: +86 10 68011404
Email: emc@chinattl.com

1.3.2 Details of accreditation status

Accredited by: China National Accreditation for Laboratory (CNAL)
Registration number: CNAL Registration No.L0570
Standard: ISO/IEC 17025:2005

1.3.3 Test location, where different from section 1.3.1

Name: -----
Street: -----
City: -----
Country: -----
Telephone: -----
Fax: -----
Postcode: -----

1.4 Details of applicant or manufacturer

1.4.1 Applicant

Name: Ezze Mobile Tech., Inc
Address: 1F, Bubmusa Bldg., 151-31, Nonhyun-dong,
Kangnam-ku, Seoul
Country: Korea
Telephone: 82-2-519-7802
Fax: 82-2-519-7882
Contact: Robin Jang
Telephone: +82-2-519-7802
Email: robinjang@ezzemobile.com

1.4.2 Manufacturer (if different from applicant in section 1.4.1)

Name: --
Address: --
City: --
Country: --

1.4.3 Manufactory (if different from applicant in section 1.4.1)

Name: --
Address: --

2 Test Item

2.1 General Information

Manufacturer: Ezze Mobile Tech., Inc

Name: GSM/GPRS Mobile Phone (Tri Band GSM 850/1800/1900) handheld Cellular phone

Model Number: M3EQ

Serial Number: --

Production Status: Product

Receipt date of test item: 2008-05-28

2.2 Outline of EUT

E.U.T. is a GSM/GPRS Mobile Phone (Tri Band GSM 850/1800/1900) handheld Cellular phone.

2.3 Modifications Incorporated in EUT

The EUT has not been modified from what is described by the brand name and unique type identification stated above.

2.4 Equipment Configuration

Equipment configuration list:

Item	Generic Description	Manufacturer	Type	Serial No.	Remarks
A	Mobile Station	Ezze Mobile Tech., Inc	M3EQ	--	None
B	Adapter	DE MING ELECTRONIC CO., LTD	USB type charger (JYCC-228D)	--	None
C	Battery	Shenzhen ZhiYin ELECTRONIC CO., LTD.	Lithium Ion Rechargeable Battery (ICP043443B/ NEC)	--	None
D	Headset	Rich star	Wire Type	--	None

Cables:

Item	Cable Type	Manufacturer	Length	Shield	Quantity	Remarks
1	DC cable on Adapter	Unknown	1.0m	No	1	None

2.5 Other Information

(a) Adaptor information:

Input: 100-240VAC 50-60Hz

Output: 5.0V

(b) Battery information:

3.7VDC 750mAh

Test Report

3 Summary of Test Results

A brief summary of the tests carried out is shown as following.

	Name of Test	Result
1、	Peak power	Pass
2、	Band edge (conducted)	Pass
3、	Band edge (radiated)	Pass
4、	Frequency separation	Pass
5、	Number of hopping frequency	Pass
6、	Time of occupancy	Pass
7、	Spurious emission (conducted)	Pass
8、	Spurious emission (radiated)	Pass
9、	Power line Conducted Emissions	Pass
Note: none		

4 Test Results

4.1 Peak power

Specifications:	15.247 (b)(3)(i),(ii)and(iii)					
Date of Tests	2008-06-05					
Test conditions:	Ambient Temperature:15℃-35℃ Relative Humidity:30%-60% Air pressure: 86-106kPa					
Operation Mode	Fix channel transmit					
Test Results:	Pass					
Test equipment Used:						
Asset Number	Description	Manufacturer	Model Number	Serial Number	Cal Due	State
7805	EMI Test Receiver	R/S	ESI26	100211	2009-01-03	Normal
7330	Universal Radio Communications Tester	R&S	CMU200	100233	2009-02-22	Normal

Test Setup:

The Universal Radio Communications Tester was used to set the TX channel and power level. The transmitter output is connected to Spectrum analyzer through a coupling.

Note: cable loss is 8 dB

Test Results:


channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Result
0	2402	-1.27	30	Pass
39	2441	-0.34	30	Pass
78	2480	-0.34	30	pass

FCC Parts 15 subpart C 15.247
Equipment: M3EQ

REPORT NO.: B08GC5372-FCC-BT


Test Data:

Channel 0:



Date: 5.JUN.2008 17:11:53

Channel 39




Date: 5.JUN.2008 17:11:08



FCC Parts 15 subpart C 15.247
Equipment: M3EQ

REPORT NO.: B08GC5372-FCC-BT

Channel 78



Date: 5.JUN.2008 17:12:34

4.2 Band edges (conducted)

Specifications:	15.247 (d)					
Date of Tests	2008-06-01					
Test conditions:	Ambient Temperature:15℃-35℃ Relative Humidity:30%-60% Air pressure: 86-106kPa					
Operation Mode	Fix channel transmit					
Test Results:	Pass					
Test equipment Used:						
Asset Number	Description	Manufacturer	Model Number	Serial Number	Cal Due	State
7805	EMI Test Receiver	R/S	ESI26	100211	2009-01-03	Normal
7330	Universal Radio Communications Tester	R&S	CMU200	100233	2009-02-22	Normal

Test Setup:


The Universal Radio Communications Tester was used to set the TX channel and power level. The transmitter output is connected to Spectrum analyzer through a coupling.

FCC Parts 15 subpart C 15.247
Equipment: M3EQ

REPORT NO.: B08GC5372-FCC-BT


Test data:

Hopping frequency mode, left band edge



Date: 1.JUN.2008 17:38:02


Fixed frequency mode, Channel 0 left band edge




FCC Parts 15 subpart C 15.247
Equipment: M3EQ

REPORT NO.: B08GC5372-FCC-BT

Hopping frequency mode, right band edge



Fixed frequency mode, Channel 78 right band edge



4.3 Band edges measurement (Radiated)

Specifications:	15.247 (c); 15.205(a) and 15.209(a)					
Date of Tests	2008-06-01					
Test conditions:	Ambient Temperature:15℃-35℃ Relative Humidity:30%-60% Air pressure: 86-106kPa					
Operation Mode	Fix channel transmit					
Test Results:	Pass					
Test equipment Used:						
Asset Number	Description	Manufacturer	Model Number	Serial Number	Cal Due	State
7805	EMI Test Receiver	R/S	ESI26	100211	2009-01-03	Normal
7330	Horn Antenna	R/S	HF906	100037	2010-01-09	Normal
713	Fully-Anechoic Chamber	ETS	11.8m×6.5m×6.3m	--	2010-11-16	Normal
7330	Universal Radio Communications Tester	R&S	CMU200	100233	2009-02-22	Normal

Test Setup:

The EUT was placed in an anechoic chamber. The Universal Radio Communications Tester was used to set the TX channel and power level. The transmitter output is connected to Spectrum analyzer through a Horn antenna.

Test method:


Use peak and average detector to measure band edges.

Test should be performing under Vertical and Horizontal modes.

FCC Parts 15 subpart C 15.247
Equipment: M3EQ


REPORT NO.: B08GC5372-FCC-BT

Test data:
Channel 0
Vertical
Peak mode:



Date: 1.JUN.2008 14:30:59

Average mode:




Date: 1.JUN.2008 15:32:27

FCC Parts 15 subpart C 15.247
Equipment: M3EQ


REPORT NO.: B08GC5372-FCC-BT

Channel 0
Horizontal
Peak mode:



Date: 1.JUN.2008 14:32:06

Average mode:



Date: 1.JUN.2008 15:33:45


FCC Parts 15 subpart C 15.247
Equipment: M3EQ

REPORT NO.: B08GC5372-FCC-BT

Channel 78


Vertical

Peak mode:



Date: 1. JUN. 2008 14:38:47

Average mode:




Date: 1. JUN. 2008 15:38:21


FCC Parts 15 subpart C 15.247
Equipment: M3EQ

REPORT NO.: B08GC5372-FCC-BT

Channel 78
Horizontal
Peak mode:



Average mode:



4.4 Frequency separation

Specifications:	15.247(a)(1)					
Date of Test	2008-06-01					
Test conditions:	Ambient Temperature:15℃-35℃ Relative Humidity:30%-60% Air pressure: 86-106kPa					
Operation Mode	Fix channel transmit					
Test Results:	Pass					
Test equipment Used:						
Asset Number	Description	Manufacturer	Model Number	Serial Number	Cal Due	State
7805	EMI Test Receiver	R/S	ESI26	100211	2009-01-03	Normal
7330	Universal Radio Communications Tester	R&S	CMU200	100233	2009-02-22	Normal

Test Setup

The Universal Radio Communications Tester was used to set the TX channel and power level. The transmitter output is connected to Spectrum analyzer through a coupling.

Test Result:


Channel separation (kHz)	20dB Bandwidth (kHz)		Limit (kHz)	Result
998	Ch 0	1148	>25	Pass
	Ch 39	1148	>25	Pass
	Ch 78	1148	>25	Pass

FCC Parts 15 subpart C 15.247
Equipment: M3EQ


REPORT NO.: B08GC5372-FCC-BT

Test data:

Channel Separation




20dB Bandwidth (Ch 0)



FCC Parts 15 subpart C 15.247
Equipment: M3EQ


REPORT NO.: B08GC5372-FCC-BT

20dB Bandwidth (Ch 39)



Date: 1.JUN.2008 17:56:37

20dB Bandwidth (Ch 78)



Date: 1.JUN.2008 17:58:06

4.5 Number of hopping frequency

Specifications:	15.247(a)(1)(ii)					
Date of Test	2008-06-01					
Test conditions:	Ambient Temperature:15℃-35℃ Relative Humidity:30%-60% Air pressure: 86-106kPa					
Operation Mode	hopping					
Test Results:	Pass					
Test equipment Used:						
Asset Number	Description	Manufacturer	Model Number	Serial Number	Cal Due	State
7805	EMI Test Receiver	R/S	ESI26	100211	2009-01-03	Normal
7330	Universal Radio Communications Tester	R&S	CMU200	100233	2009-02-22	Normal

Test Setup

The Universal Radio Communications Tester was used to set the TX channel and power level. The transmitter output is connected to Spectrum analyzer through a coupling.

Test Result:

Result (No. of Ch)	Limit (No. of Ch)	Result
79	>75	Pass

FCC Parts 15 subpart C 15.247
Equipment: M3EQ

REPORT NO.: B08GC5372-FCC-BT

Test data:

Channel Number

 Marker 1 [T1]

Ref Lvl

8 dBm

-6.76 dBm

2.48002104 GHz


RBW 300 kHz

VBW 1 MHz

SWT 5 ms

RF Att 30 dB

Unit dBm



Date: 1.JUN.2008 18:01:06

4.6 Time of occupancy

Specifications:	15.247(a)(1)(iii)					
Date of Test	2008-06-01					
Test conditions:	Ambient Temperature:15℃-35℃ Relative Humidity:30%-60% Air pressure: 86-106kPa					
Operation Mode	Fix channel					
Test Results:	Pass					
Test equipment Used:						
Asset Number	Description	Manufacturer	Model Number	Serial Number	Cal Due	State
7805	EMI Test Receiver	R/S	ESI26	100211	2009-01-03	Normal
7330	Universal Radio Communications Tester	R&S	CMU200	100233	2009-02-22	Normal

Test Setup

The Universal Radio Communications Tester was used to set the TX channel and power level. The transmitter output is connected to Spectrum analyzer through a coupling.

Test Result:**Function for DH5:**


$$\text{Total Dwell Time} = \text{pulsetime} \times \left(\frac{1600}{6} \right) / 79 \times 31.6$$

Channel	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
0	2.963	316.1	31.6	400	Pass
39	2.966	316.4	31.6		Pass
78	2.821	300.9	31.6		Pass


FCC Parts 15 subpart C 15.247
Equipment: M3EQ

REPORT NO.: B08GC5372-FCC-BT

Test data:
Channel 0




Channel 39



FCC Parts 15 subpart C 15.247
Equipment: M3EQ

REPORT NO.: B08GC5372-FCC-BT

Channel 78



Date: 1.JUN.2008 18:13:20

4.7 Spurious Measurement (Conducted)

Specifications:	15.209(a) and 15.205(a)					
Date of Test	2008-06-01					
Test conditions:	Ambient Temperature:15℃ -35℃ Relative Humidity:30%-60% Air pressure: 86-106kPa					
Operation Mode	Fix channel transmit					
Test Results:	Pass					
Test equipment Used:						
Asset Number	Description	Manufacturer	Model Number	Serial Number	Cal Due	State
7805	EMI Test Receiver	R/S	ESI26	100211	2009-01-03	Normal
7330	Universal Radio Communications Tester	R&S	CMU200	100233	2009-02-22	Normal

Test Setup

The Universal Radio Communications Tester was used to set the TX channel and power level. The transmitter output is connected to Spectrum analyzer through a coupling.


Test Result:

Channel	Result
0	Pass
39	Pass
78	Pass

FCC Parts 15 subpart C 15.247
Equipment: M3EQ


REPORT NO.: B08GC5372-FCC-BT

Test data:
Channel 0



Date: 1.JUN.2008 18:17:45

Channel 39




Date: 1.JUN.2008 18:19:31



FCC Parts 15 subpart C 15.247
Equipment: M3EQ

REPORT NO.: B08GC5372-FCC-BT

Channel 78



Date: 1.JUN.2008 18:21:43

4.8 Radiated Spurious Measurement

Specifications:	15.209(a) and 15.205(a)					
Date of Test	2008-06-03					
Test conditions:	Ambient Temperature:15℃-35℃ Relative Humidity:30%-60% Air pressure: 86-106kPa					
Operation Mode	hopping					
Test Results:	Fix channel transmit					
Test equipment Used:						
Asset Number	Description	Manufacturer	Model Number	Serial Number	Cal Due	State
7805	EMI Test Receiver	R/S	ESI26	100211	2009-01-03	Normal
713	Fully-Anechoic Chamber	ETS	11.8m×6.5m×6.3m	--	2010-11-16	Normal
7330	Universal Radio Communications Tester	R&S	CMU200	100233	2009-02-22	Normal

Test Setup

The EUT was placed in an anechoic chamber. The CMU 200 was used to set the TX channel and power level. The transmitter output is connected to Spectrum analyzer through a Bilog antenna (for frequency under 1GHz) or a horn antenna (for frequency above 1GHz).

Limit:

Frequency (MHz)	Field Strength (uV/m)	Measurement Distance (m)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

FCC Parts 15 subpart C 15.247
Equipment: M3EQ

REPORT NO.: B08GC5372-FCC-BT

Test result:
9kHz-30MHz

There is No frequency exceeds and near limit line in 20dB scope blow.

The test method is magnetic measurement using loop antenna.

30MHz-1GHz:

Frequency [MHz]	Level [dBuV/m]	Limit [dBuV/m]	Antenna height [cm]	Turntable azimuth [degree]	Antenna polarization [V/H]
31.560000	38.4	40.0	100	225	VERTICAL
86.640000	30.2	40.0	179	78	VERTICAL
497.760000	42.5	46.0	100	148	HORIZONTAL

Note: --

Above 1GHz:

Channel 0:

Frequency[GHz]	Level[dBuV/m]	Limit[dBuV/m]	Antenna Polarization[V/H]	Detector
--	--	--	--	Peak
--	--	--	--	Average

Channel 39:

Frequency[GHz]	Level[dBuV/m]	Limit[dBuV/m]	Antenna Polarization[V/H]	Detector
--	--	--	--	Peak
--	--	--	--	Average

Channel 78:

Frequency[GHz]	Level[dBuV/m]	Limit[dBuV/m]	Antenna Polarization[V/H]	Detector
--	--	--	--	Peak
--	--	--	--	Average

Note:

1. Test from 1GHz up to 10th harmonic of operating frequency.
2. 2.4~2.4835GHz band is the operating frequency.

4.9 Power line Conducted Emissions

Specifications:	ANSI C63.4 voltage mains test					
Date of Test	2008-06-05					
Test conditions:	Ambient Temperature:15℃-35℃ Relative Humidity:30%-60% Air pressure: 86-106kPa					
Operation Mode	Hopping					
Test Results:	Pass					
Test equipment Used:						
Asset Number	Description	Manufacturer	Model Number	Serial Number	Cal Due	State
7805	EMI Test Receiver	R/S	ESI26	100211	2009-01-03	Normal
7330	Artificial Mains Network	R/S	ESH2-Z5	837480/002	2009-01-9	Normal
714	Shielding Room	ETS	--	19003	2010-11-16	Normal
7330	Universal Radio Communications Tester	R&S	CMU200	100233	2009-02-22	Normal

Test Setup

The EUT was placed in a shielding room. The Universal Radio Communications Tester was used to set the TX channel and power level. The ac adapter output is connected to Spectrum analyzer through an AMN (Artificial Mains Network).


Limits of the conducted disturbance at the AC mains ports:

Frequency range	Limit(Quasi-peak)	Limit(Average)
0.15 MHz to 0.5 MHz	66 dBμV – 56 dBμV	56 dBμV – 46 dBμV
>0.5 MHz to 5MHz	56 dBμV	46 dBμV
>5 MHz to 30 MHz	60 dBμV	50 dBμV
NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.		

Test Result:

Pass					
Detector (QP/AV)	Frequency (MHz)	Level (dBμV)	Limit (dBμV)	Line	PE
--	--	--	--	--	--
Remarks: No frequency exceeds the limit.					

Test data:



Annex A EUT Photos



Front view with flip close




Front view with flip open

FCC Parts 15 subpart C 15.247
Equipment: M3EQ

REPORT NO.: B08GC5372-FCC-BT



Back view




Adaptor

FCC Parts 15 subpart C 15.247
Equipment: M3EQ

REPORT NO.: B08GC5372-FCC-BT



cable




Battery

FCC Parts 15 subpart C 15.247
Equipment: M3EQ

REPORT NO.: B08GC5372-FCC-BT




Earphone




Main board (face)

FCC Parts 15 subpart C 15.247
Equipment: M3EQ

REPORT NO.: B08GC5372-FCC-BT




Main board (back)



Adaptor face

FCC Parts 15 subpart C 15.247
Equipment: M3EQ

REPORT NO.: B08GC5372-FCC-BT



Adaptor back

ANNEX B Deviations from Prescribed Test Methods

No deviation from Prescribed Test Methods.

_____ The End of this Report _____

CTL Test Report