



Maximum Permissible Exposure Evaluation

FCC ID: RYK-WNFS267AXIBT

Report No.	:	TBR-C-202503-0098-1
Applicant	:	SparkLAN Communications, Inc.
Equipment Under Test (EUT)		
EUT Name	:	IEEE 802.11ax/ac/a/b/g/n 2x2 WiFi 6E with Bluetooth5.3 Combo Module
Model No.	:	WNFS-267AXI(BT)
Series Model No.	:	AP12676_SDM2, AP6676SDSR
Brand Name	:	SparkLAN, Ampak
Sample ID	:	HC-C-202503-0098-01-01-1#&HC-C-202503-0098-01-01-2#
Receipt Date	:	2025-04-08
Test Date	:	2025-04-08 to 2025-06-30
Issue Date	:	2025-07-02
Standards	:	FCC Part 2.1091
Test Method	:	KDB 447498 D01 General RF Exposure Guidance v06
Conclusions	:	PASS
In the configuration tested, the EUT complied with the standards specified above.		
Test By	:	<i>Rick Chan</i> Rick Chan
Reviewed By	:	<i>Wade Lv</i> Wade Lv
Approved By	:	<i>Ivan Su</i> Ivan Su

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in the report.

CONTENTS

CONTENTS.....	2
1. GENERAL INFORMATION ABOUT EUT.....	4
1.1 Client Information.....	4
1.2 General Description of EUT (Equipment Under Test)	4
2. MEASUREMENT UNCERTAINTY	5
3. TEST FACILITY.....	6
4. METHOD OF MEASUREMENT FOR FCC.....	7
5. TEST RESULT.....	8



Revision History



1. General Information about EUT

1.1 Client Information

Applicant	:	SparkLAN Communications, Inc.
Address	:	5F, No. 199, Ruihu St., Neihu Dist., Taipei City 114067, Taiwan (R.O.C.)
Manufacturer	:	SparkLAN Communications, Inc.
Address	:	5F, No. 199, Ruihu St., Neihu Dist., Taipei City 114067, Taiwan (R.O.C.)

1.2 General Description of EUT (Equipment Under Test)

EUT Name	:	IEEE 802.11ax/ac/a/b/g/n 2x2 WiFi 6E with Bluetooth5.3 Combo Module															
Models No.	:	WNFS-267AXI(BT), AP12676_SDM2, AP6676SDSR															
Model Difference	:	<table border="1"> <thead> <tr> <th>Brand</th> <th>Model</th> <th>Difference</th> </tr> </thead> <tbody> <tr> <td>SparkLAN</td> <td>WNFS-267AX(BT)</td> <td></td> </tr> <tr> <td>Ampak</td> <td>AP12676_SDM2</td> <td>Same as WNFS-267AX(BT),Marketing purpose only</td> </tr> <tr> <td>SparkLAN</td> <td>AP6676SDSR</td> <td>AP6676SDSR that is SIP module is main RF part of WNFS-267AX(BT)&AP12676_SDM2</td> </tr> <tr> <td>Ampak</td> <td></td> <td></td> </tr> </tbody> </table> <p>*Except above change,there are no change to technical construction that is included circuit diagram,PCB layout,components and component layout,all electrical construction and mechanical construction.</p>	Brand	Model	Difference	SparkLAN	WNFS-267AX(BT)		Ampak	AP12676_SDM2	Same as WNFS-267AX(BT),Marketing purpose only	SparkLAN	AP6676SDSR	AP6676SDSR that is SIP module is main RF part of WNFS-267AX(BT)&AP12676_SDM2	Ampak		
Brand	Model	Difference															
SparkLAN	WNFS-267AX(BT)																
Ampak	AP12676_SDM2	Same as WNFS-267AX(BT),Marketing purpose only															
SparkLAN	AP6676SDSR	AP6676SDSR that is SIP module is main RF part of WNFS-267AX(BT)&AP12676_SDM2															
Ampak																	
Product Description	:	<p>Operation Frequency:</p> <p>Bluetooth V5.3: 2402MHz~2480MHz 802.11b/g/n(HT20): 2412MHz~2462MHz 802.11ax(HE20): 2412MHz~2462MHz U-NII-1: 5180MHz~5240MHz U-NII-2A: 5260MHz~5320MHz U-NII-2C: 5500MHz~5720MHz U-NII-3: 5745MHz~5825MHz U-NII-5: 5955MHz~6415MHz U-NII-6: 6435MHz~6515MHz U-NII-7: 6535MHz~6875MHz U-NII-8: 6895MHz~7115MHz</p> <p>Modulation Type:</p> <p>Bluetooth & BLE: GFSK, Pi/4-DQPSK, 8DPSK 802.11b: DSSS (DQPSK, DBPSK, CCK) 802.11g: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11a: OFDM (QPSK, BPSK, 16QAM, 64QAM) 802.11n: OFDM (QPSK, BPSK, 16QAM, 64QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)</p>															
Power Rating	:	DC 3.3V															
Software Version	:	wl0: Jun 12 2024 16:55:30 version 18.40.98 (WLTEST)(g1527f835) FWID 01-9522ca94															
Hardware Version	:	V00															
Remark:	The above antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.																



2. Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

Test Item	Parameters	Expanded Uncertainty (U_{Lab})
Conducted Emission	Level Accuracy: 9kHz~150kHz 150kHz to 30MHz	± 3.50 dB ± 3.10 dB
Radiated Emission	Level Accuracy: 9kHz to 30 MHz	± 4.60 dB
Radiated Emission	Level Accuracy: 30MHz to 1000 MHz	± 4.50 dB
Radiated Emission	Level Accuracy: Above 1000MHz	± 4.20 dB
RF Power-Conducted	Level Accuracy: Above 1000MHz	± 0.95 dB
Power Spectral Density-Conducted	Level Accuracy: Above 1000MHz	± 3 dB
Occupied Bandwidth	Level Accuracy: 30MHz to 1000 MHz Above 1000MHz	$\pm 3.8\%$
Unwanted Emission-Conducted	Level Accuracy: 30MHz to 1000 MHz Above 1000MHz	± 2.72 dB
Temperature	/	$\pm 0.6^{\circ}\text{C}$
Humidity	/	$\pm 4\%$
Supply voltages	/	$\pm 2\%$
Time	/	$\pm 4\%$



3. Test Facility

The testing report were performed by the Shenzhen Toby Technology Co., Ltd., in their facilities located at 1/F., Building 6, Rundongsheng Industrial Zone, Longzhu, Xixiang, Bao'an District, Shenzhen, Guangdong, China. At the time of testing, the following bodies accredited the Laboratory:

CNAS (L5813)

The Laboratory has been accredited by CNAS to ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories for the competence in the field of testing. And the Registration No.: CNAS L5813.

A2LA Certificate No.: 4750.01

The laboratory has been accredited by American Association for Laboratory Accreditation(A2LA) to ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories for the technical competence in the field of Electrical Testing. And the A2LA Certificate No.: 4750.01.FCC Accredited Test Site Number: 854351. Designation Number: CN1223.

IC Registration No.: (11950A)

The Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing. The site registration: Site# 11950A. CAB identifier: CN0056.



4. Method of Measurement for FCC

4.1 EUT Operation Condition:

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.2 Exposure Evaluation:

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = (PG)/4\pi R^2$$

Where

S: power density

P: power input to the antenna

G: power gain of the antenna in the direction of interest relative to an isotropic radiator.

R: distance to the center of radiation of the antenna

4.3 Simultaneous transmission MPE Considerations

According to KDB447498 D01 v06: All transmitters and antennas in the host must be either evaluated for MPE compliance, by measurement or computational modeling, or qualify for the standalone MPE test exclusion in section 7.1. Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modeled or measured field strengths or power density, is ≤ 1.0 . This means that:

$$\sum \text{ of MPE ratios} \leq 1.0$$



5. Test Result

Worst MPE Result							
Test Mode	Antenna	Conducted Power(max) (dBm)	Turn-up Power (dB)	Max tune up power (dBm) [P]	Max. ANT Gain (dBi) [G]	Distance (cm) [R]	Power Density (mW/ cm ²) [S]
2.4G g	total	16.68	16±1	17	5.96	20	0.03933
2.4G n20	total	16.46	16±1	17	5.96	20	0.03933
2.4G ax20	total	14.44	14±1	15	5.96	20	0.02482
5G a	total	21.75	21±1	22	6.34	20	0.13575
5G n20	total	21.84	21±1	22	6.34	20	0.13575
5G n40	total	21.37	21±1	22	6.34	20	0.13575
5G ac20	total	21.76	21±1	22	6.34	20	0.13575
5G ac40	total	21.52	21±1	22	6.34	20	0.13575
5G ac80	total	20.74	20±1	21	6.34	20	0.10783
5G ax20	total	24.20	24±1	25	6.34	20	0.27085
5G ax40	total	21.80	21±1	22	6.34	20	0.13575
5G ax80	total	21.20	21±1	22	6.34	20	0.13575
6G ax20	total	0.4	0±1	1	6.34	20	0.00108
6G ax40	total	3.99	3±1	4	6.34	20	0.00215
6G ax80	total	4.99	4±1	5	6.34	20	0.00271

Note: The antenna gain used max. antenna gain

Conclusion:

As specified in Table 1B of 47 CFR 1.1310- Limits for Maximum Permissible Exposure (MPE),

Limits for General Population/ Uncontrolled Exposure

Frequency Range (MHz)	Power density (mW/ cm ²)
300-1,500	F/1500
1,500-100,000	1.0

For BT&2.4G WIFI&5G WIFI&6G WIFI:

MPE limit S: 1mW/ cm²

The worst MPE is calculated as **0.27085mW/cm² < limit 1mW/cm²**. So, RF exposure limit warning or SAR test are not required. The EUT will only be used with a separation of 20cm or greater between the antenna and nearby persons and can therefore be considered a mobile transmitter per 47 CFR2.1091 (b).

The RF Exposure Information page from the manual is included here for reference.

For a more detailed features description, please refer to the RF Test Report.

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----END OF THE REPORT-----

