



FCC 47 CFR PART 15 SUBPART C

TEST REPORT

**For
HSDPA/WCDMA/EDGE/GPRS/GSM 850/900/1800/1900/2100MHz Mobile
Phone**

Model: i-mobile i858

Trade Name: i-mobile

Prepared for

**YuHua TelTech (Shanghai) Co.,Ltd.
4F/2, District B, No. 1000 Jinhai Road, Pudong 201206, Shanghai, P.R.
China**

Issued by

COMPLIANCE CERTIFICATION SERVICES (KUNSHAN) INC.

10#Weiye Rd, Innovation Park Eco. & Tec. Development Zone

Kunshan city JiangSu, (215300) CHINA

TEL: 86-512-57355888

FAX: 86-512-57370818



Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document.



TABLE OF CONTENTS

1. TEST RESULT CERTIFICATION	3
2. EUT DESCRIPTION	4
3. TEST METHODOLOGY	5
EUT CONFIGURATION.....	5
EUT EXERCISE 5	
GENERAL TEST PROCEDURES	5
MODIFICATION 5	
FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS.....	6
DESCRIPTION OF TEST MODES.....	6
4. INSTRUMENT CALIBRATION.....	7
5. FACILITIES AND ACCREDITATIONS	8
FACILITIES 8	
EQUIPMENT 8	
LABORATORY ACCREDITATIONS AND LISTING	8
TABLE OF ACCREDITATIONS AND LISTINGS.....	9
6. SETUP OF EQUIPMENT UNDER TEST	10
SETUP CONFIGURATION OF EUT.....	10
SUPPORT EQUIPMENT	10
7. FCC PART 15.247 REQUIREMENTS.....	11
PEAK POWER	11
BAND EDGES MEASUREMENT	13
PEAK POWER SPECTRAL DENSITY	24
FREQUENCY SEPARATION	26
NUMBER OF HOPPING FREQUENCY	31
TIME OF OCCUPANCY (DWELL TIME).....	34
RADIO FREQUENCY EXPOSURE	41
SPURIOUS EMISSIONS	42
POWERLINE CONDUCTED EMISSIONS	60



1. TEST RESULT CERTIFICATION

Applicant: YuHua TelTech (Shanghai) Co.,Ltd.
4F/2, District B, No. 1000 Jinhai Road, Pudong
201206, Shanghai, P.R. China

Equipment Under Test: HSDPA/WCDMA/EDGE/GPRS/GSM
850/900/1800/1900/2100MHz Mobile Phone

Trade Name: i-mobile

Model: i-mobile i858

Date of Test: April 15, 2010

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 15 Subpart C	No non-compliance noted

We here by certify that:

The above equipment was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4: 2003 and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 15.207, 15.209, 15.247.

The test results of this report relate only to the tested sample EUT identified in this report.

Approved by:

Miro Chueh
EMC Manager
Compliance Certification Services Inc.

Reviewed by:

Lin Zhang
EMC Section Manager
Compliance Certification Services Inc.



2. EUT DESCRIPTION

Product	HSDPA/WCDMA/EDGE/GPRS/GSM 850/900/1800/1900/2100MHz Mobile Phone
Trade Name	i-mobile
Model Number	i-mobile i858
Model Discrepancy	NA
Power Supply	Powered from an AC/DC power adapter Model Number :LSD-D05I55 Input:100-240V Output:5.0V/550mA Rechargeable battery Model:BL-84 Li-polymer 3.7V 1500mAh(5.6Wh) Voltage:4.2V
Frequency Range	2402 ~ 2480 MHz
Transmit Power	1.68dBm
Modulation Technique	FHSS
Transmit Data Rate	GFSK(1 Mbps), $\pi/4$ -DQPSK(2 Mbps),8-DPSK(3 Mbps)
Number of Channels	79 Channels
Antenna Specification	Max Gain: 1.0 dBi

Remark: This submittal(s) (test report) is intended for FCC ID: S2VTN100 filing to comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.



3. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4 and FCC CFR 47 2.1046, 2.1047, 2.1049, 2.1051, 2.1053, 2.1055, 2.1057, 15.207, 15.209 and 15.247.

EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

EUT EXERCISE

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 13.1.4.1 of ANSI C63.4.

MODIFICATION

N/A

**FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS**

- (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 -	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.52525	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	156.7 - 156.9	3260 - 3267	23.6 - 24.0
12.29 - 12.293	162.0125 - 167.17	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	167.72 - 173.2	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	240 - 285	3600 - 4400	(²)
13.36 - 13.41	322 - 335.4		

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

² Above 38.6

- (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition.

After verification, all tests were carried out with the worst case test modes as shown below GFSK(1M) and 8-DPSK(3 Mbps) Channel Low (2402MHz) 、Mid (2441MHz) and High (2480MHz), these were chosen for full testing.



4. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.



5. FACILITIES AND ACCREDITATIONS

FACILITIES

All measurement facilities used to collect the measurement data are located at CCS China Kunshan Lab at 10#Weiye Rd, Innovation Park Eco. & Tec. Development Zone

Kunshan city JiangSu, (215300), CHINA.

The sites are constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 22.

EQUIPMENT

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.



Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

LABORATORY ACCREDITATIONS AND LISTING

The test facilities used to perform radiated and conducted emissions tests are accredited by American Association for Laboratory Accreditation Program for the specific scope accreditation under Lab Code: 200581-0 to perform Electromagnetic Interference tests according to FCC Part 15 and CISPR 22 requirements. In addition, the test facilities are listed with Industry Canada, Certification and Engineering Bureau, IC5743 for 10m chamber 10m, IC5743 for 10m chamber 3m.

**TABLE OF ACCREDITATIONS AND LISTINGS**

Country	Agency	Scope of Accreditation	Logo
USA	A2LA	47 CFR FCC Part 15/18 (using ANSI C63.4:2003); VCCI V3; CNS 13438; CNS 13439; CNS 13803; CISPR 11; EN 55011; CISPR 13; EN 55013; CISPR 22:2005; CISPR 22:1997 +A1 :2000+A2 :2002; EN 55022:2006; EN55022 :1998 +A1 :2001+A2 :2003; EN 61000-6-3 (excluding discontinuous interference); EN 61000-6-4; AS/NZS CISPR 22; CAN/CSA-CEI/IEC CISPR 22; EN 61000-3-2; EN 61000-3-3; EN550024; EN 61000-4-2; EN 61000-4-3; EN61000-4-4; EN 61000-4-5; EN 61000-4-6; IEC 61000-4-8; EN 61000-4-11; IEC61000-3-2; IEC61000-3-3; IEC 61000-4-2; IEC 61000-4-3; IEC 61000-4-4; IEC 61000-4-5; IEC 61000-4-6; IEC 61000-4-8; IEC 61000-4-11; EN 300 220-3; EN 300 328; EN 300 330-2; EN 300 440-1; EN 300-440-2; EN 300 893; EN 301 489-01; EN 301 489-3; EN 301 489-07; EN 301 489-17; 47 CFR FCC Part 15, 22, 24	 TESTING CERT #2541.01
USA	FCC	3/10 meter Sites to perform FCC Part 15/18 measurements	 93105, 90471
Japan	VCCI	3/10 meter Sites and conducted test sites to perform radiated/conducted measurements	VCCI R-1600 C-1707

** No part of this report may be used to claim or imply product endorsement by A2LA or any agency of the US Government.*



6. SETUP OF EQUIPMENT UNDER TEST

SETUP CONFIGURATION OF EUT

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

SUPPORT EQUIPMENT

No.	Equipment	Model No.	Serial No.	FCC ID	Trade Name	Data Cable	Power Cord
1	N/A	N/A	N/A	N/A	N/A	N/A	N/A

Remark:

- 1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.*
- 2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.*



7. FCC PART 15.247 REQUIREMENTS

PEAK POWER

LIMIT

The maximum peak output power of the intentional radiator shall not exceed the following:


1. According to §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.
2. According to §15.247(b)(3), for systems using digital modulation in the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz: 1 Watt.
3. According to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY44020154	04/24/2010
Peak and Avg Power Sensor	Agilent	E9327A	US40441788	07/29/2010
EPM-P Series Power Meter	Agilent	E4416A	QB41292714	04/24/2010

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

The transmitter output is connected to the Power Meter.



TEST RESULTS

No non-compliance noted

Test Data

1M

Channel	Frequency (MHz)	Reading Power (dBm)	Factor (dB)	Output Power (dBm)	Output Power (W)	Limit (W)	Result
Low	2402	0.18	1.50	1.68	0.00147	1	PASS
Mid	2441	-0.15	1.50	1.35	0.00136		PASS
High	2480	-0.39	1.50	1.11	0.00129		PASS

3M

Channel	Frequency (MHz)	Reading Power (dBm)	Factor (dB)	Output Power (dBm)	Output Power (W)	Limit (W)	Result
Low	2402	-0.33	1.50	1.17	0.00131	1	PASS
Mid	2441	-0.65	1.50	0.85	0.00122		PASS
High	2480	-0.91	1.50	0.59	0.00115		PASS

BAND EDGES MEASUREMENT

LIMIT


According to §15.247(c), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

MEASUREMENT EQUIPMENT USED

3M Semi Anechoic Chamber (977)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY44020154	04/24/2010
Spectrum Analyzer	Agilent	E4446A	US44300398	04/24/2010
EMI Test Receiver	R&S	ESPI3	101026	04/24/2010
Pre-Amplifier	MINI	ZFL-1000VH2	d041703	02/28/2011
Pre-Amplifier	Miteq	NSP4000-NF	870731	02/28/2011
Bilog Antenna	Sunol	JB1	A110204-2	11/22/2010
Horn-antenna	SCHWARZBECK	BBHA9120D	D:266	12/04/2010
PSG Analog Signal Generator	Agilent	E8257C	MY43321570	04/24/2010
Turn Table	CT	CT123	4165	N.C.R
Antenna Tower	CT	CTERG23	3256	N.C.R
Controller	CT	CT100	95637	N.C.R
Site NSA	CCS	N/A	N/A	04/06/2010

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

1. The EUT is placed on a turntable, which is 0.8m above the ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
 - (a) PEAK: RBW=VBW=1MHz / Sweep=AUTO
 - (b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO
5. Repeat the procedures until all the PEAK and AVERAGE versus POLARIZATION are measured.

TEST RESULTS

1M

CH LOW

[illegible]

CH HIGH

[illegible]

Refer to attach spectrum analyzer data chart.




Band Edges (CH Low)

Detector mode: Peak

Polarity: Vertical

Agilent




Marker			
Select Marker			
1	2	3	4
Normal			
Delta			
Delta Pair (Tracking Ref)			
Ref Δ			
Span Pair			
Span Center			
Off			
More 1 of 2			

File Operation Status, A:\SCREN203.GIF file saved

Detector mode: Average

Polarity: Vertical

Agilent



Marker			
Select Marker			
1	2	3	4
Normal			
Delta			
Delta Pair (Tracking Ref)			
Ref Δ			
Span Pair			
Span Center			
Off			
More 1 of 2			


File Operation Status, A:\SCREN204.GIF file saved



Detector mode: Peak

Polarity: Horizontal

Agilent




Marker			
Select Marker			
1	2	3	4
Normal			
Delta			
Delta Pair (Tracking Ref)			
Ref		▲	
Span Pair			
Span		Center	
Off			
More 1 of 2			

File Operation Status, A:\SCREN205.GIF file saved

Detector mode: Average

Polarity: Horizontal

Agilent



Marker			
Select Marker			
1	2	3	4
Normal			
Delta			
Delta Pair (Tracking Ref)			
Ref		▲	
Span Pair			
Span		Center	
Off			
More 1 of 2			

File Operation Status, A:\SCREN206.GIF file saved




Band Edges (CH High)

Detector mode: Peak

Polarity: Vertical

Agilent




Marker			
Select Marker			
1	2	3	4
Normal			
Delta			
Delta Pair (Tracking Ref)			
Ref			
Span Pair			
Span			
Center			
Off			
More			
1 of 2			

File Operation Status, A:\SCREN209.GIF file saved

Detector mode: Average

Polarity: Vertical

Agilent




Marker			
Select Marker			
1	2	3	4
Normal			
Delta			
Delta Pair (Tracking Ref)			
Ref			
Span Pair			
Span			
Center			
Off			
More			
1 of 2			

File Operation Status, A:\SCREN210.GIF file saved

**Detector mode: Peak****Polarity: Horizontal**

Agilent

**Marker****Select Marker**

1 2 3 4

Normal

Delta

Delta Pair
(Tracking Ref)
Ref Δ Span Pair
Span Center


Off

More
1 of 2

File Operation Status, A:\SCREN207.GIF file saved

Detector mode: Average**Polarity: Horizontal**

Agilent

**Marker****Select Marker**

1 2 3 4

Normal

Delta

Delta Pair
(Tracking Ref)
Ref Δ Span Pair
Span Center

Off

More
1 of 2

File Operation Status, A:\SCREN208.GIF file saved



**3M****CH LOW**

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Peak Margin (dB)	AV Margin (dB)
					Peak (dBuV/m)	AV (dBuV/m)				
2390.00	V	48.56	38.76	4.80	53.36	43.56	74	54	-20.64	-10.44
2390.00	H	50.21	38.37	4.80	55.01	43.17	74	54	-18.99	-10.83

CH HIGH


Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Peak Margin (dB)	AV Margin (dB)
					Peak (dBuV/m)	AV (dBuV/m)				
2483.50	V	51.23	39.13	4.80	56.03	43.93	74	54	-17.97	-10.07
2483.50	H	50.89	38.99	4.80	55.69	43.79	74	54	-18.31	-10.21

Refer to attach spectrum analyzer data chart.


**Band Edges (CH Low)****Detector mode: Peak****Polarity: Vertical****Detector mode: Average****Polarity: Vertical**

**Detector mode: Peak****Polarity: Horizontal**

Agilent

**Detector mode: Average****Polarity: Horizontal**

Agilent






Band Edges (CH High)

Detector mode: Peak

Polarity: Vertical

Agilent



Marker

Select Marker

1 2 3 4

Normal

Delta

Delta Pair

(Tracking Ref)

Ref

Span

Center

Off


More

1 of 2

Detector mode: Average

Polarity: Vertical

Agilent



Marker

Select Marker

1 2 3 4

Normal

Delta

Delta Pair

(Tracking Ref)

Ref

Span

Center


Off

More

1 of 2

**Detector mode: Peak****Polarity: Horizontal**


Agilent

**Marker****Select Marker**

1 2 3 4

Normal**Delta****Delta Pair**
(Tracking Ref)
Ref Δ **Span Pair**
Span Center**Off****More**
1 of 2**Detector mode: Average****Polarity: Horizontal**

Agilent

**Marker****Select Marker**

1 2 3 4

Normal**Delta****Delta Pair**
(Tracking Ref)
Ref Δ **Span Pair**
Span Center**Off****More**
1 of 2



PEAK POWER SPECTRAL DENSITY

LIMIT


1. For direct sequence systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.
2. The direct sequence operating of the hybrid system, with the frequency hopping operation turned off, shall comply with the power density requirements of paragraph (d) of this section.

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY44020154	04/24/2010

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW = 3kHz, VBW = 10kHz, Span = 300kHz, Sweep=100s
4. Record the max. reading.
5. Repeat the above procedure until the measurements for all frequencies are completed.



TEST RESULTS

NA (this test item is not required for FHSS modulation technical)



FREQUENCY SEPARATION

LIMIT


According to §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY44020154	04/24/2010

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set center frequency of spectrum analyzer = middle of hopping channel.
4. Set the spectrum analyzer as RBW = 30kHz, VBW = 100kHz, Span = 3MHz, Sweep = auto.
5. Max hold, mark 2 peaks of hopping channel and record the 2 peaks frequency.

TEST RESULTS

No non-compliance noted


Test Data

1M

Channel Separation	20dB Bandwidth	Result
(MHz)	(kHz)	
1.000	923.537	Pass

**Test Plot****Measurement of Channel Separation**

Agilent

**Marker****Select Marker**

1 2 3 4

Marker Trace

Auto 1 2 3

Readout
Frequency**Marker Table**


On Off

Marker All Off**More**
2 of 2

Copyright 2000–2003 Agilent Technologies

Measurement of 20dB Bandwidth**Channel low**

Agilent

**Marker****Select Marker**

1 2 3 4

Marker Trace

Auto 1 2 3

Readout
Frequency**Marker Table**


On Off

Marker All Off**More**
2 of 2

Copyright 2000–2003 Agilent Technologies

**Channel middle**

* Agilent



Occupied Bandwidth
855.6358 kHz

Occ BW % Pwr 99.00 %
x dB -20.00 dB

Transmit Freq Error 8.786 kHz
x dB Bandwidth 915.657 kHz

Freq/Channel

Center Freq
2.44099994 GHz

Start Freq
2.43949994 GHz

Stop Freq
2.44249994 GHz

CF Step
300.000000 kHz
Auto Man


Freq Offset
0.00000000 Hz

Signal Track
On Off

Copyright 2000-2003 Agilent Technologies

Channel high

* Agilent



Occupied Bandwidth
879.2692 kHz

Occ BW % Pwr 99.00 %
x dB -20.00 dB

Transmit Freq Error -23.137 kHz
x dB Bandwidth 912.516 kHz

Marker

Select Marker
1 2 3 4

Marker Trace
Auto 1 2 3

Readout
Frequency

Marker Table
On Off



Marker All Off

More
2 of 2

Copyright 2000-2003 Agilent Technologies

**3M**

Channel Separation	20dB Bandwidth	two-thirds of the 20 dB bandwidth	Result
(MHz)	(kHz)	(kHz)	
1.000	1288.00	858.67	Pass

Test Plot**Measurement of Channel Separation****Measurement of 20dB Bandwidth****Channel low**

**Channel middle**

Agilent

R L

Freq/Channel

Ch Freq 2.441 GHz Trig Free

Occupied Bandwidth

Center Freq
2.44100000 GHzStart Freq
2.43950000 GHzStop Freq
2.44250000 GHzCF Step
300.000000 kHz
Auto ManFreq Offset
0.00000000 HzSignal Track
On Off

Ref 10 dBm

Atten 20 dB

#Peak

Log

10

dB/

Offst

1.5

dB

Center 2.441 000 GHz

Span 3 MHz

#Res BW 10 kHz

#VBW 30 kHz

Sweep 28.68 ms (601 pts)

Occupied Bandwidth

Occ BW % Pwr 99.00 %

1.2262 MHz

x dB -20.00 dB

Transmit Freq Error

-8.757 kHz

x dB Bandwidth

1.278 MHz

Channel high

Agilent

R L

Freq/Channel

Ch Freq 2.48 GHz Trig Free

Occupied Bandwidth

Center Freq
2.48000000 GHzStart Freq
2.47850000 GHzStop Freq
2.48150000 GHzCF Step
300.000000 kHz
Auto ManFreq Offset
0.00000000 HzSignal Track
On Off

Ref 10 dBm

Atten 20 dB

#Peak

Log

10

dB/

Offst

1.5

dB

Center 2.480 000 GHz

Span 3 MHz

#Res BW 10 kHz

#VBW 30 kHz

Sweep 28.68 ms (601 pts)

Occupied Bandwidth

Occ BW % Pwr 99.00 %

1.2155 MHz

x dB -20.00 dB

Transmit Freq Error

-10.572 kHz

x dB Bandwidth

1.288 MHz



NUMBER OF HOPPING FREQUENCY

LIMIT


According to §15.247(a)(1)(ii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz bands shall use at least 75 hopping frequencies.

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY44020154	04/24/2010

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set spectrum analyzer Start=2400MHz, Stop = 2441.5MHz, Sweep = auto and Start=2441.5MHz, Stop = 2483.5MHz, Sweep = auto.
4. Set the spectrum analyzer as RBW, VBW=100kHz.
5. Max hold, view and count how many channel in the band.

TEST RESULTS

No non-compliance noted

Test Data

1M


Result (No. of CH)	Limit (No. of CH)	Result
79	>75	PASS




Test Plot

Channel Number

2.4 GHz – 2.4415 GHz





2.4415 GHz – 2.4835 GHz



**3M**

Result (No. of CH)	Limit (No. of CH)	Result
79	>75	PASS

Test Plot**Channel Number****2.4 GHz – 2.4415 GHz****2.4415 GHz – 2.4835 GHz**



TIME OF OCCUPANCY (DWELL TIME)

LIMIT


According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz bands. The average time of occupancy on any channels shall not greater than 0.4 s within a period 0.4 s multiplied by the number of hopping channels employed.

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY44020154	04/24/2010

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set center frequency of spectrum analyzer = operating frequency.
4. Set the spectrum analyzer as RBW, VBW=1MHz, Span = 0Hz, Sweep = auto.
5. Repeat above procedures until all frequency measured were complete.

**TEST RESULTS**

No non-compliance noted

Test Data**1M****DH 1**

$$0.400 * (1600/2)/79 * 31.6 = 128.00 \text{ (ms)}$$

Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
0.400	128.00	31.60	400	PASS

DH 3

$$1.77 * (1600/4)/79 * 31.6 = 283.20 \text{ (ms)}$$

Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
1.77	283.20	31.60	400	PASS


DH 5

$$2.929 * (1600/6)/79 * 31.6 = 312.43 \text{ (ms)}$$

Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
2.929	312.43	31.60	400	PASS

**Test Plot****DH 1**

* Agilent




Marker			
Select Marker			
1	2	3	4
Marker Trace			
Auto	1	2	3
Readout			
Time			
Marker Table			
On		Off	
Marker All Off			
More			
2 of 2			

Copyright 2000–2003 Agilent Technologies

DH 3

* Agilent




Marker			
Select Marker			
1	2	3	4
Normal			
Delta			
Delta Pair			
(Tracking Ref)			
Ref	Δ		
Span Pair			
Span	Center		
Off			
More			
1 of 2			

Copyright 2000–2003 Agilent Technologies

**DH 5**

* Agilent



Copyright 2000–2003 Agilent Technologies

**3M****DH 1**

$$0.433 * (1600/2)/79 * 31.6 = 138.56 \text{ (ms)}$$

Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
0.433	138.56	31.60	400	PASS

DH 3

$$1.70 * (1600/4)/79 * 31.6 = 272.00 \text{ (ms)}$$

Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
1.70	272.00	31.60	400	PASS


DH 5

$$2.933 * (1600/6)/79 * 31.6 = 312.85 \text{ (ms)}$$


Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
2.933	312.85	31.60	400	PASS

**Test Plot****DH 1**

Agilent

**DH 3**


Agilent





DH 5

Agilent





RADIO FREQUENCY EXPOSURE

LIMIT

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See §15.247(b)(4) and §1.1307(b)(1) of this chapter.

EUT Specification

EUT	HSDPA/WCDMA/EDGE/GPRS/GSM 850/900/1800/1900/2100MHz Mobile Phone
Frequency band (Operating)	<input type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5.825GHz <input checked="" type="checkbox"/> Others: <u>Bluetooth: 2.402GHz ~ 2.480GHz</u>
Device category	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others _____
Exposure classification	<input type="checkbox"/> Occupational/Controlled exposure ($S = 5mW/cm^2$) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure ($S=1mW/cm^2$)
Antenna diversity	<input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
Max. output power	1.68dBm (1.472mW)
Antenna gain (Max)	1 dBi (Numeric gain: 1.259mW)
Evaluation applied	<input type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation <input checked="" type="checkbox"/> N/A

Remark:

1. The maximum output power is 1.68dBm (1.472mW) at 2402MHz (with 1.259 numeric antenna gain.)
2. DTS device is not subject to routine RF evaluation; MPE estimate is used to justify the compliance.
3. For mobile or fixed location transmitters, no SAR consideration applied. The minimum separation generally be used is at least 20 cm, even if the calculations indicate that the MPE distance would be lesser.

TEST RESULTS

No non-compliance noted.



SPURIOUS EMISSIONS

Conducted Measurement

LIMIT


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY44020154	04/24/2010

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.

The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 KHz. The video bandwidth is set to 100 KHz.


Measurements are made over the 30MHz to 26GHz range with the transmitter set to the lowest, middle, and highest channels.

TEST RESULTS

No non-compliance noted

**Test Plot****1M****CH Low****30MHz ~ 2.9GHz**

* Agilent

**Marker****Select Marker**
1 2 3 4

Normal

Delta

Delta Pair
(Tracking Ref)
Ref Δ Span Pair
Span Center


Off

More
1 of 2

Copyright 2000-2003 Agilent Technologies

2.9GHz ~ 26.5GHz

* Agilent

**Marker****Select Marker**
1 2 3 4

Normal

Delta

Delta Pair
(Tracking Ref)
Ref Δ Span Pair
Span Center


Off

More
1 of 2

Copyright 2000-2003 Agilent Technologies

**CH Mid****30MHz ~ 2.9GHz**


* Agilent

**Marker****Select Marker**

1 2 3 4

Normal**Delta****Delta Pair**
(Tracking Ref)
Ref **Span Pair**
Span Center**Off****More**
1 of 2**Copyright 2000-2003 Agilent Technologies****2.9GHz ~ 26.5GHz**

* Agilent


**Marker****Select Marker**

1 2 3 4

Normal**Delta****Delta Pair**
(Tracking Ref)
Ref **Span Pair**
Span Center**Off****More**
1 of 2**Copyright 2000-2003 Agilent Technologies**

**CH High****30MHz ~ 2.9GHz**


* Agilent

**Marker****Select Marker**

1 2 3 4

Normal**Delta****Delta Pair**
(Tracking Ref)
Ref **Span Pair**
Span Center**Off****More**
1 of 2**Copyright 2000-2003 Agilent Technologies****2.9GHz ~ 26.5GHz**

* Agilent


**Marker****Select Marker**

1 2 3 4

Normal**Delta****Delta Pair**
(Tracking Ref)
Ref **Span Pair**
Span Center**Off****More**
1 of 2**Copyright 2000-2003 Agilent Technologies**

**3M****CH Low****30MHz ~ 2.9GHz**


* Agilent



Marker
Select Marker
1 2 3 4
Normal
Delta
Delta Pair (Tracking Ref)
Ref
Span Pair
Span Center
Off
More 1 of 2

2.9GHz ~ 26.5GHz


* Agilent



Marker
Select Marker
1 2 3 4
Normal
Delta
Delta Pair (Tracking Ref)
Ref
Span Pair
Span Center
Off
More 1 of 2

**CH Mid****30MHz ~ 2.9GHz**

* Agilent

**Marker****Select Marker**

1 2 3 4

Normal**Delta****Delta Pair**

(Tracking Ref)


Ref

Span PairSpan Center**Off****More**

1 of 2

2.9GHz ~ 26.5GHz

* Agilent

**Marker****Select Marker**

1 2 3 4

Normal**Delta****Delta Pair**

(Tracking Ref)


Ref

Span PairSpan Center**Off****More**

1 of 2

**CH High****30MHz ~ 2.9GHz**


* Agilent



Marker			
Select Marker			
1	2	3	4
Normal			
Delta			
Delta Pair (Tracking Ref)			
Ref			
Span Pair			
Span <u>Center</u>			
Off			
More 1 of 2			

2.9GHz ~ 26.5GHz

* Agilent



Marker			
Select Marker			
1	2	3	4
Normal			
Delta			
Delta Pair (Tracking Ref)			
Ref			
Span Pair			
Span <u>Center</u>			
Off			
More 1 of 2			



Radiated Emissions

LIMIT

1. Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (mV/m)	Measurement Distance (m)
30-88	100*	3
88-216	150*	3
216-960	200*	3
Above 960	500	3

Remark: Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

2. In the above emission table, the tighter limit applies at the band edges.

Frequency (Hz)	Field Strength (μ V/m at 3-meter)	Field Strength (dB μ V/m at 3-meter)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54




MEASUREMENT EQUIPMENT USED

3M Semi Anechoic Chamber (977)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY44020154	04/24/2010
Spectrum Analyzer	Agilent	E4446A	US44300398	04/24/2010
EMI Test Receiver	R&S	ESPI3	101026	04/24/2010
Pre-Amplifier	MINI	ZFL-1000VH2	d041703	02/28/2011
Pre-Amplifier	Miteq	NSP4000-NF	870731	02/28/2011
Bilog Antenna	Sunol	JB1	A110204-2	11/22/2010
Horn-antenna	SCHWARZBECK	BBHA9120D	D:266	12/04/2010
PSG Analog Signal Generator	Agilent	E8257C	MY43321570	04/24/2010
Turn Table	CT	CT123	4165	N.C.R
Antenna Tower	CT	CTERG23	3256	N.C.R
Controller	CT	CT100	95637	N.C.R
Site NSA	CCS	N/A	N/A	04/06/2010
Loop Antenna	ARA	PLA-1030/B	1029	02/24/2011


Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration


Below 30MHz



Below 1 GHz



Above 1 GHz



TEST PROCEDURE

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Set the spectrum analyzer in the following setting as:



Below 1GHz:

RBW=100kHz / VBW=300kHz / Sweep=AUTO

Above 1GHz:

(a) PEAK: RBW=VBW=1MHz / Sweep=AUTO

(b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO

7. Repeat above procedures until the measurements for all frequencies are complete.



TEST RESULTS

Below 1 GHz

Operation Mode: Normal Link

Test Date: April 14, 2010

Temperature: 23°C

Tested by: jeff

Humidity: 50 % RH

Polarity: Ver. / Hor.

Freq. (MHz)	Ant.Pol. H/V	Detector Mode (PK/QP)	Reading (dBuV)	Factor (dB)	Actual FS (dBuV/m)	Limit 3m (dBuV/m)	Safe Margin (dB)
37.65	V	Peak	40.56	-6.24	34.32	40.0	-5.68
109.67	V	Peak	43.65	-10.41	33.24	43.5	-10.26
183.22	V	Peak	45.91	-10.77	35.14	43.5	-8.36
272.33	V	Peak	48.34	-8.03	40.31	46.0	-5.69
412.58	V	Peak	41.2	-4.18	37.02	46.0	-8.98
961.77	V	Peak	39.75	4.55	44.3	54.0	-9.7
41.67	H	Peak	42.57	-10.78	31.79	40	-8.21
90.36	H	Peak	47.9	-14.92	32.98	43.5	-10.52
188.49	H	Peak	45.64	-10.83	34.81	43.5	-8.69
233.82	H	Peak	48.72	-9.81	38.91	46.0	-7.09
372.89	H	Peak	43.05	-5.28	37.77	46.0	-8.23
962.57	H	Peak	39.77	4.56	44.33	54.0	-9.67

Notes:

1. Measuring frequencies from 9 KHz to the 1GHz, No emission found between lowest internal used/generated frequency to 30 MHz.
2. Radiated emissions measured in frequency range from 9 KHz to 1000MHz were made with an instrument using Peak detector mode.
3. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. The IF bandwidth of SPA between 30MHz to 1GHz was 100kHz.

**Above 1 GHz****1M****Operation
Mode:**

TX/ CH Low

Test Date: April 14, 2010**Temperature:** 23°C**Tested by:** jeff**Humidity:** 50 % RH**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
4804.52	V	40.16	29.89	10.85	51.01	40.74	74	54	-13.26	average
7206.88	V	39.76	26.52	18.37	58.13	44.89	74	54	-9.11	average
4805.45	H	39.84	28.17	10.84	50.68	39.01	74	54	-14.99	average
7205.64	H	38.9	26.05	18.37	57.27	44.42	74	54	-9.58	average

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1GHz to 10th harmonics of fundamental, RBW = 1MHz, VBW = 1MHz, Sweep time = Auto.
 - b. AV Setting 1GHz to 10th harmonics of fundamental, RBW = 1MHz, VBW = 10Hz, Sweep time = Auto.



Operation Mode: TX/ CH Mid
Temperature: 23°C
Humidity: 50 % RH

Test Date: April 14, 2010**Tested by:** jeff**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
4884.34	V	38.52	27.99	11.26	49.78	39.25	74	54	-14.75	average
7326.33	V	41.56	25.16	19.28	60.84	44.44	74	54	-9.56	average
4885	H	38.19	27.85	11.26	49.45	39.11	74	54	-14.89	average
7333.67	H	40.83	24.88	19.31	60.14	44.19	74	54	-9.81	average

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1GHz to 10th harmonics of fundamental, RBW = 1MHz, VBW = 1MHz, Sweep time = Auto.
 - b. AV Setting 1GHz to 10th harmonics of fundamental, RBW = 1MHz, VBW = 10Hz, Sweep time = Auto.



Operation Mode: TX/ CH High
Temperature: 23°C
Humidity: 50 % RH

Test Date: April 14, 2010**Tested by:** jeff**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
4958.66	V	39.76	30.16	11.32	51.08	41.48	74	54	-12.52	average
7326.33	V	40.55	24.87	19.56	60.11	44.43	74	54	-9.57	average
4959.81	H	39.07	29.98	11.32	50.39	41.3	74	54	-12.7	average
7324.56	H	40.13	25.34	19.56	59.69	44.9	74	54	-9.10	average

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1GHz to 10th harmonics of fundamental, RBW = 1MHz, VBW = 1MHz, Sweep time = Auto.
 - b. AV Setting 1GHz to 10th harmonics of fundamental, RBW = 1MHz, VBW = 10Hz, Sweep time = Auto.

3M

Operation Mode: TX/ CH Low

Test Date: April 14, 2010

Temperature: 23°C

Tested by: jeff

Humidity: 50 % RH

Polarity: Ver. / Hor.

[illegible]

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1GHz to 10th harmonics of fundamental, RBW = 1MHz, VBW = 1MHz, Sweep time = Auto.
 - b. AV Setting 1GHz to 10th harmonics of fundamental, RBW = 1MHz, VBW = 10Hz, Sweep time = Auto.



Operation Mode: TX/ CH Mid
Temperature: 23°C
Humidity: 50 % RH

Test Date: April 14, 2010

Tested by: jeff

Polarity: Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
4884.67	V	38.44	27.65	11.26	49.7	38.91	74	54	-15.09	average
7325.61	V	41.34	24.67	19.28	60.62	43.95	74	54	-10.05	average
4884.65	H	37.58	27.54	11.26	48.84	38.8	74	54	-15.2	average
7331.26	H	40.52	24.6	19.31	59.83	43.91	74	54	-10.09	average

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1GHz to 10th harmonics of fundamental, RBW = 1MHz, VBW = 1MHz, Sweep time = Auto.
 - b. AV Setting 1GHz to 10th harmonics of fundamental, RBW = 1MHz, VBW = 10Hz, Sweep time = Auto.



Operation Mode: TX/ CH High
Temperature: 23°C
Humidity: 50 % RH

Test Date: April 14, 2010**Tested by:** jeff**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
4958.76	V	39.64	29.56	11.32	50.96	40.88	74	54	-13.12	average
7325.16	V	40.25	23.15	19.56	59.81	42.71	74	54	-11.29	average
4958.79	H	38.79	29.64	11.32	50.11	40.96	74	54	-13.04	average
7323.12	H	39.26	26.57	19.56	58.82	46.13	74	54	-7.87	average

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1GHz to 10th harmonics of fundamental, RBW = 1MHz, VBW = 1MHz, Sweep time = Auto.
 - b. AV Setting 1GHz to 10th harmonics of fundamental, RBW = 1MHz, VBW = 10Hz, Sweep time = Auto.



POWERLINE CONDUCTED EMISSIONS

LIMIT

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50


Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

MEASUREMENT EQUIPMENT USED

Conducted Emission				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMC Analyzer	R&S	ESCI3	100781	04/24/2010
V (V-LISN)	Schwarzbeck	NNLK 8129	8129-143	04/24/2010
LISN (EUT)	FCC	FCC-LISN-50/250-50-2-02	SN:05012	04/24/2010
TRANSIENT LIMITER	SCHAFFNER	CFL9206	1710	04/24/2010

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

TEST PROCEDURE

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.



TEST RESULTS

The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. Significant peaks are then marked as shown on the following data page, and these signals are then quasi-peaked.

Test Data

Model: i-mobile i858**Test Mode:** Normal Link**Temperature:** 25°C**Humidity:** 43% RH**Tested by:** jeff**Test Results:** Pass

Freq. (MHz)	Q.P. Raw reading (dBuV)	AVG Raw reading (dBuV)	Correction factor(dB)	Q.P. Amptd. (dBuV)	AVG Amptd. (dBuV)	Q.P. Limit (dBuV)	AVG Limit (dBuV)	Q.P. Margin (dB)	AVG Margin (dB)	Line/Neutral
0.161	36.78	24.75	10.06	46.84	34.81	65.68	55.68	-18.84	-20.87	Line
0.723	29.76	20.58	10.95	40.71	31.53	56.00	46.00	-15.29	-14.47	Line
0.871	28.56	18.52	11.00	39.56	29.52	56.00	46.00	-16.44	-16.48	Line
1.626	24.41	14.87	11.06	35.47	25.93	56.00	46.00	-20.53	-20.07	Line
2.576	22.10	13.17	11.12	33.22	24.29	56.00	46.00	-22.78	-21.71	Line
3.456	20.39	11.10	11.16	31.55	22.26	56.00	46.00	-24.45	-23.74	Line
0.161	31.37	21.55	10.16	41.53	31.71	65.68	55.68	-24.15	-23.97	Neutral
0.205	27.20	10.79	10.18	37.38	20.97	64.41	54.41	-27.03	-33.44	Neutral
0.712	26.38	15.74	10.15	36.53	25.89	56.00	46.00	-19.47	-20.11	Neutral
0.804	23.79	13.37	10.15	33.94	23.52	56.00	46.00	-22.06	-22.48	Neutral
1.622	22.94	12.38	10.43	33.37	22.81	56.00	46.00	-22.63	-23.19	Neutral
2.560	21.19	10.42	10.68	31.87	21.10	56.00	46.00	-24.13	-24.90	Neutral

Remark:

1. The measuring frequencies range between 0.15 MHz and 30 MHz.
2. The emissions measured in the frequency range between 0.15 MHz and 30MHz were made with an instrument using Quasi-peak detector and Average detector.
3. "---" denotes the emission level was or more than 2dB below the Average limit, and no re-check was made.
4. The IF bandwidth of SPA between 0.15MHz and 30MHz was 10KHz. The IF bandwidth of Test Receiver between 0.15MHz and 30MHz was 9kHz.

Note:

Freq. = Emission frequency in KHz

Factor (dB) = cable loss + Insertion loss of LISN+ Insertion loss of TRANSIENT LIMITER
(The TRANSIENT LIMITER included 10 dB ATTENUATION)



*Amptd dBuV = Uncorrected Analyzer/Receiver reading + cable loss + Insertion loss of LISN+ Insertion loss of TRANSIENT LIMITER,
if it > 0.5 dB*

Limit dBuV = Limit stated in standard


Margin dB = Reading in reference to limit

Calculation Formula

Margin (dB) = Amptd (dBuV) – Limit (dBuV)

Test Plot

Conducted emissions (Line 1)



Test Plot

Conducted emissions (Line 2)

