

FCC Test Report

Report No.: RF171213C12

FCC ID: S4L4GF41

Test Model: 4GF41

Received Date: Dec. 13, 2017

Test Date: Dec. 22 ~ Dec. 26, 2017

Issued Date: Dec. 29, 2017

Applicant: TomTom International B.V.

Address: De Ruijterkade 154, 1011 AC Amsterdam The Netherlands

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan (R.O.C.)

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, TAIWAN (R.O.C.)

**FCC Registration /
Designation Number:** 788550 / TW0003



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	4
1 Certificate of Conformity	5
2 Summary of Test Results	6
2.1 Measurement Uncertainty	6
2.2 Modification Record	6
3 General Information	7
3.1 General Description of EUT	7
3.2 Description of Test Modes	8
3.2.1 Test Mode Applicability and Tested Channel Detail	9
3.3 Duty Cycle of Test Signal	10
3.4 Description of Support Units	11
3.4.1 Configuration of System under Test	11
3.5 General Description of Applied Standards	12
4 Test Types and Results	13
4.1 Radiated Emission and Bandedge Measurement	13
4.1.1 Limits of Radiated Emission and Bandedge Measurement	13
4.1.2 Test Instruments	14
4.1.3 Test Procedures	15
4.1.4 Deviation from Test Standard	15
4.1.5 Test Setup	16
4.1.6 EUT Operating Conditions	17
4.1.7 Test Results	18
4.2 6dB Bandwidth Measurement	33
4.2.1 Limits of 6dB Bandwidth Measurement	33
4.2.2 Test Setup	33
4.2.3 Test Instruments	33
4.2.4 Test Procedure	33
4.2.5 Deviation from Test Standard	33
4.2.6 EUT Operating Conditions	33
4.2.7 Test Result	34
4.3 Conducted Output Power Measurement	36
4.3.1 Limits of Conducted Output Power Measurement	36
4.3.2 Test Setup	36
4.3.3 Test Instruments	36
4.3.4 Test Procedures	36
4.3.5 Deviation from Test Standard	36
4.3.6 EUT Operating Conditions	36
4.3.7 Test Results	37
4.4 Power Spectral Density Measurement	38
4.4.1 Limits of Power Spectral Density Measurement	38
4.4.2 Test Setup	38
4.4.3 Test Instruments	38
4.4.4 Test Procedure	38
4.4.5 Deviation from Test Standard	38
4.4.6 EUT Operating Condition	38
4.4.7 Test Results	39
4.5 Conducted Out of Band Emission Measurement	41
4.5.1 Limits of Conducted Out of Band Emission Measurement	41
4.5.2 Test Setup	41
4.5.3 Test Instruments	41
4.5.4 Test Procedure	41
4.5.5 Deviation from Test Standard	41
4.5.6 EUT Operating Condition	41

4.5.7 Test Results	41
5 Pictures of Test Arrangements.....	45
Appendix – Information on the Testing Laboratories	46

Release Control Record

Issue No.	Description	Date Issued
RF171213C12	Original release	Dec. 29, 2017

1 Certificate of Conformity

Product: GPS Navigation System

Brand: TOMTOM

Test Model: 4GF41

Sample Status: Engineering sample

Applicant: TomTom International B.V.

Test Date: Dec. 22 ~ Dec. 26, 2017

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.247)
ANSI C63.10:2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : Celine Chou , **Date:** Dec. 29, 2017
Celine Chou / Specialist

Approved by : Ken Liu , **Date:** Dec. 29, 2017
Ken Liu / Senior Manager

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247)			
FCC Clause	Test Item	Result	Remarks
15.207	AC Power Conducted Emission	N/A	EUT is powered from DC
15.205 / 15.209 / 15.247(d)	Radiated Emissions and Band Edge Measurement	Pass	Meet the requirement of limit. Minimum passing margin is -5.1dB at 916.66MHz.
15.247(d)	Antenna Port Emission	Pass	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	Pass	Meet the requirement of limit.
15.247(b)	Conducted power	Pass	Meet the requirement of limit.
15.247(e)	Power Spectral Density	Pass	Meet the requirement of limit.
15.203	Antenna Requirement	Pass	No antenna connector is used.

N/A: Not Applicable

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (±)
Radiated Emissions up to 1 GHz	30MHz ~ 200MHz	3.63 dB
	200MHz ~ 1000MHz	3.64 dB
Radiated Emissions above 1 GHz	1GHz ~ 18GHz	2.29 dB
	18GHz ~ 40GHz	2.29 dB

2.2 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 General Description of EUT

Product	GPS Navigation System
Brand	TOMTOM
Test Model	4GF41
Sample Status	Engineering sample
Power Supply Rating	3.6Vdc (Battery) 5Vdc (Car Charger or Bike Docking or Car Docking)
Modulation Type	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
Modulation Technology	DSSS, OFDM
Transfer Rate	802.11b: 11/5.5/2/1Mbps 802.11g: 54/48/36/24/18/12/9/6Mbps 802.11n: up to 65Mbps
Operating Frequency	2412 ~ 2462MHz
Number of Channel	11
Output Power	58.479mW
Antenna Type	Chip antenna with -1.2dBi gain
Antenna Connector	NA
Accessory Device	Refer to note
Cable Supplied	Refer to note

Note:

- The EUT provides 1 completed transmitter and 1 receiver.

Modulation Mode	TX Function
802.11b	1TX
802.11g	1TX
802.11n (HT20)	1TX

- The EUT has two kinds of capacities for sale (8GB and 16GB), after pre-tested found 16GB was the worse, therefore chosen for final test and presented in the test report.

- The EUT contains the following accessories.

Item	Brand	Model	Specification	Remark
Car Charger	TOMTOM	4UUC3Z	Input: 12/24Vdc, 1A Output: 5Vdc, 1.2A	Option
Bike Docking	TOMTOM	4GF01	Input: 12/24Vdc, 1.3A Output: 5Vdc, 2A	Accessory
Bike Power Cable	TOMTOM	4GE0.001.04	1.9m $\pm$ 1cm non-shielded power cable without core	Accessory
Car Docking	TOMTOM	4GF02	Input: 5Vdc Output: pass through to output directly	Option
USB Cable	TOMTOM	4UUC.001.04B	1.5m shielded USB cable without core	Accessory
Battery	TOMTOM (Skypower)	VF3W	Power rating: 3.6Vdc , 3220mAh	Accessory

- WLAN, BT and BT LE technology cannot transmit simultaneously.

3.2 Description of Test Modes

11 channels are provided for 802.11b, 802.11g and 802.11n (HT20):

Channel	Frequency	Channel	Frequency
1	2412MHz	7	2442MHz
2	2417MHz	8	2447MHz
3	2422MHz	9	2452MHz
4	2427MHz	10	2457MHz
5	2432MHz	11	2462MHz
6	2437MHz		

3.2.1 Test Mode Applicability and Tested Channel Detail

EUT Configure Mode	Applicable to				Description
	RE $\geq$ 1G	RE<1G	PLC	APCM	
A	√	√	Note 2	√	EUT + USB Cable + Car Charger (12Vdc)
B	-	√	Note 2	-	EUT + USB Cable + Car Charger (24Vdc)
C	-	√	Note 2	-	EUT + Bike Docking + Bike Power Cable (12Vdc)
D	-	√	Note 2	-	EUT + Bike Docking + Bike Power Cable (24Vdc)
E	-	√	Note 2	-	EUT + Car Docking + USB Cable + Car Charger (12Vdc)
F	-	√	Note 2	-	EUT + Car Docking + USB Cable + Car Charger (24Vdc)

Where RE $\geq$ 1G: Radiated Emission above 1GHz & Bandedge Measurement
 PLC: Power Line Conducted Emission

RE<1G: Radiated Emission below 1GHz
 APCM: Antenna Port Conducted Measurement

Note:

1. The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **X-plane**.
2. No need to concern of PLC due to the EUT is powered from DC.

Radiated Emission Test (Above 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
A	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
A	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
A	802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	6.5

Radiated Emission Test (Below 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
A, B, C, D, E, F	802.11b	1 to 11	1	DSSS	DBPSK	1.0

Antenna Port Conducted Measurement:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
A	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
A	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
A	802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	6.5

Test Condition:

Applicable to	Environmental Conditions	Input Power	Tested by
RE≥1G	25 deg. C, 70% RH	12Vdc	Luis Lee
RE<1G	25 deg. C, 70% RH	12Vdc 24Vdc	Luis Lee
APCM	25 deg. C, 60% RH	12Vdc	Chris Lin


3.3 Duty Cycle of Test Signal

802.11b: Duty cycle of test signal is 100%.

802.11g, 802.11n (HT20): Duty cycle of test signal is > 98%.

802.11g: Duty cycle = $5.482/5.513 = 0.994$

802.11n (HT20): Duty cycle = $5.080/5.087 = 0.999$



3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.


ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	DC Power Supply	Keysight	U8002A	MY56330015	NA	-

Note: All power cords of the above support units are non-shielded (1.8m).


ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	DC	1	0.5	N	0	-

3.4.1 Configuration of System under Test


Test Mode A and B



Test Mode C and D



Test Mode E and F



3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247)

KDB 558074 D01 DTS Meas Guidance v04

ANSI C63.10:2013

All test items have been performed and recorded as per the above standards.

Note: The EUT has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC).
The test report has been issued separately.

4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

Note:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.1.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
Test Receiver ROHDE & SCHWARZ	ESCI	100424	Oct. 17, 2017	Oct. 16, 2018
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100040	Aug. 18, 2017	Aug. 17, 2018
BILOG Antenna SCHWARZBECK	VULB9168	9168-155	Dec. 11, 2017	Dec. 10, 2018
HORN Antenna SCHWARZBECK	BBHA 9120D	9120D-1170	Dec. 13, 2017	Dec. 12, 2018
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA9170241	Dec. 01, 2017	Nov. 30, 2018
Loop Antenna EMCI	EM-6879	269	Aug. 11, 2017	Aug. 10, 2018
Preamplifier Agilent (Below 1GHz)	8447D	2944A10631	Aug. 08, 2017	Aug. 07, 2018
Preamplifier Agilent (Above 1GHz)	8449B	3008A01960	Aug. 08, 2017	Aug. 07, 2018
RF signal cable HUBER+SUHNER	SUCOFLEX 104	MY 13380+295012/04	Aug. 08, 2017	Aug. 07, 2018
RF signal cable HUBER+SUHNER	SUCOFLEX 104	Cable-CH4-03 (250724)	Aug. 08, 2017	Aug. 07, 2018
Software BV ADT	ADT_Radiated_ V7.6.15.9.4	NA	NA	NA
Antenna Tower inn-co GmbH	MA 4000	010303	NA	NA
Antenna Tower Controller BV ADT	AT100	AT93021703	NA	NA
Turn Table BV ADT	TT100	TT93021703	NA	NA
Turn Table Controller BV ADT	SC100	SC93021703	NA	NA
High Speed Peak Power Meter	ML2495A	0824012	Aug. 18, 2017	Aug. 17, 2018
Power Sensor	MA2411B	0738171	Aug. 18, 2017	Aug. 17, 2018

- Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HwaYa Chamber 4.
3. The FCC Designation Number is TW0003. The number will be varied with the Lab location and scope as attached.
4. The IC Site Registration No. is IC 7450F-4.

4.1.3 Test Procedures

For Radiated emission below 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Both X and Y axes of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Radiated emission above 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 10 Hz (Duty cycle $\geq 98\%$) for Peak detection at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 Deviation from Test Standard


No deviation.

4.1.5 Test Setup


For Radiated emission below 30MHz



For Radiated emission 30MHz to 1GHz



For Radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT Operating Conditions

- a. Set the EUT under transmission condition continuously at specific channel frequency.

4.1.7 Test Results

Above 1GHz Data:

802.11b

CHANNEL	TX Channel 1	DETECTOR	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz	FUNCTION	Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	59.1 PK	74.0	-14.9	2.19 H	147	25.7	33.4
2	2390.00	46.0 AV	54.0	-8.0	2.19 H	147	12.6	33.4
3	*2412.00	100.7 PK			2.44 H	156	67.3	33.4
4	*2412.00	97.0 AV			2.44 H	156	63.6	33.4
5	4824.00	51.3 PK	74.0	-22.7	2.16 H	281	47.7	3.6
6	4824.00	41.2 AV	54.0	-12.8	2.16 H	281	37.6	3.6
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	58.2 PK	74.0	-15.8	1.25 V	304	24.8	33.4
2	2390.00	45.9 AV	54.0	-8.1	1.25 V	304	12.5	33.4
3	*2412.00	91.0 PK			1.37 V	342	57.6	33.4
4	*2412.00	87.5 AV			1.37 V	342	54.1	33.4
5	4824.00	51.3 PK	74.0	-22.7	1.04 V	254	47.7	3.6
6	4824.00	42.9 AV	54.0	-11.1	1.04 V	254	39.3	3.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	101.5 PK			2.21 H	265	68.1	33.4
2	*2437.00	97.7 AV			2.21 H	265	64.3	33.4
3	4874.00	51.2 PK	74.0	-22.8	2.05 H	277	47.9	3.3
4	4874.00	41.4 AV	54.0	-12.6	2.05 H	277	38.1	3.3
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	92.5 PK			1.00 V	253	59.1	33.4
2	*2437.00	89.0 AV			1.00 V	253	55.6	33.4
3	4874.00	50.1 PK	74.0	-23.9	2.16 V	241	46.8	3.3
4	4874.00	40.4 AV	54.0	-13.6	2.16 V	241	37.1	3.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz	FUNCTION	Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	103.3 PK			2.48 H	237	69.8	33.5
2	*2462.00	99.5 AV			2.48 H	237	66.0	33.5
3	2483.50	58.2 PK	74.0	-15.8	2.59 H	227	24.7	33.5
4	2483.50	46.0 AV	54.0	-8.0	2.59 H	227	12.5	33.5
5	4924.00	51.5 PK	74.0	-22.5	2.21 H	294	48.2	3.3
6	4924.00	41.2 AV	54.0	-12.8	2.21 H	294	37.9	3.3
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	94.2 PK			1.02 V	255	60.7	33.5
2	*2462.00	90.7 AV			1.02 V	255	57.2	33.5
3	2483.50	58.2 PK	74.0	-15.8	1.19 V	231	24.7	33.5
4	2483.50	46.0 AV	54.0	-8.0	1.19 V	231	12.5	33.5
5	4924.00	50.6 PK	74.0	-23.4	1.06 V	245	47.3	3.3
6	4924.00	42.3 AV	54.0	-11.7	1.06 V	245	39.0	3.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

802.11g

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	59.3 PK	74.0	-14.7	1.24 H	157	25.7	33.6
2	2390.00	46.8 AV	54.0	-7.2	1.24 H	157	13.2	33.6
3	*2412.00	97.3 PK			1.00 H	144	63.8	33.5
4	*2412.00	87.3 AV			1.00 H	144	53.8	33.5
5	4824.00	47.3 PK	74.0	-26.7	2.45 H	143	43.6	3.7
6	4824.00	34.1 AV	54.0	-19.9	2.45 H	143	30.4	3.7
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	58.7 PK	74.0	-15.3	3.67 V	304	25.1	33.6
2	2390.00	46.4 AV	54.0	-7.6	3.67 V	304	12.8	33.6
3	*2412.00	96.1 PK			3.62 V	313	62.6	33.5
4	*2412.00	86.1 AV			3.62 V	313	52.6	33.5
5	4824.00	45.5 PK	74.0	-28.5	1.53 V	244	41.8	3.7
6	4824.00	33.4 AV	54.0	-20.6	1.53 V	244	29.7	3.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	99.2 PK			1.00 H	145	65.8	33.4
2	*2437.00	89.0 AV			1.00 H	145	55.6	33.4
3	4874.00	47.1 PK	74.0	-26.9	1.94 H	256	43.2	3.9
4	4874.00	34.3 AV	54.0	-19.7	1.94 H	256	30.4	3.9
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	99.1 PK			4.00 V	307	65.7	33.4
2	*2437.00	88.9 AV			4.00 V	307	55.5	33.4
3	4874.00	45.7 PK	74.0	-28.3	2.36 V	157	41.8	3.9
4	4874.00	33.3 AV	54.0	-20.7	2.36 V	157	29.4	3.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz	FUNCTION	Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	99.0 PK			1.03 H	143	65.5	33.5
2	*2462.00	88.9 AV			1.03 H	143	55.4	33.5
3	2483.50	65.4 PK	74.0	-8.6	1.37 H	145	31.9	33.5
4	2483.50	48.4 AV	54.0	-5.6	1.37 H	145	14.9	33.5
5	4924.00	47.5 PK	74.0	-26.5	2.68 H	205	43.3	4.2
6	4924.00	34.8 AV	54.0	-19.2	2.68 H	205	30.6	4.2
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	98.9 PK			4.00 V	311	65.4	33.5
2	*2462.00	88.7 AV			4.00 V	311	55.2	33.5
3	2483.50	65.3 PK	74.0	-8.7	3.89 V	306	31.8	33.5
4	2483.50	48.2 AV	54.0	-5.8	3.89 V	306	14.7	33.5
5	4924.00	46.5 PK	74.0	-27.5	2.14 V	157	42.3	4.2
6	4924.00	34.1 AV	54.0	-19.9	2.14 V	157	29.9	4.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

802.11n (HT20)

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	60.4 PK	74.0	-13.6	1.04 H	169	26.8	33.6
2	2390.00	47.4 AV	54.0	-6.6	1.04 H	169	13.8	33.6
3	*2412.00	97.0 PK			1.00 H	148	63.5	33.5
4	*2412.00	86.9 AV			1.00 H	148	53.4	33.5
5	4824.00	45.5 PK	74.0	-28.5	1.57 H	148	41.8	3.7
6	4824.00	33.0 AV	54.0	-21.0	1.57 H	148	29.3	3.7
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	62.0 PK	74.0	-12.0	3.68 V	314	28.4	33.6
2	2390.00	48.2 AV	54.0	-5.8	3.68 V	314	14.6	33.6
3	*2412.00	96.7 PK			4.00 V	306	63.2	33.5
4	*2412.00	86.6 AV			4.00 V	306	53.1	33.5
5	4824.00	45.4 PK	74.0	-28.6	3.16 V	290	41.7	3.7
6	4824.00	33.0 AV	54.0	-21.0	3.16 V	290	29.3	3.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	97.3 PK			3.99 H	306	63.9	33.4
2	*2437.00	87.2 AV			3.99 H	306	53.8	33.4
3	4874.00	47.1 PK	74.0	-26.9	2.14 H	360	43.2	3.9
4	4874.00	33.8 AV	54.0	-20.2	2.14 H	360	29.9	3.9
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	97.7 PK			3.99 V	306	64.3	33.4
2	*2437.00	86.8 AV			3.99 V	306	53.4	33.4
3	4874.00	46.0 PK	74.0	-28.0	2.68 V	152	42.1	3.9
4	4874.00	33.6 AV	54.0	-20.4	2.68 V	152	29.7	3.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz	FUNCTION	Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	98.2 PK			1.00 H	139	64.7	33.5
2	*2462.00	88.1 AV			1.00 H	139	54.6	33.5
3	2483.50	65.4 PK	74.0	-8.6	1.05 H	143	31.9	33.5
4	2483.50	48.8 AV	54.0	-5.2	1.05 H	143	15.3	33.5
5	4924.00	46.1 PK	74.0	-27.9	1.14 H	265	41.9	4.2
6	4924.00	33.9 AV	54.0	-20.1	1.14 H	265	29.7	4.2
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	98.1 PK			4.00 V	310	64.6	33.5
2	*2462.00	87.9 AV			4.00 V	310	54.4	33.5
3	2483.50	67.4 PK	74.0	-6.6	3.83 V	303	33.9	33.5
4	2483.50	48.3 AV	54.0	-5.7	3.83 V	303	14.8	33.5
5	4924.00	47.4 PK	74.0	-26.6	3.25 V	209	43.2	4.2
6	4924.00	34.4 AV	54.0	-19.6	3.25 V	209	30.2	4.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

Below 1GHz worst-case data: 802.11b

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		
TEST MODE	A		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	53.18	13.5 QP	40.0	-26.5	1.50 H	24	27.5	-14.0
2	161.85	19.0 QP	43.5	-24.5	1.01 H	254	32.6	-13.6
3	200.66	19.0 QP	43.5	-24.5	1.01 H	272	35.5	-16.5
4	287.97	22.7 QP	46.0	-23.3	1.01 H	158	35.1	-12.4
5	402.46	21.3 QP	46.0	-24.7	1.50 H	228	31.6	-10.3
6	951.59	30.1 QP	46.0	-15.9	1.50 H	224	29.1	1.0
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	78.41	20.5 QP	40.0	-19.5	1.00 V	150	37.9	-17.4
2	132.74	26.7 QP	43.5	-16.8	1.49 V	32	41.7	-15.0
3	225.88	25.4 QP	46.0	-20.6	1.00 V	163	41.5	-16.1
4	313.20	24.4 QP	46.0	-21.6	1.49 V	59	36.1	-11.7
5	390.81	28.1 QP	46.0	-17.9	1.00 V	223	38.5	-10.4
6	503.36	26.1 QP	46.0	-19.9	1.25 V	219	34.4	-8.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		
TEST MODE	B		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	78.41	19.0 QP	40.0	-21.0	1.50 H	159	36.4	-17.4
2	130.80	27.6 QP	43.5	-15.9	1.01 H	76	42.6	-15.0
3	200.66	21.3 QP	43.5	-22.2	1.01 H	284	37.8	-16.5
4	225.88	21.3 QP	46.0	-24.7	1.50 H	316	37.4	-16.1
5	315.14	25.1 QP	46.0	-20.9	1.01 H	276	36.8	-11.7
6	730.38	26.7 QP	46.0	-19.3	1.50 H	135	29.9	-3.2
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	30.50	34.5 QP	40.0	-5.5	1.49 V	6	50.2	-15.7
2	136.62	35.3 QP	43.5	-8.2	1.99 V	13	49.8	-14.5
3	289.91	26.2 QP	46.0	-19.8	1.24 V	129	38.5	-12.3
4	315.14	28.0 QP	46.0	-18.0	1.00 V	80	39.7	-11.7
5	505.30	26.4 QP	46.0	-19.6	1.00 V	226	34.6	-8.2
6	745.91	31.9 QP	46.0	-14.1	1.24 V	12	34.6	-2.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		
TEST MODE	C		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	264.69	24.5 QP	46.0	-21.5	1.01 H	95	37.9	-13.4
2	315.14	23.5 QP	46.0	-22.5	1.01 H	93	35.2	-11.7
3	375.29	24.5 QP	46.0	-21.5	2.00 H	72	35.2	-10.7
4	712.92	31.2 QP	46.0	-14.8	1.51 H	12	35.1	-3.9
5	747.85	34.6 QP	46.0	-11.4	2.00 H	218	37.3	-2.7
6	936.07	38.6 QP	46.0	-7.4	1.51 H	12	38.2	0.4
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	39.60	27.6 QP	40.0	-12.4	1.50 V	46	42.2	-14.6
2	134.68	26.8 QP	43.5	-16.7	1.00 V	75	41.5	-14.7
3	315.14	29.1 QP	46.0	-16.9	1.50 V	113	40.8	-11.7
4	747.85	34.7 QP	46.0	-11.3	1.00 V	136	37.4	-2.7
5	885.62	39.1 QP	46.0	-6.9	1.99 V	96	39.7	-0.6
6	939.95	38.2 QP	46.0	-7.8	1.99 V	117	37.4	0.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		
TEST MODE	D		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	416.04	23.7 QP	46.0	-22.3	1.99 H	66	33.8	-10.1
2	441.26	22.8 QP	46.0	-23.2	1.99 H	90	32.1	-9.3
3	730.38	37.6 QP	46.0	-8.4	1.99 H	243	40.8	-3.2
4	747.85	38.0 QP	46.0	-8.0	1.49 H	272	40.7	-2.7
5	914.72	39.3 QP	46.0	-6.7	1.49 H	313	38.9	0.4
6	939.95	38.8 QP	46.0	-7.2	1.49 H	228	38.0	0.8
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	43.48	22.8 QP	40.0	-17.2	2.00 V	9	37.2	-14.4
2	134.68	27.4 QP	43.5	-16.1	1.50 V	45	42.1	-14.7
3	167.67	26.5 QP	43.5	-17.0	1.50 V	139	40.2	-13.7
4	315.14	27.7 QP	46.0	-18.3	1.50 V	77	39.4	-11.7
5	369.47	25.9 QP	46.0	-20.1	2.00 V	9	36.7	-10.8
6	916.66	40.9 QP	46.0	-5.1	2.00 V	9	40.5	0.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		
TEST MODE	E		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	53.18	25.0 QP	40.0	-15.0	1.00 H	137	39.0	-14.0
2	134.68	28.6 QP	43.5	-14.9	1.51 H	75	43.3	-14.7
3	214.24	19.1 QP	43.5	-24.4	1.51 H	293	35.3	-16.2
4	282.15	21.1 QP	46.0	-24.9	1.00 H	262	33.6	-12.5
5	707.10	31.5 QP	46.0	-14.5	2.00 H	330	35.4	-3.9
6	936.07	40.0 QP	46.0	-6.0	1.00 H	208	39.6	0.4
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	33.78	31.2 QP	40.0	-8.8	1.99 V	9	46.6	-15.4
2	136.62	31.0 QP	43.5	-12.5	1.00 V	63	45.5	-14.5
3	367.53	28.2 QP	46.0	-17.8	1.00 V	344	39.0	-10.8
4	716.80	36.3 QP	46.0	-9.7	1.00 V	126	40.0	-3.7
5	745.91	34.7 QP	46.0	-11.3	1.49 V	161	37.4	-2.7
6	939.95	39.7 QP	46.0	-6.3	1.00 V	232	38.9	0.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		
TEST MODE	F		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	134.68	27.9 QP	43.5	-15.6	1.99 H	320	42.6	-14.7
2	173.49	23.8 QP	43.5	-19.7	1.49 H	104	37.9	-14.1
3	730.38	38.7 QP	46.0	-7.3	1.00 H	68	41.9	-3.2
4	747.85	34.1 QP	46.0	-11.9	1.99 H	43	36.8	-2.7
5	895.32	40.3 QP	46.0	-5.7	1.49 H	18	40.8	-0.5
6	936.07	37.5 QP	46.0	-8.5	1.49 H	13	37.1	0.4
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	30.00	23.3 QP	40.0	-16.7	1.01 V	217	39.0	-15.7
2	57.07	26.5 QP	40.0	-13.5	1.51 V	37	40.7	-14.2
3	134.68	25.6 QP	43.5	-17.9	2.00 V	88	40.3	-14.7
4	167.67	23.9 QP	43.5	-19.6	1.51 V	262	37.6	-13.7
5	747.85	36.0 QP	46.0	-10.0	1.51 V	164	38.7	-2.7
6	936.07	38.9 QP	46.0	-7.1	1.01 V	131	38.5	0.4

Remarks:


1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

4.2 6dB Bandwidth Measurement

4.2.1 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.2.2 Test Setup



4.2.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.2.4 Test Procedure

- Set resolution bandwidth (RBW) = 100kHz.
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

4.2.5 Deviation from Test Standard

No deviation.

4.2.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.2.7 Test Result

802.11b

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
1	2412	8.11	0.5	Pass
6	2437	8.11	0.5	Pass
11	2462	9.03	0.5	Pass

802.11g


Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
1	2412	16.44	0.5	Pass
6	2437	16.43	0.5	Pass
11	2462	16.42	0.5	Pass

802.11n (HT20)


Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
1	2412	17.65	0.5	Pass
6	2437	17.63	0.5	Pass
11	2462	17.63	0.5	Pass

Spectrum Plot of Worst Value


802.11b



802.11g



802.11n (HT20)




4.3 Conducted Output Power Measurement

4.3.1 Limits of Conducted Output Power Measurement

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30dBm)

4.3.2 Test Setup



4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.3.4 Test Procedures

A peak / average power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak / average power sensor. Record the power level.

4.3.5 Deviation from Test Standard

No deviation.

4.3.6 EUT Operating Conditions

Same as item 4.3.6.

4.3.7 Test Results

For Peak Power

802.11b

Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass / Fail
1	2412	55.976	17.48	30.00	Pass
6	2437	55.081	17.41	30.00	Pass
11	2462	58.479	17.67	30.00	Pass

802.11g

Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass / Fail
1	2412	25.645	14.09	30.00	Pass
6	2437	26.242	14.19	30.00	Pass
11	2462	27.102	14.33	30.00	Pass

802.11n (HT20)

Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass / Fail
1	2412	17.418	12.41	30.00	Pass
6	2437	17.298	12.38	30.00	Pass
11	2462	18.113	12.58	30.00	Pass

For Average Power

802.11b

Channel	Frequency (MHz)	Average Power (mW)	Average Power (dBm)
1	2412	30.130	14.79
6	2437	29.854	14.75
11	2462	31.477	14.98

802.11g

Channel	Frequency (MHz)	Average Power (mW)	Average Power (dBm)
1	2412	13.740	11.38
6	2437	14.289	11.55
11	2462	14.588	11.64

802.11n (HT20)


Channel	Frequency (MHz)	Average Power (mW)	Average Power (dBm)
1	2412	9.333	9.70
6	2437	9.247	9.66
11	2462	9.795	9.91

4.4 Power Spectral Density Measurement

4.4.1 Limits of Power Spectral Density Measurement

The Maximum of Power Spectral Density Measurement is 8dBm.

4.4.2 Test Setup



4.4.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.4.4 Test Procedure

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth.
- Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set the VBW $\geq 3 \times \text{RBW}$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.

4.4.5 Deviation from Test Standard

No deviation.

4.4.6 EUT Operating Condition

Same as item 4.3.6

4.4.7 Test Results

802.11b

Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Pass / Fail
1	2412	-7.00	8.00	Pass
6	2437	-7.27	8.00	Pass
11	2462	-6.52	8.00	Pass

802.11g


Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Pass / Fail
1	2412	-13.15	8.00	Pass
6	2437	-11.48	8.00	Pass
11	2462	-12.69	8.00	Pass

802.11n (HT20)


Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Pass / Fail
1	2412	-13.80	8.00	Pass
6	2437	-12.86	8.00	Pass
11	2462	-13.79	8.00	Pass

Spectrum Plot of Worst Value


802.11b



802.11g



802.11n (HT20)




4.5 Conducted Out of Band Emission Measurement

4.5.1 Limits of Conducted Out of Band Emission Measurement

Below 20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.5.2 Test Setup



4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.5.4 Test Procedure

MEASUREMENT PROCEDURE REF

- Set the RBW = 100 kHz.
- Set the VBW $\geq$ 300 kHz.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

MEASUREMENT PROCEDURE OOB

- Set RBW = 100 kHz.
- Set VBW $\geq$ 300 kHz.
- Detector = peak.
- Sweep = auto couple.
- Trace Mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.

4.5.5 Deviation from Test Standard

No deviation.

4.5.6 EUT Operating Condition

Same as item 4.3.6


4.5.7 Test Results

The conducted emission test is performed on each TX port of operating mode without summing or adding 10log (N) since the limit is relative emission limit.


The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.

802.11b


CH 1




CH 6




CH 11



CH 1 Band edge




CH 11 Band edge




802.11g


CH 1




CH 6



CH 11





CH 1 Band edge





802.11n (HT20)



CH 1




CH 6




CH 11



CH 1 Band edge



CH 11 Band edge



5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---