



Washington Laboratories, Ltd.
7560 LINDBERGH DRIVE
GAIITHERSBURG, MD 20879
(301) 417 - 0220 FAX # (301) 417 - 9069

August 20, 2007

Mr. Rich Fabina
American Telecommunications Certification Body Inc.
6731 Whittier Ave
McLean, VA 22101

RE: Comments of August 18, 2007
APPLICATION: S5750016517 for Honeywell International Inc.

Dear Mr. Fabina:

Below are the comments that you have provided regarding the application for certification referenced above. Our responses to those comments are in ***bold italic***. Many responses refer you to additional exhibit(s) which has been uploaded to the application folder at the ATCB website.

Thank you for your attention. Please feel free to contact us for any additional information that you may require.

Regards,

Steven D. Koster
EMC Operations Manager

Brian J. Dettling
Documentation Specialist

WLL Project: 9455

1. The list of hopping frequencies recently provided in the amended operational description lists 2482 MHz as the highest operating channel for this transmitter. The test report tested 2481 MHz as the highest channel. Either provide a statement that the hopset that uses 2482 MHz as the highest channel is not used in the USA and supportive information that the user cannot select this hopset or retest this transmitter for bandedge compliance at the highest operating channel.

R. Additional frequency information has been added to the Operational Description. Please see “6517 Operational Description Rev 1”.

Further info is provided from the client here:

Please note that the highest frequency used in the USA hopping patterns [in the pattern labeled as **US Guard Bands (3)**] is 2481 MHz.

Note that 2482 MHz is only used in the hopping pattern labeled as **EU Guard Bands (7)**, in other words, 2482 MHz is used only for European applications.