

FCC RF Test Report

APPLICANT : Mosby LLC
EQUIPMENT : Tablet PC
MODEL NAME : GL056ZE
FCC ID : S5R-4940
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DSS) Spread Spectrum Transmitter

The testing was completed on Oct. 03, 2013. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the procedures and shown to be compliant with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.



Reviewed by: Joseph Lin / Supervisor



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.

TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION.....	5
1.1 Applicant.....	5
1.2 Feature of Equipment Under Test	5
1.3 Product Specification of Equipment Under Test.....	5
1.4 Modification of EUT	5
1.5 Testing Site.....	6
1.6 Applied Standards	6
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....	7
2.1 Descriptions of Test Mode.....	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	9
2.4 Support Unit used in test configuration and system	10
2.5 EUT Operation Test Setup	10
2.6 Measurement Results Explanation Example.....	11
3 TEST RESULT	12
3.1 Number of Channel Measurement	12
3.2 Hopping Channel Separation Measurement	14
3.3 Dwell Time Measurement.....	21
3.4 20dB Bandwidth Measurement	24
3.5 Peak Output Power Measurement	31
3.6 Conducted Band Edges Measurement.....	33
3.7 Conducted Spurious Emission Measurement	40
3.8 Radiated Band Edges and Spurious Emission Measurement	50
3.9 AC Conducted Emission Measurement.....	61
3.10 Antenna Requirements.....	71
4 LIST OF MEASURING EQUIPMENT.....	72
5 UNCERTAINTY OF EVALUATION.....	73

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR332727-07A	Rev. 01	Initial issue of report	Oct. 08, 2013

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(1)	Number of Channels	$\geq 15\text{Chs}$	Pass	-
3.2	15.247(a)(1)	Hopping Channel Separation	$\geq 2/3$ of 20dB BW	Pass	-
3.3	15.247(a)(1)	Dwell Time of Each Channel	$\leq 0.4\text{sec}$ in 31.6sec period	Pass	-
3.4	15.247(a)(1)	20dB Bandwidth	NA	Pass	-
3.5	15.247(b)(1)	Peak Output Power	$\leq 125\text{ mW}$	Pass	-
3.6	15.247(d)	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
3.7	15.247(d)	Conducted Spurious Emission	$\leq 20\text{dBc}$	Pass	-
3.8	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 9.90 dB at 2483.530 MHz
3.9	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 10.20 dB at 1.622 MHz
3.10	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-

1 General Description

1.1 Applicant

Mosby LLC
2825 E. Cottonwood Parkway
Suite 500
Salt Lake City, Utah 84121

1.2 Feature of Equipment Under Test

Product Feature	
Equipment	Tablet PC
Model Name	GL056ZE
FCC ID	S5R-4940
EUT supports Radios application	GSM/EGPRS/WCDMA/HSPA/LTE WLAN 11b/g/n (HT20), WLAN 11a/n (HT20/HT40) Bluetooth v3.0

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.3 Product Specification of Equipment Under Test

Product Specification subjective to this standard	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	79
Carrier Frequency of Each Channel	2402+n*1 MHz; n=0~78
Maximum Output Power to Antenna	Bluetooth BR(1Mbps) : 6.1 dBm (0.0041 W) Bluetooth EDR (2Mbps) : 7.5 dBm (0.0056 W) Bluetooth EDR (3Mbps) : 7.4 dBm (0.0055 W)
Antenna Type	Fixed Internal Antenna with gain 2.10 dBi
Type of Modulation	Bluetooth BR (1Mbps) : GFSK Bluetooth EDR (2Mbps) : $\pi/4$ -DQPSK Bluetooth EDR (3Mbps) : 8-DPSK

1.4 Modification of EUT

No modifications are made to the EUT during all test items.

1.5 Testing Site

Test Site	SPORTON INTERNATIONAL INC.			
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL: +886-3-3273456 / FAX: +886-3-3284978			
Test Site No.	Sporton Site No.			FCC Registration No.
	TH02-HY	CO05-HY	03CH07-HY	722060

Note: The test site complies with ANSI C63.4 2003 requirement.

1.6 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

FCC Part 15 Subpart C §15.247

FCC Public Notice DA 00-705

ANSI C63.4-2003

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Descriptions of Test Mode

Preliminary tests were performed in different data rates and recorded the RF output power in the following table:

Channel	Frequency	Bluetooth RF Output Power		
		Data Rate / Modulation		
		GFSK	$\pi/4$ -DQPSK	8-DPSK
		1Mbps	2Mbps	3Mbps
Ch00	2402MHz	5.4 dBm	7.2 dBm	7.2 dBm
Ch39	2441MHz	5.9 dBm	7.3 dBm	7.2 dBm
Ch78	2480MHz	6.1 dBm	7.5 dBm	7.4 dBm

Remark:

1. All the test data for each data rate were verified, but only the worst case was reported.
 2. The worse data rate was 2Mbps for Radiated Spurious Emissions and all the data rate were tested for RF conducted items and reported.
 3. For AFH mode, the power and other characteristics remain the same as 1Mbps data rate.
- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). Pre-scanned tests, X, Y, Z in three orthogonal panels, and different data rates were conducted to determine the final configuration (X plane as worst plane) from all possible combinations, and the worst mode of radiated spurious emissions is Bluetooth 2Mbps mode, and recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.


2.2 Test Mode

The following summary table is showing all test modes to demonstrate in compliance with the standard.


Summary table of Test Cases			
Test Item	Data Rate / Modulation		
	Bluetooth BR 1Mbps GFSK	Bluetooth EDR 2Mbps $\pi/4$ -DQPSK	Bluetooth EDR 3Mbps 8-DPSK
Conducted Test Cases	Mode 1: CH00_2402 MHz	Mode 4: CH00_2402 MHz	Mode 7: CH00_2402 MHz
	Mode 2: CH39_2441 MHz	Mode 5: CH39_2441 MHz	Mode 8: CH39_2441 MHz
	Mode 3: CH78_2480 MHz	Mode 6: CH78_2480 MHz	Mode 9: CH78_2480 MHz
Radiated Test Cases	Bluetooth EDR 2Mbps $\pi/4$ -DQPSK		
	Mode 1: CH00_2402 MHz Mode 2: CH39_2441 MHz Mode 3: CH78_2480 MHz		
AC Conducted Emission	Mode 1 :WCDMA Band II Idle + Bluetooth Link + WLAN (2.4GHz, 11n HT20, Ch06, MCS0) Link + H Pattern + Earphone + USB Cable (Charging from Adapter)		
	Mode 2 :WCDMA Band II Idle + Bluetooth Link + WLAN (5GHz, 11n HT20, Ch157, MCS0) Link + H Pattern + Earphone + USB Cable (Charging from Adapter)		
	Mode 3 :WCDMA Band II Idle + WLAN (2.4GHz, 11n HT20, Ch06, MCS0) MIMO Tx + H Pattern + Earphone + USB Cable (Charging from Adapter)		
	Mode 4 :WCDMA Band II Idle + WLAN (5GHz, 11n HT20, Ch157, MCS0) MIMO Tx + H Pattern + Earphone + USB Cable (Charging from Adapter)		
Remark:			
1. For radiated test cases, the worst mode data rate 2Mbps was reported only, because this data rate has the highest RF output power at preliminary tests, and the conducted spurious emissions and conducted band edge measurement for each data rate are no worse than 2Mbps, and no other significantly frequencies found in conducted spurious emission.			
2. The worst case of conducted emission is mode 3.			

2.3 Connection Diagram of Test System


<Bluetooth Tx Mode>



<AC Conducted Emission Mode>



<AC Conducted Emission Mode for MIMO Tx>



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
3.	WLAN AP	D-Link	DIR-628	KA2DIR628A2	N/A	Unshielded, 1.8 m
4.	Notebook	DELL	Latitude E6320	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
5.	iPod Earphone	Apple	N/A	N/A	Unshielded, 1.0 m	N/A
6.	Adapter	Foxlink	A02710	Verification	N/A	N/A

2.5 EUT Operation Test Setup

For Bluetooth function, programmed RF utility, “ADB” installed in the notebook make the EUT provides functions like channel selection and power level for continuous transmitting and receiving signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 Number of Channel Measurement

3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedure

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = the frequency band of operation; RBW $\geq$ 1% of the span; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. The number of hopping frequency used is defined as the number of total channel.
7. Record the measurement data derived from spectrum analyzer.


3.1.4 Test Setup




3.1.5 Test Result of Number of Hopping Frequency

Test Mode :	2Mbps	Temperature :	24~26°C
Test Engineer :	Stuart Lin	Relative Humidity :	48~51%
Number of Hopping (Channel)	Adaptive Frequency Hopping (Channel)	Limits (Channel)	Pass/Fail
79	20	> 15	Pass

Number of Hopping Channel Plot on Channel 00 - 78



Date: 11.SEP.2013 10:05:01



Date: 11.SEP.2013 10:12:53

3.2 Hopping Channel Separation Measurement

3.2.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels; $RBW \geq 1\%$ of the span;
 $VBW \geq RBW$; Sweep = auto; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.2.4 Test Setup




3.2.5 Test Result of Hopping Channel Separation

Test Mode :	1Mbps	Temperature :	24~26°C
Test Engineer :	Stuart Lin	Relative Humidity :	48~51%


Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.002	0.6933	Pass
39	2441	1.002	0.6907	Pass
78	2480	1.002	0.6907	Pass

Channel Separation Plot on Channel 00 - 01




Date: 11.SEP.2013 09:08:40

Channel Separation Plot on Channel 39 - 40



Date: 11.SEP.2013 09:09:41

Channel Separation Plot on Channel 77 - 78




Date: 11.SEP.2013 09:12:32

Test Mode :	2Mbps	Temperature :	24~26°C
Test Engineer :	Stuart Lin	Relative Humidity :	48~51%


Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.002	0.7680	Pass
39	2441	1.002	0.7680	Pass
78	2480	1.002	0.7640	Pass

Channel Separation Plot on Channel 00 - 01




Date: 11.SEP.2013 09:34:06

Channel Separation Plot on Channel 39 - 40




Date: 11.SEP.2013 09:31:27

Channel Separation Plot on Channel 77 - 78




Date: 11.SEP.2013 09:24:44

Channel Separation Plot on Channel 39 - 40



Date: 11.SEP.2013 09:47:38

Channel Separation Plot on Channel 77 - 78



Date: 11.SEP.2013 09:43:24

3.3 Dwell Time Measurement

3.3.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW $\geq$ RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.3.4 Test Setup



3.3.5 Test Result of Dwell Time


Test Mode :	DH5	Temperature :	24~26°C
Test Engineer :	Stuart Lin	Relative Humidity :	48~51%

Mode	Hopping Channel Number	Hops Over Occupancy Time(hops)	Package Transfer Time (msec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
Normal	79	106.67	2.93	0.31	0.4	Pass
AFH	20	53.33	2.93	0.16	0.4	Pass

Remark:

1. In normal mode, hopping rate is 1600hops/s with 6 slots in 79 hopping channels.
With channel hopping rate $(1600 / 6 / 79)$ in Occupancy Time Limit (0.4×79) (s),
Hops Over Occupancy Time comes to $(1600 / 6 / 79) \times (0.4 \times 79) = 106.67$ hops.
2. In AFH mode, hopping rate is 800hops/s with 6 slots in 20 hopping channels.
With channel hopping rate $(800 / 6 / 20)$ in Occupancy Time Limit (0.4×20) (s),
Hops Over Occupancy Time comes to $(800 / 6 / 20) \times (0.4 \times 20) = 53.33$ hops.
3. Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time

Package Transfer Time Plot



Date: 29.AUG.2013 10:18:45

3.4 20dB Bandwidth Measurement

3.4.1 Limit of 20dB Bandwidth

Reporting only


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the following spectrum analyzer settings for 20dB Bandwidth measurement.
Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel;
RBW $\geq$ 1% of the 20 dB bandwidth; VBW $\geq$ RBW; Sweep = auto; Detector function = peak;
Trace = max hold.
5. Measure and record the results in the test report.

3.4.4 Test Setup




3.4.5 Test Result of 20dB Bandwidth

Test Mode :	1Mbps	Temperature :	24~26°C
Test Engineer :	Stuart Lin	Relative Humidity :	48~51%


Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.040
39	2441	1.036
78	2480	1.036

20 dB Bandwidth Plot on Channel 00




Date: 3.OCT.2013 16:33:24

20 dB Bandwidth Plot on Channel 39



Date: 3.OCT.2013 16:32:22

20 dB Bandwidth Plot on Channel 78




Date: 3.OCT.2013 16:31:21

Test Mode :	2Mbps	Temperature :	24~26℃
Test Engineer :	Stuart Lin	Relative Humidity :	48~51%


Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.152
39	2441	1.152
78	2480	1.146

20 dB Bandwidth Plot on Channel 00




Date: 3.OCT.2013 16:27:11

20 dB Bandwidth Plot on Channel 39



Date: 3.OCT.2013 16:28:31

20 dB Bandwidth Plot on Channel 78




Date: 3.OCT.2013 16:29:43

Test Mode :	3Mbps	Temperature :	24~26℃
Test Engineer :	Stuart Lin	Relative Humidity :	48~51%


Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.200
39	2441	1.200
78	2480	1.200

20 dB Bandwidth Plot on Channel 00




Date: 3.OCT.2013 16:25:46

20 dB Bandwidth Plot on Channel 39



Date: 3.OCT.2013 16:23:25

20 dB Bandwidth Plot on Channel 78



Date: 3.OCT.2013 16:24:32

3.5 Peak Output Power Measurement

3.5.1 Limit of Peak Output Power

Section 15.247 (b) The maximum peak conducted output power of the intentional radiator shall not exceed the following: (1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts. The power limit for 1Mbps is 1watt, and for 2Mbps, 3Mbps and AFH are 0.125 watts.


3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power with cable loss and record the results in the test report.
5. Measure and record the results in the test report.

3.5.4 Test Setup



3.5.5 Test Result of Peak Output Power

Test Mode :	1Mbps	Temperature :	24~26℃
Test Engineer :	Stuart Lin	Relative Humidity :	48~51%

Channel	Frequency (MHz)	RF Power (dBm)		
		GFSK	Max. Limits (dBm)	Pass/Fail
		1 Mbps		
00	2402	5.4	20.97	Pass
39	2441	5.9	20.97	Pass
78	2480	6.1	20.97	Pass

Note: For AFH mode using 20 hopping channels, the maximum output power limit is 20.97dBm.

Test Mode :	2Mbps	Temperature :	24~26℃
Test Engineer :	Stuart Lin	Relative Humidity :	48~51%

Channel	Frequency (MHz)	RF Power (dBm)		
		$\pi/4$ -DQPSK	Max. Limits (dBm)	Pass/Fail
		2 Mbps		
00	2402	7.2	20.97	Pass
39	2441	7.3	20.97	Pass
78	2480	7.5	20.97	Pass

Test Mode :	3Mbps	Temperature :	24~26℃
Test Engineer :	Stuart Lin	Relative Humidity :	48~51%

Channel	Frequency (MHz)	RF Power (dBm)		
		8-DPSK	Max. Limits (dBm)	Pass/Fail
		3 Mbps		
00	2402	7.2	20.97	Pass
39	2441	7.2	20.97	Pass
78	2480	7.4	20.97	Pass

3.6 Conducted Band Edges Measurement

3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The testing follows the guidelines in Band-edge Compliance of RF Conducted Emissions of FCC Public Notice DA 00-705 Measurement Guidelines.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Set RBW = 100kHz, VBW = 300kHz. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 300kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
4. Enable hopping function of the EUT and then repeat step 2. and 3.
5. Measure and record the results in the test report.


3.6.4 Test Setup



3.6.6 Test Result of Conducted Band Edges


Test Mode :	1Mbps	Temperature :	24~26°C
Test Channel :	00 and 78	Relative Humidity :	48~51%
		Test Engineer :	Stuart Lin

Low Band Edge Plot on Channel 00



Date: 11.SEP.2013 09:04:29


High Band Edge Plot on Channel 78



Date: 11.SEP.2013 09:13:53


Test Mode :	2Mbps	Temperature :	24~26℃
Test Channel :	00 and 78	Relative Humidity :	48~51%
		Test Engineer :	Stuart Lin

Low Band Edge Plot on Channel 00



Date: 11.SEP.2013 09:37:25


High Band Edge Plot on Channel 78



Date: 11.SEP.2013 09:41:11


Test Mode :	3Mbps	Temperature :	24~26℃
Test Channel :	00 and 78	Relative Humidity :	48~51%
		Test Engineer :	Stuart Lin

Low Band Edge Plot on Channel 00



Date: 11.SEP.2013 09:51:28

High Band Edge Plot on Channel 78




Date: 11.SEP.2013 09:44:35

3.6.7 Test Result of Conducted Hopping Mode Band Edges


Test Mode :	1Mbps	Temperature :	24~26°C
Test Engineer :	Stuart Lin	Relative Humidity :	48~51%

1Mbps Hopping Mode Low Band Edge Plot



Date: 11.SEP.2013 10:31:34


1Mbps Hopping Mode High Band Edge Plot



Date: 11.SEP.2013 10:29:27


Test Mode :	2Mbps	Temperature :	24~26℃
Test Engineer :	Stuart Lin	Relative Humidity :	48~51%

2Mbps Hopping Mode Low Band Edge Plot



Date: 11.SEP.2013 10:25:22

2Mbps Hopping Mode High Band Edge Plot



Date: 11.SEP.2013 10:27:45

3.7 Conducted Spurious Emission Measurement

3.7.1 Limit of Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


3.7.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.7.3 Test Procedure

1. The testing follows the guidelines in Spurious RF Conducted Emissions of FCC Public Notice DA 00-705 Measurement Guidelines
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW = 300kHz, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


3.7.4 Test Setup



3.7.5 Test Result of Conducted Spurious Emission


Test Mode :	1Mbps	Temperature :	24~26°C
Test Channel :	00	Relative Humidity :	48~51%
		Test Engineer :	Stuart Lin

1Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Date: 11.SEP.2013 09:06:09


1Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz



Date: 11.SEP.2013 09:06:31


Test Mode :	1Mbps	Temperature :	24~26°C
Test Channel :	39	Relative Humidity :	48~51%
		Test Engineer :	Stuart Lin

1Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Date: 11.SEP.2013 09:11:11


1Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz



Date: 11.SEP.2013 09:11:33


Test Mode :	1Mbps	Temperature :	24~26°C
Test Channel :	78	Relative Humidity :	48~51%
		Test Engineer :	Stuart Lin

1Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Date: 11.SEP.2013 09:15:15


1Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz



Date: 11.SEP.2013 09:15:37


Test Mode :	2Mbps	Temperature :	24~26°C
Test Channel :	00	Relative Humidity :	48~51%
		Test Engineer :	Stuart Lin

2Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Date: 11.SEP.2013 09:38:43


2Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz



Date: 11.SEP.2013 09:39:04


Test Mode :	2Mbps	Temperature :	24~26°C
Test Channel :	39	Relative Humidity :	48~51%
		Test Engineer :	Stuart Lin

2Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Date: 11.SEP.2013 09:27:59


2Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz



Date: 11.SEP.2013 09:28:21


Test Mode :	2Mbps	Temperature :	24~26°C
Test Channel :	78	Relative Humidity :	48~51%
		Test Engineer :	Stuart Lin

2Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Date: 11.SEP.2013 23:53:46


2Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz



Date: 11.SEP.2013 23:54:07


Test Mode :	3Mbps	Temperature :	24~26°C
Test Channel :	00	Relative Humidity :	48~51%
		Test Engineer :	Stuart Lin

3Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Date: 11.SEP.2013 09:52:28


3Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz



Date: 11.SEP.2013 09:52:50


Test Mode :	3Mbps	Temperature :	24~26°C
Test Channel :	39	Relative Humidity :	48~51%
		Test Engineer :	Stuart Lin

3Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Date: 11.SEP.2013 09:49:05


3Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz



Date: 11.SEP.2013 09:49:26


Test Mode :	3Mbps	Temperature :	24~26°C
Test Channel :	78	Relative Humidity :	48~51%
		Test Engineer :	Stuart Lin

3Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Date: 11.SEP.2013 09:45:38

3Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz



Date: 11.SEP.2013 09:46:00

3.8 Radiated Band Edges and Spurious Emission Measurement

3.8.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.8.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.8.3 Test Procedures

1. The testing follows the guidelines in Spurious Radiated Emissions of FCC Public Notice DA 00-705 Measurement Guidelines.
2. The EUT was placed on a turntable with 0.8 meter above ground.
3. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz, RBW=1MHz for $f > 1$ GHz ; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
 - (3) For average measurement: use duty cycle correction factor method per 15.35(c).
Duty cycle = On time/100 milliseconds
On time = $N_1 * L_1 + N_2 * L_2 + \dots + N_{n-1} * L_{n-1} + N_n * L_n$
Where N_1 is number of type 1 pulses, L_1 is length of type 1 pulses, etc.
Average Emission Level = Peak Emission Level + $20 * \log(\text{Duty cycle})$
7. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level


Note: The average levels were calculated from the peak level corrected with duty cycle correction factor (-24.70dB) derived from $20 \log(\text{dwell time}/100\text{ms})$. This correction is only for signals that hop with the fundamental signal, such as bandedge and harmonic. Other spurious signals that are independent of the hopping signal would not use this correction

3.8.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz




3.8.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.


3.8.6 Duty cycle correction factor for average measurement

2DH5 on time (One Pulse) Plot on Channel 39



Date: 27.AUG.2013 23:50:52

2DH5 on time (Count Pulses) Plot on Channel 39



Date: 27.AUG.2013 23:57:44

Note:

1. Worst case Duty cycle = on time/100 milliseconds = $2 * 2.91 / 100 = 5.82 \%$
2. Worst case Duty cycle correction factor = $20 * \log(\text{Duty cycle}) = -24.70 \text{ dB}$
3. 2DH5 has the highest duty cycle worst case and is reported.

Duty Cycle Correction Factor Consideration for AFH mode:

Bluetooth normal hopping rate is 1600Hz and reduced to 800Hz in AFH mode; due to the reduced number of hopping frequencies, with the same packet configuration the dwell time in each channel frequency within 100msec period is longer in AFH mode than normal mode.

In AFH mode, the minimum hopping frequencies are 20, to get the longest dwell time DH5 packet is observed; the period to have DH5 packet completing one hopping sequence is

$$2.91 \text{ ms} \times 20 \text{ channels} = 58.2 \text{ ms}$$

There cannot be 2 complete hopping sequences within 100ms period, considering the random hopping behavior, maximum 2 hops can be possibly observed within the period. $[100\text{ms} / 57.6\text{ms}] = 2 \text{ hops}$

Thus, the maximum possible ON time:

$$2.91 \text{ ms} \times 2 = 5.82 \text{ ms}$$

Worst case Duty Cycle Correction factor, which is derived from the maximum possible ON time,

$$20 \times \log(5.82 \text{ ms}/100\text{ms}) = -24.70 \text{ dB}$$

3.8.7 Test Result of Radiated Spurious at Band Edges

Test Mode :	2Mbps	Temperature :	21~24°C
Test Channel :	00	Relative Humidity :	51~53%
		Test Engineer :	Eric Shih

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2372.46	46.26	-27.74	74	41.37	32.28	6.88	34.27	191	248	Peak
2372.46	21.56	-32.44	54	-	-	-	-	-	-	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2323.77	45.94	-28.06	74	41.13	32.23	6.8	34.22	159	325	Peak
2323.77	21.24	-32.76	54	-	-	-	-	-	-	Average

Test Mode :	2Mbps	Temperature :	21~24°C
Test Channel :	78	Relative Humidity :	51~53%
		Test Engineer :	Eric Shih

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.68	62.41	-11.59	74	57.4	32.38	7.06	34.43	115	353	Peak
2483.68	37.71	-16.29	54	-	-	-	-	-	-	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.53	64.1	-9.9	74	59.09	32.38	7.06	34.43	179	353	Peak
2483.53	39.4	-14.6	54	-	-	-	-	-	-	Average

3.8.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Note: Pre-scanned all test modes and only choose the worst case mode recorded in the test report for radiated spurious emission below 1GHz.

Test Mode :	2Mbps	Temperature :	21~24°C
Test Channel :	00	Relative Humidity :	51~53%
Test Engineer :	Eric Shih	Polarization :	Horizontal
Remark :	2402 MHz is fundamental signal which can be ignored.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2402	102.51	-	-	97.6	32.3	6.91	34.3	191	248	Peak
2402	77.81	-	-	-	-	-	-	-	-	Average
4803	40.11	-33.89	74	56.34	33.98	8.75	58.96	100	0	Peak
4803	15.41	-38.59	54	-	-	-	-	-	-	Average

Note: Other harmonics are lower than background noise.

Test Mode :	2Mbps	Temperature :	21~24°C
Test Channel :	00	Relative Humidity :	51~53%
Test Engineer :	Eric Shih	Polarization :	Vertical
Remark :	2402 MHz is fundamental signal which can be ignored.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2402	104.71	-	-	99.8	32.3	6.91	34.3	159	325	Peak
2402	80.01	-	-	-	-	-	-	-	-	Average
4803	40.7	-33.3	74	56.93	33.98	8.75	58.96	100	0	Peak
4803	16	-38	54	-	-	-	-	-	-	Average

Note: Other harmonics are lower than background noise.

Test Mode :	2Mbps	Temperature :	21~24°C
Test Channel :	39	Relative Humidity :	51~53%
Test Engineer :	Eric Shih	Polarization :	Horizontal
Remark :	2442 MHz is fundamental signal which can be ignored.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2442	102.04	-	-	97.09	32.35	6.99	34.39	129	352	Peak
2442	77.34	-	-	-	-	-	-	-	-	Average
4881	40.66	-33.34	74	56.69	33.95	8.85	58.83	100	0	Peak
4881	15.96	-38.04	54	-	-	-	-	-	-	Average
7323	42.3	-31.7	74	53.6	35.53	10.91	57.74	100	0	Peak
7323	17.6	-36.4	54	-	-	-	-	-	-	Average

Note: Other harmonics are lower than background noise.

Test Mode :	2Mbps	Temperature :	21~24°C
Test Channel :	39	Relative Humidity :	51~53%
Test Engineer :	Eric Shih	Polarization :	Vertical
Remark :	2442 MHz is fundamental signal which can be ignored.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2442	102.22	-	-	97.27	32.35	6.99	34.39	188	336	Peak
2442	77.52	-	-	-	-	-	-	-	-	Average
4881	40.72	-33.28	74	56.75	33.95	8.85	58.83	100	0	Peak
4881	16.02	-37.98	54	-	-	-	-	-	-	Average
7323	41.38	-32.62	74	52.68	35.53	10.91	57.74	100	0	Peak
7323	16.68	-37.32	54	-	-	-	-	-	-	Average

Note: Other harmonics are lower than background noise.

Test Mode :	2Mbps	Temperature :	21~24°C
Test Channel :	78	Relative Humidity :	51~53%
Test Engineer :	Eric Shih	Polarization :	Horizontal
Remark :	2480 MHz is fundamental signal which can be ignored.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
123.96	18.57	-24.93	43.5	36.85	11.7	1.12	31.1	-	-	Peak
167.97	20.92	-22.58	43.5	41.06	9.75	1.23	31.12	-	-	Peak
222.78	23.29	-22.71	46	42.13	10.72	1.44	31	-	-	Peak
458.2	21.46	-24.54	46	32.72	17.21	2.32	30.79	-	-	Peak
608.7	22.38	-23.62	46	30.37	19.87	2.72	30.58	-	-	Peak
850.2	24.42	-21.58	46	28.95	22.6	3.27	30.4	100	47	Peak
2480	101.5	-	-	96.49	32.38	7.06	34.43	115	353	Peak
2480	76.8	-	-	-	-	-	-	-	-	Average
4959	40.53	-33.47	74	56.36	33.91	8.92	58.66	100	0	Peak
4959	15.83	-38.17	54	-	-	-	-	-	-	Average
7440	42.43	-31.57	74	53.73	35.51	11.04	57.85	100	0	Peak
7440	17.73	-36.27	54	-	-	-	-	-	-	Average

Note: Other harmonics are lower than background noise.

Test Mode :	2Mbps	Temperature :	21~24°C
Test Channel :	78	Relative Humidity :	51~53%
Test Engineer :	Eric Shih	Polarization :	Vertical
Remark :	2480 MHz is fundamental signal which can be ignored.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
42.96	24.93	-15.07	40	43.79	11.7	0.64	31.2	100	58	Peak
122.88	22.24	-21.26	43.5	40.52	11.7	1.12	31.1	-	-	Peak
223.05	24.1	-21.9	46	42.94	10.72	1.44	31	-	-	Peak
339.9	21.99	-24.01	46	36.73	14.37	1.89	31	-	-	Peak
638.8	22.23	-23.77	46	29.83	20.11	2.81	30.52	-	-	Peak
871.2	25.56	-20.44	46	29.81	22.81	3.3	30.36	-	-	Peak
2480	102.59	-	-	97.58	32.38	7.06	34.43	179	353	Peak
2480	77.89	-	-	-	-	-	-	-	-	Average
4959	40.25	-33.75	74	56.08	33.91	8.92	58.66	100	0	Peak
4959	15.55	-38.45	54	-	-	-	-	-	-	Average
7440	42.49	-31.51	74	53.79	35.51	11.04	57.85	100	0	Peak
7440	17.79	-36.21	54	-	-	-	-	-	-	Average

Note: Other harmonics are lower than background noise.

3.9 AC Conducted Emission Measurement

3.9.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.9.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.9.3 Test Procedures


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.9.4 Test Setup



3.9.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	20~22℃
Test Engineer :	Slash Huang	Relative Humidity :	45~47%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	WCDMA Band II Idle + Bluetooth Link + WLAN (2.4GHz, 11n HT20, Ch06, MCS0) Link + H Pattern + Earphone + USB Cable (Charging from Adapter)		




Final Result : Quasi-Peak

Frequency (MHz)	Quasi-Peak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.166000	46.4	Off	L1	19.4	18.8	65.2
0.222000	38.5	Off	L1	19.4	24.2	62.7
0.278000	33.3	Off	L1	19.3	27.6	60.9
0.558000	36.7	Off	L1	19.4	19.3	56.0
3.254000	36.5	Off	L1	19.6	19.5	56.0
3.854000	36.8	Off	L1	19.6	19.2	56.0

Final Result : Average

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.166000	38.2	Off	L1	19.4	17.0	55.2
0.222000	27.9	Off	L1	19.4	24.8	52.7
0.278000	21.4	Off	L1	19.3	29.5	50.9
0.558000	26.9	Off	L1	19.4	19.1	46.0
3.254000	25.9	Off	L1	19.6	20.1	46.0
3.854000	25.2	Off	L1	19.6	20.8	46.0

Test Mode :	Mode 1	Temperature :	20~22℃
Test Engineer :	Slash Huang	Relative Humidity :	45~47%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	WCDMA Band II Idle + Bluetooth Link + WLAN (2.4GHz, 11n HT20, Ch06, MCS0) Link + H Pattern + Earphone + USB Cable (Charging from Adapter)		




Final Result : Quasi-Peak

Frequency (MHz)	Quasi-Peak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.158000	42.9	Off	N	19.3	22.7	65.6
0.214000	33.6	Off	N	19.4	29.4	63.0
1.358000	30.9	Off	N	19.5	25.1	56.0
3.054000	34.6	Off	N	19.6	21.4	56.0
3.494000	35.8	Off	N	19.6	20.2	56.0
4.054000	36.5	Off	N	19.6	19.5	56.0

Final Result : Average

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.158000	35.6	Off	N	19.3	20.0	55.6
0.214000	22.0	Off	N	19.4	31.0	53.0
1.358000	21.5	Off	N	19.5	24.5	46.0
3.054000	23.8	Off	N	19.6	22.2	46.0
3.494000	24.0	Off	N	19.6	22.0	46.0
4.054000	24.5	Off	N	19.6	21.5	46.0

Test Mode :	Mode 2	Temperature :	20~22℃
Test Engineer :	Slash Huang	Relative Humidity :	45~47%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	WCDMA Band II Idle + Bluetooth Link + WLAN (5GHz, 11n HT20, Ch157, MCS0) Link + H Pattern + Earphone + USB Cable (Charging from Adapter)		




Final Result : Quasi-Peak

Frequency (MHz)	Quasi-Peak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.158000	41.9	Off	L1	19.3	23.7	65.6
0.454000	37.1	Off	L1	19.3	19.7	56.8
0.526000	34.4	Off	L1	19.4	21.6	56.0
2.902000	35.8	Off	L1	19.6	20.2	56.0
3.262000	36.3	Off	L1	19.6	19.7	56.0
3.766000	36.9	Off	L1	19.6	19.1	56.0

Final Result : Average

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.158000	35.1	Off	L1	19.3	20.5	55.6
0.454000	27.8	Off	L1	19.3	19.0	46.8
0.526000	25.9	Off	L1	19.4	20.1	46.0
2.902000	25.5	Off	L1	19.6	20.5	46.0
3.262000	25.8	Off	L1	19.6	20.2	46.0
3.766000	25.8	Off	L1	19.6	20.2	46.0

Test Mode :	Mode 2	Temperature :	20~22℃
Test Engineer :	Slash Huang	Relative Humidity :	45~47%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	WCDMA Band II Idle + Bluetooth Link + WLAN (5GHz, 11n HT20, Ch157, MCS0) Link + H Pattern + Earphone + USB Cable (Charging from Adapter)		




Final Result : Quasi-Peak

Frequency (MHz)	Quasi-Peak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.158000	39.8	Off	N	19.3	25.8	65.6
0.174000	38.4	Off	N	19.4	26.4	64.8
0.190000	34.3	Off	N	19.4	29.7	64.0
3.142000	35.1	Off	N	19.7	20.9	56.0
3.766000	36.3	Off	N	19.6	19.7	56.0
4.318000	35.4	Off	N	19.6	20.6	56.0

Final Result : Average

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.158000	27.8	Off	N	19.3	27.8	55.6
0.174000	28.6	Off	N	19.4	26.2	54.8
0.190000	25.0	Off	N	19.4	29.0	54.0
3.142000	23.7	Off	N	19.7	22.3	46.0
3.766000	24.4	Off	N	19.6	21.6	46.0
4.318000	24.0	Off	N	19.6	22.0	46.0

Test Mode :	Mode 3	Temperature :	20~22℃
Test Engineer :	Slash Huang	Relative Humidity :	45~47%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	WCDMA Band II Idle + WLAN (2.4GHz, 11n HT20, Ch06, MCS0) MIMO Tx + H Pattern + Earphone + USB Cable (Charging from Adapter)		




Final Result : Quasi-Peak

Frequency (MHz)	Quasi-Peak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	42.6	Off	L1	19.4	23.4	66.0
0.174000	39.6	Off	L1	19.4	25.2	64.8
0.438000	36.5	Off	L1	19.4	20.6	57.1
0.550000	39.7	Off	L1	19.4	16.3	56.0
0.630000	39.8	Off	L1	19.4	16.2	56.0
0.942000	37.2	Off	L1	19.4	18.8	56.0
1.070000	37.9	Off	L1	19.4	18.1	56.0
1.502000	38.6	Off	L1	19.4	17.4	56.0

Final Result : Average

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	31.2	Off	L1	19.4	24.8	56.0
0.174000	32.3	Off	L1	19.4	22.5	54.8
0.438000	30.3	Off	L1	19.4	16.8	47.1
0.550000	30.7	Off	L1	19.4	15.3	46.0
0.630000	32.0	Off	L1	19.4	14.0	46.0
0.942000	31.5	Off	L1	19.4	14.5	46.0
1.070000	32.0	Off	L1	19.4	14.0	46.0
1.502000	33.3	Off	L1	19.4	12.7	46.0

Test Mode :	Mode 3	Temperature :	20~22℃
Test Engineer :	Slash Huang	Relative Humidity :	45~47%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	WCDMA Band II Idle + WLAN (2.4GHz, 11n HT20, Ch06, MCS0) MIMO Tx + H Pattern + Earphone + USB Cable (Charging from Adapter)		




Final Result : Quasi-Peak

Frequency (MHz)	Quasi-Peak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.438000	41.2	Off	N	19.4	15.9	57.1
0.566000	39.3	Off	N	19.4	16.7	56.0
0.646000	38.9	Off	N	19.4	17.1	56.0
1.126000	38.7	Off	N	19.5	17.3	56.0
1.534000	40.1	Off	N	19.4	15.9	56.0
1.622000	40.8	Off	N	19.4	15.2	56.0
2.654000	40.8	Off	N	19.6	15.2	56.0

Final Result : Average

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.438000	31.7	Off	N	19.4	15.4	47.1
0.566000	31.8	Off	N	19.4	14.2	46.0
0.646000	32.7	Off	N	19.4	13.3	46.0
1.126000	34.3	Off	N	19.5	11.7	46.0
1.534000	34.7	Off	N	19.4	11.3	46.0
1.622000	35.8	Off	N	19.4	10.2	46.0
2.654000	30.9	Off	N	19.6	15.1	46.0

Test Mode :	Mode 4	Temperature :	20~22℃
Test Engineer :	Slash Huang	Relative Humidity :	45~47%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	WCDMA Band II Idle + WLAN (5GHz, 11n HT20, Ch157, MCS0) MIMO Tx + H Pattern + Earphone + USB Cable (Charging from Adapter)		




Final Result : Quasi-Peak

Frequency (MHz)	Quasi-Peak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.230000	33.5	Off	L1	19.4	28.9	62.4
0.246000	33.3	Off	L1	19.4	28.6	61.9
2.694000	33.0	Off	L1	19.6	23.0	56.0
3.486000	34.2	Off	L1	19.6	21.8	56.0
3.758000	34.3	Off	L1	19.6	21.7	56.0
4.270000	34.2	Off	L1	19.6	21.8	56.0

Final Result : Average

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.230000	21.2	Off	L1	19.4	31.2	52.4
0.246000	21.0	Off	L1	19.4	30.9	51.9
2.694000	24.6	Off	L1	19.6	21.4	46.0
3.486000	23.3	Off	L1	19.6	22.7	46.0
3.758000	23.3	Off	L1	19.6	22.7	46.0
4.270000	22.7	Off	L1	19.6	23.3	46.0

Test Mode :	Mode 4	Temperature :	20~22℃
Test Engineer :	Slash Huang	Relative Humidity :	45~47%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	WCDMA Band II Idle + WLAN (5GHz, 11n HT20, Ch157, MCS0) MIMO Tx + H Pattern + Earphone + USB Cable (Charging from Adapter)		



Final Result : Quasi-Peak

Frequency (MHz)	Quasi-Peak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.158000	40.4	Off	N	19.3	25.2	65.6
0.174000	40.1	Off	N	19.4	24.7	64.8
0.190000	38.2	Off	N	19.4	25.8	64.0
1.102000	37.5	Off	N	19.5	18.5	56.0
1.510000	37.2	Off	N	19.4	18.8	56.0
1.638000	38.9	Off	N	19.5	17.1	56.0
2.566000	37.4	Off	N	19.6	18.6	56.0

Final Result : Average

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.158000	29.2	Off	N	19.3	26.4	55.6
0.174000	31.9	Off	N	19.4	22.9	54.8
0.190000	30.2	Off	N	19.4	23.8	54.0
1.102000	32.4	Off	N	19.5	13.6	46.0
1.510000	31.8	Off	N	19.4	14.2	46.0
1.638000	33.6	Off	N	19.5	12.4	46.0
2.566000	26.9	Off	N	19.6	19.1	46.0

3.10 Antenna Requirements

3.10.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.10.2 Antenna Connected Construction

Non-detachable antenna is used.

3.10.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz~40GHz	Jun. 07, 2013	Aug. 29, 2013 ~ Oct. 03, 2013	Jun. 06, 2014	Conducted (TH02-HY)
Power Meter	Agilent	E4416A	GB41292344	300MHz~40GHz	Feb. 05, 2013	Aug. 29, 2013 ~ Oct. 03, 2013	Feb. 04, 2014	Conducted (TH02-HY)
Power Sensor	Agilent	E9327A	US40441548	300MHz~40GHz	Feb. 05, 2013	Aug. 29, 2013 ~ Oct. 03, 2013	Feb. 04, 2014	Conducted (TH02-HY)
EMI Test Receiver	Rohde & Schwarz	ESCI 7	100724	9kHz~7GHz	Sep. 03, 2012	Aug. 27, 2013 ~ Aug. 28, 2013	Sep. 02, 2013	Radiation (03CH07-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP30	101067	9KHz~30GHz	Nov. 30, 2012	Aug. 27, 2013 ~ Aug. 28, 2013	Nov. 29, 2013	Radiation (03CH07-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	860004/0001	9 kHz~30 MHz	Jul. 03, 2012	Aug. 27, 2013 ~ Aug. 28, 2013	Jul. 03, 2014	Radiation (03CH07-HY)
Bilog Antenna	Schaffner	CBL6111C	2726	30MHz~1GHz	Oct. 06, 2012	Aug. 27, 2013 ~ Aug. 28, 2013	Oct. 05, 2013	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ESCO	3117	00075962	1GHz ~ 18GHz	Aug. 22, 2013	Aug. 27, 2013 ~ Aug. 28, 2013	Aug. 21, 2014	Radiation (03CH07-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170251	18GHz~40GHz	Sep. 28, 2012	Aug. 27, 2013 ~ Aug. 28, 2013	Sep. 27, 2013	Radiation (03CH07-HY)
Preamplifier	COM-POWER	PA-103A	161241	30MHz~1GHz	Feb. 26, 2013	Aug. 27, 2013 ~ Aug. 28, 2013	Feb. 25, 2014	Radiation (03CH07-HY)
Preamplifier	Agilent	8449B	3008A02362	1GHz~26.5GHz	Dec. 01, 2012	Aug. 27, 2013 ~ Aug. 28, 2013	Nov. 30, 2013	Radiation (03CH07-HY)
Turn Table	ChainTek	ChainTek 3000	N/A	0 ~ 360 degree	N/A	Aug. 27, 2013 ~ Aug. 28, 2013	N/A	Radiation (03CH07-HY)
Antenna Mast	ChainTek	ChainTek 3000	N/A	N/A	N/A	Aug. 27, 2013 ~ Aug. 28, 2013	N/A	Radiation (03CH07-HY)
EMI Test Receiver	Rohde & Schwarz	ESCS 30	100356	9kHz ~ 2.75GHz	Nov. 13, 2012	Aug. 30, 2013 ~ Sep. 04, 2013	Nov. 12, 2013	Conduction (CO05-HY)
Two-LISN (for auxiliary equipment)	Rohde & Schwarz	ENV216	100081	9kHz ~ 30MHz	Dec. 12, 2012	Aug. 30, 2013 ~ Sep. 04, 2013	Dec. 11, 2013	Conduction (CO05-HY)
Two-LISN	Rohde & Schwarz	ENV216	100080	9kHz ~ 30MHz	Dec. 06, 2012	Aug. 30, 2013 ~ Sep. 04, 2013	Dec. 05, 2013	Conduction (CO05-HY)
AC Power Source	APC	APC-1000W	N/A	N/A	N/A	Aug. 30, 2013 ~ Sep. 04, 2013	N/A	Conduction (CO05-HY)

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.26
--	------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.54
--	------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	4.72
--	------