

Modular Approval Request

 Applicant: OFI, Inc.
 FCC ID: S9C-3065-3

2016-04-04

To Whom It May Concern:

Pursuant to Section 15.212(a)(1) of the FCC rules, the Applicant, request for single modular approval, compliance with the requirements are addressed below.

Single Modular Approval Requirements	Justification
(i) The radio elements of the modular transmitter must have their own shielding. The physical crystal and tuning capacitors may be located external to the shielded radio elements.	<p>The 13.56 MHz near-field RFID reader is not shielded due to ineffectiveness of a shield at these frequencies.</p> <p><i>This module shall be used only in products designed by OFI and subject to further investigation according to FCC Part 15B therefore excessive unintended emissions due to interactions between the 13.56MHz RFID reader module and incorporating product can be avoided.</i></p>
(ii) The modular transmitter must have buffered modulation/data inputs (if such inputs are provided) to ensure that the module will comply with part 15 requirements under conditions of excessive data rates or over-modulation.	<p>The 13.56 MHz near-field RFID reader has no modulation inputs, and has buffered data inputs.</p>
(iii) The modular transmitter must have its own power supply regulation.	<p>The 13.56 MHz near-field RFID reader does not have its own power supply regulation and relies on suitable regulated power being supplied.</p> <p><i>External power supply regulation is a condition of use as stated in the user guide. This module shall be used only in products designed by OFI, therefore a regulated power supply meeting the requirements stated in the user guide is assured.</i></p>
(iv) The modular transmitter must comply with the antenna and transmission system requirements of §§ 15.203, 15.204(b) and 15.204(c). The antenna must either be permanently attached or employ a “unique” antenna coupler (at all connections between the module and the antenna, including the cable). The “professional installation” provision of § 15.203 is not applicable to modules but can apply to limited modular approvals under paragraph (b) of this section.	<p>The 13.56 MHz near-field RFID reader has integral PCB trace antennas and has no antenna connector.</p>
(v) The modular transmitter must be tested in a stand-alone configuration, <i>i.e.</i> , the module must not be inside another device during testing for compliance with part 15 requirements. Unless the transmitter module will be battery powered, it must comply with the AC line conducted requirements found in § 15.207. AC or DC power lines and data input/output lines connected to the module must not contain ferrites, unless they will be	<p>The module was tested in a stand-alone configuration.</p>

<p>marketed with the module (see § 15.27(a)). The length of these lines shall be the length typical of actual use or, if that length is unknown, at least 10 centimeters to insure that there is no coupling between the case of the module and supporting equipment. Any accessories, peripherals, or support equipment connected to the module during testing shall be unmodified and commercially available (see § 15.31(i)).</p>	
<p>(vi) The modular transmitter must be equipped with either a permanently affixed label or must be capable of electronically displaying its FCC identification number.</p> <p>(A) If using a permanently affixed label, the modular transmitter must be labeled with its own FCC identification number, and, if the FCC identification number is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains Transmitter Module FCC ID: XYZMODEL1" or "Contains FCC ID: XYZMODEL1." Any similar wording that expresses the same meaning may be used. The Grantee may either provide such a label, an example of which must be included in the application for equipment authorization, or, must provide adequate instructions along with the module which explain this requirement. In the latter case, a copy of these instructions must be included in the application for equipment authorization.</p> <p>(B) If the modular transmitter uses an electronic display of the FCC identification number, the information must be readily accessible and visible on the modular transmitter or on the device in which it is installed. If the module is installed inside another device, then the outside of the device into which the module is installed must display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains FCC certified transmitter module(s)." Any similar wording that expresses the same meaning may be used. The user manual must include instructions on how to access the electronic display. A copy of these instructions must be included in the application for equipment authorization.</p>	<p>The module has a permanently affixed label or is permanently marked with its FCC identification number. The module user guide contains the necessary end-product marking requirements.</p>
<p>(vii) The modular transmitter must comply with any specific rules or operating requirements that ordinarily apply to a complete transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements. A copy of these instructions must be included in the application for equipment authorization.</p>	<p>The module user guide contains all of the required instructions.</p>
<p>(viii) The modular transmitter must comply with any applicable RF exposure requirements in its final configuration.</p>	<p>The module user guide includes the application limitation that prohibits the module being used in a product designed to be used such that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user, and a limitation on the MPE ratio of the optional co-located radio network module such that the conditions for simultaneous test exclusion requirements for</p>

uncontrolled RF exposure are met by the RFID near-field reader and the optional radio network module.

The 3065-3 module shall be used only in products designed by OFI, therefore compliance with these limitations is assured.

Sincerely,



Geoff Jones