



**FCC CFR47 PART 15 SUBPART E
INDUSTRY CANADA RSS-210 ISSUE 8**

CERTIFICATION TEST REPORT

FOR

**Dual-Band 802.11 a/b/g/n Industrial Access Point with Integrated DOCSIS 3.0
Modem**

MODEL NUMBER: ZoneFlex7761-CM

**FCC ID: S9GZF7761CM
IC: 5912A-ZF7761CM**

REPORT NUMBER: 10U13475-3, Revision C

ISSUE DATE: JUNE 06, 2011

Prepared for
**RUCKUS WIRELESS
880 WEST MAUDE AVE., SUITE 101
SUNNYVALE, CA 94085, U.S.A.**

Prepared by
**COMPLIANCE CERTIFICATION SERVICES
47173 BENICIA STREET
FREMONT, CA 94538, U.S.A.
TEL: (510) 771-1000
FAX: (510) 661-0888**



NVLAP LAB CODE 200065-0

Revision History

Rev.	Issue Date	Revisions	Revised By
--	03/02/11	Initial Issue	F. Ibrahim
A	03/03/11	Inserted the conducted spurious data for the notch band of 5.6-5.65 GHz	F. Ibrahim
B	03/21/11	Revised output power values in sections 7.4.2, section 7.6.2, section 7.7.2, section 7.8.2, and section 7.9.2. Revised MPE section.	F. Ibrahim
C	06/06/11	Revised sections 7.4.6, 7.5.2, 7.5.4, 7.5.6, 7.6.2, 7.6.4, 7.6.6, 7.7.6, 7.8.2, 7.8.4, 7.8.6, 7.9.2, 7.9.4, and 7.9.6 for limits and test procedure paragraphs.	F. Ibrahim

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	6
2. TEST METHODOLOGY	7
3. FACILITIES AND ACCREDITATION	7
4. CALIBRATION AND UNCERTAINTY	7
4.1. MEASURING INSTRUMENT CALIBRATION	7
4.2. SAMPLE CALCULATION	7
4.3. MEASUREMENT UNCERTAINTY	7
5. EQUIPMENT UNDER TEST	8
5.1. DESCRIPTION OF EUT	8
5.2. MAXIMUM OUTPUT POWER	8
5.3. DESCRIPTION OF AVAILABLE ANTENNAS	9
5.4. SOFTWARE AND FIRMWARE	9
5.5. WORST-CASE CONFIGURATION AND MODE	9
5.6. DESCRIPTION OF TEST SETUP	10
6. TEST AND MEASUREMENT EQUIPMENT	12
7. ANTENNA PORT TEST RESULTS	13
7.1. 802.11a THREE CHAIN LEGACY MODE IN THE 5.2 GHz BAND	13
7.1.1. 26 dB and 99% BANDWIDTH	13
7.1.2. OUTPUT POWER	23
7.1.3. AVERAGE POWER	34
7.1.4. PEAK POWER SPECTRAL DENSITY	35
7.1.5. PEAK EXCURSION	40
7.1.6. CONDUCTED SPURIOUS EMISSIONS	51
7.2. 802.11n THREE CHAINS HT20 MODE IN THE 5.2 GHz BAND	55
7.2.1. 26 dB and 99% BANDWIDTH	55
7.2.2. OUTPUT POWER	65
7.2.3. AVERAGE POWER	76
7.2.4. PEAK POWER SPECTRAL DENSITY	77
7.2.5. PEAK EXCURSION	81
7.2.6. CONDUCTED SPURIOUS EMISSIONS	92
7.3. 802.11n THREE CHAINS HT40 MODE IN THE 5.2 GHz BAND	96
7.3.1. 26 dB and 99% BANDWIDTH	96
7.3.2. OUTPUT POWER	103
7.3.3. AVERAGE POWER	111
7.3.4. PEAK POWER SPECTRAL DENSITY	112
7.3.5. PEAK EXCURSION	115
7.3.6. CONDUCTED SPURIOUS EMISSIONS	123
7.4. 802.11a THREE CHAINS LEGACY MODE IN THE 5.3 GHz BAND	126

7.4.1.	26 dB and 99% BANDWIDTH	126
7.4.2.	OUTPUT POWER	136
7.4.3.	AVERAGE POWER	147
7.4.4.	PEAK POWER SPECTRAL DENSITY	148
7.4.5.	PEAK EXCURSION	153
7.4.6.	CONDUCTED SPURIOUS EMISSIONS.....	164
7.5.	<i>802.11n THREE CHAIN HT20 MODE IN THE 5.3 GHz BAND</i>	<i>168</i>
7.5.1.	26 dB and 99% BANDWIDTH	168
7.5.2.	OUTPUT POWER	178
7.5.3.	AVERAGE POWER	189
7.5.4.	PEAK POWER SPECTRAL DENSITY	190
7.5.5.	PEAK EXCURSION	194
7.5.6.	CONDUCTED SPURIOUS EMISSIONS.....	205
7.6.	<i>802.11n THREE CHAINS HT40 MODE IN THE 5.3 GHz BAND</i>	<i>209</i>
7.6.1.	26 dB and 99% BANDWIDTH	209
7.6.2.	OUTPUT POWER	216
7.6.3.	AVERAGE POWER	224
7.6.4.	PEAK POWER SPECTRAL DENSITY	225
7.6.5.	PEAK EXCURSION	229
7.6.6.	CONDUCTED SPURIOUS EMISSIONS.....	237
7.7.	<i>802.11a THREE CHAINS Legacy MODE IN THE 5.6 GHz BAND</i>	<i>240</i>
7.7.1.	26 dB and 99% BANDWIDTH	240
7.7.2.	OUTPUT POWER	250
7.7.3.	AVERAGE POWER	261
7.7.4.	PEAK POWER SPECTRAL DENSITY	262
7.7.5.	PEAK EXCURSION	267
7.7.6.	CONDUCTED SPURIOUS EMISSIONS.....	278
7.8.	<i>802.11n THREE CHAINS HT20 MODE IN THE 5.6 GHz BAND</i>	<i>288</i>
7.8.1.	26 dB and 99% BANDWIDTH	288
7.8.2.	OUTPUT POWER	298
7.8.3.	AVERAGE POWER	309
7.8.4.	PEAK POWER SPECTRAL DENSITY	310
7.8.5.	PEAK EXCURSION	315
7.8.6.	CONDUCTED SPURIOUS EMISSIONS.....	326
7.9.	<i>802.11n THREE CHAINS HT40 MODE IN THE 5.6 GHz BAND</i>	<i>336</i>
7.9.1.	26 dB and 99% BANDWIDTH	336
7.9.2.	OUTPUT POWER	346
7.9.3.	AVERAGE POWER	357
7.9.4.	PEAK POWER SPECTRAL DENSITY	358
7.9.5.	PEAK EXCURSION	363
7.9.6.	CONDUCTED SPURIOUS EMISSIONS.....	374
7.10.	<i>RECEIVER CONDUCTED SPURIOUS EMISSIONS</i>	<i>381</i>
8.	RADIATED TEST RESULTS	391
8.1.	<i>LIMITS AND PROCEDURE</i>	<i>391</i>
8.2.	<i>TRANSMITTER ABOVE 1 GHz</i>	<i>392</i>
8.2.1.	TX ABOVE 1 GHz FOR 802.11a MODE IN THE 5.2 GHz BAND	392
8.2.2.	TX ABOVE 1 GHz FOR 802.11n HT20 MODE IN THE 5.2 GHz BAND	397

8.2.3.	TX ABOVE 1 GHz FOR 802.11n HT40 MODE IN THE 5.2 GHz BAND	402
8.2.4.	TX ABOVE 1 GHz FOR 802.11a MODE IN THE 5.3 GHz BAND	407
8.2.5.	TX ABOVE 1 GHz FOR 802.11n HT20 MODE IN THE 5.3 GHz BAND	412
8.2.6.	TX ABOVE 1 GHz FOR 802.11n HT40 MODE IN THE 5.3 GHz BAND	417
8.2.7.	TX ABOVE 1 GHz FOR 802.11a MODE IN THE 5.6 GHz BAND	426
8.2.8.	TX ABOVE 1 GHz FOR 802.11n HT20 MODE IN THE 5.6 GHz BAND	433
8.2.9.	TX ABOVE 1 GHz FOR 802.11n HT40 MODE IN THE 5.6 GHz BAND	440
8.3.	WORST-CASE BELOW 1 GHz.....	447
9.	AC POWER LINE CONDUCTED EMISSIONS	451
10.	DYNAMIC FREQUENCY SELECTION	455
10.1.	OVERVIEW.....	455
10.1.1.	LIMITS.....	455
10.1.2.	TEST AND MEASUREMENT SYSTEM	458
10.1.3.	SETUP OF EUT	461
10.1.4.	DESCRIPTION OF EUT	462
10.2.	RESULTS FOR 20 MHz BANDWIDTH	463
10.2.1.	TEST CHANNEL	463
10.2.2.	RADAR WAVEFORMS AND TRAFFIC.....	463
10.2.3.	CHANNEL AVAILABILITY CHECK TIME.....	470
10.2.4.	OVERLAPPING CHANNEL TESTS	475
10.2.5.	MOVE AND CLOSING TIME.....	475
10.2.6.	DETECTION BANDWIDTH.....	481
10.2.7.	IN-SERVICE MONITORING.....	483
10.3.	RESULTS FOR 40 MHz BANDWIDTH	490
10.3.1.	TEST CHANNEL	490
10.3.2.	RADAR WAVEFORMS AND TRAFFIC.....	490
10.3.3.	CHANNEL AVAILABILITY CHECK TIME.....	497
10.3.4.	OVERLAPPING CHANNEL TESTS	502
10.3.5.	MOVE AND CLOSING TIME.....	502
10.3.6.	NON-OCCUPANCY PERIOD.....	508
10.3.7.	DETECTION BANDWIDTH.....	509
10.3.8.	IN-SERVICE MONITORING.....	511
11.	MAXIMUM PERMISSIBLE EXPOSURE	518
12.	SETUP PHOTOS	522

11. MAXIMUM PERMISSIBLE EXPOSURE

FCC RULES

§1.1310 The criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of §2.1093 of this chapter.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)—Continued

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

NOTE 1 TO TABLE 1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

NOTE 2 TO TABLE 1: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

IC RULES

IC Safety Code 6, Section 2.2.1 (a) A person other than an RF and microwave exposed worker shall not be exposed to electromagnetic radiation in a frequency band listed in Column 1 of Table 5, if the field strength exceeds the value given in Column 2 or 3 of Table 5, when averaged spatially and over time, or if the power density exceeds the value given in Column 4 of Table 5, when averaged spatially and over time.

Table 5
Exposure Limits for Persons Not Classed As RF and Microwave Exposed Workers (Including the General Public)

1 Frequency (MHz)	2 Electric Field Strength; rms (V/m)	3 Magnetic Field Strength; rms (A/m)	4 Power Density (W/m ²)	5 Averaging Time (min)
0.003–1	280	2.19		6
1–10	$280/f$	$2.19/f$		6
10–30	28	$2.19/f$		6
30–300	28	0.073	2*	6
300–1 500	$1.585f^{0.5}$	$0.0042f^{0.5}$	$f/150$	6
1 500–15 000	61.4	0.163	10	6
15 000–150 000	61.4	0.163	10	$616\,000/f^{1.2}$
150 000–300 000	$0.158f^{0.5}$	$4.21 \times 10^{-4}f^{0.5}$	$6.67 \times 10^{-5}f$	$616\,000/f^{1.2}$

* Power density limit is applicable at frequencies greater than 100 MHz.

Notes: 1. Frequency, f , is in MHz.
2. A power density of 10 W/m² is equivalent to 1 mW/cm².
3. A magnetic field strength of 1 A/m corresponds to 1.257 microtesla (μT) or 12.57 milligauss (mG).

EQUATIONS

Power density is given by:

$$S = \text{EIRP} / (4 * \pi * D^2)$$

where

S = Power density in W/m²

EIRP = Equivalent Isotropic Radiated Power in W

D = Separation distance in m

Power density in units of W/m² is converted to units of mW/cm² by dividing by 10.

Distance is given by:

$$D = \text{SQRT} (\text{EIRP} / (4 * \pi * S))$$

where

D = Separation distance in m

EIRP = Equivalent Isotropic Radiated Power in W

S = Power density in W/m²

For multiple colocated transmitters operating simultaneously in frequency bands where the limit is identical, the total power density is calculated using the total EIRP obtained by summing the Power * Gain product (in linear units) of each transmitter.

$$\text{Total EIRP} = (P_1 * G_1) + (P_2 * G_2) + \dots + (P_n * G_n)$$

where

P_x = Power of transmitter x

G_x = Numeric gain of antenna x

In the table(s) below, Power and Gain are entered in units of dBm and dBi respectively and conversions to linear forms are used for the calculations.

LIMITS

From FCC §1.1310 Table 1 (B), the maximum value of S = 1.0 mW/cm²

From IC Safety Code 6, Section 2.2 Table 5 Column 4, S = 10 W/m²

RESULTS

Multiple chain or colocated transmitters								
Band	Mode	Chain for MIMO	Separation Distance (m)	Output Power (dBm)	Antenna Gain (dBi)	Duty Cycle (%)	IC Power Density (W/m ²)	FCC Power Density (mW/cm ²)
5 GHz	WLAN	1		17.33	5.50	100		
5 GHz	WLAN	2		18.91	5.50	100		
5 GHz	WLAN	3		17.83	5.50	100		
Combined			0.20				1.36	0.136

Notes:

Output power is the average output power for each chain.