

PART NUMBER "A"	COUNTRY OF ORIGIN "B"
XX = CN	Made in China
XX = MY	Assembled in China with PCBA from Malaysia
XX = MX	Assembled in Mexico



SEE Tabulation column  
PART NUMBER "A"

SEE Tabulation column  
COUNTRY OF ORIGIN "B"

PART NUMBER "A"	COUNTRY OF ORIGIN "B"
XX = CN	Made in China

**NOTE:** AC connector must be removed to replace batteries. Press tab to remove AC connector.

Clean annually. See User Guide for more info.

**Wi-Fi**

YYYY, MMM, DD

Smoke sensitivity: xxx +/- xxx %/ft OBS

**ETL** US

**Intertek**

XXXXXX

**Model RGSAR-RW**

Photoelectric Smoke Alarm w/  
Voice, Wireless Interlink, & Wi-Fi,  
120VAC (60Hz, 85mA Max) w / AA  
battery backup. Constant exposures  
to high or low temperatures or high  
humidity may reduce battery life.

**CONFORMS TO**  
UL STD 217, 9<sup>th</sup> ed  
Multi-Criteria  
Smoke Alarm

**38707**

**DSN: BHSC1714LH000770**

**REPLACE BATTERIES AT LEAST ONCE A YEAR.**

**WARNING:** USE ONLY BATTERIES SPECIFIED IN MARKING (Energizer E91, Gold Peak 15A Golden Power GLR6A). USE OF A DIFFERENT BATTERY MAY HAVE A DETRIMENTAL EFFECT ON ALARM OPERATION. NOTE: Do not use lithium batteries in this unit. Unit will not attach to mounting bracket without batteries installed.

Made in China.

**SMOKE ALARM:** 3 Long beeps, repeating

**NOTE:** Not a CO alarm, but can transmit a CO ALARM signal: 4 quick beeps, repeating.

**STANDBY:** AC power-green LED on, DC only-green LED blinks every 60s. **FAULT:** Amber LED blinks 1-4 times with 3 chirps every 60s.

**LOW BATTERY:** Amber LED blinks every 6s with 1 chirp every 60s. **END OF UNIT LIFE:** Amber LED blinks twice with 2 chirps every 60s. **Temp Range:** 40° F (4.4° C) to 100° F (37.8° C). **Humidity Range:** Up to 95% relative humidity (RH), non-condensing.

Contains FCC ID SAK-ESP32S3 FCC ID: SAK-RGSARRW

L-000352-CN-00 Rev A

PART NUMBER "A"	COUNTRY OF ORIGIN "B"
XX = MY	Assembled in China with PCBA from Malaysia

**NOTE:** AC connector must be removed to replace batteries. Press tab to remove AC connector.

Clean annually. See User Guide for more info.

Wi-Fi

YYYY, MMM, DD

Smoke sensitivity : xxx +/- xxx %/ft OBS

  
**Intertek**  
XXXXXX  
**Model RGSAR-RW**  
Photoelectric Smoke Alarm w/  
Voice, Wireless Interlink, & Wi-Fi  
120VAC (60Hz, 85mA Max) w / AA  
battery backup. Constant exposures  
to high or low temperatures or high  
humidity may reduce battery life.

CONFORMS TO  
UL STD 217, 9<sup>th</sup> ed  
Multi-Criteria  
Smoke Alarm

  
38707

  
DSN: BHSC1714LH000770

J-000352MY-00 Rev A

**NOTE:** Not a CO alarm, but can transmit a CO ALARM signal: 4 quick beeps, repeating. **STANDBY:** AC power-green LED on. DC only-green LED blinks every 60s. **FAULT:** Amber LED blinks 1-4 times with 3 chirps every 60s. **LOW BATTERY:** Amber LED blinks every 6s with 1 chirp every 60s. **END OF UNIT LIFE:** Amber LED blinks twice with 2 chirps every 60s. **Temp Range:** 40° F (4.4° C) to 100° F (37.8° C). **Humidity Range:** Up to 95% relative humidity (RH), non-condensing. Contains FCC ID SAK-ESP3253 FCC ID: SAK-RGSARRW

**REPLACE BATTERIES AT LEAST ONCE A YEAR.**

**⚠WARNING:** USE ONLY BATTERIES SPECIFIED IN MARKING (Energizer E91, Gold Peak 15A, Golden Power GLR6A). USE OF A DIFFERENT BATTERY MAY HAVE A DETRIMENTAL EFFECT ON ALARM OPERATION. NOTE: Do not use lithium batteries in this unit. Unit will not attach to mounting bracket without batteries installed.

Assembled in China  
with PCBA from Malaysia

PART NUMBER "A"	COUNTRY OF ORIGIN "B"
XX = MX	Assembled in Mexico

**NOTE:** AC connector must be removed to replace batteries. Press tab to remove AC connector.

Clean annually. See User Guide for more info.

**Wi-Fi**

YYYY, MMM, DD

Smoke sensitivity : xxx +/- xxx %/ft OBS

**E1V** **US**

**Intertek**

XXXXXX

**Model RGSAR-RW**

Photoelectric Smoke Alarm w/  
Voice, Wireless Interlink, & Wi-Fi.  
120VAC (60Hz, 85mA Max) w / AA  
battery backup. Constant exposures  
to high or low temperatures or high  
humidity may reduce battery life.

**CONFORMS TO**  
UL STD 217, 9" ed  
Multi-Criteria  
Smoke Alarm

**F.P.O.**

38707

DSN: BHSC1714LH000770

J-000352/MX-00 Rev A

**SMOKE ALARM:** 3 Long beeps, repeating. **NOTE: Not a CO alarm, but can transmit a CO ALARM signal: 4 quick beeps, repeating.** **STANDBY:** AC power-green LED on. DC only-green LED blinks every 60s. **FAULT:** Amber LED blinks 1-4 times with 3 chirps every 60s. **LOW BATTERY:** Amber LED blinks every 6s with 1 chirp every 60s. **END OF UNIT LIFE:** Amber LED blinks twice with 2 chirps every 60s. **Temp Range:** 40° F (4.4° C) to 100° F (37.8° C). **Humidity Range:** Up to 95% relative humidity (RH), non-condensing. Contains FCC ID SAK-ESP3253 FCC ID: SAK-RGSARRW

**REPLACE BATTERIES AT LEAST ONCE A YEAR.**

**⚠WARNING: USE ONLY BATTERIES SPECIFIED IN MARKING** (Energizer E91, Gold Peak 15A, Golden Power GLR6A). **USE OF A DIFFERENT BATTERY MAY HAVE A DETRIMENTAL EFFECT ON ALARM OPERATION.** NOTE: Do not use lithium batteries in this unit. **Unit will not attach to mounting bracket without batteries installed.**

Assembled in Mexico

