

**ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT
INTENTIONAL RADIATOR CERTIFICATION TO
FCC PART 15 SUBPART C REQUIREMENT**

OF

Multimedia Player

**MODEL No.: Mee-M100R, Mee-M100R Series, Mee-M100RX, M100R, M100R
Series, M100RX, M100RA, M100RB**

FCC ID: SB5-13100R2

Trademark: 

REPORT NO: ES1306090101E

ISSUE DATE: June 28, 2013

Prepared for

MeeBoss Inc.

7F., No. 189, Gangqian Rd, Neihu Dist., Taipei City, Taiwan 11494

Prepared by

SHENZHEN EMTEK CO., LTD.

**Bldg 69, Majialong Industry Zone, Nanshan District,
Shenzhen, Guangdong, China**

TEL: 86-755-26954280

FAX: 86-755-26954282

VERIFICATION OF COMPLIANCE


Applicant:	MeeBoss Inc. 7F., No. 189, Gangqian Rd, Neihu Dist., Taipei City, Taiwan 11494
Manufacturer:	SAGE ELECTRONICS CO., LTD. ShaJing Town, Bao An District, ShenZhen, China
Product Description:	MeeBoss Inc.
Model Number:	Mee-M100R, Mee-M100R Series, Mee-M100RX, M100R, M100R Series, M100RX, M100RA, M100RB Note: All the models are the same, except their model number for trading purpose. We take Mee-M100R to test.
File Number:	ES1306090101E
Date of Test:	June 9, 2013 to June 25, 2013

We hereby certify that:

The above equipment was tested by SHENZHEN EMTEK CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2009) and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.247.

The test results of this report relate only to the tested sample identified in this report.

Date of Test : June 9, 2013 to June 25, 2013

Prepared by : 
Jack.Li/Editor

Reviewer : 
June Xie/Supervisor

Approve & Authorized Signer : 
Lisa Wang/Manager

Table of Contents

1. GENERAL INFORMATION	5
1.1 PRODUCT DESCRIPTION	5
1.2 RELATED SUBMITTAL(S) / GRANT(S)	5
1.3 TEST METHODOLOGY	6
1.4 SPECIAL ACCESSORIES.....	6
1.5 EQUIPMENT MODIFICATIONS	6
1.6 TEST FACILITY	6
2. SYSTEM TEST CONFIGURATION.....	7
2.1 EUT CONFIGURATION.....	7
2.2 EUT EXERCISE	7
2.3 TEST PROCEDURE	7
2.4 CONFIGURATION OF TESTED SYSTEM	7
3. DESCRIPTION OF TEST MODES	9
4. SUMMARY OF TEST RESULTS.....	10
5. CONDUCTED EMISSIONS TEST	11
5.1 MEASUREMENT PROCEDURE	11
5.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	11
5.3 MEASUREMENT EQUIPMENT USED	11
5.4 CONDUCTED EMISSION LIMIT	11
5.5 MEASUREMENT RESULT	12
6. RADIATED EMISSION TEST	13
6.1 MEASUREMENT PROCEDURE	13
6.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	13
6.3 MEASUREMENT EQUIPMENT USED	14
6.4 RADIATED EMISSION LIMIT.....	14
6.5 MEASUREMENT RESULT	16
7. 6DB BANDWIDTH TEST.....	40
7.1 MEASUREMENT PROCEDURE	40
7.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	40
7.3 MEASUREMENT EQUIPMENT USED	40
7.4 MEASUREMENT RESULTS.....	40
8. MAXIMUM PEAK OUTPUT POWER TEST.....	49
8.1 MEASUREMENT PROCEDURE	49
8.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	49
8.3 MEASUREMENT EQUIPMENT USED	49
8.4 PEAK POWER OUTPUT LIMIT	49
8.5 MEASUREMENT RESULTS.....	49
9. BAND EDGE TEST	51
9.1 MEASUREMENT PROCEDURE	51
9.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	51
9.3 MEASUREMENT EQUIPMENT USED	51
9.4 MEASUREMENT RESULTS.....	51
10. POWER DENSITY	54
10.1 TEST EQUIPMENT.....	54
10.2 MEASURING INSTRUMENTS AND SETTING	54
10.3 TEST PROCEDURES	54
10.4 BLOCK DIAGRAM OF TEST SETUP.....	54

10.5	LIMIT	54
10.6	TEST RESULT	55
11.	ANTENNA PORT EMISSION	63
11.1	TEST EQUIPMENT.....	63
11.2	MEASURING INSTRUMENTS AND SETTING	63
11.3	TEST PROCEDURES	63
11.4	BLOCK DIAGRAM OF TEST SETUP	63
11.5	TEST RESULT	63
12.	ANTENNA APPLICATION.....	76
12.1	ANTENNA REQUIREMENT	76
12.2	RESULT	76

1. General Information

1.1 Product Description

A major technical descriptions of EUT is described as following:

- A). Standards: IEEE802.11b/g/n (HT20, HT40)
 B). Operation Frequency: 802.11b/g/n HT20: 2412-2462MHz;
 802.11 n HT40: 2422-2452MHz;
 C). Modulation: OFDM with BPSK/QPSK/16QAM/64QAM for802.11g/n
 (HT20, HT40),
 DSSS with DBPSK/DQPSK/CCK for 802.11b
 D). Number of Channel: 802.11b/g/n HT20: 11Channels;
 802.11n HT40: 7Channels
 E).Conducted Power: 8.84dBm(802.11b),8.61dBm(802.11g), 8.79dBm(802.11n
 HT20), 8.57dBm(802.11n HT40)
 F) Antenna Gain: 2.8dBi
 G). Antenna Type: Metal Antenna
 H). Power Supply: DC 5V, 1A from AC Adapter
 I). Adapter : Model: GFP051U-050100-Q
 Input: AC 100-240V, 50/60Hz 0.2A
 Output: DC 5V, 1A

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	5	2432	9	2452
2	2417	6	2437	10	2457
3	2422	7	2442	11	2462
4	2427	8	2447		

Note:

1. This device is MID included 802.11b, 802.11g, 802.11n HT20 and802.11n HT40 2.4GHz transceiver function.
2. Test of channel was included the lowest middle and highest frequency in lowest data rate and to perform the test, then record on this report.

1.2 Related Submittal(s) / Grant(s)

This submittal(s) (test report) is intended for FCC ID: SB5-13100R2 filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

1.3 Test Methodology

All the test program has follow FCC new test procedure KDB558074 D01 v03r01, Both conducted and radiated testing was performed according to the procedures in ANSI C63.10 (2009). Radiated testing was performed at an antenna to EUT distance 3 meters.

1.4 Special Accessories

Not available for this EUT intended for grant.

1.5 Equipment Modifications

Not available for this EUT intended for grant.

1.6 Test Facility

Site Description

EMC Lab. : Accredited by CNAS, 2010.10.29
The certificate is valid until 2013.10.28
The Laboratory has been assessed and proved to be in compliance with CNAS/CL01: 2006(identical to ISO/IEC17025: 2005)
The Certificate Registration Number is L2291

Accredited by TUV Rheinland Shenzhen 2010.5.25
The Laboratory has been assessed according to the requirements ISO/IEC 17025

Accredited by FCC, October 28, 2010
The Certificate Registration Number is 406365.

Accredited by Industry Canada, March 05, 2010
The Certificate Registration Number is 46405-4480.

Name of Firm : SHENZHEN EMTEK CO., LTD.
Site Location : Bldg 69, Majialong Industry Zone,
Nanshan District, Shenzhen, Guangdong, China

2. System Test Configuration

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

2.3 Test Procedure

2.3.1 Conducted Emissions

The EUT is placed on a turn table which is 0.8 m above ground plane. According to the requirements of ANSI C63.4-2009 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.


2.3.2 Radiated Emissions

The EUT is placed on a turn table which is 0.8 m above ground plane. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. Emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 13.1.4.1 of ANSI C63.4-2009.

2.4 Configuration of Tested System

Fig. 2-1 Configuration of Tested System

For Conducted Emission:



For Radiate Emission




Table 2-1 Equipment Used in Tested System

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.	Note
1.	MeeBoss Inc.		Mee-M100R	SB5-13100R2	N/A	EUT
2.	Adapter	GFP	GFP051U-050100-Q	N/A	N/A	
3.	Notebook	Lenovo	20020	N/A	EB16076441	
4.	LCD TV	SONY	KDL-24EX520	N/A	6258850	

Note:

- (1) Unless otherwise denoted as EUT in 『Remark』 column, device(s) used in tested system is a support equipment.

3. Description of Test Modes

The Transmitter of EUT is an Internet Tablet and powered by host equipment; these is Digital Transmission system (DTS) and have modulation OFDM, DSSS, DBPSK, DQPSK, CCK, 16QAM, 64QAM. According exploratory test, EUT will have maximum output power in those data rate (802.11b: 1 Mbps; 802.11g: 6 Mbps; 802.11n HT20: MCS0; 802.11n HT40: MCS0), so those data rate were used for all test.

For 802.11b/g/n HT20:

1. For lowest channel : 2412MHz (Channel 1)
2. For middle channel : 2437MHz (Channel 6)
3. For highest channel: 2462MHz (Channel 11)

For 802.11b/g/n HT40:

1. For lowest channel : 2422MHz (Channel 3)
2. For middle channel : 2437MHz (Channel 6)
3. For highest channel: 2452MHz (Channel 9)

4. Summary of Test Results


FCC Rules	Description Of Test	Result
§15.247(a)(2)	6dB bandwidth	Pass
§15.247(b)(3)	Max Peak output Power test	Pass
§15.247(e)	Power density	Pass
§15.247(d)	Band edge test	Pass
§15.207	AC Power Conducted Emission	Pass
§15.247(d), §15.209	Radiated Emission	Pass
§15.247(d)	Antenna Port Emission	Pass
§15.247(b)&§15.203	Antenna Application	Pass

5. Conducted Emissions Test

5.1 Measurement Procedure

1. The EUT was placed on a table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.

5.2 Test SET-UP (Block Diagram of Configuration)



5.3 Measurement Equipment Used

Conducted Emission Test Site					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Test Receiver	Rohde & Schwarz	ESCS30	828985/018	05/29/2013	05/28/2014
L.I.S.N.	Schwarzbeck	NNLK8129	8129203	05/29/2013	05/28/2014
50Ω Coaxial Switch	Anritsu	MP59B	M20531	N/A	N/A
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100006	05/29/2013	05/28/2014
Voltage Probe	Rohde & Schwarz	TK9416	N/A	05/29/2013	05/28/2014
I.S.N	Rohde & Schwarz	ENY22	1109.9508.02	05/29/2013	05/28/2014

5.4 Conducted Emission Limit

Conducted Emission Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

- Note:** 1. The lower limit shall apply at the transition frequencies
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

5.5 Measurement Result

Date of Test:	June 9, 2013	Temperature:	26℃
Frequency Detector:	0.15~30MHz	Humidity:	60%
Test Result:	PASS	Test Mode:	WIFI Mode

Test Line	Frequency MHz	Emission Level QP dB(μV)	Emission Level AV dB(μV)	Limits QP dB(μV)	Limits AV dB(μV)	Over QP dB(μV)	Over AV dB(μV)
Line	0.150	49.880	36.330	66.000	56.00	-16.12	-19.67
	0.250	44.910	29.410	61.760	51.76	-16.85	-22.35
	0.490	36.740	25.290	56.170	46.17	-19.43	-20.88
	6.950	47.700	28.410	60.000	50.00	-12.30	-21.59
	12.500	43.230	37.760	60.000	50.00	-16.77	-12.24
	26.850	38.190	34.990	60.000	50.00	-21.81	-15.01
Neutral	0.150	49.820	35.740	66.000	56.00	-16.18	-20.26
	0.230	45.000	28.200	62.450	52.45	-17.45	-24.25
	0.260	44.030	28.080	61.430	51.43	-17.40	-23.35
	0.420	41.120	37.580	57.450	47.45	-16.33	-9.87
	6.775	47.290	35.450	60.000	50.00	-12.71	-14.55
	12.450	42.010	29.490	60.000	50.00	-17.99	-20.51

6. Radiated Emission Test


6.1 Measurement Procedure

1. The EUT was placed on a turn table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measured was complete.


For emissions measurement set the bandwidth of the Spectrum's RBW at 1MHz above 1GHz and RBW 100 KHz below 1GHz.

6.2 Test SET-UP (Block Diagram of Configuration)


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



6.3 Measurement Equipment Used

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
EMI Test Receiver	Rohde & Schwarz	ESU	1302.6005.26	05/29/2013	05/28/2014
Pre-Amplifier	HP	8447D	2944A07999	05/29/2013	05/28/2014
Bilog Antenna	Schwarzbeck	VULB9163	142	05/14/2013	05/13/2014
Loop Antenna	ARA	PLA-1030/B	1029	05/14/2013	05/13/2014
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170399	05/14/2013	05/13/2014
Horn Antenna	Schwarzbeck	BBHA 9120	D143	05/14/2013	05/13/2014
Cable	Schwarzbeck	AK9513	ACRX1	05/29/2013	05/28/2014
Cable	Rosenberger	N/A	FP2RX2	05/29/2013	05/28/2014
Cable	Schwarzbeck	AK9513	CRPX1	05/29/2013	05/28/2014
Cable	Schwarzbeck	AK9513	CRRX2	05/29/2013	05/28/2014

6.4 Radiated Emission Limit

The emissions from an intentional radiator shall not exceed the field strength levels specified in the following table 15.209(a):

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

15.205 Restricted bands of operation

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

- Remark:
1. Emission level in dBuV/m=20 log (uV/m)
 2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
 3. Only spurious frequency is permitted to locate within the Restricted Bands specified in provision of § 15.205, and the emissions located in restricted bands also comply with 15.209 limit.

6.5 Measurement Result

We take 802.11b/g/n(HT20, HT40) mode to test, and the worst test data as following and all modulation methods do not exceed the above mentioned limits.

Operation Mode:	TX Mode	Test Date :	June 25, 2013
Frequency Range:	30~1000MHz	Temperature :	26℃
Test Result:	PASS	Humidity :	60 %
Measured Distance:	3m	Test By:	WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Over (dB)
--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor = $40 \log(\text{Specific distance} / \text{test distance})$ (dB);

Limit line = Specific limits (dBuV) + distance extrapolation factor.

Operation Mode:	802.11b TX Channel 1	Test Date :	June 25, 2013
Frequency Range:	30~1000MHz	Temperature :	26℃
Test Result:	PASS	Humidity :	60 %
Measured Distance:	3m	Test By:	WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Over (dB)	Note
31.55	V	34.72	40.00	-5.28	PK
42.44	V	34.60	40.00	-5.40	PK
311.36	V	36.46	46.00	-9.54	PK
376.65	V	35.76	46.00	-10.24	PK
623.81	V	40.07	46.00	-5.93	PK
936.27	V	42.50	46.00	-3.50	PK
57.98	H	24.29	40.00	-15.71	PK
121.71	H	25.06	43.50	-18.44	PK
308.25	H	28.28	46.00	-17.72	PK
466.81	H	28.72	46.00	-17.28	PK
622.26	H	34.33	46.00	-11.67	PK
933.16	H	32.01	46.00	-13.99	PK

- Note:**
- (1) All Readings are Peak Value.
 - (2) Emission Level = Reading Level + Probe Factor + Cable Loss.
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.
 - (4) EUT stood on the table position is the worst case result in the report.

Operation Mode: 802.11b TX Channel 6 Test Date : June 25, 2013
 Frequency Range: 30~1000MHz Temperature : 26°C
 Test Result: PASS Humidity : 60 %
 Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Over (dB)	Note
31.20	V	33.97	40.00	-6.03	PK
41.96	V	34.95	40.00	-5.05	PK
312.03	V	36.25	46.00	-9.75	PK
378.70	V	36.99	46.00	-9.01	PK
622.76	V	40.52	46.00	-5.48	PK
935.10	V	42.23	46.00	-3.77	PK
59.34	H	26.85	40.00	-13.15	PK
119.63	H	25.84	43.50	-17.66	PK
309.27	H	28.78	46.00	-17.22	PK
468.02	H	28.21	46.00	-17.79	PK
623.24	H	34.12	46.00	-11.88	PK
934.00	H	31.56	46.00	-14.44	PK

- Note:**
- (1) All Readings are Peak Value.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.
 - (4) EUT stood on the table position is the worst case result in the report.

Operation Mode: 802.11b TX Channel 11 Test Date : June 25, 2013
Frequency Range: 30~1000MHz Temperature : 26°C
Test Result: PASS Humidity : 60 %
Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Over (dB)	Note
31.76	V	34.47	40.00	-5.53	PK
43.42	V	33.85	40.00	-6.15	PK
310.98	V	35.41	46.00	-10.59	PK
374.60	V	34.45	46.00	-11.55	PK
624.86	V	37.09	46.00	-8.91	PK
935.01	V	38.79	46.00	-7.21	PK
56.83	H	21.97	40.00	-18.03	PK
124.04	H	24.37	43.50	-19.13	PK
310.03	H	27.16	46.00	-18.84	PK
464.76	H	27.58	46.00	-18.42	PK
623.51	H	32.45	46.00	-13.55	PK
934.39	H	31.22	46.00	-14.78	PK

- Note:**
- (1) All Readings are Peak Value.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.
 - (4) EUT stood on the table position is the worst case result in the report.

Operation Mode: 802.11g TX Channel 1 Test Date : June 25, 2013
 Frequency Range: 30~1000MHz Temperature : 26°C
 Test Result: PASS Humidity : 60 %
 Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Over (dB)	Note
31.34	V	34.04	40.00	-5.96	PK
42.36	V	34.99	40.00	-5.01	PK
310.38	V	37.11	46.00	-8.89	PK
375.46	V	36.08	46.00	-9.92	PK
620.70	V	40.43	46.00	-5.57	PK
939.35	V	42.28	46.00	-3.72	PK
59.00	H	24.02	40.00	-15.98	PK
120.98	H	24.68	43.50	-18.82	PK
307.76	H	27.97	46.00	-18.03	PK
463.76	H	29.50	46.00	-16.50	PK
621.12	H	33.97	46.00	-12.03	PK
931.71	H	32.42	46.00	-13.58	PK

- Note:**
- (1) All Readings are Peak Value.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.
 - (4) EUT stood on the table position is the worst case result in the report.

Operation Mode: 802.11g TX Channel 6 Test Date : June 25, 2013
Frequency Range: 30~1000MHz Temperature : 26°C
Test Result: PASS Humidity : 60%
Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Over (dB)	Note
31.46	V	33.02	40.00	-6.98	PK
42.01	V	33.94	40.00	-6.06	PK
313.89	V	36.90	46.00	-9.10	PK
372.71	V	35.53	46.00	-10.47	PK
618.24	V	40.55	46.00	-5.45	PK
940.70	V	42.20	46.00	-3.80	PK
60.05	H	23.59	40.00	-16.41	PK
118.50	H	24.34	43.50	-19.16	PK
308.77	H	27.74	46.00	-18.26	PK
462.71	H	28.45	46.00	-17.55	PK
622.17	H	34.12	46.00	-11.88	PK
933.03	H	31.97	46.00	-14.03	PK

- Note:**
- (1) All Readings are Peak Value.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.
 - (4) EUT stood on the table position is the worst case result in the report.

Operation Mode: 802.11g TX Channel 11 Test Date : June 25, 2013
Frequency Range: 30~1000MHz Temperature : 26°C
Test Result: PASS Humidity : 60 %
Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Over (dB)	Note
31.53	V	33.73	40.00	-6.27	PK
41.31	V	33.87	40.00	-6.13	PK
308.26	V	35.06	46.00	-10.94	PK
377.81	V	33.86	46.00	-12.14	PK
620.58	V	41.80	46.00	-4.20	PK
938.91	V	44.95	46.00	-1.05	PK
60.36	H	21.36	40.00	-18.64	PK
122.46	H	24.30	43.50	-19.20	PK
305.24	H	24.92	46.00	-21.08	PK
465.82	H	28.38	46.00	-17.62	PK
621.83	H	32.61	46.00	-13.39	PK
933.04	H	31.65	46.00	-14.35	PK

- Note:**
- (1) All Readings are Peak Value.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.
 - (4) EUT stood on the table position is the worst case result in the report.

Operation Mode: 802.11n
HT20 TX Channel 1
Frequency Range: 30~1000MHz
Test Result: PASS
Measured Distance: 3m
Test Date : June 25, 2013
Temperature : 26°C
Humidity : 60 %
Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Over (dB)	Note
31.72	V	34.26	40.00	-5.74	PK
41.39	V	35.05	40.00	-4.95	PK
311.15	V	36.21	46.00	-9.79	PK
376.10	V	35.61	46.00	-10.39	PK
624.87	V	39.72	46.00	-6.28	PK
936.19	V	42.32	46.00	-3.68	PK
57.33	H	24.18	40.00	-15.82	PK
122.12	H	24.50	43.50	-19.00	PK
309.27	H	28.96	46.00	-17.04	PK
465.76	H	28.20	46.00	-17.80	PK
623.36	H	34.78	46.00	-11.22	PK
934.11	H	33.06	46.00	-12.94	PK

- Note:**
- (1) All Readings are Peak Value.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.
 - (4) EUT stood on the table position is the worst case result in the report.

Operation Mode: 802.11n Test Date : June 25, 2013
HT20 TX Channel 6
Frequency Range: 30~1000MHz Temperature : 26°C
Test Result: PASS Humidity : 60 %
Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Over (dB)	Note
34.08	V	33.72	40.00	-6.28	PK
40.34	V	33.88	40.00	-6.12	PK
313.18	V	36.03	46.00	-9.97	PK
372.65	V	35.05	46.00	-10.95	PK
622.76	V	39.36	46.00	-6.64	PK
934.16	V	42.10	46.00	-3.90	PK
58.38	H	22.82	40.00	-17.18	PK
124.75	H	25.12	43.50	-18.38	PK
310.71	H	29.97	46.00	-16.03	PK
463.75	H	27.64	46.00	-18.36	PK
620.11	H	35.14	46.00	-10.86	PK
933.06	H	32.65	46.00	-13.35	PK

- Note:**
- (1) All Readings are Peak Value.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.
 - (4) EUT stood on the table position is the worst case result in the report.

Operation Mode: 802.11n Test Date : June 25, 2013
 HT20 TX Channel 11
 Frequency Range: 30~1000MHz Temperature : 26°C
 Test Result: PASS Humidity : 60 %
 Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Over (dB)	Note
32.70	V	33.61	40.00	-6.39	PK
40.34	V	33.80	40.00	-6.20	PK
308.79	V	35.19	46.00	-10.81	PK
378.45	V	34.56	46.00	-11.44	PK
624.75	V	40.74	46.00	-5.26	PK
938.54	V	41.20	46.00	-4.80	PK
58.69	H	23.50	40.00	-16.50	PK
123.60	H	24.28	43.50	-19.22	PK
305.54	H	26.83	46.00	-19.17	PK
467.82	H	26.42	46.00	-19.58	PK
624.11	H	33.24	46.00	-12.76	PK
935.57	H	32.01	46.00	-13.99	PK

- Note:**
- (1) All Readings are Peak Value.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.
 - (4) EUT stood on the table position is the worst case result in the report.

Operation Mode:	802.11n HT40 TX Channel 3	Test Date :	June 25, 2013
Frequency Range:	30~1000MHz	Temperature :	26°C
Test Result:	PASS	Humidity :	60 %
Measured Distance:	3m	Test By:	WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Over (dB)	Note
32.20	V	34.97	40.00	-5.03	PK
43.42	V	35.33	40.00	-4.67	PK
312.01	V	36.22	46.00	-9.78	PK
375.58	V	35.61	46.00	-10.39	PK
624.40	V	40.72	46.00	-5.28	PK
937.05	V	42.13	46.00	-3.87	PK
58.76	H	25.06	40.00	-14.94	PK
120.68	H	24.39	43.50	-19.11	PK
309.90	H	28.42	46.00	-17.58	PK
467.18	H	29.70	46.00	-16.30	PK
623.31	H	34.70	46.00	-11.30	PK
934.41	H	32.64	46.00	-13.36	PK

- Note:**
- (1) All Readings are Peak Value.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.
 - (4) EUT stood on the table position is the worst case result in the report.

Operation Mode: 802.11n Test Date : June 25, 2013
HT40 TX Channel 6
Frequency Range: 30~1000MHz Temperature : 26℃
Test Result: PASS Humidity : 60 %
Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Over (dB)	Note
33.35	V	34.50	40.00	-5.50	PK
42.37	V	34.10	40.00	-5.90	PK
314.04	V	36.04	46.00	-9.96	PK
372.13	V	35.05	46.00	-10.95	PK
622.29	V	40.36	46.00	-5.64	PK
935.02	V	41.91	46.00	-4.09	PK
56.31	H	24.32	40.00	-15.68	PK
118.05	H	25.01	43.50	-18.49	PK
311.34	H	29.43	46.00	-16.57	PK
465.17	H	28.26	46.00	-17.74	PK
620.06	H	35.06	46.00	-10.94	PK
936.97	H	32.23	46.00	-13.77	PK

- Note:**
- (1) All Readings are Peak Value.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.
 - (4) EUT stood on the table position is the worst case result in the report.

Operation Mode: 802.11n Test Date : June 25, 2013
HT40 TX Channel 9
Frequency Range: 30~1000MHz Temperature : 26°C
Test Result: PASS Humidity : 60 %
Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Over (dB)	Note
34.09	V	34.02	40.00	-5.98	PK
41.32	V	34.86	40.00	-5.14	PK
311.93	V	35.11	46.00	-10.89	PK
373.91	V	35.29	46.00	-10.71	PK
622.17	V	39.94	46.00	-6.06	PK
934.58	V	41.14	46.00	-4.86	PK
57.67	H	25.42	40.00	-14.58	PK
119.53	H	24.17	43.50	-19.33	PK
307.61	H	27.37	46.00	-18.63	PK
467.23	H	28.58	46.00	-17.42	PK
621.11	H	33.92	46.00	-12.08	PK
938.33	H	31.59	46.00	-14.41	PK

- Note:**
- (1) All Readings are Peak Value.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.
 - (4) EUT stood on the table position is the worst case result in the report.

Operation Mode: 802.11b TX Channel 1 Test Date : June 25, 2013
 Frequency Range: 1GHz~25GHz Temperature : 26°C
 Test Result: PASS Humidity : 60 %
 Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4835.39	V	50.08	36.81	74.00	54.00	-23.92	-17.19
7215.25	V	50.21	37.17	74.00	54.00	-23.79	-16.83
9692.43	V	51.33	40.08	74.00	54.00	-22.67	-13.92
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--
4835.37	H	49.20	35.76	74.00	54.00	-24.80	-18.24
7216.18	H	50.07	36.29	74.00	54.00	-23.93	-17.71
9687.83	H	51.37	37.34	74.00	54.00	-22.63	-16.66

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) Data of measurement within this frequency range shown “ -- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Operation Mode: 802.11b TX Channel 6 Test Date : June 25, 2013
Frequency Range: 1GHz~25GHz Temperature : 26℃
Test Result: PASS Humidity : 60 %
Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4886.02	V	49.47	36.47	74.00	54.00	-24.53	-17.53
7288.25	V	49.36	36.44	74.00	54.00	-24.64	-17.56
9793.17	V	52.68	40.75	74.00	54.00	-21.32	-13.25
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--
4885.58	H	48.75	35.49	74.00	54.00	-25.25	-18.51
7291.79	H	49.39	35.97	74.00	54.00	-24.61	-18.03
9788.85	H	50.14	36.41	74.00	54.00	-23.86	-17.59

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

Note: (1) All Readings are Peak Value and AV.
(2) Emission Level= Reading Level+Probe Factor +Cable Loss.
(3) Data of measurement within this frequency range shown “ -- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Operation Mode: 802.11b TX Channel 11 Test Date : June 25, 2013
Frequency Range: 1GHz~25GHz Temperature : 26℃
Test Result: PASS Humidity : 60 %
Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4935.41	V	49.17	35.92	74.00	54.00	-24.83	-18.08
7364.32	V	49.16	36.49	74.00	54.00	-24.84	-17.51
9893.69	V	51.70	39.72	74.00	54.00	-22.30	-14.28
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--
4933.90	H	50.15	36.05	74.00	54.00	-23.85	-17.95
7365.45	H	51.15	37.12	74.00	54.00	-22.85	-16.88
9889.18	H	50.52	36.78	74.00	54.00	-23.48	-17.22

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

Note: (1) All Readings are Peak Value and AV.
(2) Emission Level= Reading Level+Probe Factor +Cable Loss.
(3) Data of measurement within this frequency range shown “ -- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Operation Mode: 802.11g TX Channel 1 Test Date : June 25, 2013
Frequency Range: 1GHz~25GHz Temperature : 26°C
Test Result: PASS Humidity : 60 %
Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4838.02	V	49.54	37.62	74.00	54.00	-24.46	-16.38
7218.30	V	49.86	37.73	74.00	54.00	-24.14	-16.27
9692.31	V	52.38	39.06	74.00	54.00	-21.62	-14.94
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--
4834.02	H	49.82	36.20	74.00	54.00	-24.18	-17.80
7217.14	H	51.15	37.31	74.00	54.00	-22.85	-16.69
9686.78	H	51.47	37.78	74.00	54.00	-22.53	-16.22

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

Note: (1) All Readings are Peak Value and AV.
(2) Emission Level= Reading Level +Probe Factor +Cable Loss.
(3) Data of measurement within this frequency range shown “ -- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Operation Mode: 802.11g TX Channel 6 Test Date : June 25, 2013
Frequency Range: 1GHz~25GHz Temperature : 26°C
Test Result: PASS Humidity : 60 %
Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4886.64	V	48.09	36.72	74.00	54.00	-25.91	-17.28
7289.72	V	51.98	38.40	74.00	54.00	-22.02	-15.60
9792.19	V	53.71	40.27	74.00	54.00	-20.29	-13.73
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--
4883.24	H	51.43	37.04	74.00	54.00	-22.57	-16.96
7292.77	H	51.90	36.96	74.00	54.00	-22.10	-17.04
9788.40	H	52.68	37.90	74.00	54.00	-21.32	-16.10

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) Data of measurement within this frequency range shown “ -- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Operation Mode: 802.11g TX Channel 11 Test Date : June 25, 2013
Frequency Range: 1GHz~25GHz Temperature : 26℃
Test Result: PASS Humidity : 60 %
Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4936.20	V	48.40	35.57	74.00	54.00	-25.60	-18.43
7360.47	V	49.45	35.89	74.00	54.00	-24.55	-18.11
9891.64	V	54.71	39.63	74.00	54.00	-19.29	-14.37
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--
4931.56	H	51.03	37.29	74.00	54.00	-22.97	-16.71
7366.43	H	51.46	37.36	74.00	54.00	-22.54	-16.64
9888.20	H	50.22	36.80	74.00	54.00	-23.78	-17.20

N All emissions not reported were more than 20dB below the specified limit or in the noise floor.

Note: (1) All Readings are Peak Value and AV.
(2) Emission Level= Reading Level+Probe Factor +Cable Loss.
(3) Data of measurement within this frequency range shown “ -- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Operation Mode: 802.11n Test Date : June 25, 2013
HT20 TX Channel 1
Frequency Range: 1GHz~25GHz Temperature : 26°C
Test Result: PASS Humidity : 60 %
Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4833.71	V	50.99	37.26	74.00	54.00	-23.01	-16.74
7217.02	V	50.62	37.46	74.00	54.00	-23.38	-16.54
9693.11	V	52.35	40.96	74.00	54.00	-21.65	-13.04
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--
4833.73	H	50.43	34.51	74.00	54.00	-23.57	-19.49
7215.19	H	48.71	35.33	74.00	54.00	-25.29	-18.67
9688.40	H	49.32	36.29	74.00	54.00	-24.68	-17.71

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) Data of measurement within this frequency range shown “ -- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Operation Mode: 802.11n Test Date : June 25, 2013
HT20 TX Channel 6
Frequency Range: 1GHz~25GHz Temperature : 26°C
Test Result: PASS Humidity : 60%
Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4886.65	V	51.22	36.61	74.00	54.00	-22.78	-17.39
7289.58	V	51.87	38.35	74.00	54.00	-22.13	-15.65
9791.99	V	53.33	41.32	74.00	54.00	-20.67	-12.68
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--
4880.34	H	51.74	35.46	74.00	54.00	-22.26	-18.54
7290.81	H	49.42	34.30	74.00	54.00	-24.58	-19.70
9787.92	H	50.42	35.64	74.00	54.00	-23.58	-18.36

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

Note: (1) All Readings are Peak Value and AV.
(2) Emission Level= Reading Level+Probe Factor +Cable Loss.
(3) Data of measurement within this frequency range shown “ -- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Operation Mode: 802.11n Test Date : June 25, 2013
HT20 TX Channel 11
Frequency Range: 1GHz~25GHz Temperature : 26°C
Test Result: PASS Humidity : 60%
Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4935.05	V	52.13	38.17	74.00	54.00	-21.87	-15.83
7362.27	V	49.98	0.46	74.00	54.00	-24.02	-53.54
9891.86	V	54.21	41.75	74.00	54.00	-19.79	-12.25
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--
4934.24	H	51.48	35.49	74.00	54.00	-22.52	-18.51
7366.12	H	49.80	36.06	74.00	54.00	-24.20	-17.94
9887.87	H	50.57	36.92	74.00	54.00	-23.43	-17.08

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

Note: (1) All Readings are Peak Value and AV.
(2) Emission Level= Reading Level+Probe Factor +Cable Loss.
(3) Data of measurement within this frequency range shown “ -- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Operation Mode: 802.11n Test Date : June 25, 2013
HT40 TX Channel 3
Frequency Range: 1GHz~25GHz Temperature : 26°C
Test Result: PASS Humidity : 60 %
Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4849.54	V	51.90	37.71	74.00	54.00	-22.10	-16.29
7267.05	V	50.21	37.17	74.00	54.00	-23.79	-16.83
9689.22	V	51.33	40.08	74.00	54.00	-22.67	-13.92
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--
4849.32	H	49.20	35.76	74.00	54.00	-24.80	-18.24
7267.07	H	50.07	36.29	74.00	54.00	-23.93	-17.71
9689.38	H	51.37	37.34	74.00	54.00	-22.63	-16.66

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) Data of measurement within this frequency range shown “ -- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Operation Mode: 802.11n HT40 TX Channel 6 Test Date : June 25, 2013
Frequency Range: 1GHz~25GHz Temperature : 26℃
Test Result: PASS Humidity : 60%
Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4886.75	V	51.03	37.33	74.00	54.00	-22.97	-16.67
7312.78	V	49.58	36.76	74.00	54.00	-24.42	-17.24
9759.57	V	52.14	40.60	74.00	54.00	-21.86	-13.40
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--
4885.14	H	50.18	36.27	74.00	54.00	-23.82	-17.73
7337.18	H	49.71	36.50	74.00	54.00	-24.29	-17.50
9760.66	H	52.26	37.09	74.00	54.00	-21.74	-16.91

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) Data of measurement within this frequency range shown “ -- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Operation Mode: 802.11n Test Date : June 25, 2013
HT40 TX Channel 9
Frequency Range: 1GHz~25GHz Temperature : 26°C
Test Result: PASS Humidity : 60%
Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4917.82	V	51.28	37.59	74.00	54.00	-22.72	-16.41
7362.36	V	48.70	36.12	74.00	54.00	-25.30	-17.88
9814.48	V	51.08	39.87	74.00	54.00	-22.92	-14.13
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--
4917.71	H	48.82	35.53	74.00	54.00	-25.18	-18.47
7362.34	H	48.76	36.61	74.00	54.00	-25.24	-17.39
9814.74	H	50.44	36.67	74.00	54.00	-23.56	-17.33

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

Note: (1) All Readings are Peak Value and AV.
(2) Emission Level= Reading Level+Probe Factor +Cable Loss.
(3) Data of measurement within this frequency range shown “ -- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

7. 6dB Bandwidth Test

7.1 Measurement Procedure

The EUT was operating in IEEE 802.11b/g/n mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.

1. Set resolution bandwidth (RBW) = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequency) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

7.2 Test SET-UP (Block Diagram of Configuration)



7.3 Measurement Equipment Used


EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Agilent	E4407B	88156318	05/29/2013	05/28/2014



7.4 Measurement Results

6 Bandwidth Test Data Chart:
Refer to attached data chart.

Spectrum Detector:	PK	Test Date :	June 20, 2013
Test By:	Jack	Temperature :	26°C
Test Result:	PASS	Humidity :	60 %
Operation Mode: 802.11b			


Channel number	Channel frequency (MHz)	Measurement level (MHz)	Required Limit (kHz)
1	2412	12.161	>500
6	2437	12.079	>500
11	2462	12.076	>500







Spectrum Detector: PK Test Date : June 20, 2013
 Test By: Jack Temperature : 26℃
 Test Result: PASS Humidity : 60 %
 Operation Mode: 802.11 g


Channel number	Channel frequency (MHz)	Measurement level (MHz)	Required Limit (kHz)
1	2412	16.133	>500
6	2437	16.141	>500
11	2462	16.439	>500







Spectrum Detector: PK Test Date : June 20, 2013
 Test By: Jack Temperature : 26°C
 Test Result: PASS Humidity : 60 %
 Operation Mode: 802.11 n HT20


Channel number	Channel frequency (MHz)	Measurement level (MHz)	Required Limit (kHz)
1	2412	17.070	>500
6	2437	17.088	>500
11	2462	16.916	>500







Spectrum Detector: PK Test Date : June 20, 2013
 Test By: Jack Temperature : 26°C
 Test Result: PASS Humidity : 60 %
 Operation Mode: 802.11 n HT40

Channel number	Channel frequency (MHz)	Measurement level (MHz)	Required Limit (kHz)
3	2422	35.521	>500
6	2437	35.545	>500
9	2452	35.629	>500





8. Maximum Peak Output Power Test

8.1 Measurement Procedure

The maximum peak conducted output power can be measured using a broadband peak RF power meter. The power meter must have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast, average-responding diode type sensor.

- a. The Transmitter output (antenna port) was connected to the power meter.
- b. Turn on the EUT and power meter and then record the peak power value.
- c. Repeat above procedures on all channels needed to be tested.

8.2 Test SET-UP (Block Diagram of Configuration)



8.3 Measurement Equipment Used

EQUIPMENT TYPE	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Power meter	ML2495A	0824006	05/29/2013	05/28/2014
Power sensor	MA2411B	0738172	05/29/2013	05/28/2014

8.4 Peak Power output limit

The maximum peak power shall be less 1Watt.

8.5 Measurement Results

Spectrum Detector:	PK	Test Date :	June 20, 2013
Test By:	Jack	Temperature :	20°C
Test Result:	PASS	Humidity :	60 %
Operation Mode: 802.11b			

Channel number	Channel Frequency(MHz)	Peak Power output(dBm)	Peak Power Limit(W)	Pass/Fail
1	2412	8.84	1W(30dBm)	PASS
6	2437	8.80	1W(30dBm)	PASS
11	2462	8.60	1W(30dBm)	PASS

Spectrum Detector: PK Test Date : June 20, 2013
Test By: Jack Temperature : 26°C
Test Result: PASS Humidity : 60 %
Operation Mode: 802.11g

Channel number	Channel Frequency (MHz)	Peak Power output(dBm)	Peak Power Limit(W)	Pass/Fail
1	2412.00	8.46	1W(30dBm)	PASS
6	2437.00	8.61	1W(30dBm)	PASS
11	2462.00	8.47	1W(30dBm)	PASS

Spectrum Detector: PK Test Date : June 20, 2013
Test By: Jack Temperature : 26°C
Test Result: PASS Humidity : 60 %
Operation Mode: 802.11n H20

Channel number	Channel Frequency (MHz)	Peak Power output(dBm)	Peak Power Limit(W)	Pass/Fail
1	2412.00	8.79	1W(30dBm)	PASS
6	2437.00	8.23	1W(30dBm)	PASS
11	2462.00	8.24	1W(30dBm)	PASS

Spectrum Detector: PK Test Date : June 20, 2013
Test By: Jack Temperature : 26°C
Test Result: PASS Humidity : 60 %
Operation Mode: 802.11n H40

Channel number	Channel Frequency (MHz)	Peak Power output(dBm)	Peak Power Limit(W)	Pass/Fail
3	2422.00	8.45	1W(30dBm)	PASS
6	2437.00	8.57	1W(30dBm)	PASS
9	2452.00	8.56	1W(30dBm)	PASS

9. Band Edge Test

9.1 Measurement Procedure

1. The EUT was Operating in hopping mode or could be controlled its channel. Printed out test result from the spectrum by hard copy function.
2. The EUT was placed on a turn table which is 0.8m above ground plane.
3. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
4. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
5. Repeat above procedures until all frequency measured were complete.

9.2 Test SET-UP (Block Diagram of Configuration)

As 6.2 Test set up (B) and (C)

9.3 Measurement Equipment Used

Same as 6.3 Radiated Emission Measurement.

9.4 Measurement Results

Test mode: 802.11b

Spectrum Detector:	PK/AV	Test Date :	June 20, 2013
Test By:	Jack	Temperature :	26 °C
Test channel:	01	Humidity :	60 %

Frequency (MHz)	Polarity	Level (dBuV/m)		Limited (dBuV/m)	
		PK	AV	PK	AV
2390	H	43.27	31.78	74	54
2390	V	44.53	32.62	74	54

Spectrum Detector:	PK/AV	Test Date :	June 20, 2013
Test By:	Jack	Temperature :	26 °C
Test channel:	11	Humidity :	60 %

Frequency (MHz)	Polarity	Level (dBuV/m)		Limited (dBuV/m)	
		PK	AV	PK	AV
2483.5	H	43.11	31.91	74	54
2483.5	V	42.68	30.67	74	54

Test mode: 802.11g

Spectrum Detector: PK/AV Test Date : June 20, 2013
Test By: Jack Temperature : 26 °C
Test channel: 01 Humidity : 60 %

Frequency (MHz)	Polarity	Level (dBuV/m)		Limited (dBuV/m)	
		PK	AV	PK	AV
2390.00	H	43.62	32.13	74	54
2390.00	V	44.27	31.98	74	54

Spectrum Detector: PK/AV Test Date : June 20, 2013
Test By: Jack Temperature : 26 °C
Test channel: 11 Humidity : 60 %

Frequency (MHz)	Polarity	Level (dBuV/m)		Limited (dBuV/m)	
		PK	AV	PK	AV
2483.50	H	43.76	32.15	74	54
2483.50	V	42.91	29.82	74	54

Test mode: 802.11n HT20

Spectrum Detector: PK/AV Test Date : June 20, 2013
Test By: Jack Temperature : 26 °C
Test channel: 01 Humidity : 60 %

Frequency (MHz)	Polarity	Level (dBuV/m)		Limited (dBuV/m)	
		PK	AV	PK	AV
2390.00	H	43.52	31.9	74	54
2390.00	V	44.39	33.06	74	54

Spectrum Detector: PK/AV Test Date : June 20, 2013
Test By: Jack Temperature : 26 °C
Test channel: 11 Humidity : 60 %

Frequency (MHz)	Polarity	Level (dBuV/m)		Limited (dBuV/m)	
		PK	AV	PK	AV
2483.50	H	44.09	32.66	74	54
2483.50	V	41.7	30.35	74	54

Test mode: 802.11n HT40

Spectrum Detector: PK/AV Test Date : June 20, 2013
 Test By: Jack Temperature : 26 °C
 Test channel: 03 Humidity : 60%

Frequency (MHz)	Polarity	Level (dBuV/m)		Limited (dBuV/m)	
		PK	AV	PK	AV
2390.00	H	43.39	31.92	74	54
2390.00	V	44.36	32.11	74	54

Spectrum Detector: PK/AV Test Date : June 20, 2013
 Test By: Jack Temperature : 26 °C
 Test channel: 09 Humidity : 60 %

Frequency (MHz)	Polarity	Level (dBuV/m)		Limited (dBuV/m)	
		PK	AV	PK	AV
2483.50	H	42.06	31.4	74	54
2483.50	V	42.23	30.36	74	54

10. Power Density

10.1 Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Agilent	E4407B	88156318	05/29/2013	05/28/2014

10.2 Measuring Instruments and Setting


The following table is the setting of spectrum analyzer.

Spectrum analyzer	Setting
Attenuation	Auto
Span Frequency	Set the span to 1.5 times the DTS bandwidth.
RB	3kHz $\geq$ RBW $\leq$ 100KHz
VB	3 x RBW
Detector	Peak
Trace	Max hold
Sweep Time	Automatic

10.3 Test Procedures

- a. The transmitter output (antenna port) was connected to the spectrum analyzer.
- b. Set analyzer center frequency to DTS channel center frequency.
- c. Set the analyzer span to a minimum of 1.5 times the DTS bandwidth.
- d. Set the RBW $\geq$ 3 kHz. Set the VBW $\geq$ 3 x RBW.
- e. Detector = peak.
- f. Sweep time = auto couple.
- g. Trace mode = max hold.
- h. Allow trace to fully stabilize.
- i. Use the peak marker function to determine the maximum amplitude level.

10.4 Block Diagram of Test Setup




10.5 Limit



The transmitted power density averaged over any 1 second interval shall not be greater +8dBm in any 3 kHz bandwidth.

10.6 Test Result

Spectrum Detector:	PK	Test Date :	June 20, 2013
Test By:	Jack	Temperature :	26 °C
Test Result:	PASS	Humidity :	60 %
Operation Mode:	802.11 b		


Channel	Measurement Level (dBm)	Required Limit (dBm)	Result
1	-15.72	<8dBm	PASS
6	-18.17	<8dBm	PASS
11	-18.55	<8dBm	PASS







Spectrum Detector:	PK	Test Date :	June 20, 2013
Test By:	Andy	Temperature :	28℃
Test Result:	PASS	Humidity :	65 %
Operation Mode: 802.11 g			


Channel	Measurement Level (dBm)	Required Limit (dBm)	Result
1	-18.78	<8dBm	PASS
6	-20.09	<8dBm	PASS
11	-21.39	<8dBm	PASS







Spectrum Detector: PK Test Date : June 20, 2013
 Test By: Andy Temperature : 28℃
 Test Result: PASS Humidity : 65 %
 Operation Mode: 802.11 n HT20

Channel	Measurement Level (dBm)	Required Limit (dBm)	Result
1	-17.75	<8dBm	PASS
6	-19.68	<8dBm	PASS
11	-20.78	<8dBm	PASS








Spectrum Detector: PK Test Date : June 20, 2013
 Test By: Andy Temperature : 28℃
 Test Result: PASS Humidity : 65 %

Operation Mode: 802.11 n HT40

Channel	Measurement Level (dBm)	Required Limit (dBm)	Result
3	-22.36	<8dBm	PASS
6	-22.21	<8dBm	PASS
9	-22.49	<8dBm	PASS





11. Antenna Port Emission

11.1 Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Agilent	E4407B	88156318	05/29/2013	05/28/2014

11.2 Measuring Instruments and Setting


The following table is the setting of spectrum analyzer.

Spectrum analyzer	Setting
Attenuation	Auto
RB	100kHz
VB	300kHz
Detector	Peak
Trace	Max hold

11.3 Test Procedures

The conducted spurious emissions were measured conducted using a spectrum analyzer at low, Middle, and high channels, the limit was determined by attenuation 20dB of the RF peak power output.



11.4 Block Diagram of Test setup





11.5 Test Result

PASS.



802.11b Low Channel 1





802.11b Mid Channel 6





802.11b High Channel 11





802.11g Low Channel 1





802.11g Mid Channel 6





802.11g High Channel 11





802.11n HT20 Low Channel 1





802.11n HT20 Mid Channel 6





802.11n HT20 High Channel 11





802.11n HT40 Low Channel 3



802.11n HT40 Mid Channel 6



802.11n HT40 High Channel 9



12. Antenna Application

12.1 Antenna Requirement

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

12.2 Result

The EUT'S antenna is Metal Antenna. The antenna's gain is 2.8dBi and meets the requirement.