

# Report on the FCC and IC Testing of the Siemens AG

Model: SIMATIC RTLS5201T

In accordance with  
FCC 47 CFR Part 1.1310 and Part 2.1093 &  
ISED RSS-GEN Issue 5, section 3.4 and ISED RSS-102,  
Issue 5, section 2.5

Prepared for: Siemens AG  
Gleiwitzer Str. 555  
90475 Nuernberg  
Germany

FCC ID: SCF5201T01  
IC: 267X-5201T01



Product Service

Choose certainty.  
Add value.

## COMMERCIAL-IN-CONFIDENCE

Date: 2023-03-08

Document Number: TR-713278992-05 | Revision: 0

RESPONSIBLE FOR	NAME	DATE	SIGNATURE
Project Management	Michael Ingerl	2023-03-08	 SIGN-ID 768487
Authorised Signatory	Matthias Stumpe	2023-03-08	 SIGN-ID 768644

Signatures in this approval box have checked this document in line with the requirements of TÜV SÜD Product Service document control rules.

### ENGINEERING STATEMENT

The measurements shown in this report were made in accordance with the procedures described on test pages. All reported testing was carried out on a sample equipment to demonstrate limited compliance with FCC 47 CFR Part 1.1310 and Part 2.1093 & ISED RSS-GEN Issue 5, section 3.4 and ISED RSS-102, Issue 5, section 2.5. The sample tested was found to comply with the requirements defined in the applied rules.

RESPONSIBLE FOR	NAME	DATE	
Testing	Michael Ingerl	2023-03-08	 SIGN-ID 768488
Laboratory Accreditation DAkkS Reg. No. D-PL-11321-11-02 DAkkS Reg. No. D-PL-11321-11-03	Laboratory recognition Registration No. BNetzA-CAB-16/21-15	ISED Canada test site registration 3050A-2	

### EXECUTIVE SUMMARY

A sample of this product was tested and found to be compliant with FCC 47 CFR Part 1.1310 and Part 2.1093 & ISED RSS-GEN Issue 5, section 3.4 and ISED RSS-102, Issue 5, section 2.5

### DISCLAIMER AND COPYRIGHT

This non-binding report has been prepared by TÜV SÜD Product Service with all reasonable skill and care. The document is confidential to the potential Client and TÜV SÜD Product Service. No part of this document may be reproduced without the prior written approval of TÜV SÜD Product Service. © 2023 TÜV SÜD Product Service.

Trade Register Munich  
HRB 85742  
VAT ID No. DE129484267  
Information pursuant to Section 2(1)  
DL-InfoV (Germany) at  
[www.tuvsud.com/imprint](http://www.tuvsud.com/imprint)

Managing Directors:  
Walter Reithmaier (CEO)  
Patrick van Welij

Phone: +49 9421 5682-0  
Fax: +49 9421 5682-199  
[www.tuvsud.com](http://www.tuvsud.com)

TÜV SÜD Product Service GmbH  
Äußere Frühlingstraße 45  
94315 Straubing  
Germany

## Contents

<b>1</b>	<b>Report Summary .....</b>	<b>2</b>
1.1	Report Modification Record.....	2
1.2	Introduction.....	2
1.3	Brief Summary of Results .....	3
1.4	Basic information of EUT .....	4
1.5	EUT Modification Record .....	5
1.6	Test Location.....	5
<b>2</b>	<b>Test Details .....</b>	<b>6</b>
2.1	Exposure of Humans to RF Fields .....	6
<b>3</b>	<b>Measurement Uncertainty .....</b>	<b>10</b>

## 1 Report Summary

### 1.1 Report Modification Record

Alterations and additions to this report will be issued to the holders of each copy in the form of a complete document.

Revision	Description of Change	Date of Issue
0	First Revision	2023-03-08

**Table 1**

### 1.2 Introduction

Applicant	Siemens AG
Manufacturer	Siemens AG
Model Number(s)	SIMATIC RTLS5201T
Serial Number(s)	17:A6:10:02:09:56
MLFB(s)	6GT2752-0TS01
Hardware Version(s)	FS:01
Number of Samples Tested	1
Test Specification/Issue/Date	FCC 47 CFR Part 1.1310 and Part 2.1093 & ISED RSS-GEN Issue 5, section 3.4 and ISED RSS-102, Issue 5, section 2.5
Test Plan/Issue/Date	---
Order Number	713278992
Date of Receipt of EUT	2023-02-28
Start of Test	2023-02-28
Finish of Test	2023-02-28
Name of Engineer(s)	Michael Ingerl
Related Document(s)	KDB 447498 D04 General RF Exposure Guidance ANSI C63.10 (2013)



### 1.3 Brief Summary of Results

A brief summary of the tests carried out in accordance with FCC 47 CFR Part 1.1310 and Part 2.1093 & ISED RSS-GEN Issue 5, section 3.4 and ISED RSS-102, Issue 5, section 2.5 is shown below.

Section	Specification Clause	Test Description	Result	Comments/Base Standard
Configuration and Mode: 3V DC Battery Powered – Continuous transmitting				
2.1	1.1310	Exposure of Humans to RF Fields	Pass	KDB 447498 D04

**Table 2**

#### 1.4 Basic information of EUT

<b>Equipment characteristics:</b>			
<i>Type of equipment:</i>	RTLS Transponder		
<i>Type designation:</i>	SIMATIC RTLS5201T		
	<input type="checkbox"/> AC Nominal: Minimum: Maximum: Nominal frequency:	<input type="checkbox"/> DC Nominal:	<input checked="" type="checkbox"/> Battery Nominal: 3 V
	Short Range Device using Ultra Wideband technology		
	LT1-System		
	UWB, BPSK with BPM		
	Internal PCB Antenna		
	2 dBi		
	1 (6489 MHz)		

## 1.5 EUT Modification Record

The table below details modifications made to the EUT during the test programme.  
The modifications incorporated during each test are recorded on the appropriate test pages.

Modification State	Description of Modification still fitted to EUT	Modification Fitted By	Date Modification Fitted
0	As supplied by the customer / SN: 17:A6:10:02:09:56	Not Applicable	Not Applicable

**Table 3**

## 1.6 Test Location

TÜV SÜD Product Service conducted the following tests at our Straubing Test Laboratory.

Test Name	Name of Engineer(s)
Configuration and Mode: 3V DC Battery Powered – Continuous transmitting	
Exposure of Humans to RF Fields	Michael Ingerl

**Table 4**

Office Address:

Äußere Frühlingstraße 45  
94315 Straubing  
Germany



## 2 Test Details

### 2.1 Exposure of Humans to RF Fields

#### 2.1.1 Specification Reference

FCC 47 CFR Part 1.1310 and Part 2.1093 &  
ISED RSS-GEN Issue 5, section 3.4 and ISED RSS-102, Issue 5, section 2.5  
KDB 447498 D04 General RF Exposure Guidance

#### 2.1.2 Equipment Under Test and Modification State

SIMATIC RTLS5201T, S/N: 17:A6:10:02:09:56 - Modification State 0

#### 2.1.3 Date of Test

2023-02-28

#### 2.1.4 Evaluation Results

acc. to KDB 447498 D04:

EIRP: -63.18 dBm / MHz (RMS) = 0.000000481 mW / MHz

UWB Bandwidth: 498 MHz

Total EIRP Power:  $0.000000481 \times 498 \text{ MHz} = 0.00024 \text{ mW}$

Antenna gain declared to be 2 dBi therefore conducted power is 0.00015 mW

Limit: 1 mW -> **Pass**

Note: Values taken from Test Report TR-713278992-04.

ISED RSS-GEN Issue 5, section 3.2 and ISED RSS-102, Issue 5, section 2.5 :

Exposure of Humans to RF Fields	Applicable	Declared by applicant	Measured	Exemption
The antenna is				
<input type="checkbox"/> detachable				
The conducted output power (CP in watts) is measured at the antenna connector: $CP =$				
The effective isotropic radiated power (EIRP in watts) is calculated using				
<input type="checkbox"/> the numerical antenna gain: $G =$	<input type="checkbox"/>			
$EIRP = G \cdot CP \Rightarrow EIRP =$				
<input type="checkbox"/> the field strength <sup>1</sup> in V/m: $FS = \dots \text{ V/m}$		<input type="checkbox"/>		
$EIRP = \frac{(FS \cdot D)^2}{30} \Rightarrow EIRP = \text{ mW}$				
with:				
Distance between the antennas in m: $D = \text{ mm}$	<input type="checkbox"/>			
<input checked="" type="checkbox"/> not detachable				
A field strength measurement is used to determine the effective isotropic radiated power (EIRP in watts) given by:				
$EIRP = \frac{(FS \cdot D)^2}{30} \Rightarrow EIRP = 0.00024 \text{ mW}$ (See at TR-713278992-04)				
with:				
Field strength in V/m: $FS =$ =		<input type="checkbox"/>		
Distance between the two antennas in m: $D =$		<input type="checkbox"/>		
Selection of output power				
The output power TP is the higher of the conducted or effective isotropic radiated power (e.i.r.p.):				
$TP = 0.00024 \text{ mW}$				

<sup>1</sup> The conversion formula is valid only for properly matched antennas. In other cases the transmitter output power may have to be measured by a terminated measurement when applying the exemption clauses. If an open area test site is used for field strength measurement, the effect due to the metal ground reflecting plane should be subtracted from the maximum field strength value in order to reference it to free space, before calculating TP.



Exposure of Humans to RF Fields (continued)		Applicable	Declared by applicant	Measured	Exemption
Separation distance between the user and the transmitting device is					
<input checked="" type="checkbox"/> less than or equal to 20 cm		<input type="checkbox"/> greater than 20 cm		<input checked="" type="checkbox"/>	<input type="checkbox"/>
Transmitting device is					
<input type="checkbox"/> in the vicinity of the human head		<input type="checkbox"/> body-worn		<input type="checkbox"/>	<input type="checkbox"/>

SAR evaluation										
Frequency (MHz)	Exemption limits (mW) <sup>2</sup> at separation distance of									
	≤5 mm	10 mm	15 mm	20 mm	25 mm	30 mm	35 mm	40 mm	45 mm	≥50 mm
450	52	70	88	106	123	141	159	177	195	213
835	17	30	42	55	67	80	92	105	117	130
1900	7	10	18	34	60	99	153	225	316	431
2450	4	7	15	30	52	83	123	173	235	309
3500	2	6	16	32	55	86	124	170	225	290
5800	1	6	15	27	41	56	71	85	97	106
Carrier frequency:	$f = 6489 \text{ MHz}$									
Distance:	$d = 5 \text{ mm}$									
Transmitter output power:	$TP = 0.00024 \text{ mW}$									
Limit:	$TP_{limit} = 1.00 \text{ mW}$									

<sup>2</sup> The exemption limit in the table are based on measurements and simulations on half-wave dipole antennas at separation distances of 5 mm to 25 mm from a flat phantom, providing a SAR value of approximately 0.4 W/kg for 1 g of tissue. For low frequencies (300 MHz to 835 MHz), the exemption limits are derived from a linear fit. For high frequencies (1900 MHz and above), the exemption limits are derived from a third order polynomial fit.

### 3 Measurement Uncertainty

The measurement uncertainty in the laboratory is less than or equal to the maximum measurement uncertainty according to CISPR16-4-2: 2011 + A1 + A2 + Cor1 (UCISPR). This normative regulation means that the measured value is also the value to be assessed in relation to the limit value.

For a 95% confidence level. the measurement uncertainties for defined systems are:

Radio Testing			
Test Name	kp	Expanded Uncertainty	Note
Occupied Bandwidth	2.0	±1.14 %	2
RF-Frequency error	1.96	±1 · 10-7	7
RF-Power. conducted carrier	2	±0.079 dB	2
RF-Power uncertainty for given BER	1.96	+0.94 dB / -1.05	7
RF power. conducted. spurious emissions	1.96	+1.4 dB / -1.6 dB	7
RF power. radiated			
25 MHz – 4 GHz	1.96	+3.6 dB / -5.2 dB	8
1 GHz – 18 GHz	1.96	+3.8 dB / -5.6 dB	8
18 GHz – 26.5 GHz	1.96	+3.4 dB / -4.5 dB	8
40 GHz – 170 GHz	1.96	+4.2 dB / -7.1 dB	8
Spectral Power Density. conducted	2.0	±0.53 dB	2
Maximum frequency deviation			
300 Hz – 6 kHz	2	±2.89 %	2
6 kHz – 25 kHz	2	±0.2 dB	2
Maximum frequency deviation for FM	2	±2.89 %	2
Adjacent channel power 25 MHz – 1 GHz	2	±2.31 %	2
Temperature	2	±0.39 K	4
(Relative) Humidity	2	±2.28 %	2
DC- and low frequency AC voltage			
DC voltage	2	±0.01 %	2
AC voltage up to 1 kHz	2	±1.2 %	2
Time	2	±0.6 %	2

Table 5

Radio Interference Emission Testing			
Test Name	kp	Expanded Uncertainty	Note
Conducted Voltage Emission			
9 kHz to 150 kHz (50Ω/50µH AMN)	2	± 3.8 dB	1
150 kHz to 30 MHz (50Ω/50µH AMN)	2	± 3.4 dB	1
100 kHz to 200 MHz (50Ω/5µH AMN)	2	± 3.6 dB	1
Discontinuous Conducted Emission			
9 kHz to 150 kHz (50Ω/50µH AMN)	2	± 3.8 dB	1
150 kHz to 30 MHz (50Ω/50µH AMN)	2	± 3.4 dB	1
Conducted Current Emission			
9 kHz to 200 MHz	2	± 3.5 dB	1
Magnetic Fieldstrength			
9 kHz to 30 MHz (with loop antenna)	2	± 3.9 dB	1
9 kHz to 30 MHz (large-loop antenna 2 m)	2	± 3.5 dB	1
Radiated Emission			
Test distance 1 m (ALSE)			
9 kHz to 150 kHz	2	± 4.6 dB	1
150 kHz to 30 MHz	2	± 4.1 dB	1
30 MHz to 200 MHz	2	± 5.2 dB	1
200 MHz to 2 GHz	2	± 4.4 dB	1
2 GHz to 3 GHz	2	± 4.6 dB	1
Test distance 3 m			
30 MHz to 300 MHz	2	± 4.9 dB	1
300 MHz to 1 GHz	2	± 5.0 dB	1
1 GHz to 6 GHz	2	± 4.6 dB	1
Test distance 10 m			
30 MHz to 300 MHz	2	± 4.9 dB	1
300 MHz to 1 GHz	2	± 4.9 dB	1
Radio Interference Power			
30 MHz to 300 MHz	2	± 3.5 dB	1
Harmonic Current Emissions			4
Voltage Changes. Voltage Fluctuations and Flicker			4

Table 6

Immunity Testing			
Test Name	kp	Expanded Uncertainty	Note
Electrostatic Discharges			4
Radiated RF-Field			
Pre-calibrated field level	2	+32.2 / -24.3 %	5
Dynamic feedback field level	2.05	+21.2 / -17.5 %	3
Electrical Fast Transients (EFT) / Bursts			4
Surges			4
Conducted Disturbances. induced by RF-Fields			
via CDN	2	+15.1 / -13.1 %	6
via EM clamp	2	+42.6 / -29.9 %	6
via current clamp	2	+43.9 / -30.5 %	6
Power Frequency Magnetic Field	2	+20.7 / -17.1 %	2
Pulse Magnetic Field			4
Voltage Dips. Short Interruptions and Voltage Variations			4
Oscillatory Waves			4
Conducted Low Frequency Disturbances			
Voltage setting	2	$\pm 0.9 \%$	2
Frequency setting	2	$\pm 0.1 \%$	2
Electrical Transient Transmission in Road Vehicles			4

**Table 7**

Note 1:

The expanded uncertainty reported according to CISPR 16-4-2:2003-11 is based on a standard uncertainty multiplied by a coverage factor of kp = 2. providing a level of confidence of p = 95.45%

Note 2:

The expanded uncertainty reported according to UKAS Lab 34 (Edition 1. 2002-08) is based on a standard uncertainty multiplied by a coverage factor of kp = 2. providing a level of confidence of p = 95.45%

Note 3:

The expanded uncertainty reported according to UKAS Lab 34 (Edition 1. 2002-08) is based on a standard uncertainty multiplied by a coverage factor of kp = 2.05. providing a level of confidence of p = 95.45%

Note 4:

It has been demonstrated that the used test equipment meets the specified requirements in the standard with at least a 95%confidence.

Note 5:

The expanded uncertainty reported according to IEC 61000-4-3 is based on a standard uncertainty multiplied by a coverage factor of kp = 2. providing a level of confidence of p = 95.45%

Note 6:

The expanded uncertainty reported according to IEC 61000-4-6 is based on a standard uncertainty multiplied by a coverage factor of kp = 2. providing a level of confidence of p = 95.45%

Note 7:

The expanded uncertainty reported according ETSI TR 100 028 V1.4.1 (all parts) to is based on a standard uncertainty multiplied by a coverage factor of kp = 1.96. providing a level of confidence of p = 95.45%

Note 8:

The expanded uncertainty reported according to ETSI TR 102 273 V1.2.1 (all parts) is based on a standard uncertainty multiplied by a coverage factor of kp = 1.96. providing a level of confidence of p = 95.45%