

**RF-EXPOSURE ASSESSMENT REPORT**

FCC 47 CFR Part 2.1091  
Industry Canada RSS-102

**RF-Exposure evaluation of mobile equipment**

**Report Reference No.** .....: G0M-1302-2617-TFC091M-V01

**Testing Laboratory** .....: Eurofins Product Service GmbH

Address .....: Storkower Str. 38c  
15526 Reichenwalde  
Germany

Accreditation .....:



A2LA Accredited Testing Laboratory, Certificate No.: 1983.01  
FCC Filed Test Laboratory, Reg.-No.: 96970  
IC OATS Filing assigned code: 3470A

**Applicant's name** .....: Agilion GmbH

Address .....: Blankenauer Str. 74  
09113 Chemnitz  
GERMANY

**Test specification:**

Standard .....: 47 CFR 1.1310 / 47 CFR 2.1091 / 47 CFR 2.1093  
OET Bulletin 65:1997  
RSS-102, Issue 4:2010  
Safety Code 6:2009

**Equipment under test (EUT):**

Product description WIRELESS THR GATEWAY / WIRELESS THR ANCHOR

Model No. 6021105 / 6021203

Hardware version 1.0

Firmware / Software version 2.0

FCC-ID: SCF6021112 IC: N/A

**Test result** Passed

**Possible test case verdicts:**

- not applicable to test object .....: N/A
- test object does meet the requirement .....: P (Pass)
- test object does not meet the requirement .....: F (Fail)

**Testing:**

Date of receipt of test item .....: 2013-02-21

Date (s) of assessment .....: 2013-04-09

Compiled by .....: Christian Weber

Assessed by (+ signature) .....: Christian Weber  
(Testing Manager)



Approved by (+ signature) .....: Toralf Jahn  
(Test Lab Manager)



Date of issue .....: 2013-04-09

Total number of pages .....: 12

**General remarks:**

**The test results presented in this report relate only to the object tested.**

**The results contained in this report reflect the results for this particular model and serial number. It is the responsibility of the manufacturer to ensure that all production models meet the intent of the requirements detailed within this report.**

This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.

**Additional comments:**

---

## Version History

| Version | Issue Date | Remarks         | Revised by |
|---------|------------|-----------------|------------|
| 01      | 2013-04-09 | Initial Release |            |

---

## **REPORT INDEX**

|          |  |           |
|----------|--|-----------|
| <b>1</b> | <b>EQUIPMENT (TEST ITEM) DESCRIPTION</b> | <b>5</b>  |
| 1.1      | Reference Documents                      | 6         |
| 1.2      | Radiation Sources                        | 7         |
| <b>2</b> | <b>RESULT SUMMARY</b>                    | <b>8</b>  |
| <b>3</b> | <b>RF-EXPOSURE CLASSIFICATIONS</b>       | <b>9</b>  |
| <b>4</b> | <b>ASSESSMENT</b>                        | <b>10</b> |
| 4.1      | MPE Assessment – 47 CFR 2.1091 / RSS-102 | 10        |

## 1 Equipment (Test item) Description

|                                    |  |
|------------------------------------|--|
| <b>Description</b>                 | WIRELESS THR GATEWAY / WIRELESS THR ANCHOR |
| <b>Model</b>                       | 6021105 / 6021203                          |
| <b>Serial number</b>               | None                                       |
| <b>Hardware version</b>            | 1.0  |
| <b>Software / Firmware version</b> | 2.0  |
| <b>FCC-ID</b>                      | SCF6021112                                 |
| <b>IC</b>                          | N/A  |
| <b>Equipment type</b>              | End product                                |

## 1.1 Reference Documents

| Document type                         | Document No.              | Issued by                     | Date       |
|---------------------------------------|---------------------------|-------------------------------|------------|
| FCC 15.247 Module<br>Test Report      | G0M20902-2239-C-1         | Eurofins Product Service GmbH | 2009-03-12 |
| FCC 15.247 End Product<br>Test Report | G0M-1302-2617-TFC247C-V01 | Eurofins Product Service GmbH | 2013-04-09 |

## 1.2 Radiation Sources

| Mode #           | Description                         |                       |
|------------------|-------------------------------------|-----------------------|
| CHIRP 2.4<br>GHz | Frequency range [MHz]               | 2410 – 2474           |
|                  | Channels                            | 1 Chirp Channel       |
|                  | Transmission modes                  | Chirp Spread Spectrum |
|                  | Modulations                         | None                  |
|                  | Maximum radiated power [dBm]        | 19.89 + 6.0 = 25.89   |
|                  | Maximum transmission duty cycle [%] | 100                   |
|                  | Antenna gain [dBi]                  | 6.0                   |
|                  | Antenna diameter [cm]               | 10                    |

## 2 Result Summary

| FCC 47 CFR Part 2.1091, IC RSS-102 |   |        |         |
|------------------------------------|---|--------|---------|
| Product Specific Standard Section  | Requirement                                     | Result | Remarks |
| 47 CFR 2.1091                      | Maximum permissible exposure @ 20cm below limit | PASS   |         |
| RSS-102 2.5.2                      | Maximum permissible exposure @ 20cm below limit | N/A    |         |
| <b>Remarks:</b>                    |   |        |         |

### 3 RF-Exposure Classifications

| Device Types |  |
|--------------|--|
| Fixed        | A fixed device is defined as a device physically secured at one fixed location and cannot be easily re-located.  |
| Mobile       | A mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons. (47 CFR 2.1091) |
| Portable     | A portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user. (47 CFR 2.1093)   |

| Exposure Categories               |  |
|-----------------------------------|--|
| Occupational / Controlled         | Limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure. |
| General population / uncontrolled | Exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.   |

## 4 Assessment

### 4.1 MPE Assessment – 47 CFR 2.1091 / RSS-102

| <b>MPE Assessment acc. to 47 CFR 2.1091 / IC RSS-102</b>      |                               |   | <b>Verdict: PASS</b>              |                         |  |  |
|---|-------------------------------|---|-----------------------------------|-------------------------|--|--|
| Assessment according to reference                             |                               | Reference Method                              |                                   |                         |  |  |
|   |                               | FCC OET Bulletin 65 / RSS-102 & Safety Code 6 |                                   |                         |  |  |
| Device type   |                               | mobile  |                                   |                         |  |  |
| Exposure category   |                               | General public                                |                                   |                         |  |  |
| <b>IC Limits – Occupational / Controlled Exposure</b>         |                               |   |                                   |                         |  |  |
| Frequency range [MHz]   | Electric field strength [V/M] | Magnetic field strength [A/M]                 | Power density [W/m <sup>2</sup> ] | Averaging time [min]    |  |  |
| 0.003 – 1.0   | 600                           | 4.9   | N/A                               | 6                       |  |  |
| 1 – 10  | 600/f                         | 4.9/f   | N/A                               | 6                       |  |  |
| 10 – 30   | 60                            | 4.9/f   | N/A                               | 6                       |  |  |
| 30 – 300  | 60                            | 0.163   | 10.0*                             | 6                       |  |  |
| 300 – 1500  | 3.54·f <sup>0.5</sup>         | 0.0094·f <sup>0.5</sup>                       | f/30                              | 6                       |  |  |
| 1500 - 15000  | 137                           | 0.364   | 50                                | 6                       |  |  |
| 15000 - 150000  | 137                           | 0.364   | 50                                | 616000/f <sup>0.5</sup> |  |  |
| 150000 - 300000   | 0.354·f <sup>0.5</sup>        | 9.4·10 <sup>-4</sup> ·f <sup>0.5</sup>        | 3.33·10 <sup>-4</sup> ·f          | 616000/f <sup>0.5</sup> |  |  |
| <b>IC Limits – General Population / Uncontrolled Exposure</b> |                               |   |                                   |                         |  |  |
| Frequency range [MHz]   | Electric field strength [V/M] | Magnetic field strength [A/M]                 | Power density [W/m <sup>2</sup> ] | Averaging time [min]    |  |  |
| 0.003 – 1.0   | 280                           | 2.19  | N/A                               | 6                       |  |  |
| 1 – 10  | 280/f                         | 2.19/f  | N/A                               | 6                       |  |  |
| 10 – 30   | 28                            | 2.19/f  | N/A                               | 6                       |  |  |
| 30 – 300  | 28                            | 0.073   | 2.0*                              | 6                       |  |  |
| 300 – 1500  | 1.585·f <sup>0.5</sup>        | 0.0042·f <sup>0.5</sup>                       | f/150                             | 6                       |  |  |
| 1500 - 15000  | 61.4                          | 0.163   | 10                                | 6                       |  |  |
| 15000 - 150000  | 61.4                          | 0.163   | 10                                | 616000/f <sup>0.5</sup> |  |  |
| 150000 - 300000   | 0.158·f <sup>0.5</sup>        | 4.21·10 <sup>-4</sup> ·f <sup>0.5</sup>       | 6.67·10 <sup>-5</sup> ·f          | 616000/f <sup>0.5</sup> |  |  |

\* = Power density is applicable at frequencies greater than 100 MHz; f in MHz

| <b>FCC Limits – Occupational / Controlled Exposure</b>         |                               |                               |                                     |                      |
|--|-------------------------------|-------------------------------|-------------------------------------|----------------------|
| Frequency range [MHz]  | Electric field strength [V/M] | Magnetic field strength [A/M] | Power density [mW/cm <sup>2</sup> ] | Averaging time [min] |
| 0.3 – 3.0  | 614                           | 1.63                          | (100)*                              | 6                    |
| 3.0 - 30   | 1842/f                        | 4.89/f                        | (900/f <sup>2</sup> )*              | 6                    |
| 30 - 300   | 61.4                          | 0.163                         | 1.0                                 | 6                    |
| 300 - 1500   | N/A                           | N/A                           | f/300                               | 6                    |
| 1500 - 100000  | N/A                           | N/A                           | 5.0                                 | 6                    |
| <b>FCC Limits – General Population / Uncontrolled Exposure</b> |                               |                               |                                     |                      |
| Frequency range [MHz]  | Electric field strength [V/M] | Magnetic field strength [A/M] | Power density [mW/cm <sup>2</sup> ] | Averaging time [min] |
| 0.3 – 1.34   | 614                           | 1.63                          | (100)*                              | 30                   |
| 1.34 - 30  | 842/f                         | 2.19/f                        | (180/f <sup>2</sup> )*              | 30                   |
| 30 - 300   | 27.5                          | 0.073                         | 0.2                                 | 30                   |
| 300 - 1500   | N/A                           | N/A                           | f/1500                              | 30                   |
| 1500 - 100000  | N/A                           | N/A                           | 1.0                                 | 30                   |

\* = Plane wave equivalent power density; f in MHz

| <b>Assessment Relations</b>  |  |  |  |  |
|--|--|--|--|--|
| $\lambda[m] = \frac{c \left[ \frac{m}{s} \right]}{f[Hz]} ; R_{FF}[m] \geq \frac{2 \cdot D[m]^2}{\lambda[m]}$   |  |  |  |  |
| $S[mW/cm^2] = \frac{P_{E.I.R.P.}[mW]}{4\pi R[cm]^2} ; R[cm] = \sqrt{\frac{P_{E.I.R.P.}[mW]}{4\pi S[mW/cm^2]}}$ |  |  |  |  |
| $P_R[mW] = P_C[mW] \cdot G ; P_R[dBm] = P_C[dBm] + G[dBi]$   |  |  |  |  |
| $DCC [dB] = 10 \cdot \log_{10} \left( \frac{DC[\%]}{100} \right)$  |  |  |  |  |

| <b>Assessment procedure</b>   |  |  |  |  |
|---|--|--|--|--|
| <p>For each radio and frequency band the worst case transmission mode with the highest peak conducted or radiated power is evaluated at the frequency that results in the most restrictive rf-exposure limit. From the peak power values, antenna gains and duty cycles taken from the reference documents, the source average radiated power values are calculated. From the average radiated power the power densities at antenna far-field distance, at 20cm separation distance from the radiation source is calculated. Compliance with the RF-Exposure limit is determined at 20cm separation distance.</p> |  |  |  |  |

| Assessment results – CHIRP 2.4 GHz                                  |                          |                        |
|---|--------------------------|------------------------|
| Transmission mode   |                          |                        |
| Operating mode frequency range [MHz]                                | 2410 – 2474              |                        |
| Assessment frequency (f) [MHz]                                      | 2441.75                  |                        |
| Transmission duty cycle (DC) [%]                                    | 100                      |                        |
| Peak conducted power (P <sub>c</sub> ) [dBm]                        | 19.89                    |                        |
| Peak radiated power (P <sub>R</sub> ) [dBm e.i.r.p.]                | 25.89                    |                        |
| Peak Antenna gain (G) [dBi]   | 6.0                      |                        |
| Maximum Antenna Diameter D [cm]                                     | 10.0                     |                        |
| Antenna far-field distance  |                          |                        |
| Transmission frequency wavelength (λ)                               | 0.123 m                  | 12.29 cm               |
| Antenna far-field distance (R <sub>FF</sub> )                       | 0.163 m                  | 16.28 cm               |
| Power evaluation  |                          |                        |
| Peak conducted power (P <sub>c</sub> )                              | 97.50 mW                 | 19.89 dBm              |
| Peak Antenna Gain (G)   | 3.98                     | 6.00 dBi               |
| Calculated peak radiated power (P <sub>R-Calc</sub> )               | 388.15 mW                | 25.89 dBm              |
| Measured peak radiated power (P <sub>R</sub> )                      | 388.15 mW                | 25.89 dBm              |
| Source average Power  |                          |                        |
| Maximum transmission duty cycle (DC)                                | 100.0 %                  |                        |
| Duty cycle correction (DCC)   | 1.00                     | 0.00 dB                |
| Measured peak radiated power (P <sub>R</sub> )                      | 388.15 mW                | 25.89 dBm              |
| Averaged peak radiated power (P <sub>RAVG</sub> )                   | 388.15 mW                | 25.89 dBm              |
| Power density   |                          |                        |
| Compliance power density limit                                      | 1.000 mW/cm <sup>2</sup> | 10.00 W/m <sup>2</sup> |
| Power density @ Antenna far-field distance                          | 0.117 mW/cm <sup>2</sup> | 1.166 W/m <sup>2</sup> |
| Power density @ 20cm  | 0.077 mW/cm <sup>2</sup> | 0.772 W/m <sup>2</sup> |
| Distance for compliance power density                               | 0.056 m                  | 5.56 cm                |
| Verdict   |                          |                        |
| The power density of the EUT at 20cm is below the FCC/IC MPE limit! |                          |                        |
| Comments:   |                          |                        |