

TEST REPORT
No.: 17-1-0264601T06

According to:
FCC Regulations
Part 1.1310
Part 2.1091

for

Agilion GmbH

WIRELESS MESH GATEWAY PULSE | PHASE

FCC: SCF6032502

Laboratory Accreditation and Listings						
 Deutsche Akkreditierungsstelle D-PL-12047-01-01	 FEDERAL COMMUNICATIONS COMMISSION U.S.A. MRA US-EU 0003	 Industry Canada Reg. No.: 3462D-2 Reg. No.: 3462D-3	 Voluntary Controls for Electromagnetic Emissions Reg. No.: R-2666 C-2914, T-1967, G-301			
 AUTHORIZED RF LABORATORY	 ctia Authorized™ Test Lab Lab Code: 20011130-00					
accredited according to DIN EN ISO/IEC 17025						
CETECOM GmbH Laboratory Radio Communications & Electromagnetic Compatibility Im Teebruch 116 • 45219 Essen • Germany Registered in Essen, Germany, Reg. No.: HRB Essen 8984 Tel.: + 49 (0) 20 54 / 95 19-954 • Fax: + 49 (0) 20 54 / 95 19-964 E-mail: info@cetecom.com • Internet: www.cetecom.com						

Table of contents

1. SUMMARY OF TEST RESULTS.....	3
1.1. Summary of tests results	3
1.2. Attestation:.....	3
2. ADMINISTRATIVE DATA	4
2.1. Identification of the testing laboratory.....	4
2.2. Test location	4
2.3. Organizational items	4
2.4. Applicant's details	4
2.5. Manufacturer's details	4
3. EQUIPMENT UNDER TEST (EUT).....	5
3.1. Summary of product description.....	5
3.2. EUT Technologies	5
3.3. Antenna Information.....	5
3.4. EUT: Type, S/N etc. and short descriptions used in this test report	6
3.5. Auxiliary Equipment (AE): Type, S/N etc. and short descriptions.....	6
3.6. EUT set-ups	6
3.7. EUT operating modes	6
4. MEASUREMENTS	7
4.1. Radio Frequency Exposure Evaluation §2.1091	7
4.1.1. Test location and equipment (for reference numbers please see chapter 'List of test equipment').....	7
4.3. MPE Calculation method.....	9
4.4. Evaluation Method.....	9
4.5. Results for fixed and mobile.....	10
4.6. Conclusion	12
4.7. Measurement uncertainties	12
5. ABBREVIATIONS USED IN THIS REPORT	13
6. ACCREDITATION DETAILS OF CETECOM'S LABORATORIES AND TEST SITES	13
7. PHOTOGRAPHS OF THE EUT'S	14
8. VERSIONS OF TEST REPORTS (CHANGE HISTORY)	15

Table of annex

Total pages

Annex 1: Separate document applicant's document "2018-05-17_MPE"

01

The listed attachments are an integral part of this report.

1. Summary of test results

The test results apply exclusively to the test samples as presented in this Report. The CETECOM GmbH does not assume responsibility for any conclusions and generalizations taken in conjunction with other specimens or samples of the type of the item presented to tests.

The presented Equipment Under Test (in this report, hereinafter referred as EUT) integrates a BT 2.4 GHz RF Transceiver. Other implemented wireless technologies were not considered within this test report.

Following tests have been performed to show compliance with applicable FCC Part 2.1091 and FCC Part 1.1310 of the FCC CFR 47 Rules.

1.1. Summary of tests results

RF-Exposure Evaluation (separation distance user to RF-radiating element greater 20cm)						
Test cases	Port	References & Limits		EUT set-up	EUT op. mode	Result
		FCC Standard	Test Limit			
Radio frequency radiation exposure Requirements	Cabinet	§1.1310 §2.1091 §2.1093	RF-Field Strength Limits: FCC: "general population/uncontrolled" environment	1	1-2	Pass


Remark: Calculations based on Datasheet delivered by applicant

1.2. Attestation:

I declare that all measurements were performed by me or under my supervision and that all measurements have been performed and are correct to my best knowledge and belief to Industry Canada standards. All requirements as shown in above table are met in accordance with enumerated standards.



Dipl.-Ing. Rachid Acharkaoui
Responsible for test section



M. Schäfers
Responsible for test report

2. Administrative Data

2.1. Identification of the testing laboratory

Company name:	CETECOM GmbH
Address:	Im Teelbruch 116 45219 Essen - Kettwig Germany
Responsible for testing laboratory:	Dipl.-Ing. Rachid Acharkaoui
Deputy:	Dipl.-Ing. Niels Jeß

2.2. Test location

2.2.1. Test laboratory “CTC”

Company name:	see chapter 2.1. Identification of the testing laboratory
---------------	---

2.3. Organizational items

Responsible for test report:	M. Schäfers
Receipt of EUT:	--
Date(s) of test:	--
Date of report:	2018-03-13

2.4. Applicant's details

Applicant's name:	Agilion GmbH
Address:	Blankenauer Str. 74 09113 Chemnitz Germany
Contact person:	Sven Sieber

2.5. Manufacturer's details

Manufacturer's name:	please see applicant's details
Address:	please see applicant's details

3. Equipment under test (EUT)

3.1. Summary of product description

FCC ID:	SCF6032502		
Product name	WIRELESS MESH GATEWAY PULSE PHASE		
Exposure category	<input checked="" type="checkbox"/> General population/uncontrolled environment <input type="checkbox"/> Occupational exposure/controlled environment		
Output power	<input type="checkbox"/> Conducted <input type="checkbox"/> ERP <input checked="" type="checkbox"/> EIRP <input type="checkbox"/> Peak <input checked="" type="checkbox"/> Source-based time-averaging		
Antenna gain	details refer to: "2018-05-17_MPE"		
Technology	<input type="checkbox"/> MIMO <input checked="" type="checkbox"/> non-MIMO		
	<input type="checkbox"/> 2T2R <input type="checkbox"/> 3T3R <input type="checkbox"/> 4T4R <input checked="" type="checkbox"/> 1T1R <input type="checkbox"/> 1T2R <input type="checkbox"/> 2T1R		
Evaluation type	<input checked="" type="checkbox"/> Standalone <input type="checkbox"/> Simultaneous transmission		
Evaluation distance	<input checked="" type="checkbox"/> 20 cm <input type="checkbox"/> XXX cm		declares by manufacturer
EUT type	<input checked="" type="checkbox"/> Production Unit <input type="checkbox"/> Pre-Production Unit <input type="checkbox"/> Engineering Unit		
Device type	<input type="checkbox"/> Mobile device <input checked="" type="checkbox"/> Fixed device		
Refer rules	<input checked="" type="checkbox"/> CFR 47 FCC Part 2.1091 <input checked="" type="checkbox"/> CFR 47 FCC Part 1.1310 <input checked="" type="checkbox"/> KDB 447497 D01v06 October 23, 2015 <input checked="" type="checkbox"/> KDB 865664 D01v01r02 October 23, 2015		

3.2. EUT Technologies

Wireless Technologies	Frequency bands	Operation mode
<input checked="" type="checkbox"/> ZigBee	<input checked="" type="checkbox"/> 2.4GHz	normal operation mode
<input checked="" type="checkbox"/> UWB	<input checked="" type="checkbox"/> 4GHz <input checked="" type="checkbox"/> 6.4GHz	normal operation mode

3.3. Antenna Information

Wireless Technologies	Frequency bands	Antenna type	Maximum antenna gain	
<input checked="" type="checkbox"/> ZigBee	<input checked="" type="checkbox"/> 2.4GHz	<input type="checkbox"/> PIFA <input checked="" type="checkbox"/> PCB	<input checked="" type="checkbox"/> Antenna 0	2 dBi gain max
<input checked="" type="checkbox"/> UWB	<input checked="" type="checkbox"/> 4GHz <input checked="" type="checkbox"/> 6.4GHz	<input type="checkbox"/> PIFA <input checked="" type="checkbox"/> PCB	<input checked="" type="checkbox"/> Antenna 1	2 dBi gain max

3.4. EUT: Type, S/N etc. and short descriptions used in this test report

Short description*)	EUT	Type	S/N serial number	HW hardware status	SW software status
EUT A	WIRELESS MESH GATEWAY PULSE PHASE	6032502	A33787	0583	2.0.8

*) EUT short description is used to simplify the identification of the EUT in this test report.

3.5. Auxiliary Equipment (AE): Type, S/N etc. and short descriptions

AE short description *)	Auxiliary Equipment	Type	S/N serial number	HW hardware status	SW software status
AE 1	--	--	--	--	--

*) AE short description is used to simplify the identification of the auxiliary equipment in this test report.

3.6. EUT set-ups

EUT set-up no.*)	Combination of EUT and AE	Remarks
set. 1	EUT A	--

*) EUT set-up no. is used to simplify the identification of the EUT set-up in this test report.

3.7. EUT operating modes

EUT operating mode no.*)	Description of operating modes	Additional information
op. 1	ZigBee	Only theoretically calculation
op. 2	UWB	Only theoretically calculation

*) EUT operating mode no. is used to simplify the test report.

4. Measurements

4.1. Radio Frequency Exposure Evaluation §2.1091

4.1.1. Test location and equipment (for reference numbers please see chapter 'List of test equipment')

test location	<input checked="" type="checkbox"/> CETECOM Essen (Chapter. 2.2.1)	<input type="checkbox"/> Please see Chapter. 2.2.2	<input type="checkbox"/> Please see Chapter. 2.2.3
For Evaluation instruments are not needed. Results are determined by calculation based on applicants delivered Tune-Up procedure.			

4.1.2. Requirements

FCC: §1.1310	<i>The criteria used for the evaluation of human exposure to radio frequency radiation is table 1 according FCC §1.1310 and table chapter 4.2 of RSS-102 standard and it is subject for evaluation of the RF exposure prior to equipment authorization. As the mobile equipment is authorized under Part 22 (Subpart H) and Part 24 of the FCC Rules, it is subject for evaluation of the RF exposure prior to equipment authorization.</i>
FCC § 2.1091	<i>Further information on evaluating compliance with these limits can be found in the FCC's OST/OET Bulletin Number 65, "Evaluating Compliance with FCC-Specified Guidelines for Human Exposure to Radiofrequency Radiation." For purposes of these requirements mobile devices are defined by the FCC as transmitters designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between radiating structures and the body of the user or nearby persons. These devices are normally evaluated for exposure potential with relation to the MPE limits given in Table 1 of Appendix A.</i>

4.1.2.1. Valid for FCC

Table 1: LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range [MHz]	Electric field strength [V/m]	Magnetic field strength [A/m]	Power density [mW/cm ²]	Averaging time [minutes]
30 - 300	61.4	0.163	1.0	6
300 - 1500	-		f/300	6
1500 - 100,000	-		5	6
(B) Limits for General Population / Uncontrolled Exposure				
0.3 - 1.34	614	1.63	*(100)	30
1.34 - 30	824/f	2.19/f	*(180/f ²)	30
30 - 300	27.5	0.073	0.2	30
300 - 1500	-	-	f/1500	30
1500 - 100,0	-	-	1.0	30

f=frequency in MHz

*Plane-wave equivalent power density

NOTE1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure. These limits apply to amateur station licensees and members of their immediate household as discussed in the text.

NOTE2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure. As discussed in the text, these limits apply to neighbours living near amateur radio stations.

4.1.3 General Limits:

FCC: §1.1307	<i>Cellular Radiotelephone Service (subpart H of part 22)</i> Non-building-mounted antennas: height above ground level to lowest point of antenna < 10 m and total power of all channels > 1000 W ERP (1640 W EIRP)
FCC §1.1307	<i>Personal Communications Services (part 24)</i> Broadband PCS (subpart E): non-building-mounted antennas: height above ground level to lowest point of antenna < 10 m and total power of all channels > 2000 W ERP (3280 W EIRP)
FCC §1.1310	<i>LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)</i> Table 1(B) Limits for General Population/Uncontrolled Exposure 300–1500 MHz: $f/1500$ mW/cm ² 1500–100,000 MHz: 1.0 mW/cm ²
FCC §2.1091	<i>Subject to routine evaluation is required when the device operate at frequencies of 1.5 GHz or below and their effective radiated power (ERP) is 1.5 watts or more, or if they operate at frequencies above 1.5 GHz and their ERP is 3 watts or more.</i>
FCC §24.232	(a) <i>Base stations are limited to 1640 watts peak equivalent isotropically radiated power (e.i.r.p.) with an antenna height up to 300 meters HAAT.</i> b) <i>Mobile/portable stations are limited to 2 watts e.i.r.p. peak power, ...</i>
FCC §22.913	(a) <i>Maximum ERP. The effective radiated power (ERP) of base transmitters and cellular repeaters must not exceed 500 Watts. The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts.</i>
FCC §27.50 (C)(10)	(10) <i>Portable stations (hand-held devices) are limited to 3 watts ERP; and</i>
FCC §27.50(d)	(4) <i>Fixed, mobile, and portable (hand-held) stations operating in the 1710-1755 MHz band are limited to 1 watt EIRP.</i>
KDBs	No. 447498 D01 v06

4.3. MPE Calculation method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{EIRP}{4\pi R^2} = \frac{P * G}{4\pi R^2}$$

$$G_{NUMERIC} = \frac{S * 4\pi R^2}{P}$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the centre of radiation of the antenna

4.4. Evaluation Method

4.4.1. Standalone

Valid for ZigBee Mode:

- The peak power was checked on 3 frequencies (lowest/middle/highest) within the ZigBee band and the results compared to applicant's declared power values (datasheet).
- No duty-cycle correction factor is applicable

Valid for UWB Mode:

- The peak power was checked on 3 frequencies (lowest/middle/highest) within the UWB bands and the results compared to applicant's declared power values (datasheet).
- No duty-cycle correction factor is applicable

Please find in the following tables the calculations based on applicants datasheet for the power values.

4.5. Results for fixed and mobile

4.5.1. Results for FCC Standard

4.5.1.1. MPE results for ZigBee 2.4GHz

Operation Mode	Frequency on channel (MHz)	Declared maximum conducted output power (dBm)	Max. positive tolerance according manufacturer (dB)	Antenna Gain (dBi)	Declared maximum EIRP (Measured+Tune-up) (dBm)	Duty cycle %	Declared Maximum conducted output power (W)	Equivalent conducted output power (output power x duty cycle) (mW)	MPE Limit accord. Table 1 (mW/cm^2)	MPE-Value (mW/cm^2)	Margin to Limit:	Fraction for Co-Location calculations	Max. Fraction-Value within Frequency-Band
ZigBee 2.4GHz	2407,0	9,0	2,0	2,0	13,0	100%	0,0200	20,0	1,0000	0,0040	0,9960	0,003969	0,0039694
	2445,0	9,0	2,0	2,0	13,0		0,0200	20,0	1,0000	0,0040	0,9960	0,003969	
	2483,0	9,0	2,0	2,0	13,0		0,0200	20,0	1,0000	0,0040	0,9960	0,003969	

Maximum calculated MPE value:		
Lowest MPE-Limit:	1,0000	[mW/cm^2]
Highest MPE value:	0,0040	[mW/cm^2]
Lowest Margin to limit:	0,9960	[mW/cm^2]

4.5.1.2. MPE results for UWB 4GHz and 6.4GHz

Operation Mode	Frequency on channel (MHz)	Declared maximum conducted output power (dBm)	Max. positive tolerance according manufacturer (dB)	Antenna Gain (dBi)	Declared maximum EIRP (Measured+Tune-up) (dBm)	Duty cycle %	Declared Maximum conducted output power (W)	Equivalent conducted output power (output power x duty cycle) (mW)	MPE Limit accord. Table 1 (mW/cm^2)	MPE-Value (mW/cm^2)	Margin to Limit:	Fraction for Co-Location calculations	Max. Fraction-Value within Frequency-Band
UWB 4GHz	3774,0	-14,31	2,0	2,0	-10,3	100%	0,0001	0,1	1,0000	0,00001852	1,0000	0,000019	0,0000185
	3993,6	-14,31	2,0	2,0	-10,3		0,0001	0,1	1,0000	0,00001852	1,0000	0,000019	
	4243,2	-14,31	2,0	2,0	-10,3		0,0001	0,1	1,0000	0,00001852	1,0000	0,000019	
UWB 6.4GHz	6240,0	-14,31	2,0	2,0	-10,3	100%	0,0001	0,1	1,0000	0,00001852	1,0000	0,000019	0,0000185
	6489,6	-14,31	2,0	2,0	-10,3		0,0001	0,1	1,0000	0,00001852	1,0000	0,000019	
	6739,2	-14,31	2,0	2,0	-10,3		0,0001	0,1	1,0000	0,00001852	1,0000	0,000019	

Maximum calculated MPE value:		
Lowest MPE-Limit:	1,0000	[mW/cm^2]
Highest MPE value:	0,00001852	[mW/cm^2]
Lowest Margin to limit:	0,99998148	[mW/cm^2]

4.5.1.3. Co-location assessment (scenario)

Following table shows calculations with ZigBee and UWB technology active in the device.

Special limitations such as interactions between the transmitting RF-antennas due small physical distance between them, are not sufficient modeled by the far field formula for power density. For such cases a non-linear program electromagnetic software or MPE measurements should be performed.

Ratio of MPE- Value/Limit	ZigBee 2.4GHz	UWB 4GHz	UWB 6.4GHz
	0,003969448	1,85238E-05	1,85238E-05
ZigBee 2.4GHz	0,003969448	--	0,003987972
UWB 4GHz	1,85238E-05	0,003987972	--
UWB 6.4GHz	1,85238E-05	0,003987972	3,70476E-05
Maximum-Value		0,003987972	

4.6. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

4.7. Measurement uncertainties

The reported uncertainties are calculated based on the standard uncertainty multiplied with the appropriate coverage factor **k**, such that a confidence level of approximately 95% is achieved.

For uncertainty determination, each component used in the concrete measurement set-up was taken in account and it's contribution to the overall uncertainty according it's statistical distribution calculated.

Following table shows expectable uncertainties for each measurement type performed.

RF-Measurement	Reference	Frequency range	Calculated uncertainty based on a confidence level of 95%						Remarks	
Conducted emissions (U CISPR)	CISPR 16-2-1	9 kHz - 150 kHz 150 kHz - 30 MHz	4.0 dB 3.6 dB						-	
Radiated emissions Enclosure	CISPR 16-2-3	30 MHz - 1 GHz 1 GHz - 18 GHz	4.2 dB 5.1 dB						E-Field	
Disturbance power	CISPR 16-2-2	30 MHz - 300 MHz	-						-	
Power Output radiated	-	30 MHz - 4 GHz	3.17 dB						Substitution method	
Power Output conducted	-	Set-up No.	Cel-C1	Cel-C2	BT1	W1	W2			
		9 kHz - 12.75 GHz	N/A	0.60	--	--	--			
		12.75 - 26.5GHz	N/A	0.82	--	--	--			
Conducted emissions on RF-port	-	9 kHz - 2.8 GHz	0.70	N/A	--	--	--		N/A - not applicable	
		2.8 GHz - 12.75GHz	1.48	N/A	--	--	--			
		12.75 GHz - 18GHz	1.81	N/A	--	--	--			
		18 GHz - 26.5GHz	1.83	N/A	--	--	--			
Occupied bandwidth	-	9 kHz - 4 GHz	0.1272 ppm (Delta Marker)						Frequency error	
			1.0 dB						Power	
Emission bandwidth	-	9 kHz - 4 GHz	0.1272 ppm (Delta Marker)						Frequency error	
			See above: 0.70 dB						Power	
Frequency stability	-	9 kHz - 20 GHz	0.0636 ppm						-	
Radiated emissions Enclosure	-	150 kHz - 30 MHz	5.0 dB						Magnetic field E-field Substitution	
		30 MHz - 1 GHz	4.2 dB							
		1 GHz - 20 GHz	3.17 dB							

Table: measurement uncertainties, valid for conducted/radiated measurements

5. Abbreviations used in this report

The abbreviations	
ANSI	American National Standards Institute
AV , AVG, CAV	Average detector
EIRP	Equivalent isotropically radiated power, determined within a separate measurement
EGPRS	Enhanced General Packet Radio Service
EUT	Equipment Under Test
FCC	Federal Communications Commission, USA
IC	Industry Canada
n.a.	not applicable
Op-Mode	Operating mode of the equipment
PK	Peak
RBW	resolution bandwidth
RF	Radio frequency
RSS	Radio Standards Specification, Dokuments from Industry Canada
Rx	Receiver
TCH	Traffic channel
Tx	Transmitter
QP	Quasi peak detector
VBW	Video bandwidth
ERP	Effective radiated power

6. Accreditation details of CETECOM's laboratories and test sites

Ref.-No.	Accreditation Certificate	Valid for laboratory area or test site	Accreditation Body
-	D-PL-12047-01-01	All laboratories and test sites of CETECOM GmbH, Essen	DAkkS, Deutsche Akkreditierungsstelle GmbH
337 487 558 348 348	MRA US-EU 0003	Radiated Measurements 30 MHz to 1 GHz, 3 m / 10 m (OATS) Radiated Measurements 30 MHz to 1 GHz, 3 m (SAR) Radiated Measurements above 1 GHz, 3 m (FAR) Mains Ports Conducted Interference Measurements Telecommunication Ports Conducted Interference Measurem.	FCC, Federal Communications Commission Laboratory Division, USA
337 487 550 558	3462D-1 3462D-2 3462D-2 3462D-3	Radiated Measurements 30 MHz to 1 GHz, 3 m / 10 m (OATS) Radiated Measurements 30 MHz to 1 GHz, 3 m (SAR) Radiated Measurements 1 GHz to 6 GHz, 3 m (SAR) Radiated Measurements above 1 GHz, 3 m (FAR)	IC, Industry Canada Certification and Engineering Bureau
487 550 348 348	R-2666 G-301 C-2914 T-1967	Radiated Measurements 30 MHz to 1 GHz, 3 m (SAR) Radiated Measurements 1 GHz to 6 GHz, 3 m (SAR) Mains Ports Conducted Interference Measurements Telecommunication Ports Conducted Interference Measurem.	VCCI, Voluntary Control Council for Interference by Information Technology Equipment, Japan

OATS = Open Area Test Site, SAR = Semi Anechoic Room, FAR = Fully Anechoic Room

7. Photographs of the EUT's

Photograph 1: EUT A Top side



Photograph 2: EUT A Bottom side



Photograph 2: EUT A Front side



8. Versions of test reports (change history)

Version	Applied changes	Date of release
--	Initial release	2018-02-20