



Product Integrity Laboratory

5151-47th Street, NE
Calgary, Alberta T3J 3R2
Tel: (403) 568-6605
Fax : (403) 568-6970

Certification Test Report

**CFR 47 FCC Part 15, Subpart C Section 15.225
Industry Canada RSS 210, Issue 6**

**Wireless Dynamics Inc.
FCC ID # SHFSDID1020
IC ID # 5998A-SDID1020**

**Project Code CG-225
(Report CG-225-1)**

Revision: 0

November 28, 2005

Prepared for: Wireless Dynamics Inc.

Author: Glen Moore/ Kuganesan Pararajasingam

Approved by: Nick Kobrosly
Director of Operations

Confidentiality Statement: This report and the information contained herein represent the results of testing articles/products identified and selected by the client. The tests were performed to specifications and/or procedures approved by the client. National Technical Systems ("NTS") makes no representations expressed or implied that such testing fully demonstrates efficiency, performance, reliability, or any other characteristic of the articles being tested, or similar products. This report should not be relied upon as an endorsement or certification by NTS of the equipment tested, nor does it represent any statement whatsoever as to its merchantability or fitness of the test article or similar products for a particular purpose. This document shall not be reproduced except in full without written approval from National Technical Systems ("NTS") and the customer.

Report Summary

NTS Canada

Product Integrity Laboratory
5151-47th Street, N.E. Calgary Alberta T3J 3R2

Accreditation Numbers: FCC 101386
IC 46405-3978 File # IC3978-2
Standards Council of Canada Accredited Laboratory No. 440

Performed For: Wireless Dynamics Inc.
220, 3636-23rd Street NE
Calgary, T2E8Z5
Canada

Customer Representative: Carlos Aguirre Charo
RF Engineer

EUT Description:

EUT Description	Manufacturer	Model	Revision	Serial Number
13.56 MHz SDID Card	Wireless Dynamics Inc.	SDID1020	A	24, 29

The test results contained in this report refer exclusively to the product(s) presented for testing. The test results do not cover models or products not referred herein. This test report should not be published or duplicated in whole or part without permission from the testing body and the customer.

NTS Product Integrity Laboratory, 5151-47th Street N.E. Tel: 403-568-6605, Fax: 403-568-6970

Test Summary

Appendix	Test/Requirement Description	Deviations* from:			Pass / Fail	Applicable Rule Parts
		Base Standard	Test Basis	NTS Procedure		
A	Radiated E-Field Emissions 30 MHz – 1 GHz	No	No	No	PASS	FCC 15.209, RSS 210 A2.6
B	Conducted Voltage Emissions 150 kHz – 30 MHz AC Power Leads	No	No	No	PASS	15.207, RSS 210
C	Radiated H-Field Emissions 9 kHz – 30 MHz	No	No	No	PASS	FCC 15.209 , 15.225, RSS 210 Issue 6 A2.6
D	Frequency Stability	No	No	No	PASS	FCC 15.225, RSS 210 A2.6

Test Result: The product presented for testing complied with test requirements as shown above.

Prepared By: _____
Kuganesan Pararajasingam
EMC Engineer

Checked By: _____
Glen Moore
EMC Manager

The test results contained in this report refer exclusively to the product(s) presented for testing. The test results do not cover models or products not referred herein. This test report should not be published or duplicated in whole or part without permission from the testing body and the customer.

NTS Product Integrity Laboratory, 5151-47th Street N.E. Tel: 403-568-6605, Fax: 403-568-6970

Table of Contents

REPORT SUMMARY	2
TEST SUMMARY	3
REGISTER OF REVISIONS	5
1.0 INTRODUCTION	6
1.1 PURPOSE	6
2.0 EUT DESCRIPTION	6
2.1 CONFIGURATION	6
2.2 MODE OF OPERATION	6
3.0 SUPPORT EQUIPMENT	6
3.1 CONFIGURATION	6
3.2 CABLES	7
APPENDICES	8
APPENDIX A: RADIATED EMISSIONS 30 MHZ – 1 GHZ	9
APPENDIX B: CONDUCTED EMISSIONS 150 KHZ – 30 MHZ	12
APPENDIX C: RADIATED H-FIELD EMISSIONS 9 KHZ - 30 MHZ	16
APPENDIX D: FREQUENCY STABILITY	23
APPENDIX E: TEST EQUIPMENTS	25
END OF DOCUMENT	28

The test results contained in this report refer exclusively to the product(s) presented for testing. The test results do not cover models or products not referred herein. This test report should not be published or duplicated in whole or part without permission from the testing body and the customer.

NTS Product Integrity Laboratory, 5151-47th Street N.E. Tel: 403-568-6605, Fax: 403-568-6970

REGISTER OF REVISIONS

Revision	Date	Description of Revisions
0	November 23, 2005	Draft release for review
1	November 28, 2005	Release to TCB following internal review

The test results contained in this report refer exclusively to the product(s) presented for testing. The test results do not cover models or products not referred herein. This test report should not be published or duplicated in whole or part without permission from the testing body and the customer.

NTS Product Integrity Laboratory, 5151-47th Street N.E. Tel: 403-568-6605, Fax: 403-568-6970

1.0 INTRODUCTION

1.1 PURPOSE

The purpose of this document is to describe the tests applied by NTS Canada to demonstrate compliance of the SDID1020 from Wireless Dynamics Inc. to FCC Part 15 Subpart C section 15.225 for Intentional Radiator and the equivalent sections of Industry Canada's RSS 210 Issue 5

2.0 EUT DESCRIPTION

2.1 CONFIGURATION

Description of EUT

	Name	Model	Revision	Serial Number
EUT	SDID Card	SDID1020	N/A	24/29
Classification	Low Power Transmitter			
Size (m)	NA			
Weight	NA			
Power	3.1 VDC			
Description	13.56 MHz RFID Reader			

2.2 MODE OF OPERATION

The SDID1020 was tested while in a Reader/Writer mode with worst case results reported. For Radiated emissions the EUT was checked in three orthogonal planes with worst case results reported. The EUT was also check all available data rates for worst case. For testing purposes the SDID card was plugged into an extender board to present a worst case emissions signature (no shielding from host system).


3.0 SUPPORT EQUIPMENT

3.1 CONFIGURATION

All support equipment information was supplied by the client and was verified by NTS.

The test results contained in this report refer exclusively to the product(s) presented for testing. The test results do not cover models or products not referred herein. This test report should not be published or duplicated in whole or part without permission from the testing body and the customer.

NTS Product Integrity Laboratory, 5151-47th Street N.E. Tel: 403-568-6605, Fax: 403-568-6970



Note : To present the worst case test configuration an extender board (passive) was used to expose the SDID1020 card, so that the emission level would not be dependent on the shielding of this device.

PDA

Position	Qty	Model #	P/N	Serial Number
10m Support Room	1	Zire72 Palm1	NA	00V9A7C456RN

PalmOne AC Adaptor

Position	Qty	Description	P/N	Serial Number
10m Support Room	1	R3W005-500	163-5877B-US	NA

Adaptor Board

Position	Qty	Description	P/N	Serial Number
10m Support Room	1	SD Extend 300	NA	F100061RevA

3.2 CABLES

Support Cable List

Quantity	Model	Routing		Description	Cable Length (m)
		From	To		
1	Power	PalmOne AC Adaptor	PDA	Unshielded	0.9
1	Power	AC Mains	PalmOne AC Adaptor	Unshielded, Permanent connection to power supply	1.8

The test results contained in this report refer exclusively to the product(s) presented for testing. The test results do not cover models or products not referred herein. This test report should not be published or duplicated in whole or part without permission from the testing body and the customer.

NTS Product Integrity Laboratory, 5151-47th Street N.E. Tel: 403-568-6605, Fax: 403-568-6970

APPENDICES

The test results contained in this report refer exclusively to the product(s) presented for testing. The test results do not cover models or products not referred herein. This test report should not be published or duplicated in whole or part without permission from the testing body and the customer.

NTS Product Integrity Laboratory, 5151-47th Street N.E. Tel: 403-568-6605, Fax: 403-568-6970

APPENDIX A: RADIATED EMISSIONS 30 MHZ – 1 GHZ

A.1. Base Standard & Test Basis

Base Standard	CFR Title 47 – Telecommunications, Chapter I - FCC Part 15.209 – Radio Frequency Devices
Test Basis	ANSI C63.4 - 2003 Methods of Measurement of Radio Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
Test Method	NTS Radiated Emissions Test Method E001R7

A.2. Specifications

Frequency	FCC Part 15 10-m Limit (Quasi-Peak)
MHz	dBμV/m
30 - 88	29.54
88 - 216	33.06
216 - 960	35.56
960 - 1000	43.52

Notes: Limit extrapolated from 3m using 10m Limit = 3m Limit – 20 * log₁₀(10/3)

A.3. Measurement Uncertainty

Radiated Emissions 30 MHz – 1 GHz	Measurement Uncertainty	Expanded Uncertainty (K=2)
(dB)	+2.32/-2.36	+4.65/-4.72

A.4. Deviations

Deviation Number	Time & Date	Description and Justification of Deviation	Deviation Reference			Approval
			Base Standard	Test Basis	NTS Procedure	
none						

A.5. Test Method

The EUT was placed on a non-conductive table 0.8 meters above the ground plane. The table was centered on a motorized turntable. The emission levels were maximized by rotating the turntable through 360 degrees, a measurement antenna was positioned at a distance of 10meters as measured from the closest point of the EUT, and scanned from 1-4 meters.

A spectrum analyzer with peak detection was used to find the maximum field strength during the scans. The EUT was tested in 3 orthogonal planes, with the worst case results being reported.

The test results contained in this report refer exclusively to the product(s) presented for testing. The test results do not cover models or products not referred herein. This test report should not be published or duplicated in whole or part without permission from the testing body and the customer.

NTS Product Integrity Laboratory, 5151-47th Street N.E. Tel: 403-568-6605, Fax: 403-568-6970

Test Results


Compliant. The worst case emission level at 10m was 25.11dB μ V/m at 81.38MHz with a margin of 4.43dB.

A.6. Sample Calculation

Emission Level = Measured Level + Correction Factors

Margin = Limit – Emission Level

A.7. Test Data

 Product Integrity Laboratory V2.5		Project Number: CG-225 Model: SDiD1020 (Wireless Dynamics Inc.) Comments: Conf08:E- 120VAC, Zire72 (PDA), PDA on Vertical Upright position, SDiD1020-24, l code 100% ASK fast mode, Power cord draped to the floor routed over to receptacle				Tester: Deniz Test ID: RE02c-10m-225								
Standard		FCC15_B		Measurement Distance		10		meters						
Antenna		CL		Frequency	AF	CL+LNA	Total CF	Detector	Measured Value	Corrected Value	Limit	Margin	Mast Height	Turntable Angle
Horizontal				MHz	dB/m	dB	dB/m		dBuV	dBuV/m	dBuV/m	dB	cm	degrees
2701 RX BiCon Hpol		10M Total Link Factor		81.39	7.65	-24.48	-16.83	QP	33.84	17.01	29.54	12.53	400.0	7.0
Vertical														
2701 RX BiCon Vpol		10M Total Link Factor		40.68	12.20	-24.99	-12.79	QP	24.82	12.03	29.54	17.52	100.0	28.5
2701 RX BiCon Vpol		10M Total Link Factor		81.38	7.70	-24.48	-16.78	QP	41.89	25.11	29.54	4.43	115.4	104.3
2701 RX BiCon Vpol		10M Total Link Factor		114.57	12.16	-24.09	-11.93	QP	20.91	8.98	33.06	24.09	106.2	20.8
2701 RX BiCon Vpol		10M Total Link Factor		120.11	12.30	-24.01	-11.71	QP	25.46	13.75	33.06	19.32	335.2	262.0
2701 RX BiCon Vpol		10M Total Link Factor		911.47	21.10	-20.79	0.31	QP	26.73	27.04	35.56	8.52	163.6	16.8
Positive Margin indicates a Pass														

A.8. Tested By

This testing was conducted in accordance with the ISO 17025:1999 scope of accreditation, table 1; Quality Manual.

Name: Deniz Demirci
Function: EMC Engineer

The test results contained in this report refer exclusively to the product(s) presented for testing. The test results do not cover models or products not referred herein. This test report should not be published or duplicated in whole or part without permission from the testing body and the customer.

NTS Product Integrity Laboratory, 5151-47th Street N.E. Tel: 403-568-6605, Fax: 403-568-6970




Figure 1 RE - Horizontal – 30 MHz – 1 GHz




Figure 2 RE - Vertical – 30 MHz – 1 GHz

The test results contained in this report refer exclusively to the product(s) presented for testing. The test results do not cover models or products not referred herein. This test report should not be published or duplicated in whole or part without permission from the testing body and the customer.

NTS Product Integrity Laboratory, 5151-47th Street N.E. Tel: 403-568-6605, Fax: 403-568-6970

APPENDIX B: CONDUCTED EMISSIONS 150 KHZ – 30 MHZ

B.1. Base Standard & Test Basis

Base Standard	CFR Title 47 – Telecommunications, Chapter I - FCC Part 15.207 – Radio Frequency Devices, RSS 210 Issue 6
Test Basis	ANSI C63.4 - 2003 Methods of Measurement of Radio Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
Test Method	NTS Conducted Emissions Test Method E011R1

B.2. Specifications

Frequency MHz	Limit	
	Quasi-Peak dBμV	Average dBμV
0.150 – 0.500	66 to 56 ¹	56 to 46 ¹
0.500 – 5.00	56	46
5.00 – 30.00	60	50

Note 1: decrease with the logarithm of the frequency

B.3. Measurement Uncertainty

Conducted Current Emissions 150 kHz – 30 MHz	Measurement Uncertainty	Expanded Uncertainty (K=2)
(dB)	+1.21/-1.33	+2.41/-2.66

B.4. Deviations

Deviation Number	Time & Date	Description and Justification of Deviation	Deviation Reference			Approval
			Base Standard	Test Basis	NTS Procedure	
none						

The test results contained in this report refer exclusively to the product(s) presented for testing. The test results do not cover models or products not referred herein. This test report should not be published or duplicated in whole or part without permission from the testing body and the customer.

NTS Product Integrity Laboratory, 5151-47th Street N.E. Tel: 403-568-6605, Fax: 403-568-6970

B.5. Test Results

Compliant. The worst case emission level was 46.15dB μ V at 0.332MHz with a margin of 3.26dB.


B.6. Sample Calculation

Correction Factor = LISN Correction Factor + Cable Loss

Corrected Value = Measurement + Correction Factor

Margin = Limit – Corrected Emission Level

B.7. Test Data



Product Integrity Laboratory V2.5

Project Number: CG-225
Model: SDID1020 (Wireless Dynamics Inc.)
Comments: Conf08-E- 120VAC, Zire72 (PDA), PDA on Vertical Upright position, SDID1020-24, I code 100% ASK fast mode
Power cord draped to the floor routed over to receptacle

Tester: Deniz
Test ID: CE02tc-10m-225

Standard:
FCC15_B

Voltage/Line	LISN/Lead	Frequency	Measurement Detector	Measured Value	CF	Corrected Value	Limit Detector Type	Limit	Margin
		MHz		dBuV	dB	dBuV		dBuV	dB
Phase1	LISN A1	0.16	QP	31.4	11.71	43.11	QP	65.52	22.40
Phase1	LISN A1	0.17	QP	30.9	11.58	42.48	QP	64.96	22.48
Phase1	LISN A1	0.19	QP	29.83	11.35	41.18	QP	63.83	22.65
Phase1	LISN A1	0.29	QP	27.01	10.90	37.91	QP	60.48	22.58
Neutral	LISN A1	0.32	QP	27.19	10.84	38.03	QP	59.78	21.76
Neutral	LISN A1	13.56	QP	34.55	11.72	46.27	QP	60.00	13.73
Neutral	LISN A4	0.16	QP	31.35	11.69	43.04	QP	65.62	22.57
Neutral	LISN A4	0.20	QP	29.73	11.27	41.00	QP	63.56	22.56
Neutral	LISN A4	0.25	QP	27.87	11.00	38.87	QP	61.72	22.85
Neutral	LISN A4	0.34	QP	26.71	10.78	37.49	QP	59.27	21.78
Neutral	LISN A4	0.35	QP	26.27	10.76	37.03	QP	59.01	21.98
Neutral	TT LISN A4	13.56	QP	35.87	11.42	47.29	QP	60.00	12.71
Phase1	LISN A1	0.16	Avg	14.92	11.74	26.66	Avg	55.62	28.95
Phase1	LISN A1	0.23	Avg	13.32	11.12	24.44	Avg	52.42	27.99
Phase1	LISN A1	0.32	Avg	12.74	10.84	23.58	Avg	49.77	26.19
Phase1	LISN A1	0.35	Avg	12.18	10.78	22.96	Avg	48.95	25.99
Phase1	LISN A1	0.60	Avg	10.96	10.62	21.58	Avg	46.00	24.42
Phase1	LISN A1	13.56	Avg	33.54	11.72	45.26	Avg	50.00	4.74
Neutral	LISN A4	0.15	Avg	15.1	11.75	26.85	Avg	55.84	28.98
Neutral	LISN A4	0.18	Avg	14.39	11.43	25.82	Avg	54.44	28.62
Neutral	LISN A4	0.33	Avg	35.36	10.79	46.15	Avg	49.41	3.26
Neutral	LISN A4	0.35	Avg	12.33	10.76	23.09	Avg	49.01	25.92
Neutral	LISN A4	0.60	Avg	11.04	10.59	21.63	Avg	46.00	24.37
Neutral	LISN A4	13.56	Avg	34.83	11.63	46.46	Avg	50.00	3.54

Positive Margin indicates a Pass

Positive Margin indicates a Pass

B.8. Tested By

This testing was conducted in accordance with the ISO 17025:1999 scope of accreditation, table 1; Quality Manual.

Name: Deniz Demirci
Function: EMC Engineer

The test results contained in this report refer exclusively to the product(s) presented for testing. The test results do not cover models or products not referred herein. This test report should not be published or duplicated in whole or part without permission from the testing body and the customer.

NTS Product Integrity Laboratory, 5151-47th Street N.E. Tel: 403-568-6605, Fax: 403-568-6970




Figure 3 CE –Line A1 – 150 kHz – 30 MHz (QP Detector)




Figure 4 CE –Return A2 – 150 kHz – 30 MHz (QP Detector)

The test results contained in this report refer exclusively to the product(s) presented for testing. The test results do not cover models or products not referred herein. This test report should not be published or duplicated in whole or part without permission from the testing body and the customer.

NTS Product Integrity Laboratory, 5151-47th Street N.E. Tel: 403-568-6605, Fax: 403-568-6970




Figure 5 CE –Line A1 – 150 kHz – 30 MHz (Average Detector)




Figure 6 CE –Return A2 – 150 kHz – 30 MHz (Average Detector)

The test results contained in this report refer exclusively to the product(s) presented for testing. The test results do not cover models or products not referred herein. This test report should not be published or duplicated in whole or part without permission from the testing body and the customer.

NTS Product Integrity Laboratory, 5151-47th Street N.E. Tel: 403-568-6605, Fax: 403-568-6970

APPENDIX C: RADIATED H-FIELD EMISSIONS 9 KHZ - 30 MHZ

C.1. Base Standard & Test Basis

Base Standard	CFR Title 47 – Telecommunications, Chapter I - FCC Part 15.209 and Part 15.225 – Radio Frequency Devices, RSS 210 Issue 6,
Test Basis	ANSI C63.4 - 2003 Methods of Measurement of Radio Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
Test Method	NTS Radiated H-Field Emissions Test Method 28.2, Rev 1.0

C.2. Specifications

Frequency (F)	Limit		Limit at 10m
	Field Strength	Distance	
MHz	$\mu\text{V/m}$	m	$\text{dB}\mu\text{V/m}$
0.009 – 0.49	2400/ F(kHz)	300	107.6 to 72.9 ¹
0.49 – 1.705	24000/ F(kHz)	30	52.9 to 42.1 ¹
1.705 – 13.11	30	30	48.6
13.11 – 13.41	106	30	59.6
13.41 – 13.553	334	30	69.6
13.553 – 13.567	15848	30	103.1
13.567 – 13.71	334	30	69.6
13.71 – 14.01	106	30	59.6
14.01 – 30	30	30	48.6

Notes:

- ¹ decrease with the logarithm of the frequency.
- Limit is extrapolated from 300m and 30 to 10m by adding 59.1dB and 19.1dB respectively.

C.3. Measurement Uncertainty

Radiated H-Field Emissions 9kHz – 30MHz	Measurement Uncertainty	Expanded Uncertainty (K=2)
(DB)	+2.15/-2.19	+4.30/-4.38

C.4. Deviations

Deviation Number	Time & Date	Description and Justification of Deviation	Deviation Reference			Approval
			Base Standard	Test Basis	NTS Procedure	
none						

The test results contained in this report refer exclusively to the product(s) presented for testing. The test results do not cover models or products not referred herein. This test report should not be published or duplicated in whole or part without permission from the testing body and the customer.

NTS Product Integrity Laboratory, 5151-47th Street N.E. Tel: 403-568-6605, Fax: 403-568-6970

C.5. Test Method

The EUT was placed on a non-conductive table 0.8 meters above the ground plane. The table was centered on a motorized turntable. The fundamental field strength was maximized by rotating the turntable through 360 degrees. The receive Loop antenna was positioned at a distance of 3 meters as measured from the closest point of the EUT and 1 meter above the ground plane. A spectrum analyzer with peak detection was used to find the maximum field strength during the scans. The EUT was tested in 3 orthogonal planes and all data rates (1.6 kbps (I Code SLI slow mode, 100% and 10 % ASK), 26 kbps (I Code SLI fast mode, 100% and 10 % ASK), 106 kbps (14443A/B), 212 kbps (14443A/B), 424 kbps (14443A/B), 848 kbps (14443A/B) with the worst case results being reported.


C.6. Test Results

Compliant. The worst case fundamental field strength is 42.33dB μ V/m

C.7. Sample Calculation

Margin = Limit – Emission Level

C.8. Test Data



Product Integrity
Laboratory V2.5

Project Number: CG-225
Model: SDID1020 (Wireless Dynamics Inc.)
Comments: Conf08:E- 120VAC, Zire72 (PDA), PDA on Vertical Upright position, SDID1020-24, I code 100% ASK fast mode, Power cord draped to the floor routed over to receptacle

Tester: Deniz
Test ID: RE01-10m-225

Standard :	FCC Part 15	Measurement Distance :	10 meters	Measurement Type :	H-Field				
Antenna	Frequency	AF	CL	Total CF	Detector	Measured Value	Corrected Value	Limit	Margin
Parallel	MHz	dB/m	dB	dB/m		dBuV	dBuV/m	dBuV/m	dB
R&S HFH2-Z2 Loop	0.03	19.40	0.12	19.52	Peak	24.61	44.13	97.27	53.14
R&S HFH2-Z2 Loop	13.55	20.34	0.60	20.94	Peak	13.68	34.62	69.55	34.93
R&S HFH2-Z2 Loop	13.56	20.34	0.60	20.94	Peak	21.39	42.33	103.08	60.75
R&S HFH2-Z2 Loop	13.57	20.34	0.59	20.93	Peak	20.49	41.42	69.55	28.13
Perpendicular									
R&S HFH2-Z2 Loop	13.55	20.34	0.60	20.94	Peak	12.99	33.93	69.55	35.62
R&S HFH2-Z2 Loop	13.56	20.34	0.60	20.94	Peak	20.33	41.27	103.08	61.81
R&S HFH2-Z2 Loop	13.57	20.34	0.59	20.93	Peak	17.85	38.78	69.55	30.77

Positive Margin indicates a Pass


C.9. Tested By

This testing was conducted in accordance with the ISO 17025:1999 scope of accreditation, table 1; Quality Manual.

Name: Deniz Demirci
Function: EMC Engineer

The test results contained in this report refer exclusively to the product(s) presented for testing. The test results do not cover models or products not referred herein. This test report should not be published or duplicated in whole or part without permission from the testing body and the customer.

NTS Product Integrity Laboratory, 5151-47th Street N.E. Tel: 403-568-6605, Fax: 403-568-6970




Title: CG-225 SDID1020 (Wireless Dynamics Inc.) Parallel
Comment A: Conf08: 120VAC, Zire72 (PDA), PDA on Vertical UP-right position
Date: 21.NOV.2005 15:49:52

Figure 7 RE - Parallel – 13.06MHz – 14.06MHz

The test results contained in this report refer exclusively to the product(s) presented for testing. The test results do not cover models or products not referred herein. This test report should not be published or duplicated in whole or part without permission from the testing body and the customer.

NTS Product Integrity Laboratory, 5151-47th Street N.E. Tel: 403-568-6605, Fax: 403-568-6970



Title: CG-225 SDID1020 (Wireless Dynamics Inc.) Perpendicular
Comment A: Conf08: 120VAC, Zire72 (PDA), PDA on Vertical UP-right position
Date: 21.NOV.2005 16:02:48

Figure 8 RE - Perpendicular – 13.06MHz – 14.06MHz

The test results contained in this report refer exclusively to the product(s) presented for testing. The test results do not cover models or products not referred herein. This test report should not be published or duplicated in whole or part without permission from the testing body and the customer.

NTS Product Integrity Laboratory, 5151-47th Street N.E. Tel: 403-568-6605, Fax: 403-568-6970




Figure 9 RE - Parallel – 9kHz – 150kHz




Figure 10 RE - Parallel – 150kHz – 13.06MHz

The test results contained in this report refer exclusively to the product(s) presented for testing. The test results do not cover models or products not referred herein. This test report should not be published or duplicated in whole or part without permission from the testing body and the customer.

NTS Product Integrity Laboratory, 5151-47th Street N.E. Tel: 403-568-6605, Fax: 403-568-6970




Figure 11 RE - Parallel – 14.06MHz – 30.0MHz




Figure 12 RE – Perpendicular – 9kHz – 150kHz

The test results contained in this report refer exclusively to the product(s) presented for testing. The test results do not cover models or products not referred herein. This test report should not be published or duplicated in whole or part without permission from the testing body and the customer.

NTS Product Integrity Laboratory, 5151-47th Street N.E. Tel: 403-568-6605, Fax: 403-568-6970




Figure 13 RE - Perpendicular – 150kHz – 13.06MHz




Figure 14 RE - Perpendicular – 14.06MHz – 30.0MHz

The test results contained in this report refer exclusively to the product(s) presented for testing. The test results do not cover models or products not referred herein. This test report should not be published or duplicated in whole or part without permission from the testing body and the customer.

NTS Product Integrity Laboratory, 5151-47th Street N.E. Tel: 403-568-6605, Fax: 403-568-6970

APPENDIX D: FREQUENCY STABILITY

D.1. Base Standard & Test Basis

Base Standard	CFR Title 47 – Telecommunications, Chapter I - FCC Part 15.225 – Radio Frequency Devices, RSS 210 Issue 6
Test Basis	ANSI C63.4 - 2003 Methods of Measurement of Radio Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
Test Method	ANSI C63.4 - 2003 , 13.1.6 - Frequency Measurements

D.2. Specifications

Supply Voltage	Temperature	Maximum Tolerance
VAC	°C	kHz
120	20	1.356
138 (115%)	20	1.356
102 (85%)	20	1.356
120	-20	1.356
120	50	1.356

D.3. Deviations

Deviation Number	Time & Date	Description and Justification of Deviation	Deviation Reference			Approval
			Base Standard	Test Basis	NTS Procedure	
none						

The test results contained in this report refer exclusively to the product(s) presented for testing. The test results do not cover models or products not referred herein. This test report should not be published or duplicated in whole or part without permission from the testing body and the customer.

NTS Product Integrity Laboratory, 5151-47th Street N.E. Tel: 403-568-6605, Fax: 403-568-6970

D.4. Test Results

Compliant. The maximum frequency tolerance was found to be 946.6Hz.

D.5. Sample Calculation

None

D.6. Test Data

Voltage (VDC)	Temperature (Celcius)	Frequency (MHz)
3.1	20	13.5609466
3.6	20	13.5609466
2.9 (end operating point)	20	13.5609466
3.1	-20	13.56070140
3.1	50	13.56070140

D.7. Tested By

This testing was conducted in accordance with the ISO 17025:1999 scope of accreditation, table 1; Quality Manual.

Name: Kuganesan Pararajasingam
Function: EMC Engineer

The test results contained in this report refer exclusively to the product(s) presented for testing. The test results do not cover models or products not referred herein. This test report should not be published or duplicated in whole or part without permission from the testing body and the customer.

NTS Product Integrity Laboratory, 5151-47th Street N.E. Tel: 403-568-6605, Fax: 403-568-6970

APPENDIX E: TEST EQUIPMENTS

E.1. Radiated Emissions 30 MHz – 1 GHz Measurement Equipment

Description	Manufacturer	Type/Model	Asset #	Cal Due	Cal Date
10m ANECHOIC CHAMBER					
Bilog Antenna	<input checked="" type="checkbox"/> Chase	CBL 6111B	260398	23APR06	23APR04
	<input type="checkbox"/> Chase	CBL 6112B	260301		
RF Cable	Suhner Succoflex	Ferrite bead loaded cable	260388	07JAN06	07JAN04
CONTROL ROOM					
Test Receiver	<input checked="" type="checkbox"/> Rohde & Schwarz	ESAI	260110 / 260111	2FEB06	2FEB05
Mast Controller	EMCO	2090	260165	N/A	N/A
Multi Device Controller TT1 (Turntable)	07JAN06	07JAN04		N/A	N/A
RF 10m East site Link				Suhner Succoflex	NA
- Cable 1	Suhner Succoflex	NA	263135		
- Cable 2	Suhner Succoflex	NA	263161		
- Cable 3	Suhner Succoflex	NA	263162		
- Cable 4	TDL	SMC-002	260162		
- Amplifier	Hewlett Packard	8447F	260164		

The test results contained in this report refer exclusively to the product(s) presented for testing. The test results do not cover models or products not referred herein. This test report should not be published or duplicated in whole or part without permission from the testing body and the customer.

NTS Product Integrity Laboratory, 5151-47th Street N.E. Tel: 403-568-6605, Fax: 403-568-6970

E.2. Conducted Emissions 10 kHz – 30 MHz Measurement Equipment

Description		Manufacturer	Type/Model	Serial #	Cal Due	Cal Date
10m ANECHOIC CHAMBER						
A LISN Link					07JAN06	07JAN04
-LISN A Switch	<input checked="" type="checkbox"/> A	NA	NA	263177		
-Cable Switch to Limiter	<input checked="" type="checkbox"/> A	NA	NA	263164		
- Cable LISN to Switch	<input checked="" type="checkbox"/> A1	Succoflex	NA	263168	07JAN06	07JAN04
	<input type="checkbox"/> A2	Succoflex	NA	263169	07JAN06	07JAN04
	<input type="checkbox"/> A3	Succoflex	NA	263170	07JAN06	07JAN04
	<input checked="" type="checkbox"/> A4	Succoflex	NA	263171	07JAN06	07JAN04
- Table Top LISN	<input checked="" type="checkbox"/> TT	EMCO	3825	260354	08JAN06	08JAN04
B LISN Link					07JAN06	07JAN04
-LISN B Switch	<input type="checkbox"/> B	NA	NA	263176		
-Cable Switch to Limiter	<input type="checkbox"/> B	NA	NA	263165		
- Cable LISN to Switch	<input type="checkbox"/> B1	Succoflex	NA	263172	07JAN06	07JAN04
	<input type="checkbox"/> B2	Succoflex	NA	263173	07JAN06	07JAN04
	<input type="checkbox"/> B3	Succoflex	NA	263174	07JAN06	07JAN04
	<input type="checkbox"/> B4	Succoflex	NA	263175	07JAN06	07JAN04
CONTROL ROOM						
		Rohde & Schwarz	ESAI	260110 / 260111		
Mast Controller		EMCO	2090	260166	N/A	N/A
Switch Matrix		TDL	SMC-002	260162	07JAN06	07JAN04
Cable Switch Matrix to Receiver		NA	NA	263166	07JAN06	07JAN04
A LISN Link					07JAN06	07JAN04
-LISN A Limiter	<input checked="" type="checkbox"/> A	NA	NA	263178		
-Cable Switch to Limiter	<input checked="" type="checkbox"/> A	NA	NA	263164		
B LISN Link					07JAN06	07JAN04
-LISN B Limiter	<input type="checkbox"/> B	NA	NA	263179		
-Cable Switch to Limiter	<input type="checkbox"/> B	NA	NA	263194		

The test results contained in this report refer exclusively to the product(s) presented for testing. The test results do not cover models or products not referred herein. This test report should not be published or duplicated in whole or part without permission from the testing body and the customer.

NTS Product Integrity Laboratory, 5151-47th Street N.E. Tel: 403-568-6605, Fax: 403-568-6970

E.3. Radiated H-Field Emissions 10kHz – 30MHz Measurement Equipment

Description		Manufacturer	Type/Model	Serial #	Cal Due	Cal Date
10m ANECHOIC CHAMBER						
Loop Antenna		R&S	HFH2-Z2	DE12245	09NOV05	09NOV04
Loop Antenna Power Supply		NA	NA	263257	N/A	N/A
Cable	<input checked="" type="checkbox"/> 3m center site bulkhead to antenna	Succoflex	NA	263136	08JAN06	08JAN04
	<input type="checkbox"/> H-Field site bulkhead to antenna	Succoflex	NA	263387	08JAN06	08JAN04
CONTROL ROOM						
Mast Controller		EMCO	2090	260166	N/A	N/A
Multi Device Controller TT1 (Turntable)		EMCO	2090	260165	N/A	N/A
Test Receiver		Rohde & Schwarz	ESAI	260110 / 260111	02FEB06	02FEB05
<input checked="" type="checkbox"/> RF 3m Center site Link					08JAN06	08JAN04
- Cable 1		Succoflex	NA	263188		
- Cable 2		Succoflex	NA	263134		
<input type="checkbox"/> RF 10m H-Field site Link					08JAN06	08JAN04
- Cable 1		Succoflex	NA	263184		
- Cable 2		Succoflex	NA	263189		
- Cable 3		Succoflex	NA	263167		
- Switch Matrix Controller		TDL	SMC-002	260162		

E.4. Frequency Stability Measurement Equipment

Description	Manufacturer	Type/Model	Serial #	Cal Due	Cal Date
Temperature Chamber	Thermotron Industries	SM-8C	17013-S	NA	NA
Data Acquisition/ Switch unit	Hewlett Packard	34970A	US37003408	24SEP05	24SEP04
Spectrum Analyzer 9k-40GHz	Rohde & Schwarz	FSEK	260104	05APR06	05ARP05
DC Power Supply	Hewlett Packard	6632B	US36351938	NA	NA
RMS Multimeter	Fluke	87	69460888	10Jan06	10Jan05

The test results contained in this report refer exclusively to the product(s) presented for testing. The test results do not cover models or products not referred herein. This test report should not be published or duplicated in whole or part without permission from the testing body and the customer.

NTS Product Integrity Laboratory, 5151-47th Street N.E. Tel: 403-568-6605, Fax: 403-568-6970

END OF DOCUMENT

The test results contained in this report refer exclusively to the product(s) presented for testing. The test results do not cover models or products not referred herein. This test report should not be published or duplicated in whole or part without permission from the testing body and the customer.

NTS Product Integrity Laboratory, 5151-47th Street N.E. Tel: 403-568-6605, Fax: 403-568-6970