



# SPORTON International Inc.


No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.  
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / www.sporton.com.tw

Project No: CB10505061

## Maximum Permissible Exposure Report

Applicant's company	Xirrus, Inc.
Applicant Address	2101 Corporate Center Drive, Thousand Oaks, CA 91320 USA
FCC ID	SK6-XD2240B
Manufacturer's company	Lite-On Network Communication (Dongguan) Limited
Manufacturer Address	30#Keji Rd.,Yin Hu Industrial Area, Qingxi Town, DongGuan City, Guangdong, China

Product Name	Wireless Access Point
Brand Name	XIRRUS, AVAYA
Model Name	XD2240 -1, WAP9144 -1
Ref. Standard(s)	47 CFR FCC Part 2 Subpart J, section 2.1091
Received Date	Aug. 17, 2015
Final Test Date	Apr. 25, 2016
Submission Type	Original Equipment



Sam Chen

SPORTON INTERNATIONAL INC.





## Table of Contents

<b>1. GENERAL DESCRIPTION.....</b>	<b>1</b>
1.1. EUT General Information .....	1
1.2. Table for Multiple List.....	1
1.3. Testing Location.....	1
<b>2. MAXIMUM PERMISSIBLE EXPOSURE.....</b>	<b>2</b>
2.1. Limit of Maximum Permissible Exposure .....	2
2.2. MPE Calculation Method .....	2
2.3. Calculated Result and Limit.....	3



### History of This Test Report

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA582537-03	Rev. 01	Initial issue of report	May 17, 2016

## 1. GENERAL DESCRIPTION

### 1.1. EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
2.4GHz WLAN	2400-2483.5	2412-2462	802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)
5GHz WLAN	5150-5250 5725-5850	5180-5240 5745-5825	802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)
Bluetooth	2400-2483.5	2402-2480	BR / EDR: FHSS (GFSK / $\pi/4$ -DQPSK / 8DPSK) LE: DSSS (GFSK)

### 1.2. Table for Multiple List

The brand name and model numbers in the following table are all refer to the identical product.

Brand Name	Model Name	Description
XIRRUS	XD2240 -1	All the design is the same, just for different marketing use.
AVAYA	WAP9144 -1	

From the above models, model: XD2240 -1 was selected as representative model for the test and its data was recorded in this report.

### 1.3. Testing Location

Testing Location		
<input type="checkbox"/>	HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-327-0973
<input checked="" type="checkbox"/>	JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

## 2. MAXIMUM PERMISSIBLE EXPOSURE

### 2.1. Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; \*Plane-wave equivalent power density

### 2.2. MPE Calculation Method

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

**E** = Electric field (V/m)

**P** = Peak RF output power (W)

**G** = EUT Antenna numeric gain (numeric)

**d** = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

### 2.3. Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

For 5GHz Band:

Antenna Type : PIFA Ant.

Conducted Power for IEEE 802.11ac MCS0/Nss1 (VHT40): 23.22 dBm

Distance (cm)	Test Freq. (MHz)	Directional Gain (dBi)	Antenna Gain (numeric)	The maximum combined Average Output Power		Power Density (S) (mW/cm <sup>2</sup> )	Limit of Power Density (S) (mW/cm <sup>2</sup> )	Test Result
				(dBm)	(mW)			
20	5795	7.29	5.3580	23.2245	210.1109	0.2240	1	Complies

Note:  $Directional\ Gain = 10 \log \left[ \frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{K=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$

For 2.4GHz Band:

Antenna Type : PIFA Ant.

Conducted Power for IEEE 802.11ac MCS0/Nss1 (VHT20): 24.23 dBm

Distance (cm)	Test Freq. (MHz)	Directional Gain (dBi)	Antenna Gain (numeric)	The maximum combined Average Output Power		Power Density (S) (mW/cm <sup>2</sup> )	Limit of Power Density (S) (mW/cm <sup>2</sup> )	Test Result
				(dBm)	(mW)			
20	2437	7.02	5.0350	24.2328	265.0239	0.2656	1	Complies

Note:  $Directional\ Gain = 10 \log \left[ \frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{K=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$

For Bluetooth:

Antenna Type : PIFA Ant.

Conducted Power for BR (GFSK) 1 Mbps: 8.89 dBm

Distance (cm)	Test Freq. (MHz)	Antenna Gain (dBi)	Antenna Gain (numeric)	Average Output Power		Power Density (S) (mW/cm <sup>2</sup> )	Limit of Power Density (S) (mW/cm <sup>2</sup> )	Test Result
				(dBm)	(mW)			
20	2441	3.20	2.0893	8.8882	7.7414	0.0032	1	Complies

### Conclusion:

Both of the 2.4GHz WLAN function, 5GHz WLAN function and Bluetooth function can transmit simultaneously, the formula of calculated the MPE is:

$$\text{CPD1} / \text{LPD1} + \text{CPD2} / \text{LPD2} + \dots\text{etc.} < 1$$

**CPD = Calculation power density**

**LPD = Limit of power density**

Mode 1. 2.4GHz WLAN (Radio 1) + 2.4GHz WLAN (Radio 2) + Bluetooth (Radio 3)

Therefore, the worst-case situation is  $0.2656 / 1 + 0.2656 / 1 + 0.0032 / 1 = 0.5344$ , which is less than "1".

This confirmed that the device complies.

Mode 2. 2.4GHz WLAN (Radio 1) + 5GHz WLAN (Radio 2) + Bluetooth (Radio 3)

Therefore, the worst-case situation is  $0.2656 / 1 + 0.2240 / 1 + 0.0032 / 1 = 0.4928$ , which is less than "1".

This confirmed that the device complies.

Mode 3. 5GHz WLAN (Radio 1) + 2.4GHz WLAN (Radio 2) + Bluetooth (Radio 3)

Therefore, the worst-case situation is  $0.2240 / 1 + 0.2656 / 1 + 0.0032 / 1 = 0.4928$ , which is less than "1".

This confirmed that the device complies.

Mode 4. 5GHz WLAN (Radio 1) + 5GHz WLAN (Radio 2) + Bluetooth (Radio 3)

Therefore, the worst-case situation is  $0.2240 / 1 + 0.2240 / 1 + 0.0032 / 1 = 0.4512$ , which is less than "1".

This confirmed that the device complies.