




FCC Test Report

Equipment : Hardened Wireless Access Point
Brand Name : Xirrus
Model No. : XH2120
FCC ID : SK6-XH2120
Standard : 47 CFR FCC Part 15.247
Operating Band : 2400 MHz – 2483.5 MHz
FCC Classification : DTS
Applicant : Xirrus, INC.
Manufacturer : 2101 Corporate Center Drive Thousand Oaks,
California 91320

The product sample received on Jun. 18, 2015 and completely tested on Aug. 19, 2015. We, SPORTON, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.10-2013 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:



Kevin Liang / Assistant Manager





Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	Support Equipment.....	7
1.3	Testing Applied Standards	7
1.4	Testing Location Information	7
1.5	Measurement Uncertainty	8
2	TEST CONFIGURATION OF EUT.....	9
2.1	The Worst Case Modulation Configuration	9
2.2	The Worst Case Power Setting Parameter	9
2.3	The Worst Case Measurement Configuration	10
2.4	Test Setup Diagram	11
3	TRANSMITTER TEST RESULT	13
3.1	AC Power-line Conducted Emissions	13
3.2	6dB Bandwidth	16
3.3	RF Output Power.....	18
3.4	Power Spectral Density	21
3.5	Transmitter Bandedge Emissions	24
3.6	Transmitter Unwanted Emissions.....	27
4	TEST EQUIPMENT AND CALIBRATION DATA.....	56

APPENDIX A. TEST PHOTOS

APPENDIX B. PHOTOGRAPHS OF EUT



Summary of Test Result

Conformance Test Specifications					
Report Clause	Ref. Std. Clause	Description	Measured	Limit	Result
1.1.2	15.203	Antenna Requirement	Antenna connector mechanism complied	FCC 15.203	Complied
3.1	15.207	AC Power-line Conducted Emissions	[dBuV]: 0.4420810MHz 45.44 (Margin 11.58dB) - QP 39.80 (Margin 7.22dB) - AV	FCC 15.207	Complied
3.2	15.247(a)	6dB Bandwidth	6dB Bandwidth Unit [MHz] 20M:7.29/ 40M: 36.32	≥500kHz	Complied
3.3	15.247(b)	RF Output Power (Maximum Peak Conducted Output Power)	Power [dBm]: 26.90	Power [dBm]:30	Complied
3.4	15.247(e)	Power Spectral Density	PSD [dBm/100kHz]: -3.17	PSD [dBm/3kHz]:8	Complied
3.5	15.247(d)	Transmitter Radiated Bandedge Emissions	Non-Restricted Bands: 2399.824MHz: 26.44 dB Restricted Bands [dBuV/m at 3m]: 2483.5MHz 69.77 (Margin 4.23 dB) - PK 52.92 (Margin 1.08 dB) - AV	Non-Restricted Bands: > 20 dBc Restricted Bands: FCC 15.209	Complied
3.6	15.247(d)	Transmitter Radiated Unwanted Emissions	Restricted Bands [dBuV/m at 3m]: 600.36 MHz 37.25 (Margin 8.75 dB) - PK	Non-Restricted Bands: > 20 dBc Restricted Bands: FCC 15.209	Complied



Revision History



1 General Description

1.1 Information

1.1.1 RF General Information

There are two RF 2x2 modules in the EUT. They are the same RF module type. RF information is for one RF module. RF chip is " QCA 9882-BR4A"

RF General Information					
Frequency Range (MHz)	IEEE Std. 802.11	Ch. Freq. (MHz)	Channel Number	Transmit Chains (N _{TX})	RF Output Power (dBm)
2400-2483.5	b	2412-2462	1-11 [11]	2	25.69
2400-2483.5	g	2412-2462	1-11 [11]	2	26.90
2400-2483.5	n (HT20)	2412-2462	1-11 [11]	2	26.38
2400-2483.5	n (HT40)	2422-2452	3-9 [7]	2	22.88

Note 1: RF output power specifies that Maximum Peak Conducted Output Power.
 Note 2: 802.11b uses a combination of DSSS-DBPSK, DQPSK, CCK modulation.
 Note 3: 802.11g/n uses a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM modulation.

1.1.2 Antenna Information

Antenna Category	
<input checked="" type="checkbox"/>	External antenna (dedicated antennas)
<input checked="" type="checkbox"/>	Single power level with corresponding antenna(s).
<input type="checkbox"/>	Multiple power level and corresponding antenna(s).
<input checked="" type="checkbox"/>	RF connector provided
	<input checked="" type="checkbox"/> Unique antenna connector. (e.g., MMCX, U.FL, IPX, and RP-SMA, RP-N type...)
	<input type="checkbox"/> Standard antenna connector. (e.g., SMA, N, BNC, and TNC type...)

Antenna General Information				
No.	Ant. Cat.	Ant. Type	Gain (dBi)	Cable Length (m)
1	External	OMNI	2	-
2	External	OMNI	2.3	0.8
3	External	OMNI	2.3	3.1

Note 1: The EUT was pre-tested Antenna 2 and Antenna 3 because the gain of Antenna 2 and Antenna 3 is the same and higher than Antenna 1 among those Antennas.
 Next, comparing the cable length of Antenna 2 and Antenna 3, the worst case of Radiation Emission below 1GHz was Antenna 3 and the worst case of Radiation Emission above 1GHz was Antenna 2.
 Note 2: 11b/g/n only includes 2TX/2RX to emission. IEEE 802.11n has the CDD function.



1.1.3 Type of EUT

Identify EUT	
EUT Serial Number	N/A
Presentation of Equipment	<input type="checkbox"/> Production ; <input type="checkbox"/> Pre-Production ; <input checked="" type="checkbox"/> Prototype
Type of EUT	
<input checked="" type="checkbox"/> Stand-alone	
<input type="checkbox"/> Combined (EUT where the radio part is fully integrated within another device) Combined Equipment - Brand Name / Model No.: ...	
<input type="checkbox"/> Plug-in radio (EUT intended for a variety of host systems) Host System - Brand Name / Model No.: ...	
<input type="checkbox"/> Other:	

1.1.4 Test Signal Duty Cycle

Operated Mode for Worst Duty Cycle	
<input type="checkbox"/> Operated normally mode for worst duty cycle	
<input checked="" type="checkbox"/> Operated test mode for worst duty cycle	
Test Signal Duty Cycle (x)	Power Duty Factor [dB] – (10 log 1/x)
<input checked="" type="checkbox"/> 100.00% - IEEE 802.11b	0.00
<input checked="" type="checkbox"/> 100.00% - IEEE 802.11g	0.00
<input checked="" type="checkbox"/> 100.00% - IEEE 802.11n (HT20)	0.00
<input checked="" type="checkbox"/> 100.00% - IEEE 802.11n (HT40)	0.00

1.1.5 EUT Operational Condition

Supply Voltage	<input type="checkbox"/> AC mains	<input checked="" type="checkbox"/> DC	
Type of DC Source	<input checked="" type="checkbox"/> From PoE	<input type="checkbox"/> External AC adapter	<input type="checkbox"/> Li-ion Battery



1.2 Support Equipment

Support Equipment - RF Conducted				
No.	Equipment	Brand Name	Model Name	FCC ID
1	Notebook	DELL	E5540	DoC
2	NB Adapter	DELL	HA65NM130	DoC

Support Equipment - AC Conduction and Radiated Emission				
No.	Equipment	Brand Name	Model Name	FCC ID
1	PoE	DNI	DPSN-80DB A-R	DoC

1.3 Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR FCC Part 15
- ♦ ANSI C63.10-2013
- ♦ FCC KDB 558074
- ♦ FCC KDB 662911

1.4 Testing Location Information

Testing Location				
<input checked="" type="checkbox"/>	HWA YA	ADD :	No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.	
		TEL :	886-3-327-3456	FAX : 886-3-327-0973
Test Condition		Test Site No.	Test Engineer	Test Environment
AC Conduction		CO04-HY	Zeus	21°C / 60%
RF Conducted		TH01-HY	Shiming	21.9°C / 61%
Radiated Emission		03CH03-HY	Terry	24.3°C / 64.6%
FCC				
636805				



1.5 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Measurement Uncertainty		
Test Item	Uncertainty	
AC power-line conducted emissions	±2.3 dB	
Emission bandwidth, 6dB bandwidth	±0.6 %	
RF output power, conducted	±0.1 dB	
Power density, conducted	±0.6 dB	
Unwanted emissions, conducted	9 – 150 kHz	±0.4 dB
	0.15 – 30 MHz	±0.4 dB
	30 – 1000 MHz	±0.6 dB
	1 – 18 GHz	±0.5 dB
	18 – 40 GHz	±0.5 dB
	40 – 200 GHz	N/A
All emissions, radiated	9 – 150 kHz	±2.5 dB
	0.15 – 30 MHz	±2.3 dB
	30 – 1000 MHz	±2.6 dB
	1 – 18 GHz	±3.6 dB
	18 – 40 GHz	±3.8 dB
	40 – 200 GHz	N/A
Temperature	±0.8 °C	
Humidity	±5 %	
DC and low frequency voltages	±0.9 %	
Time	±1.4 %	
Duty Cycle	±0.6 %	



2 Test Configuration of EUT

2.1 The Worst Case Modulation Configuration

We select one module to test because power of only one module is maximum.

Two modules can work in 2.4GHz or 5GHz together, but they never work at the same channel.

Worst Modulation Used for Conformance Testing			
Modulation Mode	Transmit Chains (N _{TX})	Data Rate / MCS	Worst Data Rate / MCS
11b	2	1-11 Mbps	1 Mbps
11g	2	6-54 Mbps	6 Mbps
HT20	2	MCS 0-15	MCS 0
HT40	2	MCS 0-15	MCS 0

2.2 The Worst Case Power Setting Parameter

The Worst Case Power Setting Parameter (2400-2483.5MHz band)							
Test Software Version	Cart						
Modulation Mode	N _{TX}	Test Frequency (MHz)					
		NCB: 20MHz			NCB: 40MHz		
		2412	2437	2462	2422	2437	2452
11b	2	20	24	18.5	-	-	-
11g	2	14.5	21	14.5	-	-	-
HT20	2	14	20	14	-	-	-
HT40	2	-	-	-	13	15.5	12.5




2.3 The Worst Case Measurement Configuration



The Worst Case Mode for Following Conformance Tests	
Tests Item	AC power-line conducted emissions
Condition	AC power-line conducted measurement for line and neutral Test Voltage: 120Vac / 60Hz
Operating Mode	Operating Mode Description
1	PoE Mode

The Worst Case Mode for Following Conformance Tests	
Tests Item	RF Output Power, Power Spectral Density, 6 dB Bandwidth
Test Condition	Conducted measurement at transmit chains
Modulation Mode	11b, 11g, HT20, HT40

The Worst Case Mode for Following Conformance Tests					
Tests Item	Transmitter Radiated Unwanted Emissions Transmitter Radiated Bandedge Emissions				
Test Condition	Radiated measurement If EUT consist of multiple antenna assembly (multiple antenna are used in EUT regardless of spatial multiplexing MIMO configuration), the radiated test should be performed with highest antenna gain of each antenna type.				
User Position	<input checked="" type="checkbox"/> EUT will be placed in fixed position. <input type="checkbox"/> EUT will be placed in mobile position and operating multiple positions. EUT shall be performed three orthogonal planes. <input type="checkbox"/> EUT will be a hand-held or body-worn battery-powered devices and operating multiple positions. EUT shall be performed three orthogonal planes.				
Operating Mode	<input checked="" type="checkbox"/> 1. PoE Mode				
Modulation Mode	11b, 11g, HT20, HT40				
Orthogonal Planes of EUT	<table border="1"><thead><tr><th>X Plane</th><th>Y Plane</th></tr></thead><tbody><tr><td></td><td></td></tr></tbody></table>	X Plane	Y Plane		
X Plane	Y Plane				
					
Worst Planes of EUT	V				

2.4 Test Setup Diagram



Test Setup Diagram - Radiated Test - below 1GHz**Test Setup Diagram - Radiated Test - above 1GHz**

3 Transmitter Test Result

3.1 AC Power-line Conducted Emissions

3.1.1 AC Power-line Conducted Emissions Limit

AC Power-line Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: * Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.1.3 Test Procedures


Test Method
<input checked="" type="checkbox"/> Refer as ANSI C63.10-2013, clause 6.2 for AC power-line conducted emissions.

3.1.4 Test Setup





3.1.5 Test Result of AC Power-line Conducted Emissions




Note 1: ">20dB" means emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found emissions (No emissions were detected.)



AC Power-line Conducted Emissions Result



3.2 6dB Bandwidth

3.2.1 6dB Bandwidth Limit

6dB Bandwidth Limit
Systems using digital modulation techniques:
<input checked="" type="checkbox"/> 6 dB bandwidth \geq 500 kHz.


3.2.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.2.3 Test Procedures

Test Method
<input checked="" type="checkbox"/> For the emission bandwidth shall be measured using one of the options below:
<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 8.1 Option 1 for 6 dB bandwidth measurement.
<input type="checkbox"/> Refer as FCC KDB 558074, clause 8.2 Option 2 for 6 dB bandwidth measurement.
<input type="checkbox"/> Refer as ANSI C63.10, clause 6.9.1 for occupied bandwidth testing.
<input checked="" type="checkbox"/> For conducted measurement.
<input type="checkbox"/> The EUT supports single transmit chain and measurements performed on this transmit chain.
<input type="checkbox"/> The EUT supports diversity transmitting and the results on transmit chain port 1 is the worst case.
<input checked="" type="checkbox"/> The EUT supports multiple transmit chains using options given below:
<input type="checkbox"/> Option 1: Multiple transmit chains measurements need to be performed on one of the active transmit chains (antenna outputs). All measurement had be performed on transmit chains 1.
<input checked="" type="checkbox"/> Option 2: Multiple transmit chains measurements need to be performed on each transmit chains individually (antenna outputs). All measurement had be performed on all transmit chains.


3.2.4 Test Setup





3.2.5 Test Result of Emission Bandwidth

Emission Bandwidth Result						
Condition			Emission Bandwidth (MHz)			
Modulation Mode	N _{TX}	Freq. (MHz)	99% Bandwidth		6dB Bandwidth	
			Chain Port 1	Chain Port 2	Chain Port 1	Chain Port 2
11b	2	2412	12.95	13.32	7.54	7.35
11b	2	2437	16.32	16.56	9.03	9.33
11b	2	2462	12.93	12.87	7.29	7.53
11g	2	2412	16.43	16.38	16.42	16.41
11g	2	2437	22.42	22.56	16.53	16.38
11g	2	2462	16.43	16.46	16.39	16.39
HT20	2	2412	17.64	17.64	17.61	17.73
HT20	2	2437	20.85	21.03	17.64	17.62
HT20	2	2462	17.66	17.61	17.67	17.59
HT40	2	2422	36.26	36.22	36.48	36.40
HT40	2	2437	36.22	36.22	36.40	36.32
HT40	2	2452	36.22	36.14	36.40	36.40
Limit			N/A		≥500 kHz	
Result			Complied			

Note 1: N_{TX} = Number of Transmit Chains



3.3 RF Output Power

3.3.1 RF Output Power Limit

RF Output Power Limit	
Maximum Peak Conducted Output Power or Maximum Conducted Output Power Limit	
<input checked="" type="checkbox"/> 2400-2483.5 MHz Band:	
<input checked="" type="checkbox"/> If $G_{TX} \leq 6$ dBi, then $P_{Out} \leq 30$ dBm (1 W)	
<input checked="" type="checkbox"/> Point-to-multipoint systems (P2M): If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)$ dBm	
<input type="checkbox"/> Point-to-point systems (P2P): If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm	
<input type="checkbox"/> Smart antenna system (SAS):	
	<input type="checkbox"/> Single beam: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm
	<input type="checkbox"/> Overlap beam: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm
	<input type="checkbox"/> Aggregate power on all beams: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3 + 8$ dB dBm
e.i.r.p. Power Limit:	
<input checked="" type="checkbox"/> 2400-2483.5 MHz Band	
<input checked="" type="checkbox"/> Point-to-multipoint systems (P2M): $P_{eirp} \leq 36$ dBm (4 W)	
<input type="checkbox"/> Point-to-point systems (P2P): $P_{eirp} \leq \text{MAX}(36, [P_{Out} + G_{TX}])$ dBm	
<input type="checkbox"/> Smart antenna system (SAS)	
	<input type="checkbox"/> Single beam: $P_{eirp} \leq \text{MAX}(36, P_{Out} + G_{TX})$ dBm
	<input type="checkbox"/> Overlap beam: $P_{eirp} \leq \text{MAX}(36, P_{Out} + G_{TX})$ dBm
	<input type="checkbox"/> Aggregate power on all beams: $P_{eirp} \leq \text{MAX}(36, [P_{Out} + G_{TX} + 8])$ dBm
P_{Out} = maximum peak conducted output power or maximum conducted output power in dBm, G_{TX} = the maximum transmitting antenna directional gain in dBi. P_{eirp} = e.i.r.p. Power in dBm.	


3.3.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.3.3 Test Procedures

Test Method	
<input checked="" type="checkbox"/> Maximum Peak Conducted Output Power	<input type="checkbox"/> Refer as FCC KDB 558074, clause 9.1.1 Option 1 (RBW \geq EBW method). <input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 9.1.2 Option 2 (peak power meter for VBW \geq DTS BW)
<input checked="" type="checkbox"/> Maximum Conducted Output Power	[duty cycle \geq 98% or external video / power trigger] <input type="checkbox"/> Refer as FCC KDB 558074, clause 9.2.2.2 Method AVGSA-1 (spectral trace averaging). <input type="checkbox"/> Refer as FCC KDB 558074, clause 9.2.2.3 Method AVGSA-1 Alt. (slow sweep speed) duty cycle < 98% and average over on/off periods with duty factor <input type="checkbox"/> Refer as FCC KDB 558074, clause 9.2.2.4 Method AVGSA-2 (spectral trace averaging). <input type="checkbox"/> Refer as FCC KDB 558074, clause 9.2.2.5 Method AVGSA-2 Alt. (slow sweep speed) RF power meter and average over on/off periods with duty factor or gated trigger <input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 9.2.3 Method AVGPM (using an RF average power meter).
<input checked="" type="checkbox"/> For conducted measurement.	<input type="checkbox"/> The EUT supports single transmit chain and measurements performed on this transmit chain. <input type="checkbox"/> The EUT supports diversity transmitting and the results on transmit chain port 1 is the worst case. <input checked="" type="checkbox"/> The EUT supports multiple transmit chains using options given below: Refer as FCC KDB 662911, In-band power measurements. Using the measure-and-sum approach, measured all transmit ports individually. Sum the power (in linear power units e.g., mW) of all ports for each individual sample and save them. <input checked="" type="checkbox"/> If multiple transmit chains, EIRP calculation could be following as methods: $P_{total} = P_1 + P_2 + \dots + P_n$ (calculated in linear unit [mW] and transfer to log unit [dBm]) $EIRP_{total} = P_{total} + DG$

3.3.4 Test Setup





3.3.5 Test Result of Maximum Peak Conducted Output Power

Maximum Peak Conducted Output Power Result									
Condition			RF Output Power (dBm)						
Modulation Mode	N _{TX}	Freq. (MHz)	Chain Port 1	Chain Port 2	Sum Chain	Power Limit	DG (dBi)	EIRP Power	EIRP Limit
11b	2	2412	21.44	21.64	24.55	30.00	2.3	26.85	36.00
11b	2	2437	22.70	22.65	25.69	30.00	2.3	27.99	36.00
11b	2	2462	20.52	21.01	23.78	30.00	2.3	26.08	36.00
11g	2	2412	19.18	19.88	22.55	30.00	2.3	24.85	36.00
11g	2	2437	23.64	24.12	26.90	30.00	2.3	29.20	36.00
11g	2	2462	18.73	19.99	22.42	30.00	2.3	24.72	36.00
HT20	2	2412	18.66	19.14	21.92	30.00	2.3	24.22	36.00
HT20	2	2437	23.28	23.46	26.38	30.00	2.3	28.68	36.00
HT20	2	2462	18.05	19.33	21.75	30.00	2.3	24.05	36.00
HT40	2	2422	17.38	18.05	20.74	30.00	2.3	23.04	36.00
HT40	2	2437	19.61	20.11	22.88	30.00	2.3	25.18	36.00
HT40	2	2452	16.59	17.53	20.10	30.00	2.3	22.40	36.00
Result			Complied						

3.3.6 Test Result of Maximum Conducted Output Power

Maximum Conducted Output Power									
Condition			RF Output Power (dBm)						
Modulation Mode	N _{TX}	Freq. (MHz)	Chain Port 1	Chain Port 2	Sum Chain	Power Limit	DG (dBi)	EIRP Power	EIRP Limit
11b	2	2412	18.59	18.75	21.68	30.00	2.3	23.98	36.00
11b	2	2437	19.84	19.78	22.82	30.00	2.3	25.12	36.00
11b	2	2462	17.61	18.12	20.88	30.00	2.3	23.18	36.00
11g	2	2412	14.15	14.79	17.49	30.00	2.3	19.79	36.00
11g	2	2437	18.74	18.98	21.87	30.00	2.3	24.17	36.00
11g	2	2462	13.89	14.91	17.44	30.00	2.3	19.74	36.00
HT20	2	2412	13.65	14.24	16.97	30.00	2.3	19.27	36.00
HT20	2	2437	18.23	18.51	21.38	30.00	2.3	23.68	36.00
HT20	2	2462	13.28	14.39	16.88	30.00	2.3	19.18	36.00
HT40	2	2422	12.37	12.97	15.69	30.00	2.3	17.99	36.00
HT40	2	2437	14.44	15.16	17.83	30.00	2.3	20.13	36.00
HT40	2	2452	11.68	12.46	15.10	30.00	2.3	17.40	36.00
Result			Complied						



3.4 Power Spectral Density

3.4.1 Power Spectral Density Limit

Power Spectral Density Limit
<input checked="" type="checkbox"/> Power Spectral Density (PSD) $\leq 8 \text{ dBm/3kHz}$


3.4.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.4.3 Test Procedures


Test Method
<input checked="" type="checkbox"/> Peak power spectral density procedures that the same method as used to determine the conducted output power. If maximum peak conducted output power was measured to demonstrate compliance to the output power limit, then the peak PSD procedure below (Method PKPSD) shall be used. If maximum conducted output power was measured to demonstrate compliance to the output power limit, then one of the average PSD procedures shall be used, as applicable based on the following criteria (the peak PSD procedure is also an acceptable option).
<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 10.2 Method PKPSD (RBW=3-100kHz;detector=peak).. [duty cycle $\geq 98\%$ or external video / power trigger]
<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 10.3 Method AVGPSD-1 (spectral trace averaging).
<input type="checkbox"/> Refer as FCC KDB 558074, clause 10.4 Method AVGPSD-1 Alt. (slow sweep speed) duty cycle $< 98\%$ and average over on/off periods with duty factor
<input type="checkbox"/> Refer as FCC KDB 558074, clause 10.5 Method AVGPSD-2 (spectral trace averaging).
<input type="checkbox"/> Refer as FCC KDB 558074, clause 10.6 Method AVGPSD-2 Alt. (slow sweep speed)
<input checked="" type="checkbox"/> For conducted measurement.
<input type="checkbox"/> The EUT supports single transmit chain and measurements performed on this transmit chain.
<input type="checkbox"/> The EUT supports diversity transmitting and the results on transmit chain port 1 is the worst case.
<input checked="" type="checkbox"/> The EUT supports multiple transmit chains using options given below:
<input checked="" type="checkbox"/> Option 1: Measure and sum the spectra across the outputs. Refer as FCC KDB 662911, In-band power spectral density (PSD). Sample all transmit ports simultaneously using a spectrum analyzer for each transmit port. Where the trace bin-by-bin of each transmit port summing can be performed. (i.e., in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 and that from the first spectral bin of output 3, and so on up to the N_{TX} output to obtain the value for the first frequency bin of the summed spectrum.). Add up the amplitude (power) values for the different transmit chains and use this as the new data trace.
<input type="checkbox"/> Option 2: Measure and add $10 \log(N) \text{ dB}$, where N is the number of transmit chains. Refer as FCC KDB 662911, In-band power spectral density (PSD). Performed at each transmit chains and each transmit chains shall be compared with the limit have been reduced with $10 \log(N)$. Or each transmit chains shall be add $10 \log(N)$ to compared with the limit.

3.4.4 Test Setup



3.4.5 Test Result of Power Spectral Density


Condition			Power Spectral Density	
Modulation Mode	N _{TX}	Freq. (MHz)	Sum Chain (dBm/100kHz)	PSD Limit (dBm/3kHz)
11b	2	2412	-4.56	8.00
11b	2	2437	-3.17	8.00
11b	2	2462	-4.98	8.00
11g	2	2412	-12.17	8.00
11g	2	2437	-7.06	8.00
11g	2	2462	-12.30	8.00
HT20	2	2412	-13.16	8.00
HT20	2	2437	-9.09	8.00
HT20	2	2462	-13.35	8.00
HT40	2	2422	-17.63	8.00
HT40	2	2437	-15.02	8.00
HT40	2	2452	-17.91	8.00
Result			Complied	

**Worst Power Spectral Density Plots**

Note: Have been offset 15.2dBm for 3kHz data.

3.5 Transmitter Bandedge Emissions

3.5.1 Transmitter Radiated Bandedge Emissions Limit




3.5.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.5.3 Test Procedures

Test Method
<input checked="" type="checkbox"/> The average emission levels shall be measured in [duty cycle \geq 98 or duty factor].
<input checked="" type="checkbox"/> Refer as ANSI C63.10, clause 6.9.2.2 bandedge testing shall be performed at the lowest frequency channel and highest frequency channel within the allowed operating band.
<input checked="" type="checkbox"/> For the transmitter unwanted emissions shall be measured using following options below:
<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 11 for unwanted emissions into non-restricted bands.
<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 12 for unwanted emissions into restricted bands.
<input type="checkbox"/> Refer as FCC KDB 558074, clause 12.2.5.1 Option 1 (trace averaging for duty cycle $\geq 98\%$)
<input type="checkbox"/> Refer as FCC KDB 558074, clause 12.2.5.2 Option 2 (trace averaging + duty factor).
<input type="checkbox"/> Refer as FCC KDB 558074, clause 12.2.5.3 Option 3 (Reduced VBW $\geq 1/T$).
<input checked="" type="checkbox"/> Refer as ANSI C63.10, clause 4.1.4.2.3 (Reduced VBW). VBW $\geq 1/T$, where T is pulse time.
<input type="checkbox"/> Refer as ANSI C63.10, clause 4.1.4.2.4 average value of pulsed emissions.
<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 11.3 and 12.2.4 measurement procedure peak limit.
<input checked="" type="checkbox"/> For the transmitter bandedge emissions shall be measured using following options below:
<input type="checkbox"/> Refer as FCC KDB 558074, clause 13.3 for narrower resolution bandwidth (100kHz) using the band power and summing the spectral levels (i.e., 1 MHz).
<input checked="" type="checkbox"/> Refer as ANSI C63.10, clause 6.10 for band-edge testing.
<input type="checkbox"/> Refer as ANSI C63.10, clause 6.10.6.2 for marker-delta method for band-edge measurements.
<input checked="" type="checkbox"/> For radiated measurement, refer as FCC KDB 558074, clause 12.2.7.

3.5.4 Test Setup





3.5.5 Transmitter Radiated Bandedge Emissions

2400-2483.5MHz Transmitter Radiated Bandedge Emissions (Non-restricted Band)								
Modulation Mode	N _{TX}	Test Freq. (MHz)	In-band PSD [i] (dBuV/100 kHz)	Freq. (MHz)	Out-band PSD [o] (dBuV/100 kHz)	[i] – [o] (dB)	Limit (dB)	Pol.
11b	2	2412	107.82	2399.152	70.39	37.43	20	V
11b	2	2462	107.41	2525.800	60.89	46.52	20	V
11g	2	2412	99.66	2399.824	73.22	26.44	20	V
11g	2	2462	99.20	2515.600	60.71	38.49	20	V
HT20	2	2412	97.98	2399.824	68.48	29.50	20	V
HT20	2	2462	99.24	2524.000	60.37	38.87	20	V
HT40	2	2422	94.15	2399.760	64.95	29.20	20	V
HT40	2	2452	94.35	2542.880	60.36	33.99	20	V

Note 1: Measurement worst emissions of receive antenna polarization

2400-2483.5MHz Transmitter Radiated Bandedge Emissions (Restricted Band)										
Modulation Mode	N _{TX}	Freq. (MHz)	Measure Distance (m)	Freq. (MHz) PK	Level (dBuV/m) PK	Limit (dBuV/m) PK	Freq. (MHz) AV	Level (dBuV/m) AV	Limit (dBuV/m) AV	Pol.
11b	2	2412	3	2389.296	66.30	74	2387.728	52.81	54	V
11b	2	2462	3	2483.500	64.92	74	2484.600	52.15	54	V
11g	2	2412	3	2389.968	70.55	74	2389.968	52.31	54	V
11g	2	2462	3	2483.500	69.77	74	2483.500	52.92	54	V
HT20	2	2412	3	2389.968	68.48	74	2389.968	51.05	54	V
HT20	2	2462	3	2483.500	69.38	74	2483.500	52.82	54	V
HT40	2	2422	3	2388.408	66.40	74	2389.992	51.86	54	V
HT40	2	2452	3	2483.600	68.12	74	2483.840	52.67	54	V

Note 1: Measurement worst emissions of receive antenna polarization.



3.6 Transmitter Unwanted Emissions

3.6.1 Transmitter Radiated Unwanted Emissions Limit

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1: Test distance for frequencies at or above 30 MHz, measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

Note 2: Test distance for frequencies at below 30 MHz, measurements may be performed at a distance closer than the EUT limit distance; however, an attempt should be made to avoid making measurements in the near field. When performing measurements below 30 MHz at a closer distance than the limit distance, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two or more distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). The test report shall specify the extrapolation method used to determine compliance of the EUT.

Un-restricted Band Emissions Limit	
RF output power procedure	Limit (dB)
Peak output power procedure	20
Average output power procedure	30

Note 1: If the peak output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum measured in-band peak PSD level.

Note 2: If the average output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the power in any 100 kHz outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum measured in-band average PSD level.

3.6.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.




3.6.3 Test Procedures

Test Method
<input checked="" type="checkbox"/> Measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).
<input checked="" type="checkbox"/> The average emission levels shall be measured in [duty cycle \geq 98 or duty factor].
<input checked="" type="checkbox"/> For the transmitter unwanted emissions shall be measured using following options below:
<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 11 for unwanted emissions into non-restricted bands.
<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 12 for unwanted emissions into restricted bands.
<input type="checkbox"/> Refer as FCC KDB 558074, clause 12.2.5.1 Option 1 (trace averaging for duty cycle $\geq 98\%$)
<input type="checkbox"/> Refer as FCC KDB 558074, clause 12.2.5.2 Option 2 (trace averaging + duty factor).
<input type="checkbox"/> Refer as FCC KDB 558074, clause 12.2.5.3 Option 3 (Reduced VBW $\geq 1/T$).
<input checked="" type="checkbox"/> Refer as ANSI C63.10, clause 4.1.4.2.3 (Reduced VBW). VBW $\geq 1/T$, where T is pulse time.
<input type="checkbox"/> Refer as ANSI C63.10, clause 4.1.4.2.4 average value of pulsed emissions.
<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 11.3 and 12.2.4 measurement procedure peak limit.
<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 12.2.3 measurement procedure Quasi-Peak limit.
<input checked="" type="checkbox"/> For radiated measurement, refer as FCC KDB 558074, clause 12.2.7.
<input checked="" type="checkbox"/> Refer as ANSI C63.10, clause 6.4 for radiated emissions below 30 MHz and test distance is 3m.
<input checked="" type="checkbox"/> Refer as ANSI C63.10, clause 6.5 for radiated emissions 30 MHz to 1 GHz and test distance is 3m.
<input checked="" type="checkbox"/> Refer as ANSI C63.10, clause 6.6 for radiated emissions above 1 GHz and test distance is 3m.


3.6.4 Test Setup

Transmitter Radiated Unwanted Emissions Below 1GHz



Magnetic field tests shall be performed in the frequency range of 9 kHz to 30 MHz using a calibrated loop antenna. Electric field tests shall be performed in the frequency range of 30 MHz to 1000 MHz using a calibrated bi-log antenna.

Transmitter Radiated Unwanted Emissions Above 1GHz




Electric field tests shall be performed in the frequency range of 1 GHz to 10th harmonic of highest fundamental frequency or 40 GHz using a calibrated horn antenna.


3.6.5 Transmitter Radiated Unwanted Emissions (Below 30MHz)

All amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.




3.6.6 Transmitter Radiated Unwanted Emissions (Below 1GHz)











3.6.7 Transmitter Radiated Unwanted Emissions (Above 1GHz)





























Transmitter Radiated Unwanted Emissions (Above 1GHz)									
Modulation Mode		11g		Test Freq. (MHz)		2437			
N _{TX}		2		Polarization		H			
Level (dBuV/m)									Date: 2015-06-18
1	4874.000	33.57	-20.43	54.00	28.20	33.31	4.51	32.45	Average
2	4874.000	47.93	-26.07	74.00	42.56	33.31	4.51	32.45	Peak
3	7311.000	36.90	-17.10	54.00	27.71	36.11	5.75	32.67	Average
4	7311.000	50.87	-23.13	74.00	41.68	36.11	5.75	32.67	Peak
5	9748.000	53.38			41.20	38.61	6.71	33.14	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.
 Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (111.97 dBuV/m).
 Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.












Transmitter Radiated Unwanted Emissions (Above 1GHz)																																																																															
Modulation Mode		HT20		Test Freq. (MHz)		2437																																																																									
N _{TX}	2			Polarization		V																																																																									
Level (dBuV/m)									Date: 2015-06-18																																																																						
<table border="1"> <thead> <tr> <th></th><th>Freq</th><th>Level</th><th>Over Limit</th><th>Limit</th><th>Read</th><th>Antenna</th><th>Cable</th><th>Preamp</th><th></th></tr> <tr> <th></th><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr> </thead> <tbody> <tr> <td>1</td><td>4874.000</td><td>33.50</td><td>-20.50</td><td>54.00</td><td>28.13</td><td>33.31</td><td>4.51</td><td>32.45</td><td>Average</td></tr> <tr> <td>2</td><td>4874.000</td><td>48.15</td><td>-25.85</td><td>74.00</td><td>42.78</td><td>33.31</td><td>4.51</td><td>32.45</td><td>Peak</td></tr> <tr> <td>3</td><td>7311.000</td><td>36.98</td><td>-17.02</td><td>54.00</td><td>27.79</td><td>36.11</td><td>5.75</td><td>32.67</td><td>Average</td></tr> <tr> <td>4</td><td>7311.000</td><td>51.17</td><td>-22.83</td><td>74.00</td><td>41.98</td><td>36.11</td><td>5.75</td><td>32.67</td><td>Peak</td></tr> <tr> <td>5</td><td>9748.000</td><td>54.25</td><td></td><td></td><td>42.07</td><td>38.61</td><td>6.71</td><td>33.14</td><td>Peak</td></tr> </tbody> </table>											Freq	Level	Over Limit	Limit	Read	Antenna	Cable	Preamp			MHz	dBuV/m	dB	dBuV/m	Level	Factor	Loss	Factor	Remark	1	4874.000	33.50	-20.50	54.00	28.13	33.31	4.51	32.45	Average	2	4874.000	48.15	-25.85	74.00	42.78	33.31	4.51	32.45	Peak	3	7311.000	36.98	-17.02	54.00	27.79	36.11	5.75	32.67	Average	4	7311.000	51.17	-22.83	74.00	41.98	36.11	5.75	32.67	Peak	5	9748.000	54.25			42.07	38.61	6.71	33.14	Peak
	Freq	Level	Over Limit	Limit	Read	Antenna	Cable	Preamp																																																																							
	MHz	dBuV/m	dB	dBuV/m	Level	Factor	Loss	Factor	Remark																																																																						
1	4874.000	33.50	-20.50	54.00	28.13	33.31	4.51	32.45	Average																																																																						
2	4874.000	48.15	-25.85	74.00	42.78	33.31	4.51	32.45	Peak																																																																						
3	7311.000	36.98	-17.02	54.00	27.79	36.11	5.75	32.67	Average																																																																						
4	7311.000	51.17	-22.83	74.00	41.98	36.11	5.75	32.67	Peak																																																																						
5	9748.000	54.25			42.07	38.61	6.71	33.14	Peak																																																																						
Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.) Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical) Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition. Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (111.16 dBuV/m). Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.																																																																															



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT20	Test Freq. (MHz)	2437
N _{TX}	2	Polarization	H



Freq	Level	Over Limit	Limit Line	Read Antenna		Cable Loss	Preamp Factor	Remark	
				MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m
1	4874.000	33.43	-20.57	54.00	28.06	33.31	4.51	32.45	Average
2	4874.000	47.56	-26.44	74.00	42.19	33.31	4.51	32.45	Peak
3	7311.000	37.03	-16.97	54.00	27.84	36.11	5.75	32.67	Average
4	7311.000	50.73	-23.27	74.00	41.54	36.11	5.75	32.67	Peak
5	9748.000	54.38			42.20	38.61	6.71	33.14	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.


Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (111.16 dBuV/m).

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT20	Test Freq. (MHz)	2462
N _{TX}	2	Polarization	V



Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Remark
		Limit	Line	Level	Factor	Loss	Factor	
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	4924.000	33.47	-20.53	54.00	27.97	33.39	4.55	32.44 Average
2	4924.000	47.39	-26.61	74.00	41.89	33.39	4.55	32.44 Peak
3	7386.000	37.72	-16.28	54.00	28.31	36.33	5.78	32.70 Average
4	7386.000	51.72	-22.28	74.00	42.31	36.33	5.78	32.70 Peak
5	9848.000	54.95			42.56	38.75	6.77	33.13 Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (105.89 dBuV/m).

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.




Transmitter Radiated Unwanted Emissions (Above 1GHz)																																																																															
Modulation Mode		HT20		Test Freq. (MHz)		2462																																																																									
N _{TX}		2		Polarization		H																																																																									
Level (dB _{UV} /m)									Date: 2015-06-18																																																																						
<table border="1"> <thead> <tr> <th></th><th>Freq</th><th>Level</th><th>Over Limit</th><th>Limit Line</th><th>Read Antenna Level</th><th>Antenna Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Remark</th></tr> <tr> <th></th><th>MHz</th><th>dB_{UV}/m</th><th>dB</th><th>dB_{UV}/m</th><th>dB_{UV}</th><th>dB/m</th><th>dB</th><th>dB</th><th></th></tr> </thead> <tbody> <tr> <td>1</td><td>4924.000</td><td>33.51</td><td>-20.49</td><td>54.00</td><td>28.01</td><td>33.39</td><td>4.55</td><td>32.44</td><td>Average</td></tr> <tr> <td>2</td><td>4924.000</td><td>47.74</td><td>-26.26</td><td>74.00</td><td>42.24</td><td>33.39</td><td>4.55</td><td>32.44</td><td>Peak</td></tr> <tr> <td>3</td><td>7386.000</td><td>37.65</td><td>-16.35</td><td>54.00</td><td>28.24</td><td>36.33</td><td>5.78</td><td>32.70</td><td>Average</td></tr> <tr> <td>4</td><td>7386.000</td><td>52.02</td><td>-21.98</td><td>74.00</td><td>42.61</td><td>36.33</td><td>5.78</td><td>32.70</td><td>Peak</td></tr> <tr> <td>5</td><td>9848.000</td><td>54.72</td><td></td><td></td><td>42.33</td><td>38.75</td><td>6.77</td><td>33.13</td><td>Peak</td></tr> </tbody> </table>											Freq	Level	Over Limit	Limit Line	Read Antenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark		MHz	dB _{UV} /m	dB	dB _{UV} /m	dB _{UV}	dB/m	dB	dB		1	4924.000	33.51	-20.49	54.00	28.01	33.39	4.55	32.44	Average	2	4924.000	47.74	-26.26	74.00	42.24	33.39	4.55	32.44	Peak	3	7386.000	37.65	-16.35	54.00	28.24	36.33	5.78	32.70	Average	4	7386.000	52.02	-21.98	74.00	42.61	36.33	5.78	32.70	Peak	5	9848.000	54.72			42.33	38.75	6.77	33.13	Peak
	Freq	Level	Over Limit	Limit Line	Read Antenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark																																																																						
	MHz	dB _{UV} /m	dB	dB _{UV} /m	dB _{UV}	dB/m	dB	dB																																																																							
1	4924.000	33.51	-20.49	54.00	28.01	33.39	4.55	32.44	Average																																																																						
2	4924.000	47.74	-26.26	74.00	42.24	33.39	4.55	32.44	Peak																																																																						
3	7386.000	37.65	-16.35	54.00	28.24	36.33	5.78	32.70	Average																																																																						
4	7386.000	52.02	-21.98	74.00	42.61	36.33	5.78	32.70	Peak																																																																						
5	9848.000	54.72			42.33	38.75	6.77	33.13	Peak																																																																						
Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.) Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical) Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition. Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (105.89 dB _{UV} /m). Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.																																																																															







Transmitter Radiated Unwanted Emissions (Above 1GHz)									
Modulation Mode		HT40		Test Freq. (MHz)		2422			
N _{TX}		2		Polarization		H			
Level (dBuV/m)									Date: 2015-06-18
1	4844.000	33.47	-20.53	54.00	28.17	33.25	4.51	32.46	Average
2	4844.000	47.10	-26.90	74.00	41.80	33.25	4.51	32.46	Peak
3	7266.000	36.39	-17.61	54.00	27.28	36.02	5.74	32.65	Average
4	7266.000	50.69	-23.31	74.00	41.58	36.02	5.74	32.65	Peak
5	9688.000	54.22			42.17	38.50	6.69	33.14	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.
 Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (101.81 dBuV/m).
 Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.










Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT40	Test Freq. (MHz)	2452
N _{TX}	2	Polarization	H



Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Remark
		Limit	Line	Level	Factor	Loss	Factor	
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	4904.000	33.11	-20.89	54.00	27.67	33.36	4.53	32.45 Average
2	4904.000	47.06	-26.94	74.00	41.62	33.36	4.53	32.45 Peak
3	7356.000	37.13	-16.87	54.00	27.82	36.24	5.76	32.69 Average
4	7356.000	51.10	-22.90	74.00	41.79	36.24	5.76	32.69 Peak
5	9808.000	54.34			42.02	38.70	6.75	33.13 Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (102.32 dBuV/m).

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.



4 Test Equipment and Calibration Data

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMC Receiver	R&S	ESCS 30	100174	9kHz ~ 2.75GHz	Apr. 15, 2015	AC Conduction
LISN	SCHWARZBECK MESS-ELEKTRONIK	NSLK 8127	8127-477	9kHz ~ 30MHz	Jan. 22, 2015	AC Conduction
RF Cable-CON	HUBER+SUHNER	RG213/U	07611832020001	9kHz ~ 30MHz	Oct. 31, 2014	AC Conduction
EMI Filter	LINDGREN	LRE-2030	2651	< 450 Hz	NCR	AC Conduction

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Spectrum Analyzer	R&S	FSV 40	101500	9KHz~40GHz	May 05, 2015	RF Conducted
Temp. and Humidity Chamber	Giant Force	GTH-225-20-SP-SD	MAA1112-007	-20 ~ 100°C	Apr. 07, 2015	RF Conducted
Signal Generator	R&S	SMR40	100116	10MHz ~ 40GHz	Jul. 31, 2014	RF Conducted
Power Sensor	Anritsu	MA2411B	0917017	300MHz ~ 40GHz	Feb. 17, 2015	RF Conducted
Power Meter	Anritsu	ML2495A	0949003	300MHz ~ 40GHz	Feb. 17, 2015	RF Conducted

Note: Calibration Interval of instruments listed above is one year.



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	30MHz ~ 1GHz 3m	Nov. 29, 2014	Radiation Emission
Amplifier	HP	8447D	2944A08033	10kHz ~ 1.3GHz	May 11, 2015	Radiation Emission
Amplifier	Agilent	8449B	3008A02120	1GHz ~ 26.5GHz	Sep. 01, 2014	Radiation Emission
Spectrum	R&S	FSP40	100004	9kHz ~ 40GHz	Apr. 02, 2015	Radiation Emission
Bilog Antenna	SCHAFFNER	CBL 6112D	22237	30MHz ~ 1GHz	Sep. 20, 2014	Radiation Emission
Horn Antenna	AARONIA AG	POWERLOG 70180	05192	1GHz ~ 18GHz	May 01, 2015	Radiation Emission
RF Cable-R03m	Jye Bao	RG142	CB021	9kHz ~ 1GHz	Nov. 15, 2014	Radiation Emission
RF Cable-high	SUHNER	SUCOFLEX 106	03CH03-HY	1GHz ~ 40GHz	Dec. 12, 2014	Radiation Emission
Turn Table	EM Electronics	EM Electronics	060615	0 ~ 360 degree	N/A	Radiation Emission
Antenna Mast	MF	MF-7802	MF780208179	1 ~ 4 m	N/A	Radiation Emission

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Loop Antenna	TESEQ	HLA 6120	31244	9 kHz~30 MHz	Feb. 02, 2015	Radiation Emission

Note: Calibration Interval of instruments listed above is two years.