

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan

District, Shenzhen, China 518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594 Report No.: SZEM120500256102

Email: ee.shenzhen@sgs.com Page: 1 of 5

SAR Evaluation Report

Application No.: SZEM1205002561IT

Applicant: ARCHOS SA

Manufacturer: ARCHOS SA

Product Name: Home Tablet

Model No.(EUT): AC97CA

FCC ID: SOVAC97CA

Standard: FCC CFR Title 47 Part 1.1307

FCC CFR Title 47 Part 2.1093

Date of Receipt: 2012-05-17

Date of Test: 2012-05-21 to 2012-06-14

Date of Issue: 2012-07-05

Test Result: PASS*

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Jack Zhang EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM120500256102

Page: 2 of 5

2 Contents

1	COVE	R PAGE	1
-	00.2		
2	CON	ITENTS	2
_	001		
3	GEN	IERAL INFORMATION	3
Ū			
	3.1	CLIENT INFORMATION	
	3.2	GENERAL DESCRIPTION OF EUT	3
	3.3	TEST LOCATION	
	3.4	TEST FACILITY	
	3.5	DEVIATION FROM STANDARDS	4
	3.6	ABNORMALITIES FROM STANDARD CONDITIONS	4
	3.7	OTHER INFORMATION REQUESTED BY THE CUSTOMER	4
	CAD	EVALUATION	_
4	SAR		
	4.1	RF EXPOSURE COMPLIANCE REQUIREMENT	5
	4.1.1	1 Standard requirement	5
	4.1.2	1 Standard requirement2 Limits :	5
		B FUT RF Exposure	



Report No.: SZEM120500256102

Page: 3 of 5

3 General Information

3.1 Client Information

Applicant:	ARCHOS SA
Address of Applicant:	12,Rue Ampere 91430 Igny France
Manufacturer:	ARCHOS SA
Address of Manufacturer:	12,Rue Ampere 91430 Igny France

3.2 General Description of EUT

Product Name:	Home Tablet
Model No.:	AC97CA
Trade Mark:	ARCHOS
Operation Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz
	IEEE 802.11n(HT40): 2422MHz to 2452MHz
Channel Numbers:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels
	IEEE 802.11n HT40: 7 Channels
Channel Separation:	5MHz
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK)
	IEEE for 802.11g : OFDM(64QAM, 16QAM, QPSK, BPSK)
	IEEE for 802.11n(HT20 and HT40): OFDM (64QAM, 16QAM,
	QPSK,BPSK)
Sample Type:	Portable production
Test Power Grade:	12dBm (manufacturer declare)
Test Software of EUT:	Wi-Fi Android Test (manufacturer declare)
Antenna Type and Gain:	Type: Integral
	Gain: 0dBi
Power Supply:	Adapter: AC ADAPTOR MODEL: HNO090200X INPUT: AC 100-240V-50/60Hz 0.6A MAX OUTPUT: 9.0V=2.0A

3.3 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch E&E Lab No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

No tests were sub-contracted.

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM120500256102

Page: 4 of 5

3.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

VCCI

The 3m Semi-anechoic chamber, Full-anechoic Chamber and Shielded Room (7.5m x 4.0m x 3.0m) of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2197, G-416, T-1153 and C-2383 respectively.

• FCC – Registration No.: 556682

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

Industry Canada (IC)

The 3m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1.

3.5 Deviation from Standards

None.

3.6 Abnormalities from Standard Conditions

None.

3.7 Other Information Requested by the Customer

None.



Report No.: SZEM120500256102

Page: 5 of 5

4 SAR Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Standard Requirement

15.247(b)(4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6dBi. Except as shown in paragraph (c) of this section. if transmitting antennas of directional gain greater than 6dBi are used. the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1). (b)(2). and (b)(3) of this section. as appropriate. by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.1.2 Limits

According to KDB447498 D01, SAR evaluation is typically not required when the maximum transmitter and antenna output power are ≤ 60/f(GHz) mW.

4.1.3 EUT RF Exposure

The Max Conducted Peak Output Power is 11.65dBm(14.62177mW) in lowest channel;

The best case gain of the antenna is 0dBi.

0dBi logarithmic terms convert to numeric result is nearly 1.

According to the formula. calculate the EIRP test result:

EIRP= P x G = 14.62177mW x 1 = 14.62177mW ①

SAR requirement:

S=60 / f(GHz) = 60/2.402 = 24.98mW ②;

(1) < (2).

So the SAR report is not required.