



RF TEST REPORT

Applicant ZTE Corporation

FCC ID SRQ-DL2XLB28

Product LTE/WCDMA/GSM (GPRS) Multi-Mode
Digital Mobile Phone

Model ZTE BLADE A602、ZTE Blade A602、
BLADE A602、Blade A602、DL2 XL、
Digicel DL2 XL、DIGICEL DL2 XL

Report No. RXA1710-0351RF04

Issue Date November 21, 2017

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC CFR47 Part 15C (2017)**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Performed by: Xianqing Li

Approved by: Kai Xu

TA Technology (Shanghai) Co., Ltd.

No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000



TABLE OF CONTENT

1. Test Laboratory	4
1.1. Notes of the test report.....	4
1.2. Test facility	4
1.3. Testing Location.....	5
2. General Description of Equipment under Test.....	6
3. Applied Standards	8
4. Test Configuration	9
5. Test Case Results	10
5.1. Average Power Output –Conducted.....	10
5.2. 6dB Bandwidth	13
5.3. Band Edge	18
5.4. Power Spectral Density	21
5.5. Spurious RF Conducted Emissions.....	26
5.6. Radiated Emissions in the Restricted Band	33
5.7. Radiates Emission	38
5.8. Conducted Emission	72
6. Main Test Instruments.....	74
ANNEX A: EUT Appearance and Test Setup	75
A.1 EUT Appearance	75
A.2 Test Setup	78



Summary of measurement results

Number	Summary of measurements of results	Clause in FCC rules	Verdict
1	Maximum Average conducted output power	15.247(b)(3)	PASS
2	6 dB bandwidth	15.247(a)(2)	PASS
3	Power spectral density	15.247(e)	PASS
4	Band Edge	15.247(d)	PASS
5	Spurious RF Conducted Emissions	15.247(d)	PASS
6	Radiated Emissions in restricted frequency bands	15.247(d),15.205,15.209	PASS
7	Radiated Emissions	15.247(d),15.205,15.209	PASS
8	Conducted Emissions	15.207	PASS
Date of Testing: October 31 2017~ November 11, 2017			

1. Test Laboratory

1.1. Notes of the test report

This report shall not be reproduced in full or partial, without the written approval of **TA technology (shanghai) co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above. This report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.

1.2. Test facility

CNAS (accreditation number: L2264)

TA Technology (Shanghai) Co., Ltd. has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS).

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

IC (recognition number is 8510A)

TA Technology (Shanghai) Co., Ltd. has been listed by industry Canada to perform electromagnetic emission measurement.

VCCI (recognition number is C-4595, T-2154, R-4113, G-10766)

TA Technology (Shanghai) Co., Ltd. has been listed by industry Japan to perform electromagnetic emission measurement.

A2LA (Certificate Number: 3857.01)

TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.



1.3. Testing Location

Company: TA Technology (Shanghai) Co., Ltd.
Address: No.145, Jintang Rd, Tangzhen Industry Park, Pudong
City: Shanghai
Post code: 201201
Country: P. R. China
Contact: Xu Kai
Telephone: +86-021-50791141/2/3
Fax: +86-021-50791141/2/3-8000
Website: <http://www.ta-shanghai.com>
E-mail: xukai@ta-shanghai.com



2. General Description of Equipment under Test

Client Information

Applicant	ZTE Corporation
Applicant address	ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China
Manufacturer	ZTE Corporation
Manufacturer address	ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

**General information**

EUT Description	
Model	ZTE BLADE A602、 ZTE Blade A602、 BLADE A602、 Blade A602、 DL2 XL、 Digicel DL2 XL、 DIGICEL DL2 XL
IMEI	866112030002964
Hardware Version	MB V1.0
Software Version	DIG_DL2XL_B28_V1.0
Power Supply	Battery/AC adapter
Antenna Type	Internal Antenna
Antenna Connector	A permanently attached antenna (meet with the standard FCC Part 15.203 requirement)
Antenna Gain	WiFi Antenna: -4.49 dBi BLE Antenna: -4.49 dBi
additional beamforming gain	0 dB
Test Mode	Bluetooth(Low Energy) 802.11b 802.11g, 802.11n(HT20/HT40);
Modulation Type	BLE :GFSK 802.11b: DSSS; 802.11g/n(HT20/HT40): OFDM
Max. Conducted Power	Wi-Fi 2.4G : 14.55 dBm BLE : 3.79 dBm
Operating Frequency Range(s)	802.11b/g/n(HT20): 2412 ~ 2462 MHz 802.11n(HT40): 2422 ~ 2452 MHz BLE: 2402 ~2480 MHz
EUT Accessory	
Adapter	Manufacturer: DOKOCOM Model: LPL-A008050150Z
Battery	Manufacturer: ZHENGZHOU BAK BATTERY CO., LTD Model: Li3830T43P6h856337
Earphone	Manufacturer: Shen zhen FDC Electronics Co.,Ltd. Model: DEM-93
USB Extend Cable	71cm Cable, unshield
Note: The information of the EUT is declared by the manufacturer.	



3. Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

Test standards

- **FCC CFR47 Part 15C (2017) Radio Frequency Devices**
- **ANSI C63.10 (2013)**
- **KDB 558074 D01 DTS Meas Guidance v04**

4. Test Configuration

Test Mode

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

The radiated emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis). The worst emission was found in lie-down position (X axis) and the worst case was recorded.

In order to find the worst case condition, Pre-tests are needed at the presence of different data rate. Preliminary tests have been done on all the configuration for confirming worst case. Data rate below means worst-case rate of each test item.

Worst-case data rates are shown as following table.

Band	Data Rate
Bluetooth(Low Energy)	1Mbps
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0

5. Test Case Results

5.1. Average Power Output –Conducted


Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Methods of Measurement

During the process of the testing, The EUT was connected to Spectrum Analyzer with a known loss. The EUT is max power transmission with proper modulation. The Average detector is used. We use Maximum Average Conducted Output Power Level Method in KDB 558074 D01 for this test.

Test Setup



Limits

Rule Part 15.247 (b) (3) specifies that " For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz: 1 Watt."

Average Output Power	$\leq 1W$ (30dBm)
----------------------	-------------------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 0.44$ dB.

Test Results

Packet Type	Single Antenna Power Index		
	CH1	CH6	CH11
802.11b	16	16	16
802.11g	13.5	13.5	13.5
802.11n HT20	12.5	12.5	12.5
Packet Type	CH3	CH6	CH9
802.11n HT40	12.5	12.5	12.5

Band	T _{on} (ms)	T _(on+off) (ms)	Duty cycle	Duty cycle correction Factor(dB)
802.11b	8.39	8.42	1.00	NA
802.11g	1.39	1.42	0.98	0.09
802.11n HT20	1.30	1.34	0.97	0.13
802.11n HT40	0.64	0.68	0.94	0.26
BLE	0.38	0.62	0.613	2.126
Note: when Duty cycle>0.98, Duty cycle correction Factor not required.				



Network Standards	Carrier frequency (MHz)	Read Value (dBm)	Average Output Power(dBm)	Limit (dBm)	Conclusion
802.11b	2412	14.14	14.14	30	PASS
	2437	14.55	14.55	30	PASS
	2462	14.09	14.09	30	PASS
802.11g	2412	11.58	11.67	30	PASS
	2437	11.75	11.84	30	PASS
	2462	11.82	11.91	30	PASS
802.11n HT20	2412	10.40	10.53	30	PASS
	2437	10.74	10.87	30	PASS
	2462	10.80	10.93	30	PASS
802.11n HT40	2422	10.46	10.72	30	PASS
	2437	10.31	10.57	30	PASS
	2452	10.57	10.83	30	PASS
Bluetooth (Low Energy)	2402	1.66	3.79	30	PASS
	2440	1.39	3.52	30	PASS
	2480	1.59	3.72	30	PASS

Note:Output Power=Read Value+Duty cycle correction factor

5.2. 6dB Bandwidth


Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The EUT was connected to the spectrum analyzer through an external attenuator (20dB) and a known loss cable. RBW is set to 100 kHz; VBW is set to 300 kHz on spectrum analyzer.

Test Setup



Limits

Rule Part 15.247 (a) (2) specifies that “Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.”

minimum 6 dB bandwidth	≥ 500 kHz
------------------------	-----------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 936$ Hz.

**Test Results:**

Network Standards	Carrier frequency (MHz)	99% bandwidth (MHz)	Minimum 6 dB bandwidth (MHz)	Limit (kHz)	Conclusion
802.11b	2412	11.965	8.596	500	PASS
	2437	12.537	10.060	500	PASS
	2462	12.034	9.070	500	PASS
802.11g	2412	16.378	15.720	500	PASS
	2437	16.600	16.440	500	PASS
	2462	16.416	16.060	500	PASS
802.11n HT20	2412	17.535	16.340	500	PASS
	2437	17.724	17.670	500	PASS
	2462	17.550	17.140	500	PASS
802.11n HT40	2422	35.772	35.160	500	PASS
	2437	36.296	36.370	500	PASS
	2452	35.756	35.130	500	PASS
Bluetooth (Low Energy)	2402	1.0428	0.7030	500	PASS
	2440	1.0480	0.7024	500	PASS
	2480	1.0441	0.7024	500	PASS

802.11b, Carrier frequency (MHz): 2412



802.11g, Carrier frequency (MHz): 2412



802.11b, Carrier frequency (MHz): 2437




802.11g, Carrier frequency (MHz): 2437



802.11b, Carrier frequency (MHz): 2462



802.11g, Carrier frequency (MHz): 2462






802.11n(HT20), Carrier frequency (MHz): 2412



802.11n(HT40), Carrier frequency (MHz): 2422



802.11n(HT20), Carrier frequency (MHz): 2437



802.11n(HT40), Carrier frequency (MHz): 2437



802.11n(HT20), Carrier frequency (MHz):2462



802.11n(HT40), Carrier frequency (MHz):2452





BLE Carrier frequency (MHz): 2402



BLE Carrier frequency (MHz): 2440



BLE Carrier frequency (MHz): 2480



5.3. Band Edge


Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The EUT was connected to the spectrum analyzer through an external attenuator (20dB) and a known loss cable the band edge of the lowest and highest channels were measured. The peak detector is used and RBW is set to 100 kHz and VBW is set to 300 kHz on spectrum analyzer. Spectrum analyzer plots are included on the following pages.

Test Setup



Limits

Rule Part 15.247(d) specifies that “In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.”

Measurement Uncertainty


The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$.

Frequency	Uncertainty
2GHz-3GHz	1.407 dB




Test Results: PASS


802.11b, Channel No.: 1




802.11b, Channel No.: 11




802.11g, Channel No.: 1




802.11g, Channel No.: 11



802.11n(HT20), Channel No.: 1



802.11n(HT20), Channel No.: 11




802.11n(HT40), Channel No.: 3



802.11n(HT40), Channel No.: 9





5.4. Power Spectral Density

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa


Method of Measurement

The EUT was connected to the spectrum analyzer through an external attenuator (20dB) and a known loss cable.

RBW is set to 3 kHz and VBW is set to 10 kHz for BLE/ Wi-Fi 2.4G on spectrum analyzer.

Set the span to 1.5 times the DTS channel bandwidth. Sweep time = auto couple. Trace mode = max hold. The Average power spectral density is recorded.

Test setup



Limits

Rule Part 15.247(e) specifies that” For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. ”

Limits	≤ 8 dBm / 3kHz
--------	----------------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 0.75\text{dB}$.

**Test Results:**

Network Standards	Channel Number	Read Value (dBm)	Power Spectral Density (dBm / 3kHz)	Limit (dBm / 3kHz)	Conclusion
802.11b	1	-18.46	-18.46	8	PASS
	6	-18.21	-18.21	8	PASS
	11	-18.17	-18.17	8	PASS
802.11g	1	-22.84	-22.75	8	PASS
	6	-23.20	-23.11	8	PASS
	11	-22.77	-22.68	8	PASS
802.11n HT20	1	-23.74	-23.61	8	PASS
	6	-24.27	-24.14	8	PASS
	11	-23.91	-23.78	8	PASS
802.11n HT40	3	-26.10	-25.84	8	PASS
	6	-25.66	-25.40	8	PASS
	9	-25.44	-25.18	8	PASS
Bluetooth (Low Energy)	0	-15.65	-13.52	8	PASS
	19	-16.17	-14.04	8	PASS
	39	-12.65	-10.52	8	PASS

Note: Power Spectral Density =Read Value+Duty cycle correction factor



802.11b, Channel No.: 1




802.11g, Channel No.: 1



802.11b, Channel No.: 6



802.11g, Channel No.: 6



802.11b, Channel No.: 11



802.11g, Channel No.: 11





802.11n(HT20), Channel No. 1



802.11n(HT40), Channel No. 3




802.11n(HT20), Channel No. 6



802.11n(HT40), Channel No. 6




802.11n(HT20), Channel No. 11



802.11n(HT40), Channel No. 9




BLE, Channel No.: 0



BLE, Channel No.: 19



BLE, Channel No.: 39



5.5. Spurious RF Conducted Emissions

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The EUT was connected to the spectrum analyzer with a known loss. The spectrum analyzer scans from 30MHz to the 10th harmonic of the carrier. The peak detector is used. Set RBW to100kHz and VBW to 300 kHz, Sweep is set to ATUO.

The test is in transmitting mode.

Test setup



Limits

Rule Part 15.247(d) pacifies that “In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.”

Network Standards	Carrier frequency (MHz)	Reference value (dBm)	Limit
802.11b	2412	1.360	-18.640
	2437	1.604	-18.396
	2462	1.823	-18.177
802.11g	2412	0.883	-19.117
	2437	-2.997	-22.997
	2462	-1.784	-21.784
802.11n HT20	2412	-6.239	-26.239
	2437	-3.56	-23.560
	2462	-4.924	-24.924
802.11n HT40	2422	-6.169	-26.169
	2437	-6.742	-26.742
	2452	-5.246	-25.246
Bluetooth (Low Energy)	2402	1.810	-18.190
	2440	1.673	-18.327
	2480	3.108	-16.892




Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$.


Frequency	Uncertainty
100kHz-2GHz	0.684 dB
2GHz-26GHz	1.407 dB




Test Results:




802.11b CH1 30MHz to 18GHz




802.11b CH1 18GHz to 26.5GHz




802.11b CH6 30MHz to 18GHz




802.11b CH6 18GHz to 26.5GHz




802.11b CH11 30MHz to 18GHz




802.11b CH11 18GHz to 26.5GHz




802.11g CH1 30MHz to 18GHz




802.11g CH1 18GHz to 26.5GHz




802.11g CH6 30MHz to 18GHz




802.11g CH6 18GHz to 26.5GHz




802.11g CH11 30MHz to 18GHz




802.11g CH11 18GHz to 26.5GHz




802.11n (HT20) CH1 30MHz to 18GHz




802.11n (HT20) CH1 18GHz to 26.5GHz




802.11n (HT20) CH6 30MHz to 18GHz




802.11n (HT20) CH6 18GHz to 26.5GHz




802.11n (HT20) CH11 30MHz to 18GHz




802.11n (HT20) CH11 18GHz to 26.5GHz




802.11n (HT40) CH3 30MHz to 18GHz




802.11n (HT40) CH3 18GHz to 26.5GHz




802.11n (HT40) CH6 30MHz to 18GHz




802.11n (HT40) CH6 18GHz to 26.5GHz




802.11n (HT40) CH9 30MHz to 18GHz




802.11n (HT40) CH9 18GHz to 26.5GHz




BLE CH0 30MHz to 18GHz




BLE CH0 18GHz to 26.5GHz




BLE CH19 30MHz to 18GHz



BLE CH19 18GHz to 26.5GHz



BLE CH39 30MHz to 18GHz



BLE CH39 18GHz to 26.5GHz

5.6. Radiated Emissions in the Restricted Band

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The Equipment Under Test (EUT) was set up on a non-conductive table in the semi-anechoic chamber. The test was performed at the distance of 3 m between the EUT and the receiving antenna. The turntable shall be rotated from 0 to 360 degrees for detecting the maximum of radiated spurious signal level. The measurements shall be repeated with orthogonal polarization of the test antenna. RBW is set to 100kHz. The data of cable loss and antenna factor has been calibrated in full testing frequency range before the testing. Sweep the whole frequency band through the range from 9kHz to the 10th harmonic of the carrier, and the emissions less than 20 dB below the permissible value are reported.

Set the spectrum analyzer in the following:


- (a) PEAK: RBW=1MHz /VBW=3MHz / Sweep=AUTO
- (b) AVERAGE: RBW=1MHz /VBW=3MHz / Sweep=AUTO

This setting method can refer to **KDB 558074**.

The field strength of spurious emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis). The worst emission was found in stand-up position (Y axis) and the antenna is vertical.

The test is in transmitting mode.

Test setup



Note: Area side: 2.4mX3.6m

Limits

Spurious Radiated Emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)
13.36 - 13.41			

Limit in restricted band

Frequency of emission (MHz)	Field strength(uV/m)	Field strength(dBuV/m)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above960	500	54

§15.35(b)

There is also a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit.

Peak Limit=74 dBuV/m

Average Limit=54 dBuV/m

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$, $U = 3.55$ dB.




Test Results:


PASS

The signal beyond the limit is carrier.


802.11b-Channel 1: Peak




802.11b-Channel 11: Peak




802.11b-Channel 1: Average




802.11b-Channel 11: Average



802.11g-Channel 1: Peak




802.11g-Channel 11: Peak







802.11g-Channel 1: Average




802.11g-Channel 11: Average




802.11n HT20 -Channel 1: Peak




802.11n HT20-Channel 11: Peak



802.11n HT20-Channel 1: Average




802.11n HT20-Channel 11: Average







802.11n HT40 -Channel 3: Peak




802.11n HT40-Channel 9: Peak




802.11n HT40-Channel 3: Average




802.11n HT40-Channel 9: Average




BLE -Channel 0: Peak




BLE -Channel 39: Peak



BLE -Channel 0: Average



BLE -Channel 39: Average



5.7. Radiates Emission

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	102.5kPa

Method of Measurement

The test set-up was made in accordance to the general provisions of ANSI C63.10-2013. The Equipment Under Test (EUT) was set up on a non-conductive table in the semi-anechoic chamber. The test was performed at the distance of 3 m between the EUT and the receiving antenna. The radiated emissions measurements were made in a typical installation configuration.

Sweep the whole frequency band through the range from 9 kHz to the 10th harmonic of the carrier, and the emissions less than 20 dB below the permissible value are reported.

During the test, below 30MHz, the center of the loop shall be 1 meters; above 30MHz, the height of receive antenna shall be moved from 1 to 4 meters, and the antenna shall be performed under horizontal and vertical polarization. The turntable shall be rotated from 0 to 360 degrees for detecting the maximum of radiated spurious signal level. The measurements shall be repeated with orthogonal polarization of the test antenna. The data of cable loss and antenna factor has been calibrated in full testing frequency range before the testing.

Set the spectrum analyzer in the following:

Below 1GHz (detector: Peak and Quasi-Peak)

RBW=100 kHz / VBW=300 kHz / Sweep=AUTO

Above 1GHz (detector: Peak):

(a) PEAK: RBW=1MHz / VBW=3MHz/ Sweep=AUTO


(b) AVERAGE: RBW=1MHz / VBW=3MHz / Sweep=AUTO

The radiated emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis). The worst emission was found in lie-down position (X axis) and the worst case was recorded.


The test is in transmitting mode.

Test setup


9KHz ~ 30MHz



30MHz ~ 1GHz



Above 1GHz



Note: Area side:2.4mX3.6m

Limits

Rule Part 15.247(d) specifies that “In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).”

Limit in restricted band

Frequency of emission (MHz)	Field strength(uV/m)	Field strength(dBuV/m)
0.009–0.490	2400/F(kHz)	/
0.490–1.705	24000/F(kHz)	/
1.705–30.0	30	/
30-88	100	40
88-216	150	43.5
216-960	200	46
Above960	500	54

§15.35(b)

There is also a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$.

Frequency	Uncertainty
9KHz-30MHz	3.55 dB
30MHz-200MHz	4.19 dB
200MHz-1GHz	3.63 dB
Above 1GHz	3.68 dB



Test result

Sweep from 9 kHz to 30MHz, and the emissions more than 20 dB below the permissible value are not reported.


The following graphs display the maximum values of horizontal and vertical by software.

For above 1GHz, Blue trace uses the peak detection, Green trace uses the average detection.

During the test, the Radiates Emission from 30MHz to 1GHz was performed in all modes with all channels, 802.11b, Channel 11 are selected as the worst condition. The test data of the worst-case condition was recorded in this report.

Continuous TX mode:

FCC RE 0.03-1GHz QP Class B



Radiates Emission from 30MHz to 1GHz

Frequency (MHz)	Quasi-Peak (dBuV/m)	Reading value (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
52.916250	10.1	-2.9	125.0	H	198.0	13.0	29.9	40.0
65.532500	7.8	-2.5	125.0	H	172.0	10.3	32.2	40.0
110.392500	18.3	6.0	100.0	V	245.0	12.3	25.2	43.5
206.061250	16.6	4.3	125.0	H	101.0	12.3	26.9	43.5
513.185000	18.3	-2.6	125.0	H	32.0	20.9	27.7	46.0
880.972500	25.7	-0.8	114.0	V	279.0	26.5	20.3	46.0


Remark: 1. Quasi-Peak = Reading value + Correction factor

2. Correction Factor = Antenna factor+ Insertion loss(cable loss+amplifier gain)

3. Margin = Limit – Quasi-Peak


802.11b CH1

RE 1G-3GHz PK+AV




Note: The signal beyond the limit is carrier.
Radiates Emission from 1GHz to 3GHz

RE 3-18GHz PK+AV



Radiates Emission from 3GHz to 18GHz

BELL_RE 18-26.5GHz PK+AV



Radiates Emission from 18GHz to 26.5GHz



Frequency (MHz)	Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1111.750000	38.3	100.0	H	173.0	47.5	-9.2	35.7	74
1385.000000	39.2	100.0	V	91.0	47.2	-8.0	34.8	74
1702.250000	43.4	100.0	H	296.0	49.9	-6.5	30.6	74
1880.500000	46.8	100.0	H	296.0	52.9	-6.1	27.2	74
2021.250000	49.1	100.0	H	307.0	54.9	-5.8	24.9	74
2695.250000	48.0	100.0	H	296.0	50.6	-2.6	26.0	74


Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

Frequency (MHz)	Average (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1010.500000	28.4	100.0	H	66.0	38.1	-9.7	25.6	54
1377.250000	28.4	100.0	V	149.0	36.5	-8.1	25.6	54
1702.250000	36.5	100.0	H	296.0	43.0	-6.5	17.5	54
1880.500000	40.9	100.0	H	296.0	47.0	-6.1	13.1	54
2021.500000	45.2	100.0	H	284.0	51.0	-5.8	8.8	54
2695.250000	43.9	100.0	H	296.0	46.5	-2.6	10.1	54

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)


802.11b CH6

RE 1G-3GHz PK+AV




Note: The signal beyond the limit is carrier.
Radiates Emission from 1GHz to 3GHz

RE 3-18GHz PK+AV



Radiates Emission from 3GHz to 18GHz

BELL_RE 18-26.5GHz PK+AV



Radiates Emission from 18GHz to 26.5GHz



Frequency (MHz)	Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1186.500000	38.1	100.0	H	13.0	46.9	-8.8	35.9	74
1417.250000	39.4	100.0	V	178.0	47.4	-8.0	34.6	74
1538.500000	39.4	100.0	H	181.0	47.0	-7.6	34.6	74
1918.000000	42.8	100.0	H	306.0	48.9	-6.1	31.2	74
2096.500000	48.9	100.0	H	294.0	53.8	-4.9	25.1	74
2795.250000	45.3	100.0	H	294.0	47.1	-1.8	28.7	74


Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

Frequency (MHz)	Average (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1185.750000	27.3	100.0	H	158.0	36.1	-8.8	26.7	54
1420.250000	28.7	100.0	H	101.0	36.6	-7.9	25.3	54
1538.500000	28.2	100.0	H	181.0	35.8	-7.6	25.8	54
1917.750000	36.6	100.0	H	294.0	42.7	-6.1	17.4	54
2096.500000	46.0	100.0	H	294.0	50.9	-4.9	8.0	54
2795.250000	41.7	100.0	H	294.0	43.5	-1.8	12.3	54

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)


802.11b CH11

RE 1G-3GHz PK+AV




Note: The signal beyond the limit is carrier.
Radiates Emission from 1GHz to 3GHz

RE 3-18GHz PK+AV



Radiates Emission from 3GHz to 18GHz

BELL_RE 18-26.5GHz PK+AV



Radiates Emission from 18GHz to 26.5GHz



Frequency (MHz)	Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1198.750000	37.8	100.0	H	73.0	46.8	-9.0	36.2	74
1378.750000	38.6	100.0	V	284.0	46.6	-8.0	35.4	74
1727.500000	40.0	100.0	H	40.0	46.7	-6.7	34.0	74
1955.250000	43.0	100.0	H	282.0	48.6	-5.6	31.0	74
2171.500000	42.8	100.0	H	282.0	47.2	-4.4	31.2	74
2895.250000	46.4	100.0	H	18.0	47.4	-1.0	27.6	74

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)


Frequency (MHz)	Average (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1186.750000	27.4	100.0	H	105.0	36.2	-8.8	26.6	54
1380.500000	28.5	100.0	V	240.0	36.5	-8.0	25.5	54
1695.750000	29.2	100.0	V	183.0	35.8	-6.6	24.8	54
1954.250000	37.3	100.0	H	282.0	43.0	-5.7	16.7	54
2171.500000	37.8	100.0	H	282.0	42.2	-4.4	16.2	54
2895.250000	39.6	100.0	H	18.0	40.6	-1.0	14.4	54

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)




802.11g CH1

RE 1G-3GHz PK+AV




Note: The signal beyond the limit is carrier.
Radiates Emission from 1GHz to 3GHz

RE 3-18GHz PK+AV



Radiates Emission from 3GHz to 18GHz

BELL_RE 18-26.5GHz PK+AV



Radiates Emission from 18GHz to 26.5GHz



Frequency (MHz)	Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1190.000000	38.3	100.0	V	259.0	47.2	-8.9	35.7	74
1420.250000	38.9	100.0	H	101.0	46.8	-7.9	35.1	74
1702.250000	52.9	100.0	H	248.0	59.4	-6.5	21.1	74
1880.500000	48.1	100.0	H	248.0	54.2	-6.1	25.9	74
2010.750000	45.8	100.0	H	0.0	51.5	-5.7	28.2	74
2693.500000	45.1	100.0	H	248.0	47.7	-2.6	28.9	74


Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

Frequency (MHz)	Average (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1183.750000	27.4	100.0	H	237.0	36.2	-8.8	26.6	54
1378.000000	28.4	100.0	V	328.0	36.5	-8.1	25.6	54
1703.000000	37.0	100.0	H	248.0	43.5	-6.5	17.0	54
1877.500000	35.3	100.0	H	248.0	41.4	-6.1	18.7	54
2017.000000	33.1	100.0	H	248.0	38.9	-5.8	20.9	54
2693.500000	35.1	100.0	H	248.0	37.7	-2.6	18.9	54

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)


802.11g CH6

BELL_RE 18-26.5GHz PK+AV




Note: The signal beyond the limit is carrier.
Radiates Emission from 1GHz to 3GHz

RE 3-18GHz PK+AV



Radiates Emission from 3GHz to 18GHz

BELL_RE 18-26.5GHz PK+AV



Radiates Emission from 18GHz to 26.5GHz



Frequency (MHz)	Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
18554.62500	53.5	100.0	V	301.0	53.3	0.2	20.5	74
20302.43750	53.7	100.0	H	230.0	54.8	-1.1	20.3	74
21830.31250	54.9	100.0	V	90.0	56.8	-1.9	19.1	74
21948.25000	55.4	100.0	V	131.0	56.7	-1.3	18.6	74
23444.25000	54.0	100.0	V	0.0	54.1	-0.1	20.0	74
25324.87500	56.4	100.0	V	245.0	55.9	0.5	17.6	74

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)


Frequency (MHz)	Average (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
18153.00000	41.3	100.0	V	240.0	40.0	1.3	12.7	54
20411.87500	41.8	100.0	V	267.0	42.7	-0.9	12.2	54
21826.06250	43.9	100.0	V	318.0	45.8	-1.9	10.1	54
21882.37500	44.2	100.0	V	312.0	45.9	-1.7	9.8	54
23426.18750	43.1	100.0	V	177.0	43.2	-0.1	10.9	54
25297.25000	44.2	100.0	V	223.0	43.7	0.5	9.8	54

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)




802.11g CH11

RE 1G-3GHz PK+AV




Note: The signal beyond the limit is carrier.
Radiates Emission from 1GHz to 3GHz

RE 3-18GHz PK+AV



Radiates Emission from 3GHz to 18GHz

BELL_RE 18-26.5GHz PK+AV



Radiates Emission from 18GHz to 26.5GHz



Frequency (MHz)	Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1155.250000	37.6	100.0	V	0.0	46.7	-9.1	36.4	74
1421.000000	38.7	100.0	H	158.0	46.6	-7.9	35.3	74
1779.000000	52.6	100.0	H	248.0	59.0	-6.4	21.4	74
1948.250000	45.0	100.0	H	259.0	50.6	-5.6	29.0	74
2239.000000	42.6	100.0	V	305.0	47.3	-4.7	31.4	74
2897.000000	45.5	100.0	H	236.0	46.5	-1.0	28.5	74

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)


Frequency (MHz)	Average (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1177.750000	27.5	100.0	H	124.0	36.2	-8.7	26.5	54
1384.500000	28.7	100.0	H	3.0	36.7	-8.0	25.3	54
1783.750000	32.2	100.0	H	248.0	38.4	-6.2	21.8	54
1949.750000	31.0	100.0	H	248.0	36.6	-5.6	23.0	54
2239.000000	30.9	100.0	V	305.0	35.6	-4.7	23.1	54
2884.500000	34.8	100.0	H	101.0	35.6	-0.8	19.2	54

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)




802.11n (HT20) CH1

RE 1G-3GHz PK+AV




Note: The signal beyond the limit is carrier.
Radiates Emission from 1GHz to 3GHz

RE 3-18GHz PK+AV



Radiates Emission from 3GHz to 18GHz

BELL_RE 18-26.5GHz PK+AV



Radiates Emission from 18GHz to 26.5GHz



Frequency (MHz)	Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1070.750000	37.6	100.0	H	271.0	46.9	-9.3	36.4	74
1419.750000	39.0	100.0	H	31.0	46.9	-7.9	35.0	74
1702.250000	51.8	100.0	H	259.0	58.3	-6.5	22.2	74
1876.500000	46.3	100.0	H	259.0	52.4	-6.1	27.7	74
2244.250000	42.6	100.0	H	113.0	47.3	-4.7	31.4	74
2894.250000	44.7	100.0	H	135.0	45.6	-0.9	29.3	74

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)


Frequency (MHz)	Average (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1109.500000	27.5	100.0	V	214.0	36.8	-9.3	26.5	54
1416.000000	28.5	100.0	V	281.0	36.5	-8.0	25.5	54
1700.000000	31.6	100.0	H	259.0	38.1	-6.5	22.4	54
1879.000000	33.0	100.0	H	271.0	39.1	-6.1	21.0	54
2244.250000	31.1	100.0	H	113.0	35.8	-4.7	22.9	54
2892.000000	34.7	100.0	V	352.0	35.6	-0.9	19.3	54

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)




802.11n (HT20) CH6

RE 1G-3GHz PK+AV




Note: The signal beyond the limit is carrier.
Radiates Emission from 1GHz to 3GHz

RE 3-18GHz PK+AV



Radiates Emission from 3GHz to 18GHz

BELL_RE 18-26.5GHz PK+AV



Radiates Emission from 18GHz to 26.5GHz



Frequency (MHz)	Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1168.500000	37.8	100.0	H	91.0	46.6	-8.8	36.2	74
1421.000000	39.8	100.0	V	0.0	47.7	-7.9	34.2	74
1741.500000	42.9	100.0	H	36.0	49.4	-6.5	31.1	74
2053.250000	40.8	100.0	V	153.0	46.2	-5.4	33.2	74
2612.250000	43.9	100.0	H	192.0	46.2	-2.3	30.1	74
2911.750000	46.0	100.0	V	299.0	47.2	-1.2	28.0	74

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)


Frequency (MHz)	Average (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1115.750000	27.1	100.0	H	309.0	36.3	-9.2	26.9	54
1422.000000	28.3	100.0	V	277.0	36.3	-8.0	25.7	54
1741.500000	28.4	100.0	H	36.0	34.9	-6.5	25.6	54
2053.750000	30.6	100.0	H	102.0	36.0	-5.4	23.4	54
2612.250000	32.5	100.0	H	192.0	34.8	-2.3	21.5	54
2977.000000	34.8	100.0	V	0.0	35.8	-1.0	19.2	54

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)




802.11n (HT20) CH11

RE 1G-3GHz PK+AV




Note: The signal beyond the limit is carrier.
Radiates Emission from 1GHz to 3GHz

RE 3-18GHz PK+AV



Radiates Emission from 3GHz to 18GHz

BELL_RE 18-26.5GHz PK+AV



Radiates Emission from 18GHz to 26.5GHz



Frequency (MHz)	Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1196.250000	37.9	100.0	H	146.0	46.8	-8.9	36.1	74
1417.000000	39.1	100.0	H	10.0	47.1	-8.0	34.9	74
1782.750000	46.2	100.0	H	283.0	52.4	-6.2	27.8	74
2050.750000	38.4	100.0	V	226.0	43.8	-5.4	35.6	74
2322.250000	41.8	100.0	V	65.0	45.7	-3.9	32.2	74
2978.500000	45.1	100.0	V	181.0	46.1	-1.0	28.9	74

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)


Frequency (MHz)	Average (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1184.250000	27.3	100.0	V	181.0	36.1	-8.8	26.7	54
1417.750000	28.4	100.0	H	146.0	36.4	-8.0	25.6	54
1782.750000	28.0	100.0	H	283.0	34.2	-6.2	26.0	54
2055.000000	30.6	100.0	V	214.0	36.0	-5.4	23.4	54
2322.250000	30.1	100.0	V	65.0	34.0	-3.9	23.9	54
2972.750000	35.0	100.0	V	214.0	36.0	-1.0	19.0	54

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)




802.11n (HT40) CH3

RE 1G-3GHz PK+AV




Note: The signal beyond the limit is carrier.
Radiates Emission from 1GHz to 3GHz

RE 3-18GHz PK+AV



Radiates Emission from 3GHz to 18GHz

BELL_RE 18-26.5GHz PK+AV



Radiates Emission from 18GHz to 26.5GHz



Frequency (MHz)	Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1191.750000	37.6	100.0	V	0.0	46.5	-8.9	36.4	74
1420.750000	38.7	100.0	V	236.0	46.6	-7.9	35.3	74
1714.750000	48.5	100.0	H	282.0	55.0	-6.5	25.5	74
1883.000000	44.5	100.0	H	282.0	50.7	-6.2	29.5	74
2272.500000	42.7	100.0	V	303.0	46.5	-3.8	31.3	74
2891.000000	45.1	100.0	H	0.0	46.0	-0.9	28.9	74

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)


Frequency (MHz)	Average (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1191.750000	27.5	100.0	H	100.0	36.4	-8.9	26.5	54
1419.250000	28.5	100.0	H	269.0	36.5	-8.0	25.5	54
1714.750000	30.8	100.0	H	282.0	37.3	-6.5	23.2	54
1889.500000	31.3	100.0	H	269.0	37.7	-6.4	22.7	54
2272.500000	30.8	100.0	V	303.0	34.6	-3.8	23.2	54
2891.000000	33.7	100.0	H	0.0	34.6	-0.9	20.3	54

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)




802.11n (HT40) CH6

RE 1G-3GHz PK+AV




Note: The signal beyond the limit is carrier.
Radiates Emission from 1GHz to 3GHz

RE 3-18GHz PK+AV



Radiates Emission from 3GHz to 18GHz

BELL_RE 18-26.5GHz PK+AV



Radiates Emission from 18GHz to 26.5GHz



Frequency (MHz)	Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1057.000000	37.9	100.0	V	344.0	47.3	-9.4	36.1	74
1417.750000	39.5	100.0	V	221.0	47.5	-8.0	34.5	74
1748.500000	48.6	100.0	H	326.0	55.0	-6.4	25.4	74
1921.500000	43.9	100.0	H	326.0	50.0	-6.1	30.1	74
2498.250000	59.1	100.0	H	340.0	61.4	-2.3	14.9	74
2654.000000	45.3	100.0	H	207.0	47.4	-2.1	28.7	74


Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

Frequency (MHz)	Average (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1057.000000	25.8	100.0	V	344.0	35.2	-9.4	28.2	54
1422.000000	28.5	100.0	V	355.0	36.5	-8.0	25.5	54
1748.500000	30.7	100.0	H	326.0	37.1	-6.4	23.3	54
1921.500000	29.8	100.0	H	326.0	35.9	-6.1	24.2	54
2499.000000	39.4	100.0	H	326.0	41.7	-2.3	14.6	54
2654.000000	33.3	100.0	H	207.0	35.4	-2.1	20.7	54

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)


802.11n (HT40) CH9

RE 1G-3GHz PK+AV




Note: The signal beyond the limit is carrier.
Radiates Emission from 1GHz to 3GHz

RE 3-18GHz PK+AV



Radiates Emission from 3GHz to 18GHz

BELL_RE 18-26.5GHz PK+AV



Radiates Emission from 18GHz to 26.5GHz



Frequency (MHz)	Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1186.250000	37.8	100.0	V	337.0	46.6	-8.8	36.2	74
1418.250000	39.2	100.0	V	337.0	47.2	-8.0	34.8	74
1772.000000	47.7	100.0	H	295.0	54.0	-6.3	26.3	74
1933.500000	41.9	100.0	H	145.0	47.7	-5.8	32.1	74
2271.750000	42.0	100.0	V	303.0	45.8	-3.8	32.0	74
2869.750000	44.5	100.0	V	213.0	45.4	-0.9	29.5	74


Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

Frequency (MHz)	Average (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1185.000000	27.3	100.0	H	32.0	36.1	-8.8	26.7	54
1422.500000	28.6	100.0	V	270.0	36.6	-8.0	25.4	54
1772.000000	31.8	100.0	H	295.0	38.1	-6.3	22.2	54
1933.500000	28.9	100.0	H	145.0	34.7	-5.8	25.1	54
2271.750000	31.2	100.0	V	303.0	35.0	-3.8	22.8	54
2869.750000	32.8	100.0	V	213.0	33.7	-0.9	21.2	54

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)


BLE-Channel 0

RE 1G-3GHz PK+AV




Note: The signal beyond the limit is carrier.
Radiates Emission from 1GHz to 3GHz

RE 3-18GHz PK+AV



Radiates Emission from 3GHz to 18GHz

RE 18-26.5GHz PK+AV



Radiates Emission from 18GHz to 26.5GHz



Frequency (MHz)	Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1187.250000	38.6	100.0	H	119.0	47.4	-8.8	35.4	74
1419.500000	38.7	100.0	V	347.0	46.7	-8.0	35.3	74
1731.750000	40.5	100.0	H	152.0	47.0	-6.5	33.5	74
2058.500000	41.3	100.0	H	187.0	46.6	-5.3	32.7	74
2609.250000	44.4	100.0	V	358.0	46.7	-2.3	29.6	74
2977.500000	46.0	100.0	H	259.0	47.0	-1.0	28.0	74

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)


Frequency (MHz)	Average (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1185.000000	27.6	100.0	V	280.0	36.4	-8.8	26.4	54
1418.500000	29.0	100.0	H	176.0	37.0	-8.0	25.0	54
1731.750000	29.4	100.0	H	152.0	35.9	-6.5	24.6	54
2047.000000	30.8	100.0	H	30.0	36.2	-5.4	23.2	54
2609.250000	33.1	100.0	V	358.0	35.4	-2.3	20.9	54
2975.250000	35.3	100.0	H	209.0	36.3	-1.0	18.7	54

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)




BLE-Channel 19

RE 1G-3GHz PK+AV




Note: The signal beyond the limit is carrier.
Radiates Emission from 1GHz to 3GHz

RE 3-18GHz PK+AV



Radiates Emission from 3GHz to 18GHz

RE 18-26.5GHz PK+AV



Radiates Emission from 18GHz to 26.5GHz



Frequency (MHz)	Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1185.250000	38.9	100.0	V	358.0	47.7	-8.8	35.1	74
1409.250000	38.5	100.0	H	259.0	46.7	-8.2	35.5	74
1669.500000	40.3	100.0	H	19.0	47.0	-6.7	33.7	74
2051.750000	41.5	100.0	H	30.0	46.9	-5.4	32.5	74
2541.250000	44.6	100.0	H	30.0	47.3	-2.7	29.4	74
2935.500000	46.6	100.0	V	325.0	47.9	-1.3	27.4	74

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)


Frequency (MHz)	Average (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1191.250000	28.1	100.0	V	292.0	37.0	-8.9	25.9	54
1424.500000	28.7	100.0	H	108.0	36.7	-8.0	25.3	54
1695.750000	29.9	100.0	V	148.0	36.5	-6.6	24.1	54
2051.750000	31.0	100.0	V	270.0	36.4	-5.4	23.0	54
2541.250000	32.2	100.0	H	30.0	34.9	-2.7	21.8	54
2979.750000	35.3	100.0	H	8.0	36.3	-1.0	18.7	54

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)




BLE-Channel 39

RE 1G-3GHz PK+AV




Note: The signal beyond the limit is carrier.
Radiates Emission from 1GHz to 3GHz

RE 3-18GHz PK+AV



Radiates Emission from 3GHz to 18GHz

RE 18-26.5GHz PK+AV



Radiates Emission from 18GHz to 26.5GHz



Frequency (MHz)	Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1193.500000	38.1	100.0	H	209.0	47.0	-8.9	35.9	74
1388.250000	39.3	100.0	V	5.0	47.3	-8.0	34.7	74
1583.750000	39.7	100.0	V	5.0	47.4	-7.7	34.3	74
2016.000000	41.2	100.0	V	274.0	47.0	-5.8	32.8	74
2345.750000	42.5	100.0	V	307.0	46.0	-3.5	31.5	74
2897.250000	45.4	100.0	V	351.0	46.4	-1.0	28.6	74

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

Frequency (MHz)	Average (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1193.500000	27.7	100.0	H	209.0	36.6	-8.9	26.3	54
1417.750000	29.2	100.0	V	351.0	37.2	-8.0	24.8	54
1583.750000	28.9	100.0	V	5.0	36.6	-7.7	25.1	54
2051.750000	31.0	100.0	H	175.0	36.4	-5.4	23.0	54
2345.750000	31.6	100.0	V	307.0	35.1	-3.5	22.4	54
2895.250000	35.2	100.0	H	187.0	36.2	-1.0	18.8	54

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

5.8. Conducted Emission

Ambient condition


Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Methods of Measurement

The EUT is placed on a non-metallic table of 80cm height above the horizontal metal reference ground plane. During the test, the EUT was operating in its typical mode. The test method is according to ANSI C63.10-2013. Connect the AC power line of the EUT to the L.I.S.N. Use EMI receiver to detect the average and Quasi-peak value. RBW is set to 9 kHz, VBW is set to 30kHz. The measurement result should include both L line and N line.

The test is in transmitting mode.

Test Setup



Note: AC Power source is used to change the voltage 110V/60Hz.

Limits

Frequency (MHz)	Conducted Limits(dBμV)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56 *	56 to 46*
0.5 - 5	56	46
5 - 30	60	50


*: Decreases with the logarithm of the frequency.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$, $U = 2.69$ dB.

Test Results:


Following plots, Blue trace uses the peak detection and Green trace uses the average detection. During the test, the Conducted Emission was performed in all modes with all channels, 802.11b, Channel 11 are selected as the worst condition. The test data of the worst-case condition was recorded in this report.



Final Result

Frequency (MHz)	QuasiPeak (dB; I V)	Average (dB; I V)	Limit (dB; I V)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.181500	---	29.33	54.42	25.09	1000.0	9.000	L1	ON	19.5
0.181500	42.29	---	64.42	22.13	1000.0	9.000	L1	ON	19.5
0.460500	---	22.48	46.68	24.21	1000.0	9.000	L1	ON	19.5
0.588750	34.76	---	56.00	21.24	1000.0	9.000	L1	ON	19.5
1.311000	---	20.25	46.00	25.75	1000.0	9.000	L1	ON	19.5
1.315500	33.20	---	56.00	22.80	1000.0	9.000	L1	ON	19.5
2.805000	---	16.43	46.00	29.57	1000.0	9.000	L1	ON	19.5
2.861250	24.23	---	56.00	31.77	1000.0	9.000	L1	ON	19.5
5.507250	---	16.16	50.00	33.84	1000.0	9.000	L1	ON	19.6
5.597250	21.47	---	60.00	38.53	1000.0	9.000	L1	ON	19.6
19.686750	24.20	---	60.00	35.80	1000.0	9.000	L1	ON	19.9
19.752000	---	17.36	50.00	32.64	1000.0	9.000	L1	ON	19.9

WIFI 2.4G_L_0.15-30MHz



Final Result

Frequency (MHz)	QuasiPeak (dB; I V)	Average (dB; I V)	Limit (dB; I V)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.179250	45.12	---	64.52	19.40	1000.0	9.000	N	ON	19.5
0.181500	---	32.44	54.42	21.98	1000.0	9.000	N	ON	19.5
0.627000	---	26.08	46.00	19.92	1000.0	9.000	N	ON	19.5
0.629250	35.44	---	56.00	20.56	1000.0	9.000	N	ON	19.5
1.223250	---	20.61	46.00	25.39	1000.0	9.000	N	ON	19.5
1.317750	29.69	---	56.00	26.31	1000.0	9.000	N	ON	19.5
2.409000	---	15.68	46.00	30.32	1000.0	9.000	N	ON	19.5
2.494500	21.17	---	56.00	34.83	1000.0	9.000	N	ON	19.5
5.340750	---	15.67	50.00	34.33	1000.0	9.000	N	ON	19.6
5.412750	19.17	---	60.00	40.83	1000.0	9.000	N	ON	19.6
19.956750	---	15.88	50.00	34.12	1000.0	9.000	N	ON	19.7
20.004000	20.06	---	60.00	39.94	1000.0	9.000	N	ON	19.7

WIFI 2.4G_N_0.15-30MHz



6. Main Test Instruments

Name	Manufacturer	Type	Serial Number	Calibration Date	Expiration Date
Spectrum Analyzer	R&S	FSV30	100815	2016-12-16	2017-12-15
EMI Test Receiver	R&S	ESCI	100948	2017-05-20	2018-05-19
TRILOG Broadband Antenna	Schwarzbeck	VULB 9163	9163-201	2014-12-06	2017-12-05
Double Ridged Waveguide Horn Antenna	R&S	HF907	100126	2014-12-06	2017-12-05
Loop Antenna	SCHWARZBECK	FMZB1519	1519-047	2017-02-18	2020-02-17
Standard Gain Horn	ETS-Lindgren	3160-09	00102644	2015-01-30	2018-01-29
EMI Test Receiver	R&S	ESCS30	100138	2016-12-16	2017-12-15
LISN	R&S	ENV216	101171	2016-12-16	2019-12-15
Spectrum Analyzer	Agilent	N9010A	MY47191109	2017-05-20	2018-05-19
RF Cable	Agilent	SMA 15cm	0001	2017-08-04	2018-02-03


*****END OF REPORT *****

ANNEX A: EUT Appearance and Test Setup

A.1 EUT Appearance



Front Side




Back Side


a: EUT



b: Adapter



c : Earphone




d : USB Cable

Picture 1 EUT and Accessory

A.2 Test Setup




30M Hz-1GHz



Above 1GHz

Picture 2 Radiated Emission Test Setup



Picture 3 Conducted Emission Test Setup