



FCC RF Test Report

APPLICANT : ZTE CORPORATION
EQUIPMENT : LTE Tablet
BRAND NAME : ZTE
MODEL NAME : K90U
FCC ID : SRQ-K90U
STANDARD : FCC Part 15 Subpart E §15.407
CLASSIFICATION : (NII) Unlicensed National Information Infrastructure

The product was received on Jul. 19, 2016 and testing was completed on Aug. 31, 2016. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

Prepared by: James Huang / Manager

Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China



TABLE OF CONTENTS

SUMMARY OF TEST RESULT 4

1 GENERAL DESCRIPTION 5

1.1 Applicant 5

1.2 Manufacturer 5

1.3 Product Feature of Equipment Under Test 5

1.4 Product Specification of Equipment Under Test 6

1.5 Modification of EUT 7

1.6 Testing Location 7

1.7 Applicable Standards 7

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST 8

2.1 Carrier Frequency and Channel 8

2.2 Test Mode 9

2.3 Connection Diagram of Test System 10

2.4 Support Unit used in test configuration and system 11

2.5 EUT Operation Test Setup 11

2.6 Measurement Results Explanation Example 12

3 TEST RESULT 13

3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement 13

3.2 Maximum Conducted Output Power Measurement 16

3.3 Power Spectral Density Measurement 17

3.4 Unwanted Emissions Measurement 20

3.5 AC Conducted Emission Measurement 25

3.6 Frequency Stability Measurement 29

3.7 Automatically Discontinue Transmission 30

3.8 Antenna Requirements 31

4 LIST OF MEASURING EQUIPMENT 32

5 UNCERTAINTY OF EVALUATION 33

APPENDIX A. CONDUCTED TEST RESULTS

APPENDIX B. RADIATED TEST RESULTS

APPENDIX C. DUTY CYCLE PLOTS

APPENDIX D. SETUP PHOTOGRAPHS



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.403(i)	6dB, 26dB and 99% Occupied Bandwidth	> 500kHz	Pass	-
3.2	15.407(a)	Maximum Conducted Output Power	≤ 30 dBm	Pass	-
3.3	15.407(a)	Power Spectral Density	≤ 30 dBm/500kHz	Pass	-
3.4	15.407(b)	Unwanted Emissions	15.407(b)(4)(i) & 15.209(a)	Pass	Under limit 7.27 dB at 33.880 MHz
3.5	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 11.79 dB at 0.350 MHz
3.6	15.407(g)	Frequency Stability	Within Operation Band	Pass	-
3.7	15.407(c)	Automatically Discontinue Transmission	Discontinue Transmission	Pass	-
3.8	15.203 & 15.407(a)	Antenna Requirement	N/A	Pass	-



1 General Description

1.1 Applicant

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

1.2 Manufacturer

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	LTE Tablet
Brand Name	ZTE
Model Name	K90U
FCC ID	SRQ-K90U
EUT supports Radios application	LTE/ WLAN2.4GHz 802.11b/g/n HT20/HT40 WLAN5GHz 802.11a/n HT20/HT40/ WLAN5GHz 802.11ac VHT20/VHT40/VHT80/ Bluetooth v3.0 + EDR/ Bluetooth v4.1 LE
IMEI Code	Conducted: 990006081532821 Radiation: 99000608153138 Conduction: 99000608153015
HW Version	u1pA
SW Version	K90UV1.0.0B06
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Channel Frequency Range	5745 MHz ~ 5825 MHz
Maximum Output Power	802.11a : 8.23 dBm / 0.0067 W 802.11n HT20 : 7.78 dBm / 0.0060 W 802.11n HT40 : 7.84 dBm / 0.0061 W 802.11ac VHT20: 7.72 dBm / 0.0059 W 802.11ac VHT40: 7.64 dBm / 0.0058 W 802.11ac VHT80: 7.76 dBm / 0.0060 W
99% Occupied Bandwidth	802.11a : 18.68 MHz 802.11n HT20 : 19.28 MHz 802.11n HT40 : 36.66 MHz 802.11ac VHT20 : 19.13 MHz 802.11ac VHT40 : 36.76 MHz 802.11ac VHT80 : 74.81 MHz
Antenna Type	PIFA Antenna with gain -0.56 dBi
Type of Modulation	802.11a/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) 802.11ac : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)



1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.	
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958	
Test Site No.	Sporton Site No.	
	TH01-KS	CO01-KS

Test Site	SPORTON INTERNATIONAL (SHENZHEN) INC.	
Test Site Location	No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755- 3320-2398	
Test Site No.	Sporton Site No.	FCC Registration No.
	03CH03-SZ	565805

Note: The test site complies with ANSI C63.4 2014 requirement.

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart E
- FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r03
- ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz) and radiated emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Z plane) were recorded in this report.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5745-5825 MHz Band 4 (U-NII-3)	149	5745	157	5785
	151*	5755	159*	5795
	153	5765	161	5805
	155#	5775	165	5825

Note:

1. The above Frequency and Channel in "*" were 802.11n HT40 and 802.11ac VHT40.
2. The above Frequency and Channel in "#" were 802.11ac VHT80.



2.2 Test Mode

Final test mode of conducted test items and radiated spurious emissions are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11a	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0
802.11ac VHT20	MCS0
802.11ac VHT40	MCS0
802.11ac VHT80	MCS0


AC Conducted Emission	Mode 1 : LTE Band 4 Idle + Bluetooth Link + WLAN (5G) Link + Earphone + USB Cable (Charging from Adapter)
Remark: For Radiated TCs, the tests were performed with adapter, earphone and USB cable.	

Ch. #		Band IV : 5745 ~ 5825 MHz		
		802.11a	802.11n HT20	802.11n HT40
L	Low	149	149	151
M	Middle	157	157	-
H	High	165	165	159


Ch. #		Band IV : 5745 ~ 5825 MHz		
		802.11ac VHT20	802.11ac VHT40	802.11ac VHT80
L	Low	149	151	-
M	Middle	157	-	155
H	High	165	159	-

2.3 Connection Diagram of Test System

< Radiated Emission Mode >



<AC Conducted Emission Mode>





2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	WLAN AP	D-Link	DIR-855	KA2DIR855A2	N/A	Unshielded, 1.8 m
3.	Notebook	Lenovo	G480	N/A	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
4.	Bluetooth Earphone	Nokia	BH-102	PYAHS-107W	N/A	N/A
5.	Earphone	Lenovo	LH102	N/A	Unshielded, 1.2m	N/A
6.	Earphone	Apple	N/A	N/A	Shielded, 1.0 m	N/A

2.5 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuously transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the Notebook under large package sizes transmission.



2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss.

Following shows an offset computation example with cable loss 7.0 dB.

Offset (dB) = RF cable loss(dB).
= 7.0 (dB)

3 Test Result

3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement

3.1.1 Description of 6dB and 26dB and 99% Occupied Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

26dB and 99% Occupied bandwidth are reporting only.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r03.
Section C) Emission bandwidth for the band 5.725-5.85GHz
2. Set RBW = 100kHz.
3. Set the VBW $\geq 3 \times$ RBW.
4. Detector = Peak.
5. Trace mode = max hold
6. Measure the maximum width of the emission that is 6 dB down from the peak of the emission.
7. Measure and record the results in the test report.



3.1.4 Test Setup






3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.





Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Maximum Conducted Output Power Measurement

3.2.1 Limit of Maximum Conducted Output Power

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.2.3 Test Procedures

The testing follows Method PM of FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r03.

Method PM (Measurement using an RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit continuously with a consistent duty cycle at its maximum power control level.
3. Measure the average power of the transmitter, and the average power is corrected with duty factor, $10 \log(1/x)$, where x is the duty cycle.

3.2.4 Test Setup



3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.



3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

For the band 5.725–5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r03. Section F) Maximum power spectral density.


Method SA-2

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).

- Measure the duty cycle.
- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 300 kHz.
- Set VBW \geq 1 MHz.
- Number of points in sweep \geq 2 Span / RBW.
- Sweep time = auto.
- Detector = RMS
- Trace average at least 100 traces in power averaging mode.
- Add $10 \log(500\text{kHz}/\text{RBW})$ to the test result.
- Add $10 \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add $10 \log(1/0.25) = 6$ dB if the duty cycle is 25 percent.

1. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
2. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.


3.3.4 Test Setup





3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.





3.4 Unwanted Emissions Measurement

This section as specified in FCC Part 15.407(b) is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement. The unwanted emissions shall comply with 15.407(b)(1) to (6), and restricted bands per FCC Part15.205.

3.4.1 Limit of Unwanted Emissions

(1) For transmitters operating in the 5.725-5.85 GHz band:

15.407(b)(4)(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

(2) Unwanted spurious emissions fallen in restricted bands per FCC Part15.205 shall comply with the general field strength limits set forth in § 15.209 as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

Note: The following formula is used to convert the EIRP to field strength.

$$E = \frac{1000000\sqrt{30P}}{3} \text{ } \mu\text{V/m, where P is the eirp (Watts)}$$



EIRP (dBm)	Field Strength at 3m (dBμV/m)
-17	78.3
- 27	68.3

(3) KDB 789033 D02 General UNII Test Procedures New Rules v01r03 G)2)c) As specified in 15.407(b), emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit of -27 dBm/MHz (or -17 dBm/MHz as specified in 15.407(b)(4)). However, an out-of-band emission that complies with both the average and peak limits of 15.209 is not required to satisfy the -27 dBm/MHz or -17 dBm/MHz peak emission limit.

3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r03. Section G) Unwanted emissions measurement.

(1) Procedure for Unwanted Emissions Measurements Below 1000MHz

- RBW = 120 kHz
- VBW = 300 kHz
- Detector = Peak
- Trace mode = max hold

(2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz

- RBW = 1 MHz
- VBW ≥ 3 MHz
- Detector = Peak
- Sweep time = auto
- Trace mode = max hold


(3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz

- RBW = 1 MHz
- VBW = 10 Hz, when duty cycle is no less than 98 percent.
- VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.


2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

3.4.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz





3.4.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

3.4.6 Test Result of Radiated Band Edges

Please refer to Appendix B.

3.4.7 Duty Cycle

Please refer to Appendix C.

3.4.8 Test Result of Unwanted Radiated Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B.



3.5 AC Conducted Emission Measurement

3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.


3.5.4 Test Setup





3.5.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	22~24°C
Test Engineer :	Amos Zhang	Relative Humidity :	44~46%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	LTE Band 4 Idle + Bluetooth Link + WLAN (5G) Link + Earphone + USB Cable (Charging from Adapter)		




Site : CO01-KS
Condition : FCC PART 15E LISN-L-20151024 LINE

mode : Mode 1
: 99000608153015 #9

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.37	36.29	-22.14	58.43	25.90	0.23	10.16	QP
2	0.37	27.69	-20.74	48.43	17.30	0.23	10.16	Average
3	0.45	36.60	-20.29	56.89	26.20	0.23	10.17	QP
4	0.45	27.20	-19.69	46.89	16.80	0.23	10.17	Average
5	0.60	34.69	-21.31	56.00	24.29	0.24	10.16	QP
6	0.60	27.19	-18.81	46.00	16.79	0.24	10.16	Average
7	3.29	35.64	-20.36	56.00	25.29	0.19	10.16	QP
8	3.29	27.54	-18.46	46.00	17.19	0.19	10.16	Average
9	3.62	36.95	-19.05	56.00	26.60	0.19	10.16	QP
10	3.62	28.55	-17.45	46.00	18.20	0.19	10.16	Average
11	4.22	36.66	-19.34	56.00	26.30	0.19	10.17	QP
12 *	4.22	28.56	-17.44	46.00	18.20	0.19	10.17	Average



Test Mode :	Mode 1	Temperature :	22~24°C
Test Engineer :	Amos Zhang	Relative Humidity :	44~46%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	LTE Band 4 Idle + Bluetooth Link + WLAN (5G) Link + Earphone + USB Cable (Charging from Adapter)		



Site : CO01-KS
Condition : FCC PART 15E LISN-N-20151024 NEUTRAL

mode : Mode 1
: 99000608153015 #9

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.35	46.28	-12.59	58.87	35.80	0.32	10.16	QP
2 *	0.35	37.08	-11.79	48.87	26.60	0.32	10.16	Average
3	0.50	43.98	-12.03	56.01	33.50	0.32	10.16	QP
4	0.50	34.08	-11.93	46.01	23.60	0.32	10.16	Average
5	0.93	39.30	-16.70	56.00	28.80	0.36	10.14	QP
6	0.93	29.80	-16.20	46.00	19.30	0.36	10.14	Average
7	3.40	37.13	-18.87	56.00	26.60	0.37	10.16	QP
8	3.40	27.83	-18.17	46.00	17.30	0.37	10.16	Average
9	3.64	41.13	-14.87	56.00	30.60	0.37	10.16	QP
10	3.64	31.13	-14.87	46.00	20.60	0.37	10.16	Average
11	4.31	39.83	-16.17	56.00	29.30	0.36	10.17	QP
12	4.31	30.73	-15.27	46.00	20.20	0.36	10.17	Average
13	4.57	39.74	-16.26	56.00	29.20	0.36	10.18	QP
14	4.57	30.84	-15.16	46.00	20.30	0.36	10.18	Average
15	6.95	40.81	-19.19	60.00	30.30	0.29	10.22	QP
16	6.95	32.41	-17.59	50.00	21.90	0.29	10.22	Average

3.6 Frequency Stability Measurement

3.6.1 Limit of Frequency Stability

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. To ensure emission at the band edge is maintained within the authorized band, those values shall be measured by radiation emissions at upper and lower frequency points, and finally compensated by frequency deviation as procedures below.
2. The EUT was operated at the maximum output power, and connected to the spectrum analyzer, which is set to maximum hold function and peak detector. The peak value of the power envelope was measured and noted. The upper and lower frequency points were respectively measured relatively 10dB lower than the measured peak value.
3. The frequency deviation was calculated by adding the upper frequency point and the lower frequency point divided by two. Those detailed values of frequency deviation are provided in table below.

3.6.4 Test Setup



3.6.5 Test Result of Frequency Stability

Please refer to Appendix A.



3.7 Automatically Discontinue Transmission

3.7.1 Limit of Automatically Discontinue Transmission

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

3.7.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.7.3 Test Result of Automatically Discontinue Transmission

While the EUT is not transmitting any information, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.



3.8 Antenna Requirements

3.8.1 Standard Applicable

According to FCC 47 CFR Section 15.407(a)(1)(2) ,if transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.8.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.8.3 Antenna Gain

The antenna gain is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Sep. 10, 2015	Jul. 31, 2016~ Aug. 30, 2016	Sep. 09, 2016	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 20, 2016	Jul. 31, 2016~ Aug. 30, 2016	Jan. 19, 2017	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 20, 2016	Jul. 31, 2016~ Aug. 30, 2016	Jan. 19, 2017	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-960502	-40~+150°C	Oct. 24, 2015	Jul. 31, 2016~ Aug. 30, 2016	Oct. 23, 2016	Conducted (TH01-KS)
EMI Test Receiver&SA	KEYSIGHT	N9038A	MY54450083	20Hz~8.4GHz	May 07, 2016	Jul. 31, 2016~ Aug. 13, 2016	May 06, 2017	Radiation (03CH03-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150246	10Hz~44GHz	May 07, 2016	Jul. 31, 2016~ Aug. 13, 2016	May 06, 2017	Radiation (03CH03-SZ)
Loop Antenna	R&S	HFH2-Z2	100354	9kHz~30MHz	May 07, 2016	Jul. 31, 2016~ Aug. 13, 2016	May 06, 2017	Radiation (03CH03-SZ)
Bilog Antenna	TeseQ	CBL6112D	35408	30MHz~2GHz	May 21, 2016	Jul. 31, 2016~ Aug. 13, 2016	May 20, 2017	Radiation (03CH03-SZ)
Double Ridge Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-1355	1GHz~18GHz	May 07, 2016	Jul. 31, 2016~ Aug. 13, 2016	May 06, 2017	Radiation (03CH03-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18Ghz~40GHz	Aug.19, 2015	Jul. 31, 2016~ Aug. 13, 2016	Aug. 18, 2016	Radiation (03CH03-SZ)
Amplifier	Burgeon	BPA-530	102210	0.01Hz~3000MHz	Oct. 20, 2015	Jul. 31, 2016~ Aug. 13, 2016	Oct. 19, 2016	Radiation (03CH03-SZ)
Amplifier	Agilent Technologies	83017A	MY39501302	500MHz~26.5GHz	Jan. 12, 2016	Jul. 31, 2016~ Aug. 13, 2016	Jan. 11, 2017	Radiation (03CH03-SZ)
HF Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz	Jul. 16, 2016	Jul. 31, 2016~ Aug. 13, 2016	Jul. 15, 2017	Radiation (03CH03-SZ)
AC Power Source	Chroma	61601	616010001985	N/A	NCR	Jul. 31, 2016~ Aug. 13, 2016	NCR	Radiation (03CH03-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Jul. 31, 2016~ Aug. 13, 2016	NCR	Radiation (03CH03-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Jul. 31, 2016~ Aug. 13, 2016	NCR	Radiation (03CH03-SZ)
EMI Receiver	R&S	ESC17	100768	9kHz~7GHz;	Apr. 29, 2016	Jul. 26, 2016	Apr. 28, 2017	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Oct. 24, 2015	Jul. 26, 2016	Oct. 23, 2016	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Oct. 24, 2015	Jul. 26, 2016	Oct. 23, 2016	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP000000811	AC 0V~300V, 45Hz~1000Hz	Oct. 24, 2015	Jul. 26, 2016	Oct. 23, 2016	Conduction (CO01-KS)

NCR: No Calibration Required



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.3dB
---	-------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.1dB
---	-------

Uncertainty of Radiated Emission Measurement (1GHz ~ 18GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0dB
---	-------

Uncertainty of Radiated Emission Measurement (18GHz ~ 40GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0dB
---	-------



Appendix A. Conducted Test Results

Test Engineer:	Ivan Chen	Temperature:	24~25	°C
Test Date:	2016/7/31~2016/8/30	Relative Humidity:	54~55	%

TEST RESULTS DATA
6dB and 26dB EBW and 99% OBW

Band IV									
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	99% Bandwidth (MHz)	26 dB Bandwidth (MHz)	6 dB Bandwidth (MHz)	6dB Bandwidth min. Limit (MHz)	Pass/Fail
11a	6M bps	1	149	5745	18.33	23.53	16.34	0.5	Pass
11a	6Mbps	1	157	5785	18.68	23.28	16.34	0.5	Pass
11a	6Mbps	1	165	5825	18.68	23.58	16.38	0.5	Pass
HT20	MCS 0	1	149	5745	19.23	23.73	17.58	0.5	Pass
HT20	MCS 0	1	157	5785	19.28	23.83	17.58	0.5	Pass
HT20	MCS 0	1	165	5825	19.08	23.48	17.58	0.5	Pass
HT40	MCS 0	1	151	5755	36.56	45.14	35.33	0.5	Pass
HT40	MCS 0	1	159	5795	36.66	44.42	35.37	0.5	Pass
VHT20	MCS 0	1	149	5745	19.13	23.88	17.56	0.5	Pass
VHT20	MCS 0	1	157	5785	19.13	23.88	17.58	0.5	Pass
VHT20	MCS 0	1	165	5825	19.03	23.58	17.58	0.5	Pass
VHT40	MCS 0	1	151	5755	36.76	44.51	35.33	0.5	Pass
VHT40	MCS 0	1	159	5795	36.76	44.96	35.37	0.5	Pass
VHT80	MCS 0	1	155	5775	74.81	83.28	75.05	0.5	Pass

TEST RESULTS DATA
Average Power Table

Band IV										
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)		Pass/Fail
11a	6M bps	1	149	5745	0.58	7.98	30.00	-0.56		Pass
11a	6Mbps	1	157	5785	0.58	8.19	30.00	-0.56		Pass
11a	6Mbps	1	165	5825	0.58	8.23	30.00	-0.56		Pass
HT20	MCS 0	1	149	5745	0.62	7.49	30.00	-0.56		Pass
HT20	MCS 0	1	157	5785	0.62	7.70	30.00	-0.56		Pass
HT20	MCS 0	1	165	5825	0.62	7.78	30.00	-0.56		Pass
HT40	MCS 0	1	151	5755	1.49	7.84	30.00	-0.56		Pass
HT40	MCS 0	1	159	5795	1.49	7.75	30.00	-0.56		Pass
VHT20	MCS 0	1	149	5745	0.79	7.43	30.00	-0.56		Pass
VHT20	MCS 0	1	157	5785	0.79	7.72	30.00	-0.56		Pass
VHT20	MCS 0	1	165	5825	0.79	7.58	30.00	-0.56		Pass
VHT40	MCS 0	1	151	5755	1.48	7.64	30.00	-0.56		Pass
VHT40	MCS 0	1	159	5795	1.48	7.51	30.00	-0.56		Pass
VHT80	MCS 0	1	155	5775	2.57	7.76	30.00	-0.56		Pass

TEST RESULTS DATA
Power Spectral Density

Band IV										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	10log (500kHz /RBW) Factor (dB)	Average Power Density (dBm/500kHz)	Average PSD Limit (dBm/500kHz)	DG (dBi)	Pass/Fail
11a	6M bps	1	149	5745	0.58	2.22	-6.77	30.00	-0.56	Pass
11a	6Mbps	1	157	5785	0.58	2.22	-7.14	30.00	-0.56	Pass
11a	6Mbps	1	165	5825	0.58	2.22	-6.79	30.00	-0.56	Pass
HT20	MCS 0	1	149	5745	0.62	2.22	-6.31	30.00	-0.56	Pass
HT20	MCS 0	1	157	5785	0.62	2.22	-6.52	30.00	-0.56	Pass
HT20	MCS 0	1	165	5825	0.62	2.22	-5.78	30.00	-0.56	Pass
HT40	MCS 0	1	151	5755	1.49	2.22	-9.04	30.00	-0.56	Pass
HT40	MCS 0	1	159	5795	1.49	2.22	-8.67	30.00	-0.56	Pass
VHT20	MCS 0	1	149	5745	0.79	2.22	-6.65	30.00	-0.56	Pass
VHT20	MCS 0	1	157	5785	0.79	2.22	-6.57	30.00	-0.56	Pass
VHT20	MCS 0	1	165	5825	0.79	2.22	-6.25	30.00	-0.56	Pass
VHT40	MCS 0	1	151	5755	1.48	2.22	-9.28	30.00	-0.56	Pass
VHT40	MCS 0	1	159	5795	1.48	2.22	-8.74	30.00	-0.56	Pass
VHT80	MCS 0	1	155	5775	2.57	2.22	-11.46	30.00	-0.56	Pass

TEST RESULTS DATA
Frequency Stability

Band IV										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Center Frequency (MHz)	Frequency Deviation (MHz)	Frequency Stability (ppm)	Temperature (°C)	Voltage (V)	Note
11a	6M bps	1	149	5745	5745.025	0.025	4.35	50	3.8	
11a	6M bps	1	149	5745	5745.050	0.050	8.70	-30	3.8	
11a	6M bps	1	149	5745	5745.050	0.050	8.70	20	4.35	
11a	6M bps	1	149	5745	5745.050	0.050	8.70	20	3.4	
11a	6M bps	1	149	5745	5745.050	0.050	8.70	20	3.8	



Appendix B. Radiated Spurious Emission

Band 4 - 5725~5850MHz WIFI 802.11a (Band Edge @ 3m)

WIFI Ant.	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 149 5745MHz		5632.6	46.3	-22	68.3	38.97	33.17	7.65	33.49	150	196	P	H
		5692.8	55.07	-44.92	99.99	47.67	33.23	7.68	33.51	150	196	P	H
		5717.2	62.59	-47.53	110.12	55.18	33.25	7.68	33.52	150	196	P	H
		5724	73.44	-46.58	120.02	66.01	33.27	7.68	33.52	150	196	P	H
		5745	110.17	-	-	102.67	33.29	7.74	33.53	150	196	P	H
		5745	100.66	-	-	93.16	33.29	7.74	33.53	150	196	A	H
		5600.2	46.45	-21.85	68.3	39.17	33.12	7.64	33.48	150	340	P	V
		5692.6	50.79	-49.05	99.84	43.39	33.23	7.68	33.51	150	340	P	V
		5719.4	60.44	-50.29	110.73	53.01	33.27	7.68	33.52	150	340	P	V
		5720.6	66.71	-45.56	112.27	59.28	33.27	7.68	33.52	150	340	P	V
		5745	107.06	-	-	99.56	33.29	7.74	33.53	150	340	P	V
		5745	98.46	-	-	90.96	33.29	7.74	33.53	150	340	A	V



WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
		5640.8	46.64	-21.66	68.3	39.31	33.17	7.65	33.49	150	184	P	H
		5697.4	46.42	-56.96	103.38	39.02	33.23	7.68	33.51	150	184	P	H
		5718	48.77	-61.57	110.34	41.34	33.27	7.68	33.52	150	184	P	H
		5720.2	49.17	-62.19	111.36	41.74	33.27	7.68	33.52	150	184	P	H
		5785	109.99	-	-	102.4	33.33	7.8	33.54	150	184	P	H
		5785	102.77	-	-	95.18	33.33	7.8	33.54	150	184	A	H
		5851	47.62	-72.40	120.02	39.9	33.41	7.87	33.56	150	184	P	H
		5859.6	46.86	-62.75	109.61	39.12	33.43	7.87	33.56	150	184	P	H
		5888.6	47.13	-48.07	95.2	39.31	33.48	7.91	33.57	150	184	P	H
		5946.8	46.2	-22.1	68.3	38.29	33.54	7.95	33.58	150	184	P	H
		5636.6	46.03	-22.27	68.3	38.7	33.17	7.65	33.49	150	320	P	V
		5699	46.5	-58.06	104.56	39.1	33.23	7.68	33.51	150	320	P	V
		5719.2	48.11	-62.57	110.68	40.68	33.27	7.68	33.52	150	320	P	V
		5721.4	47.54	-66.55	114.09	40.11	33.27	7.68	33.52	150	320	P	V
		5785	106.6	-	-	99.01	33.33	7.8	33.54	150	320	P	V
		5785	99.22	-	-	91.63	33.33	7.8	33.54	150	320	A	V
		5852.6	47.53	-68.84	116.37	39.81	33.41	7.87	33.56	150	320	P	V
		5858	47.54	-62.52	110.06	39.8	33.43	7.87	33.56	150	320	P	V
		5925	46.85	-21.45	68.3	39	33.52	7.91	33.58	150	320	P	V
		5925.2	46.95	-21.35	68.3	39.1	33.52	7.91	33.58	150	320	P	V



WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 165 5825MHz		5825	111.8	-	-	104.12	33.39	7.84	33.55	150	182	P	H
		5825	102.11	-	-	94.43	33.39	7.84	33.55	150	182	A	H
		5851.6	63.48	-55.17	118.65	55.76	33.41	7.87	33.56	150	182	P	H
		5855.6	60.71	-50.02	110.73	52.97	33.43	7.87	33.56	150	182	P	H
		5877.4	55.78	-47.74	103.52	48.01	33.46	7.87	33.56	150	182	P	H
		5936	46.75	-21.55	68.3	38.86	33.52	7.95	33.58	150	182	P	H
		5825	107.08	-	-	99.4	33.39	7.84	33.55	150	322	P	V
		5825	98.01	-	-	90.33	33.39	7.84	33.55	150	322	A	V
		5851.2	57.39	-62.17	119.56	49.67	33.41	7.87	33.56	150	322	P	V
		5855.2	58.17	-52.67	110.84	50.43	33.43	7.87	33.56	150	322	P	V
		5877	50.78	-53.03	103.81	43.01	33.46	7.87	33.56	150	322	P	V
		5925	45.69	-22.61	68.3	37.84	33.52	7.91	33.58	150	322	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11a (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 149 5745MHz		11490	50.39	-23.61	74	59.34	39.7	11.1	59.75	250	0	P	H
		17232	52.61	-15.69	68.3	55.91	40.06	14.89	58.25	150	0	P	H
		11490	48.09	-25.91	74	57.04	39.7	11.1	59.75	250	0	P	V
		17232	52.07	-16.23	68.3	55.37	40.06	14.89	58.25	150	0	P	V
802.11a CH 157 5785MHz		11570	49.05	-24.95	74	58.05	39.66	11.17	59.83	250	0	P	H
		17355	54.26	-14.04	68.3	56.94	40.34	14.78	57.8	150	0	P	H
		11570	48.61	-25.39	74	57.61	39.66	11.17	59.83	250	0	P	V
		17355	53.62	-14.68	68.3	56.3	40.34	14.78	57.8	150	0	P	V
802.11a CH 165 5825MHz		11650	49.21	-24.79	74	58.26	39.62	11.23	59.9	146	347	P	H
		17475	55.68	-12.62	68.3	57.74	40.62	14.67	57.35	100	360	P	H
		11650	48.64	-25.36	74	57.69	39.62	11.23	59.9	250	0	P	V
		17475	53.98	-14.32	68.3	56.04	40.62	14.67	57.35	150	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz
WIFI 802.11n HT20 (Band Edge @ 3m)

Table with 14 columns: WIFI Ant. 1, Note, Frequency (MHz), Level (dBµV/m), Over Limit (dB), Limit Line (dBµV/m), Read Level (dBµV), Antenna Factor (dB/m), Cable Loss (dB), Preamp Factor (dB), Ant Pos (cm), Table Pos (deg), Peak Avg. (P/A), Pol. (H/V). Rows include frequencies 5648, 5693.4, 5720, 5725, 5745, 5745, 5645.4, 5693.2, 5720, 5724.6, 5745, 5745.



WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 157 5785MHz		5630.6	46.65	-21.65	68.3	39.35	33.14	7.65	33.49	150	186	P	H
		5677.6	46.04	-42.72	88.76	38.66	33.21	7.67	33.5	150	186	P	H
		5719.6	48.92	-61.87	110.79	41.49	33.27	7.68	33.52	150	186	P	H
		5720.6	48.06	-64.21	112.27	40.63	33.27	7.68	33.52	150	186	P	H
		5785	110.56	-	-	102.97	33.33	7.8	33.54	150	186	P	H
		5785	102.92	-	-	95.33	33.33	7.8	33.54	150	186	A	H
		5853	49.05	-66.41	115.46	41.33	33.41	7.87	33.56	150	186	P	H
		5869.6	47.11	-59.7	106.81	39.37	33.43	7.87	33.56	150	186	P	H
		5889.6	46.82	-47.64	94.46	39	33.48	7.91	33.57	150	186	P	H
		5945.8	46.33	-21.97	68.3	38.42	33.54	7.95	33.58	150	186	P	H
		5611.2	45.54	-22.76	68.3	38.26	33.12	7.65	33.49	150	312	P	V
		5685.8	46.3	-48.52	94.82	38.9	33.23	7.68	33.51	150	312	P	V
		5717.8	45.86	-64.42	110.28	38.43	33.27	7.68	33.52	150	312	P	V
		5720.4	46.44	-65.37	111.81	39.01	33.27	7.68	33.52	150	312	P	V
		5785	104.56	-	-	96.97	33.33	7.8	33.54	150	312	P	V
		5785	96.86	-	-	89.27	33.33	7.8	33.54	150	312	A	V
		5851.4	45.61	-73.5	119.11	37.89	33.41	7.87	33.56	150	312	P	V
		5874.8	46.3	-59.06	105.36	38.53	33.46	7.87	33.56	150	312	P	V
	5885.2	45.59	-52.14	97.73	37.83	33.46	7.87	33.57	150	312	P	V	
	5937	45.03	-23.27	68.3	37.14	33.52	7.95	33.58	150	312	P	V	



WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 165 5825MHz		5825	111.88	-	-	104.2	33.39	7.84	33.55	150	184	P	H
		5825	105.49	-	-	97.81	33.39	7.84	33.55	150	184	A	H
		5850.2	65.08	-56.76	121.84	57.36	33.41	7.87	33.56	150	184	P	H
		5856	58.15	-52.47	110.62	50.41	33.43	7.87	33.56	150	184	P	H
		5876.4	56.82	-47.44	104.26	49.05	33.46	7.87	33.56	150	184	P	H
		5928.8	46.85	-21.45	68.3	38.96	33.52	7.95	33.58	150	184	P	H
		5825	104.37	-	-	96.69	33.39	7.84	33.55	150	313	P	V
		5825	96.88	-	-	89.2	33.39	7.84	33.55	150	313	A	V
		5850.4	57.6	-63.79	121.39	49.88	33.41	7.87	33.56	150	313	P	V
		5856.8	53.41	-56.99	110.4	45.67	33.43	7.87	33.56	150	313	P	V
		5876.6	50.98	-53.13	104.11	43.21	33.46	7.87	33.56	150	313	P	V
	5937.2	46.31	-21.99	68.3	38.42	33.52	7.95	33.58	150	313	P	V	
Remark	<ol style="list-style-type: none"> No other spurious found. All results are PASS against Peak and Average limit line. 												



Band 4 5725~5850MHz
WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20		11490	48.52	-25.48	74	57.47	39.7	11.1	59.75	250	0	P	H
		17235	52.07	-16.23	68.3	55.37	40.06	14.89	58.25	150	0	P	H
CH 149 5745MHz		11490	49.06	-24.94	74	58.01	39.7	11.1	59.75	250	0	P	V
		17235	52.62	-15.68	68.3	55.92	40.06	14.89	58.25	150	0	P	V
802.11n HT20		11570	48.84	-25.16	74	57.84	39.66	11.17	59.83	250	0	P	H
		17355	54.85	-13.45	68.3	57.53	40.34	14.78	57.8	150	0	P	H
CH 157 5785MHz		11570	49	-25	74	58	39.66	11.17	59.83	250	0	P	V
		17355	54.79	-13.51	68.3	57.47	40.34	14.78	57.8	150	0	P	V
802.11n HT20		11650	48.88	-25.12	74	57.93	39.62	11.23	59.9	250	0	P	H
		17475	54.88	-13.42	68.3	56.94	40.62	14.67	57.35	150	0	P	H
CH 165 5825MHz		11650	48.39	-25.61	74	57.44	39.62	11.23	59.9	250	0	P	V
		17475	54.82	-13.48	68.3	56.88	40.62	14.67	57.35	150	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**Band 4 5725~5850MHz
WIFI 802.11n HT40 (Band Edge @ 3m)**

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 151 5755MHz		5647.8	48.31	-19.99	68.3	40.96	33.17	7.67	33.49	160	186	P	H
		5694	49.83	-51.05	100.88	42.43	33.23	7.68	33.51	160	186	P	H
		5717	62.99	-47.07	110.06	55.58	33.25	7.68	33.52	160	186	P	H
		5720.4	68.27	-43.54	111.81	60.84	33.27	7.68	33.52	160	186	P	H
		5755	104.8	-	-	97.28	33.31	7.74	33.53	160	186	P	H
		5755	98.39	-	-	90.87	33.31	7.74	33.53	160	186	A	H
		5851.8	45.2	-73	118.2	37.48	33.41	7.87	33.56	160	186	P	H
		5857.8	48.7	-61.41	110.11	40.96	33.43	7.87	33.56	160	186	P	H
		5916.2	47.36	-27.43	74.79	39.53	33.5	7.91	33.58	160	186	P	H
		5930.8	46.11	-22.19	68.3	38.22	33.52	7.95	33.58	160	186	P	H
		5644.2	46.41	-21.89	68.3	39.08	33.17	7.65	33.49	150	211	P	V
		5651.4	47.75	-21.59	69.34	40.38	33.19	7.67	33.49	150	211	P	V
		5717.4	58.41	-51.76	110.17	51	33.25	7.68	33.52	150	211	P	V
		5724.8	60.09	-61.75	121.84	52.66	33.27	7.68	33.52	150	211	P	V
		5755	99.32	-	-	91.8	33.31	7.74	33.53	150	211	P	V
		5755	91.75	-	-	84.23	33.31	7.74	33.53	150	211	A	V
		5853.4	45.25	-69.3	114.55	37.53	33.41	7.87	33.56	150	211	P	V
		5859.4	46.72	-62.95	109.67	38.98	33.43	7.87	33.56	150	211	P	V
	5922.2	46.35	-24.01	70.36	38.5	33.52	7.91	33.58	150	211	P	V	
	5933.8	46.11	-22.19	68.3	38.22	33.52	7.95	33.58	150	211	P	V	



WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 159 5795MHz		5615.8	45.34	-22.96	68.3	38.04	33.14	7.65	33.49	150	174	P	H
		5692.6	49.21	-50.63	99.84	41.81	33.23	7.68	33.51	150	174	P	H
		5718.4	47.8	-62.65	110.45	40.37	33.27	7.68	33.52	150	174	P	H
		5722.6	46.26	-70.57	116.83	38.83	33.27	7.68	33.52	150	174	P	H
		5795	104.51	-	-	96.9	33.35	7.8	33.54	150	174	P	H
		5795	97.78	-	-	90.17	33.35	7.8	33.54	150	174	A	H
		5853.2	50.37	-64.63	115	42.65	33.41	7.87	33.56	150	174	P	H
		5856.8	51.34	-59.06	110.4	43.6	33.43	7.87	33.56	150	174	P	H
		5898.6	48.5	-39.3	87.8	40.68	33.48	7.91	33.57	150	174	P	H
		5931	45.49	-22.81	68.3	37.6	33.52	7.95	33.58	150	174	P	H
		5647.8	45.86	-22.44	68.3	38.51	33.17	7.67	33.49	177	97	P	V
		5685.2	46.28	-48.1	94.38	38.89	33.23	7.67	33.51	177	97	P	V
		5711	46.21	-62.17	108.38	38.8	33.25	7.68	33.52	177	97	P	V
		5722.8	43.84	-73.44	117.28	36.41	33.27	7.68	33.52	177	97	P	V
		5795	99.22	-	-	91.61	33.35	7.8	33.54	177	97	P	V
		5795	92.4	-	-	84.79	33.35	7.8	33.54	177	97	A	V
		5854.8	45.76	-65.6	111.36	38.02	33.43	7.87	33.56	177	97	P	V
		5855.6	45.89	-64.84	110.73	38.15	33.43	7.87	33.56	177	97	P	V
	5890.8	46.72	-46.85	93.57	38.9	33.48	7.91	33.57	177	97	P	V	
	5942	44.71	-23.59	68.3	36.8	33.54	7.95	33.58	177	97	P	V	
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz
WIFI 802.11n HT40 (Harmonic @ 3m)

Table with 14 columns: WIFI Ant. 1, Note, Frequency (MHz), Level (dBµV/m), Over Limit (dB), Limit Line (dBµV/m), Read Level (dBµV), Antenna Factor (dB/m), Cable Loss (dB), Preamp Factor (dB), Ant Pos (cm), Table Pos (deg), Peak Avg. (P/A), Pol. (H/V). Rows include test results for 802.11n HT40 CH 151 and 5755MHz, and 802.11n HT40 CH 159 and 5795MHz. A Remark section at the bottom states: 1. No other spurious found. 2. All results are PASS against Peak and Average limit line.



Band 4 5725~5850MHz
WIFI 802.11ac VHT20 (Band Edge @ 3m)

Table with 14 columns: WIFI Ant. 1, Note, Frequency (MHz), Level (dBµV/m), Over Limit (dB), Limit Line (dBµV/m), Read Level (dBµV), Antenna Factor (dB/m), Cable Loss (dB), Preamp Factor (dB), Ant Pos (cm), Table Pos (deg), Peak Avg. (P/A), Pol. (H/V). Rows include frequencies from 5649.6 to 5740 MHz.



WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT20 CH 157 5785MHz		5642.2	45.57	-22.73	68.3	38.24	33.17	7.65	33.49	150	185	P	H
		5697.8	46.07	-57.61	103.68	38.67	33.23	7.68	33.51	150	185	P	H
		5716.6	48.77	-61.18	109.95	41.36	33.25	7.68	33.52	150	185	P	H
		5720.8	47.86	-64.86	112.72	40.43	33.27	7.68	33.52	150	185	P	H
		5785	109.73	-	-	102.14	33.33	7.8	33.54	150	185	P	H
		5785	102.49	-	-	94.9	33.33	7.8	33.54	150	185	A	H
		5853.6	47.66	-66.43	114.09	39.92	33.43	7.87	33.56	150	185	P	H
		5862.4	46.69	-62.14	108.83	38.95	33.43	7.87	33.56	150	185	P	H
		5901.6	46.88	-38.7	85.58	39.06	33.48	7.91	33.57	150	185	P	H
		5936.6	46.52	-21.78	68.3	38.63	33.52	7.95	33.58	150	185	P	H
		5627.8	45.26	-23.04	68.3	37.96	33.14	7.65	33.49	150	312	P	V
		5661.6	45.51	-31.4	76.91	38.15	33.19	7.67	33.5	150	312	P	V
		5705.6	45.77	-61.1	106.87	38.36	33.25	7.68	33.52	150	312	P	V
		5723.8	45.29	-74.27	119.56	37.86	33.27	7.68	33.52	150	312	P	V
		5785	104.29	-	-	96.7	33.33	7.8	33.54	150	312	P	V
		5785	97.37	-	-	89.78	33.33	7.8	33.54	150	312	A	V
		5851.6	46.41	-72.24	118.65	38.69	33.41	7.87	33.56	150	312	P	V
		5868.2	47	-60.2	107.2	39.26	33.43	7.87	33.56	150	312	P	V
	5877.8	45.86	-57.36	103.22	38.09	33.46	7.87	33.56	150	312	P	V	
	5936.6	45.67	-22.63	68.3	37.78	33.52	7.95	33.58	150	312	P	V	



WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT20 CH 165 5825MHz		5825	109.66	-	-	101.98	33.39	7.84	33.55	159	184	P	H
		5825	102.23	-	-	94.55	33.39	7.84	33.55	159	184	A	H
		5850	58.95	-63.35	122.3	51.23	33.41	7.87	33.56	159	184	P	H
		5859.2	55.28	-54.44	109.72	47.54	33.43	7.87	33.56	159	184	P	H
		5876.6	55.83	-48.28	104.11	48.06	33.46	7.87	33.56	159	184	P	H
		5925.8	45.7	-22.6	68.3	37.81	33.52	7.95	33.58	159	184	P	H
		5825	104.67	-	-	96.99	33.39	7.84	33.55	150	313	P	V
		5825	97.76	-	-	90.08	33.39	7.84	33.55	150	313	A	V
		5850	55.41	-66.89	122.3	47.69	33.41	7.87	33.56	150	313	P	V
		5856.2	49.15	-61.41	110.56	41.41	33.43	7.87	33.56	150	313	P	V
	5876.6	50.44	-53.67	104.11	42.67	33.46	7.87	33.56	150	313	P	V	
	5942.6	45.79	-22.51	68.3	37.88	33.54	7.95	33.58	150	313	P	V	
Remark	<ol style="list-style-type: none"> No other spurious found. All results are PASS against Peak and Average limit line. 												



Band 4 5725~5850MHz
WIFI 802.11ac VHT20 (Harmonic @ 3m)

Table with 14 columns: WIFI Ant. 1, Note, Frequency (MHz), Level (dBµV/m), Over Limit (dB), Limit Line (dBµV/m), Read Level (dBµV), Antenna Factor (dB/m), Cable Loss (dB), Preamp Factor (dB), Ant Pos (cm), Table Pos (deg), Peak Avg. (P/A), Pol. (H/V). Rows include channels 149, 157, 165 and frequencies 11490, 17235, 11570, 17355, 11650, 17475.

Remark

- 1. No other spurious found.
2. All results are PASS against Peak and Average limit line.



Band 4 5725~5850MHz
WIFI 802.11ac VHT40 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT40 CH 151 5755MHz		5648.4	49.02	-19.28	68.3	41.67	33.17	7.67	33.49	150	172	P	H
		5693	50.81	-49.33	100.14	43.41	33.23	7.68	33.51	150	172	P	H
		5719.6	63.66	-47.13	110.79	56.23	33.27	7.68	33.52	150	172	P	H
		5720.8	65.33	-47.39	112.72	57.9	33.27	7.68	33.52	150	172	P	H
		5755	104.9	-	-	97.38	33.31	7.74	33.53	150	172	P	H
		5755	97.62	-	-	90.1	33.31	7.74	33.53	150	172	A	H
		5852.8	44.88	-71.04	115.92	37.16	33.41	7.87	33.56	150	172	P	H
		5859.6	49.77	-59.84	109.61	42.03	33.43	7.87	33.56	150	172	P	H
		5883.6	47.74	-51.17	98.91	39.98	33.46	7.87	33.57	150	172	P	H
		5950	45.56	-22.74	68.3	37.65	33.54	7.95	33.58	150	172	P	H
		5622.6	46.05	-22.25	68.3	38.75	33.14	7.65	33.49	150	311	P	V
		5692.8	47.11	-52.88	99.99	39.71	33.23	7.68	33.51	150	311	P	V
		5719.6	57.06	-53.73	110.79	49.63	33.27	7.68	33.52	150	311	P	V
		5720.8	58.89	-53.83	112.72	51.46	33.27	7.68	33.52	150	311	P	V
		5755	100.96	-	-	93.44	33.31	7.74	33.53	150	311	P	V
		5755	94.27	-	-	86.75	33.31	7.74	33.53	150	311	A	V
		5851.8	44.14	-74.06	118.2	36.42	33.41	7.87	33.56	150	311	P	V
		5860.4	46.75	-62.64	109.39	39.01	33.43	7.87	33.56	150	311	P	V
	5881.8	46.89	-53.36	100.25	39.12	33.46	7.87	33.56	150	311	P	V	
	5928.2	46.26	-22.04	68.3	38.37	33.52	7.95	33.58	150	311	P	V	



WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT40 CH 159 5795MHz		5643.4	46.22	-22.08	68.3	38.89	33.17	7.65	33.49	150	186	P	H
		5692.6	51.14	-48.7	99.84	43.74	33.23	7.68	33.51	150	186	P	H
		5717.4	47.61	-62.56	110.17	40.2	33.25	7.68	33.52	150	186	P	H
		5721.6	47.18	-67.37	114.55	39.75	33.27	7.68	33.52	150	186	P	H
		5795	105.18	-	-	97.57	33.35	7.8	33.54	150	186	P	H
		5795	97.72	-	-	90.11	33.35	7.8	33.54	150	186	A	H
		5851.4	52.35	-66.76	119.11	44.63	33.41	7.87	33.56	150	186	P	H
		5858.4	50.22	-59.73	109.95	42.48	33.43	7.87	33.56	150	186	P	H
		5902.2	48.04	-37.09	85.13	40.22	33.48	7.91	33.57	150	186	P	H
		5941.6	46.85	-21.45	68.3	38.94	33.54	7.95	33.58	150	186	P	H
		5646.2	45.41	-22.89	68.3	38.06	33.17	7.67	33.49	150	311	P	V
		5687.6	46.84	-49.31	96.15	39.44	33.23	7.68	33.51	150	311	P	V
		5704.6	45.64	-60.95	106.59	38.22	33.25	7.68	33.51	150	311	P	V
		5723.4	45.57	-73.08	118.65	38.14	33.27	7.68	33.52	150	311	P	V
		5795	99.32	-	-	91.71	33.35	7.8	33.54	150	311	P	V
		5795	91.2	-	-	83.59	33.35	7.8	33.54	150	311	A	V
		5852.6	45.38	-70.99	116.37	37.66	33.41	7.87	33.56	150	311	P	V
		5867.2	47.98	-59.5	107.48	40.24	33.43	7.87	33.56	150	311	P	V
	5883.6	48.14	-50.77	98.91	40.38	33.46	7.87	33.57	150	311	P	V	
	5949.8	46.3	-22	68.3	38.39	33.54	7.95	33.58	150	311	P	V	
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz
WIFI 802.11ac VHT40 (Harmonic @ 3m)

Table with 14 columns: WIFI Ant. 1, Note, Frequency (MHz), Level (dBµV/m), Over Limit (dB), Limit Line (dBµV/m), Read Level (dBµV), Antenna Factor (dB/m), Cable Loss (dB), Preamp Factor (dB), Ant Pos (cm), Table Pos (deg), Peak Avg. (P/A), Pol. (H/V). Rows include test results for 802.11ac VHT40 CH 151 and 5755MHz, and 802.11ac VHT40 CH 159 and 5795MHz. A Remark section at the bottom states: 1. No other spurious found. 2. All results are PASS against Peak and Average limit line.



Band 4 5725~5850MHz
WIFI 802.11ac VHT80 (Band Edge @ 3m)

Table with 14 columns: WIFI Ant. 1, Note, Frequency (MHz), Level (dBµV/m), Over Limit (dB), Limit Line (dBµV/m), Read Level (dBµV), Antenna Factor (dB/m), Cable Loss (dB), Preamp Factor (dB), Ant Pos (cm), Table Pos (deg), Peak Avg. (P/A), Pol. (H/V). Rows include frequency measurements from 5646.2 to 5947.2 MHz.

Remark
1. No other spurious found.
2. All results are PASS against Peak and Average limit line.



Band 4 5725~5850MHz

WIFI 802.11ac VHT80 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac		11550	47.04	-26.96	74	56.05	39.67	11.13	59.81	250	0	P	H
VHT80		17328	52.79	-15.51	68.3	55.68	40.26	14.78	57.93	150	0	P	H
CH 155		11550	48.01	-25.99	74	57.02	39.67	11.13	59.81	250	0	P	V
5775MHz		17328	52.7	-15.6	68.3	55.59	40.26	14.78	57.93	150	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission below 1GHz
5GHz WIFI 802.11a (LF @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
5GHz 802.11a LF		33.88	31.4	-8.6	40	39.14	25.02	0.62	33.38	103	57	P	H
		97.9	26.95	-16.55	43.5	40.73	18.6	0.99	33.37	-	-	P	H
		180.35	22.83	-20.67	43.5	38.28	16.46	1.28	33.19	-	-	P	H
		238.55	26.56	-19.44	46	40.82	17.45	1.4	33.11	-	-	P	H
		478.14	29.08	-16.92	46	35.97	23.67	1.99	32.55	-	-	P	H
		940.83	33.06	-12.94	46	32.04	29.24	2.88	31.1	-	-	P	H
		33.88	32.73	-7.27	40	40.47	25.02	0.62	33.38	148	306	P	V
		92.08	27.21	-16.29	43.5	41.6	18	0.99	33.38	-	-	P	V
		239.52	26.7	-19.3	46	40.92	17.49	1.4	33.11	-	-	P	V
		443.22	26.47	-19.53	46	32.18	25.05	1.89	32.65	-	-	P	V
		768.17	29.95	-16.05	46	31.77	27.34	2.52	31.68	-	-	P	V
		950.53	32.99	-13.01	46	31.75	29.42	2.88	31.06	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

- Level(dBμV/m) =
Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
- Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

- Level(dBμV/m)
= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)
= 55.45 (dBμV/m)
- Over Limit(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 55.45(dBμV/m) – 74(dBμV/m)
= -18.55(dB)

For Average Limit @ 2390MHz:

- Level(dBμV/m)
= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)
= 43.54 (dBμV/m)
- Over Limit(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 43.54(dBμV/m) – 54(dBμV/m)
= -10.46(dB)


Both peak and average measured complies with the limit line, so test result is “PASS”.



Appendix C. Duty Cycle Plots

Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
802.11a	87.44	1.36	0.73	1kHz
802.11n HT20	86.70	1.28	0.78	1kHz
802.11n HT40	71.01	0.49	2.04	3kHz
802.11ac VHT20	83.33	0.98	1.02	3kHz
802.11ac VHT40	71.13	0.49	2.03	3kHz
802.11ac VHT80	55.34	0.25	4.04	10kHz


802.11a



Date: 31.JUL.2016 16:42:38




802.11n HT20



Date: 31.JUL.2016 16:43:47


802.11n HT40



Date: 31.JUL.2016 16:49:48




802.11ac VHT20



Date: 31.JUL.2016 16:44:38


802.11ac VH40



Date: 31.JUL.2016 16:52:18



802.11ac VHT80



Date: 31.JUL.2016 16:55:13