



# TEST REPORT

No. I14Z41308-GTE02

for

**ZTE CORPORATION**

**4G Wireless Router**

**Model Name: MF253M**

**FCC ID: SRQ-MF253MA**

with

**Hardware Version: MF253M.H01**

**Software Version: EN\_VIVO\_BR\_MF253MV1.0.1B02**

**Issued Date: 2015-07-07**

**Note:**

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

**Test Laboratory:**

***FCC 2.948 Listed: No. 525429***

CTTL, Telecommunication Technology Labs, Academy of Telecommunication Research, MIIT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512, Fax:+86(0)10-62304633-2504

Email: [ctl\\_terminals@catr.cn](mailto:ctl_terminals@catr.cn), website: [www.chinattl.com](http://www.chinattl.com)



## **REPORT HISTORY**

<b>Report Number</b>	<b>Revision</b>	<b>Description</b>	<b>Issue Date</b>
I15Z41308-GTE02	Rev.0	1st edition	2015-07-07



## **CONTENTS**

<b>1. TEST LABORATORY .....</b>	<b>4</b>
<b>1.1. TESTING LOCATION .....</b>	<b>4</b>
<b>1.1. TESTING ENVIRONMENT .....</b>	<b>4</b>
<b>1.2. PROJECT DATA .....</b>	<b>4</b>
<b>1.3. SIGNATURE .....</b>	<b>4</b>
<b>2. CLIENT INFORMATION .....</b>	<b>5</b>
<b>2.1. APPLICANT INFORMATION .....</b>	<b>5</b>
<b>2.2. MANUFACTURER INFORMATION .....</b>	<b>5</b>
<b>3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) .....</b>	<b>6</b>
<b>3.1. ABOUT EUT .....</b>	<b>6</b>
<b>3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST .....</b>	<b>6</b>
<b>3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST .....</b>	<b>6</b>
<b>3.4. GENERAL DESCRIPTION .....</b>	<b>6</b>
<b>4. REFERENCE DOCUMENTS .....</b>	<b>7</b>
<b>4.1. REFERENCE DOCUMENTS FOR TESTING .....</b>	<b>7</b>
<b>5. LABORATORY ENVIRONMENT .....</b>	<b>8</b>
<b>6. SUMMARY OF TEST RESULTS .....</b>	<b>9</b>
<b>7. TEST EQUIPMENTS UTILIZED .....</b>	<b>10</b>
<b>ANNEX A: MEASUREMENT RESULTS.....</b>	<b>11</b>
<b>A.1 OUTPUT POWER .....</b>	<b>11</b>
<b>A.2 EMISSION LIMIT.....</b>	<b>15</b>
<b>A.3 FREQUENCY STABILITY .....</b>	<b>21</b>
<b>A.4 OCCUPIED BANDWIDTH .....</b>	<b>23</b>
<b>A.5 EMISSION BANDWIDTH .....</b>	<b>28</b>
<b>A.6 BAND EDGE COMPLIANCE.....</b>	<b>32</b>
<b>A.7 CONDUCTED SPURIOUS EMISSION .....</b>	<b>35</b>
<b>A.8 PEAK-TO-AVERAGE POWER RATIO .....</b>	<b>51</b>

## 1. Test Laboratory

### 1.1. Testing Location

Company Name: CTTL, Telecommunication Technology Labs, Academy of  
Telecommunication Research, MIIT  
Address: No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China  
100191.  
Postal Code: 100191  
Telephone: 00861062304633  
Fax: 00861062304793

### 1.1. Testing Environment

Normal Temperature: 15-35°C  
Relative Humidity: 20-75%

### 1.2. Project data

Testing Start Date: 2015-06-17  
Testing End Date: 2015-07-03

### 1.3. Signature



---

Shen Yi


(Prepared this test report)



---

Zhong Nan

(Reviewed this test report)



---

Sun Xiang Qian

Deputy Director of the laboratory  
(Approved this test report)



## **2. Client Information**

### **2.1. Applicant Information**

Company Name: ZTE CORPORATION  
Address /Post: ZTE Plaza, Keji Road South, Shenzhen, China  
Contact Person: Min Zhang  
Contact Email: zhang.min13@zte.com.cn  
Telephone: +86 18616587757  
Fax: +86 021 50801070

### **2.2. Manufacturer Information**

Company Name: ZTE CORPORATION  
Address /Post: ZTE Plaza, Keji Road South, Shenzhen, China  
Contact Person: Min Zhang  
Contact Email: zhang.min13@zte.com.cn  
Telephone: +86 18616587757  
Fax: +86 021 50801070

### **3. Equipment Under Test (EUT) and Ancillary Equipment (AE)**

#### **3.1. About EUT**

Description	4G Wireless Router
Model Name	MF253M
FCC ID	SRQ-MF253MA
Antenna	Integrated
Output power	24.65dBm maximum EIRP measured for Band II
Extreme vol. Limits	3.2VDC to 3.6VDC (nominal: 3.3VDC)
Extreme temp. Tolerance	-30°C to +50°C

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of CTTL, Telecommunication Technology Labs, Academy of Telecommunication Research, MIIT

#### **3.2. Internal Identification of EUT used during the test**

<b>EUT ID*</b>	<b>IMEI</b>	<b>HW Version</b>	<b>SW Version</b>
UT06a	004401783228535	MF253M.H01	EN_VIVO_BR_MF253MV1.0.1B02
UT17a	865461026007722	MF253M.H01	EN_VIVO_BR_MF253MV1.0.1B02

#### **3.3. Internal Identification of AE used during the test**

<b>AE ID*</b>	<b>Description</b>
AE1	Charger

AE1

Model	STC-A2O120150C55-A
Manufacturer	Ruide

\*AE ID: is used to identify the test sample in the lab internally.

#### **3.4. General Description**

The Equipment Under Test (EUT) is a model of 4G Wireless Router with integrated antenna. Manual and specifications of the EUT were provided to fulfil the test.



## 4. Reference Documents

### 4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

<b>Reference</b>	<b>Title</b>	<b>Version</b>
FCC Part 24	PERSONAL COMMUNICATIONS SERVICES	10-1-14 Edition
FCC Part 22	PUBLIC MOBILE SERVICES	10-1-14 Edition
ANSI/TIA-603-C	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards	2004
ANSI C63.4	Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2009
KDB 971168 D01	Measurement Guidance for Certification of Licensed Digital Transmitters	v02r02

## 5. LABORATORY ENVIRONMENT

**Control room / conducted chamber** did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. =20 %, Max. = 80 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 2 MΩ
Ground system resistance	< 0.5 Ω

**Fully-anechoic chamber 2** (8.6 meters×6.1 meters×3.85 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 2 MΩ
Ground system resistance	< 1 Ω
Site voltage standing-wave ratio ( $S_{VSWR}$ )	Between 0 and 6 dB, from 1GHz to 18GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 4000 MHz

**Semi-anechoic chamber 2 / Fully-anechoic chamber 3** (10 meters×6.7 meters×6.15 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	> 100 dB
Electrical insulation	> 2 MΩ
Ground system resistance	< 0.5 Ω
Normalised site attenuation (NSA)	< ±3.5 dB, 3 m distance
Site voltage standing-wave ratio ( $S_{VSWR}$ )	Between 0 and 6 dB, from 1GHz to 18GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 3000 MHz



## **6. SUMMARY OF TEST RESULTS**

<b>Items</b>	<b>List</b>	<b>Clause in FCC rules</b>	<b>Verdict</b>
1	Output Power	22.913(a)/24.232(c)	P
2	Emission Limit	2.1051/22.917/24.238	P
3	Frequency Stability	2.1055/24.235	P
4	Occupied Bandwidth	2.1049(h)(i)	P
5	Emission Bandwidth	22.917(b)/24.238(b)	P
6	Band Edge Compliance	22.917(b)/24.238(b)	P
7	Conducted Spurious Emission	2.1057/22.917/24.238	P
8	Peak to Average Ratio	24.232 (d)	P

## 7. Test Equipments Utilized

NO.	Description	TYPE	series number	MANUFACTURE	CAL DUE DATE	Calibration interval
1	Test Receiver	ESU26	100235	R&S	2016/3/2	1 year
2	Test Receiver	ESU26	100376	R&S	2015-10-29	1 year
3	EMI Antenna	VULB 9163	302	Schwarzbeck	2017-1-3	3 year
4	EMI Antenna	3117	00119024	ETS-Lindgren	2016-01-20	3 year
5	LISN	NV216	101200	R&S	2015-07-07	1 year
6	Universal Radio Communication Tester	CMU200	108646	R&S	2015-10-28	1 year
7	Universal Radio Communication Tester	E5515C	MY48361083	Agilent	2016-02-27	1 year
8	Spectrum Analyzer	E4440A	MY48250642	Agilent	2016-03-02	1 year
9	EMI Antenna	9117	167	Schwarzbeck	2016-04-01	3 year
10	EMI Antenna	VULB 9163	9163 175	Schwarzbeck	2015-07-15	3 year
11	EMI Antenna	3117	00119024	ETS-Lindgren	2016-01-20	3 year
12	Signal Generator	N5183A	MY49060052	Agilent	2016-03-02	1 year
13	Climate chamber	SH-241	92007454	ESPEC	2015-12-14	2 year
14	Loop Antenna	HFH2-Z2	829324/007	R&S	2017-12-10	3 year

## **ANNEX A: MEASUREMENT RESULTS**

### **A.1 OUTPUT POWER**

#### **A.1.1 Summary**

During the process of testing, the EUT was controlled via Rhode & Schwarz Digital Radio Communication tester (CMU-200) to ensure max power transmission and proper modulation. This result contains peak output power and EIRP measurements for the EUT. In all cases, output power is within the specified limits.

#### **A.1.2 Conducted**

##### **A.1.2.1 Method of Measurements**

The EUT was set up for the max output power with pseudo random data modulation. The power was measured with Rhode & Schwarz Spectrum Analyzer FSU (peak) These measurements were done at 3 frequencies, 1852.4 MHz, 1880.0MHz and 1907.6MHz for WCDMA Band II; 826.4MHz, 836.6MHz and 846.6MHz for WCDMA Band V. (bottom, middle and top of operational frequency range).

##### **Limit**

According to FCC§2.1046.

#### **WCDMA Band II**

##### **Measurement result**

	CH	Frequency(MHz)	output power(dBm)
WCDMA (Band II)	9262	1852.4	22.14
	9400	1880.0	22.85
	9538	1907.6	22.65

#### **WCDMA Band V**

##### **Measurement result**

	CH	Frequency(MHz)	output power(dBm)
WCDMA (Band V)	4132	826.4	22.44
	4183	836.6	22.56
	4233	846.6	22.03

### A.1.3 Radiated

#### A.1.3.1 Description

This is the test for the maximum radiated power from the EUT.


Rule Part 24.232(c) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power" and 24.232(c) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage."

Rule Part 22.913(a) specifies " The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts."


#### A.1.3.2 Method of Measurement

The measurements procedures in TIA-603C-2004 are used.

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere

with the radiation pattern of the antenna. A power ( $P_{Mea}$ ) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded ( $P_r$ ). The power of signal source ( $P_{Mea}$ ) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna.  
The cable loss ( $P_{cl}$ ), the Substitution Antenna Gain ( $G_a$ ) and the Amplifier Gain ( $P_{Ag}$ ) should be recorded after test.

The measurement results are obtained as described below:

$$\text{Power(EIRP)} = P_{Mea} - P_{Ag} - P_{cl} - G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole,  $ERP = EIRP - 2.15\text{dBi}$ .

**WCDMA Band II-EIRP**

**Limits**

	Burst Peak EIRP (dBm)
WCDMA Band II	≤33dBm (2W)

**Measurement result**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1852.40	-22.82	2.84	-43.75	-4.87	22.96	33.00	10.04	V
1880.00	-21.77	2.85	-43.75	-4.82	23.95	33.00	9.05	V
1907.60	-21.01	2.88	-43.77	-4.77	<b>24.65</b>	33.00	8.35	V

Frequency: 1907.60MHz

Peak EIRP(dBm)= P<sub>Mea</sub>(-21.01)- P<sub>cl</sub>(2.88dB)- P<sub>Ag</sub>(-43.77dB)-G<sub>a</sub>(-4.77dB) =24.65dBm

**ANALYZER SETTINGS: RBW = VBW = 5MHz**

**WCDMA Band V-ERP**

**Limits**

	Burst Peak EIRP (dBm)
WCDMA Band V	≤38.45dBm

**Measurement result**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
826.40	-19.51	2.25	-45.76	-0.93	2.15	22.78	38.45	15.67	V
836.60	-21.39	2.26	-45.66	-0.82	2.15	20.68	38.45	17.77	V
846.60	-18.66	2.26	-45.56	-0.81	2.15	<b>23.30</b>	38.45	15.15	V

Frequency: 846.60MHz

Peak ERP(dBm)= P<sub>Mea</sub>(-18.66dBm)- P<sub>cl</sub>(2.26dB)- P<sub>Ag</sub>(-45.56dB)-G<sub>a</sub> (-0.81dB)-2.15dB=23.30dBm

**ANALYZER SETTINGS: RBW = VBW = 5MHz**

**Note: The EUT is tested in vertical polarization mode**

## A.2 EMISSION LIMIT


### A.2.1 Measurement Method

The measurements procedures in TIA-603C-2004 are used.


The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment. The resolution bandwidth is set as outlined in Part 24.238 and Part 24.917. The spectrum is scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of WCDMA Band II ,WCDMA Band V.

#### The procedure of radiated spurious emissions is as follows:

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as ( $P_r$ ).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power ( $P_{Mea}$ ) is applied to the input of the

substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded ( $P_r$ ). The power of signal source ( $P_{Mea}$ ) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. The Path loss ( $P_{pl}$ ) between the Signal Source with the Substitution Antenna and the Substitution Antenna Gain ( $G_a$ ) should be recorded after test.

A amplifier should be connected in for the test.

The Path loss ( $P_{pl}$ ) is the summation of the cable loss and the gain of the amplifier.

The measurement results are obtained as described below:

$$\text{Power(EIRP)} = P_{Mea} - P_{pl} - G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole,  $ERP = EIRP - 2.15\text{dBi}$ .

### **A.2.2 Measurement Limit**

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log(P)$  dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

### **A.2.3 Measurement Results**

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of WCDMA Band II (1852.4 MHz, 1880.0MHz and 1907.6MHz), WCDMA Band V(826.4MHz, 836.6MHz and 846.6MHz). It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the WCDMA Band II and WCDMA Band V into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this.

**A.2.4 Measurement Results Table**

Frequency	Channel	Frequency Range	Result
WCDMA Band V	Low	30MHz-10GHz	Pass
	Middle	30MHz-10GHz	Pass
	High	30MHz-10GHz	Pass
WCDMA Band II	Low	30MHz-10GHz	Pass
	Middle	30MHz-10GHz	Pass
	High	30MHz-10GHz	Pass

**A.2.5 Sweep Table**

Working Frequency	Subrange (GHz)	RBW	VBW	Sweep time (s)
WCDMA Band V	0.03~1	100KHz	300KHz	10
	1-2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~10	1 MHz	3 MHz	3
WCDMA Band II	0.03~1	100KHz	300KHz	10
	1-2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~11	1 MHz	3 MHz	3
	11~14	1 MHz	3 MHz	3
	14~18	1 MHz	3 MHz	3
	18~20	1 MHz	3 MHz	2



**WCDMA BAND II Mode Channel 9262/1852.4MHz**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path Loss	Antenna Gain	Peak EIRP(dBm)	Limit (dBm)	Margin(dB)	Polarization
3703.22	-64.75	5.35	-8.48	-61.62	-13.00	48.62	V
6919.56	-63.05	7.18	-11.50	-58.73	-13.00	45.73	H
10110.92	-62.61	8.33	-12.94	-58.00	-13.00	45.00	H
11814.55	-62.60	9.03	-13.04	-58.59	-13.00	45.59	H
14383.55	-56.19	10.26	-14.42	-52.03	-13.00	39.03	H
16533.13	-49.94	11.25	-13.61	-47.58	-13.00	34.58	H

**WCDMA BAND II Mode Channel 9400/1880MHz**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path Loss	Antenna Gain	Peak EIRP(dBm)	Limit (dBm)	Margin(dB)	Polarization
3566.98	-64.23	5.48	-8.29	-61.42	-13.00	48.42	V
5742.27	-65.39	6.78	-10.55	-61.62	-13.00	48.62	H
8376.44	-64.78	7.81	-12.90	-59.69	-13.00	46.69	V
10365.92	-61.31	8.48	-13.05	-56.74	-13.00	43.74	H
12207.16	-63.15	9.26	-13.08	-59.33	-13.00	46.33	H
13918.68	-56.25	10.05	-14.45	-51.85	-13.00	38.85	H

**WCDMA BAND II Mode Channel 9538/1907.6MHz**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path Loss	Antenna Gain	Peak EIRP(dBm)	Limit (dBm)	Margin(dB)	Polarization
3841.46	-65.66	5.82	-8.68	-62.80	-13.00	49.80	H
5751.88	-64.33	6.78	-10.55	-60.56	-13.00	47.56	H
7761.65	-66.69	7.34	-12.41	-61.62	-13.00	48.62	V
9465.91	-63.09	8.17	-13.38	-57.88	-13.00	44.88	H
11828.40	-58.32	9.04	-13.03	-54.33	-13.00	41.33	V
15347.62	-52.58	10.86	-13.79	-49.65	-13.00	36.65	H



**WCDMA BAND V Mode Channel 4132/826.4MHz**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path Loss	Antenna Gain	Correction (dB)	Peak ERP(dBm)	Limit (dBm)	Margin(dB)	Polarization
3198.42	-60.08	5.25	-7.48	2.15	-60.00	-13.00	47.00	V
4301.41	-70.54	5.96	-9.20	2.15	-69.45	-13.00	56.45	V
5519.73	-66.27	6.66	-10.60	2.15	-64.48	-13.00	51.48	H
6680.76	-63.70	7.38	-11.22	2.15	-62.01	-13.00	49.01	H
7441.23	-67.77	7.13	-12.13	2.15	-64.92	-13.00	51.92	V
8264.71	-64.70	7.92	-12.81	2.15	-61.96	-13.00	48.96	H

**WCDMA BAND V Mode Channel 4183/836.6MHz**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path Loss	Antenna Gain	Correction (dB)	Peak ERP(dBm)	Limit (dBm)	Margin(dB)	Polarization
3391.42	-66.73	5.44	-7.94	2.15	-66.38	-13.00	53.38	H
4400.65	-66.39	6.12	-9.30	2.15	-65.36	-13.00	52.36	H
5601.83	-67.72	6.76	-10.58	2.15	-66.05	-13.00	53.05	H
6859.06	-63.14	6.71	-11.43	2.15	-60.57	-13.00	47.57	V
7986.10	-64.17	7.45	-12.59	2.15	-61.18	-13.00	48.18	H
8654.47	-64.91	7.67	-13.03	2.15	-61.70	-13.00	48.70	V

**WCDMA BAND V Mode Channel 4233/846.6MHz**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path Loss	Antenna Gain	Correction (dB)	Peak ERP(dBm)	Limit (dBm)	Margin(dB)	Polarization
3088.32	-63.96	5.15	-7.21	2.15	-64.05	-13.00	51.05	H
4145.06	-65.86	5.78	-9.05	2.15	-64.74	-13.00	51.74	H
5751.66	-68.98	6.78	-10.55	2.15	-67.36	-13.00	54.36	V
7170.52	-63.94	7.10	-11.80	2.15	-61.39	-13.00	48.39	V
8264.59	-64.46	7.92	-12.81	2.15	-61.72	-13.00	48.72	V
9380.74	-64.62	8.03	-13.33	2.15	-61.47	-13.00	48.47	V

### **A.3 FREQUENCY STABILITY**

#### **A.3.1 Method of Measurement**

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMU200 DIGITAL RADIO COMMUNICATION TESTER.

1. Measure the carrier frequency at room temperature.
2. Subject the EUT to overnight soak at -30°C.
3. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on mid channel of WCDMA Band II and WCDMA Band V, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
4. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
5. Remeasure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments remeasuring carrier frequency at each voltage. Pause at nominal voltage for 1 1/2 hours unpowered, to allow any self-heating to stabilize, before continuing.
6. Subject the EUT to overnight soak at +50°C.
7. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
8. Repeat the above measurements at 10 C increments from +50°C to -30°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

#### **A.3.2 Measurement Limit**

##### **A.3.2.1 For Hand carried battery powered equipment**

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.2VDC and 3.6VDC, with a nominal voltage of 3.3VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress. These voltages represent a tolerance of -10 % and +12.5 %. For the purposes of measuring frequency stability these voltage limits are to be used.

##### **A.3.2.2 For equipment powered by primary supply voltage**

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the



fundamental emission stays within the authorized frequency block. For this EUT section 2.1055(d)(1) applies. This requires varying primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

**A.3.3 Measurement results**

**WCDMA Band II**

**Frequency Error vs Voltage**

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.2	-11	0.006
3.3	-14	0.007
3.6	7	0.004

**Frequency Error vs Temperature**

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-30	-21	0.011
-20	-4	0.002
-10	12	0.006
0	7	0.004
10	8	0.004
20	-8	0.004
30	9	0.005
40	6	0.003
50	10	0.005

**WCDMA Band V**

**Frequency Error vs Voltage**

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.2	-6	0.007
3.3	-5	0.007
3.6	-4	0.005

**Frequency Error vs Temperature**

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-30	-10	0.012
-20	-11	0.013
-10	-10	0.012
0	-4	0.004
10	-8	0.009
20	3	0.004
30	-3	0.004
40	-4	0.005
50	-4	0.005



## **A.4 OCCUPIED BANDWIDTH**

### **Reference**

FCC: CFR Part 2.1049(h)(i)

### **A.4.1 Occupied Bandwidth Results**

Occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of the US Cellular/PCS frequency bands. The table below lists the measured 99% BW. Spectrum analyzer plots are included on the following pages.


The measurement method is from KDB 971168 4.2:

- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be set wide enough to capture all modulation products including the emission skirts (i.e., two to five times the OBW).
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
- c) Set the reference level of the instrument as required to keep the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope must be at least  $10\log (OBW / RBW)$  below the reference level.
- d) Set the detection mode to peak, and the trace mode to max hold.
- e) Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

### **WCDMA Band II (99% BW)**


Frequency(MHz)	Occupied Bandwidth (99% BW)( MHz)
1852.4	4.119
1880.0	4.151
1907.6	4.135

**WCDMA Band II**  
**Channel 9262-Occupied Bandwidth (99% BW)**




Date: 9.JUN.2015 21:15:13

**Channel 9400-Occupied Bandwidth (99% BW)**



Date: 9.JUN.2015 21:15:47

### Channel 9538-Occupied Bandwidth (99% BW)




Date: 9.JUN.2015 21:16:22

**WCDMA Band V(99% BW)**

Frequency(MHz)	Occupied Bandwidth (99% BW)( MHz)
826.4	4.519
836.6	4.503
846.6	4.519


**WCDMA Band V**

**Channel 4132-Occupied Bandwidth (99% BW)**




Date: 9.JUN.2015 21:42:08

### Channel 4183-Occupied Bandwidth (99% BW)



Date: 9 JUN.2015 21:42:43

### Channel 4233-Occupied Bandwidth (99% BW)



Date: 9 JUN.2015 21:43:17

## A.5 EMISSION BANDWIDTH

### Reference

FCC: CFR Part 22.917(b), 24.238(a)

### A.5.1 Emission Bandwidth Results

The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


Similar to conducted emissions; Emission bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies. Table below lists the measured 100% BW. Spectrum analyzer plots are included on the following pages.

### WCDMA Band II (100% BW)

Frequency(MHz)	Emission Bandwidth (100% BW)( MHz)
1852.4	4.135
1880.0	4.151
1907.6	4.119


### WCDMA Band II

#### Channel 9262-Emission Bandwidth (100% BW)




Date: 9 JUN. 2015 21:16:58

### Channel 9400-Emission Bandwidth (100% BW)



Date: 9.JUN.2015 21:17:33

### Channel 9538-Emission Bandwidth (100% BW)




Date: 9.JUN.2015 21:18:08

**WCDMA Band V(100% BW)**

Frequency(MHz)	Emission Bandwidth (100% BW)( MHz)
826.40	4.471
836.60	4.487
846.60	4.487


**WCDMA Band V**

**Channel 4132-Emission Bandwidth (100% BW)**




Date: 9 JUN 2015 21:43:53

### Channel 4183-Emission Bandwidth (100% BW)



Date: 9.JUN.2015 21:44:28

### Channel 4233-Emission Bandwidth (100% BW)



Date: 9.JUN.2015 21:45:03

## A.6 BAND EDGE COMPLIANCE

### Reference

FCC: CFR Part 22.917(b), 24.238(a).


### A.6.1 Measurement limit

On any frequency outside frequency band of the US Cellular/PCS spectrum, the power of any emission shall be attenuated below the transmitter power (P, in Watts) by at least  $43+10\log(P)$  dB. For all power levels +30 dBm to 0 dBm, this becomes a constant specification limit of -13 dBm. According to KDB 971168 6.0, a relaxation of the reference bandwidth is often provided for measurements within a specified frequency range at the edge of the authorized frequency block/band. This is often implemented by permitting the use of a narrower RBW (typically limited to a minimum RBW of 1% of the OBW) for measuring the out-of-band emissions without a requirement to integrate the result over the full reference bandwidth.

### A.6.2 Measurement result

#### WCDMA Band II


#### LOW BAND EDGE BLOCK-A (WCDMA Band II)-Channel 9262



Date: 9.JUN.2015 21:18:19




### HIGH BAND EDGE BLOCK-C (WCDMA Band II) –Channel 9538




Date: 9.JUN.2015 21:20:26

**WCDMA Band V**  
**LOW BAND EDGE BLOCK-A (WCDMA Band V)-Channel 4132**



Date: 9.JUN.2015 21:45:14

**HIGH BAND EDGE BLOCK-C (WCDMA Band V) -Channel 4233**



Date: 9.JUN.2015 21:47:20

## **A.7 CONDUCTED SPURIOUS EMISSION**

### **Reference**

FCC: CFR Part 2.1057, 22.917, 24.238.

### **A.7.1 Measurement Method**

The following steps outline the procedure used to measure the conducted emissions from the EUT.

1. Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the mobile station equipment tested, this equates to a frequency range of 13 MHz to 9 GHz, data taken from 10 MHz to 25 GHz.
2. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.
3. According to KDB 971168 6.0, the applicable rule part specifies the reference bandwidth for measuring unwanted emission levels (typically, 100 kHz if the authorized frequency band/block is at or below 1 GHz and 1 MHz if the authorized frequency band/block is above 1 GHz)

#### **WCDMA Band II Transmitter**

Channel	Frequency (MHz)
9262	1852.40
9400	1880.00
9538	1907.60

#### **WCDMA Band V Transmitter**

Channel	Frequency (MHz)
4132	826.40
4183	836.60
4233	846.60

### **A.7.2 Measurement Limit**

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.


The specification that emissions shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log(P)$  dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

### A.7.3 Measurement result

#### WCDMA Band II

#### Channel 9262: 30MHz –1GHz

Spurious emission limit –13dBm.




Date: 9 JUN.2015 21:23:08

#### Channel 9262: 1GHz –2.5GHz


Spurious emission limit –13dBm.

**NOTE: peak above the limit line is the carrier frequency.**




Date: 9 JUN.2015 21:23:36

**Channel 9262: 2.5GHz –7.5GHz**  
Spurious emission limit –13dBm.




Date: 9.JUN.2015 21:24:05

**Channel 9262: 7.5GHz –10GHz**  
Spurious emission limit –13dBm.




Date: 9.JUN.2015 21:24:33

**Channel 9262: 10GHz –15GHz**  
Spurious emission limit –13dBm.




Date: 9.JUN.2015 21:25:01

**Channel 9262: 15GHz –20GHz**  
Spurious emission limit –13dBm.



Date: 9.JUN.2015 21:25:29


**Channel 9400: 30MHz –1GHz**  
Spurious emission limit –13dBm.



Date: 9 JUN. 2015 21:26:00


**Channel 9400: 1GHz –2.5GHz**  
Spurious emission limit –13dBm.

**NOTE: peak above the limit line is the carrier frequency.**




Date: 9 JUN. 2015 21:26:28

**Channel 9400: 2.5GHz –7.5GHz**  
Spurious emission limit –13dBm.




Date: 9.JUN.2015 21:26:56

**Channel 9400: 7.5GHz –10GHz**  
Spurious emission limit –13dBm.




Date: 9.JUN.2015 21:27:24

**Channel 9400: 10GHz –15GHz**  
Spurious emission limit –13dBm.




Date: 9.JUN.2015 21:27:53

**Channel 9400: 15GHz –20GHz**  
Spurious emission limit –13dBm.



Date: 9.JUN.2015 21:28:21


**Channel 9538: 30MHz –1GHz**  
Spurious emission limit –13dBm.



Date: 9 JUN. 2015 21:28:52


**Channel 9538: 1GHz –2.5GHz**  
Spurious emission limit –13dBm.

**NOTE: peak above the limit line is the carrier frequency.**




Date: 9 JUN. 2015 21:29:20

**Channel 9538: 2.5GHz –7.5GHz**  
Spurious emission limit –13dBm.




Date: 9.JUN.2015 21:29:48

**Channel 9538: 7.5GHz –10GHz**  
Spurious emission limit –13dBm.




Date: 9.JUN.2015 21:30:16

**Channel 9538: 10GHz –15GHz**  
Spurious emission limit –13dBm.



Date: 9.JUN.2015 21:30:44

**Channel 9538: 15GHz –20GHz**  
Spurious emission limit –13dBm.




Date: 9.JUN.2015 21:31:13

**WCDMA Band V**

**Channel 4132: 30MHz –1GHz**

Spurious emission limit –13dBm.


**NOTE: peak above the limit line is the carrier frequency.**



Date: 9.JUN.2015 21:50:03


**Channel 4132: 1GHz – 2.5GHz**

Spurious emission limit –13dBm.




Date: 9.JUN.2015 21:50:31

**Channel 4132: 2.5GHz –7.5GHz**  
Spurious emission limit –13dBm.



Date: 9 JUN. 2015 21:50:59

**Channel 4132: 7.5GHz – 10GHz**  
Spurious emission limit –13dBm.




Date: 9 JUN. 2015 21:51:27

**Channel 4183: 30MHz –1GHz**

Spurious emission limit –13dBm.


**NOTE: peak above the limit line is the carrier frequency.**



Date: 9.JUN.2015 21:51:58


**Channel 4183: 1GHz – 2.5GHz**

Spurious emission limit –13dBm.




Date: 9.JUN.2015 21:52:26

**Channel 4183: 2.5GHz –7.5GHz**  
Spurious emission limit –13dBm.



Date: 9 JUN. 2015 21:52:54

**Channel 4183: 7.5GHz – 10GHz**  
Spurious emission limit –13dBm.




Date: 9 JUN. 2015 21:53:23

**Channel 4233: 30MHz –1GHz**

Spurious emission limit –13dBm.


**NOTE: peak above the limit line is the carrier frequency.**



Date: 9.JUN.2015 21:53:54


**Channel 4233: 1GHz – 2.5GHz**

Spurious emission limit –13dBm.




Date: 9.JUN.2015 21:54:22

**Channel 4233: 2.5GHz –7.5GHz**  
Spurious emission limit –13dBm.



Date: 9 JUN. 2015 21:54:50

**Channel 4233: 7.5GHz – 10GHz**  
Spurious emission limit –13dBm.



Date: 9 JUN. 2015 21:55:18

## **A.8 PEAK-TO-AVERAGE POWER RATIO**

### **Reference**

FCC: CFR Part 24.232 (d)

The peak-to-average power ratio (PAPR) of the transmitter output power must not exceed 13 dB. The PAPR measurements should be made using either an instrument with complementary cumulative distribution function (CCDF) capabilities to determine that PAPR will not exceed 13 dB for more than 0.1 percent of the time or other Commission approved procedure. The measurement must be performed using a signal corresponding to the highest PAPR expected during periods of continuous transmission.

According to KDB 971168 5.7.1:

- a) Refer to instrument's analyzer instruction manual for details on how to use the power statistics/CCDF function;
- b) Set resolution/measurement bandwidth  $\geq$  signal's occupied bandwidth;
- c) Set the number of counts to a value that stabilizes the measured CCDF curve;
- d) Set the measurement interval to 1 ms
- e) Record the maximum PAPR level associated with a probability of 0.1%

### **A.8.1 Measurement limit**

not exceed 13 dB

### **A.8.2 Measurement results**

#### **WCDMA Band II**

#### **Measurement result**

	CH	Frequency(MHz)	PAPR(dB)
WCDMA (Band II)	9262	1852.4	3.43
	9400	1880.0	3.53
	9538	1907.6	3.46

**\*\*\*END OF REPORT\*\*\***