



FCC RF Test Report

APPLICANT : ZTE CORPORATION
EQUIPMENT : LTE USB Modem
BRAND NAME : ZTE
MODEL NAME : MF823L
MARKETING NAME : MF823L LTE USB Modem
FCC ID : SRQ-MF823L
STANDARD : FCC 47 CFR Part 2, 22(H), 24(E)
CLASSIFICATION : PCS Licensed Transmitter (PCB)

The product was received on Mar. 17, 2014 and testing was completed on Mar. 27, 2014. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI / TIA / EIA-603-C-2004 and shown to be compliant with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C.



TABLE OF CONTENTS

REVISION HISTORY..... 3

SUMMARY OF TEST RESULT 4

1 GENERAL DESCRIPTION 5

 1.1 Applicant..... 5

 1.2 Manufacturer 5

 1.3 Feature of Equipment Under Test..... 5

 1.4 Product Specification of Equipment Under Test 6

 1.5 Modification of EUT 6

 1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator 6

 1.7 Testing Site 7

 1.8 Applied Standards 7

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST 8

 2.1 Test Mode..... 8

 2.2 Connection Diagram of Test System 10

 2.3 Support Unit used in test configuration and system..... 10

 2.4 Measurement Results Explanation Example 11

3 TEST RESULT..... 12

 3.1 Conducted Output Power Measurement..... 12

 3.2 Peak-to-Average Ratio 14

 3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement 22

 3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement..... 28

 3.5 Band Edge Measurement..... 48

 3.6 Conducted Spurious Emission Measurement..... 61

 3.7 Field Strength of Spurious Radiation Measurement 77

 3.8 Frequency Stability Measurement..... 91

4 LIST OF MEASURING EQUIPMENT 96

5 UNCERTAINTY OF EVALUATION 98

APPENDIX A. SETUP PHOTOGRAPHS



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	§2.1046	Conducted Output Power	N/A	PASS	-
3.2	§24.232(d)	Peak-to-Average Ratio	< 13 dB	PASS	-
3.3	§22.913(a)(2)	Effective Radiated Power	< 7 Watts	PASS	-
3.3	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
3.4	§2.1049 §22.917(a) §24.238(b)	Occupied Bandwidth	N/A	PASS	-
3.5	§2.1051 §22.917(a) §24.238(a)	Band Edge Measurement	< 43+10log ₁₀ (P[Watts])	PASS	-
3.6	§2.1051 §22.917(a) §24.238(a)	Conducted Spurious Emission	< 43+10log ₁₀ (P[Watts])	PASS	-
3.7	§2.1053 §22.917(a) §24.238(a)	Field Strength of Spurious Radiation	< 43+10log ₁₀ (P[Watts])	PASS	Under limit 36.55 dB at 5638.000 MHz
3.8	§2.1055 §22.355 §24.235	Frequency Stability for Temperature & Voltage	< 2.5 ppm	PASS	-



1 General Description

1.1 Applicant

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

1.2 Manufacturer

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

1.3 Feature of Equipment Under Test

Product Feature	
Equipment	LTE USB Modem
Brand Name	ZTE
Model Name	MF823L
Marketing Name	MF823L LTE USB Modem
FCC ID	SRQ-MF823L
EUT supports Radios application	GPRS/EGPRS/WCDMA/HSPA/HSPA+/DC-HSDPA/LTE
HW Version	xm6B
SW Version	EN_ZTE_MF823LV1.0.0B03
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Product Specification subjective to this standard	
Tx Frequency	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz
Rx Frequency	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band II: 1932.4 MHz ~ 1987.6 MHz
Maximum Output Power to Antenna	GSM850 : 32.39 dBm GSM1900 : 29.45 dBm WCDMA Band V : 22.01 dBm WCDMA Band II : 22.22 dBm
Antenna Type	PCB Antenna
Type of Modulation	GPRS: GMSK EDGE: GMSK / 8PSK WCDMA: QPSK (Uplink) HSDPA/DC-HSDPA: QPSK (Uplink) HSUPA: QPSK (Uplink) HSPA+: 16QAM (Uplink) DC-HSDPA: 64QAM LTE: QPSK / 16QAM / 64QAM

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W)	Frequency Tolerance (ppm)	Emission Designator
Part 22	GPRS850 GPRS class 8	GMSK	0.70	0.04 ppm	248KGXW
Part 22	GPRS850 EDGE class 8	8PSK	0.23	0.04 ppm	248KG7W
Part 22	WCDMA Band V RMC 12.2Kbps	QPSK	0.07	0.04 ppm	4M20F9W
Part 24	GPRS1900 GPRS class 8	GMSK	1.71	0.02 ppm	250KGXW
Part 24	GPRS1900 EDGE class 8	8PSK	0.72	0.02 ppm	244KG7W
Part 24	WCDMA Band II RMC 12.2Kbps	QPSK	0.31	0.02 ppm	4M18F9W

1.7 Testing Site

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.			
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C. TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958			
Test Site No.	Sporton Site No.			FCC Registration No.
	TH01-KS	03CH01-KS	OTA01-KS	149928

1.8 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC 47 CFR Part 2, 22(H), 24(E)
- ANSI / TIA / EIA-603-C-2004
- FCC KDB 971168 D01 Power Meas. License Digital Systems v02r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range.

Frequency range investigated for radiated emission is as follows:

1. 30 MHz to 9000 MHz for GSM850 and WCDMA Band V.
2. 30 MHz to 19000 MHz for GSM1900 and WCDMA Band II.

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	<ul style="list-style-type: none"> ■ GPRS class 8 Link ■ EDGE class 8 Link 	<ul style="list-style-type: none"> ■ GPRS class 8 Link ■ EDGE class 8 Link
GSM 1900	<ul style="list-style-type: none"> ■ GPRS class 8 Link ■ EDGE class 8 Link 	<ul style="list-style-type: none"> ■ GPRS class 8 Link ■ EDGE class 8 Link
WCDMA Band V	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link 	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link
WCDMA Band II	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link 	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link

Note: The maximum power levels are GPRS multi-slot class 8 mode for GMSK link, EDGE multi-slot class 8 mode for 8PSK link, RMC 12.2Kbps mode for WCDMA band V, and RMC 12.2Kbps mode for WCDMA band II, only these modes were used for all tests.




The conducted power tables are as follows:

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GPRS class 8	32.39	32.08	32.23	29.32	29.40	29.45
GPRS class 10	30.96	30.71	30.86	27.71	27.89	27.94
EGPRS class 8	26.76	26.49	26.52	25.27	25.38	25.44
EGPRS class 10	24.41	24.05	24.13	23.10	23.22	23.31
EGPRS class 11	22.46	22.14	22.40	21.14	21.31	21.44
EGPRS class 12	21.81	21.56	21.76	20.76	20.84	20.90

Conducted Power (*Unit: dBm)						
Band	WCDMA Band V			WCDMA Band II		
Channel	4132	4182	4233	9262	9400	9538
Frequency	826.4	836.4	846.6	1852.4	1880.0	1907.6
RMC 12.2K	21.95	21.85	22.01	22.15	22.22	21.98
HSDPA Subtest-1	21.01	20.84	21.07	21.18	21.24	21.11
HSDPA Subtest-2	21.02	20.73	21.05	21.25	21.31	21.19
HSDPA Subtest-3	20.54	20.18	20.59	20.73	20.87	20.68
HSDPA Subtest-4	20.53	20.21	20.57	20.77	20.94	20.74
DC-HSDPA Subtest-1	20.93	20.76	20.99	21.10	21.16	21.03
DC-HSDPA Subtest-2	20.94	20.65	20.97	21.17	21.23	21.11
DC-HSDPA Subtest-3	20.46	20.10	20.51	20.65	20.79	20.60
DC-HSDPA Subtest-4	20.45	20.13	20.49	20.69	20.86	20.66
HSUPA Subtest-1	20.17	20.14	20.29	20.92	21.11	20.31
HSUPA Subtest-2	19.91	19.89	19.95	19.78	19.81	19.75
HSUPA Subtest-3	19.56	19.54	19.61	20.17	20.21	19.97
HSUPA Subtest-4	20.48	20.28	20.57	20.69	20.89	20.55
HSUPA Subtest-5	20.32	20.29	20.36	20.44	20.67	20.32
HSPA+ (16QAM) Subtest-1	20.73	20.71	20.82	20.89	20.96	20.74

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU200	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	GWINSTEK	GPS-3030D	N/A	N/A	Unshielded, 1.8 m
3.	Notebook	Lenovo	G480	N/A	N/A	N/A



2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 5.2 dB and 10dB attenuator.

Example :

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 5.2 + 10 = 15.2 \text{ (dB)} \end{aligned}$$

3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The transmitter output port was connected to base station.
2. Set EUT at maximum power through base station.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.

3.1.4 Test Setup



3.1.5 Test Result of Conducted Output Power

Cellular Band									
Modes	GSM850 (GPRS class 8)			GSM850 (EDGE class 8)			WCDMA Band V (RMC 12.2Kbps)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8	826.4	836.4	846.6
Conducted Power (dBm)	32.39	32.08	32.23	26.76	26.49	26.52	21.95	21.85	22.01
Conducted Power (Watts)	1.73	1.61	1.67	0.47	0.45	0.45	0.16	0.15	0.16

PCS Band									
Modes	GSM1900 (GPRS class 8)			GSM1900 (EDGE class 8)			WCDMA Band II (RMC 12.2Kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8	1852.4	1880	1907.6
Conducted Power (dBm)	29.32	29.40	29.45	25.27	25.38	25.44	22.15	22.22	21.98
Conducted Power (Watts)	0.86	0.87	0.88	0.34	0.35	0.35	0.16	0.17	0.16

Note: maximum burst average power for GSM, and maximum average power for WCDMA.

3.2 Peak-to-Average Ratio

3.2.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and System Simulator via power divider.
2. For GSM/EGPRS operating modes:
 - a. Set EUT in maximum power output.
 - b. Set the RBW = 1MHz, VBW = 3MHz, Peak detector in spectrum analyzer for first trace.
 - c. Set the RBW = 1MHz, VBW = 3MHz, RMS detector in spectrum analyzer for second trace.
 - d. The wanted burst signal is triggered by spectrum analyzer, and measured respectively the peak level and Mean level without burst-off time, after system simulator synchronized with the spectrum analyzer.
3. For UMTS operating modes:
 - a. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
 - b. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
4. Record the deviation as Peak to Average Ratio.

3.2.4 Test Setup





3.2.5 Test Result of Peak-to-Average Ratio


PCS Band									
Modes	GSM1900 (GPRS class 8)			GSM1900 (EDGE class 8)			WCDMA Band II (RMC 12.2Kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8	1852.4	1880	1907.6
Peak-to-Average Ratio (dB)	0.29	0.29	0.31	2.83	2.87	2.86	3.20	3.24	3.04



3.2.6 Test Result (Plots) of Peak-to-Average Ratio


Band :	GSM 1900	Test Mode :	GPRS class 8 Link (GMSK)
---------------	----------	--------------------	--------------------------

Peak-to-Average Ratio on Channel 512 (1850.2 MHz)



Date: 17 MAR. 2014 23:17:41


Peak-to-Average Ratio on Channel 661 (1880.0 MHz)



Date: 17 MAR. 2014 23:17:17



Peak-to-Average Ratio on Channel 810 (1909.8 MHz)




Date: 17 MAR. 2014 23:16:54




Band :	GSM 1900	Test Mode :	EDGE class 8 Link (8PSK)
---------------	----------	--------------------	--------------------------

Peak-to-Average Ratio on Channel 512 (1850.2 MHz)



Date: 17 MAR. 2014 23:14:24


Peak-to-Average Ratio on Channel 661 (1880.0 MHz)



Date: 17 MAR. 2014 23:14:51



Peak-to-Average Ratio on Channel 810 (1909.8 MHz)




Date: 17 MAR. 2014 23:15:21



Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)
---------------	---------------	--------------------	--------------------------

Peak-to-Average Ratio on Channel 9262 (1852.4 MHz)




Complementary Cumulative Distribution Function (100000 samples)

Trace 1

Mean	22.02 dBm
Peak	25.55 dBm
Crest	3.53 dB
10 %	1.80 dB
1 %	2.72 dB
.1 %	3.20 dB
.01 %	3.44 dB

Date: 27.MAR.2014 10:02:45

Peak-to-Average Ratio on Channel 9400 (1880.0 MHz)



Complementary Cumulative Distribution Function (100000 samples)


Trace 1

Mean	22.62 dBm
Peak	26.25 dBm
Crest	3.63 dB
10 %	1.80 dB
1 %	2.72 dB
.1 %	3.24 dB
.01 %	3.48 dB

Date: 27.MAR.2014 10:03:08



Peak-to-Average Ratio on Channel 9538 (1907.6 MHz)



Complementary Cumulative Distribution Function (100000 samples)

Trace 1

Mean 22.28 dBm
 Peak 25.55 dBm
 Crest 3.27 dB

10 % 1.80 dB
 1 % 2.64 dB
 .1 % 3.04 dB
 .01 % 3.20 dB

Date: 27.MAR.2014 10:03:32



3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

3.3.1 Description of the ERP/EIRP Measurement

The substitution method, in ANSI / TIA / EIA-603-C-2004, was used for ERP/EIRP measurement, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v02r01. The ERP of mobile transmitters must not exceed 7 Watts and the EIRP of mobile transmitters are limited to 2 Watts.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The EUT was placed on a turntable with 1.5 meter height in a fully anechoic chamber.
2. The EUT was set at 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. GSM operating modes: Set RBW= 1MHz, VBW= 3MHz, RMS detector over burst;
UMTS operating modes: Set RBW= 100 kHz, VBW= 300 kHz, RMS detector over frame, and use channel power option with bandwidth=5MHz, per KDB 971168 D01.
4. The table was rotated 360 degrees to determine the position of the highest radiated power.
5. The height of the receiving antenna is adjusted to look for the maximum ERP/EIRP.
6. Taking the record of maximum ERP/EIRP.
7. A dipole antenna was substituted in place of the EUT and was driven by a signal generator.
8. The conducted power at the terminal of the dipole antenna is measured.
9. Repeat step 3 to step 5 to get the maximum ERP/EIRP of the substitution antenna.
10. $ERP/EIRP = P_s + E_t - E_s + G_s = P_s + R_t - R_s + G_s$

P_s (dBm) : Input power to substitution antenna.

G_s (dBi or dBd) : Substitution antenna Gain.

$E_t = R_t + AF$


$E_s = R_s + AF$

AF (dB/m) : Receive antenna factor

R_t : The highest received signal in spectrum analyzer for EUT.

R_s : The highest received signal in spectrum analyzer for substitution antenna.

3.3.4 Test Setup



3.3.5 Test Result of ERP

GSM850 (GPRS class 8) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-21.55	-48.12	0.00	-1.08	25.49	0.35
836.40	-20.95	-48.28	0.00	-0.93	26.40	0.44
848.80	-21.04	-48.35	0.00	-0.76	26.55	0.45
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-19.03	-47.97	0.00	-1.08	27.86	0.61
836.40	-18.77	-48.01	0.00	-0.93	28.31	0.68
848.80	-18.86	-48.05	0.00	-0.76	28.43	0.70

GSM850 (EDGE class 8) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-26.42	-48.12	0.00	-1.08	20.62	0.12
836.40	-25.75	-48.28	0.00	-0.93	21.60	0.14
848.80	-25.69	-48.35	0.00	-0.76	21.90	0.15
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-24.19	-47.97	0.00	-1.08	22.70	0.19
836.40	-23.90	-48.01	0.00	-0.93	23.18	0.21
848.80	-23.58	-48.05	0.00	-0.76	23.71	0.23



WCDMA Band V (RMC 12.2Kbps) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
826.40	-29.85	-48.12	0.00	-1.08	17.19	0.05
836.40	-30.05	-48.28	0.00	-0.93	17.30	0.05
846.60	-29.89	-48.35	0.00	-0.76	17.70	0.06
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
826.40	-28.19	-47.97	0.00	-1.08	18.70	0.07
836.40	-28.53	-48.01	0.00	-0.93	18.55	0.07
846.60	-28.61	-48.05	0.00	-0.76	18.68	0.07

3.3.6 Test Result of EIRP

GSM1900 (GPRS class 8) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-25.39	-51.88	0.00	1.96	28.45	0.70
1880.00	-25.57	-52.99	0.00	2.00	29.42	0.88
1909.80	-26.33	-54.28	0.00	1.98	29.93	0.98
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-21.82	-52.13	0.00	1.96	32.27	1.69
1880.00	-23.02	-53.17	0.00	2.00	32.15	1.64
1909.80	-23.78	-54.13	0.00	1.98	32.33	1.71

GSM1900 (EDGE class 8) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-29.22	-51.88	0.00	1.96	24.62	0.29
1880.00	-29.91	-52.99	0.00	2.00	25.08	0.32
1909.80	-30.36	-54.28	0.00	1.98	25.90	0.39
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-25.80	-52.13	0.00	1.96	28.29	0.68
1880.00	-26.58	-53.17	0.00	2.00	28.59	0.72
1909.80	-27.52	-54.13	0.00	1.98	28.59	0.72



WCDMA Band II (RMC 12.2Kbps) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1852.40	-31.31	-51.88	0.00	1.96	22.53	0.18
1880.00	-31.60	-52.99	0.00	2.00	23.39	0.22
1907.60	-34.22	-54.28	0.00	1.98	22.04	0.16
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1852.40	-29.75	-52.13	0.00	1.96	24.35	0.27
1880.00	-30.21	-53.17	0.00	2.00	24.96	0.31
1907.60	-31.27	-54.13	0.00	1.98	24.84	0.30

3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.4.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The 99% occupied bandwidth were measured, set RBW= 1% of span, VBW= 3*RBW, sample detector, trace maximum hold.
4. The 26dB bandwidth were measured, set RBW= 1% of EBW, VBW= 3*RBW, peak detector, trace maximum hold.

3.4.4 Test Setup



3.4.5 Test Result of Occupied Bandwidth and 26dB Bandwidth

Cellular Band						
Modes	GSM850 (GPRS class 8)			GSM850 (EDGE class 8)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8
99% OBW (kHz)	246.00	248.00	244.00	242.00	244.00	248.00
26dB BW (kHz)	316.00	316.00	304.00	310.00	306.00	310.00

PCS Band						
Modes	GSM1900 (GPRS class 8)			GSM1900 (EDGE class 8)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8
99% OBW (kHz)	240.00	250.00	242.00	242.00	244.00	244.00
26dB BW (kHz)	316.00	312.00	316.00	304.00	308.00	304.00

Cellular Band			
Modes	WCDMA Band V (RMC 12.2Kbps)		
Channel	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	826.4	836.4	846.6
99% OBW (MHz)	4.14	4.20	4.20
26dB BW (MHz)	4.68	4.68	4.68


PCS Band			
Modes	WCDMA Band II (RMC 12.2Kbps)		
Channel	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1852.4	1880	1907.6
99% OBW (MHz)	4.16	4.18	4.16
26dB BW (MHz)	4.68	4.68	4.66



3.4.6 Test Result (Plots) of Occupied Bandwidth and 26dB Bandwidth


Band :	GSM 850	Test Mode :	GPRS class 8 Link (GMSK)
--------	---------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 17.MAR.2014 19:14:11


26dB Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 17.MAR.2014 19:12:52




99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 17.MAR.2014 19:14:37


26dB Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 17.MAR.2014 19:13:18




99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)



Date: 17.MAR.2014 19:23:02

26dB Bandwidth Plot on Channel 251 (848.8 MHz)




Date: 17.MAR.2014 19:13:44




Band :	GSM 850	Test Mode :	EDGE class 8 Link (8PSK)
--------	---------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 17.MAR.2014 19:00:49


26dB Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 17.MAR.2014 18:25:52




99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 17.MAR.2014 18:58:22


26dB Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 17.MAR.2014 18:26:18




99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)



Date: 17.MAR.2014 18:57:30

26dB Bandwidth Plot on Channel 251 (848.8 MHz)




Date: 17.MAR.2014 18:41:14




Band :	GSM 1900	Test Mode :	GPRS class 8 Link (GMSK)
--------	----------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 17.MAR.2014 20:22:30


26dB Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 17.MAR.2014 20:21:11




99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 17.MAR.2014 20:30:08


26dB Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 17.MAR.2014 20:21:37




99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)



Date: 17.MAR.2014 20:30:54

26dB Bandwidth Plot on Channel 810 (1909.8 MHz)




Date: 17.MAR.2014 20:22:03




Band :	GSM 1900	Test Mode :	EDGE class 8 Link (8PSK)
--------	----------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 17.MAR.2014 20:01:48


26dB Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 17.MAR.2014 19:57:31




99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 17.MAR.2014 20:02:32


26dB Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 17.MAR.2014 19:58:28




99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)



Date: 17.MAR.2014 20:03:44

26dB Bandwidth Plot on Channel 810 (1909.8 MHz)




Date: 17.MAR.2014 20:14:33




Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	--------------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 4132 (826.4 MHz)



Date: 17.MAR.2014 19:34:33


26dB Bandwidth Plot on Channel 4132 (826.4 MHz)



Date: 17.MAR.2014 19:33:14




99% Occupied Bandwidth Plot on Channel 4182 (836.4 MHz)



Date: 17.MAR.2014 19:34:59


26dB Bandwidth Plot on Channel 4182 (836.4 MHz)



Date: 17.MAR.2014 19:33:40




99% Occupied Bandwidth Plot on Channel 4233 (846.6 MHz)



Date: 17.MAR.2014 19:35:25

26dB Bandwidth Plot on Channel 4233 (846.6 MHz)




Date: 17.MAR.2014 19:34:07




Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	---------------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 9262 (1852.4 MHz)



Date: 27.MAR.2014 09:37:42


26dB Bandwidth Plot on Channel 9262 (1852.4 MHz)



Date: 27.MAR.2014 09:36:24




99% Occupied Bandwidth Plot on Channel 9400 (1880.0 MHz)



Date: 27.MAR.2014 09:38:08


26dB Bandwidth Plot on Channel 9400 (1880.0 MHz)



Date: 27.MAR.2014 09:36:50




99% Occupied Bandwidth Plot on Channel 9538 (1907.6 MHz)



Date: 27.MAR.2014 09:38:34

26dB Bandwidth Plot on Channel 9538 (1907.6 MHz)



Date: 27.MAR.2014 09:37:16

3.5 Band Edge Measurement

3.5.1 Description of Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.


3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The band edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly $BW/100$.
4. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
5. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)]$ (dB)
 $= [30 + 10\log(P)]$ (dBm) - $[43 + 10\log(P)]$ (dB)
 $= -13\text{dBm}$.


3.5.4 Test Setup



3.5.5 Test Result (Plots) of Conducted Band Edge

Band :	GSM850	Test Mode :	GPRS class 8 Link (GMSK)
Correction Factor :	0.23dB	Maximum 26dB Bandwidth :	0.316MHz
Band Edge :	-20.67dBm	Measurement Value :	-20.90dBm

Lower Band Edge Plot on Channel 128 (824.2 MHz)




Date: 17.MAR.2014 19:16:30

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
 2. Band Edge= Measurement Value + Correction Factor(dB)
- For example, $-20.90\text{dBm} + 0.23\text{dB} = -20.67\text{dBm}$



Band :	GSM850	Test Mode :	GPRS class 8 Link (GMSK)
Correction Factor :	0.23dB	Maximum 26dB Bandwidth :	0.316MHz
Band Edge :	-21.13dBm	Measurement Value :	-21.36dBm

Higher Band Edge Plot on Channel 251 (848.8 MHz)




Date: 17.MAR.2014 19:16:56

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	GSM850	Test Mode :	EDGE class 8 Link (8PSK)
Correction Factor :	0.14dB	Maximum 26dB Bandwidth :	0.310MHz
Band Edge :	-23.60dBm	Measurement Value :	-23.74dBm

Lower Band Edge Plot on Channel 128 (824.2 MHz)




Date: 17.MAR.2014 18:29:30

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	GSM850	Test Mode :	EDGE class 8 Link (8PSK)
Correction Factor :	0.14dB	Maximum 26dB Bandwidth :	0.310MHz
Band Edge :	-24.83dBm	Measurement Value :	-24.97dBm

Higher Band Edge Plot on Channel 251 (848.8 MHz)




Date: 17.MAR.2014 18:29:56

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	GSM1900	Test Mode :	GPRS class 8 Link (GMSK)
Correction Factor :	0.23dB	Maximum 26dB Bandwidth :	0.316MHz
Band Edge :	-23.17dBm	Measurement Value :	-23.40dBm

Lower Band Edge Plot on Channel 512 (1850.2 MHz)




Date: 17.MAR.2014 20:24:48

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	GSM1900	Test Mode :	GPRS class 8 Link (GMSK)
Correction Factor :	0.23dB	Maximum 26dB Bandwidth :	0.316MHz
Band Edge :	-25.10dBm	Measurement Value :	-25.33dBm

Higher Band Edge Plot on Channel 810 (1909.8 MHz)




Date: 17.MAR.2014 20:25:15

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	GSM1900	Test Mode :	EDGE class 8 Link (8PSK)
Correction Factor :	0.11dB	Maximum 26dB Bandwidth :	0.308MHz
Band Edge :	-24.97dBm	Measurement Value :	-25.08dBm

Lower Band Edge Plot on Channel 512 (1850.2 MHz)




Date: 17.MAR.2014 19:52:17

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	GSM1900	Test Mode :	EDGE class 8 Link (8PSK)
Correction Factor :	0.11dB	Maximum 26dB Bandwidth :	0.308MHz
Band Edge :	-24.29dBm	Measurement Value :	-24.40dBm

Higher Band Edge Plot on Channel 810 (1909.8 MHz)




Date: 17.MAR.2014 19:52:43

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link (QPSK)
Correction Factor :	-3.30dB	Maximum 26dB Bandwidth :	4.680MHz
Band Edge :	-30.91dBm	Measurement Value :	-27.61dBm

Lower Band Edge Plot on Channel 4132 (826.4 MHz)




Date: 17.MAR.2014 19:36:54

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link (QPSK)
Correction Factor :	-3.30dB	Maximum 26dB Bandwidth :	4.680MHz
Band Edge :	-29.74dBm	Measurement Value :	-26.44dBm

Higher Band Edge Plot on Channel 4233 (846.6 MHz)



Date: 17.MAR.2014 19:37:20

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)
Correction Factor :	-3.30dB	Maximum 26dB Bandwidth :	4.680MHz
Band Edge :	-32.22dBm	Measurement Value :	-28.92dBm

Lower Band Edge Plot on Channel 9262 (1852.4 MHz)




Date: 27.MAR.2014 09:40:02

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)
Correction Factor :	-3.30dB	Maximum 26dB Bandwidth :	4.680MHz
Band Edge :	-32.11dBm	Measurement Value :	-28.81dBm

Higher Band Edge Plot on Channel 9538 (1907.6 MHz)



Date: 27.MAR.2014 09:40:28

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
2. Band Edge= Measurement Value + Correction Factor(dB)

3.6 Conducted Spurious Emission Measurement

3.6.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures


1. The EUT was connected to spectrum analyzer and base station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The middle channel for the highest RF power within the transmitting frequency was measured.
4. The conducted spurious emission for the whole frequency range was taken.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

$$= P(W) - [43 + 10\log(P)] \text{ (dB)}$$

$$= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$$

$$= -13\text{dBm}$$

3.6.4 Test Setup






3.6.5 Test Result (Plots) of Conducted Spurious Emission


Band :	GSM850	Channel :	CH189
Test Mode :	GPRS class 8 Link (GMSK)	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 17.MAR.2014 19:25:45


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 17.MAR.2014 19:26:33




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 17.MAR.2014 19:26:58

Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 17.MAR.2014 19:27:22




Band :	GSM850	Channel :	CH189
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 17.MAR.2014 19:05:48


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 17.MAR.2014 19:06:46




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 17.MAR.2014 19:07:14

Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 17.MAR.2014 19:07:39




Band :	GSM1900	Channel :	CH661
Test Mode :	GPRS class 8 Link (GMSK)	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 17.MAR.2014 20:33:10


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 17.MAR.2014 20:33:57




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 17.MAR.2014 20:34:23


Conducted Emission Plot between 7GHz ~ 13.6GHz



Date: 17.MAR.2014 20:34:49



Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz




Date: 17.MAR.2014 20:35:20




Band :	GSM1900	Channel :	CH661
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 17.MAR.2014 20:16:21


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 17.MAR.2014 20:16:54




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 17.MAR.2014 20:17:26


Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 17.MAR.2014 20:17:57



Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz




Date: 17.MAR.2014 20:18:23




Band :	WCDMA Band V	Channel :	CH4182
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 17.MAR.2014 19:42:40


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 17.MAR.2014 19:43:24




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 17.MAR.2014 19:43:53

Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 17.MAR.2014 19:44:16




Band :	WCDMA Band II	Channel :	CH9400
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 27.MAR.2014 09:55:54


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 27.MAR.2014 09:56:53




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 27.MAR.2014 09:57:46


Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 27.MAR.2014 09:58:28



Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz



Date: 27.MAR.2014 09:59:48

3.7 Field Strength of Spurious Radiation Measurement

3.7.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log(P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

3.7.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.7.3 Test Procedures


1. The EUT was placed on a rotatable wooden table with 0.8 meter above ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
11. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
= $P(W) - [43 + 10\log(P)]$ (dB)
= $[30 + 10\log(P)]$ (dBm) - $[43 + 10\log(P)]$ (dB)
= -13dBm.
12. EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain
13. ERP (dBm) = EIRP - 2.15

3.7.4 Test Setup

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz





3.7.5 Test Result of Field Strength of Spurious Radiated

Band :	GSM850	Temperature :	22~23°C
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition : FCC PART22 24 HF_EIRP_FACTOR130726 HORIZONTAL

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-75.04	-13	-62.04	-66.16	-75.69	0.57	3.37	H	Pass
2508	-68.06	-13	-55.06	-66.73	-70.29	0.78	5.16	H	Pass
3344	-66.47	-13	-53.47	-66.10	-70.11	0.87	6.66	H	Pass



Band :	GSM850	Temperature :	22~23°C
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition : FCC PART22 24 HF_EIRP_FACTOR130726 VERTICAL

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-70.15	-13	-57.15	-66.35	-70.80	0.57	3.37	V	Pass
2508	-64.13	-13	-51.13	-66.56	-66.36	0.78	5.16	V	Pass
3344	-64.72	-13	-51.72	-65.78	-68.36	0.87	6.66	V	Pass



Band :	GSM850	Temperature :	22~23°C
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition : FCC PART22 24 ... HF_EIRP_FACTOR130726 HORIZONTAL

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-72.68	-13	-59.68	-63.80	-73.33	0.57	3.37	H	Pass
2510	-62.95	-13	-49.95	-61.62	-65.18	0.78	5.16	H	Pass
3344	-65.85	-13	-52.85	-65.48	-69.49	0.87	6.66	H	Pass



Band :	GSM850	Temperature :	22~23°C
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition : FCC PART22 24 HF_EIRP_FACTOR130726 VERTICAL

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-70.34	-13	-57.34	-66.54	-70.99	0.57	3.37	V	Pass
2510	-61.55	-13	-48.55	-63.98	-63.78	0.78	5.16	V	Pass
3344	-65.30	-13	-52.30	-66.36	-68.94	0.87	6.66	V	Pass



Band :	GSM1900	Temperature :	22~23°C
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition : FCC PART22 24 HF_EIRP_FACTOR130726 HORIZONTAL

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-62.32	-13	-49.32	-65.67	-68.70	0.78	7.16	H	Pass
5640	-57.13	-13	-44.13	-67.19	-65.67	1.04	9.58	H	Pass
7520	-55.38	-13	-42.38	-66.92	-65.49	1.35	11.46	H	Pass



Band :	GSM1900	Temperature :	22~23°C
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition : FCC PART22 24 HF_EIRP_FACTOR130726 VERTICAL

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-57.15	-13	-44.15	-65.55	-63.53	0.78	7.16	V	Pass
5640	-54.12	-13	-41.12	-66.77	-62.66	1.04	9.58	V	Pass
7520	-50.77	-13	-37.77	-64.86	-60.88	1.35	11.46	V	Pass



Band :	GSM1900	Temperature :	22~23°C
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition : FCC PART22 24 HF_EIRP_FACTOR130726 HORIZONTAL

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-62.20	-13	-49.20	-65.55	-68.58	0.78	7.16	H	Pass
5640	-57.39	-13	-44.39	-67.45	-65.93	1.04	9.58	H	Pass
7520	-53.55	-13	-40.55	-65.09	-63.66	1.35	11.46	H	Pass



Band :	GSM1900	Temperature :	22~23°C
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition : FCC PART22 24 HF_EIRP_FACTOR130726 VERTICAL

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-57.36	-13	-44.36	-65.76	-63.74	0.78	7.16	V	Pass
5640	-54.09	-13	-41.09	-66.74	-62.63	1.04	9.58	V	Pass
7520	-52.21	-13	-39.21	-66.3	-62.32	1.35	11.46	V	Pass



Band :	WCDMA Band V	Temperature :	22~23°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition : FCC PART22 24 HF_EIRP_FACTOR130726 HORIZONTAL

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1674	-72.28	-13	-59.28	-63.40	-72.93	0.57	3.37	H	Pass
2508	-68.16	-13	-55.16	-66.83	-70.39	0.78	5.16	H	Pass
3344	-65.92	-13	-52.92	-65.55	-69.56	0.87	6.66	H	Pass



Band :	WCDMA Band V	Temperature :	22~23°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition : FCC PART22 24 HF_EIRP_FACTOR130726 VERTICAL

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-70.63	-13	-57.63	-66.83	-71.28	0.57	3.37	V	Pass
2508	-64.62	-13	-51.62	-67.05	-66.85	0.78	5.16	V	Pass
3344	-65.06	-13	-52.06	-66.12	-68.70	0.87	6.66	V	Pass



Band :	WCDMA Band II	Temperature :	22~23°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition : FCC PART22 24 HF_EIRP_FACTOR130726 HORIZONTAL

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-61.42	-13	-48.42	-64.77	-67.80	0.78	7.16	H	Pass
5638	-49.55	-13	-36.55	-60.95	-58.09	1.04	9.58	H	Pass
7520	-54.28	-13	-41.28	-65.82	-64.39	1.35	11.46	H	Pass



Band :	WCDMA Band II	Temperature :	22~23°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS
 Condition : FCC PART22 24 HF_EIRP_FACTOR130726 VERTICAL

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-56.26	-13	-43.26	-64.66	-62.64	0.78	7.16	V	Pass
5640	-54.20	-13	-41.20	-66.85	-62.74	1.04	9.58	V	Pass
7520	-51.21	-13	-38.21	-65.3	-61.32	1.35	11.46	V	Pass

3.8 Frequency Stability Measurement

3.8.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.8.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.8.3 Test Procedures for Temperature Variation

1. The EUT was set up in the thermal chamber and connected with the base station.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.8.4 Test Procedures for Voltage Variation

1. The EUT was placed in a temperature chamber at $25\pm 5^{\circ}\text{C}$ and connected with the base station.
2. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

3.8.5 Test Setup



3.8.6 Test Result of Temperature Variation

Band :	GSM 850	Channel :	189
Limit (ppm) :	2.5	Frequency :	836.4 MHz

Temperature (°C)	GPRS class 8		EDGE class 8		Result
	Freq. Dev. (Hz)	Deviation (ppm)	Freq. Dev. (Hz)	Deviation (ppm)	
-30	-32	-0.04	-35	-0.04	PASS
-20	-28	-0.03	-32	-0.04	
-10	-24	-0.03	19	+0.02	
0	21	+0.02	21	+0.02	
10	16	+0.02	27	+0.03	
20	15	+0.02	25	+0.03	
30	-17	-0.02	16	+0.02	
40	-19	-0.02	18	+0.02	
50	20	+0.02	-19	-0.02	

Band :	GSM 1900	Channel :	661
Limit (ppm) :	2.5	Frequency :	1880.0 MHz

Temperature (°C)	GPRS class 8		EDGE class 8		Result
	Freq. Dev. (Hz)	Deviation (ppm)	Freq. Dev. (Hz)	Deviation (ppm)	
-30	-29	-0.02	-26	-0.01	PASS
-20	-31	-0.02	-33	-0.02	
-10	24	+0.01	25	+0.01	
0	18	+0.01	12	+0.01	
10	16	+0.01	17	+0.01	
20	12	+0.01	13	+0.01	
30	15	+0.01	17	+0.01	
40	-17	-0.01	-13	-0.01	
50	-24	-0.01	22	+0.01	



Band :	WCDMA Band V	Channel :	4182
Limit (ppm) :	2.5	Frequency :	836.4 MHz

Temperature (°C)	RMC 12.2Kbps		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	-35	-0.04	PASS
-20	-32	-0.04	
-10	-18	-0.02	
0	16	+0.02	
10	21	+0.02	
20	27	+0.03	
30	25	+0.03	
40	18	+0.02	
50	-21	-0.02	

Band :	WCDMA Band II	Channel :	9400
Limit (ppm) :	2.5	Frequency :	1880.0 MHz

Temperature (°C)	RMC 12.2Kbps		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	-29	-0.02	PASS
-20	-31	-0.02	
-10	25	+0.01	
0	-13	-0.01	
10	17	+0.01	
20	13	+0.01	
30	17	+0.01	
40	-17	-0.01	
50	-24	-0.01	



3.8.7 Test Result of Voltage Variation

Band & Channel	Mode	Voltage (Volt)	Freq. Dev. (Hz)	Deviation (ppm)	Limit (ppm)	Result
GSM 850 CH189	GPRS class 8	5.0	-32	-0.04	2.5	PASS
		4.75	-19	-0.02		
		5.25	21	+0.02		
	EDGE class 8	5.0	21	+0.02		
		4.75	-19	-0.02		
		5.25	17	+0.02		
GSM 1900 CH661	GPRS class 8	5.0	18	+0.01		
		4.75	16	+0.01		
		5.25	-21	-0.01		
	EDGE class 8	5.0	11	+0.01		
		4.75	-13	-0.01		
		5.25	-27	-0.01		
WCDMA Band V CH4182	RMC 12.2Kbps	5.0	-35	-0.04		
		4.75	-21	-0.02		
		5.25	-19	-0.02		
WCDMA Band II CH9400	RMC 12.2Kbps	5.0	11	+0.01		
		4.75	-16	-0.01		
		5.25	-23	-0.01		

Note: Normal Voltage = 5.0V.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Dec. 29, 2013	Mar. 17, 2014~ Mar. 27, 2014	Dec. 28, 2014	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	N/A	Feb. 27, 2014	Mar. 17, 2014~ Mar. 27, 2014	Feb. 26, 2015	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	N/A	Feb. 27, 2014	Mar. 17, 2014~ Mar. 27, 2014	Feb. 26, 2015	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-960502	N/A	Dec. 29, 2013	Mar. 17, 2014~ Mar. 27, 2014	Dec. 28, 2014	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESCI	100534	9kHz~3GHz	Nov. 07, 2013	Mar. 17, 2014	Nov. 06, 2014	Radiation (03CH01-KS)
Spectrum Analyzer	R&S	FSP30	101399	9kHz~30GHz	May 23, 2013	Mar. 17, 2014	May 22, 2014	Radiation (03CH01-KS)
Bilog Antenna	SCHAFFNER	CBL6112D	23182	25MHz~2GHz	Dec. 07, 2013	Mar. 17, 2014	Dec. 06, 2014	Radiation (03CH01-KS)
Double Ridge Horn Antenna	EMCO	3117	75959	1GHz~18GHz	Dec. 07, 2013	Mar. 17, 2014	Dec. 06, 2014	Radiation (03CH01-KS)
Amplifier	com-power	PA-103A	161069	1MHz~1GHz	May 23, 2013	Mar. 17, 2014	May 22, 2014	Radiation (03CH01-KS)
Amplifier	Agilent	8449B	3008A02370	1GHz~26.5GHz	Dec. 29, 2013	Mar. 17, 2014	Dec. 28, 2014	Radiation (03CH01-KS)
Active Horn Antenna	com-power	AHA-118	701023	1GHz~18GHz	Nov. 18, 2013	Mar. 17, 2014	Nov. 17, 2014	Radiation (03CH01-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA170249	15GHz~40GHz	Nov. 23, 2013	Mar. 17, 2014	Nov. 22, 2014	Radiation (03CH01-KS)
Turn Table	MF	MF7802	N/A	0 ~ 360 degree	N/A	Mar. 17, 2014	N/A	Radiation (03CH01-KS)
Antenna Mast	MF	MF7802	N/A	1 m - 4 m	N/A	Mar. 17, 2014	N/A	Radiation (03CH01-KS)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP 7	100819	9kHz~7GHz	May 23, 2013	Mar. 17, 2014	May 22, 2014	ERP/EIRP (OTA01-KS)
Switch Control Manframe	Agilent	3499A	MY420054 52	N/A	N/A	Mar. 17, 2014	N/A	ERP/EIRP (OTA01-KS)
Dual 1-to-6(4) MW MUX	Agilent	N2276A	MY420008 41	N/A	N/A	Mar. 17, 2014	N/A	ERP/EIRP (OTA01-KS)
Microwave Switch	Agilent	44476A	MY420025 73	N/A	N/A	Mar. 17, 2014	N/A	ERP/EIRP (OTA01-KS)
Microwave Switch	Agilent	44476A	MY420025 86	N/A	N/A	Mar. 17, 2014	N/A	ERP/EIRP (OTA01-KS)
Diagonal Dual Polarized Horn	ETS-Lindgren	3164-04	00066993	700MHz~6GHz	N/A	Mar. 17, 2014	N/A	ERP/EIRP (OTA01-KS)
Multi-Devices Controller	ETS-Lindgren	2090-OPT1	00066604	N/A	N/A	Mar. 17, 2014	N/A	ERP/EIRP (OTA01-KS)
Conical Log Spiral (Small)	ETS-Lindgren	3102	00066951	1~10GHz	N/A	Mar. 17, 2014	N/A	ERP/EIRP (OTA01-KS)
Turn Table	ETS-Lindgren	2088	N/A	Resolution : 0.1degree	N/A	Mar. 17, 2014	N/A	ERP/EIRP (OTA01-KS)
Limiting Amplifier	ETS-lindgren	109643	920326	10M~2.5GHz	N/A	Mar. 17, 2014	N/A	ERP/EIRP (OTA01-KS)
EMQuest	ETS-Lindgren	EMQ-100	1125	N/A	N/A	Mar. 17, 2014	N/A	ERP/EIRP (OTA01-KS)
Medium Duty Holder	ETS-Lindgren	2015	N/A	N/A	N/A	Mar. 17, 2014	N/A	ERP/EIRP (OTA01-KS)



5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.54
---	------