

FCC RF Test Report

APPLICANT : ZTE CORPORATION
EQUIPMENT : LTE Ufi
BRAND NAME : ZTE
MODEL NAME : MF970
FCC ID : SRQ-MF970
STANDARD : FCC Part 15 Subpart E §15.407
CLASSIFICATION : (NII) Unlicensed National Information Infrastructure

The product was received on Jun. 29, 2015 and testing was completed on Jul. 09, 2015. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.



Reviewed by: Joseph Lin / Supervisor



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant.....	5
1.2 Manufacturer.....	5
1.3 Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	6
1.5 Modification of EUT	7
1.6 Testing Location	7
1.7 Applicable Standards.....	7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	8
2.1 Carrier Frequency and Channel	8
2.2 Pre-Scanned RF Power.....	9
2.3 Test Mode.....	12
2.4 Connection Diagram of Test System.....	13
2.5 Support Unit used in test configuration and system	14
2.6 EUT Operation Test Setup	14
2.7 Measurement Results Explanation Example.....	15
3 TEST RESULT.....	16
3.1 6dB Bandwidth Measurement	16
3.2 Maximum Conducted Output Power Measurement	18
3.3 Power Spectral Density Measurement	19
3.4 Unwanted Emissions Measurement.....	22
3.5 AC Conducted Emission Measurement.....	27
3.6 Frequency Stability Measurement.....	31
3.7 Automatically Discontinue Transmission	32
3.8 Antenna Requirements.....	33
4 LIST OF MEASURING EQUIPMENT	34
5 UNCERTAINTY OF EVALUATION	35
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. RADIATED TEST RESULTS	
APPENDIX C. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR562904C	Rev. 01	Initial issue of report	Aug. 12, 2015

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.403(i)	6dB Bandwidth	> 500kHz	Pass	-
3.2	15.407(a)	Maximum Conducted Output Power	≤ 30 dBm	Pass	-
3.3	15.407(a)	Power Spectral Density	≤ 30 dBm/500kHz	Pass	-
3.4	15.407(b)	Unwanted Emissions	$\leq -17, -27$ dBm/MHz & 15.209(a)	Pass	Under limit 4.88 dB at 38.730 MHz
3.5	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 11.97 dB at 0.440 MHz
3.6	15.407(g)	Frequency Stability	Within Operation Band	Pass	-
3.7	15.407(c)	Automatically Discontinue Transmission	Discontinue Transmission	Pass	-
3.8	15.203 & 15.407(a)	Antenna Requirement	N/A	Pass	-



1 General Description

1.1 Applicant

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057,
P.R.China

1.2 Manufacturer

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057,
P.R.China

1.3 Feature of Equipment Under Test

Product Feature & Specification	
Equipment	LTE Ufi
Brand Name	ZTE
Model Name	MF970
FCC ID	SRQ-MF970
EUT supports Radios application	WCDMA/HSPA/HSPA+(Downlink Only)/DC-HSDPA/LTE WLAN2.4GHz 802.11b/g/n HT20/HT40 WLAN5GHz 802.11a/n HT20/HT40/ WLAN5GHz 802.11ac VHT20/VHT40/VHT80
IMEI Code	Conducted sample: 866603020001578 Radiation sample: 867610020000001 Conduction sample: 004401783353580
HW Version	xz2A
SW Version	MF970V1.0.2
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Product Specification subjective to this standard			
Tx/Rx Channel Frequency Range	5725 MHz ~ 5850 MHz		
Maximum Output Power	802.11a : 8.27 dBm / 0.0067 W 802.11n HT20 : 7.22 dBm / 0.0053 W 802.11n HT40 : 7.12 dBm / 0.0052 W 802.11ac VHT20: 6.49 dBm / 0.0045 W 802.11ac VHT40: 5.47 dBm / 0.0035 W 802.11ac VHT80: 5.28 dBm / 0.0034 W		
Antenna Type / Gain	Chain Port 1 : IFA Antenna with gain 2.50 dBi Chain Port 2 : IFA Antenna with gain 2.50 dBi		
Type of Modulation	802.11a/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) 802.11ac : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)		
Antenna Function Description		Chain Port 0	Chain Port 1
	802.11a	V	V
	802.11n/ac SISO	V	V
	802.11n/ac MIMO	V	V

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.			
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958			
Test Site No.	Sporton Site No.			FCC Registration No.
	TH01-KS	03CH02-KS	CO01-KS	418269

Note: The test site complies with ANSI C63.4 2009 requirement.

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart E
- ♦ FCC KDB 789033 D02 General UNII Test Procedures New Rules v01
- ♦ FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. FCC permits the use of the 1.5 meter table as an alternative in C63.10-2013 through inquiry tracking number 961829.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz) and radiated emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases were recorded in this report.

The final configuration from all the combinations and the worst-case data rates were investigated by measuring the maximum power across all the data rates and modulation modes under section 2.2.

Based on the worst configuration found above, the RF power setting is set individually to meet FCC compliance limit for the final conducted and radiated tests shown in section 2.3.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5725-5850 MHz Band 4 (U-NII-3)	149	5745	157	5785
	151	5755	159	5795
	153	5765	161	5805
	155	5775	165	5825

Note: The above Frequency and Channel in boldface were 802.11n HT40.



2.2 Pre-Scanned RF Power

Preliminary tests were performed in different data rate and data rate associated with the highest power were chosen for full test in the following tables. Final Output Power equals to Measured Output Power adds the duty factor.

WLAN 5GHz 802.11a Average Power (dBm)											
Power vs. Channel				Power vs. Data Rate							
Channel	Frequency (MHz)	Chain Port	Data Rate 6Mbps	Channel	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps
CH 149	5745	0	7.67	CH 165	8.25	8.21	8.20	8.15	8.12	8.24	8.19
CH 157	5785	0	8.04								
CH 165	5825	0	8.27								
CH 149	5745	1	8.05	CH 157	8.13	8.10	8.20	8.11	8.09	8.15	8.08
CH 157	5785	1	8.25								
CH 165	5825	1	8.09								

WLAN 5GHz 802.11n-HT20 Output Power (dBm)											
Power vs. Channel				Power vs. Data Rate							
Channel	Frequency (MHz)	Chain Port	MCS Index MCS0	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
CH 149	5745	0	6.82	CH 165	7.16	7.19	7.18	7.16	7.19	7.17	7.18
CH 157	5785	0	7.14								
CH 165	5825	0	7.20								
CH 149	5745	1	7.04	CH 157	6.93	7.04	7.10	7.08	7.05	7.11	7.06
CH 157	5785	1	7.12								
CH 165	5825	1	7.02								
CH 149	5745	0+1(0)	2.08	CH 165	2.60	2.51	2.74	2.77	2.75	2.76	2.73
CH 157	5785	0+1(0)	2.40								
CH 165	5825	0+1(0)	3.68								
CH 149	5745	0+1(1)	4.38	CH 165	4.38	4.40	4.45	4.61	4.56	4.47	4.48
CH 157	5785	0+1(1)	4.48								
CH 165	5825	0+1(1)	4.69								
CH 149	5745	0+1	6.39	CH 165	6.59	6.56	6.69	6.80	6.76	6.71	6.71
CH 157	5785	0+1	6.57								
CH 165	5825	0+1	7.22								



WLAN 5GHz 802.11n-HT40 Output Power (dBm)											
Power vs. Channel				Power vs. Data Rate							
Channel	Frequency (MHz)	Chain Port	MCS Index MCS0	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
CH 151	5755	0	6.81	CH 151	6.76	6.72	6.68	6.80	6.67	6.66	6.65
CH 159	5795	0	6.75								
CH 151	5755	1	7.07	CH 151	7.06	7.01	6.89	6.87	6.90	6.93	6.81
CH 159	5795	1	6.84								
CH 151	5755	0+1(0)	2.86	CH 151	2.85	2.82	2.73	2.79	2.74	2.78	2.67
CH 159	5795	0+1(0)	2.80								
CH 151	5755	0+1(1)	5.08	CH 151	5.04	5.05	4.95	4.97	5.06	4.91	5.02
CH 159	5795	0+1(1)	4.75								
CH 151	5755	0+1	7.12	CH 151	7.09	7.09	6.99	7.03	7.06	6.99	7.01
CH 159	5795	0+1	6.89								

WLAN 5GHz 802.11ac VHT20 Output Power (dBm)												
Power vs. Channel				Power vs. Data Rate								
Channel	Frequency (MHz)	Chain Port	MCS Index MCS0	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8
CH 149	5745	0	5.54	CH 165	5.93	5.94	6.06	5.97	6.05	6.01	6.00	5.99
CH 157	5785	0	5.87									
CH 165	5825	0	6.07									
CH 149	5745	1	5.93	CH 157	5.97	6.08	6.07	6.16	6.14	6.12	1.10	6.15
CH 157	5785	1	6.18									
CH 165	5825	1	5.98									
CH 149	5745	0+1(0)	1.81	CH 165	2.09	2.31	2.34	2.42	2.53	2.24	2.43	2.31
CH 157	5785	0+1(0)	2.14									
CH 165	5825	0+1(0)	2.55									
CH 149	5745	0+1(1)	3.93	CH 165	3.94	4.01	4.15	4.15	4.18	4.19	4.08	4.20
CH 157	5785	0+1(1)	4.12									
CH 165	5825	0+1(1)	4.25									
CH 149	5745	0+1	6.01	CH 165	6.12	6.26	6.35	6.38	6.44	6.33	6.34	6.37
CH 157	5785	0+1	6.25									
CH 165	5825	0+1	6.49									



WLAN 5GHz 802.11ac VHT40 Output Power (dBm)													
Power vs. Channel				Power vs. Data Rate									
Channel	Frequency (MHz)	Chain Port	MCS Index MCS0	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9
CH 151	5755	0	5.33	CH 151	5.26	5.13	5.09	5.19	5.31	5.15	5.19	5.14	5.21
CH 159	5795	0	5.20	CH 151	5.33	5.34	5.31	5.42	5.37	5.35	5.29	5.45	5.39
CH 151	5755	1	5.46	CH 151	5.33	5.34	5.31	5.42	5.37	5.35	5.29	5.45	5.39
CH 159	5795	1	5.21	CH 151	5.33	5.34	5.31	5.42	5.37	5.35	5.29	5.45	5.39
CH 151	5755	0+1(0)	1.07	CH 159	1.11	1.27	1.26	1.12	1.26	1.13	1.30	1.28	1.22
CH 159	5795	0+1(0)	1.31	CH 159	1.11	1.27	1.26	1.12	1.26	1.13	1.30	1.28	1.22
CH 151	5755	0+1(1)	3.34	CH 159	3.31	3.25	3.18	3.27	3.36	3.26	3.24	3.32	3.31
CH 159	5795	0+1(1)	3.37	CH 159	3.31	3.25	3.18	3.27	3.36	3.26	3.24	3.32	3.31
CH 151	5755	0+1	5.36	CH 159	5.35	5.39	5.33	5.34	5.44	5.34	5.39	5.43	5.40
CH 159	5795	0+1	5.47	CH 159	5.35	5.39	5.33	5.34	5.44	5.34	5.39	5.43	5.40

WLAN 5GHz 802.11n-HT80 Output Power (dBm)													
Power vs. Channel				Power vs. Data Rate									
Channel	Frequency (MHz)	Chain Port	MCS Index MCS0	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9
CH 155	5775	0	4.74	CH 155	4.58	4.56	4.51	4.54	4.65	4.70	4.71	4.58	4.60
CH 155	5775	1	4.98	CH 155	4.94	4.90	4.81	4.74	4.88	4.92	4.70	4.86	4.87
CH 155	5775	0+1(0)	1.09	CH 155	0.77	1.01	0.87	0.84	0.72	0.86	0.90	0.89	1.03
CH 155	5775	0+1(1)	3.20	CH 155	3.05	3.12	3.18	3.10	3.11	3.03	3.16	3.15	3.17
CH 155	5775	0+1	5.28	CH 155	5.07	5.20	5.19	5.12	5.08	5.09	5.19	5.17	5.24

Note: Chain Port 1+2 is a calculated result from sum of the power Chain Port 1+2(1) and Chain Port 1+2(2).

2.3 Test Mode

Final test mode of conducted test items and radiated spurious emissions are considering the modulation and worse data rates from the power table described in section 2.2.

Modulation	Data Rate
802.11a	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0
802.11ac VHT20	MCS0
802.11ac VHT40	MCS0
802.11ac VHT80	MCS0


AC Conducted Emission	Mode 1 : GSM850 Idle + WLAN (5GHz) Link + USB Cable (Charging from Adapter)
Remark: For Radiated TCs, the tests were performed with adapter and USB cable.	

Ch. #		Band IV : 5725-5850 MHz		
		802.11a	802.11n HT20	802.11n HT40
L	Low	149	149	151
M	Middle	157	157	-
H	High	165	165	159


Ch. #		Band IV : 5725-5850 MHz		
		802.11ac VHT20	802.11ac VHT40	802.11ac VHT80
L	Low	149	151	-
M	Middle	157	-	155
H	High	165	159	-

2.4 Connection Diagram of Test System

<WLAN Tx Mode>



<AC Conducted Emission Mode>



2.5 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	Notebook	Lenovo	G480	PRC4	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
3.	DC Power Supply	GW INSTEK	GPD-2303S	N/A	N/A	Unshielded, 1.8 m

2.6 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuously transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the Notebook under large package sizes transmission.



2.7 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss.

Following shows an offset computation example with cable loss 7.5 dB.

$$\begin{aligned}\text{Offset (dB)} &= \text{RF cable loss(dB)} \\ &= 7.5 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB Bandwidth Measurement

3.1.1 Description of 6dB Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01.
Section C) Emission bandwidth for the band 5.725-5.85GHz
2. Set RBW = 100kHz.
3. Set the VBW $\geq 3 \times$ RBW.
4. Detector = Peak.
5. Trace mode = max hold
6. Measure the maximum width of the emission that is 6 dB down from the peak of the emission.
7. Measure and record the results in the test report.


3.1.4 Test Setup





3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Maximum Conducted Output Power Measurement

3.2.1 Limit of Maximum Conducted Output Power

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.2.3 Test Procedures

The testing follows Method PM of FCC KDB 789033 D02 General UNII Test Procedures New Rules v01.

Method PM (Measurement using an RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit continuously with a consistent duty cycle at its maximum power control level.
3. Measure the average power of the transmitter, and the average power is corrected with duty factor, $10 \log(1/x)$, where x is the duty cycle.

3.2.4 Test Setup



3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.



3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

For the band 5.725–5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01.
Section F) Maximum power spectral density.

Method SA-2

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).


1. The testing follows Method SA-2 of FCC KDB 789033 D01 General UNII Test Procedures v01r03.
 - Measure the duty cycle.
 - Set span to encompass the entire emission bandwidth (EBW) of the signal.
 - Set RBW = 300 kHz.
 - Set VBW $\geq$ 1 MHz.
 - Number of points in sweep $\geq$ 2 Span / RBW.
 - Sweep time = auto.
 - Detector = RMS
 - Trace average at least 100 traces in power averaging mode.
 - Add $10 \log(500\text{kHz}/\text{RBW})$ to the test result.
 - Add $10 \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add $10 \log(1/0.25) = 6$ dB if the duty cycle is 25 percent.

2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.
4. For **MIMO mode**, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

Method (1): Measure and sum the spectra across the outputs.

The total final Power Spectral Density is from a device with 2 transmitter outputs. The spectrum measurements of the individual outputs are all performed with the same span and number of points, the spectrum value in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 to obtain the value for the first frequency bin of the summed spectrum.


3.3.4 Test Setup





3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



3.4 Unwanted Emissions Measurement

This section as specified in FCC Part 15.407(b) is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement. The unwanted emissions shall comply with 15.407(b)(1) to (6), and restricted bands per FCC Part 15.205.

3.4.1 Limit of Unwanted Emissions

- (1) For transmitters operating in the 5725-5850 MHz band: all emissions within the frequency range from the band edge to 10 MHz above or below the band edge shall not exceed an EIRP of -17 dBm/MHz (78.3dBμV/m); for frequencies 10 MHz or greater above or below the band edge, emissions shall not exceed an EIRP of -27 dBm/MHz (68.3dBμV/m).
- (2) Unwanted spurious emissions fallen in restricted bands per FCC Part 15.205 shall comply with the general field strength limits set forth in § 15.209 as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 – 960	200	3
Above 960	500	3

Note: The following formula is used to convert the EIRP to field strength.

$$E = \frac{1000000\sqrt{30P}}{3} \text{ } \mu\text{V/m, where P is the eirp (Watts)}$$

EIRP (dBm)	Field Strength at 3m (dBμV/m)
-17	78.3
-27	68.3

- (3) KDB789033 v01r03 H)2)c)(i) As specified in 15.407(b), emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit of -27 dBm/MHz (or -17 dBm/MHz as specified in 15.407(b)(4)). However, an out-of-band emission that complies with both the average and peak limits of 15.209 is not required to satisfy the -27 dBm/MHz or -17 dBm/MHz peak emission limit.

3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01.

Section G) Unwanted emissions measurement.

(1) Procedure for Unwanted Emissions Measurements Below 1000MHz

- RBW = 120 kHz
- VBW = 300 kHz
- Detector = Peak
- Trace mode = max hold

(2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz

- RBW = 1 MHz
- VBW $\geq$ 3 MHz
- Detector = Peak
- Sweep time = auto
- Trace mode = max hold

(3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz

- RBW = 1 MHz
- VBW = 10 Hz, when duty cycle is no less than 98 percent.
- VBW $\geq$ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.


Antenna	Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
0	802.11a	95.833	2.070	0.483	1kHz
1	802.11a	95.387	2.068	0.484	1kHz
0+1	802.11n HT20	95.168	1.930	0.518	1kHz
0+1	802.11n HT40	90.649	0.950	1.053	3kHz
0+1	802.11n VHT20	95.562	1.938	0.516	1kHz
0+1	802.11n VHT40	92.292	0.958	1.044	3kHz
0+1	802.11n VHT80	83.813	0.466	2.146	3kHz




2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

3.4.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.4.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

3.4.6 Test Result of Radiated Band Edges

Please refer to Appendix B.

3.4.7 Test Result of Unwanted Radiated Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B.

3.5 AC Conducted Emission Measurement

3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.5.4 Test Setup






3.5.5 Test Result of AC Conducted Emission





Test Mode :	Mode 1	Temperature :	22~24℃
Test Engineer :	Eko Guan	Relative Humidity :	46~48%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM850 Idle + WLAN (5GHz) Link + USB Cable (Charging from Adapter)		



Site : CO01-KS
Condition : FCC PART 15E LISN-N20140306 NEUTRAL

mode	: Mode 1							
	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.44	42.78	-14.37	57.15	31.80	0.36	10.62	QP
2 *	0.44	35.18	-11.97	47.15	24.20	0.36	10.62	Average
3	0.52	42.52	-13.48	56.00	31.60	0.29	10.63	QP
4	0.52	32.72	-13.28	46.00	21.80	0.29	10.63	Average
5	0.56	38.40	-17.60	56.00	27.50	0.27	10.63	QP
6	0.56	27.70	-18.30	46.00	16.80	0.27	10.63	Average
7	4.60	36.24	-19.76	56.00	25.20	0.20	10.84	QP
8	4.60	30.84	-15.16	46.00	19.80	0.20	10.84	Average
9	4.98	38.85	-17.15	56.00	27.80	0.20	10.85	QP
10	4.98	32.75	-13.25	46.00	21.70	0.20	10.85	Average
11	5.48	40.26	-19.74	60.00	29.20	0.20	10.86	QP
12	5.48	34.26	-15.74	50.00	23.20	0.20	10.86	Average

3.6 Frequency Stability Measurement

3.6.1 Limit of Frequency Stability

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. To ensure emission at the band edge is maintained within the authorized band, those values shall be measured by radiation emissions at upper and lower frequency points, and finally compensated by frequency deviation as procedures below.
2. The EUT was operated at the maximum output power, and connected to the spectrum analyzer, which is set to maximum hold function and peak detector. The peak value of the power envelope was measured and noted. The upper and lower frequency points were respectively measured relatively 10dB lower than the measured peak value.
3. The frequency deviation was calculated by adding the upper frequency point and the lower frequency point divided by two. Those detailed values of frequency deviation are provided in table below.

3.6.4 Test Setup



3.6.5 Test Result of Frequency Stability

Please refer to Appendix A.

3.7 Automatically Discontinue Transmission

3.7.1 Limit of Automatically Discontinue Transmission

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

3.7.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.7.3 Test Result of Automatically Discontinue Transmission

While the EUT is not transmitting any information, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.

3.8 Antenna Requirements

3.8.1 Standard Applicable

According to FCC 47 CFR Section 15.407(a)(1)(2) ,if transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.8.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.8.3 Antenna Gain

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

For CDD transmissions, directional gain is calculated as

Directional gain = G_{ANT} + Array Gain, where Array Gain is as follows.

For power spectral density (PSD) measurements on all devices,

Array Gain = $10 \log(N_{ANT}/N_{SS}=1)$ dB.

For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$.

The EUT supports CDD mode.

The power and PSD limit should be modified if the directional gain of EUT is over 6 dBi,

The directional gain "DG" is calculated as following table.

	Chain	Chain	DG	DG	Power	PSD
	Port 1	Port 2	for	for	Limit	Limit
			Power	PSD	Reduction	Reduction
	(dBi)	(dBi)	(dBi)	(dBi)	(dB)	(dB)
Band IV	2.50	2.50	2.50	5.51	0.00	0.00

Power limit reduction = Composite gain – 6dBi, (min = 0)

PSD limit reduction = Composite gain + PSD Array gain – 6dBi, (min = 0)



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Oct. 28, 2014	Jul. 09, 2015	Oct. 27, 2015	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	30MHz~40GHz	Jan. 23, 2015	Jul. 09, 2015	Jan. 22, 2016	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 23, 2015	Jul. 09, 2015	Jan. 22, 2016	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-960502	-40~+150°C	Oct. 25, 2014	Jul. 09, 2015	Oct. 24, 2015	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESR7	101403	9kHz~7GHz; Max 30dBm	Sep. 29, 2014	Jul. 06, 2015	Sep. 28, 2015	Radiation (03CH02-KS)
Spectrum Analyzer	R&S	FSV40	101040	10kHz~40GHz; Max 30dBm	Sep. 25, 2014	Jul. 06, 2015	Sep. 24, 2015	Radiation (03CH02-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Nov. 13, 2014	Jul. 06, 2015	Nov. 12, 2015	Radiation (03CH02-KS)
Bilog Antenna	TeseQ	CBL6112D	37879	30MHz~2GHz	Sep. 13, 2014	Jul. 06, 2015	Sep. 12, 2015	Radiation (03CH02-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75957	1GHz~18GHz	Nov. 08, 2014	Jul. 06, 2015	Nov. 07, 2015	Radiation (03CH02-KS)
Active Horn Antenna	com-power	AHA-118	701030	1GHz~18GHz	Nov. 08, 2014	Jul. 06, 2015	Nov. 07, 2015	Radiation (03CH02-KS)
SHF-EHF Horn	com-power	AH-840	101070	18GHz~40GHz	Sep. 04, 2014	Jul. 06, 2015	Sep. 03, 2015	Radiation (03CH02-KS)
Amplifier	com-power	PA-103A	161069	1kHz~1000MHz / 32 dB	May 04, 2015	Jul. 06, 2015	May 03, 2016	Radiation (03CH02-KS)
Amplifier	Agilent	8449B	3008A02384	1GHz~26.5GHz Gain 30dB	Oct. 28, 2014	Jul. 06, 2015	Oct. 27, 2015	Radiation (03CH02-KS)
AC Power Source	Chroma	61601	616010002473	N/A	NCR	Jul. 06, 2015	NCR	Radiation (03CH02-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	Jul. 06, 2015	NCR	Radiation (03CH02-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	Jul. 06, 2015	NCR	Radiation (03CH02-KS)
EMI Receiver	R&S	ESC17	100768	9kHz~7GHz;	May 04, 2015	Jul. 03, 2015	May 03, 2016	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Oct. 25, 2014	Jul. 03, 2015	Oct. 24, 2015	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Oct. 25, 2014	Jul. 03, 2015	Oct. 24, 2015	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP000000811	AC 0V~300V, 45Hz~1000Hz	Oct. 25, 2014	Jul. 03, 2015	Oct. 24, 2015	Conduction (CO01-KS)



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.3 dB
--	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.1 dB
--	--------



Appendix A. Conducted Test Results

Report Number : FR562904C

Test Engineer:	Ocean Wang	Temperature:	21~25	°C
Test Date:	2015/7/9	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB bandwidth

FCC Band IV									
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	6 dB Bandwidth (MHz)		FCC 6 dB Bandwidth Min. Limit (MHz)		Pass/Fail
					Ant 0	Ant 1	Ant 0	Ant 1	
11a	6Mbps	1	149	5745	15.52		0.5	0.5	Pass
11a	6Mbps	1	157	5785	15.36		0.5	0.5	Pass
11a	6Mbps	1	165	5825	15.36		0.5	0.5	Pass
HT20	MCS0	1	149	5745	15.08		0.5	0.5	Pass
HT20	MCS0	1	157	5785	15.08		0.5	0.5	Pass
HT20	MCS0	1	165	5825	15.48		0.5	0.5	Pass
HT40	MCS0	1	151	5755		35.12	0.5	0.5	Pass
HT40	MCS0	1	159	5795		35.04	0.5	0.5	Pass
VHT20	MCS0	1	149	5745		15.08	0.5	0.5	Pass
VHT20	MCS0	1	157	5785		15.12	0.5	0.5	Pass
VHT20	MCS0	1	165	5825		15.12	0.5	0.5	Pass
VHT40	MCS0	1	151	5755		35.12	0.5	0.5	Pass
VHT40	MCS0	1	159	5795		35.04	0.5	0.5	Pass
VHT80	MCS0	1	155	5775		75.12	0.5	0.5	Pass
HT20	MCS0	2	149	5745	15.12	15.36	0.5		Pass
HT20	MCS0	2	157	5785	15.12	15.32	0.5		Pass
HT20	MCS0	2	165	5825	15.44	15.44	0.5		Pass
HT40	MCS0	2	151	5755	35.12	35.04	0.5		Pass
HT40	MCS0	2	159	5795	35.12	35.12	0.5		Pass
VHT20	MCS0	2	149	5745	15.12	15.12	0.5		Pass
VHT20	MCS0	2	157	5785	15.12	15.12	0.5		Pass
VHT20	MCS0	2	165	5825	15.12	15.44	0.5		Pass
VHT40	MCS0	2	151	5755	35.12	35.12	0.5		Pass
VHT40	MCS0	2	159	5795	35.12	35.04	0.5		Pass
VHT80	MCS0	2	155	5775	75.20	75.20	0.5		Pass

TEST RESULTS DATA
Average Power Table

FCC Band IV														
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)		Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
					Ant 0	Ant 1	Ant 0	Ant 1	SUM	Ant 0	Ant 1	Ant 0	Ant 1	
11a	6Mbps	1	149	5745	0.18	0.21	7.67	8.05		30.00	30.00	2.50	2.50	Pass
11a	6Mbps	1	157	5785	0.18	0.21	8.04	8.25		30.00	30.00	2.50	2.50	Pass
11a	6Mbps	1	165	5825	0.18	0.21	8.27	8.09		30.00	30.00	2.50	2.50	Pass
HT20	MCS0	1	149	5745	0.19	0.20	6.82	7.04		30.00	30.00	2.50	2.50	Pass
HT20	MCS0	1	157	5785	0.19	0.20	7.14	7.12		30.00	30.00	2.50	2.50	Pass
HT20	MCS0	1	165	5825	0.19	0.20	7.20	7.02		30.00	30.00	2.50	2.50	Pass
HT40	MCS0	1	151	5755	0.42	0.39	6.81	7.07		30.00	30.00	2.50	2.50	Pass
HT40	MCS0	1	159	5795	0.42	0.39	6.75	6.84		30.00	30.00	2.50	2.50	Pass
VHT20	MCS0	1	149	5745	0.20	0.20	5.54	5.93		30.00	30.00	2.50	2.50	Pass
VHT20	MCS0	1	157	5785	0.20	0.20	5.87	6.18		30.00	30.00	2.50	2.50	Pass
VHT20	MCS0	1	165	5825	0.20	0.20	6.07	5.98		30.00	30.00	2.50	2.50	Pass
VHT40	MCS0	1	151	5755	0.43	0.39	5.33	5.46		30.00	30.00	2.50	2.50	Pass
VHT40	MCS0	1	159	5795	0.43	0.39	5.20	5.21		30.00	30.00	2.50	2.50	Pass
VHT80	MCS0	1	155	5775	0.75	0.75	4.74	4.98		30.00	30.00	2.50	2.50	Pass
HT20	MCS0	2	149	5745	0.22	0.22	2.08	4.38	6.39	30.00		2.50		Pass
HT20	MCS0	2	157	5785	0.22	0.22	2.40	4.48	6.57	30.00		2.50		Pass
HT20	MCS0	2	165	5825	0.22	0.22	3.68	4.69	7.22	30.00		2.50		Pass
HT40	MCS0	2	151	5755	0.47	0.43	2.86	5.08	7.12	30.00		2.50		Pass
HT40	MCS0	2	159	5795	0.47	0.43	2.80	4.75	6.89	30.00		2.50		Pass
VHT20	MCS0	2	149	5745	0.20	0.20	1.81	3.93	6.01	30.00		2.50		Pass
VHT20	MCS0	2	157	5785	0.20	0.20	2.14	4.12	6.25	30.00		2.50		Pass
VHT20	MCS0	2	165	5825	0.20	0.20	2.55	4.25	6.49	30.00		2.50		Pass
VHT40	MCS0	2	151	5755	0.35	0.44	1.07	3.34	5.36	30.00		2.50		Pass
VHT40	MCS0	2	159	5795	0.35	0.44	1.31	3.37	5.47	30.00		2.50		Pass
VHT80	MCS0	2	155	5775	0.77	0.77	1.09	3.20	5.28	30.00		2.50		Pass

TEST RESULTS DATA
Power Spectral Density

FCC Band IV																
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)		10log (500kHz /RBW) Factor (dB)		Average Power Density (dBm/500kHz)			Average PSD Limit (dBm/500kHz)		DG (dBi)		Pass /Fail
					Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1	SUM	Ant 0	Ant 1	Ant 0	Ant 1	
11a	6Mbps	1	149	5745	0.18	0.21	2.22	2.22	-2.25			30.00	30.00	2.50	2.50	Pass
11a	6Mbps	1	157	5785	0.18	0.21	2.22	2.22	-2.28			30.00	30.00	2.50	2.50	Pass
11a	6Mbps	1	165	5825	0.18	0.21	2.22	2.22	-2.34			30.00	30.00	2.50	2.50	Pass
HT20	MCS0	1	149	5745	0.19	0.20	2.22	2.22	-3.22			30.00	30.00	2.50	2.50	Pass
HT20	MCS0	1	157	5785	0.19	0.20	2.22	2.22	-3.73			30.00	30.00	2.50	2.50	Pass
HT20	MCS0	1	165	5825	0.19	0.20	2.22	2.22	-3.80			30.00	30.00	2.50	2.50	Pass
HT40	MCS0	1	151	5755	0.42	0.39	2.22	2.22		-10.52		30.00	30.00	2.50	2.50	Pass
HT40	MCS0	1	159	5795	0.42	0.39	2.22	2.22		-10.72		30.00	30.00	2.50	2.50	Pass
VHT20	MCS0	1	149	5745	0.20	0.20	2.22	2.22		-8.50		30.00	30.00	2.50	2.50	Pass
VHT20	MCS0	1	157	5785	0.20	0.20	2.22	2.22		-8.57		30.00	30.00	2.50	2.50	Pass
VHT20	MCS0	1	165	5825	0.20	0.20	2.22	2.22		-8.63		30.00	30.00	2.50	2.50	Pass
VHT40	MCS0	1	151	5755	0.43	0.39	2.22	2.22		-12.00		30.00	30.00	2.50	2.50	Pass
VHT40	MCS0	1	159	5795	0.43	0.39	2.22	2.22		-12.22		30.00	30.00	2.50	2.50	Pass
VHT80	MCS0	1	155	5775	0.75	0.75	2.22	2.22		-15.76		30.00	30.00	2.50	2.50	Pass
HT20	MCS0	2	149	5745	0.22	0.22	2.22				-6.25	30.00		5.51		Pass
HT20	MCS0	2	157	5785	0.22	0.22	2.22				-6.47	30.00		5.51		Pass
HT20	MCS0	2	165	5825	0.22	0.22	2.22				-6.44	30.00		5.51		Pass
HT40	MCS0	2	151	5755	0.47	0.43	2.22				-9.03	30.00		5.51		Pass
HT40	MCS0	2	159	5795	0.47	0.43	2.22				-9.33	30.00		5.51		Pass
VHT20	MCS0	2	149	5745	0.20	0.20	2.22				-6.92	30.00		5.51		Pass
VHT20	MCS0	2	157	5785	0.20	0.20	2.22				-6.97	30.00		5.51		Pass
VHT20	MCS0	2	165	5825	0.20	0.20	2.22				-7.16	30.00		5.51		Pass
VHT40	MCS0	2	151	5755	0.35	0.44	2.22				-10.73	30.00		5.51		Pass
VHT40	MCS0	2	159	5795	0.35	0.44	2.22				-11.31	30.00		5.51		Pass
VHT80	MCS0	2	155	5775	0.77	0.77	2.22				-15.22	30.00		5.51		Pass

TEST RESULTS DATA
Frequency Stability

Band IV										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Center Frequency (MHz)	Frequency Deviation (MHz)	Frequency Stability (ppm)	Temperature (°C)	Voltage (V)	Note
11a	6Mbps	1	149	5745	5745.000	0.000	0.00	20	3.6	
11a	6Mbps	1	149	5745	5745.000	0.000	0.00	20	4.35	
11a	6Mbps	1	149	5745	5745.000	0.000	0.00	20	3.8	
11a	6Mbps	1	149	5745	5745.000	0.000	0.00	-30	3.8	
11a	6Mbps	1	149	5745	5745.000	0.000	0.00	50	3.8	



Appendix B. Radiated Test Results

Band 4 - 5725~5850MHz

WIFI 802.11a (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
0		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a CH 149 5745MHz	*	5742	103.54	-	-	97.16	35.19	7.48	36.29	150	27	P	H
	*	5742	93.82	-	-	87.44	35.19	7.48	36.29	150	27	A	H
		5714.84	56.36	-11.94	68.3	50.02	35.16	7.45	36.27	150	27	P	H
		5724.12	68.98	-9.32	78.3	62.61	35.18	7.47	36.28	150	27	P	H
	*	5742	103.02	-	-	96.64	35.19	7.48	36.29	283	88	P	V
	*	5742	93.02	-	-	86.64	35.19	7.48	36.29	283	88	A	V
		5709.32	55.51	-12.79	68.3	49.17	35.16	7.45	36.27	283	88	P	V
		5724.12	68.49	-9.81	78.3	62.12	35.18	7.47	36.28	283	88	P	V
802.11a CH 157 5785MHz	*	5788	104.22	-	-	97.77	35.24	7.53	36.32	168	31	P	H
	*	5786	94.33	-	-	87.88	35.24	7.53	36.32	168	31	A	H
	*	5782	101.6	-	-	95.18	35.22	7.51	36.31	300	81	P	V
	*	5780	91.31	-	-	84.89	35.22	7.51	36.31	300	81	A	V
802.11a CH 165 5825MHz	*	5828	103.17	-	-	96.68	35.27	7.57	36.35	210	308	P	H
	*	5828	93.38	-	-	86.89	35.27	7.57	36.35	210	308	A	H
		5850.96	59.07	-19.23	78.3	52.56	35.28	7.59	36.36	210	308	P	H
		5860.4	54.9	-13.4	68.3	48.36	35.3	7.61	36.37	210	308	P	H
	*	5824	97.38	-	-	90.89	35.27	7.57	36.35	150	215	P	V
	*	5824	87.51	-	-	81.02	35.27	7.57	36.35	150	215	A	V
		5850.88	54.17	-24.13	78.3	47.66	35.28	7.59	36.36	150	215	P	V
		5861.04	49.86	-18.44	68.3	43.32	35.3	7.61	36.37	150	215	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11a (Harmonic @ 3m)

WIFI Ant. 0	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 149 5745MHz		11490	56.85	-17.15	74	44.12	38.99	10.77	37.03	150	85	P	H
		11490	43.55	-10.45	54	30.82	38.99	10.77	37.03	150	85	A	H
		11490	55.21	-18.79	74	42.48	38.99	10.77	37.03	150	360	P	V
		11490	41.21	-12.79	54	28.48	38.99	10.77	37.03	150	360	A	V
802.11a CH 157 5785MHz		11571	56.23	-17.77	74	43.38	39.06	10.8	37.01	174	55	P	H
		11571	42.17	-11.83	54	29.32	39.06	10.8	37.01	174	55	A	H
		11570	57.22	-16.78	74	44.37	39.06	10.8	37.01	150	96	P	V
		11570	43.62	-10.38	54	30.77	39.06	10.8	37.01	150	96	A	V
802.11a CH 165 5825MHz		11652	56.89	-17.11	74	43.92	39.12	10.84	36.99	150	169	P	H
		11652	42.59	-11.41	54	29.62	39.12	10.84	36.99	150	169	A	H
		11649	56.33	-17.67	74	43.38	39.11	10.83	36.99	150	58	P	V
		11649	42.85	-11.15	54	29.9	39.11	10.83	36.99	150	58	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

5GHz WIFI 802.11a (LF @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
0		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
5GHz 802.11a LF		32.91	24.19	-15.81	40	40.48	18.2	0.76	35.25	103	65	P	H
		110.51	25.89	-17.61	43.5	47.93	11.91	1.36	35.31	-	-	P	H
		263.77	15.65	-30.35	46	36.37	11.98	2.13	34.83	-	-	P	H
		346.22	16.69	-29.31	46	34.79	14.52	2.44	35.06	-	-	P	H
		453.89	18.64	-27.36	46	33.68	17.02	2.81	34.87	-	-	P	H
		547.01	19.85	-26.15	46	33.08	18.15	3.12	34.5	-	-	P	H
		38.73	33.12	-6.88	40	52.71	14.56	0.82	34.97	115	25	P	V
		55.22	30.35	-9.65	40	57.79	7.2	0.97	35.61	-	-	P	V
		161.92	24.86	-18.64	43.5	47.35	10.78	1.64	34.91	-	-	P	V
		362.71	16.47	-29.53	46	34.08	15.01	2.5	35.12	-	-	P	V
		443.22	17.37	-28.63	46	32.64	16.89	2.78	34.94	-	-	P	V
		545.07	19.04	-26.96	46	32.31	18.11	3.12	34.5	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Band 4 - 5725~5850MHz

WIFI 802.11a (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a CH 149 5745MHz	*	5742	102.47	-	-	96.09	35.19	7.48	36.29	150	244	P	H
	*	5746	92.42	-	-	86.04	35.19	7.48	36.29	150	244	A	H
		5710.52	56.36	-11.94	68.3	50.02	35.16	7.45	36.27	150	244	P	H
		5724.6	59.37	-18.93	78.3	53	35.18	7.47	36.28	150	244	P	H
	*	5742	98.66	-	-	92.28	35.19	7.48	36.29	295	156	P	V
	*	5744	88.78	-	-	82.4	35.19	7.48	36.29	295	156	A	V
		5709.88	55.13	-13.17	68.3	48.79	35.16	7.45	36.27	295	156	P	V
		5724.92	56.68	-21.62	78.3	50.31	35.18	7.47	36.28	295	156	P	V
802.11a CH 157 5785MHz	*	5782	101.58	-	-	95.16	35.22	7.51	36.31	150	28	P	H
	*	5782	92.49	-	-	86.07	35.22	7.51	36.31	150	28	A	H
	*	5782	101.66	-	-	95.24	35.22	7.51	36.31	223	203	P	V
	*	5782	92.51	-	-	86.09	35.22	7.51	36.31	223	203	A	V
802.11a CH 165 5825MHz	*	5822	101.37	-	-	94.88	35.27	7.57	36.35	150	251	P	H
	*	5822	91.83	-	-	85.34	35.27	7.57	36.35	150	251	A	H
		5850.8	55.54	-22.76	78.3	49.03	35.28	7.59	36.36	150	251	P	H
		5863.44	54.46	-13.84	68.3	47.92	35.3	7.61	36.37	150	251	P	H
	*	5822	93.31	-	-	86.82	35.27	7.57	36.35	150	17	P	V
	*	5822	83.44	-	-	76.95	35.27	7.57	36.35	150	17	A	V
		5856.72	52.78	-25.52	78.3	46.24	35.3	7.61	36.37	150	17	P	V
		5885.36	51.83	-16.47	68.3	45.28	35.3	7.63	36.38	150	17	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11a (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 149 5745MHz		11490	52.09	-21.91	74	39.36	38.99	10.77	37.03	155	103	P	H
		11490	38.12	-15.88	54	25.39	38.99	10.77	37.03	155	103	A	H
		11490	51.94	-22.06	74	39.21	38.99	10.77	37.03	150	185	P	V
		11490	38.07	-15.93	54	25.34	38.99	10.77	37.03	150	185	A	V
802.11a CH 157 5785MHz		11571	51.49	-22.51	74	38.64	39.06	10.8	37.01	150	98	P	H
		11571	37.04	-16.96	54	24.19	39.06	10.8	37.01	150	98	A	H
		11571	52.16	-21.84	74	39.31	39.06	10.8	37.01	150	231	P	V
		11571	38.46	-15.54	54	25.61	39.06	10.8	37.01	150	231	A	V
802.11a CH 165 5825MHz		10650	52.41	-21.59	74	40.91	38.33	10.42	37.25	150	132	P	H
		10650	38	-16	54	26.5	38.33	10.42	37.25	150	132	A	H
		10650	51.46	-22.54	74	39.96	38.33	10.42	37.25	186	83	P	V
		10650	37.13	-16.87	54	25.63	38.33	10.42	37.25	186	83	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

5GHz WIFI 802.11a (LF @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
5GHz 802.11a LF		32.91	26.19	-13.81	40	42.48	18.2	0.76	35.25	166	52	P	H
		110.51	22.89	-20.61	43.5	44.93	11.91	1.36	35.31			P	H
		263.77	14.65	-31.35	46	35.37	11.98	2.13	34.83			P	H
		572.23	20.99	-25.01	46	34.17	18.33	3.19	34.7			P	H
		736.16	20.8	-25.2	46	32.02	19.66	3.65	34.53			P	H
		908.82	22.48	-23.52	46	31.54	21.45	4.05	34.56			P	H
	!	38.73	35.12	-4.88	40	54.71	14.56	0.82	34.97	199	85	P	V
		55.22	32.35	-7.65	40	59.79	7.2	0.97	35.61			P	V
		110.51	23.4	-20.1	43.5	45.44	11.91	1.36	35.31			P	V
		161.92	29.86	-13.64	43.5	52.35	10.78	1.64	34.91			P	V
		578.05	20.78	-25.22	46	33.97	18.37	3.2	34.76			P	V
		853.53	22.24	-23.76	46	31.55	21.12	3.92	34.35			P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Band 4 5725~5850MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI Ant. 0+1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 149 5745MHz	*	5746	100.19	-	-	93.81	35.19	7.48	36.29	159	34	P	H
	*	5746	90.29	-	-	83.91	35.19	7.48	36.29	159	34	A	H
		5701.64	57.66	-10.64	68.3	51.32	35.16	7.45	36.27	159	34	P	H
		5724.68	60.76	-17.54	78.3	54.39	35.18	7.47	36.28	159	34	P	H
	*	5742	101.53	-	-	95.15	35.19	7.48	36.29	238	152	P	V
	*	5742	91.52	-	-	85.14	35.19	7.48	36.29	238	152	A	V
		5701	57.55	-10.75	68.3	51.21	35.16	7.45	36.27	238	152	P	V
		5724.44	60.89	-17.41	78.3	54.52	35.18	7.47	36.28	238	152	P	V
802.11n HT20 CH 157 5785MHz	*	5788	101.07	-	-	94.62	35.24	7.53	36.32	150	36	P	H
	*	5786	91.44	-	-	84.99	35.24	7.53	36.32	150	36	A	H
	*	5780	100.25	-	-	93.83	35.22	7.51	36.31	240	151	P	V
	*	5782	90.16	-	-	83.74	35.22	7.51	36.31	240	151	A	V
802.11n HT20 CH 165 5825MHz	*	5828	101.68	-	-	95.19	35.27	7.57	36.35	245	122	P	H
	*	5826	91.59	-	-	85.1	35.27	7.57	36.35	245	122	A	H
		5852.48	51.07	-27.23	78.3	44.56	35.28	7.59	36.36	245	122	P	H
		5862.64	51.27	-17.03	68.3	44.73	35.3	7.61	36.37	245	122	P	H
	*	5820	97.94	-	-	91.45	35.27	7.57	36.35	300	151	P	V
	*	5828	87.82	-	-	81.33	35.27	7.57	36.35	300	151	A	V
		5850.8	57.54	-20.76	78.3	51.03	35.28	7.59	36.36	300	151	P	V
		5879.68	58.2	-10.1	68.3	51.65	35.3	7.63	36.38	300	151	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz
WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant. 0+1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 149 5745MHz		11490	50.6	-23.4	74	37.87	38.99	10.77	37.03	150	98	P	H
		11490	49.82	-24.18	74	37.09	38.99	10.77	37.03	150	309	P	V
802.11n HT20 CH 157 5785MHz		11570	49.48	-24.52	74	36.63	39.06	10.8	37.01	150	332	P	H
		11570	48.58	-25.42	74	35.73	39.06	10.8	37.01	200	145	P	V
802.11n HT20 CH 165 5825MHz		11650	50.13	-23.87	74	37.18	39.11	10.83	36.99	150	114	P	H
		11650	48.72	-25.28	74	35.77	39.11	10.83	36.99	150	326	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI Ant. 0+1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 151 5755MHz	*	5752	94.27	-	-	87.86	35.21	7.5	36.3	150	296	P	H
	*	5750	85.61	-	-	79.23	35.19	7.48	36.29	150	296	A	H
		5713.24	52.96	-15.34	68.3	46.62	35.16	7.45	36.27	150	296	P	H
		5721.4	56.57	-21.73	78.3	50.2	35.18	7.47	36.28	150	296	P	H
	*	5758	96.86	-	-	90.45	35.21	7.5	36.3	223	200	P	V
	*	5748	88.07	-	-	81.69	35.19	7.48	36.29	223	200	A	V
		5713.88	56.16	-12.14	68.3	49.82	35.16	7.45	36.27	223	200	P	V
		5721.48	59.52	-18.78	78.3	53.15	35.18	7.47	36.28	223	200	P	V
802.11n HT40 CH 159 5795MHz	*	5798	95	-	-	88.55	35.24	7.53	36.32	150	299	P	H
	*	5788	85.64	-	-	79.19	35.24	7.53	36.32	150	299	A	H
		5856.56	50.62	-27.68	78.3	44.08	35.3	7.61	36.37	150	299	P	H
		5881.92	50.59	-17.71	68.3	44.04	35.3	7.63	36.38	150	299	P	H
	*	5798	95.66	-	-	89.21	35.24	7.53	36.32	150	200	P	V
	*	5798	85.89	-	-	79.44	35.24	7.53	36.32	150	200	A	V
		5852.48	51.28	-27.02	78.3	44.77	35.28	7.59	36.36	150	200	P	V
		5873.36	50.66	-17.64	68.3	44.11	35.3	7.63	36.38	150	200	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz
WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI Ant. 0+1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 151 5755MHz		11510	50.33	-23.67	74	37.59	39	10.77	37.03	150	100	P	H
		11511	50	-24	74	37.26	39	10.77	37.03	150	85	P	V
802.11n HT40 CH 159 5795MHz		11590	49.93	-24.07	74	37.06	39.07	10.81	37.01	174	55	P	H
		11589	50.3	-23.7	74	37.43	39.07	10.81	37.01	162	114	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11ac VHT20 (Band Edge @ 3m)

WIFI Ant. 0+1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT20 CH 149 5745MHz	*	5744	99.44	-	-	93.06	35.19	7.48	36.29	300	81	P	H
	*	5744	89.48	-	-	83.1	35.19	7.48	36.29	300	81	A	H
		5714.44	51.44	-16.86	68.3	45.1	35.16	7.45	36.27	300	81	P	H
		5723.96	56.64	-21.66	78.3	50.27	35.18	7.47	36.28	300	81	P	H
	*	5746	99.96	-	-	93.58	35.19	7.48	36.29	300	16	P	V
	*	5748	90.09	-	-	83.71	35.19	7.48	36.29	300	16	A	V
		5712.68	51.37	-16.93	68.3	45.03	35.16	7.45	36.27	300	16	P	V
		5724.6	57.55	-20.75	78.3	51.18	35.18	7.47	36.28	300	16	P	V
802.11ac VHT20 CH 157 5785MHz	*	5784	98.11	-	-	91.69	35.22	7.51	36.31	160	48	P	H
	*	5784	88.51	-	-	82.09	35.22	7.51	36.31	160	48	A	H
	*	5782	97.68	-	-	91.26	35.22	7.51	36.31	300	155	P	V
	*	5782	87.62	-	-	81.2	35.22	7.51	36.31	300	155	A	V
802.11ac VHT20 CH 165 5825MHz	*	5828	98.04	-	-	91.55	35.27	7.57	36.35	257	122	P	H
	*	5828	88.41	-	-	81.92	35.27	7.57	36.35	257	122	A	H
		5851.36	51.44	-26.86	78.3	44.93	35.28	7.59	36.36	257	122	P	H
		5863.84	51.43	-16.87	68.3	44.89	35.3	7.61	36.37	257	122	P	H
	*	5824	97.31	-	-	90.82	35.27	7.57	36.35	300	65	P	V
	*	5824	87.52	-	-	81.03	35.27	7.57	36.35	300	65	A	V
		5858	50.29	-28.01	78.3	43.75	35.3	7.61	36.37	300	65	P	V
		5866.32	52.21	-16.09	68.3	45.67	35.3	7.61	36.37	300	65	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11ac VHT20 (Harmonic @ 3m)

WIFI Ant. 0+1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT20		11490	48.74	-25.26	74	36.01	38.99	10.77	37.03	169	258	P	H
CH 149 5745MHz		11490	48.23	-25.77	74	35.5	38.99	10.77	37.03	150	100	P	V
802.11ac VHT20		11570	48.27	-25.73	74	35.42	39.06	10.8	37.01	300	48	P	H
CH 157 5785MHz		11571	48.01	-25.99	74	35.16	39.06	10.8	37.01	195	66	P	V
802.11ac VHT20		11649	50.35	-23.65	74	37.4	39.11	10.83	36.99	150	33	P	H
CH 165 5825MHz		11650	48.37	-25.63	74	35.42	39.11	10.83	36.99	150	313	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz
WIFI 802.11ac VHT40 (Band Edge @ 3m)

WIFI Ant. 0+1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT40 CH 151 5755MHz	*	5754	95.17	-	-	88.76	35.21	7.5	36.3	300	78	P	H
	*	5742	76.98	-	-	70.6	35.19	7.48	36.29	300	78	A	H
		5709.48	50.54	-17.76	68.3	44.2	35.16	7.45	36.27	300	78	P	H
		5723.64	51	-27.3	78.3	44.63	35.18	7.47	36.28	300	78	P	H
	*	5754	94.78	-	-	88.37	35.21	7.5	36.3	300	77	P	V
	*	5752	85.65	-	-	79.24	35.21	7.5	36.3	300	77	A	V
		5708.84	57.11	-11.19	68.3	50.77	35.16	7.45	36.27	300	77	P	V
		5721.56	58.69	-19.61	78.3	52.32	35.18	7.47	36.28	300	77	P	V
802.11ac VHT40 CH 159 5795MHz	*	5798	94.69	-	-	88.24	35.24	7.53	36.32	168	34	P	H
	*	5798	86	-	-	79.55	35.24	7.53	36.32	150	34	A	H
		5852.8	53.53	-24.77	78.3	47.02	35.28	7.59	36.36	150	34	P	H
		5886.56	50.89	-17.41	68.3	44.34	35.3	7.63	36.38	150	34	P	H
	*	5792	94.67	-	-	88.22	35.24	7.53	36.32	300	156	P	V
	*	5792	85.14	-	-	78.69	35.24	7.53	36.32	300	156	A	V
		5856.88	50.81	-27.49	78.3	44.27	35.3	7.61	36.37	300	156	P	V
		5879.12	51.4	-16.9	68.3	44.85	35.3	7.63	36.38	300	156	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11ac VHT40 (Harmonic @ 3m)

WIFI Ant. 0+1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT40		11510	49.97	-24.03	74	37.23	39	10.77	37.03	200	155	P	H
CH 151 5755MHz		11511	49.41	-24.59	74	36.67	39	10.77	37.03	150	79	P	V
802.11ac VHT40		11590	49.07	-24.93	74	36.2	39.07	10.81	37.01	150	190	P	H
CH 159 5795MHz		11589	49.82	-24.18	74	36.95	39.07	10.81	37.01	150	147	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11ac VHT80 (Band Edge @ 3m)

WIFI Ant. 0+1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT80 CH 155 5775MHz	*	5776	92.51	-	-	86.09	35.22	7.51	36.31	150	34	P	H
	*	5786	82.79	-	-	76.34	35.24	7.53	36.32	150	34	A	H
		5710.52	59.53	-8.77	68.3	53.19	35.16	7.45	36.27	150	34	P	H
		5718.84	62.93	-15.37	78.3	56.56	35.18	7.47	36.28	150	34	P	H
		5851.36	56.7	-21.6	78.3	50.19	35.28	7.59	36.36	150	34	P	H
		5864.4	55.64	-12.66	68.3	49.1	35.3	7.61	36.37	150	34	P	H
	*	5750	90.33	-	-	83.95	35.19	7.48	36.29	300	200	P	V
	*	5768	80.71	-	-	74.3	35.21	7.5	36.3	300	200	A	V
		5712.6	60.87	-7.43	68.3	54.53	35.16	7.45	36.27	300	200	P	V
		5723.16	63.17	-15.13	78.3	56.8	35.18	7.47	36.28	300	200	P	V
		5851.68	55.24	-23.06	78.3	48.73	35.28	7.59	36.36	300	200	P	V
		5867.52	54.59	-13.71	68.3	48.05	35.3	7.61	36.37	300	200	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

**Band 4 5725~5850MHz****WIFI 802.11ac VHT80 (Harmonic @ 3m)**

WIFI Ant. 0+1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT80		11550	50.88	-23.12	74	38.07	39.04	10.79	37.02	150	174	P	H
CH 155 5775MHz		11550	49.78	-24.22	74	36.97	39.04	10.79	37.02	150	322	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

5GHz WIFI 802.11n HT20 (LF @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
0+1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
5GHz 802.11n HT20 LF		110.51	16.89	-26.61	43.5	38.93	11.91	1.36	35.31	-	-	P	H
		263.77	17.65	-28.35	46	38.37	11.98	2.13	34.83	-	-	P	H
		408.3	21.62	-24.38	46	37.79	16.34	2.67	35.18	-	-	P	H
		622.67	21.15	-24.85	46	34	18.73	3.32	34.9	-	-	P	H
		736.16	21.8	-24.2	46	33.02	19.66	3.65	34.53	-	-	P	H
		857.41	21.85	-24.15	46	31.14	21.15	3.93	34.37	105	221	P	H
		38.73	33.12	-6.88	40	52.71	14.56	0.82	34.97	174	200	P	V
		55.22	30.35	-9.65	40	57.79	7.2	0.97	35.61	-	-	P	V
		72.68	21.85	-18.15	40	48.06	7.78	1.1	35.09	-	-	P	V
		161.92	22.86	-20.64	43.5	45.35	10.78	1.64	34.91	-	-	P	V
		443.22	18.37	-27.63	46	33.64	16.89	2.78	34.94	-	-	P	V
		672.14	21.38	-24.62	46	33.6	19.13	3.48	34.83	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Emission below 1GHz

5GHz WIFI 802.11n HT40 (LF @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
0+1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
5GHz 802.11n HT40 LF		110.51	24.89	-18.61	43.5	46.93	11.91	1.36	35.31	100	219	P	H
		263.77	14.65	-31.35	46	35.37	11.98	2.13	34.83	-	-	P	H
		346.22	14.69	-31.31	46	32.79	14.52	2.44	35.06	-	-	P	H
		540.22	16.81	-29.19	46	30.2	18.02	3.1	34.51	-	-	P	H
		687.66	18.75	-27.25	46	30.84	19.22	3.53	34.84	-	-	P	H
		869.05	20.18	-25.82	46	29.42	21.22	3.96	34.42	-	-	P	H
		38.73	30.12	-9.88	40	49.71	14.56	0.82	34.97	-	-	P	V
		53.28	30.57	-9.43	40	57.17	7.85	0.96	35.41	166	98	P	V
		160.95	24.62	-18.88	43.5	47.09	10.81	1.63	34.91	-	-	P	V
		215.27	18.11	-25.39	43.5	41.2	10.02	1.91	35.02	-	-	P	V
		545.07	18.04	-27.96	46	31.31	18.11	3.12	34.5	-	-	P	V
		880.69	21.1	-24.9	46	30.32	21.28	3.98	34.48	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Emission below 1GHz

5GHz WIFI 802.11ac VHT20 (LF @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
0+1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
5GHz 802.11n HT40 LF		32.91	23.19	-16.81	40	39.48	18.2	0.76	35.25	102	144	P	H
		110.51	19.89	-23.61	43.5	41.93	11.91	1.36	35.31	-	-	P	H
		388.9	18.94	-27.06	46	35.69	15.85	2.6	35.2	-	-	P	H
		572.23	22.99	-23.01	46	36.17	18.33	3.19	34.7	-	-	P	H
		687.66	22.75	-23.25	46	34.84	19.22	3.53	34.84	-	-	P	H
		774.96	23.23	-22.77	46	33.91	20.05	3.74	34.47	-	-	P	H
		37.76	30.86	-9.14	40	49.78	15.32	0.81	35.05	200	305	P	V
		57.16	27.83	-12.17	40	55.41	7	0.99	35.57	-	-	P	V
		161.92	23.86	-19.64	43.5	46.35	10.78	1.64	34.91	-	-	P	V
		443.22	17.37	-28.63	46	32.64	16.89	2.78	34.94	-	-	P	V
		672.14	20.38	-25.62	46	32.6	19.13	3.48	34.83	-	-	P	V
		853.53	22.24	-23.76	46	31.55	21.12	3.92	34.35	-	-	P	V
Remark	1. No other spurious found.												
	2. All results are PASS against limit line.												



Emission below 1GHz

5GHz WIFI 802.11ac VHT40 (LF @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
0+1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
5GHz 802.11n HT40 LF		32.91	22.19	-17.81	40	38.48	18.2	0.76	35.25	100	326	P	H
		110.51	18.89	-24.61	43.5	40.93	11.91	1.36	35.31	-	-	P	H
		205.57	15.28	-28.22	43.5	38.84	9.63	1.87	35.06	-	-	P	H
		408.3	18.62	-27.38	46	34.79	16.34	2.67	35.18	-	-	P	H
		518.88	19.21	-26.79	46	33.08	17.64	3.02	34.53	-	-	P	H
		622.67	20.15	-25.85	46	33	18.73	3.32	34.9	-	-	P	H
		38.73	32.21	-7.79	40	51.8	14.56	0.82	34.97	200	156	P	V
		109.54	24.17	-19.33	43.5	46.2	11.93	1.35	35.31	-	-	P	V
		161.92	23.86	-19.64	43.5	46.35	10.78	1.64	34.91	-	-	P	V
		443.22	18.37	-27.63	46	33.64	16.89	2.78	34.94	-	-	P	V
		525.67	19.27	-26.73	46	32.98	17.76	3.05	34.52	-	-	P	V
		727.43	21.46	-24.54	46	32.87	19.57	3.63	34.61	-	-	P	V
Remark	1. No other spurious found.												
	2. All results are PASS against limit line.												



Emission below 1GHz

5GHz WIFI 802.11ac VHT80 (LF @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
0+1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
5GHz 802.11n HT40 LF		110.51	19.89	-23.61	43.5	41.93	11.91	1.36	35.31	100	145	P	H
		166.77	15.84	-27.66	43.5	38.51	10.6	1.66	34.93	-	-	P	H
		263.77	15.65	-30.35	46	36.37	11.98	2.13	34.83	-	-	P	H
		388.9	15.94	-30.06	46	32.69	15.85	2.6	35.2	-	-	P	H
		482.99	17.5	-28.5	46	32.07	17.2	2.9	34.67	-	-	P	H
		572.23	18.99	-27.01	46	32.17	18.33	3.19	34.7	-	-	P	H
		55.22	32.35	-7.65	40	59.79	7.2	0.97	35.61	122	98	P	V
		106.63	21.17	-22.33	43.5	43.17	11.98	1.34	35.32	-	-	P	V
		161.92	23.86	-19.64	43.5	46.35	10.78	1.64	34.91	-	-	P	V
		290.93	15.09	-30.91	46	34.49	13.13	2.24	34.77	-	-	P	V
		672.14	22.38	-23.62	46	34.6	19.13	3.48	34.83	-	-	P	V
		905.91	24.97	-21.03	46	34.05	21.44	4.04	34.56	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

**Note symbol**

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	P eak or A verage
H/V	H orizontal or V ertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
0+1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.