



REPORT No. : SZ14100069W02

# FCC RF TEST REPORT

APPLICANT : ZTE Corporation  
PRODUCT NAME : WCDMA Digital Mobile Phone Handset  
MODEL NAME : NX406E  
TRADE NAME : ZTE  
BRAND NAME : ZTE  
FCC ID : SRQ-NX406E  
STANDARD(S) : 47 CFR Part 15 Subpart C  
ISSUE DATE : 2014-11-05



**SHENZHEN MORLAB COMMUNICATIONS TECHNOLOGY Co., Ltd.**

NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

**MORLAB GROUP**

FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road,  
Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China

Tel: 86-755-36698555  
Http://www.morlab.com

Fax: 86-755-36698525  
E-mail: service@morlab.cn



# DIRECTORY

**TEST REPORT DECLARATION .....4**

**1. TECHNICAL INFORMATION .....5**

1.1. APPLICANT INFORMATION .....5

1.2. EQUIPMENT UNDER TEST (EUT) DESCRIPTION.....5

1.2.1. IDENTIFICATION OF ALL USED EUTS.....5

1.3. TEST STANDARDS AND RESULTS .....6

1.3.1. TEST ENVIRONMENT CONDITIONS .....6

**2. 47 CFR PART 15C REQUIREMENTS .....7**

2.1. ANTENNA REQUIREMENT.....7

2.1.1. APPLICABLE STANDARD.....7

2.1.2. RESULT: COMPLIANT.....7

2.2. PEAK OUTPUT POWER.....7

2.2.1. REQUIREMENT .....7

2.2.2. TEST DESCRIPTION .....7

2.2.3. TEST RESULT .....8

2.3. AVERAGE POWER.....11

2.3.1. REQUIREMENT .....11

2.3.2. TEST DESCRIPTION .....11

2.3.3. RESULTS .....11

2.4. 6DB BANDWIDTH .....12

2.4.1. REQUIREMENT .....12

2.4.2. TEST DESCRIPTION .....12

2.4.3. TEST RESULT .....12

2.5. CONDUCTED SPURIOUS EMISSIONS AND BAND EDGE .....15

2.5.1. REQUIREMENT .....15

2.5.2. TEST DESCRIPTION .....15

2.5.3. TEST RESULT .....15

2.6. POWER SPECTRAL DENSITY (PSD) .....19

2.6.1. REQUIREMENT .....19

2.6.2. TEST DESCRIPTION .....19

2.6.3. TEST RESULT .....19



**2.7. RESTRICTED FREQUENCY BANDS .....22**

2.7.1. REQUIREMENT ..... 22

2.7.2. TEST DESCRIPTION ..... 22

2.7.3. TEST RESULT ..... 23

**2.8. CONDUCTED EMISSION .....26**

2.8.1. REQUIREMENT ..... 26

2.8.2. TEST DESCRIPTION ..... 26

2.8.3. TEST RESULT ..... 27

**2.9. RADIATED EMISSION .....29**

2.9.1. REQUIREMENT ..... 29

2.9.2. TEST DESCRIPTION ..... 29

2.9.3. TEST RESULT ..... 32

**2.10. RF EXPOSURE EVALUATION .....36**

2.10.1. REQUIREMENT ..... 36

2.10.2. RESULT ..... 36

**ANNEX A GENERAL INFORMATION .....37**

**1.1 IDENTIFICATION OF THE RESPONSIBLE TESTING LABORATORY .....37**

**1.2 IDENTIFICATION OF THE RESPONSIBLE TESTING LOCATION .....37**

**1.3 FACILITIES AND ACCREDITATIONS .....37**

**1.4 TEST EQUIPMENTS UTILIZED .....38**

1.4.1 CONDUCTED TEST EQUIPMENTS ..... 38

1.4.2 CONDUCTED EMISSION TEST EQUIPMENTS ..... 38

1.4.3 RADIATED TEST EQUIPMENTS ..... 39

1.4.4 CLIMATE CHAMBER ..... 39

1.4.5 VIBRATION TABLE ..... 39

1.4.6 ANECHOIC CHAMBER ..... 39

Change History		
Issue	Date	Reason for change
1.0	2014-11-05	First edition



### Test Report Declaration

Applicant	ZTE Corporation
Applicant Address	ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, P.R. China
Manufacturer	ZTE Corporation
Manufacturer Address	ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, P.R. China
Product Name	WCDMA Digital Mobile Phone Handset
Model Name	NX406E
Brand Name	ZTE
HW Version	NX406J
SW Version	NX406J_VE_V1.01
Test Standards	47 CFR Part 15 Subpart C
Test Date	2014-10-16 to 2014-10-30
Test Result	PASS

Tested by : Wu Jianwu  
Wu Jianwu

Reviewed by : Qiu Xiaojun  
Qiu Xiaojun

Approved by : Zeng Dexin  
Zeng Dexin



# 1. Technical Information

Note: Provide by applicant.

## 1.1. Applicant Information

Company:	ZTE Corporation
Address:	ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, P.R. China

## 1.2. Equipment under Test (EUT) Description

Brand Name:	ZTE
Trade Name:	ZTE
Model Name:	NX406E
Frequency Range:	The frequency range used is 2402MHz - 2480MHz (40 channels, at intervals of 2MHz);
Modulation Type:	GFSK
Antenna Type:	PIFA Antenna
Antenna Gain:	1.5dBi

### NOTE:

The EUT is WCDMA Digital Mobile Phone Handset, it contains Bluetooth 4.0 LE Module operating at 2.4GHz ISM band; the frequencies allocated for the Bluetooth 4.0 LE is  $F(\text{MHz})=2402+2*n$  ( $0 \leq n \leq 39$ ). The lowest, middle, highest channel numbers of the Bluetooth Module used and tested in this report are separately 0 (2402MHz), 20 (2442MHz) and 39 (2480MHz).

For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

### 1.2.1. Identification of all used EUTs

The EUT identity consists of numerical and letter characters, the letter character indicates the test sample, and the following two numerical characters indicate the software version of the test sample.

EUT Identity	Hardware Version	Software Version
A01	NX406J	NX406J_VE_V1.01



### 1.3. Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart C (Bluetooth, 2.4GHz ISM band radiators) for the EUT FCC ID Certification:

No.	Identity	Document Title
1	47 CFR Part 15 (10-1-13 Edition)	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Result
1	15.203	Antenna Requirement	<b><u>PASS</u></b>
2	15.247(b)	Peak Output Power	<b><u>PASS</u></b>
3	15.247(a)	Bandwidth	<b><u>PASS</u></b>
4	15.247(d)	Conducted Spurious Emission and Band Edge	<b><u>PASS</u></b>
5	15.247(d)	Restricted Frequency Bands	<b><u>PASS</u></b>
6	15.207	Conducted Emission	<b><u>PASS</u></b>
7	15.209 ,15.247(d)	Radiated Emission	<b><u>PASS</u></b>
8	15.247(e)	Power spectral density (PSD)	<b><u>PASS</u></b>
9	15.247(i),1.1307& 2.1093	RF exposure evaluation	<b><u>PASS</u></b>

The tests of Conducted Emission and Radiated Emission were performed according to the method of measurements prescribed in ANSI C63.4 2009.

These RF tests were performed according to the method of measurements prescribed in KDB558074 D01 v03r02 (05/06/2014).

#### 1.3.1. Test Environment Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15 - 35
Relative Humidity (%):	30 -60
Atmospheric Pressure (kPa):	86-106



## 2. 47 CFR PART 15C REQUIREMENTS

### 2.1. Antenna requirement

#### 2.1.1. Applicable Standard

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

#### 2.1.2. Result: Compliant

The EUT has a permanently and irreplaceable attached antenna. Please refer to the EUT internal photos.

### 2.2. Peak Output Power


#### 2.2.1. Requirement

According to FCC section 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum peak conducted output power of the intentional radiator shall not exceed 1 Watt.

#### 2.2.2. Test Description

The measured output power was calculated by the reading of the spectrum analyzer and calibration.

##### A. Test Setup:



The EUT (Equipment under the test) which is powered by the Battery is coupled to the Spectrum analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading, all test result in Spectrum analyzer.

**B. Equipments List:**

Please reference ANNEX A(1.4).


**2.2.3. Test Result**

The lowest, middle and highest channels are selected to perform testing to verify the conducted RF output peak power of the Module.


**A. Test Verdict:**

Channel	Frequency (MHz)	Measured Output Peak Power		Refer to Plot	Limit		Verdict
		dBm	W		dBm	W	
0	2402	-0.937	0.000806	Plot A	30	1	PASS
19	2442	-1.364	0.000730	Plot B			PASS
39	2480	-0.287	0.000940	Plot C			PASS


**B. Test Plots:**



(Plot A: Channel 0: 2402MHz)



(Plot B: Channel 19: 2442MHz)



(Plot C: Channel 39: 2480MHz)

## 2.3. Average power

### 2.3.1. Requirement

None: for reporting purposes only.

### 2.3.2. Test Description

The transmitter output is connected to a power meter.

#### A. Test Setup:



#### B. Equipments List:

Please reference ANNEX A(1.4).

### 2.3.3. Results

The cable assembly insertion loss of 1.5dB was entered as an offset in the power meter to allow for direct reading of power.

Channel	Frequency (MHz)	Average Power	
		dBm	W
0	2402	-0.71	0.000849
19	2442	-1.31	0.000740
39	2480	-1.88	0.000650


## 2.4. 6dB Bandwidth

### 2.4.1. Requirement

According to FCC section 15.247(a) (2), Systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

### 2.4.2. Test Description

#### A. Test Set:



The EUT which is powered by the Battery, is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

#### B. Equipments List:

Please reference ANNEX A(1.4).

### 2.4.3. Test Result


The lowest, middle and highest channels are selected to perform testing to record the 6 dB bandwidth of the Module.

#### A. Test Verdict:




Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Refer to Plot	Limits(kHz)	Result
0	2402	0.7308	Plot A	≥500	PASS
20	2442	0.7294	Plot B	≥500	PASS
39	2480	0.7325	Plot C	≥500	PASS


**B. Test Plots:**



(Plot A: Channel 0: 2402MHz)



(Plot B: Channel 20: 2442 MHz)



(Plot C: Channel 39: 2480MHz)


## 2.5. Conducted Spurious Emissions and Band Edge

### 2.5.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

### 2.5.2. Test Description

#### A. Test Set:



The EUT which is powered by the Battery, is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

#### B. Equipments List:

Please reference ANNEX A(1.4).

### 2.5.3. Test Result

The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions.


#### A. Test Verdict:




Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Refer to Plot	Limit (dBm)		Verdict
				Carrier Level	Calculated -20dBc Limit	
0	2402	-41.190	Plot A.1	-1.285	-21.3	PASS
20	2442	-46.570	Plot B.1	-1.380	-21.4	PASS
39	2480	-46.700	Plot C.1	-1.939	-22.0	PASS

**B. Test Plots:**


**Note:** the power of the Module transmitting frequency should be ignored.




(Plot A.1: Channel = 0, 30MHz to 25GHz)




(Band Edge@ Channel = 0)



(Plot B.1: Channel = 20, 30MHz to 25GHz)



(Plot C.1: Channel = 39, 30MHz to 25GHz)



(Band Edge@ Channel = 39)


## 2.6. Power spectral density (PSD)

### 2.6.1. Requirement

According to FCC section 15.247(e), the same method of determining the conducted output power shall be used to determine the power spectral density. If a peak output power is measured, then a peak power spectral density measurement is required. If an average output power is measured, then an average power spectral density measurement should be used.

### 2.6.2. Test Description

#### A. Test Set:



The EUT which is powered by the Battery, is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

#### B. Equipments List:

Please reference ANNEX A(1.4).

### 2.6.3. Test Result

The lowest, middle and highest channels are tested.


#### A. Test Verdict:




Spectral power density (dBm/3kHz)					
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Refer to Plot	Limit (dBm/3kHz)	Verdict
0	2402	-13.39	Plot A	8	PASS
20	2442	-13.99	Plot B	8	PASS
39	2480	-14.54	Plot C	8	PASS

Measurement uncertainty:  $\pm 1.3$ dB


**B. Test Plots:**



(Plot A: Channel = 0)



(Plot B: Channel = 20)



(Plot C: Channel = 39)


## 2.7. Restricted Frequency Bands

### 2.7.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

### 2.7.2. Test Description

#### A. Test Setup



The Module is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the



ground to determine the maximum value of the field strength.

## B. Equipments List:

Please reference ANNEX A(1.4).

## 2.7.3. Test Result

The lowest and highest channels are tested to verify the Restricted Frequency Bands.

The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V/m]} = U_R + A_T + A_{\text{Factor}} \text{ [dB]}; A_T = L_{\text{Cable loss}} \text{ [dB]} - G_{\text{preamp}} \text{ [dB]}$$

$A_T$ : Total correction Factor except Antenna

$U_R$ : Receiver Reading

$G_{\text{preamp}}$ : Pre-amplifier Gain


$A_{\text{Factor}}$ : Antenna Factor at 3m

Note: Restricted Frequency Bands were performed when antenna was at vertical and horizontal polarity, and only the worse test condition (vertical) was recorded in this test report.


## A. Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading UR (dBuV)	AT (dB)	AFactor (dB@3m)	Max. Emission E (dBuV/m)	Limit (dBuV/m)	Verdict
		PK/ AV						
0	2353.04	PK	47.23	-33.63	32.56	47.02	74	Pass
0	2353.56	AV	35.00	-33.63	32.56	35.89	54	Pass
39	2485.76	PK	48.89	-33.18	32.50	49.00	74	Pass
39	2483.50	AV	36.18	-33.18	32.50	37.70	54	Pass


## B. Test Plots:




(Plot A1: Channel = 0 PEAK)



(Plot A2: Channel = 0 AVG)



(Plot B1: Channel = 20 PEAK)



(Plot B2: Channel = 39 AVG)



## 2.8. Conducted Emission

### 2.8.1. Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 $\mu$ H/50 $\Omega$  line impedance stabilization network (LISN).


Frequency range (MHz)	Conducted Limit (dB $\mu$ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

NOTE:

- (a) The lower limit shall apply at the band edges.
- (b) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

### 2.8.2. Test Description

#### A. Test Setup:



The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.4:2009

### B. Equipments List:

Please reference ANNEX A(1.4).


## 2.8.3. Test Result

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.


### A. Test setup:

The EUT configuration of the emission tests is EUT + Link.

### B. Test Plots:



(Plot A: L Phase)



(Plot B: N Phase)



## 2.9. Radiated Emission

### 2.9.1. Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ( $\mu\text{V}/\text{m}$ )	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:


1. For Above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
2. For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK)

In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table)


### 2.9.2. Test Description

#### A. Test Setup:


- 1) For radiated emissions from 9kHz to 30MHz



2) For radiated emissions from 30MHz to 1GHz



## 3) For radiated emissions above 1GHz



The test site semi-anechoic chamber has met the requirement of NSA tolerance 4dB according to the standards: ANSI C63.4 (2009). The EUT was set-up on insulator 80cm above the Ground Plane. The set-up and test methods were according to ANSI C63.4.

The EUT of the EUT is powered by the Battery charged with the AC Adapter which is powered by 120V, 60Hz AC mains supply. The Module is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading. During the measurement, the EUT is activated and controlled by the Wireless Router via a Common Antenna, and is set to operate under hopping-on test mode.

For the Test Antenna:

- In the frequency range of 9kHz to 30MHz, magnetic field is measured with Loop Test Antenna. The Test Antenna is positioned with its plane vertical at 1m distance from the EUT. The center of the Loop Test Antenna is 1m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.
- In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 2GHz) and Horn Test Antenna (above 2GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. The emission levels at both horizontal and vertical polarizations should be tested.



## B. Equipments List:

Please reference ANNEX A(1.4).

## 2.9.3. Test Result

According to ANSI C63.4 selection 4.2.2, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak limit, it is unnecessary to perform an quasi-peak measurement.

The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V/m]} = U_R + A_T + A_{\text{Factor}} \text{ [dB]}; A_T = L_{\text{Cable loss}} \text{ [dB]} - G_{\text{preamp}} \text{ [dB]}$$

$A_T$ : Total correction Factor except Antenna

$U_R$ : Receiver Reading

$G_{\text{preamp}}$ : Preamplifier Gain

$A_{\text{Factor}}$ : Antenna Factor at 3m


During the test, the total correction Factor  $A_T$  and  $A_{\text{Factor}}$  were built in test software.

**Note:** All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

The low frequency, which started from 9KHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.


## A. Test Plots for the Whole Measurement Frequency Range:

Plots for Channel = 0



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
39.676	30.99	N.A	N.A	N.A	40.0	N.A	Horizontal	PASS
88.055	22.73	N.A	N.A	N.A	43.5	N.A	Horizontal	PASS
436.384	26.92	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2402.000	51.34	N.A	N.A	N.A	N.A	N.A	Horizontal	N.A
7004.988	43.27	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
16825.436	47.18	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
39.676	27.26	N.A	N.A	N.A	40.0	N.A	Vertical	PASS
56.608	19.61	N.A	N.A	N.A	40.0	N.A	Vertical	PASS
479.925	23.88	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2402.000	51.31	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
7334.165	44.28	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
12985.037	47.63	N.A	N.A	74.0	N.A	54.0	Vertical	PASS


(Antenna Vertical, 30MHz to 25GHz)



Plot for Channel = 20




(Antenna Horizontal, 30MHz to 25GHz)




(Antenna Vertical, 30MHz to 25GHz)



Plot for Channel = 39



(Antenna Horizontal, 30MHz to 25GHz)



(Antenna Vertical, 30MHz to 25GHz)



## 2.10. RF exposure evaluation

### 2.10.1. Requirement

According to § 1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of Commission's guideline.

### 2.10.2. Result

Please refer to SAR report.



## Annex A General Information

### 1.1 Identification of the Responsible Testing Laboratory

Company Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Department:	Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Responsible Test Lab Manager:	Mr. Su Feng
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

### 1.2 Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

### 1.3 Facilities and Accreditations

Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L3572.

All measurement facilities used to collect the measurement data are located at FL.1, Building A, FeiYang Science Park, Block 67, BaoAn District, Shenzhen, 518101 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.10 2009, ANSI C63.4 2009 and CISPR Publication 22; the FCC registration number is 695796.

The IC registration number is 7183A-2.



## 1.4 Test Equipments Utilized

### 1.4.1 Conducted Test Equipments

No.	Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal. Due
1	Spectrum Analyzer	MY45101810	E4407B	Agilent	2014.02.26	2015.02.25
2	Power Splitter	NW521	1506A	Weinschel	2014.02.26	2015.02.25
3	Attenuator 1	(n.a.)	10dB	Resnet	2014.02.26	2015.02.25
4	Attenuator 2	(n.a.)	3dB	Resnet	2014.02.26	2015.02.25
5	USB Wideband Power Sensor	MY52280010	U2021XA	Agilent	2014.02.26	2015.02.25
6	EXA Signal Analyzer	MY51440152	N9010A	Agilent	2014.02.26	2015.02.25
7	RF cable	CB01	RF01	Morlab	N/A	N/A
8	Coaxial cable	CB02	RF02	Morlab	N/A	N/A
9	SMA connector	CN01	RF03	HUBER-SUHNER	N/A	N/A

### 1.4.2 Conducted Emission Test Equipments

No.	Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal. Due
1	Receiver	US44210471	E7405A	Agilent	2014.02.26	2015.02.25
2	LISN	812744	NSLK 8127	Schwarzbeck	2014.02.26	2015.02.25
3	Service Supplier	100448	CMU200	R&S	2014.02.26	2015.02.25
4	Pulse Limiter (20dB)	9391	VTSD 9561-D	Schwarzbeck	2014.02.26	2015.02.25
5	Coaxial cable(BNC)	CB01	EMC01	Morlab	N/A	N/A



### 1.4.3 Radiated Test Equipments

No.	Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal.Due Date
1	Receiver	US44210471	E7405A	Agilent	2014.02.26	2015.02.25
2	Test Antenna - Bi-Log	9163-274	9m*6m*6m	Albatross	2014.02.26	2015.02.25
3	Test Antenna - Horn	9120D-963	VULB 9163	Schwarzbeck	2014.02.26	2015.02.25
4	Test Antenna - Horn	71688	BBHA 9120D	Schwarzbeck	2014.02.26	2015.02.25
5	Test Antenna - Loop	1519-022	HL050S7	R&S	2014.02.26	2015.02.25
6	Reject Filter	(n.a.)	BRM50702	Micro-Tronics	2014.02.26	2015.02.25
7	Coaxial cable (N male)	CB02	EMC02	Morlab	N/A	N/A
8	Coaxial cable (N male)	CB03	EMC03	Morlab	N/A	N/A

### 1.4.4 Climate Chamber

No.	Equipment Name	Serial No.	Type	Manufacturer	Cal.Date	Cal.Due Date
1	Climate Chamber	2004012	HL4003T	Yinhe	2014.02.26	2015.02.25

### 1.4.5 Vibration Table

No.	Equipment Name	Serial No.	Type	Manufacturer	Cal.Date	Cal.Due Date
1	Vibration Table	N/A	ACT2000- S015L	CMI-COM	2014.02.26	2015.02.25

### 1.4.6 Anechoic Chamber

No.	Equipment Name	Serial No.	Type	Manufacturer	Cal.Date	Cal.Due Date
1	Anechoic Chamber	N/A	9m*6m*6m	Albatross	2014.02.26	2015.02.25

\*\*\*\*\* END OF REPORT \*\*\*\*\*