



Test Report No.: SA170123W004



RF EXPOSURE REPORT

Product: Industry Wireless Router

Model Name: R800

FCC ID: SRQ-R800

Applicant: ZTE Corporation

Address: ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park,
Nanshan District, Shenzhen, Guangdong, P.R.China

Manufacturer: ZTE Corporation

Address: ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park,
Nanshan District, Shenzhen, Guangdong, P.R.China

Prepared by: Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch

Lab Location: No. 34, Chenwulu Section, Guantai Rd., Houjie Town,
Dongguan City, Guangdong 523942, China

TEL: +86 769 8593 5656

FAX: +86 769 8593 1080

E-MAIL: customerservice.dg@cn.bureauveritas.com

Report No.: SA170123W004

Received Date: Jan. 23, 2017

Test Date: Feb. 08, 2017 ~ Mar. 06, 2017

Issued Date: Mar. 08, 2017

This report should not be used by the client to claim product certification, approval, or endorsement by A2LA or any government agencies.

Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie
Town, Dongguan City,
Guangdong 523942, China

Tel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com



TABLE OF CONTENTS

RF EXPOSURE REPORT.....	1
RELEASE CONTROL RECORD	3
1 CERTIFICATION	4
2 GENERAL INFORMATION	5
2.1 GENERAL DESCRIPTION OF EUT	5
3 RF EXPOSURE	7
3.1 LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)	7
3.2 MPE CALCULATION FORMULA	7
3.3 CLASSIFICATION	7
3.4 CONDUCTED POWER	8
3.5 CALCULATION RESULT OF MAXIMUM CONDUCTED POWER.....	21
3.6 CONCLUSION OF SIMULTANEOUS TRANSMITTER	22



BUREAU
VERITAS

Test Report No.: SA170123W004

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
SA170123W004	Original release	Mar. 08, 2017

Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie
Town, Dongguan City,
Guangdong 523942, China

Tel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com



1 CERTIFICATION

PRODUCT: Industry Wireless Router
BRAND NAME: ZTE
MODEL NAME: R800
APPLICANT: ZTE Corporation
TESTED: Feb. 08, 2017 ~ Mar. 06, 2017
TEST SAMPLE: Identical Prototype
STANDARDS: **FCC Part 2 (Section 2.1091)**
FCC OET Bulletin 65, Supplement C (01-01)
KDB 447498 D01 General RF Exposure Guidance v06
IEEE C95.1

The above equipment has been tested by **Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch** and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Harry , **DATE:** Mar. 08, 2017
(Harry Li/ Engineer)

APPROVED BY : Sam Tung , **DATE:** Mar. 08, 2017
(Sam Tung / Manager)



2 GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Industry Wireless Router	
MODEL NAME	R800	
NOMINAL VOLTAGE	12Vdc (from adapter)	
OPERATING TEMPERATURE RANGE	-20 ~ 60°C	
MODULATION TYPE	WLAN	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
	WCDMA	BPSK/QPSK
	LTE	QPSK, 16QAM
OPERATING FREQUENCY	WIFI 2.4G	2412~ 2462MHz for 11b/g/n(HT20) 2422~ 2452MHz for 11b/g/n(HT40)
	WCDMA	1852.4MHz ~ 1907.6MHz (FOR WCDMA 1900) 826.4MHz ~ 846.6MHz (FOR WCDMA 850)
	LTE	1850.7MHz ~ 1909.3MHz (FOR LTE Band2) 1710.7MHz ~ 1754.3MHz (FOR LTE Band4) 824.7MHz ~ 848.3MHz (FOR LTE Band5) 699.7MHz ~ 715.3MHz (FOR LTE Band12) 706.5MHz ~ 713.5MHz (FOR LTE Band17)
ANTENNA GAIN	WLAN 2.4G	External Antenna with 3.1dBi gain
	WCDMA 850	Fixed External Antenna with 0.57dBi gain
	WCDMA 1900	Fixed External Antenna with 1.5dBi gain
	LTE Band 2	Fixed External Antenna with 1.5dBi gain
	LTE Band 4	Fixed External Antenna with 1.5dBi gain
	LTE Band 5	Fixed External Antenna with 0.57dBi gain
	LTE Band 12	Fixed External Antenna with 0.91dBi gain
LTE Band 17	Fixed External Antenna with 0.91dBi gain	
HW VERSION	R800X-V1.1	
SW VERSION	V1.8.8	
I/O PORTS	Refer to user's manual	
CABLE SUPPLIED	N/A	

NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.



2. The EUT was powered by the following adapter:

ADAPTER	
BRAND:	ZTE
MODEL:	MAU-120100X-D-16
INPUT:	AC 100-240V, 700mA
OUTPUT:	DC 12V, 1000mA

3. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.



3 RF EXPOSURE

3.1 LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm ²)	AVERAGE TIME (minutes)
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz

3.2 MPE CALCULATION FORMULA

$$Pd = (Pout * G) / (4 * pi * r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

3.3 CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.



3.4 CONDUCTED POWER

WIFI 2.4G

802.11b

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
1	2412	15.56	N/A
6	2437	15.49	N/A
11	2462	15.31	N/A

802.11g

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
1	2412	15.22	N/A
6	2437	15.11	N/A
11	2462	15.04	N/A

802.11n (20MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
1	2412	11.11	N/A
6	2437	10.56	N/A
11	2462	10.03	N/A

802.11n (40MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
3	2422	11.42	N/A
6	2437	11.01	N/A
9	2452	10.57	N/A



Band	WCDMA II		
Channel	9262	9400	9538
Frequency (MHz)	1852.4	1880.0	1907.6
RMC 12.2K	21.63	21.55	21.35
HSPA			
HSDPA Subtest-1	20.80	20.72	20.52
HSDPA Subtest-2	20.77	20.69	20.49
HSDPA Subtest-3	20.27	20.19	19.99
HSDPA Subtest-4	20.23	20.15	19.95
HSUPA Subtest-1	20.35	20.27	20.07
HSUPA Subtest-2	18.41	18.33	18.13
HSUPA Subtest-3	19.37	19.29	19.09
HSUPA Subtest-4	18.39	18.31	18.11
HSUPA Subtest-5	20.29	20.21	20.01

Band	WCDMA V		
Channel	4132	4182	4233
Frequency (MHz)	826.4	836.4	846.6
RMC 12.2K	23.15	22.85	22.67
HSPA			
HSDPA Subtest-1	22.25	21.95	21.77
HSDPA Subtest-2	22.21	21.91	21.73
HSDPA Subtest-3	21.70	21.40	21.22
HSDPA Subtest-4	21.66	21.36	21.18
HSUPA Subtest-1	22.34	22.04	21.86
HSUPA Subtest-2	20.31	20.01	19.83
HSUPA Subtest-3	21.41	21.11	20.93
HSUPA Subtest-4	20.38	20.08	19.90
HSUPA Subtest-5	22.31	22.01	21.83



LTE BAND 2

LTE Band 2							
BW	Modulation	RB Size	RB Offset	Low CH 18607	Mid CH 18900	High CH 19193	3GPP MPR (dB)
				Frequency 1850.7 MHz	Frequency 1880 MHz	Frequency 1909.3 MHz	
1.4MHz	QPSK	1	0	21.26	21.51	21.23	0
		1	2	21.16	21.41	21.13	0
		1	5	21.09	21.34	21.06	0
		3	0	21.25	21.50	21.22	0
		3	1	21.15	21.40	21.12	0
		3	3	21.08	21.33	21.05	0
	16QAM	6	0	20.33	20.58	20.30	1
		1	0	20.21	20.46	20.18	1
		1	2	20.13	20.38	20.10	1
		1	5	20.07	20.32	20.04	1
		3	0	20.19	20.44	20.16	1
		3	1	20.11	20.36	20.08	1
		3	3	20.05	20.30	20.02	1
		6	0	19.44	19.69	19.41	2
BW	Modulation	RB Size	RB Offset	Low CH 18615	Mid CH 18900	High CH 19185	3GPP MPR (dB)
				Frequency 1851.5 MHz	Frequency 1880 MHz	Frequency 1908.5 MHz	
3 MHz	QPSK	1	0	21.29	21.54	21.26	0
		1	7	21.19	21.44	21.16	0
		1	14	21.12	21.37	21.09	0
		8	0	20.40	20.65	20.37	1
		8	3	20.33	20.58	20.30	1
		8	7	20.26	20.51	20.23	1
		15	0	20.36	20.61	20.33	1
	16QAM	1	0	20.24	20.49	20.21	1
		1	7	20.16	20.41	20.13	1
		1	14	20.10	20.35	20.07	1
		8	0	19.47	19.72	19.44	2
		8	3	19.42	19.67	19.39	2
		8	7	19.36	19.61	19.33	2
		15	0	19.47	19.72	19.44	2



LTE Band 2							
BW	Modulation	RB Size	RB Offset	Low CH 18625	Mid CH 18900	High CH 19175	3GPP MPR (dB)
				Frequency 1852.5 MHz	Frequency 1880 MHz	Frequency 1907.5 MHz	
5 MHz	QPSK	1	0	21.32	21.57	21.29	0
		1	12	21.22	21.47	21.19	0
		1	24	21.15	21.40	21.12	0
		12	0	20.43	20.68	20.40	1
		12	6	20.36	20.61	20.33	1
		12	13	20.29	20.54	20.26	1
		25	0	20.39	20.64	20.36	1
	16QAM	1	0	20.27	20.52	20.24	1
		1	12	20.19	20.44	20.16	1
		1	24	20.13	20.38	20.10	1
		12	0	19.50	19.75	19.47	2
		12	6	19.45	19.70	19.42	2
		12	13	19.39	19.64	19.36	2
		25	0	19.50	19.75	19.47	2
BW	Modulation	RB Size	RB Offset	Low CH 18650	Mid CH 18900	High CH 19150	3GPP MPR (dB)
				Frequency 1855 MHz	Frequency 1880 MHz	Frequency 1905 MHz	
10 MHz	QPSK	1	0	21.34	21.59	21.31	0
		1	24	21.24	21.49	21.21	0
		1	49	21.17	21.42	21.14	0
		25	0	20.45	20.70	20.42	1
		25	12	20.38	20.63	20.35	1
		25	25	20.31	20.56	20.28	1
		50	0	20.41	20.66	20.38	1
	16QAM	1	0	20.29	20.54	20.26	1
		1	24	20.21	20.46	20.18	1
		1	49	20.15	20.40	20.12	1
		25	0	19.52	19.77	19.49	2
		25	12	19.47	19.72	19.44	2
		25	25	19.41	19.66	19.38	2
		50	0	19.52	19.77	19.49	2



LTE Band 2							
BW	Modulation	RB Size	RB Offset	Low CH	Mid CH	High CH	3GPP MPR (dB)
				18675	18900	19125	
				Frequency	Frequency	Frequency	
				1857.5 MHz	1880 MHz	1902.5 MHz	
15 MHz	QPSK	1	0	21.37	21.62	21.34	0
		1	37	21.27	21.52	21.24	0
		1	74	21.20	21.45	21.17	0
		36	0	20.48	20.73	20.45	1
		36	19	20.41	20.66	20.38	1
		36	39	20.34	20.59	20.31	1
		75	0	20.44	20.69	20.41	1
	16QAM	1	0	20.32	20.57	20.29	1
		1	37	20.24	20.49	20.21	1
		1	74	20.18	20.43	20.15	1
		36	0	19.55	19.80	19.52	2
		36	19	19.50	19.75	19.47	2
		36	39	19.44	19.69	19.41	2
		75	0	19.55	19.80	19.52	2
BW	Modulation	RB Size	RB Offset	Low CH	Mid CH	High CH	3GPP MPR (dB)
				18700	18900	19100	
				Frequency	Frequency	Frequency	
				1860 MHz	1880 MHz	1900 MHz	
20MHz	QPSK	1	0	21.42	21.67	21.39	0
		1	50	21.32	21.57	21.29	0
		1	99	21.25	21.50	21.22	0
		50	0	20.53	20.78	20.50	1
		50	25	20.46	20.71	20.43	1
		50	50	20.39	20.64	20.36	1
		100	0	20.49	20.74	20.46	1
	16QAM	1	0	20.37	20.62	20.34	1
		1	50	20.29	20.54	20.26	1
		1	99	20.23	20.48	20.20	1
		50	0	19.60	19.85	19.57	2
		50	25	19.55	19.80	19.52	2
		50	50	19.49	19.74	19.46	2
		100	0	19.60	19.85	19.57	2



LTE BAND 4

LTE Band 4							
BW	Modulation	RB Size	RB Offset	Low CH 19957	Mid CH 20175	High CH 20393	MPR
				Frequency 1710.7 MHz	Frequency 1732.5 MHz	Frequency 1754.3 MHz	
1.4MHz	QPSK	1	0	20.55	20.62	20.64	0
		1	2	20.49	20.56	20.58	0
		1	5	20.44	20.51	20.53	0
		3	0	20.53	20.60	20.62	0
		3	1	20.47	20.54	20.56	0
		3	3	20.42	20.49	20.51	0
		6	0	19.43	19.50	19.52	1
	16QAM	1	0	19.45	19.52	19.54	1
		1	2	19.40	19.47	19.49	1
		1	5	19.35	19.42	19.44	1
		3	0	19.44	19.51	19.53	1
		3	1	19.39	19.46	19.48	1
		3	3	19.34	19.41	19.43	1
		6	0	18.30	18.37	18.39	2
BW	Modulation	RB Size	RB Offset	Low CH 19965	Mid CH 20175	High CH 20385	MPR
				Frequency 1711.5 MHz	Frequency 1732.5 MHz	Frequency 1753.5 MHz	
3 MHz	QPSK	1	0	20.56	20.63	20.65	0
		1	7	20.50	20.57	20.59	0
		1	14	20.45	20.52	20.54	0
		8	0	19.51	19.58	19.60	1
		8	3	19.42	19.49	19.51	1
		8	7	19.38	19.45	19.47	1
		15	0	19.44	19.51	19.53	1
	16QAM	1	0	19.46	19.53	19.55	1
		1	7	19.41	19.48	19.50	1
		1	14	19.36	19.43	19.45	1
		8	0	18.53	18.60	18.62	2
		8	3	18.48	18.55	18.57	2
		8	7	18.42	18.49	18.51	2
		15	0	18.31	18.38	18.40	2



LTE Band 4							
BW	Modulation	RB Size	RB Offset	Low CH 19975	Mid CH 20175	High CH 20375	MPR
				Frequency 1712.5 MHz	Frequency 1732.5 MHz	Frequency 1752.5 MHz	
5 MHz	QPSK	1	0	20.59	20.66	20.68	0
		1	12	20.53	20.60	20.62	0
		1	24	20.48	20.55	20.57	0
		12	0	19.54	19.61	19.63	1
		12	6	19.45	19.52	19.54	1
		12	13	19.41	19.48	19.50	1
		25	0	19.47	19.54	19.56	1
	16QAM	1	0	19.49	19.56	19.58	1
		1	12	19.44	19.51	19.53	1
		1	24	19.39	19.46	19.48	1
		12	0	18.56	18.63	18.65	2
		12	6	18.51	18.58	18.60	2
		12	13	18.45	18.52	18.54	2
		25	0	18.34	18.41	18.43	2
BW	Modulation	RB Size	RB Offset	Low CH 20000	Mid CH 20175	High CH 20350	MPR
				Frequency 1715 MHz	Frequency 1732.5 MHz	Frequency 1750 MHz	
10 MHz	QPSK	1	0	20.63	20.70	20.72	0
		1	24	20.57	20.64	20.66	0
		1	49	20.52	20.59	20.61	0
		25	0	19.58	19.65	19.67	1
		25	12	19.49	19.56	19.58	1
		25	25	19.45	19.52	19.54	1
		50	0	19.51	19.58	19.60	1
	16QAM	1	0	19.53	19.60	19.62	1
		1	24	19.48	19.55	19.57	1
		1	49	19.43	19.50	19.52	1
		25	0	18.60	18.67	18.69	2
		25	12	18.55	18.62	18.64	2
		25	25	18.49	18.56	18.58	2
		50	0	18.38	18.45	18.47	2



LTE Band 4							
BW	Modulation	RB Size	RB Offset	Low CH 20025	Mid CH 20175	High CH 20325	MPR
				Frequency 1717.5 MHz	Frequency 1732.5 MHz	Frequency 1747.5 MHz	
15 MHz	QPSK	1	0	20.69	20.76	20.78	0
		1	37	20.63	20.70	20.72	0
		1	74	20.58	20.65	20.67	0
		36	0	19.64	19.71	19.73	1
		36	19	19.55	19.62	19.64	1
		36	39	19.51	19.58	19.60	1
		75	0	19.57	19.64	19.66	1
	16QAM	1	0	19.59	19.66	19.68	1
		1	37	19.54	19.61	19.63	1
		1	74	19.49	19.56	19.58	1
		36	0	18.66	18.73	18.75	2
		36	19	18.61	18.68	18.70	2
		36	39	18.55	18.62	18.64	2
		75	0	18.44	18.51	18.53	2
BW	Modulation	RB Size	RB Offset	Low CH 20050	Mid CH 20175	High CH 20300	MPR
				Frequency 1720 MHz	Frequency 1732.5 MHz	Frequency 1745 MHz	
20MHz	QPSK	1	0	20.72	20.79	20.81	0
		1	50	20.66	20.73	20.75	0
		1	99	20.61	20.68	20.70	0
		50	0	19.67	19.74	19.76	1
		50	25	19.58	19.65	19.67	1
		50	50	19.54	19.61	19.63	1
		100	0	19.60	19.67	19.69	1
	16QAM	1	0	19.62	19.69	19.71	1
		1	50	19.57	19.64	19.66	1
		1	99	19.52	19.59	19.61	1
		50	0	18.69	18.76	18.78	2
		50	25	18.64	18.71	18.73	2
		50	50	18.58	18.65	18.67	2
		100	0	18.47	18.54	18.56	2



LTE BAND 5

Band/BW	Modulation	RB Size	RB Offset	Low CH 20407	Mid CH 20525	High CH 20643	3GPP MPR (dB)
				Frequency 824.7 MHz	Frequency 836.5 MHz	Frequency 848.3 MHz	
5/1.4	QPSK	1	0	21.48	21.59	21.53	0
		1	2	21.41	21.52	21.46	0
		1	5	21.36	21.47	21.41	0
		3	0	21.46	21.57	21.51	0
		3	1	21.39	21.50	21.44	0
		3	3	21.34	21.45	21.39	0
	16QAM	6	0	20.40	20.51	20.45	1
		1	0	20.52	20.63	20.57	1
		1	2	20.46	20.57	20.51	1
		1	5	20.40	20.51	20.45	1
		3	0	20.51	20.62	20.56	1
		3	1	20.45	20.56	20.50	1
		3	3	20.39	20.50	20.44	1
		6	0	19.41	19.52	19.46	2
Band/BW	Modulation	RB Size	RB Offset	Low CH 20415	Mid CH 20525	High CH 20635	3GPP MPR (dB)
				Frequency 825.5 MHz	Frequency 836.5 MHz	Frequency 847.5 MHz	
5/3	QPSK	1	0	21.52	21.63	21.57	0
		1	7	21.45	21.56	21.50	0
		1	14	21.40	21.51	21.45	0
		8	0	20.78	20.89	20.83	1
		8	3	20.74	20.85	20.79	1
		8	7	20.67	20.78	20.72	1
		15	0	20.44	20.55	20.49	1
	16QAM	1	0	20.56	20.67	20.61	1
		1	7	20.50	20.61	20.55	1
		1	14	20.44	20.55	20.49	1
		8	0	19.39	19.50	19.44	2
		8	3	19.34	19.45	19.39	2
		8	7	19.30	19.41	19.35	2
		15	0	19.45	19.56	19.50	2



Band/BW	Modulation	RB Size	RB Offset	Low CH 20425	Mid CH 20525	High CH 20625	3GPP MPR (dB)
				Frequency 826.5 MHz	Frequency 836.5 MHz	Frequency 846.5 MHz	
5/5	QPSK	1	0	21.58	21.69	21.63	0
		1	12	21.51	21.62	21.56	0
		1	24	21.46	21.57	21.51	0
		12	0	20.84	20.95	20.89	1
		12	6	20.80	20.91	20.85	1
		12	13	20.73	20.84	20.78	1
		25	0	20.50	20.61	20.55	1
	16QAM	1	0	20.62	20.73	20.67	1
		1	12	20.56	20.67	20.61	1
		1	24	20.50	20.61	20.55	1
		12	0	19.45	19.56	19.50	2
		12	6	19.40	19.51	19.45	2
		12	13	19.36	19.47	19.41	2
		25	0	19.51	19.62	19.56	2
Band/BW	Modulation	RB Size	RB Offset	Low CH 20450	Mid CH 20525	High CH 20600	3GPP MPR (dB)
				Frequency 829 MHz	Frequency 836.5 MHz	Frequency 844 MHz	
5/10	QPSK	1	0	21.61	21.72	21.66	0
		1	24	21.54	21.65	21.59	0
		1	49	21.49	21.60	21.54	0
		25	0	20.87	20.98	20.92	1
		25	12	20.83	20.94	20.88	1
		25	25	20.76	20.87	20.81	1
		50	0	20.53	20.64	20.58	1
	16QAM	1	0	20.65	20.76	20.70	1
		1	24	20.59	20.70	20.64	1
		1	49	20.53	20.64	20.58	1
		25	0	19.48	19.59	19.53	2
		25	12	19.43	19.54	19.48	2
		25	25	19.39	19.50	19.44	2
		50	0	19.54	19.65	19.59	2



LTE BAND 12

LTE Band 12							
BW	Modulation	RB Size	RB Offset	Low CH 23017	Mid CH 23095	High CH 23173	MPR
				Frequency 699.7 MHz	Frequency 707.5 MHz	Frequency 715.3 MHz	
1.4 MHz	QPSK	1	0	23.38	23.41	23.45	0
		1	2	23.33	23.36	23.40	0
		1	5	23.27	23.30	23.34	0
		3	0	23.36	23.39	23.43	0
		3	1	23.31	23.34	23.38	0
		3	3	23.25	23.28	23.32	0
		6	0	22.64	22.67	22.71	1
	16QAM	1	0	22.43	22.46	22.50	1
		1	2	22.36	22.39	22.43	1
		1	5	22.31	22.34	22.38	1
		3	0	22.42	22.45	22.49	1
		3	1	22.35	22.38	22.42	1
		3	3	22.30	22.33	22.37	1
		6	0	21.64	21.67	21.71	2
BW	Modulation	RB Size	RB Offset	Low CH 23025	Mid CH 23095	High CH 23165	MPR
				Frequency 700.5 MHz	Frequency 707.5 MHz	Frequency 714.5 MHz	
3 MHz	QPSK	1	0	23.42	23.45	23.49	0
		1	7	23.37	23.40	23.44	0
		1	14	23.31	23.34	23.38	0
		8	0	22.68	22.71	22.75	1
		8	3	22.62	22.65	22.69	1
		8	7	22.57	22.60	22.64	1
		15	0	22.68	22.71	22.75	1
	16QAM	1	0	22.47	22.50	22.54	1
		1	7	22.40	22.43	22.47	1
		1	14	22.35	22.38	22.42	1
		8	0	21.53	21.56	21.60	2
		8	3	21.49	21.52	21.56	2
		8	7	21.45	21.48	21.52	2
		15	0	21.68	21.71	21.75	2



LTE Band 12							
BW	Modulation	RB Size	RB Offset	Low CH 23035	Mid CH 23095	High CH 23155	MPR
				Frequency 701.5 MHz	Frequency 707.5 MHz	Frequency 713.5 MHz	
5 MHz	QPSK	1	0	23.48	23.51	23.55	0
		1	12	23.43	23.46	23.50	0
		1	24	23.37	23.40	23.44	0
		12	0	22.74	22.77	22.81	1
		12	6	22.68	22.71	22.75	1
		12	13	22.63	22.66	22.70	1
		25	0	22.74	22.77	22.81	1
	16QAM	1	0	22.53	22.56	22.60	1
		1	12	22.46	22.49	22.53	1
		1	24	22.41	22.44	22.48	1
		12	0	21.59	21.62	21.66	2
		12	6	21.55	21.58	21.62	2
		12	13	21.51	21.54	21.58	2
		25	0	21.74	21.77	21.81	2
BW	Modulation	RB Size	RB Offset	Low CH 23060	Mid CH 23095	High CH 23130	MPR
				Frequency 704 MHz	Frequency 707.5 MHz	Frequency 711 MHz	
10 MHz	QPSK	1	0	23.51	23.54	23.58	0
		1	24	23.46	23.49	23.53	0
		1	49	23.40	23.43	23.47	0
		25	0	22.77	22.80	22.84	1
		25	12	22.71	22.74	22.78	1
		25	25	22.66	22.69	22.73	1
		50	0	22.77	22.80	22.84	1
	16QAM	1	0	22.56	22.59	22.63	1
		1	24	22.49	22.52	22.56	1
		1	49	22.44	22.47	22.51	1
		25	0	21.62	21.65	21.69	2
		25	12	21.58	21.61	21.65	2
		25	25	21.54	21.57	21.61	2
		50	0	21.77	21.80	21.84	2



LTE BAND 17

LTE Band 17							
BW	Modulation	RB Size	RB Offset	Low CH 23755	Mid CH 23790	High CH 23825	MPR
				Frequency 706.5 MHz	Frequency 710 MHz	Frequency 713.5 MHz	
5 MHz	QPSK	1	0	23.23	23.33	23.25	0
		1	12	23.17	23.27	23.19	0
		1	24	23.12	23.22	23.14	0
		12	0	22.21	22.31	22.23	1
		12	6	22.17	22.27	22.19	1
		12	13	22.12	22.22	22.14	1
		25	0	22.14	22.24	22.16	1
	16QAM	1	0	22.17	22.27	22.19	1
		1	12	22.12	22.22	22.14	1
		1	24	22.05	22.15	22.07	1
		12	0	21.24	21.34	21.26	2
		12	6	21.18	21.28	21.20	2
		12	13	21.13	21.23	21.15	2
		25	0	21.17	21.27	21.19	2
BW	Modulation	RB Size	RB Offset	Low CH 23780	Mid CH 23790	High CH 23800	MPR
				Frequency 709 MHz	Frequency 710 MHz	Frequency 711 MHz	
10 MHz	QPSK	1	0	23.27	23.37	23.29	0
		1	24	23.21	23.31	23.23	0
		1	49	23.16	23.26	23.18	0
		25	0	22.25	22.35	22.27	1
		25	12	22.21	22.31	22.23	1
		25	25	22.16	22.26	22.18	1
		50	0	22.18	22.28	22.20	1
	16QAM	1	0	22.21	22.31	22.23	1
		1	24	22.16	22.26	22.18	1
		1	49	22.09	22.19	22.11	1
		25	0	21.28	21.38	21.30	2
		25	12	21.22	21.32	21.24	2
		25	25	21.17	21.27	21.19	2
		50	0	21.21	21.31	21.23	2



3.5 CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

WIFI

Band	Frequency (MHz)	Antenna Gain (dBi)	Conducted Time Average Power (dBm)	E.I.R.P Power (mW)	Power Density (mW/cm ²)	limit (mW/cm ²)	PASS / FAIL
WIFI 2.4G	2412	3.1	15.56	73.451	0.015	1.00	PASS

WCDMA

Band	Frequency (MHz)	Operating Mode	Antenna Gain (dBi)	Conducted Time Average Power (dBm)	E.I.R.P Power (mW)	Power Density (mW/cm ²)	limit (mW/cm ²)	PASS / FAIL
WCDMA II	1852.4	RMC12.2K	1.5	21.63	205.589	0.041	1.00	PASS
WCDMA V	826.4	RMC12.2K	0.57	23.15	235.505	0.047	0.55	PASS

LTE

Band	Frequency (MHz)	Operating Mode	Antenna Gain (dBi)	Conducted Time Average Power (dBm)	E.I.R.P Power (mW)	Power Density (mW/cm ²)	limit (mW/cm ²)	PASS / FAIL
Band2	1880	QPSK	1.5	21.67	207.491	0.041	1.00	PASS
Band4	1745	QPSK	1.5	20.81	170.216	0.034	1.00	PASS
Band5	836.5	QPSK	0.57	21.72	169.434	0.034	0.56	PASS
Band12	711	QPSK	0.91	23.58	281.190	0.056	0.47	PASS
Band17	710	QPSK	0.91	23.37	267.917	0.053	0.47	PASS



3.6 CONCLUSION OF SIMULTANEOUS TRANSMITTER

Both of the WLAN and plug-in device can transmit simultaneously, the formula of calculated the MPE is:

$$\text{CPD1/LPD1} + \text{CPD2/LPD2} + \dots \text{etc.} < 1$$

CPD = Calculation power density

LPD = Limit of power density

Therefore the worst-case situation is

$0.015/1.00 + 0.041/1.00 + 0.047/0.55 + 0.041/1.00 + 0.034/1.00 + 0.034/0.56 + 0.056/0.47 + 0.053/0.47 = 0.509084$, which is less than "1", This confirmed that the device comply with FCC 1.1310 MPE limit.

--END--