



BUREAU
VERITAS

Test Report No.: RF150420N007-1



FCC TEST REPORT (WIFI)

Product: Automotive Multi-function MiFi Terminal
Model Name: VM6200
FCC ID: SRQ-VM6200
Applicant: ZTE Corporation
Address: ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park,
Nanshan District, Shenzhen, Guangdong, P.R. China
Manufacturer: ZTE Corporation
Address: ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park,
Nanshan District, Shenzhen, Guangdong, P.R. China
Prepared by: Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch
Lab Location: No. 34, Chenwulu Section, Guantai Rd., Houjie Town,
Dongguan City, Guangdong 523942, China
TEL: +86 769 8593 5656
FAX: +86 769 8593 1080
E-MAIL: customerservice.dg@cn.bureauveritas.com
Report No.: RF150420N007-1
Received Date: Apr. 20, 2015
Test Date: Apr. 21, 2015 ~ May 28, 2015
Issued Date: May 29, 2015

This report should not be used by the client to claim product certification, approval, or endorsement by A2LA or any government agencies.

Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie
Town, Dongguan City,
Guangdong 523942, China

Tel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com



TABLE OF CONTENTS

RELEASE CONTROL RECORD 4

1 CERTIFICATION 5

2 SUMMARY OF TEST RESULTS..... 7

2.1 MEASUREMENT UNCERTAINTY 7

3 GENERAL INFORMATION 8

3.1 GENERAL DESCRIPTION OF EUT..... 8

3.2 DESCRIPTION OF TEST MODES..... 9

3.2.1 CONFIGURATION OF SYSTEM UNDER TEST 9

3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL..... 9

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS.....11

3.4 DESCRIPTION OF SUPPORT UNITS..... 12

4 TEST TYPES AND RESULTS..... 13

4.1 CONDUCTED EMISSION MEASUREMENT 13

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT 13

4.1.2 TEST INSTRUMENTS..... 13

4.1.3 TEST PROCEDURES 14

4.1.4 DEVIATION FROM TEST STANDARD 14

4.1.5 TEST SETUP 15

4.1.6 EUT OPERATING CONDITIONS 15

4.1.7 TEST RESULTS 16

4.2 RADIATED EMISSION MEASUREMENT 18

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT 18

4.2.2 TEST INSTRUMENTS..... 19

4.2.3 TEST PROCEDURES 20

4.2.4 DEVIATION FROM TEST STANDARD 20

4.2.5 TEST SETUP 21

4.2.6 EUT OPERATING CONDITIONS 21

4.2.7 TEST RESULTS 22

4.3 6DB BANDWIDTH MEASUREMENT 33

4.3.1 LIMITS OF 6DB BANDWIDTH MEASUREMENT 33

4.3.2 TEST INSTRUMENTS..... 33

4.3.3 TEST PROCEDURE..... 33

4.3.4 DEVIATION FROM TEST STANDARD 34



4.3.5	TEST SETUP	34
4.3.6	EUT OPERATING CONDITIONS	34
4.3.7	TEST RESULTS	35
4.4	CONDUCTED OUTPUT POWER	38
4.4.1	LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT	38
4.4.2	TEST SETUP	38
4.4.3	TEST INSTRUMENTS	38
4.4.4	TEST PROCEDURES	38
4.4.5	DEVIATION FROM TEST STANDARD	39
4.4.6	EUT OPERATING CONDITIONS	39
4.4.7	TEST RESULTS	39
4.4.7.1	MAXIMUM PEAK OUTPUT POWER	39
4.4.7.2	AVERAGE OUTPUT POWER (FOR REFERENCE)	40
4.5	POWER SPECTRAL DENSITY MEASUREMENT	41
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	41
4.5.2	TEST SETUP	41
4.5.3	TEST INSTRUMENTS	41
4.5.4	TEST PROCEDURE	41
4.5.5	DEVIATION FROM TEST STANDARD	41
4.5.6	EUT OPERATING CONDITION	41
4.5.7	TEST RESULTS	42
4.6	OUT OF BAND EMISSION MEASUREMENT	45
4.6.1	LIMITS OF OUT OF BAND EMISSION MEASUREMENT	45
4.6.2	TEST SETUP	45
4.6.3	TEST INSTRUMENTS	45
4.6.4	TEST PROCEDURE	45
4.6.5	DEVIATION FROM TEST STANDARD	46
4.6.6	EUT OPERATING CONDITION	46
4.6.7	TEST RESULTS	46
4.6.8	TEST RESULTS	47
5	PHOTOGRAPHS OF THE TEST CONFIGURATION	50
6	APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	51



BUREAU Test Report No.: RF150420N007-1
VERITAS

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF150420N007-1	Original release	May 29, 2015



**BUREAU
VERITAS**

Test Report No.: RF150420N007-1

1 CERTIFICATION

PRODUCT: Automotive Multi-function MiFi Terminal
BRAND NAME: ZTE
MODEL NAME: VM6200
APPLICANT: ZTE Corporation
TESTED: Apr. 21, 2015 ~ May 28, 2015
TEST SAMPLE: Production Unit
STANDARDS: **FCC Part 15, Subpart C. Section 15.247**
ANSI C63.10-2013

The above equipment has been tested by **Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : , **DATE:** May 29, 2015
(Yuqiang Yin / Engineer)

APPROVED BY : , **DATE:** May 29, 2015
(Glyn He / Supervisor)



BUREAU
VERITAS

Test Report No.: RF150420N007-1



2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -15.96dB at 0.40MHz.
15.205 15.209	Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -5.6dB at 2400.00MHz.
15.247(d)	Out of band Emission Measurement	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted Output power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.66dB
Radiated emissions	9KHz ~ 30MHz	2.74dB
	30MHz ~ 1GMHz	3.55dB
	1GHz ~ 18GHz	4.84dB
	18GHz ~ 40GHz	1.94dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.



3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Automotive Multi-function MiFi Terminal
MODEL NAME	VM6200
NOMINAL VOLTAGE	14Vdc (adapter or host equipment)
MODULATION TECHNOLOGY	DSSS, OFDM, DTS
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
TRANSMISSION RATE	802.11b: 11/ 5.5/ 2.0 / 1.0 Mbps 802.11g: 54/ 48/ 36 / 24 / 18 / 9/ 6 Mbps 802.11n: up to 135 Mbps
OPERATING FREQUENCY	2412-2462MHz for 11b/g/n(HT20)
MAX. OUTPUT POWER	WLAN: 47.424mW (Maximum)
ANTENNA TYPE	Dipole Antenna with 2.2dBi gain
I/O PORTS	Refer to user's manual
CABLE SUPPLIED	N/A

NOTE:

- For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
- The EUT incorporates a SISO function. Physically, the EUT provides one transmitter and one receiver.

MODULATION MODE	TX/RX FUNCTION
802.11b	1TX /1RX
802.11g	1TX /1RX
802.11n (20MHz)	1TX /1RX

- For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.



3.2 DESCRIPTION OF TEST MODES

11 channels are provided for 802.11b, 802.11g and 802.11n (HT20):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

3.2.1 CONFIGURATION OF SYSTEM UNDER TEST

Please see section 5 photographs of the test configuration for reference.

3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports. The worst case was found when positioned on Y axis for radiated emission. Following test modes were selected for the final test, and the final worst case is marked in boldface and recorded in the report:

EUT CONFIGURE MODE	APPLICABLE TO				MODE
	RE<1G	RE≥1G	PLC	APCM	
-	√	√	√	√	-

Where **RE<1G**: Radiated Emission below 1GHz **RE≥1G**: Radiated Emission above 1GHz
PLC: Power Line Conducted Emission **APCM**: Antenna Port Conducted Measurement

NOTE: No need to concern of Conducted Emission due to the EUT is powered by battery.

RADIATED EMISSION TEST (BELOW 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1	CCK	DBPSK	1.0

For the test results, only the worst case was shown in test report.



RADIATED EMISSION TEST (ABOVE 1GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	CCK	DBPSK	1.0
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
802.11n HT20	1 to 11	1, 6, 11	OFDM	BPSK	6.5

POWER LINE CONDUCTED EMISSION TEST:

The EUT was tested with the following mode

EUT CONFIGURE MODE	TESTED CONDITION
-	WIFI (2.4G) Link

BANDEDGE MEASUREMENT:

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 11	CCK	DBPSK	1.0
802.11g	1 to 11	1, 11	OFDM	BPSK	6.0
802.11n HT20	1 to 11	1, 11	OFDM	BPSK	6.5



ANTENNA PORT CONDUCTED MEASUREMENT:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	CCK	DBPSK	1.0
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
802.11n HT20	1 to 11	1, 6, 11	OFDM	BPSK	6.5

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE	TESTED BY
RE<1G	22deg. C, 54%RH	14Vdc (adapter or host equipment)	Blue Zheng
RE≥1G	22deg. C, 54%RH	14Vdc (adapter or host equipment)	Blue Zheng
PLC	25deg. C, 60%RH	14Vdc (adapter or host equipment)	Yuqiang Yin
APCM	25deg. C, 60%RH	14Vdc (adapter or host equipment)	Yuqiang Yin

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C, Section 15.247

558074 D01 DTS Meas Guidance v03r01

ANSI C63.10-2013

Note:

1. All test items have been performed and recorded as per the above standards.
2. The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (Verification). The test report has been issued separately.



3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	DC source	LONG WEI	PS-6403D	010934269	N/A
2	PC	HP	A6608CN	3CR83825X3	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	DC Line: Unshielded, Detachable 1.0m
2	AC Line: Unshielded, Detachable 1.5m



4 TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESCI	100340	May 11,15	May 10,16
Artificial Mains Network	Rohde&Schwarz	ENV216	101173	May 11,15	May 10,16
Artificial Mains Network	Rohde&Schwarz	ESH3-Z5	100317	May 11,15	May 10,16
Test software	ADT	ADT_Cond_V7.3.7	N/A	N/A	N/A

- NOTE:**
1. The test was performed in shielded room 553.
 2. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.



4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.


NOTE: All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation.



4.1.5 TEST SETUP



- Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes**

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT OPERATING CONDITIONS

- a. Turned on the power and connected of all equipment.
- b. EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.




BUREAU VERITAS Test Report No.: RF150420N007-1
4.1.7 TEST RESULTS

PHASE	Line	6dB BANDWIDTH	9kHz
--------------	------	----------------------	------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15781	10.82	30.40	18.76	41.22	29.58	65.58	55.58	-24.36	-26.00
2	0.2125	10.65	27.66	17.26	38.31	27.91	63.11	53.11	-24.79	-25.19
3	0.25547	10.64	24.12	14.42	34.76	25.06	61.58	51.58	-26.82	-26.52
4	0.27500	10.64	23.74	10.60	34.38	21.24	60.97	50.97	-26.58	-29.72
5	0.37266	10.65	26.06	15.82	36.71	26.47	58.44	48.44	-21.73	-21.97
6	0.38828	10.65	26.58	11.38	37.23	22.03	58.10	48.10	-20.87	-26.07

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.






PHASE	Neutral	6dB BANDWIDTH	9kHz
--------------	---------	----------------------	------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.21641	10.55	28.94	18.72	39.49	29.27	62.96	52.96	-23.47	-23.69
2	0.26328	10.56	26.56	17.58	37.12	28.14	61.33	51.33	-24.21	-23.19
3	0.27891	10.57	24.10	7.32	34.67	17.89	60.85	50.85	-26.18	-32.96
4	0.38828	10.61	30.24	14.64	40.85	25.25	58.10	48.10	-17.25	-22.85
5	0.40000	10.62	31.28	18.24	41.90	28.86	57.85	47.85	-15.96	-19.00
6	0.41953	10.62	28.56	17.92	39.18	28.54	57.46	47.46	-18.27	-18.91

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.





4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



4.2.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESU 26	100005	May 11,15	May 10,16
Bilog Antenna	Teseq	CBL 6111D	30643	Jul. 25, 14	Jul. 24, 15
Horn Antenna (1GHz -18GHz)	ETS -Lindgren	3117	00062558	May 30, 14	May 29, 16
Amplifier (9kHz-1GHz)	SONOMA	310D	186955	Mar. 04,15	Mar. 03, 16
Pre-Amplifier (18GHz-40GHz)	EMCI	EMC 184045	980102	Nov. 20,14	Nov. 19,15
Pre-Amplifier (100MHz-26.5GHz)	Agilent	8449B	3008A00409	May 11,15	May 10,16
GPS Generator+ Antenna	TOJOIN	GNSS-5000A	E1-010119	Aug. 08, 14	Aug. 07, 15
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	NSEMC003	Apr. 19,14	Apr. 18,16
Test Software	ADT	ADT_Radiated _V7.6.15.9.2	N/A	N/A	N/A

NOTE:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
2. The test was performed in 966 Chamber.
3. The FCC Site Registration No. is 502831.



4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

NOTE:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation



4.2.5 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT OPERATING CONDITIONS

- a. Set the EUT under full load condition and placed them on a testing table.
- b. Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- c. The necessary accessories enable the EUT in full functions.



4.2.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA:


802.11b

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	30.00	22.8 QP	40.0	-17.2	1.00 H	0	35.35	-12.55
2	63.95	23.4 QP	40.0	-16.6	1.00 H	0	48.78	-25.34
3	89.82	24.2 QP	43.5	-19.3	1.00 H	0	45.46	-21.26
4	133.47	17.3 QP	43.5	-26.2	1.00 H	0	35.71	-18.38
5	440.63	22.6 QP	46.0	-23.4	1.00 H	0	33.41	-10.80
6	738.10	26.4 QP	46.0	-19.7	1.00 H	0	29.24	-2.89

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.






CHANNEL	TX Channel 1	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	31.62	33.7 QP	40.0	-6.3	1.00 V	0	47.05	-13.34
2	63.95	24.4 QP	40.0	-15.6	1.00 V	0	49.76	-25.34
3	97.90	20.1 QP	43.5	-23.5	1.00 V	0	40.51	-20.46
4	128.62	16.8 QP	43.5	-26.7	1.00 V	0	35.28	-18.44
5	440.63	22.3 QP	46.0	-23.7	1.00 V	0	33.09	-10.80
6	587.75	24.4 QP	46.0	-21.7	1.00 V	0	30.44	-6.09

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.





802.11b

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	50.8 PK	74.0	-23.2	1.42 H	126	47.64	3.16
2	2390.00	37.2 AV	54.0	-16.8	1.42 H	126	34.04	3.16
3	#2400.00	52.5 PK	67.9	-15.4	1.42 H	126	49.31	3.19
4	#2400.00	39.3 AV	59.6	-20.3	1.42 H	126	36.11	3.19
5	*2412.00	87.9 PK			1.42 H	126	84.67	3.23
6	*2412.00	79.6 AV			1.42 H	126	76.37	3.23
7	4824.00	47.1 PK	74.0	-26.9	1.00 H	144	37.65	9.45
8	4824.00	32.6 AV	54.0	-21.4	1.00 H	144	23.15	9.45
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	50.4 PK	74.0	-23.6	1.14 V	328	47.24	3.16
2	2390.00	37.1 AV	54.0	-16.9	1.14 V	328	33.94	3.16
3	#2400.00	51.4 PK	69.1	-17.7	1.14 V	328	48.21	3.19
4	#2400.00	39.1 AV	60.1	-21.0	1.14 V	328	35.91	3.19
5	*2412.00	89.1 PK			1.14 V	328	85.87	3.23
6	*2412.00	80.1 AV			1.14 V	328	76.87	3.23
7	4824.00	46.9 PK	74.0	-27.1	1.06 V	311	37.45	9.45
8	4824.00	32.5 AV	54.0	-21.5	1.06 V	311	23.05	9.45

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.



CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	89.0 PK			1.22 H	356	85.68	3.32
2	*2437.00	78.5 AV			1.22 H	356	75.18	3.32
3	4874.00	46.9 PK	74.0	-27.1	1.00 H	177	37.38	9.52
4	4874.00	31.6 AV	54.0	-22.4	1.00 H	177	22.08	9.52
5	7311.00	49.9 PK	74.0	-24.1	1.00 H	360	38.04	11.86
6	7311.00	34.6 AV	54.0	-19.4	1.00 H	360	22.74	11.86
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	85.2 PK			1.00 V	0	81.88	3.32
2	*2437.00	77.2 AV			1.00 V	0	73.88	3.32
3	4874.00	47.2 PK	74.0	-26.8	1.00 V	145	37.68	9.52
4	4874.00	31.5 AV	54.0	-22.5	1.00 V	145	21.98	9.52
5	7311.00	49.7 PK	74.0	-24.3	1.00 V	0	37.84	11.86
6	7311.00	34.6 AV	54.0	-19.4	1.00 V	0	22.74	11.86

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.



CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	85.2 PK			1.20 H	356	81.81	3.39
2	*2462.00	75.3 AV			1.20 H	356	71.91	3.39
3	2483.50	49.1 PK	74.0	-24.9	1.20 H	356	45.63	3.47
4	2483.50	36.3 AV	54.0	-17.7	1.20 H	356	32.83	3.47
5	4924.00	46.2 PK	74.0	-27.8	1.00 H	189	36.60	9.60
6	4924.00	31.7 AV	54.0	-22.3	1.00 H	189	22.10	9.60
7	7386.00	49.4 PK	74.0	-24.6	1.00 H	0	37.59	11.81
8	7386.00	35.1 AV	54.0	-18.9	1.00 H	0	23.29	11.81
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	85.2 PK			1.26 V	324	81.81	3.39
2	*2462.00	76.9 AV			1.26 V	324	73.51	3.39
3	2483.50	48.6 PK	74.0	-25.4	1.26 V	324	45.13	3.47
4	2483.50	36.7 AV	54.0	-17.3	1.26 V	324	33.23	3.47
5	4924.00	46.7 PK	74.0	-27.3	1.00 V	179	37.10	9.60
6	4924.00	31.2 AV	54.0	-22.8	1.00 V	179	21.60	9.60
7	7386.00	49.9 PK	74.0	-24.1	1.00 V	360	38.09	11.81
8	7386.00	34.6 AV	54.0	-19.4	1.00 V	360	22.79	11.81

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * " : Fundamental frequency.



802.11g

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	49.5 PK	74.0	-24.5	1.42 H	127	46.34	3.16
2	2390.00	36.6 AV	54.0	-17.4	1.42 H	127	33.44	3.16
3	#2400.00	55.4 PK	62.6	-7.2	1.42 H	127	52.21	3.19
4	#2400.00	38.3 AV	47.7	-9.4	1.42 H	127	35.11	3.19
5	*2412.00	82.6 PK			1.42 H	127	79.37	3.23
6	*2412.00	67.7 AV			1.42 H	127	64.47	3.23
7	4824.00	46.8 PK	74.0	-27.2	1.00 H	141	37.35	9.45
8	4824.00	31.9 AV	54.0	-22.1	1.00 H	141	22.45	9.45

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	49.9 PK	74.0	-24.1	1.15 V	328	46.74	3.16
2	2390.00	37.2 AV	54.0	-16.8	1.15 V	328	34.04	3.16
3	#2400.00	59.6 PK	65.2	-5.6	1.15 V	328	56.41	3.19
4	#2400.00	39.0 AV	49.4	-10.4	1.15 V	328	35.81	3.19
5	*2412.00	85.2 PK			1.15 V	328	81.97	3.23
6	*2412.00	69.4 AV			1.15 V	328	66.17	3.23
7	4824.00	46.5 PK	74.0	-27.5	1.00 V	312	37.05	9.45
8	4824.00	32.4 AV	54.0	-21.6	1.00 V	312	22.95	9.45

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.



CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	84.7 PK			1.20 H	356	81.38	3.32
2	*2437.00	68.7 AV			1.20 H	356	65.38	3.32
3	4874.00	46.5 PK	74.0	-27.5	1.00 H	332	36.98	9.52
4	4874.00	31.4 AV	54.0	-22.6	1.00 H	332	21.88	9.52
5	7311.00	49.7 PK	74.0	-24.3	1.00 H	360	37.84	11.86
6	7311.00	34.5 AV	54.0	-19.5	1.00 H	360	22.64	11.86
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	83.8 PK			1.00 V	360	80.48	3.32
2	*2437.00	69.1 AV			1.00 V	360	65.78	3.32
3	4874.00	47.1 PK	74.0	-26.9	1.00 V	188	37.58	9.52
4	4874.00	31.6 AV	54.0	-22.4	1.00 V	188	22.08	9.52
5	7311.00	49.6 PK	74.0	-24.4	1.00 V	360	37.74	11.86
6	7311.00	34.2 AV	54.0	-19.8	1.00 V	360	22.34	11.86

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.



CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	84.9 PK			1.18 H	356	81.51	3.39
2	*2462.00	70.8 AV			1.18 H	356	67.41	3.39
3	2483.50	49.1 PK	74.0	-24.9	1.18 H	356	45.63	3.47
4	2483.50	36.5 AV	54.0	-17.5	1.18 H	356	33.03	3.47
5	4924.00	46.1 PK	74.0	-27.9	1.21 H	315	36.50	9.60
6	4924.00	31.6 AV	54.0	-22.4	1.21 H	315	22.00	9.60
7	7386.00	49.1 PK	74.0	-24.9	1.10 H	360	37.29	11.81
8	7386.00	34.8 AV	54.0	-19.2	1.10 H	360	22.99	11.81
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	86.5 PK			1.21 V	319	83.11	3.39
2	*2462.00	71.7 AV			1.21 V	319	68.31	3.39
3	2483.50	49.8 PK	74.0	-24.2	1.21 V	319	46.33	3.47
4	2483.50	36.8 AV	54.0	-17.2	1.21 V	319	33.33	3.47
5	4924.00	46.5 PK	74.0	-27.5	1.25 V	326	36.90	9.60
6	4924.00	31.3 AV	54.0	-22.7	1.25 V	326	21.70	9.60
7	7386.00	49.5 PK	74.0	-24.5	1.08 V	313	37.69	11.81
8	7386.00	34.6 AV	54.0	-19.4	1.08 V	313	22.79	11.81

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * " : Fundamental frequency.



802.11n (20MHz)

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	49.9 PK	74.0	-24.1	1.45 H	130	46.74	3.16
2	2390.00	36.7 AV	54.0	-17.3	1.45 H	130	33.54	3.16
3	#2400.00	57.1 PK	63.2	-6.1	1.45 H	130	53.91	3.19
4	#2400.00	38.4 AV	47.1	-8.7	1.45 H	130	35.21	3.19
5	*2412.00	83.2 PK			1.45 H	130	79.97	3.23
6	*2412.00	67.1 AV			1.45 H	130	63.87	3.23
7	4824.00	46.8 PK	74.0	-27.2	1.31 H	142	37.35	9.45
8	4824.00	32.1 AV	54.0	-21.9	1.31 H	142	22.65	9.45

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	49.8 PK	74.0	-24.2	1.15 V	327	46.64	3.16
2	2390.00	37.2 AV	54.0	-16.8	1.15 V	327	34.04	3.16
3	#2400.00	58.0 PK	65.0	-7.0	1.15 V	327	54.81	3.19
4	#2400.00	39.4 AV	50.2	-10.8	1.15 V	327	36.21	3.19
5	*2412.00	85.0 PK			1.15 V	327	81.77	3.23
6	*2412.00	70.2 AV			1.15 V	327	66.97	3.23
7	4824.00	46.7 PK	74.0	-27.3	1.08 V	304	37.25	9.45
8	4824.00	32.4 AV	54.0	-21.6	1.08 V	304	22.95	9.45

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.



CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	83.4 PK			1.19 H	356	80.08	3.32
2	*2437.00	66.9 AV			1.19 H	356	63.58	3.32
3	4874.00	46.8 PK	74.0	-27.2	1.18 H	347	37.28	9.52
4	4874.00	31.5 AV	54.0	-22.5	1.18 H	347	21.98	9.52
5	7311.00	49.7 PK	74.0	-24.3	1.00 H	360	37.84	11.86
6	7311.00	34.5 AV	54.0	-19.5	1.00 H	360	22.64	11.86
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	82.8 PK			1.00 V	0	79.48	3.32
2	*2437.00	66.7 AV			1.00 V	0	63.38	3.32
3	4874.00	47.1 PK	74.0	-26.9	1.00 V	0	37.58	9.52
4	4874.00	31.5 AV	54.0	-22.5	1.00 V	0	21.98	9.52
5	7311.00	49.2 PK	74.0	-24.8	1.00 V	0	37.34	11.86
6	7311.00	34.5 AV	54.0	-19.5	1.00 V	0	22.64	11.86

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.



CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	84.1 PK			1.21 H	351	80.71	3.39
2	*2462.00	67.1 AV			1.21 H	351	63.71	3.39
3	2483.50	49.0 PK	74.0	-25.0	1.21 H	351	45.53	3.47
4	2483.50	36.7 AV	54.0	-17.3	1.21 H	351	33.23	3.47
5	4924.00	46.1 PK	74.0	-27.9	1.00 H	174	36.50	9.60
6	4924.00	31.4 AV	54.0	-22.6	1.00 H	174	21.80	9.60
7	7386.00	49.2 PK	74.0	-24.8	1.00 H	0	37.39	11.81
8	7386.00	35.0 AV	54.0	-19.0	1.00 H	0	23.19	11.81
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	84.8 PK			1.25 V	326	81.41	3.39
2	*2462.00	68.3 AV			1.25 V	326	64.91	3.39
3	2483.50	49.3 PK	74.0	-24.7	1.25 V	326	45.83	3.47
4	2483.50	36.3 AV	54.0	-17.7	1.25 V	326	32.83	3.47
5	4924.00	46.7 PK	74.0	-27.3	1.00 V	188	37.10	9.60
6	4924.00	31.2 AV	54.0	-22.8	1.00 V	188	21.60	9.60
7	7386.00	49.5 PK	74.0	-24.5	1.00 V	360	37.69	11.81
8	7386.00	34.5 AV	54.0	-19.5	1.00 V	360	22.69	11.81

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * " : Fundamental frequency.



4.3 6 dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Spectrum Analyzer (10Hz–40GHz)	Rohde&Schwarz	FSV40	101003	Apr. 07,15	Apr. 06,16
Power Meter	Anritsu	ML2495A	1139001	Feb. 20,15	Feb. 19,16
Power Sensor	Anritsu	MA2411B	1126068	Feb. 20,15	Feb. 19,16
Digital Multimeter	FLUKE	15B	A1220010DG	Oct. 29, 14	Oct. 28, 15
Humid & Temp Programmable Tester	Haida	HD-2257	110807201	Sep.04,14	Sep. 03,15

NOTE:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
2. The test was performed in RF Oven room.

4.3.3 TEST PROCEDURE


1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) ≥ 3 RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



4.3.4 DEVIATION FROM TEST STANDARD

No deviation.

4.3.5 TEST SETUP



4.3.6 EUT OPERATING CONDITIONS


The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



4.3.7 TEST RESULTS

802.11b

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	11.10	0.5	PASS
6	2437	10.70	0.5	PASS
11	2462	10.48	0.5	PASS






BUREAU VERITAS

Test Report No.: RF150420N007-1

802.11g


CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	15.85	0.5	PASS
6	2437	16.50	0.5	PASS
11	2462	16.50	0.5	PASS





802.11n (20MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	17.29	0.5	PASS
6	2437	17.73	0.5	PASS
11	2462	17.37	0.5	PASS






4.4 CONDUCTED OUTPUT POWER

4.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 2400–2483.5 MHz band: 1 Watt (30dBm)

4.4.2 TEST SETUP



4.4.3 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Spectrum Analyzer (10Hz–40GHz)	Rohde&Schwarz	FSV40	101003	Apr. 09,14	Apr. 08,15
Spectrum Analyzer (9KHz-25GHz)	Agilent	E7405A	MY45118807	May 13,14	May 12,15
Power Meter	Anritsu	ML2495A	1139001	Feb. 21,14	Feb. 20,15
Power Sensor	Anritsu	MA2411B	1126068	Feb. 21,14	Feb. 20,15
Humid & Temp Programmable Tester	Haida	HD-2257	110807201	Sep.04,14	Sep. 03,15
Digital Multimeter	FLUKE	15B	A1220010D G	Oct. 29, 14	Oct. 28, 15

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

2. The test was performed in Oven room.

4.4.4 TEST PROCEDURES

A power sensor was used on the output port of the EUT. A power meter was used to read the response of the power sensor. Record the power level.



4.4.5 DEVIATION FROM TEST STANDARD

No deviation.

4.4.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.4.7 TEST RESULTS

4.4.7.1 MAXIMUM PEAK OUTPUT POWER

802.11b

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT (W)	PASS/FAIL
1	2412	16.33	42.954	1	PASS
6	2437	16.53	44.978	1	PASS
11	2462	16.76	47.424	1	PASS

802.11g

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT (W)	PASS/FAIL
1	2412	16.01	39.902	1	PASS
6	2437	15.69	37.068	1	PASS
11	2462	15.92	39.084	1	PASS

802.11n (20MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT (W)	PASS/FAIL
1	2412	13.96	24.889	1	PASS
6	2437	13.73	23.605	1	PASS
11	2462	13.89	24.491	1	PASS



4.4.7.2 AVERAGE OUTPUT POWER (FOR REFERENCE)

The average power sensor was used on the output port of the EUT. A power meter was used to read the response of the power sensor. Record the power level.

802.11b

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
1	2412	11.31	N/A
6	2437	10.92	N/A
11	2462	11.32	N/A

802.11g

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
1	2412	7.18	N/A
6	2437	7.56	N/A
11	2462	7.88	N/A

802.11n (20MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
1	2412	6.32	N/A
6	2437	6.18	N/A
11	2462	6.22	N/A




4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm/3KHz.

4.5.2 TEST SETUP



4.5.3 TEST INSTRUMENTS

Refer to section 4.3.2 to get information of above instrument.

4.5.4 TEST PROCEDURE

1. Set the span to 1.5 times the DTS bandwidth
2. Set the RBW = 100 kHz, VBW $\geq 3 \times$ RBW, Detector = peak.
3. Sweep time = auto couple, Trace mode = max hold, allow trace to fully stabilize.
4. Use the peak marker function to determine the maximum amplitude level.

4.5.5 DEVIATION FROM TEST STANDARD

No deviation.

4.5.6 EUT OPERATING CONDITION


The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



4.5.7 TEST RESULTS

802.11b

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-14.41	8	PASS
6	2437	-15.30	8	PASS
11	2462	-14.09	8	PASS






**BUREAU
VERITAS**

Test Report No.: RF150420N007-1

802.11g

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-17.51	8	PASS
6	2437	-17.56	8	PASS
11	2462	-18.57	8	PASS



**BUREAU
VERITAS**

Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie
Town, Dongguan City,
Guangdong 523942, China

Tel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com




**BUREAU
VERITAS**

Test Report No.: RF150420N007-1

802.11n (20MHz)

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-17.75	8	PASS
6	2437	-18.77	8	PASS
11	2462	-20.21	8	PASS



**BUREAU
VERITAS**




4.6 OUT OF BAND EMISSION MEASUREMENT

4.6.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 TEST SETUP



4.6.3 TEST INSTRUMENTS

Refer to section 4.3.2 to get information of above instrument.

4.6.4 TEST PROCEDURE

MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW \geq 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.



MEASUREMENT PROCEDURE OOB

1. Set RBW = 100 kHz.
2. Set VBW \geq 300 kHz.
3. Set span to encompass the spectrum to be examined
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.

4.6.5 DEVIATION FROM TEST STANDARD

No deviation.

4.6.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.6.7 TEST RESULTS

The spectrum plots are attached on the following images. D1 line indicates the highest level. D2 line indicates the 20dB offset below D1. It shows compliance to the requirement.




**BUREAU
VERITAS**

Test Report No.: RF150420N007-1


4.6.8 TEST RESULTS

802.11b


CH 1



CH 6



CH 11



Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie
Town, Dongguan City,
Guangdong 523942, China

Tel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com





**BUREAU
VERITAS**



Test Report No.: RF150420N007-1

802.11g



CH 1



CH 6



CH 11



Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie
Town, Dongguan City,
Guangdong 523942, China

Tel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com





**BUREAU
VERITAS**



Test Report No.: RF150420N007-1

802.11n (20MHz)



CH 1



CH 6



CH 11



Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie
Town, Dongguan City,
Guangdong 523942, China

Tel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com



5 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



6 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---