


FCC Test Report


APPLICANT : ZTE CORPORATION
EQUIPMENT : HOME PHONE
BRAND NAME : ZTE
MODEL NAME : WF722
FCC ID : SRQ-WF722
STANDARD : FCC 47 CFR FCC Part 15 Subpart B
CLASSIFICATION : Certification

The product was received on Jul. 04, 2013 and completely tested on Jul. 24, 2013. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.4-2003 and shown the compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.



Reviewed by: Louis Wu / Manager



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C.



TABLE OF CONTENTS

REVISION HISTORY..... 3

SUMMARY OF TEST RESULT 4

1. GENERAL DESCRIPTION 5

 1.1. Applicant..... 5

 1.2. Manufacturer 5

 1.3. Feature of Equipment Under Test..... 5

 1.4. Product Specification of Equipment Under Test 5

 1.5. Modification of EUT 6

 1.6. Test Site 6

 1.7. Applied Standards 6

2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST 7

 2.1. Test Mode 7

 2.2. Connection Diagram of Test System 8

 2.3. Support Unit used in test configuration and system..... 8

 2.4. EUT Operation Test Setup 8

3. TEST RESULT 9

 3.1. Test of AC Conducted Emission Measurement 9

 3.2. Test of Radiated Emission Measurement 13

4. LIST OF MEASURING EQUIPMENT 17

5. UNCERTAINTY OF EVALUATION 18

APPENDIX A. SETUP PHOTOGRAPHS

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.107	AC Conducted Emission	< 15.107 limits	PASS	Under limit 8.51 dB at 0.400 MHz
3.2	15.109	Radiated Emission	< 15.109 limits	PASS	Under limit 11.36 dB at 45.520 MHz

1. General Description

1.1. Applicant

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P. R. China

1.2. Manufacturer

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P. R. China

1.3. Feature of Equipment Under Test

Product Feature	
Equipment	HOME PHONE
Brand Name	ZTE
Model Name	WF722
FCC ID	SRQ-WF722
EUT supports Radios application	CDMA
HW Version	ddyA
SW Version	USCC_AM_WF722V1.0.0B01
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4. Product Specification of Equipment Under Test

Product Specification subjective to this standard	
Tx Frequency	CDMA2000 BC0: 824.70 MHz ~ 848.31 MHz CDMA2000 BC1: 1851.25 MHz ~ 1908.75 MHz
Rx Frequency Range	CDMA2000 BC0: 869.70 MHz ~ 893.31 MHz CDMA2000 BC1: 1931.25 MHz ~ 1988.75 MHz GPS : 1.57542 GHz
Antenna Type	WWAN : Fixed External Antenna GPS : Fixed Internal Antenna
Type of Modulation	CDMA2000 : QPSK GPS : BPSK

1.5. Modification of EUT

No modifications are made to the EUT during all test items.

1.6. Test Site

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.		
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C. TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958		
Test Site No.	Sporton Site No.		FCC/IC Registration No.
	CO01-KS	03CH01-KS	149928/4086E-1

1.7. Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC 47 CFR FCC Part 15 Subpart B
- ♦ ANSI C63.4-2003

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.

2. Test Configuration of Equipment Under Test

2.1. Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2003 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (30MHz to the 5th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

The following tables are showing the test modes as the worst cases and recorded in this report.

Item	EUT Configuration	Test Condition		
		EMI AC	EMI RE<1G	EMI RE≥1G
1.	Charging Mode (EUT with adapter)	☒	☒	☒

Abbreviations:


- EMI AC: AC conducted emissions
- EMI RE ≥ 1G: EUT radiated emissions ≥ 1GHz
- EMI RE < 1G: EUT radiated emissions < 1GHz

Test Items	EUT Configure Mode	Function Type
AC Conducted Emission	1	Mode 1: CDMA2000 BC0 Idle + USB Cable (Charging from Adapter) + GPS Rx + Phone Link Mode 2: CDMA2000 BC1 Idle + USB Cable (Charging from Adapter) + GPS Rx + Phone Link
Radiated Emissions < 1GHz	1	Mode 1: CDMA2000 BC0 Idle + USB Cable (Charging from Adapter) + GPS Rx + Phone Link Mode 2: CDMA2000 BC1 Idle + USB Cable (Charging from Adapter) + GPS Rx + Phone Link
Radiated Emissions ≥ 1GHz	1	Mode 1: CDMA2000 BC0 Idle + USB Cable (Charging from Adapter) + GPS Rx + Phone Link

Remark:

1. The worst case of AC is mode 1; only the test data of this mode is reported.
2. The worst case of RE < 1G is mode 1; only the test data of this mode is reported.

2.2. Connection Diagram of Test System



2.3. Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Telephone	Bubugao	HCD007(6082)TSD	N/A	N/A	N/A
2.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
3.	GPS Station	ADIVIC	MP9000	N/A	N/A	Unshielded, 1.8 m
4.	Notebook	DELL	Vostro 1450	PPD-AR5B195	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
5.	Monitor	DELL	IN1930MWc	FCC DoC	Shielded, 1.2 m	Unshielded, 1.8 m
6.	iPod	Apple	A1199	FCC DoC	shielded, 1.2 m	N/A

2.4. EUT Operation Test Setup

The EUT was in CDMA2000 idle mode during the testing. The EUT was synchronized to the BCCH, and was in continuous receiving mode by setting system simulator's paging reorganization.

3. Test Result

3.1. Test of AC Conducted Emission Measurement

3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

3.1.3 Test Procedure

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.


3.1.4 Test Setup





3.1.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	22~24°C
Test Engineer :	Harvey Tang	Relative Humidity :	50~52%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	CDMA2000 BC0 Idle + USB Cable (Charging from Adapter) + GPS Rx + Phone Link		




Site : C001-KS
 Condition: FCC CLASS-B LISN-L20130306 LINE

mode : Mode 1

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
		dBuV	dB	dBuV	dBuV	dB	dB	
1	0.33	31.14	-18.26	49.40	20.30	0.50	10.34	Average
2	0.33	40.94	-18.46	59.40	30.10	0.50	10.34	QP
3	0.40	46.10	-11.71	57.81	35.50	0.32	10.28	QP
4	0.40	39.30	-8.51	47.81	28.70	0.32	10.28	Average
5	0.44	45.73	-11.29	57.02	35.20	0.26	10.27	QP
6	0.44	36.83	-10.19	47.02	26.30	0.26	10.27	Average
7	0.48	36.49	-9.92	46.41	26.00	0.22	10.27	Average
8	0.48	45.69	-10.72	56.41	35.20	0.22	10.27	QP
9	0.50	45.66	-10.34	56.00	35.20	0.20	10.26	QP
10	0.50	35.66	-10.34	46.00	25.20	0.20	10.26	Average
11	0.55	46.05	-9.95	56.00	35.60	0.20	10.25	QP
12	0.55	36.85	-9.15	46.00	26.40	0.20	10.25	Average
13	0.59	45.94	-10.06	56.00	35.50	0.20	10.24	QP
14	0.59	36.44	-9.56	46.00	26.00	0.20	10.24	Average
15	0.62	43.23	-12.77	56.00	32.80	0.20	10.23	QP
16	0.62	32.33	-13.67	46.00	21.90	0.20	10.23	Average
17	0.69	32.11	-13.89	46.00	21.70	0.20	10.21	Average
18	0.69	42.91	-13.09	56.00	32.50	0.20	10.21	QP
19	0.74	30.39	-25.61	56.00	20.00	0.19	10.20	QP
20	0.74	24.39	-21.61	46.00	14.00	0.19	10.20	Average



Test Mode :	Mode 1	Temperature :	22~24°C
Test Engineer :	Harvey Tang	Relative Humidity :	50~52%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	CDMA2000 BC0 Idle + USB Cable (Charging from Adapter) + GPS Rx + Phone Link		



Site : C001-KS
 Condition: FCC CLASS-B LISN-N20130306 NEUTRAL

mode : Mode 1

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.36	42.49	-16.20	58.69	31.70	0.48	10.31	QP
2	0.36	38.59	-10.10	48.69	27.80	0.48	10.31	Average
3	0.44	43.33	-13.78	57.11	32.70	0.36	10.27	QP
4	0.44	33.93	-13.18	47.11	23.30	0.36	10.27	Average
5	0.47	34.69	-11.85	46.54	24.10	0.32	10.27	Average
6	0.47	43.19	-13.35	56.54	32.60	0.32	10.27	QP
7	0.51	43.36	-12.64	56.00	32.80	0.30	10.26	QP
8	0.51	33.86	-12.14	46.00	23.30	0.30	10.26	Average
9	0.55	30.63	-15.37	46.00	20.10	0.28	10.25	Average
10	0.55	42.53	-13.47	56.00	32.00	0.28	10.25	QP
11	0.58	43.20	-12.80	56.00	32.69	0.26	10.25	QP
12	0.58	32.20	-13.80	46.00	21.69	0.26	10.25	Average
13	0.62	30.96	-15.04	46.00	20.50	0.23	10.23	Average
14	0.62	41.86	-14.14	56.00	31.40	0.23	10.23	QP
15	0.72	40.90	-15.10	56.00	30.50	0.19	10.21	QP
16	0.72	28.80	-17.20	46.00	18.40	0.19	10.21	Average

3.2. Test of Radiated Emission Measurement

3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.2.2. Measuring Instruments


See list of measuring instruments of this test report.

3.2.3. Test Procedures


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dBuV/m) = 20 log Emission level (uV/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz





3.2.5. Test Result of Radiated Emission

Test Mode :	Mode 1	Temperature :	23~24°C
Test Engineer :	Stone Gu	Relative Humidity :	43~44%
Test Distance :	3m	Polarization :	Horizontal
Function Type :	CDMA2000 BC0 Idle + USB Cable (Charging from Adapter) + GPS Rx + Phone Link		




Site : 03CH01-KS
 Condition : FCC CLASS-B 3m LF_ANT_100803 HORIZONTAL

Mode : mode 1

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Preamp Loss	A/Pos	I/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1	30.00	19.64	-20.36	40.00	34.87	18.00	0.34	33.57	100	0 Peak
2	60.07	18.31	-21.69	40.00	46.11	5.30	0.48	33.58	---	---
3	128.94	19.07	-24.43	43.50	40.28	11.71	0.67	33.59	---	---
4	663.41	19.73	-26.27	46.00	32.20	18.99	1.47	32.93	---	---
5	800.18	23.63	-22.37	46.00	34.75	19.85	1.65	32.62	---	---
6	960.23	25.02	-28.98	54.00	34.90	20.79	1.77	32.44	---	---



Test Mode :	Mode 1	Temperature :	23~24°C
Test Engineer :	Stone Gu	Relative Humidity :	43~44%
Test Distance :	3m	Polarization :	Vertical
Function Type :	CDMA2000 BC0 Idle + USB Cable (Charging from Adapter) + GPS Rx + Phone Link		



Site : 03CH01-KS
 Condition : FCC CLASS-B 3m LF_ANT_100803 VERTICAL

Mode : mode 1

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	32.91	27.85	-12.15	40.00	45.05	16.04	0.35	33.59	---	---	Peak
2	45.52	28.64	-11.36	40.00	52.59	9.25	0.41	33.61	100	0	Peak
3	79.47	27.34	-12.66	40.00	53.92	6.47	0.55	33.60	---	---	Peak
4	128.94	20.67	-22.83	43.50	41.88	11.71	0.67	33.59	---	---	Peak
5	196.84	16.59	-26.91	43.50	40.47	8.86	0.82	33.56	---	---	Peak
6	960.23	25.57	-28.43	54.00	35.45	20.79	1.77	32.44	---	---	Peak

4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Receiver	R&S	ESC17	100768	9kHz~7GHz	May 23, 2013	Jul. 24, 2013	May 22, 2014	Conduction (CO01-KS)
LISN (for auxiliary equipment)	MessTec	AN3016	60103	9kHz~30MHz	Dec. 29, 2012	Jul. 24, 2013	Dec. 28, 2013	Conduction (CO01-KS)
LISN	MessTec	AN3016	60105	9kHz~30MHz	Dec. 29, 2012	Jul. 24, 2013	Dec. 28, 2013	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP0000008 11	N/A	Nov. 15, 2012	Jul. 24, 2013	Nov. 14, 2013	Conduction (CO01-KS)
EMI Test Receiver	R&S	ESC1	100534	9kHz~3GHz	Nov. 08, 2012	Jul. 23, 2013	Nov. 07, 2013	Radiation (03CH01-KS)
Spectrum Analyzer	R&S	FSP30	100400	9kHz~30GHz	May 23, 2013	Jul. 23, 2013	May 22, 2014	Radiation (03CH01-KS)
Bilog Antenna	SCHAFFNER	CBL6112D	23182	25MHz~2GHz	Dec. 07, 2012	Jul. 23, 2013	Dec. 06, 2013	Radiation (03CH01-KS)
Double Ridge Horn Antenna	EMCO	3117	00075959	1GHz~18GHz	Dec. 07, 2012	Jul. 23, 2013	Dec. 06, 2013	Radiation (03CH01-KS)
Amplifier	com-power	PA-103A	161069	1MHz~1GHz	May 23, 2013	Jul. 23, 2013	May 22, 2014	Radiation (03CH01-KS)
Amplifier	Agilent	8449B	3008A02370	1GHz~26.5GHz	Dec. 29, 2012	Jul. 23, 2013	Dec. 28, 2013	Radiation (03CH01-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	N/A	Jul. 23, 2013	N/A	Radiation (03CH01-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	N/A	Jul. 23, 2013	N/A	Radiation (03CH01-KS)

5. Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.26
---	------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.54
---	------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.72
---	------