



FCC RF Test Report

APPLICANT : ZTE CORPORATION
EQUIPMENT : LTE/CDMA Multi-Mode Digital Mobile Phone
BRAND NAME : ZTE
MODEL NAME : Z353VL
FCC ID : SRQ-Z353VL
STANDARD : 47 CFR Part 2, 24(E), 27(L), 27(F)
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)

The product was received on May 13, 2016 and completely tested on Jun. 29, 2016. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA / EIA-603-D-2010 and the testing has shown the tested sample to be in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

Prepared by: James Huang / Manager

Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China



TABLE OF CONTENTS

1 GENERAL DESCRIPTION 5
1.1 Applicant 5
1.2 Manufacturer 5
1.3 Product Feature of Equipment Under Test 5
1.4 Product Specification of Equipment Under Test 6
1.5 Modification of EUT 6
1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator 7
1.7 Testing Location 8
1.8 Applicable Standards 8
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST 9
2.1 Test Mode 9
2.2 Connection Diagram of Test System 11
2.3 Support Unit used in test configuration and system 11
2.4 Measurement Results Explanation Example 12
2.5 Frequency List of Low/Middle/High Channels 13
3 CONDUCTED TEST ITEMS 15
3.1 Measuring Instruments 15
3.2 Test Setup 15
3.3 Test Result of Conducted Test 15
3.4 Conducted Output Power 16
3.5 Peak-to-Average Ratio 16
3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement 17
3.7 Conducted Band Edge 18
3.8 Conducted Spurious Emission 20
3.9 Frequency Stability 21
4 RADIATED TEST ITEMS 22
4.1 Measuring Instruments 22
4.2 Test Setup 22
4.3 Test Result of Radiated Test 22
4.4 Effective Radiated Power and Effective Isotropic Radiated Power 23
4.5 Radiated Spurious Emission 25
5 LIST OF MEASURING EQUIPMENT 26
6 UNCERTAINTY OF EVALUATION 27

APPENDIX A. TEST RESULTS OF CONDUCTED TEST
APPENDIX B. TEST RESULTS OF RADIATED TEST
APPENDIX C. TEST SETUP PHOTOGRAPHS



SUMMARY OF TEST RESULT

| Report Section | FCC Rule | Description | Limit | Result | Remark |
|----------------|---|--|-------------------------------------|--------|--|
| 3.4 | §2.1046 | Conducted Output Power | Reporting Only | PASS | - |
| 3.5 | §24.232(d) | Peak-to-Average Ratio | <13 dB | PASS | - |
| 3.6 | §2.1049 | 99% Occupied Bandwidth and 26dB Bandwidth | Reporting Only | PASS | - |
| 3.7 | §2.1051 §24.238(a) §27.53(c)(2)(4) §27.53(h) | Conducted Band Edge Measurement (Band 2) (Band 4) (Band 13) | < 43+10log ₁₀ (P[Watts]) | PASS | - |
| 3.8 | §2.1051 §24.238(a) §27.53(c)(2) §27.53(h) | Conducted Spurious Emission (Band 2) (Band 4) (Band 13) | < 43+10log ₁₀ (P[Watts]) | PASS | - |
| 3.9 | §2.1055 §24.235 §27.54 | Frequency Stability Temperature & Voltage | Within Authorized Band | PASS | - |
| 4.4 | §27.50(b)(10) | Effective Radiated Power (Band 13) | ERP < 3 Watt | PASS | - |
| | §24.232(c) | Equivalent Isotropic Radiated Power (Band 2) | EIRP < 2Watt | | |
| | §27.50(d)(4) | Equivalent Isotropic Radiated Power (Band 4) | EIRP < 1Watt | | |
| 4.5 | §2.1053 §24.238(a) §27.53(c)(2) §27.53(f) §27.53(h) | Radiated Spurious Emission (Band 2) (Band 4) (Band 13) | < 43+10log ₁₀ (P[Watts]) | PASS | Under limit 19.35 dB at 1559.680 MHz |



1 General Description

1.1 Applicant

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

1.2 Manufacturer

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

1.3 Product Feature of Equipment Under Test

| Product Feature | |
|---------------------------------|--|
| Equipment | LTE/CDMA Multi-Mode Digital Mobile Phone |
| Brand Name | ZTE |
| Model Name | Z353VL |
| FCC ID | SRQ-Z353VL |
| EUT supports Radios application | CDMA/EV-DO/LTE/ WLAN 2.4GHz 802.11b/g/n HT20/ Bluetooth v3.0 + EDR/Bluetooth v4.1 LE |
| MEID Code | Conducted: 99000683001344 Radiation: 99000683001322 ERP&EIRP: 99000683001789 |
| HW Version | Z353VLHVV1.0 |
| SW Version | Z353VLV1.0.0B02 |
| EUT Stage | Identical Prototype |



1.4 Product Specification of Equipment Under Test

| Standards-related Product Specification | |
|---|--|
| Tx Frequency | LTE Band 2 : 1850.7 MHz ~ 1909.3 MHz LTE Band 4 : 1710.7 MHz ~ 1754.3 MHz LTE Band 13 : 779.5 MHz ~ 784.5 MHz |
| Rx Frequency | LTE Band 2 : 1930.7 MHz ~ 1989.3 MHz LTE Band 4 : 2110.7 MHz ~ 2154.3 MHz LTE Band 13 : 748.5 MHz ~ 753.5 MHz |
| Bandwidth | LTE Band 2 : 1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz / 20MHz LTE Band 4 : 1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz / 20MHz LTE Band 13 : 5MHz / 10MHz |
| Maximum Output Power to Antenna | LTE Band 2 : 22.92 dBm LTE Band 4 : 23.35 dBm LTE Band 13 : 22.83 dBm |
| Type of Modulation | QPSK / 16QAM |

1.5 Modification of EUT

No modifications are made to the EUT during all test items.



1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

| LTE Band 2 | | QPSK | | | 16QAM | | |
|-------------|------------------------------|---------------------------|-----------------|------------------------------|---------------------------|-----------------|--|
| BW(MHz) | Emission Designator (99%OBW) | Frequency Tolerance (ppm) | Maximum EIRP(W) | Emission Designator (99%OBW) | Frequency Tolerance (ppm) | Maximum EIRP(W) | |
| 1.4 | 1M09G7D | - | 0.2680 | 1M10W7D | - | 0.2139 | |
| 3 | 2M74G7D | - | 0.2510 | 2M75W7D | - | 0.2117 | |
| 5 | 4M52G7D | - | 0.2565 | 4M51W7D | - | 0.2115 | |
| 10 | 9M03G7D | 0.0053 | 0.2398 | 9M01W7D | - | 0.1921 | |
| 15 | 13M5G7D | - | 0.2580 | 13M5W7D | - | 0.1979 | |
| 20 | 18M5G7D | - | 0.2527 | 18M5W7D | - | 0.2023 | |
| LTE Band 4 | | QPSK | | | 16QAM | | |
| BW(MHz) | Emission Designator (99%OBW) | Frequency Tolerance (ppm) | Maximum EIRP(W) | Emission Designator (99%OBW) | Frequency Tolerance (ppm) | Maximum EIRP(W) | |
| 1.4 | 1M10G7D | - | 0.2582 | 1M09W7D | - | 0.2551 | |
| 3 | 2M74G7D | - | 0.3241 | 2M73W7D | - | 0.2847 | |
| 5 | 4M54G7D | - | 0.3616 | 4M51W7D | - | 0.2747 | |
| 10 | 9M03G7D | 0.0055 | 0.3398 | 9M01W7D | - | 0.2637 | |
| 15 | 13M6G7D | - | 0.3198 | 13M5W7D | - | 0.2729 | |
| 20 | 18M5G7D | - | 0.3256 | 18M5W7D | - | 0.2677 | |
| LTE Band 13 | | QPSK | | | 16QAM | | |
| BW(MHz) | Emission Designator (99%OBW) | Frequency Tolerance (ppm) | Maximum ERP(W) | Emission Designator (99%OBW) | Frequency Tolerance (ppm) | Maximum ERP(W) | |
| 5 | 4M52G7D | - | 0.1047 | 4M50W7D | - | 0.0834 | |
| 10 | 9M05G7D | 0.0092 | 0.0489 | 9M03W7D | - | 0.0802 | |



1.7 Testing Location

| | | | |
|---------------------------|---|-----------|-----------------------------|
| Test Site | SPORTON INTERNATIONAL (KUNSHAN) INC. | | |
| Test Site Location | No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958 | | |
| Test Site No. | Sporton Site No. | | FCC Registration No. |
| | TH01-KS | 03CH02-KS | 418269 |

Note: The test site complies with ANSI C63.4 2014 requirement.

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2, 24(E), 27(L), 27(F)
- ♦ ANSI / TIA / EIA-603-D-2010
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v02r02

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas. License Digital Systems v02r02 with maximum output power.


Radiated measurements are performed by rotating the EUT in three different orthogonal test planes to find the maximum emission.

| Test Items | Band | Bandwidth (MHz) | | | | | | Modulation | | RB # | | | Test Channel | | |
|------------------------|------|-----------------|---|---|----|----|----|------------|-------|------|------|------|--------------|---|---|
| | | 1.4 | 3 | 5 | 10 | 15 | 20 | QPSK | 16QAM | 1 | Half | Full | L | M | H |
| Max. Output Power | 2 | v | v | v | v | v | v | v | v | v | v | v | v | v | v |
| | 4 | v | v | v | v | v | v | v | v | v | v | v | v | v | |
| | 13 | - | - | v | | - | - | v | v | v | v | v | v | v | |
| | 13 | | | | v | | | v | v | v | v | | v | | |
| Peak-to-Average Ratio | 2 | | | | | | v | v | v | v | | v | v | v | |
| | 4 | | | | | | v | v | v | v | | v | v | v | |
| | 13 | - | - | | v | - | - | v | v | v | | v | | v | |
| 26dB and 99% Bandwidth | 2 | v | v | v | v | v | v | v | v | | | v | v | v | |
| | 4 | v | v | v | v | v | v | v | v | | | v | v | v | |
| | 13 | - | - | v | | - | - | v | v | | | v | v | v | |
| | 13 | - | - | | v | - | - | v | v | | | v | | v | |
| Conducted Band Edge | 2 | v | v | v | v | v | v | v | v | v | | v | v | v | |
| | 4 | v | v | v | v | v | v | v | v | v | | v | v | v | |
| | 13 | - | - | v | | - | - | v | v | v | | v | v | v | |
| | 13 | - | - | | v | - | - | v | v | v | | v | | v | |



| Test Items | Band | Bandwidth (MHz) | | | | | | Modulation | | RB # | | | Test Channel | | |
|-----------------------------|--|-----------------|---|---|----|----|----|------------|-------|------|------|------|--------------|---|---|
| | | 1.4 | 3 | 5 | 10 | 15 | 20 | QPSK | 16QAM | 1 | Half | Full | L | M | H |
| Conducted Spurious Emission | 2 | v | v | v | v | v | v | v | v | v | v | | v | v | v |
| | 4 | v | v | v | v | v | v | v | v | v | v | | v | v | v |
| | 13 | - | - | v | | - | - | v | v | v | | | v | v | v |
| | 13 | - | - | | v | - | - | v | v | v | | | | v | |
| Frequency Stability | 2 | | | | v | | | v | | | | v | | v | |
| | 4 | | | | v | | | v | | | | v | | v | |
| | 13 | - | - | | v | - | - | v | | | | v | | v | |
| E.R.P./ E.I.R.P. | 2 | v | v | v | v | v | v | v | v | v | v | | v | v | v |
| | 4 | v | v | v | v | v | v | v | v | v | v | | v | v | v |
| | 13 | - | - | v | | - | - | v | v | v | | | v | v | v |
| | 13 | - | - | | v | - | - | v | v | v | | | | v | |
| Radiated Spurious Emission | 2 | v | v | v | v | v | v | v | | v | | | | v | |
| | 4 | v | v | v | v | v | v | v | | v | | | | v | |
| | 13 | - | - | v | | - | - | v | | v | | | | v | |
| | 13 | - | - | | v | - | - | v | | v | | | | v | |
| Note | <p>1. The mark "v " means that this configuration is chosen for testing</p> <p>2. The mark "-" means that this bandwidth is not supported.</p> <p>3. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported.</p> | | | | | | | | | | | | | | |

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

| Item | Equipment | Trade Name | Model No. | FCC ID | Data Cable | Power Cord |
|------|------------------|------------|-----------|--------|------------------|-------------------|
| 1. | LTE Base Station | Anritsu | MT8820C | N/A | N/A | Unshielded, 1.8 m |
| 2. | Power Supply | GWINSTEK | PSS-2002 | N/A | N/A | Unshielded, 1.8 m |
| 3. | Earphone | Lenovo | SH100 | N/A | Unshielded, 1.2m | N/A |



2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss.

Following shows an offset computation example with cable loss 4.8 dB.

Example :

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)}. \\ &= 4.8 \text{ (dB)} \end{aligned}$$



2.5 Frequency List of Low/Middle/High Channels

| LTE Band 2 Channel and Frequency List | | | | |
|---------------------------------------|------------------------|--------|--------|---------|
| BW [MHz] | Channel/Frequency(MHz) | Lowest | Middle | Highest |
| 20 | Channel | 18700 | 18900 | 19100 |
| | Frequency | 1860 | 1880 | 1900 |
| 15 | Channel | 18675 | 18900 | 19125 |
| | Frequency | 1857.5 | 1880 | 1902.5 |
| 10 | Channel | 18650 | 18900 | 19150 |
| | Frequency | 1855 | 1880 | 1905 |
| 5 | Channel | 18625 | 18900 | 19175 |
| | Frequency | 1852.5 | 1880 | 1907.5 |
| 3 | Channel | 18615 | 18900 | 19185 |
| | Frequency | 1851.5 | 1880 | 1908.5 |
| 1.4 | Channel | 18607 | 18900 | 19193 |
| | Frequency | 1850.7 | 1880 | 1909.3 |

| LTE Band 4 Channel and Frequency List | | | | |
|---------------------------------------|------------------------|--------|--------|---------|
| BW [MHz] | Channel/Frequency(MHz) | Lowest | Middle | Highest |
| 20 | Channel | 20050 | 20175 | 20300 |
| | Frequency | 1720 | 1732.5 | 1745 |
| 15 | Channel | 20025 | 20175 | 20325 |
| | Frequency | 1717.5 | 1732.5 | 1747.5 |
| 10 | Channel | 20000 | 20175 | 20350 |
| | Frequency | 1715 | 1732.5 | 1750 |
| 5 | Channel | 19975 | 20175 | 20375 |
| | Frequency | 1712.5 | 1732.5 | 1752.5 |
| 3 | Channel | 19965 | 20175 | 20385 |
| | Frequency | 1711.5 | 1732.5 | 1753.5 |
| 1.4 | Channel | 19957 | 20175 | 20393 |
| | Frequency | 1710.7 | 1732.5 | 1754.3 |



| LTE Band 13 Channel and Frequency List | | | | |
|---|-------------------------------|---------------|---------------|----------------|
| BW [MHz] | Channel/Frequency(MHz) | Lowest | Middle | Highest |
| 10 | Channel | - | 23230 | - |
| | Frequency | - | 782 | - |
| 5 | Channel | 23205 | 23230 | 23255 |
| | Frequency | 779.5 | 782 | 784.5 |


3 Conducted Test Items

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.2 Test Setup


3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied Bandwidth ,Conducted Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.



3.4 Conducted Output Power

3.4.1 Description of the Conducted Output Power Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to force the EUT transmitting at maximum output power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

3.4.2 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through the system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure and record the power level from the system simulator.

3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 5.7.1.
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.



3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.6.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.6.2 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 4.2.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
(this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.



3.7 Conducted Band Edge

3.7.1 Description of Conducted Band Edge Measurement

24.238 (a) for Band 2

For operations in the 1850-1910 and 1930-1990 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power $P(\text{Watts})$ in a 1MHz bandwidth. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

27.53 (c) for Band 13

For operations in the 776-788 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power $P(\text{Watts})$ in a 100 kHz bandwidth. However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 30 kHz may be employed. In addition, the power of any unwanted emissions in any 6.25 kHz bandwidth for all frequencies between 763-775 MHz and 793-806 MHz shall be attenuated below the transmitter power, P (dBW), by at least $65 + 10 \log_{10} p(\text{watts})$, dB, for mobile and portable equipment.

27.53 (h) for Band 4

For operations in the 1710 – 1755 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power $P(\text{Watts})$ in a 1 MHz bandwidth. However, in the 1MHz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.



3.7.2 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 6.0.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The band edges of low and high channels for the highest RF powers were measured.
4. Set RBW \geq 1% EBW in the 1MHz band immediately outside and adjacent to the band edge.
5. Beyond the 1 MHz band from the band edge, RBW=1MHz was used or a narrower RBW was used and the measured power was integrated over the full required measurement bandwidth of 1 MHz.
6. Set spectrum analyzer with RMS detector.
7. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
8. Checked that all the results comply with the emission limit line.

Example:

The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

$$= P(W) - [43 + 10\log(P)] \text{ (dB)}$$

$$= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)} = -13\text{dBm.}$$



3.8 Conducted Spurious Emission

3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.8.2 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 6.0.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
7. Set spectrum analyzer with RMS detector.
8. Taking the record of maximum spurious emission.
9. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
10. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
= P(W)- [43 + 10log(P)] (dB)
= [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)
= -13dBm.



3.9 Frequency Stability

3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.9.2 Test Procedures for Temperature Variation

1. The testing follows FCC KDB 971168 v02r02 Section 9.0.
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.9.3 Test Procedures for Voltage Variation

1. The testing follows FCC KDB 971168 v02r02 Section 9.0.
2. The EUT was placed in a temperature chamber at $25\pm 5^{\circ}\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
4. The variation in frequency was measured for the worst case.


4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup

4.2.1 For radiated test from 30MHz to 1GHz



4.2.2 For radiated test above 1GHz



4.3 Test Result of Radiated Test

Please refer to Appendix B.



4.4 Effective Radiated Power and Effective Isotropic Radiated Power

4.4.1 Description of the ERP/EIRP Measurement

Effective radiated power output measurements by substitution method according to ANSI / TIA / EIA-603-D-2010, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v02r02. Mobile and portable (hand-held) stations operating are limited to average ERP of 3 watts with LTE band 13.

Equivalent isotropic radiated power output measurements by substitution method according to ANSI / TIA / EIA-603-D-2010, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v02r02. Mobile and portable (hand-held) stations operating are limited to average EIRP of 2 watts with LTE band 2 and 1 watt with LTE band 4.

4.4.2 Test Procedures

1. The EUT was placed on a non-conductive rotating platform 0.8 meters high in a semi-anechoic chamber. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and a spectrum analyzer with RMS detector per section 5. of KDB 971168 D01.
2. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power. The maximum emission was recorded from analyzer power level (LVL) from the 360 degrees rotation of the turntable and the test antenna raised and lowered over a range from 1 to 4 meters in both horizontally and vertically polarized orientations.
3. Effective Isotropic Radiated Power (EIRP) was measured by substitution method according to TIA/EIA-603-D. The EUT was replaced by the substitution antenna at same location, and then a known power from S.G. was applied into the dipole antenna through a Tx cable, and then recorded the maximum Analyzer reading through raised and lowered the test antenna. The correction factor (in dB) = S.G. - Tx Cable loss + Substitution antenna gain - Analyzer reading. Then the EUT's EIRP was calculated with the correction factor, $EIRP = LVL + \text{Correction factor}$ and $ERP = EIRP - 2.15$. Take the record of the output power at substitution antenna.



| | LTE Average | | | | | |
|--------------|-------------|---------|---------|---------|---------|---------|
| LTE BW | 1.4M | 3M | 5M | 10M | 15M | 20M |
| Span | 3MHz | 6MHz | 10MHz | 20MHz | 30MHz | 40MHz |
| RBW | 30kHz | 100kHz | 100kHz | 300kHz | 300kHz | 300kHz |
| VBW | 100kHz | 300kHz | 300kHz | 1MHz | 1MHz | 1MHz |
| Detector | RMS | RMS | RMS | RMS | RMS | RMS |
| Trace | Average | Average | Average | Average | Average | Average |
| Average Type | Power | Power | Power | Power | Power | Power |
| Sweep Count | 100 | 100 | 100 | 100 | 100 | 100 |



4.5 Radiated Spurious Emission

4.5.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI / TIA / EIA-603-D-2010. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

For LTE Band 13

For operations in the 746-758 MHz, 775-788 MHz, and 805-806 MHz bands, emissions in the band 1559-1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.5.2 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 5.8 and ANSI / TIA-603-D-2010 Section 2.2.12.
2. The EUT was placed on a rotatable wooden table with 0.8 meter above ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

$$= P(W) - [43 + 10\log(P)] \text{ (dB)}$$

$$= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$$

$$= -13\text{dBm.}$$

12. $\text{EIRP (dBm)} = \text{S.G. Power} - \text{Tx Cable Loss} + \text{Tx Antenna Gain}$
13. $\text{ERP (dBm)} = \text{EIRP} - 2.15$



5 List of Measuring Equipment

| Instrument | Manufacturer | Model No. | Serial No. | Characteristics | Calibration Date | Test Date | Due Date | Remark |
|---------------------------|--------------|-----------|--------------|--------------------------|------------------|---------------------------------|---------------|--------------------------|
| Spectrum Analyzer | R&S | FSV40 | 101040 | 10Hz~40GHz | Sep. 10, 2015 | Jun. 08, 2016~ Jun. 10, 2016 | Sep. 09, 2016 | Conducted (TH01-KS) |
| Thermal Chamber | Ten Billion | TTC-B3S | TBN-960502 | -40~+150°C | Oct. 24, 2015 | Jun. 08, 2016~ Jun. 10, 2016 | Oct. 23, 2016 | Conducted (TH01-KS) |
| EXA Spectrum Analyzer | Keysight | N9010A | MY55150208 | 10Hz-44G,MAX 30dB | Apr. 22, 2016 | Jun. 25, 2016~ Jun. 29, 2016 | Apr. 21, 2017 | Radiation (03CH02-KS) |
| Bilog Antenna | TeseQ | CBL6112D | 37879 | 30MHz-2GHz | Sep. 12, 2015 | Jun. 25, 2016~ Jun. 29, 2016 | Sep. 11, 2016 | Radiation (03CH02-KS) |
| Double Ridge Horn Antenna | ETS-Lindgren | 3117 | 75957 | 1GHz~18GHz | Nov. 07, 2015 | Jun. 25, 2016~ Jun. 29, 2016 | Nov. 06, 2016 | Radiation (03CH02-KS) |
| SHF-EHF Horn | com-power | AH-840 | 101070 | 18Ghz-40Ghz | Oct. 10, 2015 | Jun. 25, 2016~ Jun. 29, 2016 | Oct. 09, 2016 | Radiation (03CH02-KS) |
| Amplifier | com-power | PA-103A | 161069 | 1kHz ~1000MHz / 32 dB | Apr. 22, 2016 | Jun. 25, 2016~ Jun. 29, 2016 | Apr. 21, 2017 | Radiation (03CH02-KS) |
| Amplifier | Agilent | 8449B | 3008A02384 | 1-26.5GHz Gain 30dB | Oct. 24, 2015 | Jun. 25, 2016~ Jun. 29, 2016 | Oct. 23, 2016 | Radiation (03CH02-KS) |
| AC Power Source | Chroma | 61601 | 616010002473 | N/A | NCR | Jun. 25, 2016~ Jun. 29, 2016 | NCR | Radiation (03CH02-KS) |
| Turn Table | MF | MF7802 | N/A | 0~360 degree | NCR | Jun. 25, 2016~ Jun. 29, 2016 | NCR | Radiation (03CH02-KS) |
| Antenna Mast | MF | MF7802 | N/A | 1 m~4 m | NCR | Jun. 25, 2016~ Jun. 29, 2016 | NCR | Radiation (03CH02-KS) |

NCR: No Calibration Required



6 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

| | |
|---|--------|
| Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y)) | 5.1 dB |
|---|--------|

Uncertainty of Radiated Emission Measurement (1GHz ~ 18GHz)

| | |
|---|-------|
| Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y)) | 4.5dB |
|---|-------|

Uncertainty of Radiated Emission Measurement (18GHz ~ 40GHz)

| | |
|---|-------|
| Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y)) | 5.1dB |
|---|-------|



Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)

| LTE Band 2 Maximum Average Power [dBm] | | | | | | |
|--|---------|-----------|--------|--------|--------|---------|
| BW [MHz] | RB Size | RB Offset | Mod | Lowest | Middle | Highest |
| 20 | 1 | 0 | QPSK | 22.82 | 22.78 | 22.74 |
| 20 | 1 | 49 | | 22.92 | 22.77 | 22.87 |
| 20 | 1 | 99 | | 22.63 | 22.61 | 22.64 |
| 20 | 50 | 0 | | 21.87 | 21.74 | 21.77 |
| 20 | 50 | 24 | | 21.79 | 21.56 | 21.63 |
| 20 | 50 | 50 | | 21.66 | 21.64 | 21.69 |
| 20 | 100 | 0 | | 21.76 | 21.68 | 21.71 |
| 20 | 1 | 0 | 16-QAM | 21.76 | 21.96 | 21.95 |
| 20 | 1 | 49 | | 21.50 | 21.75 | 21.74 |
| 20 | 1 | 99 | | 21.72 | 21.86 | 21.81 |
| 20 | 50 | 0 | | 20.86 | 20.73 | 20.89 |
| 20 | 50 | 24 | | 20.78 | 20.59 | 20.78 |
| 20 | 50 | 50 | | 20.71 | 20.55 | 20.69 |
| 20 | 100 | 0 | | 20.63 | 20.78 | 20.70 |
| 15 | 1 | 0 | QPSK | 22.58 | 22.30 | 22.48 |
| 15 | 1 | 37 | | 22.38 | 22.44 | 22.47 |
| 15 | 1 | 74 | | 22.52 | 22.37 | 22.59 |
| 15 | 36 | 0 | | 21.59 | 21.50 | 21.58 |
| 15 | 36 | 20 | | 21.58 | 21.56 | 21.45 |
| 15 | 36 | 39 | | 21.55 | 21.49 | 21.52 |
| 15 | 75 | 0 | | 21.57 | 21.49 | 21.56 |
| 15 | 1 | 0 | 16-QAM | 21.55 | 21.50 | 21.95 |
| 15 | 1 | 37 | | 21.31 | 21.65 | 21.76 |
| 15 | 1 | 74 | | 21.45 | 21.92 | 21.73 |
| 15 | 36 | 0 | | 20.60 | 20.60 | 20.72 |
| 15 | 36 | 20 | | 20.58 | 20.66 | 20.60 |
| 15 | 36 | 39 | | 20.55 | 20.69 | 20.61 |
| 15 | 75 | 0 | | 20.66 | 20.50 | 20.49 |



| LTE Band 2 Maximum Average Power [dBm] | | | | | | |
|--|---------|-----------|--------|--------|--------|---------|
| BW [MHz] | RB Size | RB Offset | Mod | Lowest | Middle | Highest |
| 10 | 1 | 0 | QPSK | 22.57 | 22.55 | 22.59 |
| 10 | 1 | 25 | | 22.41 | 22.64 | 22.60 |
| 10 | 1 | 49 | | 22.32 | 22.68 | 22.63 |
| 10 | 25 | 0 | | 21.59 | 21.51 | 21.52 |
| 10 | 25 | 12 | | 21.58 | 21.58 | 21.56 |
| 10 | 25 | 25 | | 21.58 | 21.54 | 21.55 |
| 10 | 50 | 0 | | 21.53 | 21.52 | 21.63 |
| 10 | 1 | 0 | 16-QAM | 21.38 | 21.89 | 21.86 |
| 10 | 1 | 25 | | 21.52 | 21.46 | 21.87 |
| 10 | 1 | 49 | | 21.63 | 21.79 | 21.84 |
| 10 | 25 | 0 | | 20.51 | 20.73 | 20.64 |
| 10 | 25 | 12 | | 20.50 | 20.71 | 20.63 |
| 10 | 25 | 25 | | 20.75 | 20.65 | 20.78 |
| 10 | 50 | 0 | | 20.54 | 20.54 | 20.54 |
| 5 | 1 | 0 | QPSK | 22.57 | 22.40 | 22.48 |
| 5 | 1 | 12 | | 22.60 | 22.48 | 22.57 |
| 5 | 1 | 24 | | 22.37 | 22.47 | 22.37 |
| 5 | 12 | 0 | | 21.39 | 21.43 | 21.42 |
| 5 | 12 | 7 | | 21.37 | 21.46 | 21.46 |
| 5 | 12 | 13 | | 21.42 | 21.46 | 21.49 |
| 5 | 25 | 0 | | 21.40 | 21.40 | 21.38 |
| 5 | 1 | 0 | 16-QAM | 21.75 | 21.82 | 21.53 |
| 5 | 1 | 12 | | 21.69 | 21.54 | 21.29 |
| 5 | 1 | 24 | | 21.65 | 21.69 | 21.54 |
| 5 | 12 | 0 | | 20.42 | 20.44 | 20.43 |
| 5 | 12 | 7 | | 20.47 | 20.37 | 20.21 |
| 5 | 12 | 13 | | 20.45 | 20.40 | 20.40 |
| 5 | 25 | 0 | | 20.62 | 20.43 | 20.42 |



| LTE Band 2 Maximum Average Power [dBm] | | | | | | |
|--|---------|-----------|--------|--------|--------|---------|
| BW [MHz] | RB Size | RB Offset | Mod | Lowest | Middle | Highest |
| 3 | 1 | 0 | QPSK | 22.59 | 22.40 | 22.49 |
| 3 | 1 | 8 | | 22.65 | 22.32 | 22.48 |
| 3 | 1 | 14 | | 22.69 | 22.46 | 22.54 |
| 3 | 8 | 0 | | 21.50 | 21.40 | 21.45 |
| 3 | 8 | 4 | | 21.55 | 21.37 | 21.46 |
| 3 | 8 | 7 | | 21.56 | 21.36 | 21.44 |
| 3 | 15 | 0 | | 21.52 | 21.39 | 21.38 |
| 3 | 1 | 0 | 16-QAM | 21.66 | 21.64 | 21.56 |
| 3 | 1 | 8 | | 21.79 | 21.52 | 21.61 |
| 3 | 1 | 14 | | 21.65 | 21.59 | 21.72 |
| 3 | 8 | 0 | | 20.36 | 20.38 | 20.43 |
| 3 | 8 | 4 | | 20.31 | 20.36 | 20.43 |
| 3 | 8 | 7 | | 20.31 | 20.35 | 20.44 |
| 3 | 15 | 0 | | 20.68 | 20.24 | 20.13 |
| 1.4 | 1 | 0 | QPSK | 22.38 | 22.40 | 22.29 |
| 1.4 | 1 | 3 | | 22.48 | 22.28 | 22.31 |
| 1.4 | 1 | 5 | | 22.39 | 22.24 | 22.25 |
| 1.4 | 3 | 0 | | 22.46 | 22.38 | 22.28 |
| 1.4 | 3 | 1 | | 22.61 | 22.49 | 22.32 |
| 1.4 | 3 | 3 | | 22.52 | 22.39 | 22.39 |
| 1.4 | 6 | 0 | | 21.51 | 21.47 | 21.37 |
| 1.4 | 1 | 0 | 16-QAM | 21.19 | 21.56 | 21.63 |
| 1.4 | 1 | 3 | | 21.53 | 21.33 | 21.69 |
| 1.4 | 1 | 5 | | 21.75 | 21.20 | 21.62 |
| 1.4 | 3 | 0 | | 21.58 | 21.62 | 21.62 |
| 1.4 | 3 | 1 | | 21.55 | 21.54 | 21.65 |
| 1.4 | 3 | 3 | | 21.62 | 21.57 | 21.64 |
| 1.4 | 6 | 0 | | 20.26 | 20.36 | 20.34 |



| LTE Band 4 Maximum Average Power [dBm] | | | | | | |
|--|---------|-----------|--------|--------|--------|---------|
| BW [MHz] | RB Size | RB Offset | Mod | Lowest | Middle | Highest |
| 20 | 1 | 0 | QPSK | 23.31 | 23.19 | 23.26 |
| 20 | 1 | 49 | | 23.15 | 23.35 | 22.85 |
| 20 | 1 | 99 | | 23.04 | 22.93 | 22.69 |
| 20 | 50 | 0 | | 22.16 | 22.26 | 22.24 |
| 20 | 50 | 24 | | 22.14 | 22.11 | 22.10 |
| 20 | 50 | 50 | | 22.05 | 22.00 | 22.04 |
| 20 | 100 | 0 | | 22.10 | 22.11 | 22.17 |
| 20 | 1 | 0 | 16-QAM | 22.47 | 22.48 | 22.45 |
| 20 | 1 | 49 | | 22.44 | 22.35 | 22.35 |
| 20 | 1 | 99 | | 22.32 | 21.85 | 22.26 |
| 20 | 50 | 0 | | 21.19 | 21.29 | 21.19 |
| 20 | 50 | 24 | | 21.17 | 21.16 | 21.06 |
| 20 | 50 | 50 | | 21.06 | 21.08 | 20.95 |
| 20 | 100 | 0 | | 21.11 | 21.05 | 21.20 |
| 15 | 1 | 0 | QPSK | 23.30 | 23.29 | 23.20 |
| 15 | 1 | 37 | | 23.13 | 23.09 | 22.88 |
| 15 | 1 | 74 | | 23.15 | 22.88 | 23.10 |
| 15 | 36 | 0 | | 22.31 | 22.29 | 22.16 |
| 15 | 36 | 20 | | 22.15 | 22.16 | 22.09 |
| 15 | 36 | 39 | | 22.13 | 22.07 | 22.02 |
| 15 | 75 | 0 | | 22.18 | 22.19 | 22.10 |
| 15 | 1 | 0 | 16-QAM | 22.48 | 22.49 | 22.44 |
| 15 | 1 | 37 | | 22.46 | 22.45 | 21.97 |
| 15 | 1 | 74 | | 22.47 | 22.27 | 22.42 |
| 15 | 36 | 0 | | 21.24 | 21.24 | 21.04 |
| 15 | 36 | 20 | | 21.17 | 21.10 | 20.81 |
| 15 | 36 | 39 | | 21.16 | 21.01 | 20.84 |
| 15 | 75 | 0 | | 21.20 | 21.13 | 21.15 |



| LTE Band 4 Maximum Average Power [dBm] | | | | | | |
|--|---------|-----------|--------|--------|--------|---------|
| BW [MHz] | RB Size | RB Offset | Mod | Lowest | Middle | Highest |
| 10 | 1 | 0 | QPSK | 23.23 | 23.20 | 22.98 |
| 10 | 1 | 25 | | 23.16 | 23.17 | 23.10 |
| 10 | 1 | 49 | | 22.86 | 23.02 | 23.19 |
| 10 | 25 | 0 | | 22.30 | 22.25 | 22.12 |
| 10 | 25 | 12 | | 22.21 | 22.18 | 22.23 |
| 10 | 25 | 25 | | 22.00 | 22.01 | 22.18 |
| 10 | 50 | 0 | | 22.11 | 22.12 | 22.17 |
| 10 | 1 | 0 | 16-QAM | 22.43 | 22.11 | 21.96 |
| 10 | 1 | 25 | | 22.40 | 22.23 | 22.39 |
| 10 | 1 | 49 | | 22.25 | 21.82 | 22.29 |
| 10 | 25 | 0 | | 21.31 | 21.46 | 21.15 |
| 10 | 25 | 12 | | 21.23 | 21.44 | 21.36 |
| 10 | 25 | 25 | | 21.02 | 20.98 | 21.31 |
| 10 | 50 | 0 | | 21.13 | 21.09 | 20.99 |
| 5 | 1 | 0 | QPSK | 23.22 | 23.25 | 23.06 |
| 5 | 1 | 12 | | 23.40 | 23.04 | 23.11 |
| 5 | 1 | 24 | | 23.22 | 23.15 | 23.05 |
| 5 | 12 | 0 | | 22.27 | 22.21 | 22.06 |
| 5 | 12 | 7 | | 22.25 | 22.22 | 22.16 |
| 5 | 12 | 13 | | 22.22 | 22.15 | 22.00 |
| 5 | 25 | 0 | | 22.31 | 22.17 | 22.13 |
| 5 | 1 | 0 | 16-QAM | 22.38 | 22.48 | 22.49 |
| 5 | 1 | 12 | | 22.48 | 22.37 | 22.42 |
| 5 | 1 | 24 | | 22.18 | 22.38 | 22.43 |
| 5 | 12 | 0 | | 21.31 | 21.16 | 21.10 |
| 5 | 12 | 7 | | 21.09 | 21.18 | 20.99 |
| 5 | 12 | 13 | | 20.99 | 21.11 | 21.04 |
| 5 | 25 | 0 | | 21.21 | 21.33 | 21.05 |



| LTE Band 4 Maximum Average Power [dBm] | | | | | | |
|--|---------|-----------|--------|--------|--------|---------|
| BW [MHz] | RB Size | RB Offset | Mod | Lowest | Middle | Highest |
| 3 | 1 | 0 | QPSK | 23.27 | 23.18 | 22.99 |
| 3 | 1 | 8 | | 23.20 | 23.15 | 22.90 |
| 3 | 1 | 14 | | 23.10 | 23.10 | 23.12 |
| 3 | 8 | 0 | | 22.28 | 22.29 | 22.25 |
| 3 | 8 | 4 | | 22.33 | 22.17 | 22.24 |
| 3 | 8 | 7 | | 22.26 | 22.16 | 22.17 |
| 3 | 15 | 0 | | 22.13 | 22.19 | 22.16 |
| 3 | 1 | 0 | 16-QAM | 22.47 | 22.46 | 22.42 |
| 3 | 1 | 8 | | 22.43 | 22.35 | 22.34 |
| 3 | 1 | 14 | | 22.36 | 22.28 | 22.46 |
| 3 | 8 | 0 | | 21.17 | 21.31 | 21.06 |
| 3 | 8 | 4 | | 21.40 | 21.28 | 21.21 |
| 3 | 8 | 7 | | 21.34 | 21.35 | 20.99 |
| 3 | 15 | 0 | | 20.97 | 21.25 | 20.95 |
| 1.4 | 1 | 0 | QPSK | 23.19 | 23.08 | 22.98 |
| 1.4 | 1 | 3 | | 23.09 | 23.10 | 23.00 |
| 1.4 | 1 | 5 | | 23.05 | 23.05 | 22.97 |
| 1.4 | 3 | 0 | | 23.19 | 23.08 | 22.96 |
| 1.4 | 3 | 1 | | 23.24 | 23.13 | 22.99 |
| 1.4 | 3 | 3 | | 23.23 | 23.19 | 23.10 |
| 1.4 | 6 | 0 | | 22.26 | 22.16 | 22.06 |
| 1.4 | 1 | 0 | 16-QAM | 22.46 | 22.18 | 22.22 |
| 1.4 | 1 | 3 | | 22.48 | 22.38 | 22.18 |
| 1.4 | 1 | 5 | | 22.47 | 22.23 | 22.28 |
| 1.4 | 3 | 0 | | 22.43 | 22.37 | 22.23 |
| 1.4 | 3 | 1 | | 22.49 | 22.48 | 22.27 |
| 1.4 | 3 | 3 | | 22.47 | 22.44 | 22.21 |
| 1.4 | 6 | 0 | | 21.09 | 21.00 | 20.93 |



| LTE Band 13 Maximum Average Power [dBm] | | | | | | |
|---|---------|-----------|--------|--------|--------|---------|
| BW [MHz] | RB Size | RB Offset | Mod | Lowest | Middle | Highest |
| 10 | 1 | 0 | QPSK | | 22.79 | |
| 10 | 1 | 25 | | | 22.78 | |
| 10 | 1 | 49 | | | 22.78 | |
| 10 | 25 | 0 | | | 21.90 | |
| 10 | 25 | 12 | | | 21.85 | |
| 10 | 25 | 25 | | | 21.70 | |
| 10 | 50 | 0 | | | 21.81 | |
| 10 | 1 | 0 | 16-QAM | | 22.07 | |
| 10 | 1 | 25 | | | 22.16 | |
| 10 | 1 | 49 | | | 21.52 | |
| 10 | 25 | 0 | | | 21.01 | |
| 10 | 25 | 12 | | | 20.86 | |
| 10 | 25 | 25 | | | 20.82 | |
| 10 | 50 | 0 | | | 20.82 | |
| 5 | 1 | 0 | QPSK | 22.70 | 22.79 | 22.83 |
| 5 | 1 | 12 | | 22.80 | 22.80 | 22.81 |
| 5 | 1 | 24 | | 22.82 | 22.79 | 22.69 |
| 5 | 12 | 0 | | 21.91 | 21.92 | 21.90 |
| 5 | 12 | 7 | | 21.86 | 21.84 | 21.81 |
| 5 | 12 | 13 | | 21.87 | 21.86 | 21.79 |
| 5 | 25 | 0 | | 21.91 | 21.94 | 21.87 |
| 5 | 1 | 0 | 16-QAM | 22.05 | 22.26 | 22.35 |
| 5 | 1 | 12 | | 21.93 | 22.13 | 22.05 |
| 5 | 1 | 24 | | 22.14 | 22.04 | 21.99 |
| 5 | 12 | 0 | | 20.85 | 20.86 | 20.92 |
| 5 | 12 | 7 | | 20.97 | 20.75 | 20.94 |
| 5 | 12 | 13 | | 20.79 | 20.78 | 20.81 |
| 5 | 25 | 0 | | 20.82 | 20.97 | 20.88 |



Peak-to-Average Ratio

| Mode | LTE Band 2 / 20MHz | | | | |
|------------|--------------------|---------|-------|---------|-------------|
| Mod. | QPSK | | 16QAM | | Limit: 13dB |
| RB Size | 1RB | Full RB | 1RB | Full RB | Result |
| Lowest CH | 4.52 | 5.16 | 5.30 | 6.14 | PASS |
| Middle CH | 4.81 | 5.13 | 5.71 | 6.20 | |
| Highest CH | 4.17 | 5.22 | 5.39 | 6.20 | |

| Mode | LTE Band 4 / 20MHz | | | | |
|------------|--------------------|---------|-------|---------|-------------|
| Mod. | QPSK | | 16QAM | | Limit: 13dB |
| RB Size | 1RB | Full RB | 1RB | Full RB | Result |
| Lowest CH | 4.20 | 4.84 | 5.22 | 5.91 | PASS |
| Middle CH | 4.29 | 4.93 | 5.42 | 5.94 | |
| Highest CH | 3.91 | 5.04 | 5.10 | 5.94 | |

| Mode | LTE Band 13 / 10MHz | | | | |
|------------|---------------------|---------|-------|---------|-------------|
| Mod. | QPSK | | 16QAM | | Limit: 13dB |
| RB Size | 1RB | Full RB | 1RB | Full RB | Result |
| Lowest CH | - | - | - | - | PASS |
| Middle CH | 4.35 | 5.22 | 5.30 | 6.12 | |
| Highest CH | - | - | - | - | |




LTE Band 2 / 20MHz / QPSK

Lowest Channel / 1RB




Date: 8 JUN 2016 18:33:59

Lowest Channel / Full RB



Date: 8 JUN 2016 18:34:14

Middle Channel / 1RB



Date: 8 JUN 2016 18:34:44

Middle Channel / Full RB




Date: 8 JUN 2016 18:34:27

Highest Channel / 1RB



Date: 8 JUN 2016 18:34:57

Highest Channel / Full RB



Date: 8 JUN 2016 18:35:09




LTE Band 2 / 20MHz / 16QAM

Lowest Channel / 1RB



Date: 8 JUN 2016 18:32:40

Lowest Channel / Full RB




Date: 8 JUN 2016 18:32:51

Middle Channel / 1RB




Date: 8 JUN 2016 18:33:01

Middle Channel / Full RB




Date: 8 JUN 2016 18:33:12

Highest Channel / 1RB



Date: 8 JUN 2016 18:33:22

Highest Channel / Full RB




Date: 8 JUN 2016 18:33:32



LTE Band 4 / 20MHz / QPSK

Lowest Channel / 1RB



Date: 10 JUN 2016 03:46:34

Lowest Channel / Full RB



Date: 10 JUN 2016 03:46:13

Middle Channel / 1RB



Date: 10 JUN 2016 03:46:58

Middle Channel / Full RB



Date: 10 JUN 2016 03:47:17

Highest Channel / 1RB



Date: 10 JUN 2016 03:47:52

Highest Channel / Full RB




Date: 10 JUN 2016 03:47:34




LTE Band 4 / 20MHz / 16QAM

Lowest Channel / 1RB




Date: 10 JUN 2016 03:43:13

Lowest Channel / Full RB




Date: 10 JUN 2016 03:43:26

Middle Channel / 1RB



Date: 10 JUN 2016 03:43:37

Middle Channel / Full RB




Date: 10 JUN 2016 03:44:15

Highest Channel / 1RB



Date: 10 JUN 2016 03:44:28

Highest Channel / Full RB




Date: 10 JUN 2016 03:44:40




LTE Band 13 / 10MHz / QPSK

Middle Channel/ 1RB



Date: 9 JUN 2016 22:24:35


Middle Channel / Full RB



Date: 9 JUN 2016 22:24:51


LTE Band 13 / 10MHz / 16QAM

Middle Channel/ 1RB



Date: 9 JUN 2016 22:24:20

Middle Channel / Full RB



Date: 9 JUN 2016 22:25:05



26dB Bandwidth

| Mode | LTE Band 2 : 26dB BW(MHz) | | | | | | | | | | | |
|------------|---------------------------|-------|------|-------|------|-------|-------|-------|-------|-------|-------|-------|
| | 1.4MHz | | 3MHz | | 5MHz | | 10MHz | | 15MHz | | 20MHz | |
| BW | QPSK | 16QAM | QPSK | 16QAM | QPSK | 16QAM | QPSK | 16QAM | QPSK | 16QAM | QPSK | 16QAM |
| Mod. | QPSK | 16QAM | QPSK | 16QAM | QPSK | 16QAM | QPSK | 16QAM | QPSK | 16QAM | QPSK | 16QAM |
| Lowest CH | 1.27 | 1.28 | 2.99 | 2.99 | 4.88 | 4.94 | 9.67 | 9.81 | 14.54 | 14.48 | 20.18 | 20.14 |
| Middle CH | 1.26 | 1.29 | 2.99 | 2.99 | 4.94 | 4.94 | 9.67 | 9.89 | 14.33 | 14.57 | 20.14 | 20.10 |
| Highest CH | 1.31 | 1.25 | 3.05 | 3.01 | 4.85 | 4.95 | 9.75 | 9.99 | 14.51 | 14.42 | 20.10 | 20.14 |


| Mode | LTE Band 4 : 26dB BW(MHz) | | | | | | | | | | | |
|------------|---------------------------|-------|------|-------|------|-------|-------|-------|-------|-------|-------|-------|
| | 1.4MHz | | 3MHz | | 5MHz | | 10MHz | | 15MHz | | 20MHz | |
| BW | QPSK | 16QAM | QPSK | 16QAM | QPSK | 16QAM | QPSK | 16QAM | QPSK | 16QAM | QPSK | 16QAM |
| Mod. | QPSK | 16QAM | QPSK | 16QAM | QPSK | 16QAM | QPSK | 16QAM | QPSK | 16QAM | QPSK | 16QAM |
| Lowest CH | 1.28 | 1.30 | 3.00 | 3.03 | 4.92 | 4.97 | 10.09 | 9.67 | 14.39 | 14.60 | 20.26 | 20.14 |
| Middle CH | 1.31 | 1.32 | 3.02 | 3.03 | 4.91 | 5.03 | 9.77 | 9.77 | 14.51 | 14.66 | 20.14 | 20.14 |
| Highest CH | 1.29 | 1.30 | 3.00 | 3.05 | 4.93 | 4.97 | 9.85 | 9.97 | 14.54 | 14.48 | 20.22 | 20.18 |

| Mode | LTE Band 13 : 26dB BW(MHz) | | | | | | | | | | | |
|------------|----------------------------|-------|------|-------|------|-------|-------|-------|-------|-------|-------|-------|
| | 1.4MHz | | 3MHz | | 5MHz | | 10MHz | | 15MHz | | 20MHz | |
| BW | QPSK | 16QAM | QPSK | 16QAM | QPSK | 16QAM | QPSK | 16QAM | QPSK | 16QAM | QPSK | 16QAM |
| Mod. | QPSK | 16QAM | QPSK | 16QAM | QPSK | 16QAM | QPSK | 16QAM | QPSK | 16QAM | QPSK | 16QAM |
| Lowest CH | - | - | - | - | 4.87 | 4.93 | - | - | - | - | - | - |
| Middle CH | - | - | - | - | 4.97 | 4.93 | 9.79 | 9.69 | - | - | - | - |
| Highest CH | - | - | - | - | 4.91 | 4.97 | - | - | - | - | - | - |




LTE Band 2

Lowest Channel / 1.4MHz / QPSK




Date: 8 JUN 2016 16:22:27

Lowest Channel / 1.4MHz / 16QAM




Date: 8 JUN 2016 16:22:38

Middle Channel / 1.4MHz / QPSK




Date: 8 JUN 2016 16:29:33

Middle Channel / 1.4MHz / 16QAM




Date: 8 JUN 2016 16:29:43

Highest Channel / 1.4MHz / QPSK



Date: 8 JUN 2016 16:32:06

Highest Channel / 1.4MHz / 16QAM




Date: 8 JUN 2016 16:32:16



LTE Band 2

Lowest Channel / 3MHz / QPSK




Date: 8 JUN 2016 16:39:11

Lowest Channel / 3MHz / 16QAM




Date: 8 JUN 2016 16:39:21

Middle Channel / 3MHz / QPSK




Date: 8 JUN 2016 16:46:16

Middle Channel / 3MHz / 16QAM




Date: 8 JUN 2016 16:46:26

Highest Channel / 3MHz / QPSK



Date: 8 JUN 2016 16:48:49

Highest Channel / 3MHz / 16QAM




Date: 8 JUN 2016 16:48:59




LTE Band 2

Lowest Channel / 5MHz / QPSK




Date: 8 JUN 2016 16:55:55

Lowest Channel / 5MHz / 16QAM




Date: 8 JUN 2016 16:56:05

Middle Channel / 5MHz / QPSK




Date: 8 JUN 2016 17:03:00

Middle Channel / 5MHz / 16QAM




Date: 8 JUN 2016 17:03:11

Highest Channel / 5MHz / QPSK



Date: 8 JUN 2016 17:05:33

Highest Channel / 5MHz / 16QAM




Date: 8 JUN 2016 17:05:44



LTE Band 2

Lowest Channel / 10MHz / QPSK




Date: 8 JUN 2016 17:12:38

Lowest Channel / 10MHz / 16QAM



Date: 8 JUN 2016 17:12:49

Middle Channel / 10MHz / QPSK




Date: 8 JUN 2016 17:19:43

Middle Channel / 10MHz / 16QAM




Date: 8 JUN 2016 17:19:53

Highest Channel / 10MHz / QPSK



Date: 8 JUN 2016 17:22:15

Highest Channel / 10MHz / 16QAM



Date: 8 JUN 2016 17:22:26




LTE Band 2

Lowest Channel / 15MHz / QPSK




Date: 8 JUN 2016 17:29:20

Lowest Channel / 15MHz / 16QAM




Date: 8 JUN 2016 17:29:30

Middle Channel / 15MHz / QPSK




Date: 8 JUN 2016 17:36:24

Middle Channel / 15MHz / 16QAM




Date: 8 JUN 2016 17:36:35

Highest Channel / 15MHz / QPSK



Date: 8 JUN 2016 17:38:57

Highest Channel / 15MHz / 16QAM



Date: 8 JUN 2016 17:39:07