



FCC RF Test Report

APPLICANT : ZTE CORPORATION
EQUIPMENT : LTE/WCDMA/CDMA/GSM(GPRS)
Multi-Mode Digital Mobile Phone
BRAND NAME : ZTE
MODEL NAME : Z610DL
FCC ID : SRQ-Z610DL
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System

The product was received on Oct. 20, 2017 and testing was completed on Dec. 03, 2017. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.



Approved by: James Huang / Manager

Sporton International (Kunshan) Inc.
No.3-2 Ping-Xiang Rd, Kunshan Development Zone Kunshan City Jiangsu Province 215335
China



TABLE OF CONTENTS

1 GENERAL DESCRIPTION 5

1.1 Applicant 5

1.2 Manufacturer 5

1.3 Product Feature of Equipment Under Test 5

1.4 Product Specification of Equipment Under Test 6

1.5 Modification of EUT 6

1.6 Testing Location 6

1.7 Applicable Standards 7

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST 8

2.1 Carrier Frequency and Channel 8

2.2 Test Mode 9

2.3 Connection Diagram of Test System 10

2.4 Support Unit used in test configuration and system 11

2.5 EUT Operation Test Setup 11

2.6 Measurement Results Explanation Example 11

3 TEST RESULT 12

3.1 6dB Bandwidth Measurement 12

3.2 Output Power Measurement 14

3.3 Power Spectral Density Measurement 15

3.4 Conducted Band Edges and Spurious Emission Measurement 17

3.5 Radiated Band Edges and Spurious Emission Measurement 30

3.6 AC Conducted Emission Measurement 34

3.7 Antenna Requirements 38

4 LIST OF MEASURING EQUIPMENT 39

5 UNCERTAINTY OF EVALUATION 40

APPENDIX A. CONDUCTED TEST RESULTS

APPENDIX B. RADIATED SPURIOUS EMISSION

APPENDIX C. DUTY CYCLE PLOTS

APPENDIX D. SETUP PHOTOGRAPHS



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.2	15.247(b)	Power Output Measurement	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
		Conducted Spurious Emission		Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 7.67 dB at 43.58 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 6.04 dB at 0.152 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-



1 General Description

1.1 Applicant

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

1.2 Manufacturer

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	LTE/WCDMA/CDMA/GSM(GPRS) Multi-Mode Digital Mobile Phone
Brand Name	ZTE
Model Name	Z610DL
FCC ID	SRQ-Z610DL
EUT supports Radios application	CDMA/EV-DO/GSM/GPRS/EGPRS/WCDMA/HSPA/HSPA+ (16QAM uplink is not supported)/LTE/WLAN 2.4GHz 802.11b/g/n HT20/HT40 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80 Bluetooth v3.0 + EDR / Bluetooth v4.0 LE / Bluetooth v4.1 LE / Bluetooth v4.2 LE
IMEI Code	Conducted: 990008950012315/990008950012301 Conduction: 990008950012810 Radiation: 990008950013230/990008950013201
HW Version	Z610DLHW1.0
SW Version	Z610DLV1.0.0B03
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Channel Frequency Range	2412 MHz ~ 2462 MHz
Maximum (Peak) Output Power to antenna	802.11b : 17.54 dBm (0.0568 W) 802.11g : 22.75 dBm (0.1884 W) 802.11n HT20 : 22.39 dBm (0.1734 W) 802.11n HT40 : 22.27 dBm (0.1687 W)
Antenna Type / Gain	PIFA Antenna with gain 0.67 dBi
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Sporton International (Kunshan) Inc. is accredited to ISO 17025 by National Voluntary Laboratory Accreditation Program (NVLAP code: 600155-0) and the FCC designation No is CN5013.

Test Site	Sporton International (Kunshan) Inc.			
Test Site Location	No.3-2 Ping-Xiang Rd, Kunshan Development Zone Kunshan City Jiangsu Province 215335 China TEL : +86-512-57900158 FAX : +86-512-57900958			
Test Site No.	Sporton Site No.			FCC Test Firm Registration No.
	TH01-KS	03CH02-KS	CO01-KS	630927

Note: The test site complies with ANSI C63.4 2014 requirement.



1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz) and radiated emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases were recorded in this report.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437	-	-



2.2 Test Mode


Final test mode of conducted test items and radiated spurious emissions are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0


Test Cases	
AC Conducted Emission	Mode 1 : GSM850 Idle + Bluetooth Link + WLAN Link(2.4G) + Earphone + USB Cable (Charging from Adapter 1)
Remark: For Radiated TCs, the tests were performed with Adapter, Earphone and USB Cable.	

2.3 Connection Diagram of Test System

<WLAN Tx Mode>



<AC Conducted Emission Mode>



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	WLAN AP	LINKSYS	WRT600N	Q87-WRT600NV11	N/A	Unshielded, 1.8 m
3.	Notebook	Lenovo	G40-80	PRC4	N/A	shielded cable DC O/P 1.8m , Unshielded AC I/P cable 1.8m
4.	Bluetooth Earphone	Lenovo	LBH308	NA	N/A	N/A
5.	Earphone	Lenovo	LH102	NA	Unshielded, 1.2m	N/A
6.	SD Card	Kingston	SDC4/4GB	N/A	N/A	N/A

2.5 EUT Operation Test Setup

For WLAN function, the engineering test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss.

Following shows an offset computation example with cable loss 5.8 dB.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)}. \\ &= 5.8 \text{ (dB)} \end{aligned}$$

3 Test Result

3.1 6dB Bandwidth Measurement

3.1.1 Limit of 6dB Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v04.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. Measure and record the results in the test report.


3.1.4 Test Setup





3.1.5 Test Result of 6dB Occupied Bandwidth

Please refer to Appendix A.



3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi are used the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v04 section 9.1.2 PKPM1 Peak power meter method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.2.6 Test Result of Average output Power (Reporting Only)

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.


3.3.4 Test Setup





3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement.


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


3.4.4 Test Setup





3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Test Mode :	802.11b	Temperature :	21~25°C
Test Band :	2.4GHz Low	Relative Humidity :	51~55%
Test Channel :	01	Test Engineer :	Silent Hai







Test Mode :	802.11b	Temperature :	21~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	51~55%
Test Channel :	06	Test Engineer :	Silent Hai

WLAN 802.11b Channel 06


100kHz PSD reference Level



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz






Test Mode :	802.11b	Temperature :	21~25°C
Test Band :	2.4GHz High	Relative Humidity :	51~55%
Test Channel :	11	Test Engineer :	Silent Hai


WLAN 802.11b Channel 11

100kHz PSD reference Level




Date: 31.OCT.2017 17:58:19

High Channel Plot




Date: 31.OCT.2017 17:58:38

Spurious Emission 30MHz~3GHz



Date: 31.OCT.2017 17:58:48

Spurious Emission 2GHz~25GHz




Date: 31.OCT.2017 17:59:04



Test Mode :	802.11g	Temperature :	21~25°C
Test Band :	2.4GHz Low	Relative Humidity :	51~55%
Test Channel :	01	Test Engineer :	Silent Hai


WLAN 802.11g Channel 01

100kHz PSD reference Level




Date: 31.OCT.2017 18:01:54

Low Channel Plot




Date: 31.OCT.2017 18:03:15

Spurious Emission 30MHz~3GHz



Date: 31.OCT.2017 18:05:57

Spurious Emission 2GHz~25GHz




Date: 31.OCT.2017 18:03:53




Test Mode :	802.11g	Temperature :	21~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	51~55%
Test Channel :	06	Test Engineer :	Silent Hai

WLAN 802.11g Channel 06


100kHz PSD reference Level



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz






Test Mode :	802.11g	Temperature :	21~25°C
Test Band :	2.4GHz High	Relative Humidity :	51~55%
Test Channel :	11	Test Engineer :	Silent Hai


WLAN 802.11g Channel 11

100kHz PSD reference Level




Date: 31.OCT.2017 18:15:00

High Channel Plot




Date: 31.OCT.2017 18:16:11

Spurious Emission 30MHz~3GHz



Date: 31.OCT.2017 18:19:59


Spurious Emission 2GHz~25GHz



Date: 31.OCT.2017 18:17:07



Test Mode :	802.11n HT20	Temperature :	21~25°C
Test Band :	2.4GHz Low	Relative Humidity :	51~55%
Test Channel :	01	Test Engineer :	Silent Hai







Test Mode :	802.11n HT20	Temperature :	21~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	51~55%
Test Channel :	06	Test Engineer :	Silent Hai

WLAN 802.11n HT20 Channel 06


100kHz PSD reference Level



Spurious Emission 30MHz~3GHz




Spurious Emission 2GHz~25GHz






Test Mode :	802.11n HT20	Temperature :	21~25°C
Test Band :	2.4GHz High	Relative Humidity :	51~55%
Test Channel :	11	Test Engineer :	Silent Hai





Test Mode :	802.11n HT40	Temperature :	21~25°C
Test Band :	2.4GHz Low	Relative Humidity :	51~55%
Test Channel :	03	Test Engineer :	Silent Hai






Test Mode :	802.11n HT40	Temperature :	21~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	51~55%
Test Channel :	06	Test Engineer :	Silent Hai


WLAN 802.11n HT20 Channel 06

100kHz PSD reference Level




Date: 21.NOV.2017 08:38:48

Spurious Emission 30MHz~3GHz



Date: 21.NOV.2017 08:39:28


Spurious Emission 2GHz~25GHz



Date: 21.NOV.2017 08:40:10



Test Mode :	802.11n HT40	Temperature :	21~25°C
Test Band :	2.4GHz High	Relative Humidity :	51~55%
Test Channel :	09	Test Engineer :	Silent Hai





3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.



3.5.3 Test Procedures


1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.

For average measurement:


 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B.

3.5.7 Duty Cycle

Please refer to Appendix C.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B.



3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dBµV)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.


3.6.4 Test Setup





3.6.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	22~24°C
Test Engineer :	Amos Zhang	Relative Humidity :	43~46%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link(2.4G) + Earphone + USB Cable (Charging from Adapter 1)		




Site : CO01-KS
 Condition : FCC PART 15C LISN-L-171013-060103 LINE

mode : Mode 1
 : 990008950012810 #9

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1 *	0.152	59.87	-6.04	65.91	49.10	0.16	10.61	QP
2	0.152	43.97	-11.94	55.91	33.20	0.16	10.61	Average
3	0.166	53.03	-12.13	65.16	42.30	0.17	10.56	QP
4	0.166	36.93	-18.23	55.16	26.20	0.17	10.56	Average
5	0.187	50.88	-13.27	64.15	40.20	0.19	10.49	QP
6	0.187	35.28	-18.87	54.15	24.60	0.19	10.49	Average
7	0.207	50.56	-12.76	63.32	39.91	0.20	10.45	QP
8	0.207	35.86	-17.46	53.32	25.21	0.20	10.45	Average
9	0.226	47.75	-14.86	62.61	37.09	0.21	10.45	QP
10	0.226	32.95	-19.66	52.61	22.29	0.21	10.45	Average
11	0.246	46.15	-15.76	61.91	35.50	0.21	10.44	QP
12	0.246	31.25	-20.66	51.91	20.60	0.21	10.44	Average
13	0.317	42.95	-16.85	59.80	32.30	0.23	10.42	QP
14	0.317	27.45	-22.35	49.80	16.80	0.23	10.42	Average
15	0.385	42.25	-15.92	58.17	31.60	0.24	10.41	QP
16	0.385	33.95	-14.22	48.17	23.30	0.24	10.41	Average
17	0.474	39.19	-17.26	56.45	28.60	0.26	10.33	QP
18	0.474	31.89	-14.56	46.45	21.30	0.26	10.33	Average



Test Mode :	Mode 1	Temperature :	22~24°C
Test Engineer :	Amos Zhang	Relative Humidity :	43~46%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link(2.4G) + Earphone + USB Cable (Charging from Adapter 1)		



Site : CO01-KS
 Condition : FCC PART 15C LISN-N-171013-060103 NEUTRAL

mode : Mode 1
 : 990008950012810 #9

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1 *	0.159	51.17	-14.35	65.52	40.30	0.28	10.59	QP
2	0.159	34.07	-21.45	55.52	23.20	0.28	10.59	Average
3	0.175	47.41	-17.31	64.72	36.60	0.28	10.53	QP
4	0.175	30.31	-24.41	54.72	19.50	0.28	10.53	Average
5	0.199	48.04	-15.63	63.67	37.30	0.28	10.46	QP
6	0.199	31.34	-22.33	53.67	20.60	0.28	10.46	Average
7	0.211	46.53	-16.65	63.18	35.80	0.28	10.45	QP
8	0.211	31.03	-22.15	53.18	20.30	0.28	10.45	Average
9	0.237	43.33	-18.89	62.22	32.61	0.28	10.44	QP
10	0.237	27.33	-24.89	52.22	16.61	0.28	10.44	Average
11	0.253	43.02	-18.62	61.64	32.30	0.28	10.44	QP
12	0.253	27.92	-23.72	51.64	17.20	0.28	10.44	Average



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Oct. 12, 2017	Oct. 31, 2017~ Nov. 21, 2017	Oct. 11, 2018	Conducted (TH01-KS)
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Aug. 08, 2017	Oct. 31, 2017~ Nov. 21, 2017	Aug. 07, 2018	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 19, 2017	Oct. 31, 2017~ Nov. 21, 2017	Jan. 18, 2018	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 19, 2017	Oct. 31, 2017~ Nov. 21, 2017	Jan. 18, 2018	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESR7	101403	9kHz~7GHz; Max 30dBm	Aug. 08, 2017	Dec. 03, 2017	Aug. 07, 2018	Radiation (03CH02-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY551502 08	10Hz~44GHz, MAX 30dB	Apr. 18, 2017	Dec. 03, 2017	Apr. 17, 2018	Radiation (03CH02-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Oct. 22, 2017	Dec. 03, 2017	Oct. 21, 2018	Radiation (03CH02-KS)
Bilog Antenna	TeseQ	CBL6112D	23182	30MHz~2GHz	Jan. 22, 2017	Dec. 03, 2017	Jan. 21, 2018	Radiation (03CH02-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75957	1GHz~18GHz	Oct. 21, 2017	Dec. 03, 2017	Oct. 20, 2018	Radiation (03CH02-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA1702 49	15GHz~40GHz	Feb. 15, 2017	Dec. 03, 2017	Feb. 14, 2018	Radiation (03CH02-KS)
Amplifier	SONOMA	310N	187289	9kHz~1GHz	Aug. 07, 2017	Dec. 03, 2017	Aug. 06, 2018	Radiation (03CH02-KS)
high gain Amplifier	MITEQ	AMF-7D-0010 1800-30-10P	2012228	100MHz~18GHz	Apr. 18, 2017	Dec. 03, 2017	Apr. 17, 2018	Radiation (03CH02-KS)
Amplifier	Agilent	8449B	3008A023 84	1GHz~26.5GHz	Oct. 12, 2017	Dec. 03, 2017	Oct. 11, 2018	Radiation (03CH02-KS)
Amplifier	MITEQ	TTA1840-35- HG	1887435	18GHz~40GHz	Oct. 12, 2017	Dec. 03, 2017	Oct. 11, 2018	Radiation (03CH02-KS)
AC Power Source	Chroma	61601	616010002 473	N/A	NCR	Dec. 03, 2017	NCR	Radiation (03CH02-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	Dec. 03, 2017	NCR	Radiation (03CH02-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	Dec. 03, 2017	NCR	Radiation (03CH02-KS)
EMI Receiver	R&S	ESC17	100768	9kHz~7GHz;	Apr. 20, 2017	Nov. 23, 2017	Apr. 19, 2018	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Oct. 13, 2017	Nov. 23, 2017	Oct. 12, 2018	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Oct. 13, 2017	Nov. 23, 2017	Oct. 12, 2018	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP00000 0811	AC 0V~300V, 45Hz~1000Hz	Oct. 12, 2017	Nov. 23, 2017	Oct. 11, 2018	Conduction (CO01-KS)

NCR: No Calibration Required



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.3dB
---	-------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.2dB
---	-------

Uncertainty of Radiated Emission Measurement (1GHz ~ 18GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.7dB
---	-------

Uncertainty of Radiated Emission Measurement (18GHz ~ 40GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.3dB
---	-------



Appendix A. Conducted Test Results

A1 - DTS Part

Test Engineer:	Silent Hai	Temperature:	21~25	°C
Test Date:	2017/10/31	Relative Humidity:	51~55	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

2.4GHz Band								
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
11b	1Mbps	1	1	2412	13.34	8.53	0.50	Pass
11b	1Mbps	1	6	2437	13.24	8.55	0.50	Pass
11b	1Mbps	1	11	2462	13.49	8.07	0.50	Pass
11g	6Mbps	1	1	2412	18.38	16.34	0.50	Pass
11g	6Mbps	1	6	2437	18.23	16.34	0.50	Pass
11g	6Mbps	1	11	2462	18.68	16.34	0.50	Pass
HT20	MCS0	1	1	2412	19.08	17.54	0.50	Pass
HT20	MCS0	1	6	2437	19.08	17.56	0.50	Pass
HT20	MCS0	1	11	2462	19.23	17.58	0.50	Pass
HT40	MCS0	1	3	2422	36.36	35.12	0.50	Pass
HT40	MCS0	1	6	2437	36.36	35.12	0.50	Pass
HT40	MCS0	1	9	2452	36.96	35.68	0.50	Pass

TEST RESULTS DATA
Peak Power Table

2.4GHz Band										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
11b	1Mbps	1	1	2412	17.14	30.00	0.67	17.81	36.00	Pass
11b	1Mbps	1	6	2437	17.54	30.00	0.67	18.21	36.00	Pass
11b	1Mbps	1	11	2462	16.95	30.00	0.67	17.62	36.00	Pass
11g	6Mbps	1	1	2412	22.43	30.00	0.67	23.10	36.00	Pass
11g	6Mbps	1	6	2437	22.75	30.00	0.67	23.42	36.00	Pass
11g	6Mbps	1	11	2462	22.11	30.00	0.67	22.78	36.00	Pass
HT20	MCS0	1	1	2412	21.63	30.00	0.67	22.30	36.00	Pass
HT20	MCS0	1	6	2437	22.39	30.00	0.67	23.06	36.00	Pass
HT20	MCS0	1	11	2462	21.13	30.00	0.67	21.80	36.00	Pass
HT40	MCS0	1	3	2422	22.27	30.00	0.67	22.94	36.00	Pass
HT40	MCS0	1	6	2437	21.95	30.00	0.67	22.62	36.00	Pass
HT40	MCS0	1	9	2452	21.51	30.00	0.67	22.18	36.00	Pass

TEST RESULTS DATA
Average Power Table
(Reporting Only)

2.4GHz Band						
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
11b	1Mbps	1	1	2412	0.11	14.43
11b	1Mbps	1	6	2437	0.11	14.97
11b	1Mbps	1	11	2462	0.11	14.07
11g	6Mbps	1	1	2412	0.58	12.90
11g	6Mbps	1	6	2437	0.58	13.16
11g	6Mbps	1	11	2462	0.58	12.59
HT20	MCS0	1	1	2412	0.64	12.00
HT20	MCS0	1	6	2437	0.64	12.15
HT20	MCS0	1	11	2462	0.64	11.56
HT40	MCS0	1	3	2422	0.66	12.03
HT40	MCS0	1	6	2437	0.66	11.75
HT40	MCS0	1	9	2452	0.66	11.42

TEST RESULTS DATA
Peak Power Density

2.4GHz Band								
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
11b	1Mbps	1	1	2412	-8.34	0.67	8.00	Pass
11b	1Mbps	1	6	2437	-7.84	0.67	8.00	Pass
11b	1Mbps	1	11	2462	-8.45	0.67	8.00	Pass
11g	6Mbps	1	1	2412	-10.29	0.67	8.00	Pass
11g	6Mbps	1	6	2437	-12.21	0.67	8.00	Pass
11g	6Mbps	1	11	2462	-12.61	0.67	8.00	Pass
HT20	MCS0	1	1	2412	-12.69	0.67	8.00	Pass
HT20	MCS0	1	6	2437	-13.23	0.67	8.00	Pass
HT20	MCS0	1	11	2462	-14.05	0.67	8.00	Pass
HT40	MCS0	1	3	2422	-16.17	0.67	8.00	Pass
HT40	MCS0	1	6	2437	-16.02	0.67	8.00	Pass
HT40	MCS0	1	9	2452	-16.92	0.67	8.00	Pass



Appendix B. Radiated Spurious Emission

15C 2.4GHz 2400~2483.5MHz

WIFI 802.11b (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		2385.66	51.45	-22.55	74	46.19	31.3	5.14	31.18	100	324	P	H
		2386.57	40.61	-13.39	54	35.35	31.3	5.14	31.18	100	324	A	H
	*	2414	104.63	-	-	98.96	31.33	5.16	30.82	100	324	P	H
	*	2414	101.31	-	-	95.64	31.33	5.16	30.82	100	324	A	H
		2387.22	50.96	-23.04	74	45.7	31.3	5.14	31.18	350	120	P	V
		2389.95	39.82	-14.18	54	34.2	31.3	5.14	30.82	350	120	A	V
	*	2412	98.89	-	-	93.22	31.33	5.16	30.82	350	120	P	V
	*	2412	95.69	-	-	90.02	31.33	5.16	30.82	350	120	A	V
802.11b CH 06 2437MHz		2334.96	50.74	-23.26	74	46.33	31.22	5.09	31.9	100	328	P	H
		2389.69	39.97	-14.03	54	34.71	31.3	5.14	31.18	100	328	A	H
	*	2436	103.29	-	-	97.5	31.36	5.19	30.76	100	328	P	H
	*	2436	100.14	-	-	94.35	31.36	5.19	30.76	100	328	A	H
		2483.62	50.18	-23.82	74	44.13	31.44	5.24	30.63	100	328	P	H
		2491.72	39.26	-14.74	54	33.18	31.47	5.24	30.63	100	328	A	H
		2379.29	50.23	-23.77	74	45.02	31.27	5.12	31.18	300	58	P	V
		2389.3	39.5	-14.5	54	34.24	31.3	5.14	31.18	300	58	A	V
	*	2436	97.89	-	-	92.1	31.36	5.19	30.76	300	58	P	V
	*	2436	93.78	-	-	87.99	31.36	5.19	30.76	300	58	A	V
		2494.18	50.29	-23.71	74	44.15	31.47	5.24	30.57	300	58	P	V
	2493.58	39.26	-14.74	54	33.12	31.47	5.24	30.57	300	58	A	V	



802.11b CH 11 2462MHz	*	2462	104.09	-	-	98.16	31.41	5.21	30.69	100	320	P	H
	*	2464	101	-	-	95.07	31.41	5.21	30.69	100	320	A	H
		2483.8	50.86	-23.14	74	44.81	31.44	5.24	30.63	100	320	P	H
		2486.68	40.34	-13.66	54	34.29	31.44	5.24	30.63	100	320	A	H
	*	2462	99.26	-	-	93.33	31.41	5.21	30.69	372	150	P	V
	*	2464	96.14	-	-	90.21	31.41	5.21	30.69	372	150	A	V
		2491.84	50.61	-23.39	74	44.47	31.47	5.24	30.57	372	150	P	V
		2487.22	39.56	-14.44	54	33.51	31.44	5.24	30.63	372	150	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz

WIFI 802.11b (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		4824	41.06	-32.94	74	62.22	35.65	7.72	64.53	100	360	P	H
		4824	42.34	-31.66	74	63.5	35.65	7.72	64.53	100	360	P	V
802.11b CH 06 2437MHz		4872	42.75	-31.25	74	63.99	35.61	7.75	64.6	100	0	P	H
		7308	41.58	-32.42	74	61.41	35.89	9.29	65.01	100	0	P	H
		4872	41.95	-32.05	74	63.19	35.61	7.75	64.6	100	0	P	V
		7308	40.45	-33.55	74	60.28	35.89	9.29	65.01	100	0	P	V
802.11b CH 11 2462MHz		4926	41.33	-32.67	74	62.64	35.57	7.8	64.68	100	360	P	H
		7386	41.43	-32.57	74	61.17	35.94	9.37	65.05	100	360	P	H
		4926	41.77	-32.23	74	63.08	35.57	7.8	64.68	100	360	P	V
		7386	40.43	-33.57	74	60.17	35.94	9.37	65.05	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz
WIFI 802.11g (Band Edge @ 3m)

Table with 14 columns: WIFI, Note, Frequency, Level, Over, Limit, Read, Antenna, Cable, Preamp, Ant, Table, Peak, Pol. It contains two main sections of data for 802.11g channels 01 and 06.



802.11g CH 11 2462MHz	*	2458	103.52	-	-	97.59	31.41	5.21	30.69	182	276	P	H
	*	2458	95.48	-	-	89.55	31.41	5.21	30.69	182	276	A	H
		2483.8	55.89	-18.11	74	49.84	31.44	5.24	30.63	182	276	P	H
		2483.51	43.16	-10.84	54	37.11	31.44	5.24	30.63	182	276	A	H
	*	2468	99.25	-	-	93.26	31.41	5.21	30.63	331	156	P	V
	*	2468	91.46	-	-	85.47	31.41	5.21	30.63	331	156	A	V
		2483.8	54.85	-19.15	74	48.8	31.44	5.24	30.63	331	156	P	V
		2483.51	41.9	-12.1	54	35.85	31.44	5.24	30.63	331	156	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz

WIFI 802.11g (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11g CH 01 2412MHz		4824	41.39	-32.61	74	62.55	35.65	7.72	64.53	100	360	P	H
		4824	40.84	-33.16	74	62	35.65	7.72	64.53	100	360	P	V
802.11g CH 06 2437MHz		4872	42.13	-31.87	74	63.37	35.61	7.75	64.6	100	360	P	H
		7308	42.05	-31.95	74	61.88	35.89	9.29	65.01	100	360	P	H
		4872	42.74	-31.26	74	63.98	35.61	7.75	64.6	100	360	P	V
		7308	41.11	-32.89	74	60.94	35.89	9.29	65.01	100	360	P	V
802.11g CH 11 2462MHz		4926	40.4	-33.6	74	61.71	35.57	7.8	64.68	100	360	P	H
		7386	40.46	-33.54	74	60.2	35.94	9.37	65.05	100	360	P	H
		4926	39.84	-34.16	74	61.15	35.57	7.8	64.68	100	360	P	V
		7386	39.91	-34.09	74	59.65	35.94	9.37	65.05	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**15C 2.4GHz 2400~2483.5MHz
WIFI 802.11n HT20 (Band Edge @ 3m)**

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT20 CH 01 2412MHz		2388.78	53.53	-20.47	74	48.27	31.3	5.14	31.18	100	290	P	H
		2389.82	42.4	-11.6	54	36.78	31.3	5.14	30.82	100	290	A	H
	*	2418	103.67	-	-	97.94	31.33	5.16	30.76	100	290	P	H
	*	2418	96.13	-	-	90.4	31.33	5.16	30.76	100	290	A	H
		2389.95	50.36	-23.64	74	44.74	31.3	5.14	30.82	297	137	P	V
		2389.95	40.57	-13.43	54	34.95	31.3	5.14	30.82	297	137	A	V
	*	2420	101	-	-	95.24	31.36	5.16	30.76	297	137	P	V
	2420	93.21	-	-	87.45	31.36	5.16	30.76	297	137	A	V	
802.11n HT20 CH 06 2437MHz		2383.84	52.62	-21.38	74	47.39	31.27	5.14	31.18	108	314	P	H
		2385.01	42.53	-11.47	54	37.3	31.27	5.14	31.18	108	314	A	H
	*	2432	103.17	-	-	97.38	31.36	5.19	30.76	108	314	P	H
	*	2430	94.66	-	-	88.87	31.36	5.19	30.76	108	314	A	H
		2487.58	51.61	-22.39	74	45.53	31.47	5.24	30.63	108	314	P	H
		2488.66	41.11	-12.89	54	35.03	31.47	5.24	30.63	108	314	A	H
		2363.43	51.57	-22.43	74	46.74	31.25	5.12	31.54	100	338	P	V
		2385.66	40.51	-13.49	54	35.25	31.3	5.14	31.18	100	338	A	V
	*	2436	97	-	-	91.21	31.36	5.19	30.76	100	338	P	V
	*	2432	89.18	-	-	83.39	31.36	5.19	30.76	100	338	A	V
		2499.88	50.79	-23.21	74	44.65	31.47	5.24	30.57	100	338	P	V
	2495.38	40.16	-13.84	54	34.02	31.47	5.24	30.57	100	338	A	V	



802.11n HT20 CH 11 2462MHz	*	2464	103.2	-	-	97.27	31.41	5.21	30.69	100	235	P	H
	*	2468	95.31	-	-	89.32	31.41	5.21	30.63	100	235	A	H
		2484.52	53.85	-20.15	74	47.8	31.44	5.24	30.63	100	235	P	H
		2483.62	42.55	-11.45	54	36.5	31.44	5.24	30.63	100	235	A	H
	*	2466	100.43	-	-	94.5	31.41	5.21	30.69	326	240	P	V
	*	2466	92.16	-	-	86.23	31.41	5.21	30.69	326	240	A	V
		2484.04	54.13	-19.87	74	48.08	31.44	5.24	30.63	326	240	P	V
		2483.51	42	-12	54	35.95	31.44	5.24	30.63	326	240	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**15C 2.4GHz 2400~2483.5MHz
WIFI 802.11n HT20 (Harmonic @ 3m)**

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT20 CH 01 2412MHz		4824	41.82	-32.18	74	62.98	35.65	7.72	64.53	100	360	P	H
		4824	41.63	-32.37	74	62.79	35.65	7.72	64.53	100	360	P	V
802.11n HT20 CH 06 2437MHz		4872	43.11	-30.89	74	64.35	35.61	7.75	64.6	100	360	P	H
		7308	40.68	-33.32	74	60.51	35.89	9.29	65.01	100	360	P	H
		4872	41.79	-32.21	74	63.03	35.61	7.75	64.6	100	360	P	V
		7308	40.8	-33.2	74	60.63	35.89	9.29	65.01	100	360	P	V
802.11n HT20 CH 11 2462MHz		4926	40.64	-33.36	74	61.95	35.57	7.8	64.68	100	360	P	H
		7386	42.02	-31.98	74	61.76	35.94	9.37	65.05	100	360	P	H
		4926	39.88	-34.12	74	61.19	35.57	7.8	64.68	100	360	P	V
		7386	41.03	-32.97	74	60.77	35.94	9.37	65.05	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**15C 2.4GHz 2400~2483.5MHz
WIFI 802.11n HT40 (Band Edge @ 3m)**

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT40 CH 03 2422MHz		2389.95	55.13	-18.87	74	49.51	31.3	5.14	30.82	100	65	P	H
		2389.95	42.53	-11.47	54	36.91	31.3	5.14	30.82	100	65	A	H
	*	2430	100.82	-	-	95.03	31.36	5.19	30.76	100	65	P	H
	*	2430	92.05	-	-	86.26	31.36	5.19	30.76	100	65	A	H
		2494.06	50.44	-23.56	74	44.3	31.47	5.24	30.57	100	65	P	H
		2485.78	40.13	-13.87	54	34.08	31.44	5.24	30.63	100	65	A	H
		2361.35	50.71	-23.29	74	45.88	31.25	5.12	31.54	300	285	P	V
		2389.43	40.57	-13.43	54	35.31	31.3	5.14	31.18	300	285	A	V
	*	2418	92.49	-	-	86.76	31.33	5.16	30.76	300	285	P	V
	*	2412	85.2	-	-	79.53	31.33	5.16	30.82	300	285	A	V
		2489.68	50.75	-23.25	74	44.67	31.47	5.24	30.63	300	285	P	V
		2497.18	39.92	-14.08	54	33.78	31.47	5.24	30.57	300	285	A	V
802.11n HT40 CH 06 2437MHz		2383.84	51.11	-22.89	74	45.88	31.27	5.14	31.18	100	290	P	H
		2389.69	41.04	-12.96	54	35.78	31.3	5.14	31.18	100	290	A	H
	*	2432	99.77	-	-	93.98	31.36	5.19	30.76	100	290	P	H
	*	2432	91.9	-	-	86.11	31.36	5.19	30.76	100	290	A	H
		2484.4	50.6	-23.4	74	44.55	31.44	5.24	30.63	100	290	P	H
		2483.5	40.65	-13.35	54	34.6	31.44	5.24	30.63	100	290	A	H
		2389.82	50.64	-23.36	74	45.02	31.3	5.14	30.82	300	127	P	V
		2388.26	40.35	-13.65	54	35.09	31.3	5.14	31.18	300	127	A	V
	*	2446	95.8	-	-	89.91	31.39	5.19	30.69	300	127	P	V
	*	2448	87.76	-	-	81.87	31.39	5.19	30.69	300	127	A	V
		2491.54	50.19	-23.81	74	44.11	31.47	5.24	30.63	300	127	P	V
		2484.76	39.84	-14.16	54	33.79	31.44	5.24	30.63	300	127	A	V



802.11n HT40 CH 09 2452MHz		2363.95	50.56	-23.44	74	45.73	31.25	5.12	31.54	100	306	P	H
		2389.69	40.46	-13.54	54	35.2	31.3	5.14	31.18	100	306	A	H
	*	2440	97.99	-	-	92.17	31.39	5.19	30.76	100	306	P	H
	*	2444	90.19	-	-	84.3	31.39	5.19	30.69	100	306	A	H
		2484.22	56.69	-17.31	74	50.64	31.44	5.24	30.63	100	306	P	H
		2483.68	41.94	-12.06	54	35.89	31.44	5.24	30.63	100	306	A	H
		2385.53	50.55	-23.45	74	45.29	31.3	5.14	31.18	397	188	P	V
		2388.65	40.23	-13.77	54	34.97	31.3	5.14	31.18	397	188	A	V
	*	2440	93.77	-	-	87.95	31.39	5.19	30.76	397	188	P	V
	*	2446	85.83	-	-	79.94	31.39	5.19	30.69	397	188	A	V
		2499.4	50.65	-23.35	74	44.51	31.47	5.24	30.57	397	188	P	V
		2494.12	39.8	-14.2	54	33.66	31.47	5.24	30.57	397	188	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**15C 2.4GHz 2400~2483.5MHz
WIFI 802.11n HT40 (Harmonic @ 3m)**

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n		4842	42.33	-31.67	74	63.52	35.63	7.73	64.55	100	360	P	H
HT40		7266	41.55	-32.45	74	61.43	35.87	9.24	64.99	100	360	P	H
CH 03		4842	41.19	-32.81	74	62.38	35.63	7.73	64.55	100	360	P	V
2422MHz		7266	40.63	-33.37	74	60.51	35.87	9.24	64.99	100	360	P	V
802.11n		4872	41.58	-32.42	74	62.82	35.61	7.75	64.6	100	360	P	H
HT40		7308	40.56	-33.44	74	60.39	35.89	9.29	65.01	100	360	P	H
CH 06		4872	42.8	-31.2	74	64.04	35.61	7.75	64.6	100	360	P	V
2437MHz		7308	40.62	-33.38	74	60.45	35.89	9.29	65.01	100	360	P	V
802.11n		4902	41.45	-32.55	74	62.73	35.58	7.79	64.65	100	360	P	H
HT40		7356	39.75	-34.25	74	59.52	35.92	9.34	65.03	100	360	P	H
CH 09		4902	41.9	-32.1	74	63.18	35.58	7.79	64.65	100	360	P	V
2452MHz		7356	40.84	-33.16	74	60.61	35.92	9.34	65.03	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz

15C Emission below 1GHz

2.4GHz WIFI 802.11g (LF)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz 802.11g LF		31.94	23.89	-16.11	40	30.09	25.23	0.6	32.03	100	0	P	H
		101.78	26.98	-16.52	43.5	39.99	17.9	1.02	31.93	-	-	P	H
		201.69	24.91	-18.59	43.5	39.28	15.84	1.46	31.67	-	-	P	H
		463.59	25.82	-20.18	46	29.93	24.14	2.23	30.48	-	-	P	H
		722.58	26.75	-19.25	46	26.21	26.54	2.78	28.78	-	-	P	H
		910.76	29.19	-16.81	46	25.8	27.7	3.12	27.43	-	-	P	H
		43.58	32.33	-7.67	40	43.2	20.57	0.66	32.1	100	0	P	V
		205.57	25.18	-18.32	43.5	39.43	15.93	1.48	31.66	-	-	P	V
		462.62	26.24	-19.76	46	30.35	24.14	2.23	30.48	-	-	P	V
		594.54	26.16	-19.84	46	28.65	24.59	2.62	29.7	-	-	P	V
		801.15	27.38	-18.62	46	26.54	26.5	2.65	28.31	-	-	P	V
	865.17	28.78	-17.22	46	26.28	27.22	3.07	27.79	-	-	P	V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency per 15.209(c).
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

- Level(dBμV/m) =
Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
- Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

- Level(dBμV/m)
= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)
= 55.45 (dBμV/m)
- Over Limit(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 55.45(dBμV/m) – 74(dBμV/m)
= -18.55(dB)

For Average Limit @ 2390MHz:

- Level(dBμV/m)
= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)
= 43.54 (dBμV/m)
- Over Limit(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 43.54(dBμV/m) – 54(dBμV/m)
= -10.46(dB)


Both peak and average measured complies with the limit line, so test result is “PASS”.



Appendix C. Duty Cycle Plots


Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
802.11b	97.59	8.232	0.121	300Hz
802.11g	87.50	1.370	0.730	1kHz
802.11n HT20	86.27	1.275	0.784	1kHz
802.11n HT40	85.86	1.232	0.812	1kHz

802.11b






802.11g




802.11n HT20



Date: 30.OCT.2017 14:51:05



802.11n HT40



Date: 21.NOV.2017 08:20:06