



FCC RF Test Report

APPLICANT : ZTE CORPORATION
EQUIPMENT : WCDMA/GSM(GPRS) Dual-Mode Digital Mobile Phone
BRAND NAME : ZTE
MODEL NAME : Z667
FCC ID : SRQ-Z667
STANDARD : FCC 47 CFR Part 2, 22(H), 24(E)
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Feb. 14, 2014 and testing was completed on May 07, 2014. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI / TIA / EIA-603-C-2004 and shown to be compliant with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C.



TABLE OF CONTENTS

REVISION HISTORY..... 3

SUMMARY OF TEST RESULT 4

1 GENERAL DESCRIPTION 5

 1.1 Applicant..... 5

 1.2 Manufacturer 5

 1.3 Feature of Equipment Under Test..... 5

 1.4 Product Specification of Equipment Under Test 6

 1.5 Modification of EUT 6

 1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator 7

 1.7 Testing Site 7

 1.8 Applied Standards 7

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST 8

 2.1 Test Mode..... 8

 2.2 Connection Diagram of Test System 10

 2.3 Support Unit used in test configuration and system..... 10

 2.4 Measurement Results Explanation Example 10

3 TEST RESULT..... 11

 3.1 Conducted Output Power Measurement..... 11

 3.2 Peak-to-Average Ratio 13

 3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement 21

 3.4 Occupied Bandwidth and 26dB Bandwidth Measurement..... 27

 3.5 Band Edge Measurement..... 47

 3.6 Conducted Spurious Emission Measurement..... 60

 3.7 Field Strength of Spurious Radiation Measurement 76

 3.8 Frequency Stability Measurement..... 90

4 LIST OF MEASURING EQUIPMENT 95

5 UNCERTAINTY OF EVALUATION 97

APPENDIX A. SETUP PHOTOGRAPHS

SUMMARY OF TEST RESULT

| Report Section | FCC Rule | Description | Limit | Result | Remark |
|----------------|-------------------------------------|---|------------------------|--------|--|
| 3.1 | §2.1046 | Conducted Output Power | Reporting Only | PASS | - |
| 3.2 | §24.232(d) | Peak-to-Average Ratio | < 13 dB | PASS | - |
| 3.3 | §22.913(a)(2) | Effective Radiated Power | < 7 Watts | PASS | - |
| 3.3 | §24.232(c) | Equivalent Isotropic Radiated Power | < 2 Watts | PASS | - |
| 3.4 | §2.1049 §22.917(b) §24.238(b) | Occupied Bandwidth | Reporting Only | PASS | - |
| 3.5 | §2.1051 §22.917(a) §24.238(a) | Band Edge Measurement | < 43+10log10(P[Watts]) | PASS | - |
| 3.6 | §2.1051 §22.917(a) §24.238(a) | Conducted Emission | < 43+10log10(P[Watts]) | PASS | - |
| 3.7 | §2.1053 §22.917(a) §24.238(a) | Field Strength of Spurious Radiation | < 43+10log10(P[Watts]) | PASS | Under limit 29.03 dB at 3762.000 MHz |
| 3.8 | §2.1055 §22.355 §24.235 | Frequency Stability for Temperature & Voltage | < 2.5 ppm | PASS | - |



1 General Description

1.1 Applicant

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

1.2 Manufacturer

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

1.3 Feature of Equipment Under Test

| Product Feature | |
|---------------------------------|---|
| Equipment | WCDMA/GSM(GPRS) Dual-Mode Digital Mobile Phone |
| Brand Name | ZTE |
| Model Name | Z667 |
| FCC ID | SRQ-Z667 |
| EUT supports Radios application | GSM/GPRS/EGPRS/WCDMA/HSPA/HSPA+(Downlink Only)/ WLAN 2.4GHz 802.11b/g/n HT20/ Bluetooth v3.0 + EDR/Bluetooth v 4.0 LE |
| HW Version | wxxA |
| SW Version | Z667V1.0.0B011 |
| EUT Stage | Identical Prototype |

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

| Product Specification subjective to this standard | |
|---|---|
| Tx Frequency | GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz |
| Rx Frequency | GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band II : 1932.4 MHz ~ 1987.6 MHz |
| Maximum Output Power to Antenna | GSM850 : 33.31 dBm GSM1900 : 30.55 dBm WCDMA Band V : 23.20 dBm WCDMA Band II : 23.18 dBm |
| Antenna Type | PIFA Antenna |
| Type of Modulation | GSM: GMSK GPRS: GMSK EDGE: GMSK / 8PSK WCDMA: QPSK (Uplink) HSDPA: QPSK (Uplink) HSUPA: QPSK (Uplink) HSPA+: 16QAM(Downlink Only) |

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

| FCC Rule | System | Type of Modulation | Maximum ERP/EIRP (W) | Frequency Tolerance (ppm) | Emission Designator |
|----------|----------------------------|--------------------|----------------------|---------------------------|---------------------|
| Part 22 | GSM850 GSM | GMSK | 1.51 | 0.03 ppm | 246KGXW |
| Part 22 | GSM850 EDGE class 8 | 8PSK | 0.33 | 0.04 ppm | 244KG7W |
| Part 22 | WCDMA Band V RMC 12.2Kbps | QPSK | 0.14 | 0.04 ppm | 4M18F9W |
| Part 24 | GSM1900 GSM | GMSK | 1.31 | 0.01 ppm | 246KGXW |
| Part 24 | GSM1900 EDGE class 8 | 8PSK | 0.43 | 0.02 ppm | 244KG7W |
| Part 24 | WCDMA Band II RMC 12.2Kbps | QPSK | 0.28 | 0.02 ppm | 4M18F9W |

1.7 Testing Site

| | | | | |
|---------------------------|--|-----------|----------|-----------------------------|
| Test Site | SPORTON INTERNATIONAL (KUNSHAN) INC. | | | |
| Test Site Location | No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C. TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958 | | | |
| Test Site No. | Sporton Site No. | | | FCC Registration No. |
| | TH01-KS | 03CH01-KS | OTA01-KS | 149928 |

1.8 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 2, 22(H), 24(E)
- ANSI / TIA / EIA-603-C-2004
- FCC KDB 971168 D01 Power Meas. License Digital Systems v02r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT was rotated on three test planes to find out the worst emission (Y Plane).

Frequency range investigated for radiated emission is as follows:

1. 30 MHz to 9000 MHz for GSM850 and WCDMA Band V.
2. 30 MHz to 19000 MHz for GSM1900 and WCDMA Band II.

| Test Modes | | |
|---------------|---|---|
| Band | Radiated TCs | Conducted TCs |
| GSM 850 | <ul style="list-style-type: none"> ■ GSM Link ■ EDGE class 8 Link | <ul style="list-style-type: none"> ■ GSM Link ■ EDGE class 8 Link |
| GSM 1900 | <ul style="list-style-type: none"> ■ GSM Link ■ EDGE class 8 Link | <ul style="list-style-type: none"> ■ GSM Link ■ EDGE class 8 Link |
| WCDMA Band V | <ul style="list-style-type: none"> ■ RMC 12.2Kbps Link | <ul style="list-style-type: none"> ■ RMC 12.2Kbps Link |
| WCDMA Band II | <ul style="list-style-type: none"> ■ RMC 12.2Kbps Link | <ul style="list-style-type: none"> ■ RMC 12.2Kbps Link |

Note: The maximum power levels are GSM mode for GMSK link, EDGE multi-slot class 8 mode for 8PSK link, RMC 12.2Kbps mode for WCDMA band V and RMC 12.2Kbps mode for WCDMA band II, only these modes were used for all tests.




The conducted power tables are as follows:

| Conducted Power (*Unit: dBm) | | | | | | |
|------------------------------|--------|-------|-------|---------|-------|--------|
| Band | GSM850 | | | GSM1900 | | |
| Channel | 128 | 189 | 251 | 512 | 661 | 810 |
| Frequency | 824.2 | 836.4 | 848.8 | 1850.2 | 1880 | 1909.8 |
| GSM | 32.99 | 33.15 | 33.31 | 30.55 | 30.35 | 30.53 |
| GPRS class 8 | 32.98 | 33.13 | 33.29 | 30.48 | 30.32 | 30.49 |
| GPRS class 10 | 30.45 | 30.40 | 30.46 | 27.92 | 27.77 | 27.88 |
| EGPRS class 8 | 27.28 | 27.40 | 27.50 | 26.19 | 26.28 | 26.15 |
| EGPRS class 10 | 25.72 | 25.85 | 25.93 | 24.55 | 24.68 | 24.55 |

| Conducted Power (*Unit: dBm) | | | | | | |
|------------------------------|--------------|-------|-------|---------------|-------|--------|
| Band | WCDMA Band V | | | WCDMA Band II | | |
| Channel | 4132 | 4182 | 4233 | 9262 | 9400 | 9538 |
| Frequency | 826.4 | 836.4 | 846.6 | 1852.4 | 1880 | 1907.6 |
| RMC 12.2K | 23.17 | 23.20 | 23.16 | 23.18 | 23.04 | 22.95 |
| HSDPA Subtest-1 | 21.64 | 21.70 | 21.69 | 21.77 | 21.59 | 21.51 |
| HSDPA Subtest-2 | 21.61 | 21.80 | 21.73 | 21.80 | 21.64 | 21.60 |
| HSDPA Subtest-3 | 21.64 | 21.84 | 21.72 | 21.89 | 21.54 | 21.51 |
| HSDPA Subtest-4 | 21.72 | 21.73 | 21.69 | 21.74 | 21.59 | 21.54 |
| HSUPA Subtest-1 | 20.94 | 21.32 | 21.25 | 21.15 | 21.10 | 21.06 |
| HSUPA Subtest-2 | 21.01 | 21.19 | 21.09 | 21.13 | 21.08 | 21.03 |
| HSUPA Subtest-3 | 20.25 | 20.88 | 20.63 | 20.58 | 20.55 | 20.52 |
| HSUPA Subtest-4 | 21.67 | 21.74 | 21.62 | 21.74 | 21.49 | 21.44 |
| HSUPA Subtest-5 | 20.50 | 20.51 | 20.41 | 20.59 | 20.11 | 20.09 |

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

| Item | Equipment | Trade Name | Model No. | FCC ID | Data Cable | Power Cord |
|------|------------------|------------|-----------|--------|------------|-------------------|
| 1. | System Simulator | R&S | CMU 200 | N/A | N/A | Unshielded, 1.8 m |
| 2. | DC Power Supply | GW | GPS-3030D | N/A | N/A | Unshielded, 1.8 m |

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

$Offset = RF\ cable\ loss + attenuator\ factor.$

Following shows an offset computation example with cable loss 5.2 dB and 10dB attenuator.

Example :

$$\begin{aligned}
 Offset(dB) &= RF\ cable\ loss(dB) + attenuator\ factor(dB). \\
 &= 5.2 + 10 = 15.2\ (dB)
 \end{aligned}$$

3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The transmitter output port was connected to base station.
2. Set EUT at maximum power through base station.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure the maximum burst average power for GSM and maximum average power for GSM and WCDMA modes.

3.1.4 Test Setup



3.1.5 Test Result of Conducted Output Power

| Cellular Band | | | | | | | | | |
|-------------------------|--------------|-----------|------------|-----------------------|-----------|------------|-----------------------------|------------|-------------|
| Modes | GSM850 (GSM) | | | GSM850 (EDGE class 8) | | | WCDMA Band V (RMC 12.2Kbps) | | |
| Channel | 128 (Low) | 189 (Mid) | 251 (High) | 128 (Low) | 189 (Mid) | 251 (High) | 4132 (Low) | 4182 (Mid) | 4233 (High) |
| Frequency (MHz) | 824.2 | 836.4 | 848.8 | 824.2 | 836.4 | 848.8 | 826.4 | 836.4 | 846.6 |
| Conducted Power (dBm) | 32.99 | 33.15 | 33.31 | 27.28 | 27.40 | 27.50 | 23.17 | 23.20 | 23.16 |
| Conducted Power (Watts) | 1.99 | 2.07 | 2.14 | 0.53 | 0.55 | 0.56 | 0.21 | 0.21 | 0.21 |

| PCS Band | | | | | | | | | |
|-------------------------|---------------|-----------|------------|------------------------|-----------|------------|------------------------------|------------|-------------|
| Modes | GSM1900 (GSM) | | | GSM1900 (EDGE class 8) | | | WCDMA Band II (RMC 12.2Kbps) | | |
| Channel | 512 (Low) | 661 (Mid) | 810 (High) | 512 (Low) | 661 (Mid) | 810 (High) | 9262 (Low) | 9400 (Mid) | 9538 (High) |
| Frequency (MHz) | 1850.2 | 1880 | 1909.8 | 1850.2 | 1880 | 1909.8 | 1852.4 | 1880 | 1907.6 |
| Conducted Power (dBm) | 30.55 | 30.35 | 30.53 | 26.19 | 26.28 | 26.15 | 23.18 | 23.04 | 22.95 |
| Conducted Power (Watts) | 1.14 | 1.08 | 1.13 | 0.42 | 0.42 | 0.41 | 0.21 | 0.20 | 0.20 |

Note: maximum burst average power for GSM, and maximum average power for WCDMA.

3.2 Peak-to-Average Ratio

3.2.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and System Simulator via power divider.
2. For GSM/EGPRS operating modes:
 - a. Set EUT in maximum power output.
 - b. Set the RBW = 1MHz, VBW = 3MHz, Peak detector in spectrum analyzer for first trace.
 - c. Set the RBW = 1MHz, VBW = 3MHz, RMS detector in spectrum analyzer for second trace.
 - d. The wanted burst signal is triggered by spectrum analyzer, and measured respectively the peak level and Mean level without burst-off time, after system simulator synchronized with the spectrum analyzer.
3. For UMTS operating modes:
 - a. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
 - b. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
4. Record the deviation as Peak to Average Ratio.

3.2.4 Test Setup



3.2.5 Test Result of Peak-to-Average Ratio


| PCS Band | | | | | | | | | |
|----------------------------|---------------|-----------|------------|------------------------|-----------|------------|------------------------------|------------|-------------|
| Modes | GSM1900 (GSM) | | | GSM1900 (EDGE class 8) | | | WCDMA Band II (RMC 12.2Kbps) | | |
| Channel | 512 (Low) | 661 (Mid) | 810 (High) | 512 (Low) | 661 (Mid) | 810 (High) | 9262 (Low) | 9400 (Mid) | 9538 (High) |
| Frequency (MHz) | 1850.2 | 1880 | 1909.8 | 1850.2 | 1880 | 1909.8 | 1852.4 | 1880 | 1907.6 |
| Peak-to-Average Ratio (dB) | 0.37 | 0.39 | 0.40 | 3.10 | 3.03 | 2.93 | 3.04 | 3.00 | 2.92 |




3.2.6 Test Result (Plots) of Peak-to-Average Ratio

| | | | |
|--------|----------|-------------|-----------------|
| Band : | GSM 1900 | Test Mode : | GSM Link (GMSK) |
|--------|----------|-------------|-----------------|

Peak-to-Average Ratio on Channel 512 (1850.2 MHz)




Peak-to-Average Ratio on Channel 661 (1880.0 MHz)






Peak-to-Average Ratio on Channel 810 (1909.8 MHz)






| | | | |
|--------|----------|-------------|--------------------------|
| Band : | GSM 1900 | Test Mode : | EDGE class 8 Link (8PSK) |
|--------|----------|-------------|--------------------------|

Peak-to-Average Ratio on Channel 512 (1850.2 MHz)




Peak-to-Average Ratio on Channel 661 (1880.0 MHz)






Peak-to-Average Ratio on Channel 810 (1909.8 MHz)





| | | | |
|---------------|---------------|--------------------|--------------------------|
| Band : | WCDMA Band II | Test Mode : | RMC 12.2Kbps Link (QPSK) |
|---------------|---------------|--------------------|--------------------------|

Peak-to-Average Ratio on Channel 9262 (1852.4 MHz)




Complementary Cumulative Distribution Function (100000 samples)

Trace 1

| | |
|-------|-----------|
| Mean | 22.29 dBm |
| Peak | 25.62 dBm |
| Crest | 3.34 dB |
| 10 % | 1.72 dB |
| 1 % | 2.56 dB |
| .1 % | 3.04 dB |
| .01 % | 3.24 dB |

Date: 17.FEB.2014 14:57:07

Peak-to-Average Ratio on Channel 9400 (1880.0 MHz)



Complementary Cumulative Distribution Function (100000 samples)


Trace 1

| | |
|-------|-----------|
| Mean | 21.99 dBm |
| Peak | 25.34 dBm |
| Crest | 3.35 dB |
| 10 % | 1.72 dB |
| 1 % | 2.52 dB |
| .1 % | 3.00 dB |
| .01 % | 3.20 dB |

Date: 17.FEB.2014 14:56:35



Peak-to-Average Ratio on Channel 9538 (1907.6 MHz)



Complementary Cumulative Distribution Function (100000 samples)

Trace 1

| | |
|-------|-----------|
| Mean | 21.56 dBm |
| Peak | 24.78 dBm |
| Crest | 3.22 dB |
| 10 % | 1.72 dB |
| 1 % | 2.48 dB |
| .1 % | 2.92 dB |
| .01 % | 3.12 dB |

Date: 17.FEB.2014 14:56:07

3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

3.3.1 Description of the ERP/EIRP Measurement

The substitution method, in ANSI / TIA / EIA-603-C-2004, was used for ERP/EIRP measurement, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v01. The ERP of mobile transmitters must not exceed 7 Watts (Cellular Band) and the EIRP of mobile transmitters are limited to 2 Watts (PCS Band).

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The EUT was placed on a turntable with 1.5 meter height in a fully anechoic chamber.
2. The EUT was set at 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. GSM operating modes: Set RBW= 1MHz, VBW= 3MHz, RMS detector over burst;
UMTS operating modes: Set RBW= 100 kHz, VBW= 300 kHz, RMS detector over frame, and use channel power option with bandwidth=5MHz, per section 4.0 of KDB 971168 D01.
4. The table was rotated 360 degrees to determine the position of the highest radiated power.
5. The height of the receiving antenna is adjusted to look for the maximum ERP/EIRP.
6. Taking the record of maximum ERP/EIRP.
7. A dipole antenna was substituted in place of the EUT and was driven by a signal generator.
8. The conducted power at the terminal of the dipole antenna is measured.
9. Repeat step 3 to step 5 to get the maximum ERP/EIRP of the substitution antenna.
10. $ERP/EIRP = P_s + E_t - E_s + G_s = P_s + R_t - R_s + G_s$

P_s (dBm) : Input power to substitution antenna.

G_s (dBi or dBd) : Substitution antenna Gain.

$E_t = R_t + AF$


$E_s = R_s + AF$

AF (dB/m) : Receive antenna factor

R_t : The highest received signal in spectrum analyzer for EUT.

R_s : The highest received signal in spectrum analyzer for substitution antenna.

3.3.4 Test Setup



3.3.5 Test Result of ERP

| GSM850 (GSM) Radiated Power ERP | | | | | | |
|--|-----------------|-----------------|-----------------|-----------------|------------------|----------------|
| Horizontal Polarization | | | | | | |
| Frequency (MHz) | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBd) | ERP (dBm) | ERP (W) |
| 824.20 | -15.79 | -48.12 | 0.00 | -1.08 | 31.25 | 1.33 |
| 836.40 | -15.87 | -48.28 | 0.00 | -0.93 | 31.48 | 1.41 |
| 848.80 | -15.80 | -48.35 | 0.00 | -0.76 | 31.80 | 1.51 |
| Vertical Polarization | | | | | | |
| Frequency (MHz) | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBd) | ERP (dBm) | ERP (W) |
| 824.20 | -28.66 | -47.97 | 0.00 | -1.08 | 18.23 | 0.07 |
| 836.40 | -28.52 | -48.01 | 0.00 | -0.93 | 18.56 | 0.07 |
| 848.80 | -28.76 | -48.05 | 0.00 | -0.76 | 18.53 | 0.07 |

| GSM850 (EDGE class 8) Radiated Power ERP | | | | | | |
|---|-----------------|-----------------|-----------------|-----------------|------------------|----------------|
| Horizontal Polarization | | | | | | |
| Frequency (MHz) | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBd) | ERP (dBm) | ERP (W) |
| 824.20 | -22.21 | -48.12 | 0.00 | -1.08 | 24.83 | 0.30 |
| 836.40 | -22.18 | -48.28 | 0.00 | -0.93 | 25.17 | 0.33 |
| 848.80 | -22.42 | -48.35 | 0.00 | -0.76 | 25.17 | 0.33 |
| Vertical Polarization | | | | | | |
| Frequency (MHz) | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBd) | ERP (dBm) | ERP (W) |
| 824.20 | -34.97 | -47.97 | 0.00 | -1.08 | 11.92 | 0.02 |
| 836.40 | -35.00 | -48.01 | 0.00 | -0.93 | 12.08 | 0.02 |
| 848.80 | -35.33 | -48.05 | 0.00 | -0.76 | 11.96 | 0.02 |



| WCDMA Band V (RMC 12.2Kbps) Radiated Power ERP | | | | | | |
|--|----------|----------|----------|----------|-----------|---------|
| Horizontal Polarization | | | | | | |
| Frequency (MHz) | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBd) | ERP (dBm) | ERP (W) |
| 826.40 | -26.58 | -48.12 | 0.00 | -1.08 | 20.46 | 0.11 |
| 836.40 | -26.00 | -48.28 | 0.00 | -0.93 | 21.35 | 0.14 |
| 846.60 | -26.82 | -48.35 | 0.00 | -0.76 | 20.77 | 0.12 |
| Vertical Polarization | | | | | | |
| Frequency (MHz) | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBd) | ERP (dBm) | ERP (W) |
| 826.40 | -39.57 | -47.97 | 0.00 | -1.08 | 7.32 | 0.01 |
| 836.40 | -39.05 | -48.01 | 0.00 | -0.93 | 8.03 | 0.01 |
| 846.60 | -39.78 | -48.05 | 0.00 | -0.76 | 7.51 | 0.01 |

3.3.6 Test Result of EIRP

| GSM1900 (GSM) Radiated Power EIRP | | | | | | |
|--|-----------------|-----------------|-----------------|-----------------|-------------------|-----------------|
| Horizontal Polarization | | | | | | |
| Frequency (MHz) | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBi) | EIRP (dBm) | EIRP (W) |
| 1850.20 | -24.75 | -51.88 | 0.00 | 1.96 | 29.09 | 0.81 |
| 1880.00 | -25.36 | -52.99 | 0.00 | 2.00 | 29.63 | 0.92 |
| 1909.80 | -25.53 | -54.28 | 0.00 | 1.98 | 30.73 | 1.18 |
| Vertical Polarization | | | | | | |
| Frequency (MHz) | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBi) | EIRP (dBm) | EIRP (W) |
| 1850.20 | -24.11 | -52.13 | 0.00 | 1.96 | 29.98 | 0.99 |
| 1880.00 | -24.91 | -53.17 | 0.00 | 2.00 | 30.26 | 1.06 |
| 1909.80 | -24.95 | -54.13 | 0.00 | 1.98 | 31.16 | 1.31 |

| GSM1900 (EDGE class 8) Radiated Power EIRP | | | | | | |
|---|-----------------|-----------------|-----------------|-----------------|-------------------|-----------------|
| Horizontal Polarization | | | | | | |
| Frequency (MHz) | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBi) | EIRP (dBm) | EIRP (W) |
| 1850.20 | -29.22 | -51.88 | 0.00 | 1.96 | 24.62 | 0.29 |
| 1880.00 | -30.12 | -52.99 | 0.00 | 2.00 | 24.87 | 0.31 |
| 1909.80 | -30.45 | -54.28 | 0.00 | 1.98 | 25.81 | 0.38 |
| Vertical Polarization | | | | | | |
| Frequency (MHz) | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBi) | EIRP (dBm) | EIRP (W) |
| 1850.20 | -28.64 | -52.13 | 0.00 | 1.96 | 25.45 | 0.35 |
| 1880.00 | -29.64 | -53.17 | 0.00 | 2.00 | 25.53 | 0.36 |
| 1909.80 | -29.80 | -54.13 | 0.00 | 1.98 | 26.31 | 0.43 |



| WCDMA Band II (RMC 12.2Kbps) Radiated Power EIRP | | | | | | |
|--|----------|----------|----------|----------|------------|----------|
| Horizontal Polarization | | | | | | |
| Frequency (MHz) | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBi) | EIRP (dBm) | EIRP (W) |
| 1852.40 | -30.45 | -51.88 | 0.00 | 1.96 | 23.39 | 0.22 |
| 1880.00 | -31.50 | -52.99 | 0.00 | 2.00 | 23.49 | 0.22 |
| 1907.60 | -32.28 | -54.28 | 0.00 | 1.98 | 23.98 | 0.25 |
| Vertical Polarization | | | | | | |
| Frequency (MHz) | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBi) | EIRP (dBm) | EIRP (W) |
| 1852.40 | -29.81 | -52.13 | 0.00 | 1.96 | 24.28 | 0.27 |
| 1880.00 | -31.05 | -53.17 | 0.00 | 2.00 | 24.12 | 0.26 |
| 1907.60 | -31.69 | -54.13 | 0.00 | 1.98 | 24.43 | 0.28 |

3.4 Occupied Bandwidth and 26dB Bandwidth Measurement

3.4.1 Description of Occupied Bandwidth and 26dB Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The 99% occupied bandwidth were measured, set RBW= 1% of span, VBW= 3*RBW, sample detector, trace maximum hold.
4. The 26dB bandwidth were measured, set RBW= 1% of EBW, VBW= 3*RBW, peak detector, trace maximum hold.

3.4.4 Test Setup



3.4.5 Test Result of Occupied Bandwidth and 26dB Bandwidth

| Cellular Band | | | | | | |
|-----------------|--------------|--------------|---------------|-----------------------|--------------|---------------|
| Modes | GSM850 (GSM) | | | GSM850 (EDGE class 8) | | |
| Channel | 128 (Low) | 189 (Mid) | 251 (High) | 128 (Low) | 189 (Mid) | 251 (High) |
| Frequency (MHz) | 824.2 | 836.4 | 848.8 | 824.2 | 836.4 | 848.8 |
| 99% OBW (kHz) | 246.00 | 244.00 | 246.00 | 242.00 | 244.00 | 242.00 |
| 26dB BW (kHz) | 310.00 | 314.00 | 312.00 | 304.00 | 300.00 | 310.00 |


| PCS Band | | | | | | |
|-----------------|---------------|--------------|---------------|------------------------|--------------|---------------|
| Modes | GSM1900 (GSM) | | | GSM1900 (EDGE class 8) | | |
| Channel | 512 (Low) | 661 (Mid) | 810 (High) | 512 (Low) | 661 (Mid) | 810 (High) |
| Frequency (MHz) | 1850.2 | 1880 | 1909.8 | 1850.2 | 1880 | 1909.8 |
| 99% OBW (kHz) | 244.00 | 244.00 | 246.00 | 244.00 | 244.00 | 242.00 |
| 26dB BW (kHz) | 316.00 | 308.00 | 302.00 | 314.00 | 308.00 | 310.00 |

| Cellular Band | | | |
|-----------------|-----------------------------|------------|-------------|
| Modes | WCDMA Band V (RMC 12.2Kbps) | | |
| Channel | 4132 (Low) | 4182 (Mid) | 4233 (High) |
| Frequency (MHz) | 826.4 | 836.4 | 846.6 |
| 99% OBW (MHz) | 4.18 | 4.18 | 4.18 |
| 26dB BW (MHz) | 4.76 | 4.76 | 4.76 |

| PCS Band | | | |
|-----------------|------------------------------|------------|-------------|
| Modes | WCDMA Band II (RMC 12.2Kbps) | | |
| Channel | 9262 (Low) | 9400 (Mid) | 9538 (High) |
| Frequency (MHz) | 1852.4 | 1880 | 1907.6 |
| 99% OBW (MHz) | 4.18 | 4.18 | 4.18 |
| 26dB BW (MHz) | 4.76 | 4.76 | 4.76 |




99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 17.FEB.2014 11:41:45


26dB Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 17.FEB.2014 11:22:33




99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)



Date: 17.FEB.2014 11:42:32

26dB Bandwidth Plot on Channel 251 (848.8 MHz)




Date: 17.FEB.2014 11:22:59




| | | | |
|---------------|---------|--------------------|--------------------------|
| Band : | GSM 850 | Test Mode : | EDGE class 8 Link (8PSK) |
|---------------|---------|--------------------|--------------------------|

99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 17.FEB.2014 13:29:57


26dB Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 17.FEB.2014 13:30:50




99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 17.FEB.2014 11:56:27


26dB Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 17.FEB.2014 11:55:08




99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)



Date: 17.FEB.2014 11:56:53

26dB Bandwidth Plot on Channel 251 (848.8 MHz)




Date: 17.FEB.2014 13:32:42




| | | | |
|--------|----------|-------------|-----------------|
| Band : | GSM 1900 | Test Mode : | GSM Link (GMSK) |
|--------|----------|-------------|-----------------|

99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 17.FEB.2014 14:28:32


26dB Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 17.FEB.2014 14:35:10




99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 17.FEB.2014 14:28:58


26dB Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 17.FEB.2014 14:35:37




99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)



Date: 17.FEB.2014 14:29:25

26dB Bandwidth Plot on Channel 810 (1909.8 MHz)




Date: 17.FEB.2014 14:36:03




| | | | |
|--------|----------|-------------|--------------------------|
| Band : | GSM 1900 | Test Mode : | EDGE class 8 Link (8PSK) |
|--------|----------|-------------|--------------------------|

99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 17.FEB.2014 14:07:50


26dB Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 17.FEB.2014 14:17:57




99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 17.FEB.2014 14:08:42


26dB Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 17.FEB.2014 14:16:55




99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)



Date: 17.FEB.2014 14:11:15

26dB Bandwidth Plot on Channel 810 (1909.8 MHz)




Date: 17.FEB.2014 14:16:13




| | | | |
|--------|--------------|-------------|--------------------------|
| Band : | WCDMA Band V | Test Mode : | RMC 12.2Kbps Link (QPSK) |
|--------|--------------|-------------|--------------------------|

99% Occupied Bandwidth Plot on Channel 4132 (826.4 MHz)



Date: 17.FEB.2014 15:06:06


26dB Bandwidth Plot on Channel 4132 (826.4 MHz)



Date: 17.FEB.2014 15:11:23




99% Occupied Bandwidth Plot on Channel 4182 (836.4 MHz)



Date: 17.FEB.2014 15:06:32


26dB Bandwidth Plot on Channel 4182 (836.4 MHz)



Date: 17.FEB.2014 15:11:49




99% Occupied Bandwidth Plot on Channel 4233 (846.6 MHz)



Date: 17.FEB.2014 15:06:58

26dB Bandwidth Plot on Channel 4233 (846.6 MHz)




Date: 17.FEB.2014 15:12:16




| | | | |
|--------|---------------|-------------|--------------------------|
| Band : | WCDMA Band II | Test Mode : | RMC 12.2Kbps Link (QPSK) |
|--------|---------------|-------------|--------------------------|

99% Occupied Bandwidth Plot on Channel 9262 (1852.4 MHz)



Date: 17.FEB.2014 14:49:41


26dB Bandwidth Plot on Channel 9262 (1852.4 MHz)



Date: 17.FEB.2014 14:48:22




99% Occupied Bandwidth Plot on Channel 9400 (1880.0 MHz)



Date: 17.FEB.2014 14:50:07


26dB Bandwidth Plot on Channel 9400 (1880.0 MHz)



Date: 17.FEB.2014 14:48:48




99% Occupied Bandwidth Plot on Channel 9538 (1907.6 MHz)



Date: 17.FEB.2014 14:50:33

26dB Bandwidth Plot on Channel 9538 (1907.6 MHz)



Date: 17.FEB.2014 14:49:14

3.5 Band Edge Measurement

3.5.1 Description of Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.


3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The band edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly $BW/100$.
4. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
5. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)]$ (dB)
 $= [30 + 10\log(P)]$ (dBm) - $[43 + 10\log(P)]$ (dB)
 $= -13\text{dBm}$.

3.5.4 Test Setup






3.5.5 Test Result (Plots) of Conducted Band Edge

| | | | |
|---------------------|-----------|--------------------------|-----------------|
| Band : | GSM850 | Test Mode : | GSM Link (GMSK) |
| Correction Factor : | 0.20dB | Maximum 26dB Bandwidth : | 0.314MHz |
| Band Edge : | -17.36dBm | Measurement Value : | -17.56dBm |

Lower Band Edge Plot on Channel 128 (824.2 MHz)




Date: 17.FEB.2014 11:12:39

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)



| | | | |
|---------------------|-----------|--------------------------|-----------------|
| Band : | GSM850 | Test Mode : | GSM Link (GMSK) |
| Correction Factor : | 0.20dB | Maximum 26dB Bandwidth : | 0.314MHz |
| Band Edge : | -17.65dBm | Measurement Value : | -17.85dBm |

Higher Band Edge Plot on Channel 251 (848.8 MHz)




Date: 17.FEB.2014 11:13:05

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
2. Band Edge= Measurement Value + Correction Factor(dB)



| | | | |
|---------------------|-----------|--------------------------|--------------------------|
| Band : | GSM850 | Test Mode : | EDGE class 8 Link (8PSK) |
| Correction Factor : | 0.14dB | Maximum 26dB Bandwidth : | 0.310MHz |
| Band Edge : | -21.32dBm | Measurement Value : | -21.46dBm |

Lower Band Edge Plot on Channel 128 (824.2 MHz)




Date: 17.FEB.2014 11:58:20

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
2. Band Edge= Measurement Value + Correction Factor(dB)



| | | | |
|---------------------|-----------|--------------------------|--------------------------|
| Band : | GSM850 | Test Mode : | EDGE class 8 Link (8PSK) |
| Correction Factor : | 0.14dB | Maximum 26dB Bandwidth : | 0.310MHz |
| Band Edge : | -24.83dBm | Measurement Value : | -24.97dBm |

Higher Band Edge Plot on Channel 251 (848.8 MHz)




Date: 17.FEB.2014 11:58:46

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
2. Band Edge= Measurement Value + Correction Factor(dB)



| | | | |
|----------------------------|-----------|---------------------------------|-----------------|
| Band : | GSM1900 | Test Mode : | GSM Link (GMSK) |
| Correction Factor : | 0.23dB | Maximum 26dB Bandwidth : | 0.316MHz |
| Band Edge : | -21.06dBm | Measurement Value : | -21.29dBm |

Lower Band Edge Plot on Channel 512 (1850.2 MHz)




Date: 17.FEB.2014 14:30:51

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
2. Band Edge= Measurement Value + Correction Factor(dB)



| | | | |
|---------------------|-----------|--------------------------|-----------------|
| Band : | GSM1900 | Test Mode : | GSM Link (GMSK) |
| Correction Factor : | 0.23dB | Maximum 26dB Bandwidth : | 0.316MHz |
| Band Edge : | -22.13dBm | Measurement Value : | -22.36dBm |

Higher Band Edge Plot on Channel 810 (1909.8 MHz)




Date: 17.FEB.2014 14:31:17

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
2. Band Edge= Measurement Value + Correction Factor(dB)



| | | | |
|---------------------|-----------|--------------------------|--------------------------|
| Band : | GSM1900 | Test Mode : | EDGE class 8 Link (8PSK) |
| Correction Factor : | 0.20dB | Maximum 26dB Bandwidth : | 0.314MHz |
| Band Edge : | -26.29dBm | Measurement Value : | -26.49dBm |

Lower Band Edge Plot on Channel 512 (1850.2 MHz)




Date: 17.FEB.2014 13:48:16

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)



| | | | |
|---------------------|-----------|--------------------------|--------------------------|
| Band : | GSM1900 | Test Mode : | EDGE class 8 Link (8PSK) |
| Correction Factor : | 0.20dB | Maximum 26dB Bandwidth : | 0.314MHz |
| Band Edge : | -27.94dBm | Measurement Value : | -28.14dBm |

Higher Band Edge Plot on Channel 810 (1909.8 MHz)




Date: 17.FEB.2014 13:48:43

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
2. Band Edge= Measurement Value + Correction Factor(dB)



| | | | |
|---------------------|--------------|--------------------------|--------------------------|
| Band : | WCDMA Band V | Test Mode : | RMC 12.2Kbps Link (QPSK) |
| Correction Factor : | -3.22dB | Maximum 26dB Bandwidth : | 4.760MHz |
| Band Edge : | -22.89dBm | Measurement Value : | -19.67dBm |

Lower Band Edge Plot on Channel 4132 (826.4 MHz)




Date: 17.FEB.2014 15:08:27

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
2. Band Edge= Measurement Value + Correction Factor(dB)



| | | | |
|---------------------|--------------|--------------------------|--------------------------|
| Band : | WCDMA Band V | Test Mode : | RMC 12.2Kbps Link (QPSK) |
| Correction Factor : | -3.22dB | Maximum 26dB Bandwidth : | 4.760MHz |
| Band Edge : | -22.89dBm | Measurement Value : | -19.67dBm |

Higher Band Edge Plot on Channel 4233 (846.6 MHz)




Date: 17.FEB.2014 15:08:53

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)



| | | | |
|---------------------|---------------|--------------------------|--------------------------|
| Band : | WCDMA Band II | Test Mode : | RMC 12.2Kbps Link (QPSK) |
| Correction Factor : | -3.22dB | Maximum 26dB Bandwidth : | 4.760MHz |
| Band Edge : | -24.20dBm | Measurement Value : | -20.98dBm |

Lower Band Edge Plot on Channel 9262 (1852.4 MHz)




Date: 17.FEB.2014 14:52:02

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)



| | | | |
|----------------------------|---------------|---------------------------------|--------------------------|
| Band : | WCDMA Band II | Test Mode : | RMC 12.2Kbps Link (QPSK) |
| Correction Factor : | -3.22dB | Maximum 26dB Bandwidth : | 4.760MHz |
| Band Edge : | -24.90dBm | Measurement Value : | -21.68dBm |

Higher Band Edge Plot on Channel 9538 (1907.6 MHz)



Date: 17.FEB.2014 14:52:29

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
2. Band Edge= Measurement Value + Correction Factor(dB)

3.6 Conducted Spurious Emission Measurement

3.6.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures


1. The EUT was connected to spectrum analyzer and base station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The middle channel for the highest RF power within the transmitting frequency was measured.
4. The conducted spurious emission for the whole frequency range was taken.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

$$= P(W) - [43 + 10\log(P)] \text{ (dB)}$$

$$= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$$

$$= -13\text{dBm}.$$


3.6.4 Test Setup



3.6.5 Test Result (Plots) of Conducted Emission


| | | | |
|-------------|-----------------|-------------|-----------|
| Band : | GSM850 | Channel : | CH189 |
| Test Mode : | GSM Link (GMSK) | Frequency : | 836.4 MHz |

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 17.FEB.2014 11:46:15


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 17.FEB.2014 11:47:42




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 17.FEB.2014 11:48:52

Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 17.FEB.2014 11:49:18




| | | | |
|-------------|--------------------------|-------------|-----------|
| Band : | GSM850 | Channel : | CH189 |
| Test Mode : | EDGE class 8 Link (8PSK) | Frequency : | 836.4 MHz |

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 17.FEB.2014 13:37:02


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 17.FEB.2014 13:38:24




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 17.FEB.2014 13:39:34

Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 17.FEB.2014 13:40:14




| | | | |
|-------------|-----------------|-------------|------------|
| Band : | GSM1900 | Channel : | CH661 |
| Test Mode : | GSM Link (GMSK) | Frequency : | 1880.0 MHz |

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 17.FEB.2014 14:43:37


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 17.FEB.2014 14:44:14




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 17.FEB.2014 14:45:25


Conducted Spurious Emission Plot between 7GHz ~ 13.6G



Date: 17.FEB.2014 14:42:23



Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz




Date: 17.FEB.2014 14:42:58




| | | | |
|-------------|--------------------------|-------------|------------|
| Band : | GSM1900 | Channel : | CH661 |
| Test Mode : | EDGE class 8 Link (8PSK) | Frequency : | 1880.0 MHz |

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 17.FEB.2014 14:19:00


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 17.FEB.2014 14:19:52




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 17.FEB.2014 14:20:36


Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 17.FEB.2014 14:21:15



Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz




Date: 17.FEB.2014 14:21:51




| | | | |
|--------------------|--------------------------|--------------------|-----------|
| Band : | WCDMA Band V | Channel : | CH4182 |
| Test Mode : | RMC 12.2Kbps Link (QPSK) | Frequency : | 836.4 MHz |

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 17.FEB.2014 15:15:57


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 17.FEB.2014 15:16:48




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 17.FEB.2014 15:17:28

Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 17.FEB.2014 15:18:02




| | | | |
|-------------|--------------------------|-------------|------------|
| Band : | WCDMA Band II | Channel : | CH9400 |
| Test Mode : | RMC 12.2Kbps Link (QPSK) | Frequency : | 1880.0 MHz |

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 17.FEB.2014 14:58:12


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 17.FEB.2014 14:58:48




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 17.FEB.2014 14:59:19


Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 17.FEB.2014 14:59:51



Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz



Date: 17.FEB.2014 15:00:21

3.7 Field Strength of Spurious Radiation Measurement

3.7.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

3.7.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.7.3 Test Procedures


1. The EUT was placed on a rotatable wooden table with 0.8 meter above ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
11. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)]$ (dB)
 $= [30 + 10\log(P)]$ (dBm) - $[43 + 10\log(P)]$ (dB)
 $= -13\text{dBm}$
12. $\text{EIRP (dBm)} = \text{S.G. Power} - \text{Tx Cable Loss} + \text{Tx Antenna Gain}$
13. $\text{ERP (dBm)} = \text{EIRP} - 2.15$

3.7.4 Test Setup

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz





3.7.5 Test Result of Field Strength of Spurious Radiated

| | | | |
|-----------------|--|---------------------|------------|
| Band : | GSM850 | Temperature : | 22~23°C |
| Test Mode : | GSM Link (GMSK) | Relative Humidity : | 42~43% |
| Test Engineer : | Star Wei | Polarization : | Horizontal |
| Remark : | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | |




Site : 03CH01-KS
 Condition : FCC PART22 24 HF_EIRP_FACTOR130726 HORIZONTAL
 EUT : (FG) 421402
 Plane : Y

| Frequency (MHz) | ERP (dBm) | Limit (dBm) | Over Limit (dB) | SPA Reading (dBm) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) | Result |
|-------------------|-------------|---------------|-------------------|---------------------|--------------------|----------------------|-------------------------|----------------------|--------|
| 1674 | -50.94 | -13 | -37.94 | -48.98 | -51.59 | 0.57 | 3.37 | H | Pass |
| 2510 | -55.10 | -13 | -42.10 | -56.24 | -57.33 | 0.78 | 5.16 | H | Pass |
| 3344 | -66.08 | -13 | -53.08 | -65.71 | -69.72 | 0.87 | 6.66 | H | Pass |



| | | | |
|------------------------|--|----------------------------|----------|
| Band : | GSM850 | Temperature : | 22~23°C |
| Test Mode : | GSM Link (GMSK) | Relative Humidity : | 42~43% |
| Test Engineer : | Star Wei | Polarization : | Vertical |
| Remark : | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | |




Site : 03CH01-KS
 Condition : FCC PART22 24 HF_EIRP_FACTOR130726 VERTICAL
 EUT : (FG) 421402
 Plane : Y

| Frequency (MHz) | ERP (dBm) | Limit (dBm) | Over Limit (dB) | SPA Reading (dBm) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) | Result |
|-------------------|-------------|---------------|-------------------|---------------------|--------------------|----------------------|-------------------------|----------------------|--------|
| 1674 | -46.04 | -13 | -33.04 | -49.57 | -46.69 | 0.57 | 3.37 | V | Pass |
| 2510 | -56.16 | -13 | -43.16 | -60.50 | -58.39 | 0.78 | 5.16 | V | Pass |
| 3344 | -64.87 | -13 | -51.87 | -65.93 | -68.51 | 0.87 | 6.66 | V | Pass |



| | | | |
|------------------------|--|----------------------------|------------|
| Band : | GSM850 | Temperature : | 22~23°C |
| Test Mode : | EDGE class 8 Link (8PSK) | Relative Humidity : | 42~43% |
| Test Engineer : | Star Wei | Polarization : | Horizontal |
| Remark : | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | |




Site : 03CH01-KS
 Condition : FCC PART22 24 HF_EIRP_FACTOR130726 HORIZONTAL
 EUT : (FG) 421402
 Plane : Y

| Frequency (MHz) | ERP (dBm) | Limit (dBm) | Over Limit (dB) | SPA Reading (dBm) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) | Result |
|-------------------|-------------|---------------|-------------------|---------------------|--------------------|----------------------|-------------------------|----------------------|--------|
| 1674 | -60.32 | -13 | -47.32 | -55.58 | -60.97 | 0.57 | 3.37 | H | Pass |
| 2509 | -68.96 | -13 | -55.96 | -67.63 | -71.19 | 0.78 | 5.16 | H | Pass |
| 3344 | -66.80 | -13 | -53.80 | -66.43 | -70.44 | 0.87 | 6.66 | H | Pass |



| | | | |
|------------------------|--|----------------------------|----------|
| Band : | GSM850 | Temperature : | 22~23°C |
| Test Mode : | EDGE class 8 Link (8PSK) | Relative Humidity : | 42~43% |
| Test Engineer : | Star Wei | Polarization : | Vertical |
| Remark : | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | |




Site : 03CH01-KS
 Condition : FCC PART22 24 HF_EIRP_FACTOR130726 VERTICAL
 EUT : (FG) 421402
 Plane : Y

| Frequency (MHz) | ERP (dBm) | Limit (dBm) | Over Limit (dB) | SPA Reading (dBm) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) | Result |
|-------------------|-------------|---------------|-------------------|---------------------|--------------------|----------------------|-------------------------|----------------------|--------|
| 1672 | -53.18 | -13 | -40.18 | -55.29 | -53.83 | 0.57 | 3.37 | V | Pass |
| 2508 | -65.24 | -13 | -52.24 | -67.67 | -67.47 | 0.78 | 5.16 | V | Pass |
| 3344 | -65.89 | -13 | -52.89 | -66.95 | -69.53 | 0.87 | 6.66 | V | Pass |



| | | | |
|-----------------|--|---------------------|------------|
| Band : | GSM1900 | Temperature : | 22~23°C |
| Test Mode : | GSM Link (GMSK) | Relative Humidity : | 42~43% |
| Test Engineer : | Star Wei | Polarization : | Horizontal |
| Remark : | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | |




Site : 03CH01-KS
 Condition : FCC PART22 24 HF_EIRP_FACTOR130726 HORIZONTAL
 EUT : (FG) 421402
 Plane : Y

| Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Over Limit (dB) | SPA Reading (dBm) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) | Result |
|-------------------|--------------|---------------|-------------------|---------------------|--------------------|----------------------|-------------------------|----------------------|--------|
| 3760 | -60.96 | -13 | -47.96 | -64.31 | -67.34 | 0.78 | 7.16 | H | Pass |
| 5640 | -56.47 | -13 | -43.47 | -66.53 | -65.01 | 1.04 | 9.58 | H | Pass |
| 7520 | -55.31 | -13 | -42.31 | -66.85 | -65.42 | 1.35 | 11.46 | H | Pass |
| 9399 | -51.14 | -13 | -38.14 | -63.57 | -62.20 | 1.75 | 12.81 | H | Pass |



| | | | |
|------------------------|--|----------------------------|----------|
| Band : | GSM1900 | Temperature : | 22~23°C |
| Test Mode : | GSM Link (GMSK) | Relative Humidity : | 42~43% |
| Test Engineer : | Star Wei | Polarization : | Vertical |
| Remark : | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | |




Site : 03CH01-KS
 Condition : FCC PART22 24 HF_EIRP_FACTOR130726 VERTICAL
 EUT : (FG) 421402
 Plane : Y

| Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Over Limit (dB) | SPA Reading (dBm) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) | Result |
|-------------------|--------------|---------------|-------------------|---------------------|--------------------|----------------------|-------------------------|----------------------|--------|
| 3760 | -52.75 | -13 | -39.75 | -61.15 | -59.13 | 0.78 | 7.16 | V | Pass |
| 5640 | -53.83 | -13 | -40.83 | -66.48 | -62.37 | 1.04 | 9.58 | V | Pass |
| 7520 | -52.25 | -13 | -39.25 | -66.34 | -62.36 | 1.35 | 11.46 | V | Pass |
| 9399 | -50.82 | -13 | -37.82 | -63.35 | -61.88 | 1.75 | 12.81 | V | Pass |



| | | | |
|------------------------|--|----------------------------|------------|
| Band : | GSM1900 | Temperature : | 22~23°C |
| Test Mode : | EDGE class 8 Link (8PSK) | Relative Humidity : | 42~43% |
| Test Engineer : | Star Wei | Polarization : | Horizontal |
| Remark : | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | |




Site : 03CH01-KS
 Condition : FCC PART22 24 HF_EIRP_FACTOR130726 HORIZONTAL
 EUT : (FG) 421402
 Plane : Y

| Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Over Limit (dB) | SPA Reading (dBm) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) | Result |
|-------------------|--------------|---------------|-------------------|---------------------|--------------------|----------------------|-------------------------|----------------------|--------|
| 3760 | -61.88 | -13 | -48.88 | -65.23 | -68.26 | 0.78 | 7.16 | H | Pass |
| 5640 | -56.83 | -13 | -43.83 | -66.89 | -65.37 | 1.04 | 9.58 | H | Pass |
| 7520 | -55.35 | -13 | -42.35 | -66.89 | -65.46 | 1.35 | 11.46 | H | Pass |



| | | | |
|------------------------|--|----------------------------|----------|
| Band : | GSM1900 | Temperature : | 22~23°C |
| Test Mode : | EDGE class 8 Link (8PSK) | Relative Humidity : | 42~43% |
| Test Engineer : | Star Wei | Polarization : | Vertical |
| Remark : | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | |




Site : 03CH01-KS
 Condition : FCC PART22 24 HF_EIRP_FACTOR130726 VERTICAL
 EUT : (FG) 421402
 Plane : Y

| Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Over Limit (dB) | SPA Reading (dBm) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) | Result |
|-------------------|--------------|---------------|-------------------|---------------------|--------------------|----------------------|-------------------------|----------------------|--------|
| 3760 | -56.36 | -13 | -43.36 | -64.76 | -62.74 | 0.78 | 7.16 | V | Pass |
| 5640 | -54.79 | -13 | -41.79 | -67.44 | -63.33 | 1.04 | 9.58 | V | Pass |
| 7520 | -52.45 | -13 | -39.45 | -66.54 | -62.56 | 1.35 | 11.46 | V | Pass |



| | | | |
|------------------------|--|----------------------------|------------|
| Band : | WCDMA Band V | Temperature : | 22~23°C |
| Test Mode : | RMC 12.2Kbps Link (QPSK) | Relative Humidity : | 42~43% |
| Test Engineer : | Star Wei | Polarization : | Horizontal |
| Remark : | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | |




Site : 03CH01-KS
 Condition : FCC PART22 24 HF_EIRP_FACTOR130726 HORIZONTAL
 EUT : (FG) 421402
 Plane : Y

| Frequency (MHz) | ERP (dBm) | Limit (dBm) | Over Limit (dB) | SPA Reading (dBm) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) | Result |
|-------------------|-------------|---------------|-------------------|---------------------|--------------------|----------------------|-------------------------|----------------------|--------|
| 1672 | -73.72 | -13 | -60.72 | -64.84 | -74.37 | 0.57 | 3.37 | H | Pass |
| 2508 | -68.77 | -13 | -55.77 | -67.44 | -71.00 | 0.78 | 5.16 | H | Pass |
| 3344 | -66.90 | -13 | -53.90 | -66.53 | -70.54 | 0.87 | 6.66 | H | Pass |



| | | | |
|------------------------|--|----------------------------|----------|
| Band : | WCDMA Band V | Temperature : | 22~23°C |
| Test Mode : | RMC 12.2Kbps Link (QPSK) | Relative Humidity : | 42~43% |
| Test Engineer : | Star Wei | Polarization : | Vertical |
| Remark : | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | |




Site : 03CH01-KS
 Condition : FCC PART22 24 HF_EIRP_FACTOR130726 VERTICAL
 EUT : (FG) 421402
 Plane : Y

| Frequency (MHz) | ERP (dBm) | Limit (dBm) | Over Limit (dB) | SPA Reading (dBm) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) | Result |
|-------------------|-------------|---------------|-------------------|---------------------|--------------------|----------------------|-------------------------|----------------------|--------|
| 1670 | -64.54 | -13 | -51.54 | -61.59 | -65.19 | 0.57 | 3.37 | V | Pass |
| 2508 | -65.08 | -13 | -52.08 | -67.51 | -67.31 | 0.78 | 5.16 | V | Pass |
| 3344 | -64.80 | -13 | -51.80 | -65.86 | -68.44 | 0.87 | 6.66 | V | Pass |



| | | | |
|------------------------|--|----------------------------|------------|
| Band : | WCDMA Band II | Temperature : | 22~23°C |
| Test Mode : | RMC 12.2Kbps Link (QPSK) | Relative Humidity : | 42~43% |
| Test Engineer : | Star Wei | Polarization : | Horizontal |
| Remark : | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | |




Site : 03CH01-KS
 Condition : FCC PART22 24 HF_EIRP_FACTOR130726 HORIZONTAL
 EUT : (FG) 421402
 Plane : Y

| Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Over Limit (dB) | SPA Reading (dBm) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) | Result |
|-------------------|--------------|---------------|-------------------|---------------------|--------------------|----------------------|-------------------------|----------------------|--------|
| 3758 | -48.01 | -13 | -35.01 | -56.04 | -54.39 | 0.78 | 7.16 | H | Pass |
| 5640 | -57.44 | -13 | -44.44 | -67.50 | -65.98 | 1.04 | 9.58 | H | Pass |
| 7520 | -54.58 | -13 | -41.58 | -66.12 | -64.69 | 1.35 | 11.46 | H | Pass |



| | | | |
|------------------------|--|----------------------------|----------|
| Band : | WCDMA Band II | Temperature : | 22~23°C |
| Test Mode : | RMC 12.2Kbps Link (QPSK) | Relative Humidity : | 42~43% |
| Test Engineer : | Star Wei | Polarization : | Vertical |
| Remark : | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | |



Site : 03CH01-KS
 Condition : FCC PART22 24 HF_EIRP_FACTOR130726 VERTICAL
 EUT : (FG) 421402
 Plane : Y

| Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Over Limit (dB) | SPA Reading (dBm) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) | Result |
|-------------------|--------------|---------------|-------------------|---------------------|--------------------|----------------------|-------------------------|----------------------|--------|
| 3762 | -42.03 | -13 | -29.03 | -53.11 | -48.41 | 0.78 | 7.16 | V | Pass |
| 5640 | -54.78 | -13 | -41.78 | -67.43 | -63.32 | 1.04 | 9.58 | V | Pass |
| 7520 | -53.02 | -13 | -40.02 | -67.11 | -63.13 | 1.35 | 11.46 | V | Pass |

3.8 Frequency Stability Measurement

3.8.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.8.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.8.3 Test Procedures for Temperature Variation

1. The EUT was set up in the thermal chamber and connected with the base station.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.8.4 Test Procedures for Voltage Variation

1. The EUT was placed in a temperature chamber at $25\pm 5^{\circ}\text{C}$ and connected with the base station.
2. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

3.8.5 Test Setup



3.8.6 Test Result of Temperature Variation

| | | | |
|---------------|---------|-------------|-----------|
| Band : | GSM 850 | Channel : | 189 |
| Limit (ppm) : | 2.5 | Frequency : | 836.4 MHz |

| Temperature (°C) | GSM | | EDGE class 8 | | Result |
|------------------|-----------------|-----------------|-----------------|-----------------|--------|
| | Freq. Dev. (Hz) | Deviation (ppm) | Freq. Dev. (Hz) | Deviation (ppm) | |
| -30 | -28 | -0.03 | -32 | -0.04 | PASS |
| -20 | 22 | +0.03 | 28 | +0.03 | |
| -10 | 24 | +0.03 | 27 | +0.03 | |
| 0 | -19 | -0.02 | -24 | -0.03 | |
| 10 | 17 | +0.02 | 18 | +0.02 | |
| 20 | 15 | +0.02 | -16 | -0.02 | |
| 30 | 11 | +0.01 | 13 | +0.02 | |
| 40 | -17 | -0.02 | -15 | -0.02 | |
| 50 | -21 | -0.02 | -20 | -0.02 | |

| | | | |
|---------------|----------|-------------|------------|
| Band : | GSM 1900 | Channel : | 661 |
| Limit (ppm) : | 2.5 | Frequency : | 1880.0 MHz |

| Temperature (°C) | GSM | | EDGE class 8 | | Result |
|------------------|-----------------|-----------------|-----------------|-----------------|--------|
| | Freq. Dev. (Hz) | Deviation (ppm) | Freq. Dev. (Hz) | Deviation (ppm) | |
| -30 | -28 | -0.01 | -35 | -0.02 | PASS |
| -20 | 24 | +0.01 | -29 | -0.02 | |
| -10 | 22 | +0.01 | 26 | +0.01 | |
| 0 | 17 | +0.01 | 21 | +0.01 | |
| 10 | 16 | +0.01 | 18 | +0.01 | |
| 20 | -19 | -0.01 | 16 | +0.01 | |
| 30 | 21 | +0.01 | -19 | -0.01 | |
| 40 | 15 | +0.01 | 21 | +0.01 | |
| 50 | 17 | +0.01 | -18 | -0.01 | |



| | | | |
|----------------------|--------------|--------------------|-----------|
| Band : | WCDMA Band V | Channel : | 4182 |
| Limit (ppm) : | 2.5 | Frequency : | 836.4 MHz |

| Temperature (°C) | RMC 12.2Kbps | | Result |
|------------------|-----------------|-----------------|--------|
| | Freq. Dev. (Hz) | Deviation (ppm) | |
| -30 | -35 | -0.04 | PASS |
| -20 | 32 | +0.04 | |
| -10 | -29 | -0.03 | |
| 0 | 24 | +0.03 | |
| 10 | 21 | +0.02 | |
| 20 | -19 | -0.02 | |
| 30 | 17 | +0.02 | |
| 40 | -16 | -0.02 | |
| 50 | 13 | +0.02 | |

| | | | |
|----------------------|---------------|--------------------|----------|
| Band : | WCDMA Band II | Channel : | 9400 |
| Limit (ppm) : | 2.5 | Frequency : | 1880 MHz |

| Temperature (°C) | RMC 12.2Kbps | | Result |
|------------------|-----------------|-----------------|--------|
| | Freq. Dev. (Hz) | Deviation (ppm) | |
| -30 | -35 | -0.02 | PASS |
| -20 | -27 | -0.01 | |
| -10 | 22 | +0.01 | |
| 0 | 26 | +0.01 | |
| 10 | -19 | -0.01 | |
| 20 | 17 | +0.01 | |
| 30 | 16 | +0.01 | |
| 40 | 13 | +0.01 | |
| 50 | -18 | -0.01 | |



3.8.7 Test Result of Voltage Variation

| Band & Channel | Mode | Voltage (Volt) | Freq. Dev. (Hz) | Deviation (ppm) | Limit (ppm) | Result |
|-------------------------|-----------------|----------------|-----------------|-----------------|-------------|--------|
| GSM 850 CH189 | GSM | 3.7 | 17 | +0.02 | 2.5 | PASS |
| | | BEP | 15 | +0.02 | | |
| | | 4.2 | -21 | -0.02 | | |
| | EDGE class 8 | 3.7 | -24 | -0.03 | | |
| | | BEP | -16 | -0.02 | | |
| | | 4.2 | 13 | +0.02 | | |
| GSM 1900 CH661 | GSM | 3.7 | 22 | +0.01 | | |
| | | BEP | -19 | -0.01 | | |
| | | 4.2 | 17 | +0.01 | | |
| | EDGE class 8 | 3.7 | 21 | +0.01 | | |
| | | BEP | -18 | -0.01 | | |
| | | 4.2 | 26 | +0.01 | | |
| WCDMA Band V CH4182 | RMC 12.2Kbps | 3.7 | -19 | -0.02 | | |
| | | BEP | 24 | +0.03 | | |
| | | 4.2 | -17 | -0.02 | | |
| WCDMA Band II CH9400 | RMC 12.2Kbps | 3.7 | -18 | -0.01 | | |
| | | BEP | 22 | +0.01 | | |
| | | 4.2 | -19 | -0.01 | | |

Note:

1. Normal Voltage = 3.7V.
2. Battery End Point (BEP) = 3.5 V.



4 List of Measuring Equipment

| Instrument | Manufacturer | Model No. | Serial No. | Characteristics | Calibration Date | Test Date | Due Date | Remark |
|---------------------------|--------------|-----------|------------|-----------------------------------|------------------|---------------------------------|---------------|-----------------------|
| Spectrum Analyzer | R&S | FSP40 | 100319 | 9kHz~40GHz; Max 30dBm | Dec. 28, 2013 | Feb. 17, 2014 | Dec. 27, 2014 | Conducted (TH01-KS) |
| Spectrum Analyzer | R&S | FSV30 | 100845 | 9kHz~30GHz; Max input Power 30dBm | Dec. 04, 2013 | Feb. 17, 2014 | Dec. 03, 2014 | Conducted (TH01-KS) |
| Pulse Power Sensor | Anritsu | MA2411B | 0917070 | 30MHz~40GHz (-20~+20dBm) | Feb. 28, 2013 | Feb. 17, 2014 | Feb. 27, 2014 | Conducted (TH01-KS) |
| Power Meter | Anritsu | ML2495A | 1005002 | 50MHz Bandwidth | Feb. 28, 2013 | Feb. 17, 2014 | Feb. 27, 2014 | Conducted (TH01-KS) |
| Thermal Chamber | Ten Billion | TTC-B3S | TBN-960502 | (-40~+150) | Dec. 10, 2013 | Feb. 17, 2014 | Dec. 09, 2014 | Conducted (TH01-KS) |
| EMI Test Receiver | R&S | ESCI | 100534 | 9kHz~3GHz | Nov. 05, 2013 | Feb. 18, 2014~ Feb. 25, 2014 | Nov. 04, 2014 | Radiation (03CH01-KS) |
| Spectrum Analyzer | R&S | FSP30 | 101399 | 9kHz~30GHz | May 23, 2013 | Feb. 18, 2014~ Feb. 25, 2014 | May 22, 2014 | Radiation (03CH01-KS) |
| Bilog Antenna | SCHAFFNER | CBL6112D | 23182 | 25MHz~2GHz | Jan. 08, 2014 | Feb. 18, 2014~ Feb. 25, 2014 | Jan. 07, 2015 | Radiation (03CH01-KS) |
| Double Ridge Horn Antenna | EMCO | 3117 | 00075959 | 1GHz~18GHz | Jan. 08, 2014 | Feb. 18, 2014~ Feb. 25, 2014 | Jan. 07, 2015 | Radiation (03CH01-KS) |
| SHF-EHF Horn | Schwarzbeck | BBHA 9170 | BBHA170249 | 15GHz~40GHz | Nov. 22, 2013 | Feb. 18, 2014~ Feb. 25, 2014 | Nov. 21, 2014 | Radiation (03CH01-KS) |
| Active Horn Antenna | com-power | AHA-118 | 701030 | 1GHz~18GHz | Nov. 18, 2013 | Feb. 18, 2014~ Feb. 25, 2014 | Nov. 17, 2014 | Radiation (03CH01-KS) |
| Amplifier | com-power | PA-103A | 161069 | 1MHz~1GHz | May 23, 2013 | Feb. 18, 2014~ Feb. 25, 2014 | May 22, 2014 | Radiation (03CH01-KS) |
| Amplifier | Agilent | 8449B | 3008A02371 | 1GHz~26.5GHz | Dec. 10, 2013 | Feb. 18, 2014~ Feb. 25, 2014 | Dec. 09, 2014 | Radiation (03CH01-KS) |
| Turn Table | MF | MF7802 | N/A | 0~360 degree | NCR | Feb. 18, 2014~ Feb. 25, 2014 | NCR | Radiation (03CH01-KS) |
| Antenna Mast | MF | MF7802 | N/A | 1 m~4 m | NCR | Feb. 18, 2014~ Feb. 25, 2014 | NCR | Radiation (03CH01-KS) |



| Instrument | Manufacturer | Model No. | Serial No. | Characteristics | Calibration Date | Test Date | Due Date | Remark |
|------------------------------|--------------|-----------|------------|------------------------|------------------|--------------|--------------|---------------------|
| Spectrum Analyzer | R&S | FSP 7 | 100819 | 9kHz~7GHz | May 23, 2013 | May 07, 2014 | May 22, 2014 | ERP/EIRP (OTA01-KS) |
| Switch Control Manframe | Agilent | 3499A | MY42005452 | N/A | N/A | May 07, 2014 | N/A | ERP/EIRP (OTA01-KS) |
| Dual 1-to-6(4) MW MUX | Agilent | N2276A | MY42000841 | N/A | N/A | May 07, 2014 | N/A | ERP/EIRP (OTA01-KS) |
| Microwave Switch | Agilent | 44476A | MY42002573 | N/A | N/A | May 07, 2014 | N/A | ERP/EIRP (OTA01-KS) |
| Microwave Switch | Agilent | 44476A | MY42002586 | N/A | N/A | May 07, 2014 | N/A | ERP/EIRP (OTA01-KS) |
| Diagonal Dual Polarized Horn | ETS-Lindgren | 3164-04 | 00066993 | 700MHz~6GHz | N/A | May 07, 2014 | N/A | ERP/EIRP (OTA01-KS) |
| Multi-Devices Controller | ETS-Lindgren | 2090-OPT1 | 00066604 | N/A | N/A | May 07, 2014 | N/A | ERP/EIRP (OTA01-KS) |
| Conical Log Spiral (Small) | ETS-Lindgren | 3102 | 00066951 | 1~10GHz | N/A | May 07, 2014 | N/A | ERP/EIRP (OTA01-KS) |
| Turn Table | ETS-Lindgren | 2088 | N/A | Resolution : 0.1degree | N/A | May 07, 2014 | N/A | ERP/EIRP (OTA01-KS) |
| Limiting Amplifier | ETS-lindgren | 109643 | 920326 | 10MHz~2.5GHz | N/A | May 07, 2014 | N/A | ERP/EIRP (OTA01-KS) |
| EMQuest | ETS-Lindgren | EMQ-100 | 1125 | N/A | N/A | May 07, 2014 | N/A | ERP/EIRP (OTA01-KS) |
| Medium Duty Holder | ETS-Lindgren | 2015 | N/A | N/A | N/A | May 07, 2014 | N/A | ERP/EIRP (OTA01-KS) |



5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

| | |
|---|------|
| Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$) | 2.54 |
|---|------|