



FCC RF Test Report

APPLICANT : ZTE CORPORATION
EQUIPMENT : WCDMA/LTE Multi-mode Digital
Mobile Phone
BRAND NAME : ZTE
MODEL NAME : Z836BL
FCC ID : SRQ-Z836BL
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System

The product was completed on Oct. 31, 2016. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

Prepared by: James Huang / Manager

Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China



TABLE OF CONTENTS

SUMMARY OF TEST RESULT 4

1 GENERAL DESCRIPTION..... 5

1.1 Applicant 5

1.2 Manufacturer..... 5

1.3 Product Feature of Equipment Under Test..... 5

1.4 Product Specification of Equipment Under Test..... 6

1.5 Modification of EUT 6

1.6 Testing Location 6

1.7 Applicable Standards..... 6

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST..... 7

2.1 Descriptions of Test Mode 7

2.2 Test Mode..... 8

2.3 Connection Diagram of Test System..... 9

2.4 Support Unit used in test configuration and system 10

2.5 EUT Operation Test Setup 10

2.6 Measurement Results Explanation Example..... 11

3 TEST RESULT 12

3.1 6dB Bandwidth Measurement 12

3.2 Peak Output Power Measurement 17

3.3 Power Spectral Density Measurement 18

3.4 Conducted Band Edges and Spurious Emission Measurement 27

3.5 Radiated Band Edges and Spurious Emission Measurement 36

3.6 AC Conducted Emission Measurement..... 40

3.7 Antenna Requirements 45

4 LIST OF MEASURING EQUIPMENT..... 46

5 UNCERTAINTY OF EVALUATION..... 47

APPENDIX A. CONDUCTED TEST RESULTS

APPENDIX B. RADIATED TEST RESULTS

APPENDIX C. DUTY CYCLE PLOTS

APPENDIX D. SETUP PHOTOGRAPHS



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.2	15.247(b)(1)	Peak Output Power	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	$\leq 20\text{dBc}$	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 8.21 dB at 2483.500 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 6.59 dB at 0.549 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-



1 General Description

1.1 Applicant

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

1.2 Manufacturer

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	WCDMA/LTE Multi-mode Digital Mobile Phone
Brand Name	ZTE
Model Name	Z836BL
FCC ID	SRQ-Z836BL
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/ HSPA+(16QAM uplink is not supported)/LTE/ WLAN 2.4GHz 802.11b/g/n HT20/HT40/ Bluetooth v3.0 + EDR/Bluetooth v4.0 LE/ Bluetooth v4.2 LE
IMEI Code	Conducted: 862447030002950 Radiated: 862447030002216 Conduction: 862447030002588
HW Version	Z836BLHWV1.0
SW Version	Z836BLV1.0.0B01
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	40
Carrier Frequency of Each Channel	40 Channel(37 hopping + 3 advertising channel)
Maximum Output Power to Antenna	Bluetooth v4.0 LE: 9.35 dBm (0.0086 W) Bluetooth v4.2 LE: -0.16 dBm (0.0010 W)
Antenna Type / Gain	PIFA Antenna with gain -3.00 dBi
Type of Modulation	GFSK

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.			
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958			
Test Site No.	Sporton Site No.			FCC Registration No.
	TH01-KS	CO01-KS	03CH03-KS	306251

Note: The test site complies with ANSI C63.4 2014 requirement.

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Descriptions of Test Mode

The RF output power was recorded in the following table:

Channel	Frequency	Bluetooth LE RF Output Power	
		Data Rate / Modulation	
		GFSK	
		v4.0	v4.2
Ch00	2402MHz	9.35 dBm	-0.16 dBm
Ch19	2441MHz	8.81 dBm	-0.82 dBm
Ch39	2480MHz	8.12 dBm	-0.94 dBm

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). Pre-scanned tests, X, Y, Z in three orthogonal panels to determine the final configuration (Z plane as worst plane) from all possible combinations.

- b. AC power line Conducted Emission was tested under maximum output power.




2.2 Test Mode

The following summary table is showing all test modes to demonstrate in compliance with the standard.


Summary table of Test Cases	
Test Item	Data Rate / Modulation
	Bluetooth v4.0/v4.2 LE / GFSK
Conducted TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
Radiated TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
AC Conducted Emission	Mode 1 : GSM850 Idle + Bluetooth Link + WLAN Link + Earphone + USB Cable (Charging from Adapter 1) + Battery 1 Mode 2 : GSM850 Idle + Bluetooth Link + WLAN Link + Earphone + USB Cable (Charging from Adapter 2) + Battery 2 Mode 3 : GSM850 Idle + Bluetooth Link + WLAN Link + Earphone + USB Cable (Charging from Adapter 3) + Battery 1
Remark: The worst case of conducted emission is mode 1; only the test data of it was reported.	

2.3 Connection Diagram of Test System


<Bluetooth v4.0 LE Tx Mode>



<Bluetooth v4.2 LE Tx Mode>



<AC Conducted Emission Mode>



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	WLAN AP	Linksys	WRT600N	Q87-WRT600NV11	N/A	Unshielded, 1.8 m
3.	Notebook	Lenovo	G480	N/A	N/A	Shielded cable DC O/P 1.8 m Unshielded AC I/P cable 1.2 m
4.	Bluetooth Earphone	Nokia	BH-106	QTLBH-106	N/A	N/A
5.	Earphone	Lenovo	LH102	N/A	Unshielded, 1.2 m	N/A

2.5 EUT Operation Test Setup

For Bluetooth LE function, the engineering test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.



2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss.

Following shows an offset computation example with cable loss 5.50 dB.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)}. \\ &= 5.50 \text{ (dB)} \end{aligned}$$

3 Test Result

3.1 6dB Bandwidth Measurement

3.1.1 Limit of 6dB Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

3.1.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. Measure and record the results in the test report.

3.1.4 Test Setup






3.1.5 Test Result of 6dB Bandwidth

Test data refer to Appendix A.

Bluetooth v4.0 LE


6 dB Bandwidth Plot on Channel 00



Date: 30 SEP 2016 21:56:45




6 dB Bandwidth Plot on Channel 19



Date: 30.SEP.2016 21:59:42

6 dB Bandwidth Plot on Channel 39




Date: 30.SEP.2016 22:03:33




Bluetooth v4.2 LE

6 dB Bandwidth Plot on Channel 00






6 dB Bandwidth Plot on Channel 19



6 dB Bandwidth Plot on Channel 39



3.2 Peak Output Power Measurement

3.2.1 Limit of Peak Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v03r05.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Test data refers to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup






3.3.5 Test Result of Power Spectral Density

Test data refers to Appendix A.

3.3.6 Test Result of Power Spectral Density Plots (100kHz)

Bluetooth v4.0 LE


PSD 100kHz Plot on Channel 00



Date: 30.SEP.2016 21:57:46




PSD 100kHz Plot on Channel 19



Date: 30.SEP.2016 22:01:28

PSD 100kHz Plot on Channel 39




Date: 30.SEP.2016 22:04:09



Bluetooth v4.2 LE

PSD 100kHz Plot on Channel 00




Date: 30.SEP.2016 22:19:28



3.3.7 Test Result of Power Spectral Density Plots (3kHz)

Bluetooth v4.0 LE


PSD 3kHz Plot on Channel 00



Date: 30.SEP.2016 21:57:28




PSD 3kHz Plot on Channel 19



Date: 30.SEP.2016 22:01:12

PSD 3kHz Plot on Channel 39




Date: 30.SEP.2016 22:03:49



Bluetooth v4.2 LE


PSD 3kHz Plot on Channel 00



Date: 30.SEP.2016 22:19:13




PSD 3kHz Plot on Channel 19



Date: 30.SEP.2016 22:23:49

PSD 3kHz Plot on Channel 39



Date: 30.SEP.2016 22:31:41

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.


3.4.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.4.3 Test Procedure

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup






3.4.5 Test Result of Conducted Band Edges Plots


Bluetooth v4.0 LE

Low Band Edge Plot on Channel 00



Date: 30.SEP.2016 21:57:55

High Band Edge Plot on Channel 39




Date: 30.SEP.2016 22:04:18




Bluetooth v4.2 LE

Low Band Edge Plot on Channel 00



Date: 30.SEP.2016 22:19:42

High Band Edge Plot on Channel 39




Date: 30.SEP.2016 22:32:04



3.4.6 Test Result of Conducted Spurious Emission Plots


Bluetooth v4.0 LE

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00



Date: 30.SEP.2016 21:58:05


Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00



Date: 30.SEP.2016 21:58:13




Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19



Date: 30.SEP.2016 22:01:39


Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19



Date: 30.SEP.2016 22:01:47




Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39



Date: 30.SEP.2016 22:04:29

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39




Date: 30.SEP.2016 22:04:38




Bluetooth v4.2 LE

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps
GFSK Channel 00



Date: 30.SEP.2016 22:20:20


Conducted Spurious Emission Plot on Bluetooth LE 1Mbps
GFSK Channel 00



Date: 30.SEP.2016 22:20:28




Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19



Date: 30.SEP.2016 22:24:11


Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19



Date: 30.SEP.2016 22:24:19




Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39



Date: 30.SEP.2016 22:32:17

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39



Date: 30.SEP.2016 22:32:26



3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.




3.5.3 Test Procedures


1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.
For average measurement:
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B.

3.5.7 Duty Cycle

Please refer to Appendix C.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B.



3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBµV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


3.6.4 Test Setup





3.6.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	20~22°C
Test Engineer :	Morris Li	Relative Humidity :	48~50%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link + Earphone + USB Cable (Charging from Adapter 1) + Battery 1		




Site : CO01-KS
 Condition : FCC PART 15C LISN-L-20151024 LINE
 mode : Mode 1
 IMEI : 862447030002588/01

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1 *	0.564	42.22	-13.78	56.00	31.81	0.23	10.18	QP
2	0.564	29.92	-16.08	46.00	19.51	0.23	10.18	Average
3	0.923	39.33	-16.67	56.00	28.90	0.25	10.18	QP
4	0.923	25.03	-20.97	46.00	14.60	0.25	10.18	Average
5	1.077	38.03	-17.97	56.00	27.60	0.24	10.19	QP
6	1.077	27.13	-18.87	46.00	16.70	0.24	10.19	Average
7	1.289	39.81	-16.19	56.00	29.40	0.22	10.19	QP
8	1.289	29.21	-16.79	46.00	18.80	0.22	10.19	Average
9	1.487	38.20	-17.80	56.00	27.80	0.21	10.19	QP
10	1.487	27.30	-18.70	46.00	16.90	0.21	10.19	Average
11	1.654	35.19	-20.81	56.00	24.80	0.20	10.19	QP
12	1.654	25.69	-20.31	46.00	15.30	0.20	10.19	Average
13	2.321	35.18	-20.82	56.00	24.80	0.18	10.20	QP
14	2.321	25.98	-20.02	46.00	15.60	0.18	10.20	Average



Test Mode :	Mode 1	Temperature :	20~22°C
Test Engineer :	Morris Li	Relative Humidity :	48~50%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link + Earphone + USB Cable (Charging from Adapter 1) + Battery 1		




Site : CO01-KS
 Condition : FCC PART 15C LISN-N-20151024 NEUTRAL
 mode : Mode 1
 IMEI : 862447030002588/01

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.442	50.01	-7.01	57.02	39.50	0.32	10.19	QP
2	0.442	38.31	-8.71	47.02	27.80	0.32	10.19	Average
3	0.464	43.31	-13.32	56.63	32.80	0.32	10.19	QP
4	0.464	31.21	-15.42	46.63	20.70	0.32	10.19	Average
5 *	0.549	49.41	-6.59	56.00	38.90	0.33	10.18	QP
6	0.549	36.31	-9.69	46.00	25.80	0.33	10.18	Average
7	0.658	43.12	-12.88	56.00	32.60	0.34	10.18	QP
8	0.658	31.72	-14.28	46.00	21.20	0.34	10.18	Average
9	0.701	44.42	-11.58	56.00	33.90	0.34	10.18	QP
10	0.701	29.22	-16.78	46.00	18.70	0.34	10.18	Average
11	0.822	43.23	-12.77	56.00	32.70	0.35	10.18	QP
12	0.822	31.33	-14.67	46.00	20.80	0.35	10.18	Average
13	0.914	43.35	-12.65	56.00	32.81	0.36	10.18	QP
14	0.914	31.25	-14.75	46.00	20.71	0.36	10.18	Average
15	0.984	44.36	-11.64	56.00	33.80	0.37	10.19	QP
16	0.984	32.86	-13.14	46.00	22.30	0.37	10.19	Average
17	1.100	47.36	-8.64	56.00	36.80	0.37	10.19	QP
18	1.100	35.26	-10.74	46.00	24.70	0.37	10.19	Average
19	1.191	46.06	-9.94	56.00	35.50	0.37	10.19	QP
20	1.191	35.26	-10.74	46.00	24.70	0.37	10.19	Average
21	1.324	45.46	-10.54	56.00	34.90	0.37	10.19	QP
22	1.324	36.36	-9.64	46.00	25.80	0.37	10.19	Average



Test Mode :	Mode 1	Temperature :	20~22°C
Test Engineer :	Morris Li	Relative Humidity :	48~50%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link + Earphone + USB Cable (Charging from Adapter 1) + Battery 1		



Site : CO01-KS
 Condition : FCC PART 15C LISN-N-20151024 NEUTRAL
 mode : Mode 1
 IMEI : 862447030002588/01

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
23	1.418	44.36	-11.64	56.00	33.79	0.38	10.19	QP
24	1.418	35.76	-10.24	46.00	25.19	0.38	10.19	Average
25	1.552	44.46	-11.54	56.00	33.89	0.38	10.19	QP
26	1.552	35.26	-10.74	46.00	24.69	0.38	10.19	Average
27	1.645	44.47	-11.53	56.00	33.90	0.38	10.19	QP
28	1.645	34.27	-11.73	46.00	23.70	0.38	10.19	Average
29	2.435	43.78	-12.22	56.00	33.20	0.38	10.20	QP
30	2.435	35.28	-10.72	46.00	24.70	0.38	10.20	Average
31	2.884	42.79	-13.21	56.00	32.21	0.37	10.21	QP
32	2.884	34.39	-11.61	46.00	23.81	0.37	10.21	Average
33	3.074	43.39	-12.61	56.00	32.80	0.37	10.22	QP
34	3.074	33.49	-12.51	46.00	22.90	0.37	10.22	Average
35	3.881	41.40	-14.60	56.00	30.79	0.37	10.24	QP
36	3.881	31.00	-15.00	46.00	20.39	0.37	10.24	Average
37	4.136	42.00	-14.00	56.00	31.40	0.36	10.24	QP
38	4.136	31.40	-14.60	46.00	20.80	0.36	10.24	Average
39	4.384	39.70	-16.30	56.00	29.10	0.36	10.24	QP
40	4.384	31.10	-14.90	46.00	20.50	0.36	10.24	Average
41	4.772	40.10	-15.90	56.00	29.50	0.36	10.24	QP
42	4.772	30.30	-15.70	46.00	19.70	0.36	10.24	Average
43	5.623	45.29	-14.71	60.00	34.70	0.34	10.25	QP
44	5.623	35.79	-14.21	50.00	25.20	0.34	10.25	Average
45	6.878	44.18	-15.82	60.00	33.61	0.29	10.28	QP
46	6.878	34.88	-15.12	50.00	24.31	0.29	10.28	Average



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Aug. 09, 2016	Sep. 30, 2016	Aug. 08, 2017	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 20, 2016	Sep. 30, 2016	Jan. 19, 2017	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 20, 2016	Sep. 30, 2016	Jan. 19, 2017	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESCI	100534	9kHz~3GHz	Oct. 24, 2015	Sep. 30, 2016~ Oct. 09, 2016	Oct. 23, 2016	Radiation (03CH03-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY551502 44	10Hz~44GHz	Apr. 22, 2016	Sep. 30, 2016~ Oct. 09, 2016	Apr. 21, 2017	Radiation (03CH03-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Nov. 07, 2015	Sep. 30, 2016~ Oct. 09, 2016	Nov. 06, 2016	Radiation (03CH03-KS)
Bilog Antenna	TeseQ	CBL6112D	35406	25MHz~2GHz	Apr. 16, 2016	Sep. 30, 2016~ Oct. 09, 2016	Apr. 15, 2017	Radiation (03CH03-KS)
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-135 6	1GHz~18GHz	Apr. 16, 2016	Sep. 30, 2016~ Oct. 09, 2016	Apr. 15, 2017	Radiation (03CH03-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA1702 49	15GHz~40GHz	Mar. 03, 2016	Sep. 30, 2016~ Oct. 09, 2016	Mar. 02, 2017	Radiation (03CH03-KS)
Amplifier	SONOMA	310N	187289	9kHz~1GHz	Aug. 09, 2016	Sep. 30, 2016~ Oct. 09, 2016	Aug. 08, 2017	Radiation (03CH03-KS)
high gain Amplifier	MITEQ	AMF-7D-0010 1800-30-10P	1943529	1GHz~18GHz	Jan. 20, 2016	Sep. 30, 2016~ Oct. 09, 2016	Jan. 19, 2017	Radiation (03CH03-KS)
Amplifier	Agilent	8449B	3008A023 70	1GHz~26.5GHz	Oct. 24, 2015	Sep. 30, 2016~ Oct. 09, 2016	Oct. 23, 2016	Radiation (03CH03-KS)
AC Power Source	Chroma	61601	F1040900 04	N/A	NCR	Sep. 30, 2016~ Oct. 09, 2016	NCR	Radiation (03CH03-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Sep. 30, 2016~ Oct. 09, 2016	NCR	Radiation (03CH03-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Sep. 30, 2016~ Oct. 09, 2016	NCR	Radiation (03CH03-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	Apr. 29, 2016	Oct. 31, 2016	Apr. 28, 2017	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Oct. 13, 2016	Oct. 31, 2016	Oct. 12, 2017	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Oct. 13, 2016	Oct. 31, 2016	Oct. 12, 2017	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP00000 0811	AC 0V~300V, 45Hz~1000Hz	Oct. 13, 2016	Oct. 31, 2016	Oct. 12, 2017	Conduction (CO01-KS)

NCR: No Calibration Required



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.3dB
---	-------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.5dB
---	-------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.5dB
---	-------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.6dB
---	-------



Appendix A. Conducted Test Results

Bluetooth v4.0 Low Energy

Test Engineer:	Ivan Chen	Temperature:	24~25	°C
Test Date:	2016/9/30	Relative Humidity:	54~55	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.05	0.67	0.50	Pass
BLE	1Mbps	1	19	2440	1.05	0.67	0.50	Pass
BLE	1Mbps	1	39	2480	1.05	0.67	0.50	Pass

TEST RESULTS DATA
Peak Power Table

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	9.35	30.00	-3.00	6.35	36.00	Pass
BLE	1Mbps	1	19	2440	8.81	30.00	-3.00	5.81	36.00	Pass
BLE	1Mbps	1	39	2480	8.12	30.00	-3.00	5.12	36.00	Pass

TEST RESULTS DATA
Average Power Table
(Reporting Only)

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
BLE	1Mbps	1	0	2402	2.03	9.04
BLE	1Mbps	1	19	2440	2.03	8.59
BLE	1Mbps	1	39	2480	2.03	7.87

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	8.40	-6.55	-3.00	8.00	Pass
BLE	1Mbps	1	19	2440	7.84	-7.04	-3.00	8.00	Pass
BLE	1Mbps	1	39	2480	6.67	-8.18	-3.00	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 20dBc limit.

Bluetooth v4.2 Low Energy

Test Engineer:	Ivan Chen	Temperature:	24~25	°C
Test Date:	2016/9/30	Relative Humidity:	54~55	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.05	0.67	0.50	Pass
BLE	1Mbps	1	19	2440	1.05	0.67	0.50	Pass
BLE	1Mbps	1	39	2480	1.05	0.67	0.50	Pass

TEST RESULTS DATA
Peak Power Table

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	-0.16	30.00	-3.00	-3.16	36.00	Pass
BLE	1Mbps	1	19	2440	-0.82	30.00	-3.00	-3.82	36.00	Pass
BLE	1Mbps	1	39	2480	-0.94	30.00	-3.00	-3.94	36.00	Pass

TEST RESULTS DATA
Average Power Table
(Reporting Only)

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
BLE	1Mbps	1	0	2402	3.29	-0.47
BLE	1Mbps	1	19	2440	3.29	-1.13
BLE	1Mbps	1	39	2480	3.29	-1.04

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	-1.25	-16.27	-3.00	8.00	Pass
BLE	1Mbps	1	19	2440	-1.67	-16.72	-3.00	8.00	Pass
BLE	1Mbps	1	39	2480	-2.79	-17.85	-3.00	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 20dBc limit.



Appendix B. Radiated Spurious Emission

Bluetooth v4.0 LE

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2365.51	50.17	-23.83	74	54.85	26.91	5.43	37.02	294	47	P	H
		2381.5	40.76	-13.24	54	45.38	26.95	5.45	37.02	294	47	A	H
	*	2402	102.88	-	-	107.43	27	5.47	37.02	294	47	P	H
	*	2402	102.49	-	-	107.04	27	5.47	37.02	294	47	A	H
		2388.52	50.54	-23.46	74	55.09	27	5.47	37.02	102	117	P	V
		2385.4	40.78	-13.22	54	45.4	26.95	5.45	37.02	102	117	A	V
	*	2402	104.53	-	-	109.08	27	5.47	37.02	102	117	P	V
	*	2402	103.92	-	-	108.47	27	5.47	37.02	102	117	A	V
BLE CH 19 2440MHz		2352.12	50.72	-23.28	74	55.4	26.91	5.43	37.02	316	61	P	H
		2356.02	40.69	-13.31	54	45.37	26.91	5.43	37.02	316	61	A	H
		2492.02	51.61	-22.39	74	55.25	27.77	5.52	36.93	316	61	P	H
		2489.26	41.55	-12.45	54	45.19	27.77	5.52	36.93	316	61	A	H
	*	2440	101.71	-	-	105.8	27.39	5.49	36.97	316	61	P	H
	*	2440	100.86	-	-	104.95	27.39	5.49	36.97	316	61	A	H
		2331.71	50.65	-23.35	74	55.45	26.82	5.39	37.01	149	118	P	V
		2375.13	40.65	-13.35	54	45.27	26.95	5.45	37.02	149	118	A	V
		2492.62	51.45	-22.55	74	55.09	27.77	5.52	36.93	149	118	P	V
		2486.56	41.53	-12.47	54	45.32	27.64	5.51	36.94	149	118	A	V
	*	2440	103.41	-	-	107.5	27.39	5.49	36.97	149	118	P	V
	*	2440	102.83	-	-	106.92	27.39	5.49	36.97	149	118	A	V



BLE CH 39 2480MHz		2483.56	54.58	-19.42	74	58.37	27.64	5.51	36.94	310	45	P	H
		2483.5	45.25	-8.75	54	49.04	27.64	5.51	36.94	310	45	A	H
	*	2480	100.46	-	-	104.25	27.64	5.51	36.94	310	45	P	H
	*	2480	100.14	-	-	103.93	27.64	5.51	36.94	310	45	A	H
		2483.56	57.29	-16.71	74	61.08	27.64	5.51	36.94	149	115	P	V
		2483.5	45.79	-8.21	54	49.58	27.64	5.51	36.94	149	115	A	V
	*	2480	101.51	-	-	105.3	27.64	5.51	36.94	149	115	P	V
	*	2480	100.93	-	-	104.72	27.64	5.51	36.94	149	115	A	V
Remark	<ol style="list-style-type: none"> No other spurious found. All results are PASS against Peak and Average limit line. 												



2.4GHz 2400~2483.5MHz
BLE (Harmonic @ 3m)

Table with 14 columns: BLE, Note, Frequency (MHz), Level (dBµV/m), Over Limit (dB), Limit Line (dBµV/m), Read Level (dBµV), Antenna Factor (dB/m), Cable Loss (dB), Preamp Factor (dB), Ant Pos (cm), Table Pos (deg), Peak Avg. (P/A), Pol. (H/V). Rows include data for BLE CH 00 (2402MHz), BLE CH 19 (2440MHz), and BLE CH 39 (2480MHz).



Emission below 1GHz

2.4GHz BLE (LF)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz BLE LF		32.91	27.1	-12.9	40	31.55	26.18	0.69	31.32	100	33	P	H
		99.84	19.89	-23.61	43.5	31.22	18.9	1.21	31.44	-	-	P	H
		128.94	19.9	-23.6	43.5	31.72	18.31	1.37	31.5	-	-	P	H
		141.55	18.82	-24.68	43.5	30.85	18.06	1.44	31.53	-	-	P	H
		216.24	21.96	-24.04	46	35.48	16.23	1.73	31.48	-	-	P	H
		455.83	27.11	-18.89	46	30.45	25.24	2.66	31.24	-	-	P	H
		30.97	26.61	-13.39	40	30.38	26.86	0.66	31.29	300	125	P	V
		98.87	19.71	-23.79	43.5	31.13	18.82	1.2	31.44	-	-	P	V
		216.24	21.66	-24.34	46	35.18	16.23	1.73	31.48	-	-	P	V
		443.22	27.32	-18.68	46	30.76	25.18	2.62	31.24	-	-	P	V
		777.87	30.33	-15.67	46	30.19	27.63	3.54	31.03	-	-	P	V
		941.8	33.15	-12.85	46	30.6	29.33	3.96	30.74	-	-	P	V
Remark	<ol style="list-style-type: none"> No other spurious found. All results are PASS against limit line. 												



Bluetooth v4.2 LE

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
		(MHz)	(dBμV/m)	(dB)	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
					(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2363.43	50.19	-23.81	74	54.87	26.91	5.43	37.02	294	56	P	H
		2376.95	42.33	-11.67	54	46.95	26.95	5.45	37.02	294	56	A	H
	*	2402	91.69	-	-	96.24	27	5.47	37.02	294	56	P	H
	*	2402	91.18	-	-	95.73	27	5.47	37.02	294	56	A	H
		2366.68	50.4	-23.6	74	55.08	26.91	5.43	37.02	100	120	P	V
		2364.99	42.21	-11.79	54	46.89	26.91	5.43	37.02	100	120	A	V
	*	2402	94.25	-	-	98.8	27	5.47	37.02	100	120	P	V
	*	2402	93.77	-	-	98.32	27	5.47	37.02	100	120	A	V
BLE CH 19 2440MHz		2350.04	50.06	-23.94	74	54.8	26.86	5.41	37.01	314	55	P	H
		2362.26	42.09	-11.91	54	46.77	26.91	5.43	37.02	314	55	A	H
		2499.94	51.42	-22.58	74	55.06	27.77	5.52	36.93	314	55	P	H
		2499.1	42.83	-11.17	54	46.47	27.77	5.52	36.93	314	55	A	H
	*	2440	92.74	-	-	96.83	27.39	5.49	36.97	314	55	P	H
	*	2440	92.21	-	-	96.3	27.39	5.49	36.97	314	55	A	H
		2314.03	51.32	-22.68	74	56.19	26.77	5.37	37.01	146	114	P	V
		2379.03	42.04	-11.96	54	46.66	26.95	5.45	37.02	146	114	A	V
		2487.58	51.47	-22.53	74	55.11	27.77	5.52	36.93	146	114	P	V
		2493.58	42.77	-11.23	54	46.41	27.77	5.52	36.93	146	114	A	V
	*	2440	93.15	-	-	97.24	27.39	5.49	36.97	146	114	P	V
	*	2440	92.54	-	-	96.63	27.39	5.49	36.97	146	114	A	V



BLE CH 39 2480MHz		2495.86	52.25	-21.75	74	55.89	27.77	5.52	36.93	308	52	P	H
		2494.72	42.79	-11.21	54	46.43	27.77	5.52	36.93	308	52	A	H
	*	2480	91.86	-	-	95.65	27.64	5.51	36.94	308	52	P	H
	*	2480	91.43	-	-	95.22	27.64	5.51	36.94	308	52	A	H
		2493.82	51.95	-22.05	74	55.59	27.77	5.52	36.93	104	124	P	V
		2483.92	43.39	-10.61	54	47.18	27.64	5.51	36.94	104	124	A	V
	*	2480	91.22	-	-	95.01	27.64	5.51	36.94	104	124	P	V
	*	2480	90.76	-	-	94.55	27.64	5.51	36.94	104	124	A	V
Remark	<p>3. No other spurious found.</p> <p>4. All results are PASS against Peak and Average limit line.</p>												



2.4GHz 2400~2483.5MHz
BLE (Harmonic @ 3m)

BLE	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		4806	42.16	-31.84	74	39.66	31.48	7.71	36.69	100	360	P	H
		4806	42.68	-31.32	74	40.18	31.48	7.71	36.69	100	360	P	V
BLE CH 19 2440MHz		4878	41.7	-32.3	74	39.01	31.59	7.76	36.66	100	360	P	H
		7320	45.57	-28.43	74	38.42	34.08	9.78	36.71	100	360	P	H
		4880	42.22	-31.78	74	39.53	31.59	7.76	36.66	100	360	P	V
		7320	45.26	-28.74	74	38.11	34.08	9.78	36.71	100	360	P	V
BLE CH 39 2480MHz		4962	41.87	-32.13	74	38.96	31.72	7.82	36.63	100	360	P	H
		7440	46.39	-27.61	74	38.85	34.44	9.87	36.77	100	360	P	H
		4962	42.32	-31.68	74	39.41	31.72	7.82	36.63	100	360	P	V
		7440	45.5	-28.5	74	37.96	34.44	9.87	36.77	100	360	P	V
Remark	3. No other spurious found. 4. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

2.4GHz BLE (LF)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz BLE LF		32.91	31.1	-8.9	40	35.55	26.18	0.69	31.32	100	287	P	H
		100.81	20.11	-23.39	43.5	31.45	18.88	1.22	31.44	-	-	P	H
		216.24	21.99	-24.01	46	35.51	16.23	1.73	31.48	-	-	P	H
		447.1	27.58	-18.42	46	30.83	25.36	2.63	31.24	-	-	P	H
		838.98	31.68	-14.32	46	30.15	28.76	3.69	30.92	-	-	P	H
		964.11	33.25	-20.75	54	30.44	29.5	4.01	30.7	-	-	P	H
		32.91	29.85	-10.15	40	34.3	26.18	0.69	31.32	128	87	P	V
		97.9	21.07	-22.43	43.5	32.57	18.74	1.2	31.44	-	-	P	V
		223.03	21.77	-24.23	46	35.11	16.4	1.73	31.47	-	-	P	V
		475.23	26.46	-19.54	46	30.61	24.38	2.72	31.25	-	-	P	V
		848.68	31.13	-14.87	46	29.34	28.98	3.71	30.9	-	-	P	V
		972.84	32.79	-21.21	54	29.94	29.5	4.04	30.69	-	-	P	V
Remark	3. No other spurious found. 4. All results are PASS against limit line.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	P eak or A verage
H/V	H orizontal or V ertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

- Level(dBμV/m) =
Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
- Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

- Level(dBμV/m)
= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)
= 55.45 (dBμV/m)
- Over Limit(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 55.45(dBμV/m) – 74(dBμV/m)
= -18.55(dB)

For Average Limit @ 2390MHz:

- Level(dBμV/m)
= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)
= 43.54 (dBμV/m)
- Over Limit(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 43.54(dBμV/m) – 54(dBμV/m)
= -10.46(dB)


Both peak and average measured complies with the limit line, so test result is “PASS”.



Appendix C. Duty Cycle Plots

Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
Bluetooth v4.0 LE	62.59	0.39	2.55	3kHz
Bluetooth v4.2 LE	46.88	0.29	3.40	10kHz


Bluetooth v4.0 LE



Date: 30.SEP.2016 13:43:26



Bluetooth v4.2 LE



Date: 30.SEP.2016 13:50:08