



FCC RF Test Report

APPLICANT : ZTE CORPORATION
EQUIPMENT : LTE/WCDMA/GSM (GPRS)
Multi-Mode Digital Mobile Phone
BRAND NAME : ZTE
MODEL NAME : Z965
FCC ID : SRQ-Z965
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System

The product was received on Jun. 27, 2017 and testing was completed on Aug. 24, 2017. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.



Approved by: James Huang / Manager

Sporton International (Kunshan) Inc.
No.3-2 Ping-Xiang Rd, Kunshan Development Zone Kunshan City Jiangsu Province 215335
China



TABLE OF CONTENTS

REVISION HISTORY..... 3

SUMMARY OF TEST RESULT 4

1 GENERAL DESCRIPTION 5

 1.1 Applicant 5

 1.2 Manufacturer 5

 1.3 Product Feature of Equipment Under Test..... 5

 1.4 Product Specification of Equipment Under Test..... 6

 1.5 Modification of EUT 6

 1.6 Testing Location 7

 1.7 Applicable Standards..... 7

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST 8

 2.1 Carrier Frequency and Channel 8

 2.2 Test Mode..... 9

 2.3 Connection Diagram of Test System..... 10

 2.4 Support Unit used in test configuration and system 11

 2.5 EUT Operation Test Setup 11

 2.6 Measurement Results Explanation Example..... 11

3 TEST RESULT 12

 3.1 6dB Bandwidth Measurement 12

 3.2 Output Power Measurement..... 14

 3.3 Power Spectral Density Measurement 15

 3.4 Conducted Band Edges and Spurious Emission Measurement 17

 3.5 Radiated Band Edges and Spurious Emission Measurement 30

 3.6 AC Conducted Emission Measurement..... 34

 3.7 Antenna Requirements..... 39

4 LIST OF MEASURING EQUIPMENT 40

5 UNCERTAINTY OF EVALUATION 41

APPENDIX A. CONDUCTED TEST RESULTS

APPENDIX B. RADIATED SPURIOUS EMISSION

APPENDIX C. DUTY CYCLE PLOTS

APPENDIX D. SETUP PHOTOGRAPHS



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.2	15.247(b)	Power Output Measurement	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
		Conducted Spurious Emission		Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 1.31 dB at 4824.000 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 9.72 dB at 0.175 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-



1 General Description

1.1 Applicant

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

1.2 Manufacturer

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	LTE/WCDMA/GSM (GPRS) Multi-Mode Digital Mobile Phone
Brand Name	ZTE
Model Name	Z965
FCC ID	SRQ-Z965
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/ HSPA+ (16QAM uplink is not supported)/LTE WLAN 11b/g/n HT20/HT40 Bluetooth v3.0 + EDR/Bluetooth v4.0 LE/ Bluetooth v4.1 LE/Bluetooth v4.2 LE
IMEI Code	Conducted: 864892030004589 Radiation: 864892030010693 Conduction: 864892030006725
HW Version	Z965HW1.0
SW Version	Z965V1.1.11
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Channel Frequency Range	2412 MHz ~ 2462 MHz
Maximum (Peak) Output Power to antenna	802.11b : 17.24 dBm (0.0530 W) 802.11g : 21.81 dBm (0.1517 W) 802.11n HT20 : 20.82 dBm (0.1208 W) 802.11n HT40 : 21.15 dBm (0.1303 W)
Antenna Type / Gain	PIFA Antenna with gain -6.0 dBi
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)

1.5 Modification of EUT

No modifications are made to the EUT during all test items.



1.6 Testing Location

Sporton Lab is accredited to ISO 17025 by National Voluntary Laboratory Accreditation Program (NVLAP code: 600155-0) and the FCC designation No is CN5013.

Test Site	Sporton International (Kunshan) Inc.			
Test Site Location	No.3-2 Ping-Xiang Rd, Kunshan Development Zone Kunshan City Jiangsu Province 215335 China TEL : +86-512-57900158 FAX : +86-512-57900958			
Test Site No.	Sporton Site No.			FCC Test Firm Registration No.
	TH01-KS	03CH03-KS	CO01-KS	630927

Note: The test site complies with ANSI C63.4 2014 requirement.

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.247
- FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04
- ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz) and radiated emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases were recorded in this report.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437	-	-



2.2 Test Mode


Final test mode of conducted test items and radiated spurious emissions are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0


Test Cases	
AC Conducted Emission	Mode 1: GSM850 Idle + Bluetooth Link + WLAN Link(2.4GHz) + Earphone + Battery + USB Cable (Charging from Adapter1) Mode 2: GSM850 Idle + Bluetooth Link + WLAN Link(2.4GHz) + Earphone + Battery + USB Cable (Charging from Adapter2)
Remark: 1. The worst case of conducted emission is mode 2; only the test data of it was reported. 2. For Radiated TCs, the tests were performed with Adapter 1, Earphone, Battery and USB Cable.	

2.3 Connection Diagram of Test System

<WLAN Tx Mode>



<AC Conducted Emission Mode>



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	WLAN AP	D-Link	DIR-855	KA2DIR855A2	N/A	Unshielded, 1.8 m
3.	Notebook	Lenovo	G480	N/A	N/A	shielded cable DC O/P 1.8m , Unshielded AC I/P cable 1.8m
4.	Bluetooth Earphone	Lenovo	LBH308	NA	N/A	N/A
5.	Earphone	Lenovo	SH100	N/A	Unshielded,1.2m	N/A

2.5 EUT Operation Test Setup

For WLAN function, the engineering test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss.

Following shows an offset computation example with cable loss 5.5 dB.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)}. \\ &= 5.5 \text{ (dB)} \end{aligned}$$

3 Test Result

3.1 6dB Bandwidth Measurement

3.1.1 Limit of 6dB Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v04.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. Measure and record the results in the test report.


3.1.4 Test Setup





3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.



3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi are used the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v04 section 9.1.2 PKPM1 Peak power meter method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.2.6 Test Result of Average output Power (Reporting Only)

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.


3.3.4 Test Setup





3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement.


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


3.4.4 Test Setup





3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Test Mode :	802.11b	Temperature :	21~25°C
Test Band :	2.4GHz Low	Relative Humidity :	51~55%
Test Channel :	01	Test Engineer :	Silent Hai







Test Mode :	802.11b	Temperature :	21~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	51~55%
Test Channel :	06	Test Engineer :	Silent Hai

WLAN 802.11b Channel 06


100kHz PSD reference Level



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz







Test Mode :	802.11b	Temperature :	21~25°C
Test Band :	2.4GHz High	Relative Humidity :	51~55%
Test Channel :	11	Test Engineer :	Silent Hai

WLAN 802.11b Channel 11


100kHz PSD reference Level




High Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz







Test Mode :	802.11g	Temperature :	21~25°C
Test Band :	2.4GHz Low	Relative Humidity :	51~55%
Test Channel :	01	Test Engineer :	Silent Hai

WLAN 802.11g Channel 01


100kHz PSD reference Level




Low Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz







Test Mode :	802.11g	Temperature :	21~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	51~55%
Test Channel :	06	Test Engineer :	Silent Hai

WLAN 802.11g Channel 06


100kHz PSD reference Level



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz







Test Mode :	802.11g	Temperature :	21~25°C
Test Band :	2.4GHz High	Relative Humidity :	51~55%
Test Channel :	11	Test Engineer :	Silent Hai

WLAN 802.11g Channel 11


100kHz PSD reference Level




High Channel Plot



Spurious Emission 30MHz~3GHz




Spurious Emission 2GHz~25GHz





Test Mode :	802.11n HT20	Temperature :	21~25°C
Test Band :	2.4GHz Low	Relative Humidity :	51~55%
Test Channel :	01	Test Engineer :	Silent Hai







Test Mode :	802.11n HT20	Temperature :	21~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	51~55%
Test Channel :	06	Test Engineer :	Silent Hai

WLAN 802.11n HT20 Channel 06


100kHz PSD reference Level



Spurious Emission 30MHz~3GHz




Spurious Emission 2GHz~25GHz






Test Mode :	802.11n HT20	Temperature :	21~25°C
Test Band :	2.4GHz High	Relative Humidity :	51~55%
Test Channel :	11	Test Engineer :	Silent Hai





Test Mode :	802.11n HT40	Temperature :	21~25°C
Test Band :	2.4GHz Low	Relative Humidity :	51~55%
Test Channel :	03	Test Engineer :	Silent Hai







Test Mode :	802.11n HT40	Temperature :	21~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	51~55%
Test Channel :	06	Test Engineer :	Silent Hai

WLAN 802.11n HT40 Channel 06


100kHz PSD reference Level



Spurious Emission 30MHz~3GHz




Spurious Emission 2GHz~25GHz





Test Mode :	802.11n HT40	Temperature :	21~25°C
Test Band :	2.4GHz High	Relative Humidity :	51~55%
Test Channel :	09	Test Engineer :	Silent Hai





3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.



3.5.3 Test Procedures


1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.

For average measurement:


 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B.

3.5.7 Duty Cycle

Please refer to Appendix C.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B.



3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dBµV)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.


3.6.4 Test Setup





3.6.5 Test Result of AC Conducted Emission

Test Mode :	Mode 2	Temperature :	22~24°C
Test Engineer :	Amos Zhang	Relative Humidity :	42~46%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link(2.4GHz) + Earphone + Battery + USB Cable (Charging from Adapter2)		




Site : CO01-KS
 Condition : FCC PART 15C LISN-L-161017-060103 LINE

mode : Mode 2
 : 864892030006725 #6

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.166	47.13	-18.03	65.16	36.31	0.45	10.37	QP
2	0.166	33.43	-21.73	55.16	22.61	0.45	10.37	Average
3	0.589	35.64	-20.36	56.00	25.20	0.26	10.18	QP
4	0.589	25.94	-20.06	46.00	15.50	0.26	10.18	Average
5	0.644	36.64	-19.36	56.00	26.20	0.26	10.18	QP
6	0.644	28.64	-17.36	46.00	18.20	0.26	10.18	Average
7	1.689	39.21	-16.79	56.00	28.80	0.22	10.19	QP
8	1.689	31.61	-14.39	46.00	21.20	0.22	10.19	Average
9	2.044	41.00	-15.00	56.00	30.60	0.21	10.19	QP
10	2.044	31.70	-14.30	46.00	21.30	0.21	10.19	Average
11	2.346	40.61	-15.39	56.00	30.20	0.21	10.20	QP
12 *	2.346	31.71	-14.29	46.00	21.30	0.21	10.20	Average
13	2.581	39.02	-16.98	56.00	28.60	0.21	10.21	QP
14	2.581	30.62	-15.38	46.00	20.20	0.21	10.21	Average




Test Mode :	Mode 2	Temperature :	22~24°C
Test Engineer :	Amos Zhang	Relative Humidity :	42~46%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link(2.4GHz) + Earphone + Battery + USB Cable (Charging from Adapter2)		



Site : CO01-KS
 Condition : FCC PART 15C LISN-N-161017-060103 NEUTRAL

mode : Mode 2
 : 864892030006725 #6

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.163	54.21	-11.09	65.30	43.49	0.34	10.38	QP
2	0.163	40.31	-14.99	55.30	29.59	0.34	10.38	Average
3 *	0.175	55.00	-9.72	64.72	44.31	0.33	10.36	QP
4	0.175	42.00	-12.72	54.72	31.31	0.33	10.36	Average
5	0.184	50.28	-14.00	64.28	39.60	0.33	10.35	QP
6	0.184	37.88	-16.40	54.28	27.20	0.33	10.35	Average
7	0.211	45.26	-17.92	63.18	34.61	0.33	10.32	QP
8	0.211	30.96	-22.22	53.18	20.31	0.33	10.32	Average
9	0.226	46.45	-16.16	62.61	35.80	0.34	10.31	QP
10	0.226	33.95	-18.66	52.61	23.30	0.34	10.31	Average
11	0.238	43.24	-18.93	62.17	32.60	0.34	10.30	QP
12	0.238	30.94	-21.23	52.17	20.30	0.34	10.30	Average
13	0.249	43.23	-18.55	61.78	32.60	0.34	10.29	QP
14	0.249	30.93	-20.85	51.78	20.30	0.34	10.29	Average
15	0.289	40.91	-19.63	60.54	30.30	0.35	10.26	QP
16	0.289	29.91	-20.63	50.54	19.30	0.35	10.26	Average
17	0.339	40.19	-19.03	59.22	29.60	0.36	10.23	QP



Site : CO01-KS
 Condition : FCC PART 15C LISN-N-161017-060103 NEUTRAL
 mode : Mode 2
 : 864892030006725 #6

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
18	0.339	32.89	-16.33	49.22	22.30	0.36	10.23	Average
19	0.471	39.07	-17.42	56.49	28.50	0.38	10.19	QP
20	0.471	30.87	-15.62	46.49	20.30	0.38	10.19	Average
21	0.552	41.16	-14.84	56.00	30.60	0.38	10.18	QP
22	0.552	34.76	-11.24	46.00	24.20	0.38	10.18	Average
23	0.665	40.86	-15.14	56.00	30.30	0.38	10.18	QP
24	0.665	34.16	-11.84	46.00	23.60	0.38	10.18	Average
25	1.810	43.10	-12.90	56.00	32.50	0.41	10.19	QP
26	1.810	34.20	-11.80	46.00	23.60	0.41	10.19	Average
27	1.939	43.40	-12.60	56.00	32.80	0.41	10.19	QP
28	1.939	34.90	-11.10	46.00	24.30	0.41	10.19	Average
29	2.201	42.80	-13.20	56.00	32.20	0.41	10.19	QP
30	2.201	33.80	-12.20	46.00	23.20	0.41	10.19	Average
31	2.346	42.20	-13.80	56.00	31.60	0.40	10.20	QP
32	2.346	33.80	-12.20	46.00	23.20	0.40	10.20	Average
33	2.594	41.81	-14.19	56.00	31.20	0.40	10.21	QP
34	2.594	31.81	-14.19	46.00	21.20	0.40	10.21	Average
35	2.736	40.91	-15.09	56.00	30.30	0.40	10.21	QP
36	2.736	31.91	-14.09	46.00	21.30	0.40	10.21	Average



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Aug. 08, 2017	Aug. 09, 2017	Aug. 07, 2018	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 19, 2017	Aug. 09, 2017	Jan. 18, 2018	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 19, 2017	Aug. 09, 2017	Jan. 18, 2018	Conducted (TH01-KS)
EMI Test Receiver	Keysight	N9038A	MY56400004	3Hz~8.5GHz; Max 30dBm	Oct. 22, 2016	Aug. 10, 2017	Oct. 21, 2017	Radiation (03CH03-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150244	10Hz~44GHz	Apr. 18, 2017	Aug. 10, 2017	Apr. 17, 2018	Radiation (03CH03-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Nov. 23, 2016	Aug. 10, 2017	Nov. 22, 2017	Radiation (03CH03-KS)
Bilog Antenna	TeseQ	CBL6112D	35406	25MHz~2GHz	Apr. 22, 2017	Aug. 10, 2017	Apr. 21, 2018	Radiation (03CH03-KS)
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1356	1GHz~18GHz	Apr. 22, 2017	Aug. 10, 2017	Apr. 21, 2018	Radiation (03CH03-KS)
SHF-EHF Horn	com-power	AH-840	101070	18GHz ~40GHz	Oct. 19, 2016	Aug. 10, 2017	Oct. 18, 2017	Radiation (03CH03-KS)
Amplifier	com-power	PA-103A	161069	1MHz ~1000MHz / 32 dB	Apr. 18, 2017	Aug. 10, 2017	Apr. 17, 2018	Radiation (03CH03-KS)
Amplifier	MITEQ	TTA1840-35-HG	1887435	18~40GHz	Oct. 13, 2016	Aug. 10, 2017	Oct. 12, 2017	Radiation (03CH03-KS)
high gain Amplifier	MITEQ	AMF-7D-0010 1800-30-10P	2025788	1Ghz-18Ghz	Apr. 18, 2017	Aug. 10, 2017	Apr. 17, 2018	Radiation (03CH03-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Aug. 10, 2017	NCR	Radiation (03CH03-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Aug. 10, 2017	NCR	Radiation (03CH03-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Aug. 10, 2017	NCR	Radiation (03CH03-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	Apr. 20, 2017	Aug. 24, 2017	Apr. 19, 2018	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Oct. 13, 2016	Aug. 24, 2017	Oct. 12, 2017	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Oct. 13, 2016	Aug. 24, 2017	Oct. 12, 2017	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP000000811	AC 0V~300V, 45Hz~1000Hz	Oct. 13, 2016	Aug. 24, 2017	Oct. 12, 2017	Conduction (CO01-KS)

NCR: No Calibration Required



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.3dB
---	-------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.6dB
---	-------

Uncertainty of Radiated Emission Measurement (1GHz ~ 18GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.5dB
---	-------

Uncertainty of Radiated Emission Measurement (18GHz ~ 40GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.7dB
---	-------



Appendix A. Conducted Test Results

A1 - DTS Part

Test Engineer:	Silent Hai	Temperature:	21~25	°C
Test Date:	2017/8/9	Relative Humidity:	51~55	%

TEST RESULTS DATA
6dB Bandwidth

2.4GHz Band							
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
11b	1Mbps	1	1	2412	10.03	0.50	Pass
11b	1Mbps	1	6	2437	10.03	0.50	Pass
11b	1Mbps	1	11	2462	9.55	0.50	Pass
11g	6Mbps	1	1	2412	16.34	0.50	Pass
11g	6Mbps	1	6	2437	16.34	0.50	Pass
11g	6Mbps	1	11	2462	16.34	0.50	Pass
HT20	MCS0	1	1	2412	17.56	0.50	Pass
HT20	MCS0	1	6	2437	17.58	0.50	Pass
HT20	MCS0	1	11	2462	17.56	0.50	Pass
HT40	MCS0	1	3	2422	35.45	0.50	Pass
HT40	MCS0	1	6	2437	35.33	0.50	Pass
HT40	MCS0	1	9	2452	35.13	0.50	Pass

TEST RESULTS DATA
Peak Power Table

2.4GHz Band										
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
11b	1Mbps	1	1	2412	16.41	30.00	-6.00	10.41	36.00	Pass
11b	1Mbps	1	6	2437	17.24	30.00	-6.00	11.24	36.00	Pass
11b	1Mbps	1	11	2462	16.68	30.00	-6.00	10.68	36.00	Pass
11g	6Mbps	1	1	2412	21.81	30.00	-6.00	15.81	36.00	Pass
11g	6Mbps	1	6	2437	21.57	30.00	-6.00	15.57	36.00	Pass
11g	6Mbps	1	11	2462	21.02	30.00	-6.00	15.02	36.00	Pass
HT20	MCS0	1	1	2412	20.82	30.00	-6.00	14.82	36.00	Pass
HT20	MCS0	1	6	2437	20.69	30.00	-6.00	14.69	36.00	Pass
HT20	MCS0	1	11	2462	19.99	30.00	-6.00	13.99	36.00	Pass
HT40	MCS0	1	3	2422	21.15	30.00	-6.00	15.15	36.00	Pass
HT40	MCS0	1	6	2437	20.89	30.00	-6.00	14.89	36.00	Pass
HT40	MCS0	1	9	2452	20.46	30.00	-6.00	14.46	36.00	Pass

TEST RESULTS DATA
Average Power Table
(Reporting Only)

2.4GHz Band						
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
11b	1Mbps	1	1	2412	0.11	13.80
11b	1Mbps	1	6	2437	0.11	14.42
11b	1Mbps	1	11	2462	0.11	13.90
11g	6Mbps	1	1	2412	0.58	12.93
11g	6Mbps	1	6	2437	0.58	12.34
11g	6Mbps	1	11	2462	0.58	11.61
HT20	MCS0	1	1	2412	0.62	11.08
HT20	MCS0	1	6	2437	0.62	10.55
HT20	MCS0	1	11	2462	0.62	9.85
HT40	MCS0	1	3	2422	0.64	11.00
HT40	MCS0	1	6	2437	0.64	10.75
HT40	MCS0	1	9	2452	0.64	10.37

TEST RESULTS DATA
Peak Power Density

2.4GHz Band								
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
11b	1Mbps	1	1	2412	-9.40	-6.00	8.00	Pass
11b	1Mbps	1	6	2437	-7.90	-6.00	8.00	Pass
11b	1Mbps	1	11	2462	-8.76	-6.00	8.00	Pass
11g	6Mbps	1	1	2412	-12.63	-6.00	8.00	Pass
11g	6Mbps	1	6	2437	-13.09	-6.00	8.00	Pass
11g	6Mbps	1	11	2462	-11.77	-6.00	8.00	Pass
HT20	MCS0	1	1	2412	-14.75	-6.00	8.00	Pass
HT20	MCS0	1	6	2437	-15.00	-6.00	8.00	Pass
HT20	MCS0	1	11	2462	-15.76	-6.00	8.00	Pass
HT40	MCS0	1	3	2422	-17.58	-6.00	8.00	Pass
HT40	MCS0	1	6	2437	-17.58	-6.00	8.00	Pass
HT40	MCS0	1	9	2452	-17.34	-6.00	8.00	Pass



Appendix B. Radiated Spurious Emission

2.4GHz 2400~2483.5MHz

WIFI 802.11b (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		2389.69	43.16	-30.84	74	45.3	25.4	4.76	32.3	114	43	P	H
		2389.56	34.28	-19.72	54	36.42	25.4	4.76	32.3	114	43	A	H
	*	2412	98.88	-	-	100.87	25.54	4.78	32.31	114	43	P	H
	*	2414	95.26	-	-	97.25	25.54	4.78	32.31	114	43	A	H
		2389.69	44.14	-29.86	74	46.28	25.4	4.76	32.3	139	76	P	V
		2389.56	35.6	-18.4	54	37.74	25.4	4.76	32.3	139	76	A	V
	*	2412	100.24	-	-	102.23	25.54	4.78	32.31	139	76	P	V
	*	2412	96.98	-	-	98.97	25.54	4.78	32.31	139	76	A	V
802.11b CH 06 2437MHz		2386.83	40.85	-33.15	74	42.99	25.4	4.76	32.3	140	148	P	H
		2381.76	30.85	-23.15	54	33.03	25.35	4.75	32.28	140	148	A	H
	*	2436	99.59	-	-	101.43	25.69	4.8	32.33	140	148	P	H
	*	2436	96.36	-	-	98.2	25.69	4.8	32.33	140	148	A	H
		2497.84	41.56	-32.44	74	42.81	26.26	4.88	32.39	140	148	P	H
		2483.5	30.57	-23.43	54	31.97	26.11	4.86	32.37	140	148	A	H
		2382.67	41.86	-32.14	74	44.04	25.35	4.75	32.28	277	239	P	V
		2381.5	31.98	-22.02	54	34.16	25.35	4.75	32.28	277	239	A	V
	*	2436	102.07	-	-	103.91	25.69	4.8	32.33	277	239	P	V
	*	2436	98.88	-	-	100.72	25.69	4.8	32.33	277	239	A	V
		2484.4	40.94	-33.06	74	42.34	26.11	4.86	32.37	277	239	P	V
	2483.5	30.98	-23.02	54	32.38	26.11	4.86	32.37	277	239	A	V	



802.11b CH 11 2462MHz	*	2462	100.52	-	-	102.07	25.97	4.84	32.36	351	132	P	H
	*	2462	97.22	-	-	98.77	25.97	4.84	32.36	351	132	A	H
		2483.86	44.83	-29.17	74	46.23	26.11	4.86	32.37	351	132	P	H
		2483.5	33.07	-20.93	54	34.47	26.11	4.86	32.37	351	132	A	H
	*	2462	100.73	-	-	102.28	25.97	4.84	32.36	266	237	P	V
	*	2460	97.47	-	-	99.02	25.97	4.84	32.36	266	237	A	V
		2483.56	43.4	-30.6	74	44.8	26.11	4.86	32.37	266	237	P	V
		2483.56	33.33	-20.67	54	34.73	26.11	4.86	32.37	266	237	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**2.4GHz 2400~2483.5MHz
WIFI 802.11b (Harmonic @ 3m)**

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11b CH 01 2412MHz		4824	52.79	-21.21	74	72.01	30.9	6.87	56.99	102	12	P	H
		4824	49.73	-4.27	54	68.95	30.9	6.87	56.99	102	12	A	H
		4824	54.91	-19.09	74	74.13	30.9	6.87	56.99	350	68	P	V
		4824	52.69	-1.31	54	71.91	30.9	6.87	56.99	350	68	A	V
802.11b CH 06 2437MHz		4872	54.41	-19.59	74	73.47	31.01	6.86	56.93	100	0	P	H
		4872	51.15	-2.85	54	70.21	31.01	6.86	56.93	120	314	A	H
		7311	42.88	-31.12	74	64.18	35.34	8.47	65.11	100	0	P	H
		4872	55.57	-18.43	74	74.63	31.01	6.86	56.93	300	0	P	V
		4872	52.17	-1.83	54	71.23	31.01	6.86	56.93	300	124	A	V
		7311	38.82	-35.18	74	60.12	35.34	8.47	65.11	300	0	P	V
802.11b CH 11 2462MHz		4926	49.79	-24.21	74	68.7	31.12	6.84	56.87	300	0	P	H
		7386	40.16	-33.84	74	61.08	35.55	8.49	64.96	300	0	P	H
		4926	50.22	-23.78	74	69.13	31.12	6.84	56.87	300	360	P	V
		7386	39.16	-34.84	74	60.08	35.55	8.49	64.96	300	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
WIFI 802.11g (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11g CH 01 2412MHz		2389.69	62.48	-11.52	74	64.62	25.4	4.76	32.3	100	160	P	H
		2389.82	46.28	-7.72	54	48.42	25.4	4.76	32.3	100	160	A	H
	*	2416	99.17	-	-	101.16	25.54	4.78	32.31	100	160	P	H
	*	2418	89.87	-	-	91.86	25.54	4.78	32.31	100	160	A	H
		2389.82	60.39	-13.61	74	62.53	25.4	4.76	32.3	271	70	P	V
		2389.95	44.67	-9.33	54	46.81	25.4	4.76	32.3	271	70	A	V
	*	2420	97.15	-	-	98.99	25.69	4.8	32.33	271	70	P	V
	*	2418	89.24	-	-	91.23	25.54	4.78	32.31	271	70	A	V
802.11g CH 06 2437MHz		2385.92	43.04	-30.96	74	45.18	25.4	4.76	32.3	342	28	P	H
		2384.75	33.88	-20.12	54	36.06	25.35	4.75	32.28	342	28	A	H
	*	2432	98.32	-	-	100.16	25.69	4.8	32.33	342	28	P	H
	*	2430	90.54	-	-	92.38	25.69	4.8	32.33	342	28	A	H
		2484.52	41.86	-32.14	74	43.26	26.11	4.86	32.37	342	28	P	H
		2489.08	32.25	-21.75	54	33.5	26.26	4.88	32.39	342	28	A	H
		2384.75	43.44	-30.56	74	45.62	25.35	4.75	32.28	332	106	P	V
		2384.49	33.26	-20.74	54	35.44	25.35	4.75	32.28	332	106	A	V
	*	2432	97.63	-	-	99.47	25.69	4.8	32.33	332	106	P	V
	*	2432	89.25	-	-	91.09	25.69	4.8	32.33	332	106	A	V
		2483.62	41.93	-32.07	74	43.33	26.11	4.86	32.37	332	106	P	V
		2489.14	32.19	-21.81	54	33.44	26.26	4.88	32.39	332	106	A	V



802.11g CH 11 2462MHz	*	2460	98.46	-	-	100.01	25.97	4.84	32.36	110	27	P	H
	*	2456	89.74	-	-	91.29	25.97	4.84	32.36	110	27	A	H
		2483.98	55.98	-18.02	74	57.38	26.11	4.86	32.37	110	27	P	H
		2483.74	36.52	-17.48	54	37.92	26.11	4.86	32.37	110	27	A	H
	*	2458	96.7	-	-	98.25	25.97	4.84	32.36	263	77	P	V
	*	2468	87.77	-	-	89.32	25.97	4.84	32.36	263	77	A	V
		2484.82	52.4	-21.6	74	53.8	26.11	4.86	32.37	263	77	P	V
		2483.62	35.86	-18.14	54	37.26	26.11	4.86	32.37	263	77	A	V
Remark	<ol style="list-style-type: none"> No other spurious found. All results are PASS against Peak and Average limit line. 												



**2.4GHz 2400~2483.5MHz
WIFI 802.11g (Harmonic @ 3m)**

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11g CH 01 2412MHz		4824	45.03	-28.97	74	64.25	30.9	6.87	56.99	100	0	P	H
		4824	47.56	-26.44	74	66.78	30.9	6.87	56.99	100	360	P	V
802.11g CH 06 2437MHz		4872	45.71	-28.29	74	64.77	31.01	6.86	56.93	100	360	P	H
		7311	38.68	-35.32	74	59.98	35.34	8.47	65.11	100	360	P	H
		4872	45.15	-28.85	74	64.21	31.01	6.86	56.93	100	360	P	V
802.11g CH 11 2462MHz		7311	38.02	-35.98	74	59.32	35.34	8.47	65.11	100	360	P	V
		4926	42.61	-31.39	74	61.52	31.12	6.84	56.87	100	0	P	H
		7386	36.82	-37.18	74	57.74	35.55	8.49	64.96	100	0	P	H
		4926	41.27	-32.73	74	60.18	31.12	6.84	56.87	100	0	P	V
		7386	37.1	-36.9	74	58.02	35.55	8.49	64.96	100	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**2.4GHz 2400~2483.5MHz
WIFI 802.11n HT20 (Band Edge @ 3m)**

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 01 2412MHz		2389.56	60.21	-13.79	74	62.35	25.4	4.76	32.3	127	185	P	H
		2389.95	44.04	-9.96	54	46.18	25.4	4.76	32.3	127	185	A	H
	*	2416	97.25	-	-	99.24	25.54	4.78	32.31	127	185	P	H
	*	2418	88.72	-	-	90.71	25.54	4.78	32.31	127	185	A	H
		2389.82	60.71	-13.29	74	62.85	25.4	4.76	32.3	143	120	P	V
		2389.95	44.06	-9.94	54	46.2	25.4	4.76	32.3	143	120	A	V
	*	2412	97.72	-	-	99.71	25.54	4.78	32.31	143	120	P	V
	*	2416	88.76	-	-	90.75	25.54	4.78	32.31	143	120	A	V
802.11n HT20 CH 06 2437MHz		2385.14	43.97	-30.03	74	46.15	25.35	4.75	32.28	119	38	P	H
		2385.27	35.22	-18.78	54	37.4	25.35	4.75	32.28	119	38	A	H
	*	2432	97.1	-	-	98.94	25.69	4.8	32.33	119	38	P	H
	*	2432	89.14	-	-	90.98	25.69	4.8	32.33	119	38	A	H
		2488.78	42.99	-31.01	74	44.24	26.26	4.88	32.39	119	38	P	H
		2488.42	33.32	-20.68	54	34.57	26.26	4.88	32.39	119	38	A	H
		2385.14	43.92	-30.08	74	46.1	25.35	4.75	32.28	302	194	P	V
		2385.53	35.07	-18.93	54	37.21	25.4	4.76	32.3	302	194	A	V
	*	2434	96.63	-	-	98.47	25.69	4.8	32.33	302	194	P	V
	*	2432	88.42	-	-	90.26	25.69	4.8	32.33	302	194	A	V
		2488.6	42.36	-31.64	74	43.61	26.26	4.88	32.39	302	194	P	V
	2488.42	32.82	-21.18	54	34.07	26.26	4.88	32.39	302	194	A	V	



802.11n HT20 CH 11 2462MHz	*	2456	96.67	-	-	98.22	25.97	4.84	32.36	135	39	P	H
	*	2456	88.72	-	-	90.27	25.97	4.84	32.36	135	39	A	H
		2485.06	50.75	-23.25	74	52.15	26.11	4.86	32.37	135	39	P	H
		2483.5	34.94	-19.06	54	36.34	26.11	4.86	32.37	135	39	A	H
	*	2466	96.3	-	-	97.85	25.97	4.84	32.36	299	318	P	V
	*	2458	87.81	-	-	89.36	25.97	4.84	32.36	299	318	A	V
		2486.92	48.12	-25.88	74	49.52	26.11	4.86	32.37	299	318	P	V
	2483.68	34.45	-19.55	54	35.85	26.11	4.86	32.37	299	318	A	V	
Remark	<ol style="list-style-type: none"> No other spurious found. All results are PASS against Peak and Average limit line. 												



2.4GHz 2400~2483.5MHz
WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 01 2412MHz		4824	42.43	-31.57	74	61.65	30.9	6.87	56.99	100	360	P	H
		4824	44.14	-29.86	74	63.36	30.9	6.87	56.99	136	0	P	V
802.11n HT20 CH 06 2437MHz		4872	42.17	-31.83	74	61.23	31.01	6.86	56.93	100	0	P	H
		7311	37.14	-36.86	74	58.44	35.34	8.47	65.11	100	0	P	H
		4872	41.31	-32.69	74	60.37	31.01	6.86	56.93	100	313	P	V
		7311	36.41	-37.59	74	57.71	35.34	8.47	65.11	100	313	P	V
802.11n HT20 CH 11 2462MHz		4926	40.04	-33.96	74	58.95	31.12	6.84	56.87	100	345	P	H
		7386	37.19	-36.81	74	58.11	35.55	8.49	64.96	100	345	P	H
		4926	41.9	-32.1	74	60.81	31.12	6.84	56.87	100	0	P	V
		7386	36.67	-37.33	74	57.59	35.55	8.49	64.96	100	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**2.4GHz 2400~2483.5MHz
WIFI 802.11n HT40 (Band Edge @ 3m)**

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 03 2422MHz		2388.52	60.5	-13.5	74	62.64	25.4	4.76	32.3	107	144	P	H
		2389.82	48.39	-5.61	54	50.53	25.4	4.76	32.3	107	144	A	H
	*	2424	95	-	-	96.84	25.69	4.8	32.33	107	144	P	H
	*	2434	86.83	-	-	88.67	25.69	4.8	32.33	107	144	A	H
		2483.5	42.78	-31.22	74	44.18	26.11	4.86	32.37	107	144	P	H
		2483.5	32.1	-21.9	54	33.5	26.11	4.86	32.37	107	144	A	H
		2389.95	55.16	-18.84	74	57.3	25.4	4.76	32.3	338	86	P	V
		2389.95	43.85	-10.15	54	45.99	25.4	4.76	32.3	338	86	A	V
	*	2412	92.74	-	-	94.73	25.54	4.78	32.31	338	86	P	V
	*	2418	84.35	-	-	86.34	25.54	4.78	32.31	338	86	A	V
		2484.94	41.03	-32.97	74	42.43	26.11	4.86	32.37	338	86	P	V
		2483.62	30.87	-23.13	54	32.27	26.11	4.86	32.37	338	86	A	V
802.11n HT40 CH 06 2437MHz		2389.69	55.32	-18.68	74	57.46	25.4	4.76	32.3	117	165	P	H
		2389.95	39.52	-14.48	54	41.66	25.4	4.76	32.3	117	165	A	H
	*	2426	94.93	-	-	96.77	25.69	4.8	32.33	117	165	P	H
	*	2426	87.33	-	-	89.17	25.69	4.8	32.33	117	165	A	H
		2483.86	48.61	-25.39	74	50.01	26.11	4.86	32.37	117	165	P	H
		2483.56	34.04	-19.96	54	35.44	26.11	4.86	32.37	117	165	A	H
		2389.43	56.34	-17.66	74	58.48	25.4	4.76	32.3	264	97	P	V
		2389.95	39.74	-14.26	54	41.88	25.4	4.76	32.3	264	97	A	V
	*	2426	97.62	-	-	99.46	25.69	4.8	32.33	264	97	P	V
	*	2426	88.05	-	-	89.89	25.69	4.8	32.33	264	97	A	V
		2484.16	51.6	-22.4	74	53	26.11	4.86	32.37	264	97	P	V
		2483.56	34.69	-19.31	54	36.09	26.11	4.86	32.37	264	97	A	V



802.11n HT40 CH 09 2452MHz		2389.95	46.65	-27.35	74	48.79	25.4	4.76	32.3	101	162	P	H
		2388.39	32.92	-21.08	54	35.06	25.4	4.76	32.3	101	162	A	H
	*	2440	95.16	-	-	96.85	25.83	4.82	32.34	101	162	P	H
	*	2440	86.99	-	-	88.68	25.83	4.82	32.34	101	162	A	H
		2484.34	56.51	-17.49	74	57.91	26.11	4.86	32.37	101	162	P	H
		2483.86	39.57	-14.43	54	40.97	26.11	4.86	32.37	101	162	A	H
		2386.05	45.74	-28.26	74	47.88	25.4	4.76	32.3	278	107	P	V
		2389.69	32.52	-21.48	54	34.66	25.4	4.76	32.3	278	107	A	V
	*	2440	95.13	-	-	96.82	25.83	4.82	32.34	278	107	P	V
	*	2440	86.88	-	-	88.57	25.83	4.82	32.34	278	107	A	V
		2485.3	57.18	-16.82	74	58.58	26.11	4.86	32.37	278	107	P	V
		2484.34	39.27	-14.73	54	40.67	26.11	4.86	32.37	278	107	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**2.4GHz 2400~2483.5MHz
WIFI 802.11n HT40 (Harmonic @ 3m)**

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n		4842	44.12	-29.88	74	63.29	30.93	6.87	56.97	100	360	P	H
HT40		7266	36.47	-37.53	74	57.92	35.26	8.46	65.17	100	360	P	H
CH 03		4842	43.55	-30.45	74	62.72	30.93	6.87	56.97	300	0	P	V
2422MHz		7266	37.13	-36.87	74	58.58	35.26	8.46	65.17	300	0	P	V
802.11n		4872	43.19	-30.81	74	62.25	31.01	6.86	56.93	100	360	P	H
HT40		7311	36.45	-37.55	74	57.75	35.34	8.47	65.11	100	360	P	H
CH 06		4872	41.77	-32.23	74	60.83	31.01	6.86	56.93	100	0	P	V
2437MHz		7311	37.57	-36.43	74	58.87	35.34	8.47	65.11	100	0	P	V
802.11n		4902	40.56	-33.44	74	59.52	31.08	6.85	56.89	100	360	P	H
HT40		7356	37.43	-36.57	74	58.49	35.47	8.49	65.02	100	360	P	H
CH 09		4902	40.02	-33.98	74	58.98	31.08	6.85	56.89	100	360	P	V
2452MHz		7356	37.21	-36.79	74	58.27	35.47	8.49	65.02	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

Emission below 1GHz

2.4GHz WIFI 802.11b (LF)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz 802.11b LF		30.97	24.54	-15.46	40	29.8	25.74	0.08	31.08			P	H
		74.62	17.76	-22.24	40	33.76	14.6	0.8	31.4			P	H
		148.34	28.26	-15.24	43.5	40.84	17.32	0.99	30.89	200	360	P	H
		170.65	22.96	-20.54	43.5	35.91	16.64	1.39	30.98			P	H
		223.03	26.9	-19.1	46	39.68	16.72	1.65	31.15			P	H
		233.7	25.32	-20.68	46	37.6	17.18	1.71	31.17			P	H
		36.79	33.56	-6.44	40	42.38	22.14	0.12	31.08	100	360	P	V
		79.47	19.55	-20.45	40	34.84	15.27	0.84	31.4			P	V
		102.75	19.99	-23.51	43.5	32.5	17.77	0.43	30.71			P	V
		116.33	19.16	-24.34	43.5	31.67	17.64	0.62	30.77			P	V
		148.34	23.46	-20.04	43.5	36.04	17.32	0.99	30.89			P	V
		232.73	23.4	-22.6	46	35.73	17.14	1.7	31.17			P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

- Level(dBμV/m) =
Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
- Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

- Level(dBμV/m)
= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)
= 55.45 (dBμV/m)
- Over Limit(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 55.45(dBμV/m) – 74(dBμV/m)
= -18.55(dB)

For Average Limit @ 2390MHz:

- Level(dBμV/m)
= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)
= 43.54 (dBμV/m)
- Over Limit(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 43.54(dBμV/m) – 54(dBμV/m)
= -10.46(dB)


Both peak and average measured complies with the limit line, so test result is “PASS”.



Appendix C. Duty Cycle Plots


Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
802.11b	97.59	8.232	0.121	300Hz
802.11g	87.50	1.370	0.730	1KHz
802.11n HT20	86.70	1.275	0.784	1KHz
802.11n HT40	86.29	1.232	0.812	1KHz

802.11b






802.11g



802.11n HT20





802.11n HT40

